

# GRADIENTWIND

ENGINEERS & SCIENTISTS

February 9, 2024

**All Saints Development LP**

150 Elgin Street, Suite 1000  
Ottawa, ON K2P 1L4

Attn: Ross Farris, Senior Development Manager  
[ross.farris@windmilldevelopments.com](mailto:ross.farris@windmilldevelopments.com)

Dear Mr. Farris:

Re: Roadway Traffic Noise Addendum Letter  
315 & 321 Chapel Street, Ottawa  
GW File No.: 23-051 – Noise Addendum Letter

---

Gradient Wind Engineering Inc. (Gradient Wind) was retained by All Saints Development Limited to undertake a traffic noise assessment for a proposed mixed-use residential development located at 315 & 321 Chapel Street in Ottawa, Ontario. This addendum letter is supplemental to our traffic noise report (ref. *Gradient Wind report #23-051 – Traffic Noise*, dated August 9, 2023), to address changes in the latest site plan drawings.

Gradient Wind received updated site plan drawings in February 2024. Overall, the revised building retains a similar design to the tested configuration, which is a nine-storey nominally rectangular building affixed to the east of the existing church by a polygonal apse. Changes to the site plan include general reconfigurations of the balconies, an addition of a canopy at Level 2, and a reduction in the MPH Amenity Terrace area.

Further analysis was undertaken to examine the noise levels at the Level 4 south-facing terrace. Results indicate the noise levels are 48 dBA during the daytime period, which is well below the ENCG criterion of 55 dBA. As such, mitigation in this area is not required. The STAMSON 5.04 calculation can be seen at the end of this letter.

The minimal changes to the buildings' massing will not alter the noise impacts onto the development from nearby traffic noise sources. Therefore, the initial results, recommendations, and conclusions of our traffic noise report remain unchanged.

# GRADIENTWIND

ENGINEERS & SCIENTISTS


This concludes our response and review of the design changes for 315 & 321 Chapel Street in Ottawa, Ontario. Please advise the undersigned of any questions or concerns.

Sincerely,

**Gradient Wind Engineering Inc.**



Essraa Alqassab, B.A.Sc.  
Junior Environmental Scientist  
*Gradient Wind File #23-051 – Noise Addendum Letter*



Joshua Foster, P.Eng.  
Lead Engineer

# GRADIENTWIND

ENGINEERS & SCIENTISTS



## NOISE AT THE LEVEL 4 TERRACE – STAMSON CALCULATION

# GRADIENTWIND

ENGINEERS & SCIENTISTS

STAMSON 5.0                      NORMAL REPORT                      Date: 08-02-2024 11:30:32  
MINISTRY OF ENVIRONMENT AND ENERGY / NOISE ASSESSMENT

Filename: 14.te    Time Period: Day/Night 16/8 hours  
Description:

Road data, segment # 1: Chapel St (day/night)

-----  
Car traffic volume : 6477/563    veh/TimePeriod \*  
Medium truck volume : 515/45    veh/TimePeriod \*  
Heavy truck volume : 368/32    veh/TimePeriod \*  
Posted speed limit : 40 km/h  
Road gradient : 0 %  
Road pavement : 1 (Typical asphalt or concrete)

\* Refers to calculated road volumes based on the following input:

24 hr Traffic Volume (AADT or SADT): 8000  
Percentage of Annual Growth : 0.00  
Number of Years of Growth : 0.00  
Medium Truck % of Total Volume : 7.00  
Heavy Truck % of Total Volume : 5.00  
Day (16 hrs) % of Total Volume : 92.00

Data for Segment # 1: Chapel St (day/night)

-----  
Angle1    Angle2                      : -90.00 deg    90.00 deg  
Wood depth : 0                      (No woods.)  
No of house rows : 0 / 0  
Surface : 2                      (Reflective ground surface)  
Receiver source distance : 48.00 / 48.00 m  
Receiver height : 14.70 / 14.70 m  
Topography : 2                      (Flat/gentle slope; with barrier)  
Barrier angle1 : -90.00 deg    Angle2 : 90.00 deg  
Barrier height : 10.00 m  
Barrier receiver distance : 32.00 / 32.00 m  
Source elevation : 0.00 m  
Receiver elevation : 0.00 m  
Barrier elevation : 0.00 m  
Reference angle : 0.00



# GRADIENTWIND

ENGINEERS & SCIENTISTS

Road data, segment # 2: Laurier Ave (day/night)

-----  
Car traffic volume : 9715/845 veh/TimePeriod \*  
Medium truck volume : 773/67 veh/TimePeriod \*  
Heavy truck volume : 552/48 veh/TimePeriod \*  
Posted speed limit : 50 km/h  
Road gradient : 0 %  
Road pavement : 1 (Typical asphalt or concrete)

\* Refers to calculated road volumes based on the following input:

24 hr Traffic Volume (AADT or SADT): 12000  
Percentage of Annual Growth : 0.00  
Number of Years of Growth : 0.00  
Medium Truck % of Total Volume : 7.00  
Heavy Truck % of Total Volume : 5.00  
Day (16 hrs) % of Total Volume : 92.00

Data for Segment # 2: Laurier Ave (day/night)

-----  
Angle1 Angle2 : -90.00 deg 0.00 deg  
Wood depth : 0 (No woods.)  
No of house rows : 0 / 0  
Surface : 2 (Reflective ground surface)  
Receiver source distance : 62.00 / 62.00 m  
Receiver height : 14.70 / 14.70 m  
Topography : 2 (Flat/gentle slope; with barrier)  
Barrier angle1 : -90.00 deg Angle2 : 0.00 deg  
Barrier height : 10.00 m  
Barrier receiver distance : 51.00 / 51.00 m  
Source elevation : 0.00 m  
Receiver elevation : 0.00 m  
Barrier elevation : 0.00 m  
Reference angle : 0.00



# GRADIENTWIND

ENGINEERS & SCIENTISTS

Results segment # 1: Chapel St (day)

Source height = 1.50 m

Barrier height for grazing incidence

Source Height (m)	Receiver Height (m)	Barrier Height (m)	Elevation of Barrier Top (m)
1.50	14.70	5.90	5.90

ROAD (0.00 + 46.57 + 0.00) = 46.57 dBA

Angle1	Angle2	Alpha	RefLeq	P.Adj	D.Adj	F.Adj	W.Adj	H.Adj	B.Adj
-90	90	0.00	63.96	0.00	-5.05	0.00	0.00	0.00	-12.33

SubLeq

Segment Leq : 46.57 dBA

Results segment # 2: Laurier Ave (day)

Source height = 1.50 m

Barrier height for grazing incidence

Source Height (m)	Receiver Height (m)	Barrier Height (m)	Elevation of Barrier Top (m)
1.50	14.70	3.84	3.84

ROAD (0.00 + 42.95 + 0.00) = 42.95 dBA

Angle1	Angle2	Alpha	RefLeq	P.Adj	D.Adj	F.Adj	W.Adj	H.Adj	B.Adj
-90	0	0.00	67.51	0.00	-6.16	-3.01	0.00	0.00	-15.39

SubLeq



# GRADIENTWIND

ENGINEERS & SCIENTISTS

Segment Leq : 42.95 dBA

Total Leq All Segments: 48.14 dBA

Results segment # 1: Chapel St (night)

-----  
 Source height = 1.50 m

Barrier height for grazing incidence

Source Height (m)	! Receiver Height (m)	! Barrier Height (m)	! Elevation of Barrier Top (m)
1.50	!	14.70	!
		5.90	!
			5.90

ROAD (0.00 + 38.98 + 0.00) = 38.98 dBA

Angle1	Angle2	Alpha	RefLeq	P.Adj	D.Adj	F.Adj	W.Adj	H.Adj	B.Adj
-90	90	0.00	56.36	0.00	-5.05	0.00	0.00	0.00	-12.33

SubLeq  
 -----  
 --  
 38.98  
 -----  
 --

Segment Leq : 38.98 dBA



# GRADIENTWIND

ENGINEERS & SCIENTISTS

Results segment # 2: Laurier Ave (night)

-----

Source height = 1.50 m

Barrier height for grazing incidence

Source Height (m)	! Receiver Height (m)	! Barrier Height (m)	! Elevation of Barrier Top (m)
1.50	!	14.70	!
		3.84	!
			3.84

ROAD (0.00 + 35.35 + 0.00) = 35.35 dBA

Angle1	Angle2	Alpha	RefLeq	P.Adj	D.Adj	F.Adj	W.Adj	H.Adj	B.Adj
SubLeq									

-90	0	0.00	59.91	0.00	-6.16	-3.01	0.00	0.00	-15.39
35.35									

-----

--

Segment Leq : 35.35 dBA

Total Leq All Segments: 40.54 dBA

TOTAL Leq FROM ALL SOURCES (DAY): 48.14  
(NIGHT): 40.54

