

989 Somerset Street

TIA Strategy Report

prepared for:
Domicile Development Inc
371A Richmond Road
Ottawa ON, K2A 0E7

prepared by:
PARSONS
1223 Michael Street North
Suite 100
Ottawa, ON K1J 7T2

July 23, 2019

477039 - 01000

Document Control Page

| | |
|----------------------------|--|
| CLIENT: | Domicile Development Inc |
| PROJECT NAME: | 989 Somerset Street W |
| REPORT TITLE: | Strategy Report |
| PARSONS PROJECT NO: | 477039-01000 |
| VERSION: | Draft |
| DIGITAL MASTER: | \\XCCAN57FS01\Data\ISO\477039\1000\DOCS\4 - Strategy\Strategy_989 Somerset_2019 July.docx |
| ORIGINATOR | Juan Lavin, E.I.T. |
| REVIEWER: | Ron Jack, P. Eng |
| AUTHORIZATION: | |
| CIRCULATION LIST: | Wally Dubyk, Project Manager |
| HISTORY: | TIA Step 1 Screening Form – January 18, 2019 TIA Step 2 Scoping Report – March 5, 2019 TIA Step 3 Forecasting Report – May 4, 2019 TIA Step 4 Strategy Report – July 23, 2019 |




Table of Contents

| | |
|---|-----------|
| DOCUMENT CONTROL PAGE | I |
| 1. SCREENING FORM..... | 1 |
| 2. SCOPING REPORT..... | 1 |
| 2.1. EXISTING AND PLANNED CONDITIONS..... | 1 |
| 2.1.1. proposed development..... | 1 |
| 2.2. EXISTING CONDITIONS | 3 |
| 2.2.1. Area Road Network | 3 |
| 2.2.2. Pedestrian/Cycling Network..... | 3 |
| 2.2.3. Transit Network | 4 |
| 2.2.4. Existing Study Area Intersections..... | 5 |
| 2.2.5. Existing Intersection Volumes | 6 |
| 2.2.6. Existing Road Safety Conditions..... | 6 |
| 2.2.7. Existing Driveways to Adjacent Developments..... | 7 |
| 2.3. PLANNED CONDITIONS..... | 7 |
| 2.3.1. Planned Study Area Transportation Network Changes..... | 7 |
| 2.3.2. Other Area Development | 8 |
| 2.4. STUDY AREA..... | 10 |
| 2.4.1. Transit..... | 10 |
| 2.4.2. Intersection Design..... | 10 |
| 2.5. TIME PERIODS..... | 11 |
| 2.6. HORIZON YEARS | 11 |
| 2.7. EXEMPTION REVIEW | 11 |
| 3. FORECASTING REPORT | 11 |
| 3.1. DEVELOPMENT GENERATED TRAVEL DEMAND..... | 11 |
| 3.1.1. Trip Generation and mode shares | 11 |
| 3.1.2. Mode Shares | 12 |
| 3.1.3. Trip distribution and Trip Assignment..... | 13 |
| 3.2. BACKGROUND NETWORK TRAVEL DEMANDS | 13 |
| 3.2.1. Transportation Network Plans..... | 13 |
| 3.2.2. Background Growth | 13 |
| 3.2.3. Other Developments..... | 13 |
| 3.3. DEMAND RATIONALIZATION | 14 |
| 4. STRATEGY REPORT..... | 14 |
| 4.1. DEVELOPMENT DESIGN | 14 |
| 4.2. PARKING SUPPLY..... | 15 |
| 4.3. BOUNDARY STREET DESIGN..... | 15 |
| 4.4. ACCESS INTERSECTION DESIGN..... | 16 |

| | |
|--|-----------|
| 4.5. TRANSPORTATION DEMAND MANAGEMENT | 16 |
| 4.6. ROUTE CAPACITY..... | 17 |
| 4.7. INTERSECTION DESIGN | 17 |
| 4.7.1. Multi-modal Level of Service | 17 |
| 5. FINDINGS AND RECOMMENDATIONS | 17 |

List of Figures

| | |
|---|----|
| Figure 1: Local Context | 1 |
| Figure 2: Proposed Site Plan | 2 |
| Figure 3: Cycling Network Study Area | 4 |
| Figure 4: Area Transit Network..... | 4 |
| Figure 5: Existing Peak Hour Traffic Volumes..... | 6 |
| Figure 6: Albert Street Modifications | 8 |
| Figure 7: Other Area Developments | 9 |
| Figure 8: Study Area..... | 10 |
| Figure 9: 900 Albert Site Generated Traffic | 14 |

List of Tables

| | |
|---|----|
| Table 1: Existing Performance at Albert/City Centre..... | 6 |
| Table 2: Exemptions Review Summary | 11 |
| Table 3: TRANS Residential Trip Rates | 11 |
| Table 4: Projected Vehicle Trip Generation – TRANS Model..... | 12 |
| Table 5: TRANS Modal Site Trip Generation | 12 |
| Table 6: Mode Share Targets for Development in TOD | 12 |
| Table 7: Albert/Booth Historical Background Growth (2009-2014)..... | 13 |
| Table 8: Vehicle Parking Space Supply | 15 |
| Table 9: Bicycle Parking Requirements | 15 |
| Table 10: MMLOS – Boundary Street Segment | 16 |
| Table 11: MMLOS – Albert/City Centre..... | 17 |

List of Appendices

| |
|---|
| APPENDIX A – City Comments |
| APPENDIX B – Screening Form |
| APPENDIX C – Traffic Counts |
| APPENDIX D – Synchro Analysis: Existing Conditions |
| APPENDIX E – Collision Data |
| APPENDIX F – Background Traffic Growth Analysis |
| APPENDIX G – Multimodal Level of Service Analysis Segments |
| APPENDIX H – TDM Checklist |
| APPENDIX I – Multimodal Level of Service Analysis Intersections |

TIA Strategy Report

The following Strategy Report has been prepared in support of a Site Plan application for a proposed residential development located at 989 Somerset Street W. This document incorporated all comments from all previous steps in the TIA process, as outlined in the City Transportation Impact Assessment (TIA) Guidelines (2017). City comments from the previous submission have been provided in Appendix A.

1. SCREENING FORM

The Screening Form included as Appendix B confirmed the need for a TIA based on the ‘Trip Generation’ and ‘Location’ triggers, given that the proposed development consists of a residential building with a total of approximately 195 units and is located in a Design Priority Area (DPA) and transit-oriented development (TOD) zone. The ‘Safety’ trigger was not met.


2. SCOPING REPORT

2.1. EXISTING AND PLANNED CONDITIONS


2.1.1. PROPOSED DEVELOPMENT

Based on the proposed Site Plan provided by Domicile Development Inc, it is our understanding that the proponent is proposing a single-phase residential development consisting of a 15-storey building, totalling approximately 195 units with underground and surface parking. The main access to the site is proposed via a driveway connection to Spruce Street. The site is currently occupied by a furniture and antiques store, and a lighting store below. The site is zoned as MC – Mixed-Use Centre Zone. The site’s local context is provided as **Figure 1** and the proposed Site Plan is provided as **Figure 2**.

Figure 1: Local Context



DEC-15, 2017



NOTES:

GROSS FLOOR AREA

| | |
|-----------------------------|-----------|
| BELOW GRADE AREAS | |
| P2 PARKING | 249 SQ M |
| P1 PARKING | 249 SQ M |
| BELOW GRADE TOTAL | 498 SQ M |
| GROUND FLOOR | 188 SQ M |
| 2ND FLOOR | 168 SQ M |
| 3RD FLOOR | 167 SQ M |
| 4TH FLOOR | 167 SQ M |
| 5TH FLOOR | 191 SQ M |
| 6TH FLOOR | 191 SQ M |
| 7TH FLOOR | 191 SQ M |
| 8TH TO 13TH FLOOR (8x8)117 | 676 SQ M |
| 14TH TO 15TH FLOOR (8x10)88 | 207 SQ M |
| MECH PH | 58 SQ M |
| ABOVE GRADE TOTAL | 2057 SQ M |
| TOTAL ABOVE + BELOW AREA | 2754 SQ M |

AREA OF SITE

TOTAL SITE AREA 2551 SQ M

UNIT TYPES - RESIDENTIAL TOWER

191 APARTMENTS TOTAL

PARKING (RESIDENTIAL TOWER)

| | |
|--------------------------------|-----|
| RESIDENT | 163 |
| SURFACE | 16 |
| TOTAL PARKING | 179 |
| (TOTAL HANDICAPPED SPACES - 3) | |

MINIMUM RESIDENTIAL PARKING SPACE 0

MAXIMUM COMBINED RESIDENTIAL AND VISITOR PARKING SPACE

1.5 DWELLING UNIT = 2.08 ALLOWABLE SPACES

MIN. VISITOR PARKING: 4 FOR FIRST 12 DWELLING UNITS, 0.383 PER DWELLING UNIT, 191 DWELLING UNITS = 14.8 VISITOR SPACES

BICYCLE PARKING: 0.5 PER DWELLING UNIT: 191(0.5) = 95.5 TOTAL BICYCLE SPACES

LEGAL DESCRIPTION


PART 1 Plan of PART OF LOT 4 AND ALL OF LOT 5 (South Spruce Street Line) AND ALL OF LOT 4 AND 5 (North Somerset Street West), REGISTERED PLAN 73 CITY OF OTTAWA

ORIGINAL SURVEY PREPARED BY ANNIS O'SULLIVAN VOLLEBERG LTD. SURVEY # 13611-13 Domicile L4.5 RPT3 Topo F

NET FLOOR AREA

| | | |
|-----------------------------|------------|--------------|
| GROUND FLOOR | 388 SQ M | 4144 SQ |
| 2ND FLOOR | 1315 SQ M | 14155 SQ |
| 3RD FLOOR | 1415 SQ M | 15177 SQ |
| 4TH FLOOR | 1415 SQ M | 15177 SQ |
| 5TH FLOOR | 1284 SQ M | 13360 SQ |
| 6TH FLOOR | 1284 SQ M | 13360 SQ |
| 7TH FLOOR | 1284 SQ M | 13360 SQ |
| 8TH TO 13TH FLOOR (8x8)117 | 5386 SQ M | 60127 SQ |
| 14TH TO 15TH FLOOR (8x10)88 | 1704 SQ M | 18242 SQ |
| ABOVE GRADE TOTAL | 12446 SQ M | 146,746 SQ |
| | | (307,744 SQ) |

domicile



05 AUG 00 2016 SELECT FOR REVIEW

| no | date | revision |
|----|------|----------|
|----|------|----------|



ALCAIDE WEBSTER ARCHITECTS INC

282-1322 Carling Avenue
Ottawa, ON K2J 7H8 www.awk.ca

CONSULTANT

SURVEYOR - N/A
PLANNING - N/A
GEO-TECHNICAL - N/A
CIVIL - N/A
TRAFFIC - N/A
LANDSCAPE ARCHITECT - GINO J. AIELLO
STRUCTURAL - GIOVANNI STRUZZI
MECHANICAL/ELECTRICAL - N/A

Project

SPRUCE STREET DOMICILE DEVELOPMENTS 989 SOMERSET STREET WEST OTTAWA, ON

| | | | |
|-------|-------------|-------------|-------|
| Drawn | HR, AB, JS | Checked | VA |
| Date | AUGUST 2018 | Project no. | 12-03 |

Drawing title

SITE PLAN

SITE PLAN CONTROL

| | | | |
|----------|----|-------------|-------------|
| revision | 00 | Drawing no. | SP-1 |
|----------|----|-------------|-------------|

1 SITE PLAN
SCALE 1:125

2.2. EXISTING CONDITIONS

2.2.1. AREA ROAD NETWORK

Albert Street is an east-west arterial roadway with a 4-lane cross-section and auxiliary turn lanes at major intersections. It extends from Elgin Street in the east to Bayview Road in the west. West of Bayview Road, Albert Street continues as Scott Street, and east of Elgin Street, it continues as Mackenzie King Bridge. Within the study area, the posted speed limit is 50 km/h.

City Centre Avenue is a north-south local roadway with a 2-lane cross section that extends south from Albert Street. There is no vehicular access to Somerset Street W. The unposted speed limit is understood to be 50 km/h.

Spruce Street is an east-west local roadway extending from City Centre Avenue in the west to Booth Street in the east. Vehicle access to Preston Street is closed. Within the study area, it has a two-lane cross-section. The unposted speed limit is understood to be 50 km/h.

Elm Street is an east-west local roadway extending from City Centre Avenue in the west to Booth Street in the east. Vehicle access to Preston Street is closed. Within the study area, it has a two-lane cross-section. The unposted speed limit is understood to be 50 km/h.

Preston Street is a north-south arterial roadway with a 2-lane cross section that extends from Albert Street in the north to Queen Elizabeth Drive in the south. Auxiliary turn lanes are provided at signalized intersection. The unposted speed limit is understood to be 50 km/h.

Somerset Street W is an east-west arterial roadway with a 2-lane cross section extending from Queen Elizabeth Drive in the east to Wellington Street in the west. Auxiliary turn lanes are provided at signalized intersection. Somerset Street W has wide sidewalks with on road parking bays and bus bays. The unposted speed limit is understood to be 50 km/h.

Bayswater Avenue is a north-south collector roadway extending from Somerset Street W in the north to Carling Avenue in the south (Bayswater further north of Somerset becomes Bayview Road which extends north to the Burnside/Slidell roundabout). The unposted speed limit is understood to be 50 km/h.

2.2.2. PEDESTRIAN/CYCLING NETWORK

Figure 3 illustrates the existing pathway and cycling network in the study area, obtained from the GeoOttawa website.

Within 500m radius of the proposed site, there are north-south as well as east-west multiuse pathways (MUPs). The Trillium Pathway serves as a major pathway to connect north-south cycling and walking paths, located 150 meters west of the project alongside the east of the Trillium Light Rail Tracks and accessible via a local passage way. The Trillium Pathway offers the shortest walking route to pedestrians going to Bayview Station and offers off-grade crossing at Albert Street, promoting safety. On the north side of Albert Street, there is an east-west major cycling and walking pathways which connects to the Trillium Pathway at Bayview Station. Somerset Street W provides on road spine route bike lane, and sidewalks on both sides of the street which will be accessed at grade once the building is finished. City Centre Avenue provides a sidewalk on the east side of the roadway only with short interruptions in sidewalk. It is assumed that a large percentage of pedestrians will use the Trillium Pathway to access public transit and other facilities north of site.


Figure 3: Cycling Network Study Area



2.2.3. TRANSIT NETWORK

Transit service within the vicinity of the site is currently provided by OC Transpo. Multiple routes serve this location as it is located less than 500m walk from Bayview Station, a major transit station which serves both north-south (Trillium Line) and east-west (Confederation Line). Currently, Albert Street has an east-west bus only priority lane. There is 24-hr transit service on weekday and weekend at Bayview Station. Bayview Station on Albert Street currently serves 34 different bus routes, while Somerset Street W adjacent to the project serves bus Route #11. The current transit area network is provided as Figure 4.


Figure 4: Area Transit Network



2.2.4. EXISTING STUDY AREA INTERSECTIONS


Albert/City Centre

The Albert/City Centre intersection is a signalized four-legged intersection. The eastbound approach consists of a transit only auxiliary left-turn lane, a general purpose through lane and a general-purpose auxiliary right-turn lane which doubles as a transit through lane. The westbound approach consists of a general-purpose left-turn lane and through lane and a transit through lane and auxiliary right-turn lane. The northbound approach consists of an auxiliary left turn lane and a right turn lane. The southbound approach consists of a single all movement lane. The northbound through and southbound movements are permitted by authorized vehicles only.



Albert/Preston

The Albert/Preston intersection is a signalized three-legged intersection. The eastbound approach consists of a general-purpose through lane and a general-purpose auxiliary right-turn lane which doubles as a transit through lane. The westbound approach consists of an auxiliary left-turn lane, two through lanes and a transit only through lane. The northbound approach consists of a left-turn lane and a right-turn lane. All movements are permitted at this location.




Somerset W/Preston

The Somerset/Preston intersection is a signalized four-legged intersection. All approaches consist of an auxiliary left-turn lane and a shared through-right lane. The right-turn-on-red is prohibited for all movements from 7am to 7pm.



Somerset W/Bayswater

The Somerset/Bayswater intersection is a signalized four-legged intersection. The east, west, and southbound approaches consist of an auxiliary left-turn lane and a shared through-right lane. The northbound approach consists of an all movement lane. All movements are permitted at this location.



2.2.5. EXISTING INTERSECTION VOLUMES

The existing peak hour traffic volumes within the study area were obtained from the City of Ottawa and are illustrated in **Figure 5**. All counts are the most recent data obtained from the City with the exception of Albert/Preston intersection. Year 2014 counts were used as they resemble the current layout of the intersection, a three-legged intersection, as opposed to the 2016 four-legged intersection used for the Booth Bridge work detour. The peak hour traffic volume count data is included as Appendix C. Note that all vehicular traffic to/from the site must use the City Centre/Albert intersection, and that Spruce Street does not provide vehicular connectivity to Preston Street. The Synchro model outputs for existing conditions for Albert/City Centre are summarized in **Table 1** and are provided in Appendix D.

Figure 5: Existing Peak Hour Traffic Volumes




Table 1: Existing Performance at Albert/City Centre

| Intersection | Weekday AM Peak (PM Peak) | | | | | |
|--------------------|---------------------------|----------------------------|----------|--------------|------|------------|
| | Critical Movement | | | Intersection | | |
| | LoS | max. v/c or avg. delay (s) | Movement | Delay (s) | LoS | v/c |
| Albert/City Centre | A(A) | 0.58(0.60) | EBT(WBT) | 5.4(10.4) | A(A) | 0.52(0.57) |

Note: Analysis of signalized intersections assumes a PHF of 0.90 and a saturation flow rate of 1800 veh/h/lane.

As seen in **Table 1** the Albert/City Centre intersection overall operates at good Level of Service 'A' with modest delays.

2.2.6. EXISTING ROAD SAFETY CONDITIONS

Collision history for study area intersections and roads (2013 to 2017, inclusive) was obtained from the City of Ottawa. A total of 7 collisions were recorded in the 5 years of study. Most collisions (86%) involved only property damage, indicating low impact speeds, and 14% (one collision) involved personal injuries. The primary causes of collisions cited by police include; angle (43%) and turning movement (29%).

A standard unit of measure for assessing collisions at an intersection is based on the number collisions per million entering vehicles (MEV). At intersections within the study area, reported collisions have historically take place at a rate of:

- 0.15/MEV at the Albert/City Centre intersection;
- 0.28 /MEV at City Centre between Elm and Spruce; and,
- 0.88/MEV at City Centre between Spruce and end of road.

It is noteworthy that within the five-years of recorded collision data there were no collisions involving pedestrians or cyclists. The source collision data as provided by the City of Ottawa and related analysis is provided as Appendix E.

2.2.7. EXISTING DRIVEWAYS TO ADJACENT DEVELOPMENTS

There is a private driveway located 37m from the east property limit on Spruce that provides access to a condominium building with 21 surface parking spaces. Across the street from the proposed site are five driveways, two of which provide access to small commercial buildings with surface parking, while the remaining are private driveways. The small business on the north side of Spruce Street has parking for approximately 14 vehicles.

2.3. PLANNED CONDITIONS


2.3.1. PLANNED STUDY AREA TRANSPORTATION NETWORK CHANGES

The City has recently prepared a “complete street” plan for Albert Street within the vicinity of the site. This plan is part of the Stage 1 LRT construction handover to accommodate active modes of travelling to/from the Bayview LRT station expected to be in operation before construction of this project begins. The bus only lanes will be converted to general vehicular traffic due to the opening of the Confederation Light Rail Transit Line which will remove most buses operating on Albert Street. The plan includes the following features:

- Cycle tracks along both sides of Albert Street;
- Paved pedestrian sidewalks on both sides of Albert Street
- Cross-rides and textured cross-walks at intersections;
- Addition of bus lay-by bay area and channelized left-turn lanes;
- Fully-protected intersections; and
- Double east-west through lanes for vehicle traffic at the Albert/City Centre intersection.

The proposed Albert Street intersection design is provided as **Figure 6**. Review of the City’s design and the proposed Site Plan indicates that no changes to the City design are required.

Figure 6: Albert Street Modifications




2.3.2. OTHER AREA DEVELOPMENT

According to the City's development application search tool, the following developments are planned within the vicinity of the subject site and are illustrated in **Figure 7**.



Figure 7: Other Area Developments



900 Albert Street

Three mixed-use residential, office and retail towers have been proposed at 900 Albert Street that are at 65, 56, and 27 storeys high. The Transportation Impact Assessment (prepared by Parsons) projected an increase in vehicle traffic of approximately 204 and 273 veh/h during both the morning and afternoon peak hours. The project will have direct access to Albert Street.

1040-1050 Somerset Street

Located 200 meters west of the site will be two new mixed-use developments composed of 609 residential units and 771 m² of commercial retail. Vehicle traffic from this development is not expected to affect traffic circulation within the study area as they would use Somerset as their main point of access.

Lebreton Flats

Until recently, the NCC was negotiating with the RendezVous LeBreton Group (RLG) to transform the 21-hectare site just west of the Parliament Buildings along the historic Ottawa River. The NCC ended discussions with RLG as of February 2019, and the future of this project is unknown at this time.

Zibi/Chaudière Islands

Windmill Development’s proposed redevelopment plans of the former Domtar lands, called Zibi, entails approximately 1M ft² of mixed-use development on the Ontario side of the provincial border and approximately 2M ft² of mixed-use development on the Quebec side. The redevelopment is expected to occur in multiple phases over the next 15 to 20 years. Zibi is located approximately 1.5km to the northeast of the site, located just north of the Lebreton Flats community development.

Parsons completed a Multi-Modal Transportation Impact Study for the proposed development in April 2014. The study addressed the form and function of the adjacent arterial roads, identified the broad impacts of proposed reduced road capacity and increased traffic demand on interprovincial travel, confirmed the site vehicle access points and their functional requirements, and highlighted the importance of achieving increased transit, bike and walk mode splits and recommended the facilities needed to achieve. At full build-out, the redevelopment is expected to generate between 3,000 and 3,500 person-trips during the morning and afternoon peak hours. The estimated 900 new vehicle trips during the critical afternoon peak hour will be distributed in all directions within both provinces, and traffic volumes on the street network near 989 Somerset Street are likely to be impacted to a small degree as a result.

145 Loretta/951 Gladstone

Three mixed use residential, office and retail towers have been proposed at 145 Loretta/951 Gladstone that are at 41, 35, and 30 storeys high. Vehicle traffic from this development is not expected to affect traffic circulation within the study area as it is located over 1.6km by driving means.

2.4. STUDY AREA


2.4.1. TRANSIT

As mentioned previously, transit will be served within the area with a light rail transit system, Confederation Line for east-west trips and Trillium Line for southbound trips. Additionally, Somerset Street W will be served by Route #11.

2.4.2. INTERSECTION DESIGN

Due to the proximity of the subject development to rapid transit and cycling facilities, it is expected that site traffic generation will be low, thereby reducing the requirements for analysis and design of study area intersections. The proposed study area is depicted in **Figure 8**.

Figure 8: Study Area



- Albert/Alberta;
- City Centre;
- Somerset/Alberta;
- Somerset/Bayswater;
- City Centre adjacent to site; and,
- Spruce Street adjacent to site

2.5. TIME PERIODS

Primarily residential trips will be generated by the proposed development; therefore, the appropriate time periods to be assessed were weekday morning and afternoon commuter peak hours.

2.6. HORIZON YEARS

For the purposes of the operational analysis it is assumed that the subject development will be fully built and occupied by 2020. This will require the analysis of 2020 and 2025 horizon years.

2.7. EXEMPTION REVIEW

Based on the City's TIA guidelines and the subject site, the following modules/elements of the TIA process, summarized in **Table 2**, are recommended to be exempt in the subsequent steps of the TIA process:

Table 2: Exemptions Review Summary

| Module | Element | Exemption Consideration |
|--------------------------------|---------------------------|--|
| 4.1 Development Design | 4.1.3 New Streets Network | Not required for applications involving site plans. |
| 4.2 Parking | 4.2.2 Spillover Parking | The on-site parking is expected to meet By-Law requirements. |
| 4.8 Review of Network Concept | All elements | The site is not expected to generate 200 trips more than the established zoning. This will be confirmed in Step 3. |
| 4.4 Access Intersection Design | 4.4.3 Intersection Design | Intersection MMLoS and Synchro analysis will only be completed for existing conditions as there is only 20 new veh/h generated by the proposed development, which is considered negligible. Background traffic associated with the 900 Albert development has already been analyzed within its associated TIA. |
| 4.9 Intersection Design | 4.9.2 Intersection Design | Intersection MMLoS and Synchro analysis will only be completed for existing conditions as there is only 20 new veh/h generated by the proposed development which is considered negligible. Background traffic associated with the 900 Albert development has already been analyzed within its associated TIA. |

3. FORECASTING REPORT

3.1. DEVELOPMENT GENERATED TRAVEL DEMAND

3.1.1. TRIP GENERATION AND MODE SHARES

Appropriate trip generation rate for the proposed development consisting of approximately 195 residential units¹ was obtained from the City's 2009 TRANS Trip Generation – Residential Trip Rates. **Table 3** summarizes the trip generation rates.

Table 3: TRANS Residential Trip Rates

| Land Use | Data Source | Trip Rates | |
|---|-------------|--------------|--------------|
| | | AM Peak | PM Peak |
| High Rise Apartment | 222 | T = 0.17(du) | T = 0.16(du) |
| <i>Note: T = Average Vehicle Trip Ends; du = dwelling units</i> | | | |

¹ The most current site plan reflects 191 units. The ensuing analysis is based on a slightly higher unit count of 195 units.

Using the TRANS Trip Generation Rates for apartment and townhouse uses, the initial estimate of vehicle trips generated by the proposed residential development was projected. The results are summarized in **Table 4**.

Table 4: Projected Vehicle Trip Generation - TRANS Model

| Land Use | Area | AM Peak (Veh/h) | | | PM Peak (Veh/h) | | |
|-------------------------------|-----------|-----------------|-----------|-----------|-----------------|-----------|-----------|
| | | In | Out | Total | In | Out | Total |
| High Rise Apartments | 195 units | 7 | 26 | 33 | 19 | 12 | 31 |
| Total 'New' Auto Trips | | 7 | 26 | 33 | 19 | 12 | 31 |

As shown in **Table 4**, a total of approximately 30 to 35 veh/h are projected to travel to/from the proposed development during both the weekday morning and afternoon commuter peak hours prior to site-specific adjustments. The vehicle trips shown in **Table 4** for the proposed site were converted to total person trips using the auto modal share values in Table 3.6 of the TRANS report. Total person-trip generation values were then reduced to non-auto modal shares for a site within a transit-oriented development (TOD) zone. The modal share values for the apartment and townhouse land uses within the proposed development are summarized in **Table 5**.

Table 5: TRANS Modal Site Trip Generation

| Travel Mode | Mode Share | AM Peak (Person Trips/h) | | | PM Peak (Person Trips/h) | | |
|-------------------------------|------------|--------------------------|-----------|-----------|--------------------------|----------|-----------|
| | | In | Out | Total | In | Out | Total |
| Auto Driver | 15% | 4 | 15 | 19 | 12 | 8 | 20 |
| Auto Passenger | 5% | 2 | 4 | 6 | 3 | 3 | 6 |
| Transit | 65% | 18 | 61 | 79 | 54 | 34 | 88 |
| Non-motorized | 15% | 4 | 14 | 18 | 13 | 8 | 21 |
| Total Person Trips | 100% | 28 | 94 | 122 | 82 | 53 | 135 |
| Total 'New' Auto Trips | | 4 | 15 | 19 | 12 | 8 | 20 |

As shown in **Table 5**, based on TRANS Trip Generation and TOD mode shares, the proposed site is projected to generate approximately 120 to 135 new person-trips in the weekday morning and afternoon peak hours respectively. The increase in new two-way transit trips is estimated to be 80 to 90 trips per hour, and the new bike/walk trips is approximately 20 trips per hour.

The total amount of 'new' vehicle traffic to the study area is projected to be 20 veh/h two-way total during the AM and PM peak hours. This amount of traffic equates to approximately 1 new vehicle every 3 minutes during peak hours and is not considered a significant increase in traffic. Its impact on the operation of study area intersections will be negligible. Even if TOD mode share goals are not reached, it is anticipated that approximately 1 vehicle will leave or enter the site every 2 minutes during the peak hours, which is also not considered a significant increase in traffic.

3.1.2. MODE SHARES

Due to the site's proximity to the Bayview Station (less than 600m), TOD mode shares are applied. The mode shares for a development located in a TOD are illustrated in **Table 6**. These mode shares will also be used for the 2025 horizon year.

Table 6: Mode Share Targets for Development in TOD

| Travel Mode | Mode Share Target | Rationale |
|----------------|-------------------|--|
| Transit | 65% | Development is located within 600 m of a future LRT station, making it a Transit-Oriented Development (TOD) which have transit targets of 65%. |
| Walking | 10% | This is consistent with the City’s TMP, TOD areas and the existing TRANS trip-generation report. |
| Biking | 5% | This is consistent with the City’s TMP, TOD areas and the existing TRANS trip-generation report. |
| Auto Passenger | 5% | This is consistent with TOD targets. |
| Auto Driver | 15% | This is consistent with TOD targets. |

3.1.3. TRIP DISTRIBUTION AND TRIP ASSIGNMENT

Given the low projected number of vehicle trips (20 veh/h two-way total) projected to be generated by the proposed development, the future impact on the existing roadway network is considered negligible. All vehicular traffic will go through Albert/City Centre intersection which currently operates at good LoS ‘A’ and has capacity available. As such, no further traffic assessment is included herein.

3.2. BACKGROUND NETWORK TRAVEL DEMANDS

3.2.1. TRANSPORTATION NETWORK PLANS

See Section 2.3.1.

3.2.2. BACKGROUND GROWTH

The following background traffic growth (summarized in **Table 7**) was calculated based on historical traffic count data (years 2009, 2013 and 2014) provided by the City of Ottawa at the Albert/Booth intersection east of the site. Detailed background traffic growth analysis is included as Appendix F.

Table 7: Albert/Booth Historical Background Growth (2009-2014)


| Time Period | Percent Annual Change | | | | |
|-------------|-----------------------|-----------|----------|----------|---------------|
| | North Leg | South Leg | East Leg | West Leg | Overall |
| 8 hrs | -5.27% | -8.92% | -9.20% | -0.09% | -5.30% |
| AM Peak | -3.72% | -6.47% | -3.24% | 3.37% | -2.20% |
| PM Peak | -9.47% | -10.91% | -11.59% | -4.83% | -8.95% |

As shown in **Table 7**, Albert Street, at the Albert/Booth intersection, has experienced approximately 2 to 9% overall annual decrease in traffic within recent years. This is consistent with the decline in vehicular traffic outline in the TMP. Rather than use a negative growth rate, a more conservative growth rate of 0% was assumed as advised by the City of Ottawa Modelling Group.

3.2.3. OTHER DEVELOPMENTS

As described in Section 2.3.2, the future 900 Albert development proposes accesses to Albert Street in the vicinity of the study area intersections. As such, the expected site generated traffic volumes associated with this development are shown in **Figure 9** below and will be included in the Strategy Report.

Figure 9: 900 Albert Site Generated Traffic



3.3. DEMAND RATIONALIZATION

Based on the foregoing analysis of trip-generation and background traffic growth, the site-generated traffic volumes are considered negligible as only 1 vehicle two-way total is projected every 3 minutes during the peak hours. As such, and as the existing Albert/City Centre intersection operates at a very good Level of Service 'A', no further traffic assessment is included herein.

4. STRATEGY REPORT

4.1. DEVELOPMENT DESIGN

Location of Transit Facilities

The subject site is approximately 200m walking distance from bus stops located on Somerset Street and Preston Street and approximately 500m walking distance from the Bayview LRT Station, where the Trillium and the Confederation Lines meet.

Pedestrian Routes and Facilities

The building will have at-grade accesses directly on to City Centre Avenue from the first floor and Somerset Street from the second floor. Sidewalks are located on both sides of Somerset Street (east-west arterial). There are no sidewalks on the west side of City Centre Drive and the sidewalks on the east side are not continuous. However, the Trillium Pathway is located 150m to the west of the building and provides a grade separated north-south paved multi-use pathway. Pedestrians are more likely to access Bayview Station via the Trillium Pathway compared to City Centre Avenue as it is a shorter walking distance and eliminates road crossings. No internal walkways or site circulation is required.

Bicycle Parking

The proponent is providing bicycle parking spaces at a rate of 0.5 per unit which equates to 98 parking spaces, meeting the City's By-Law requirements. The majority of bicycle parking spaces are provided indoors in a secure, well-lit area located in the underground parking garage.

Vehicle Access

The proposed development access will utilize the existing curb depression used by the existing building on Spruce Street.

With regard to on-site circulation, the proposed parking lot is laid out such that two-way traffic can be efficiently accommodated. A Site Plan of the underground parking has been provided and meets the City's minimum By-Law requirements. The ramp width to the underground parking lot is 6m, meeting the minimum requirement. Drive aisle widths accommodating the 2-way vehicle traffic meet the minimum width of 6m. The ramp providing access to the lower level parking has proper transition grades and a ramp grade between 10% to 15%. The ramp access does not exceed a 2% or less transition grade within 6m from the property line.

Garbage pick up will take place on-site. The garbage bins are located at ground level in a garbage room with access to/from Spruce Street.

4.2. PARKING SUPPLY

The subject site is located within 600 meters walking distance to the Bayview LRT transit station. Considering Sections 101(2), 102(5), 103(1) and 103(2) of the Zoning By-Law 2008-250-Consolidation-Part 4, the vehicle parking requirements have been estimated and summarized in **Table 8**. **Table 9** summarizes the bicycle parking requirements as per City of Ottawa Zoning By-Law-Part 4, sections 100-114.

Table 8: Vehicle Parking Space Supply

| Land Use | | Rate per Unit | | Required Vehicle Spaces | | | Proposed Spaces |
|-------------|-----------|---------------|---------|-------------------------|----------|-------|-----------------|
| | | Residential | Visitor | Residential | Visitors | Total | |
| Residential | 195 units | 0 | 0.1 | 0 | 20 | 20 | 178 |

Table 9: Bicycle Parking Requirements

| Land Use | | Rate per Units | Bicycle Spaces | |
|-------------|-----------|----------------|----------------|----------|
| | | | Required | Proposed |
| Residential | 195 units | 0.5 | 98 | 98 |

As shown in **Table 8** and **Table 9**, the proposed development is required to provide a minimum of 20 vehicle parking spaces and 98 bicycle parking spaces. With a total of 178 proposed underground and surface parking spaces and 98 bicycle parking spaces, the proposed development is meeting City requirements.

4.3. BOUNDARY STREET DESIGN

The boundary streets for the development are City Centre Avenue, Somerset Street, and Spruce Street. The existing roadways, geometry consists of the following features.

- City Centre Avenue:
 - 1 vehicle travel lane in each direction;
 - 1.8m sidewalk on east side of the roadway only; and,
 - Less than 3,000 vehicles per day.
- Somerset Street
 - 1 vehicle travel lane in each direction;
 - 1.8 - 3m sidewalks on both sides of the roadway;
 - On-road parking bays; and,
 - More than 3,000 vehicles per day.
- Spruce Street
 - 1 vehicle travel lane in each direction;
 - 1.8m sidewalks on both sides of the roadway; and,

- Less than 3,000 vehicles per day along Spruce Street.

The multi-modal Level of Service analysis for the subject road segments adjacent to the site is summarized in **Table 10** with detail analysis provided in Appendix G.

Table 10: MMLoS - Boundary Street Segment

| Road Segment | Level of Service | | | | | | | |
|--|------------------|--------|----------------|--------|----------------|--------|---------------|--------|
| | Pedestrian | | Bicycle (BLoS) | | Transit (TLoS) | | Truck (TkLoS) | |
| | PLoS | Target | BLoS | Target | TLoS | Target | TkLoS | Target |
| City Centre between Spruce and Somerset | F | A | A | B | - | N/A | - | N/A |
| Somerset between Preston and Breeze Hill | B | A | C | B | D | D | C | D |
| Spruce between City Centre and Preston | B | A | A | B | - | N/A | - | N/A |

Given the development’s proximity to a future LRT Station, the target levels of service for pedestrians and cyclists are high (‘A’ to ‘B’). The transit Level of Service is met on Somerset Street. As there is no transit service on Spruce Street and City Centre Avenue, there is no TLoS. The truck Level of Service is met given the existing geometry and lane widths.

Pedestrian PLoS targets were not met on any boundary street. The triggers were different in each case: high volumes on Somerset, the absence of a boulevard on Spruce, and the lack of a west side sidewalk on City Centre. MMLoS targets would be met if these constraints/triggers were resolved, but they may not be feasible in the context of this development. In this case, the proponent is planning to accommodate pedestrians by building a sidewalk along the site frontage on City Centre Avenue, which improves the PLoS to ‘B’.

Cyclist BLoS targets were met on City Centre Avenue and Spruce Street. Increasing the bike lane width by 0.25m on Somerset Street would improve the Level of Service to BLoS ‘B’, thus meeting the target. This can be considered at the time of roadway reconstruction, if feasible.

4.4. ACCESS INTERSECTION DESIGN

Site access will use an existing 6.5m driveway to Spruce Street located approximately 300m south of the Albert/City Centre intersection. This location is acceptable with respect to the City’s Private Approach By-Law. Regarding the design, the proposed surface and underground parking lot is laid out such that two-way traffic can be efficiently accommodated. As there are only approximately 20 two-way vehicle trips projected in both peak hours, no significant changes to existing intersection operations are expected.

4.5. TRANSPORTATION DEMAND MANAGEMENT

The TDM checklist is attached as Appendix H. Some of the TDM measures that the proponent is providing/considering are as follows:

- Sidewalks provided along the site’s street frontage;
- The amount of bicycle parking meets the By-Law minimum requirement;
- Interior bike storage provided with access provided adjacent to the surface parking lot;
- Safe and direct connections for pedestrians to nearby transit stops and Bayview LRT Transit Station using multi-use pathways.

Given the type of development and its location, a high amount of non-auto trips is expected to be generated by the proposed development and that transit shares will increase, and auto shares will decrease over time for the subject site.

4.6. ROUTE CAPACITY

It is projected that 80 and 90 ‘new’ two-way transit passenger trips will be generated for the AM and PM peak hours, respectively. Considering the envisioned Confederation LRT Line is projected to operate with a capacity of 600 passengers per train and 12 trains per hour per direction during peak hours, it is anticipated that the future transit network will have sufficient capacity to accommodate the projected transit demand.

4.7. INTERSECTION DESIGN

There are only approximately 20 two-way vehicle trips projected in both peak hours which equates to approximately one vehicle every 3 minutes. Given the low number of vehicle trips projected to be generated by the proposed development, combined with the very good Level of Service operations at the Albert/City Centre intersection, the future roadway network and intersection impact is considered negligible. As such, no further traffic assessment is included herein.

4.7.1. MULTI-MODAL LEVEL OF SERVICE

The Albert/City Centre intersection is within 600 meters of high-frequency transit. The applicable target levels of service for pedestrians and cyclists is PLoS ‘A’ and BLoS ‘B’, respectively. The MMLoS analysis for the existing signalized intersection Albert/City Centre within the study area is summarized in **Table 11**, with detailed analyses provided in Appendix I. As stated in the MMLoS Guidelines, only signalized or roundabout intersections are considered for the intersection Level of Service measures.

Table 11: MMLoS – Albert/City Centre

| Intersection | Level of Service | | | |
|--------------------|-------------------|--------|----------------|--------|
| | Pedestrian (PLoS) | | Bicycle (BLoS) | |
| | PLoS | Target | BLoS | Target |
| Albert/City Centre | D | A | A | B |

As shown in **Table 11**, the bicycle target Level of Service is met at the Albert/City Centre intersection. However, the pedestrian target Level of Service is not met. Pedestrians have to cross 4 to 5 lanes of traffic when crossing Albert Street resulting in the poor PLoS. Pedestrians are encouraged to use the grade separated multi-use Trillium Pathway which would eliminate a road crossing at Albert Street. Furthermore, it provides shorter walking distances from site to Bayview Station and to connecting multi-use pathways and sidewalks on Albert Street.

5. FINDINGS AND RECOMMENDATIONS

Based on the results summarized herein the following findings and recommendations are provided:

- A residential development comprised of approximately 195 units in a 15-storey apartment is being proposed at 989 Somerset Street W with an estimated build-out in year 2020 replacing an existing furniture and antiques store and a lighting store;
- The proposed development is projected to generate ‘new’ vehicle volumes of approximately 20 veh/h two-way total during the weekday morning and afternoon peak hours. As the increase in vehicle traffic is minimal, and the existing Level of Service at the Albert/City Centre intersection is an excellent LoS ‘A’, no adverse off-site impacts are expected;
- A total of 178 parking spaces are proposed which meet the City’s minimum and maximum parking requirements for a development located in Area Z;
- 98 bicycle parking spaces are proposed which meets the minimum bicycle parking spaces outlined in the City’s By-Law requirements;

PARSONS

- Site access is proposed via the existing driveway connection to Spruce Street located 300m south of the Albert/City Centre intersection;
- TDM measures being implemented with the development include:
 - 98 bicycle parking spaces, the majority of which are within the building; and
 - A sidewalk along the site frontage on City Centre Avenue which increases the PLoS to a 'B' from current PLoS 'F'.
- The MMLOS road segment analysis shows that future conditions on boundary streets do not meet MMLOS area targets for pedestrians. Providing wider sidewalks if feasible, with a boulevard would improve the Level of Service to PLoS 'A' for Spruce Street and City Centre Avenue. Increasing the width of the bike lane on Somerset Street by 0.25m if feasible would improve the cycling Level of Service BLoS 'B', thus meeting the targets; and
- The MMLOS intersection analysis shows that Albert/City Centre intersection does not meet MMLOS area targets for pedestrians with PLoS of 'D' and target of 'A'. Pedestrians are encouraged to use the grade separated multi-use Trillium Pathway which eliminates a road crossing at Albert Street and provides shorter walking distances from the site to each of the Bayview Station, to connecting multi-use pathways, and to sidewalks on Albert Street.

Based on the foregoing findings, this report satisfies the TIA requirements for 989 Somerset and the Site Plan is recommended from a transportation perspective.

Prepared By:

Reviewed By:




Juan Lavin, E.I.T.

Ronald Jack, P.Eng.
Senior Transportation Engineer

Appendix A

City Comments

DRAFT



Comments from Wally – 989 Somerset Forecasting

Transportation Engineering Services

Development address appears to also encompass 158 Spruce Street West - which is not mentioned in the report and should be included.

We confirmed with land management that 158 Spruce will not be part of this project and there is likely an error on City's Development Application website.

The proposed development at 145 Loretta Avenue North / 951 Gladstone Avenue does not appear to have been considered as a neighbouring development that could impact future background traffic. This development should be included in the report.

The development has been included in section 2.3.2. Note: this development will be 1.67kms away for those driving.

In Section 3.2.1 there is a small error, it mentions Section 2.2 when it should be referring to Section 2.3.1 instead.

Noted, corrections made.

Traffic Signal Operations

Given the site is accessible to vehicles only through the intersection of Albert Street and City Centre, total traffic analysis should be provided for this intersection for both signalized and un-signalized scenarios. Although the impacts due to vehicle volumes are quite low, the Transit trips are high and most users would be accessing the Station on Albert St. This would increase pedestrian activity at Albert & City Centre (if still signalized) and/or the 900 Albert proposed signal. A high number of pedestrian actuations would in fact have a greater effect on operations (vs the signal cycling to service ~ 33 veh per hour).

Sensitivity tests were completed in Synchro with Albert/City Centre or 900 Albert access as a signalized intersection, and the results showed no significant change in level of operation when maxing out ped calls. Even if a higher percentage of pedestrians was assumed to use City Centre for a more conservative sensitivity test, the number of pedestrians in the existing traffic counts (13 in AM, 26 in PM), plus development generated were not shown to create any significant level of service changes.

Furthermore, the site is only expected to generate approximately 80 and 90 transit users in the AM and PM respectively. It is anticipated that most transit users will use the Trillium Pathway located approximately 150 meters west of the site, which offers grade separated crossing at Albert Street and a more direct route to the LRT Station (more than 100m shorter route than walking via City Centre).

An additional traffic analysis scenario, based on non-TOD mode shares, should be included in the submission along with the TOD projected modal share scenario. This would help to identify any interim measures required to improve on operations/safety until high transit and active modes are achieved. It would also help to identify locations

that require close monitoring in the interim until/or if high transit shares are not achieved.

Noted, revisions made to section 3.1.1. Note: Even with non-TOD mode shares, less than one vehicle trip will be generated per minute during peak hours.

The stated decline in traffic at Albert Street and Booth Street should be reviewed in more detail. The background traffic analysis is questionable with the use of a count conducted on a Friday (August 29th, 2014) and the exclusion of an August 16th, 2012 count in the analysis. Include all traffic counts in Appendix B.

A background growth rate of 0% will be used as advised by the Transportation Modelling Group at the City.

While the more recent 2017 count does not reflect typical east/west traffic due to the current Scott Street / Albert Street detour, north/south volumes are significantly higher in this count than the 2014 count and in line with 2009, 2012 and 2013 counts.

Noted, volumes updated accordingly.

Considering the low use of vehicles assumed to and from the site, during Analysis clarify pedestrian and cycling connections to the MUP and Somerset Street West from the site within the TIA document. Note - east side sidewalk on City Centre is not continuous from the site to the intersection of Albert Street and City Centre.

Noted, revisions made in section 2.2.2.

Section 2.2.1 should also address Elm Street where vehicle access to Preston Street is also closed.

Noted, section 2.2.1 updated accordingly.

General

Somerset Street W is designated as an Arterial road within the City's Official Plan with a ROW protection of 20.0 metres. Note: Maximum land requirement from property abutting existing ROW (0.90 m). Subject to widening/easement policy.

A 3.0 metres x 3.0 metres sight triangle is required at the intersection of City Centre Avenue and Spruce Street and is to be shown on all drawings.

The concrete sidewalk is to meet City standards and be 1.8 metres minimum in width and be continuous along property frontage and depressed through the proposed access (please refer to the City's sidewalk and curb standard drawing SC7.1).

Ensure that the driveway grade does not exceed 2-6% within the private property for a distance of 9.0 metres from the highway line; see Section 25 (t) of the Private Approach By-Law #2003-447. Any grade exceeding 6% will require a subsurface melting device.


Underground access ramp shall be minimum 6.7 metres wide for 2-way traffic.

Acknowledged.

Appendix B

Screening Form

DRAFT



City of Ottawa 2017 TIA Guidelines

Date

18-Jan-19

TIA Screening Form

Project

989 Somerset Street W TIA

Project Number

477039

| Results of Screening | Yes/No |
|---|--------|
| Development Satisfies the Trip Generation Trigger | Yes |
| Development Satisfies the Location Trigger | Yes |
| Development Satisfies the Safety Trigger | No |

Module 1.1 - Description of Proposed Development

| | |
|----------------------------------|---|
| Municipal Address | 989 Somerset Street |
| Description of location | Located on the north side of Somerset Street, at the corner of City Centre Avenue and Spruce Street |
| Land Use | Residential building |
| Development Size | 15 storey residential building totalling 191 units; underground and surface parking provided |
| Number of Accesses and Locations | Vehicle access proposed to Spruce Street with additional pedestrian access to Somerset Street W. |
| Development Phasing | Single Phase |
| Buildout Year | 2020 |
| Sketch Plan / Site Plan | See attached |

Module 1.2 - Trip Generation Trigger

| | | |
|------------------------------|-------------------------|-------|
| Land Use Type | Townhomes or Apartments | |
| Development Size | 191 | Units |
| Trip Generation Trigger Met? | Yes | |

Module 1.3 - Location Triggers

| | | |
|--|-----|---|
| Development Proposes a new driveway to a boundary street that is designated as part of the City's Transit Priority, Rapid Transit, or Spine Bicycle Networks (See Sheet 3) | No | Pedestrian access on Somerset Street and Spruce Street. Vehicle access on Spruce Street only. |
| Development is in a Design Priority Area (DPA) or Transit-oriented Development (TOD) zone. (See Sheet 3) | Yes | |
| Location Trigger Met? | Yes | |


Module 1.4 - Safety Triggers

| | | |
|--|-----|--|
| Posted Speed Limit on any boundary road | <80 | km/h |
| Horizontal / Vertical Curvature on a boundary street limits sight lines at a proposed driveway | No | |
| A proposed driveway is within the area of influence of an adjacent traffic signal or roundabout (i.e. within 300 m of intersection in rural conditions, or within 150 m of intersection in urban/ suburban conditions) or within auxiliary lanes of an intersection; | No | Albert/City Centre intersection 250m north of proposed driveway on Spruce Street |
| A proposed driveway makes use of an existing median break that serves an existing site | No | |
| There is a documented history of traffic operations or safety concerns on the boundary streets within 500 m of the development | No | |
| The development includes a drive-thru facility | No | |
| Safety Trigger Met? | No | |

Appendix C

Traffic Counts

DRAFT



Turning Movement Count - Peak Hour Diagram


CHAMPAGNE AVE @ WELLINGTON ST

Survey Date: Wednesday, September 07, 2016

Start Time: 07:00

WO No: 36275

Device: Miovision



Comments ALBERT ST AND CITY CENTRE DR

Turning Movement Count - Peak Hour Diagram


CHAMPAGNE AVE @ WELLINGTON ST

Survey Date: Wednesday, September 07, 2016

Start Time: 07:00

WO No: 36275

Device: Miovision




Survey Date: Wednesday, April 02, 2014

Start Time: 07:00

WO No: 29661

Device: Miovision




Survey Date: Wednesday, April 02, 2014

Start Time: 07:00

WO No: 29661

Device: Miovision



Turning Movement Count - Peak Hour Diagram


BAYSWATER AVE @ SOMERSET ST

Survey Date: Wednesday, September 07, 2016

Start Time: 07:00

WO No: 36276

Device: Miovision



Turning Movement Count - Peak Hour Diagram


BAYSWATER AVE @ SOMERSET ST

Survey Date: Wednesday, September 07, 2016

Start Time: 07:00

WO No: 36276

Device: Miovision



Comments

Turning Movement Count - Peak Hour Diagram


PRESTON ST @ SOMERSET ST

Survey Date: Tuesday, June 20, 2017

Start Time: 07:00

WO No: 37133

Device: Miovision



Turning Movement Count - Peak Hour Diagram


PRESTON ST @ SOMERSET ST

Survey Date: Tuesday, June 20, 2017

Start Time: 07:00

WO No: 37133

Device: Miovision



Appendix D

Synchro Analysis: Existing Conditions

DRAFT

Lanes, Volumes, Timings
1: City Centre & Albert

Existing AM
07/22/2019



| Lane Group | EBL | EBT | EBR | WBL | WBT | WBR | NBL | NBT | NBR | SBL | SBT | SBR |
|------------------------|-------|-------|-------|-------|-------|-------|-------|-------|-----|-------|-------|-------|
| Lane Configurations | | | | | | | | | | | | |
| Traffic Volume (vph) | 6 | 776 | 91 | 91 | 333 | 21 | 22 | 0 | 52 | 22 | 0 | 7 |
| Future Volume (vph) | 6 | 776 | 91 | 91 | 333 | 21 | 22 | 0 | 52 | 22 | 0 | 7 |
| Satd. Flow (prot) | 1658 | 1745 | 1483 | 1658 | 1745 | 1483 | 1658 | 1483 | 0 | 0 | 1625 | 0 |
| Flt Permitted | 0.501 | | | 0.323 | | | 0.736 | | | | 0.742 | |
| Satd. Flow (perm) | 874 | 1745 | 1483 | 564 | 1745 | 1483 | 1284 | 1483 | 0 | 0 | 1251 | 0 |
| Satd. Flow (RTOR) | | | 76 | | | 87 | | 191 | | | 87 | |
| Lane Group Flow (vph) | 7 | 862 | 101 | 101 | 370 | 23 | 24 | 58 | 0 | 0 | 32 | 0 |
| Turn Type | pm+pt | NA | Perm | Perm | NA | Perm | Perm | NA | | Perm | NA | |
| Protected Phases | 5 | 2 | | | 6 | | | 8 | | | | 4 |
| Permitted Phases | 2 | | 2 | 6 | | 6 | 8 | | | 4 | | |
| Detector Phase | 5 | 2 | 2 | 6 | 6 | 6 | 8 | 8 | | 4 | 4 | |
| Switch Phase | | | | | | | | | | | | |
| Minimum Initial (s) | 5.0 | 10.0 | 10.0 | 10.0 | 10.0 | 10.0 | 10.0 | 10.0 | | 10.0 | 10.0 | |
| Minimum Split (s) | 11.3 | 27.3 | 27.3 | 27.3 | 27.3 | 27.3 | 29.3 | 29.3 | | 29.3 | 29.3 | |
| Total Split (s) | 17.0 | 84.0 | 84.0 | 67.0 | 67.0 | 67.0 | 36.0 | 36.0 | | 36.0 | 36.0 | |
| Total Split (%) | 14.2% | 70.0% | 70.0% | 55.8% | 55.8% | 55.8% | 30.0% | 30.0% | | 30.0% | 30.0% | |
| Yellow Time (s) | 3.3 | 3.3 | 3.3 | 3.3 | 3.3 | 3.3 | 3.3 | 3.3 | | 3.3 | 3.3 | |
| All-Red Time (s) | 3.0 | 3.0 | 3.0 | 3.0 | 3.0 | 3.0 | 3.0 | 3.0 | | 3.0 | 3.0 | |
| Lost Time Adjust (s) | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | | 0.0 | 0.0 | |
| Total Lost Time (s) | 6.3 | 6.3 | 6.3 | 6.3 | 6.3 | 6.3 | 6.3 | 6.3 | | 6.3 | 6.3 | |
| Lead/Lag | Lead | | | Lag | Lag | Lag | | | | | | |
| Lead-Lag Optimize? | Yes | | | Yes | Yes | Yes | | | | | | |
| Recall Mode | None | C-Max | C-Max | C-Max | C-Max | C-Max | None | None | | None | None | |
| Act Effct Green (s) | 100.5 | 101.8 | 101.8 | 99.3 | 99.3 | 99.3 | 10.2 | 10.2 | | | | 10.2 |
| Actuated g/C Ratio | 0.84 | 0.85 | 0.85 | 0.83 | 0.83 | 0.83 | 0.08 | 0.08 | | | | 0.08 |
| v/c Ratio | 0.01 | 0.58 | 0.08 | 0.22 | 0.26 | 0.02 | 0.22 | 0.19 | | | | 0.17 |
| Control Delay | 2.3 | 5.7 | 0.9 | 5.2 | 4.1 | 0.0 | 56.4 | 1.4 | | | | 2.0 |
| Queue Delay | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | | | | 0.0 |
| Total Delay | 2.3 | 5.7 | 0.9 | 5.2 | 4.1 | 0.0 | 56.4 | 1.4 | | | | 2.0 |
| LOS | A | A | A | A | A | A | E | A | | | | A |
| Approach Delay | | 5.2 | | | 4.1 | | | 17.5 | | | | 2.0 |
| Approach LOS | | A | | | A | | | B | | | | A |
| Queue Length 50th (m) | 0.3 | 59.8 | 0.9 | 4.3 | 16.4 | 0.0 | 5.4 | 0.0 | | | | 0.0 |
| Queue Length 95th (m) | 1.1 | 89.2 | 3.8 | 15.6 | 42.4 | 0.0 | 14.0 | 0.0 | | | | 0.0 |
| Internal Link Dist (m) | | 330.0 | | | 569.4 | | | 245.5 | | | | 144.5 |
| Turn Bay Length (m) | 30.0 | | 50.0 | 40.0 | | 30.0 | 40.0 | | | | | |
| Base Capacity (vph) | 802 | 1479 | 1269 | 466 | 1444 | 1243 | 317 | 510 | | | | 375 |
| Starvation Cap Reductn | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | | | | 0 |
| Spillback Cap Reductn | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | | | | 0 |
| Storage Cap Reductn | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | | | | 0 |
| Reduced v/c Ratio | 0.01 | 0.58 | 0.08 | 0.22 | 0.26 | 0.02 | 0.08 | 0.11 | | | | 0.09 |

Intersection Summary

Cycle Length: 120
 Actuated Cycle Length: 120
 Offset: 0 (0%), Referenced to phase 2:EBTL and 6:WBTL, Start of Green
 Natural Cycle: 80
 Control Type: Actuated-Coordinated

Lanes, Volumes, Timings 1: City Centre & Albert

Existing AM
07/22/2019

Maximum v/c Ratio: 0.58

Intersection Signal Delay: 5.4

Intersection LOS: A

Intersection Capacity Utilization 75.6%

ICU Level of Service D

Analysis Period (min) 15

Splits and Phases: 1: City Centre & Albert



Lanes, Volumes, Timings
1: City Centre & Albert

Existing PM
07/22/2019



| Lane Group | EBL | EBT | EBR | WBL | WBT | WBR | NBL | NBT | NBR | SBL | SBT | SBR |
|------------------------|-------|-------|-------|-------|-------|-------|-------|-------|-----|-------|-------|-------|
| Lane Configurations | | | | | | | | | | | | |
| Traffic Volume (vph) | 15 | 527 | 61 | 54 | 697 | 32 | 71 | 0 | 98 | 48 | 0 | 14 |
| Future Volume (vph) | 15 | 527 | 61 | 54 | 697 | 32 | 71 | 0 | 98 | 48 | 0 | 14 |
| Satd. Flow (prot) | 1658 | 1745 | 1483 | 1658 | 1745 | 1483 | 1658 | 1483 | 0 | 0 | 1628 | 0 |
| Flt Permitted | 0.266 | | | 0.443 | | | 0.756 | | | | 0.675 | |
| Satd. Flow (perm) | 464 | 1745 | 1483 | 773 | 1745 | 1483 | 1319 | 1483 | 0 | 0 | 1141 | 0 |
| Satd. Flow (RTOR) | | | 68 | | | 87 | | 337 | | | 87 | |
| Lane Group Flow (vph) | 17 | 586 | 68 | 60 | 774 | 36 | 79 | 109 | 0 | 0 | 69 | 0 |
| Turn Type | pm+pt | NA | Perm | Perm | NA | Perm | Perm | NA | | Perm | NA | |
| Protected Phases | 5 | 2 | | | 6 | | | 8 | | | | 4 |
| Permitted Phases | 2 | | 2 | 6 | | 6 | 8 | | | 4 | | |
| Detector Phase | 5 | 2 | 2 | 6 | 6 | 6 | 8 | 8 | | 4 | | 4 |
| Switch Phase | | | | | | | | | | | | |
| Minimum Initial (s) | 5.0 | 10.0 | 10.0 | 10.0 | 10.0 | 10.0 | 10.0 | 10.0 | | 10.0 | 10.0 | |
| Minimum Split (s) | 11.3 | 27.3 | 27.3 | 27.3 | 27.3 | 27.3 | 29.3 | 29.3 | | 29.3 | 29.3 | |
| Total Split (s) | 17.0 | 84.0 | 84.0 | 67.0 | 67.0 | 67.0 | 36.0 | 36.0 | | 36.0 | 36.0 | |
| Total Split (%) | 14.2% | 70.0% | 70.0% | 55.8% | 55.8% | 55.8% | 30.0% | 30.0% | | 30.0% | 30.0% | |
| Yellow Time (s) | 3.3 | 3.3 | 3.3 | 3.3 | 3.3 | 3.3 | 3.3 | 3.3 | | 3.3 | 3.3 | |
| All-Red Time (s) | 3.0 | 3.0 | 3.0 | 3.0 | 3.0 | 3.0 | 3.0 | 3.0 | | 3.0 | 3.0 | |
| Lost Time Adjust (s) | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | | 0.0 | 0.0 | |
| Total Lost Time (s) | 6.3 | 6.3 | 6.3 | 6.3 | 6.3 | 6.3 | 6.3 | 6.3 | | 6.3 | 6.3 | |
| Lead/Lag | Lead | | | Lag | Lag | Lag | | | | | | |
| Lead-Lag Optimize? | Yes | | | Yes | Yes | Yes | | | | | | |
| Recall Mode | None | C-Max | C-Max | C-Max | C-Max | C-Max | None | None | | None | None | |
| Act Effct Green (s) | 94.1 | 94.1 | 94.1 | 89.1 | 89.1 | 89.1 | 13.3 | 13.3 | | | | 13.3 |
| Actuated g/C Ratio | 0.78 | 0.78 | 0.78 | 0.74 | 0.74 | 0.74 | 0.11 | 0.11 | | | | 0.11 |
| v/c Ratio | 0.04 | 0.43 | 0.06 | 0.10 | 0.60 | 0.03 | 0.54 | 0.23 | | | | 0.34 |
| Control Delay | 3.7 | 5.7 | 1.0 | 6.9 | 11.5 | 0.1 | 63.5 | 1.2 | | | | 10.5 |
| Queue Delay | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | | | | 0.0 |
| Total Delay | 3.7 | 5.7 | 1.0 | 6.9 | 11.5 | 0.1 | 63.5 | 1.2 | | | | 10.5 |
| LOS | A | A | A | A | B | A | E | A | | | | B |
| Approach Delay | | 5.2 | | | 10.7 | | | 27.4 | | | | 10.5 |
| Approach LOS | | A | | | B | | | C | | | | B |
| Queue Length 50th (m) | 0.7 | 35.9 | 0.0 | 2.7 | 56.8 | 0.0 | 18.0 | 0.0 | | | | 0.0 |
| Queue Length 95th (m) | 2.7 | 65.7 | 3.3 | 11.0 | 156.2 | 0.0 | 32.3 | 0.0 | | | | 9.0 |
| Internal Link Dist (m) | | 330.0 | | | 569.4 | | | 245.5 | | | | 144.5 |
| Turn Bay Length (m) | 30.0 | | 50.0 | 40.0 | | 30.0 | 40.0 | | | | | |
| Base Capacity (vph) | 470 | 1368 | 1177 | 574 | 1295 | 1123 | 326 | 620 | | | | 347 |
| Starvation Cap Reductn | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | | | | 0 |
| Spillback Cap Reductn | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | | | | 0 |
| Storage Cap Reductn | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | | | | 0 |
| Reduced v/c Ratio | 0.04 | 0.43 | 0.06 | 0.10 | 0.60 | 0.03 | 0.24 | 0.18 | | | | 0.20 |

Intersection Summary

Cycle Length: 120
 Actuated Cycle Length: 120
 Offset: 0 (0%), Referenced to phase 2:EBTL and 6:WBTL, Start of Green
 Natural Cycle: 90
 Control Type: Actuated-Coordinated

Lanes, Volumes, Timings
 1: City Centre & Albert

Existing PM
 07/22/2019

Maximum v/c Ratio: 0.60

Intersection Signal Delay: 10.4

Intersection LOS: B

Intersection Capacity Utilization 68.2%

ICU Level of Service C

Analysis Period (min) 15

Splits and Phases: 1: City Centre & Albert



Appendix E

Collision Data

DRAFT



City Operations - Transportation Services

Collision Details Report - Public Version

From: January 1, 2013 **To:** December 31, 2017

Location: CHAMPAGNE AVE @ WELLINGTON ST

Traffic Control: Stop sign

Total Collisions: 5

| Date/Day/Time | Environment | Impact Type | Classification | Surface Cond'n | Veh. Dir | Vehicle Manoeuvre | Vehicle type | First Event | No. Ped |
|-------------------------|-------------|------------------|------------------|----------------|----------|-------------------|---------------------------|---------------------|---------|
| 2014-Apr-25, Fri, 12:55 | Clear | Angle | P.D. only | Dry | North | Turning left | Automobile, station wagon | Other motor vehicle | |
| | | | | | East | Going ahead | Automobile, station wagon | Other motor vehicle | |
| 2014-Aug-27, Wed, 15:37 | Clear | Rear end | P.D. only | Dry | North | Turning right | Automobile, station wagon | Other motor vehicle | |
| | | | | | North | Turning right | Pick-up truck | Other motor vehicle | |
| 2016-Jul-09, Sat, 20:30 | Rain | Sideswipe | P.D. only | Wet | West | Changing lanes | Automobile, station wagon | Other motor vehicle | |
| | | | | | West | Turning left | Automobile, station wagon | Other motor vehicle | |
| 2017-Apr-26, Wed, 16:36 | Clear | Turning movement | Non-fatal injury | Dry | West | Turning left | Pick-up truck | Other motor vehicle | |
| | | | | | East | Going ahead | Automobile, station wagon | Other motor vehicle | |
| 2013-Oct-16, Wed, 10:30 | Clear | Angle | P.D. only | Dry | North | Turning left | Automobile, station wagon | Other motor vehicle | |
| | | | | | East | Going ahead | Automobile, station wagon | Other motor vehicle | |

Location: CITY CENTRE AVE btwn ELM ST & SPRUCE ST

Traffic Control: No control

Total Collisions: 1

| Date/Day/Time | Environment | Impact Type | Classification | Surface Cond'n | Veh. Dir | Vehicle Manoeuver | Vehicle type | First Event | No. Ped |
|------------------------|-------------|-------------|----------------|----------------|----------|-------------------|---------------------------|---------------------|---------|
| 2013-Aug-27, Tue,15:30 | Clear | Angle | P.D. only | Dry | East | Turning left | Automobile, station wagon | Other motor vehicle | |
| | | | | | South | Going ahead | Automobile, station wagon | Other motor vehicle | |

Location: CITY CENTRE AVE btwn SPRUCE ST & END

Traffic Control: No control

Total Collisions: 1

| Date/Day/Time | Environment | Impact Type | Classification | Surface Cond'n | Veh. Dir | Vehicle Manoeuver | Vehicle type | First Event | No. Ped |
|------------------------|-------------|------------------------|----------------|----------------|----------|-------------------|-------------------|--------------------|---------|
| 2017-Feb-22, Wed,09:30 | Clear | SMV unattended vehicle | P.D. only | Wet | South | Turning right | Truck and trailer | Unattended vehicle | |

Appendix F

Background Traffic Growth Analysis

DRAFT

| Time Period | Percent Annual Change | | | | |
|--------------------|------------------------------|------------------|-----------------|-----------------|----------------|
| | North Leg | South Leg | East Leg | West Leg | Overall |
| 8 hrs | -5.27% | -8.92% | -9.20% | -0.09% | -5.30% |
| AM Peak | -3.72% | -6.47% | -3.24% | 3.37% | -2.20% |
| PM Peak | -9.47% | -10.91% | -11.59% | -4.83% | -8.95% |

**Road/Road
8 hrs**

| Year | Date | North Leg | | South Leg | | East Leg | | West Leg | | Total |
|------|----------------|-----------|------|-----------|------|----------|------|----------|------|-------|
| | | SB | NB | NB | SB | WB | EB | EB | WB | |
| 2009 | Tuesday Aug 11 | 4644 | 6831 | 4419 | 3546 | 4274 | 3396 | 3553 | 3117 | 33780 |
| 2013 | Thursday May 9 | 4213 | 5464 | 3575 | 2618 | 2846 | 3105 | 5350 | 3791 | 30962 |
| 2014 | Friday Aug 29 | 3435 | 5109 | 2462 | 2171 | 2508 | 1851 | 3057 | 2331 | 22924 |
| | | | | | | | | | | |

| Year | Counts | | | | % Change | | | |
|------|--------|------|-------|-------|----------|--------|--------|--------|
| | NB | SB | NB+SB | INT | NB | SB | NB+SB | INT |
| 2009 | 6831 | 4644 | 11475 | 33780 | | | | |
| 2013 | 5464 | 4213 | 9677 | 30962 | -20.0% | -9.3% | -15.7% | -8.3% |
| 2014 | 5109 | 3435 | 8544 | 22924 | -6.5% | -18.5% | -11.7% | -26.0% |

Regression Estimate 2009 6832 4708 11540
 Regression Estimate 2014 5114 3690 8804
Average Annual Change -5.63% -4.75% -5.27%

| Year | Counts | | | | % Change | | | |
|------|--------|------|-------|-------|----------|--------|--------|--------|
| | EB | WB | EB+WB | INT | EB | WB | EB+WB | INT |
| 2009 | 3553 | 3117 | 6670 | 33780 | | | | |
| 2013 | 5350 | 3791 | 9141 | 30962 | 50.6% | 21.6% | 37.0% | -8.3% |
| 2014 | 3057 | 2331 | 5388 | 22924 | -42.9% | -38.5% | -41.1% | -26.0% |

Regression Estimate 2009 3814 3272 7086
 Regression Estimate 2014 4102 2951 7053
Average Annual Change 1.46% -2.04% -0.09%

| Year | Counts | | | | % Change | | | |
|------|--------|------|-------|-------|----------|--------|--------|--------|
| | EB | WB | EB+WB | INT | EB | WB | EB+WB | INT |
| 2009 | 3396 | 4274 | 7670 | 33780 | | | | |
| 2013 | 3105 | 2846 | 5951 | 30962 | -8.6% | -33.4% | -22.4% | -8.3% |
| 2014 | 1851 | 2508 | 4359 | 22924 | -40.4% | -11.9% | -26.8% | -26.0% |

Regression Estimate 2009 3509 4272 7781
 Regression Estimate 2014 2301 2501 4802
Average Annual Change -8.09% -10.16% -9.20%

| Year | Counts | | | | % Change | | | |
|------|--------|------|-------|-------|----------|--------|--------|--------|
| | NB | SB | NB+SB | INT | NB | SB | NB+SB | INT |
| 2009 | 4419 | 3546 | 7965 | 33780 | | | | |
| 2013 | 3575 | 2618 | 6193 | 30962 | -19.1% | -26.2% | -22.2% | -8.3% |
| 2014 | 2462 | 2171 | 4633 | 22924 | -31.1% | -17.1% | -25.2% | -26.0% |

Regression Estimate 2009 4505 3566 8071
 Regression Estimate 2014 2806 2253 5059
Average Annual Change -9.04% -8.78% -8.92%

**Road/Road
AM Peak**

| Year | Date | North Leg | | South Leg | | East Leg | | West Leg | | Total |
|------|----------------|-----------|-----|-----------|-----|----------|------|----------|-----|-------|
| | | SB | NB | NB | SB | WB | EB | EB | WB | |
| 2009 | Tuesday Aug 11 | 1013 | 796 | 558 | 625 | 357 | 667 | 566 | 406 | 4988 |
| 2013 | Thursday May 9 | 928 | 768 | 534 | 497 | 262 | 1042 | 1109 | 526 | 5666 |
| 2014 | Friday Aug 29 | 745 | 678 | 371 | 409 | 222 | 430 | 543 | 364 | 3762 |
| | | | | | | | | | | |

| Year | Counts | | | | % Change | | | |
|------|--------|------|-------|------|----------|--------|--------|--------|
| | NB | SB | NB+SB | INT | NB | SB | NB+SB | INT |
| 2009 | 796 | 1013 | 1809 | 4988 | | | | |
| 2013 | 768 | 928 | 1696 | 5666 | -3.5% | -8.4% | -6.2% | 13.6% |
| 2014 | 678 | 745 | 1423 | 3762 | -11.7% | -19.7% | -16.1% | -33.6% |

Regression Estimate 2009 804 1028 1832
 Regression Estimate 2014 710 807 1516
Average Annual Change -2.46% -4.74% -3.72%

| Year | Counts | | | | % Change | | | |
|------|--------|-----|-------|------|----------|--------|--------|--------|
| | EB | WB | EB+WB | INT | EB | WB | EB+WB | INT |
| 2009 | 566 | 406 | 972 | 4988 | | | | |
| 2013 | 1109 | 526 | 1635 | 5666 | 95.9% | 29.6% | 68.2% | 13.6% |
| 2014 | 543 | 364 | 907 | 3762 | -51.0% | -30.8% | -44.5% | -33.6% |

Regression Estimate 2009 633 424 1057
 Regression Estimate 2014 810 437 1247
Average Annual Change 5.07% 0.60% 3.37%

| Year | Counts | | | | % Change | | | |
|------|--------|-----|-------|------|----------|--------|--------|--------|
| | EB | WB | EB+WB | INT | EB | WB | EB+WB | INT |
| 2009 | 667 | 357 | 1024 | 4988 | | | | |
| 2013 | 1042 | 262 | 1304 | 5666 | 56.2% | -26.6% | 27.3% | 13.6% |
| 2014 | 430 | 222 | 652 | 3762 | -58.7% | -15.3% | -50.0% | -33.6% |

Regression Estimate 2009 734 359 1093
 Regression Estimate 2014 699 228 927
Average Annual Change -0.98% -8.64% -3.24%

| Year | Counts | | | | % Change | | | |
|------|--------|-----|-------|------|----------|--------|--------|--------|
| | NB | SB | NB+SB | INT | NB | SB | NB+SB | INT |
| 2009 | 558 | 625 | 1183 | 4988 | | | | |
| 2013 | 534 | 497 | 1031 | 5666 | -4.3% | -20.5% | -12.8% | 13.6% |
| 2014 | 371 | 409 | 780 | 3762 | -30.5% | -17.7% | -24.3% | -33.6% |

Regression Estimate 2009 573 630 1203
 Regression Estimate 2014 431 430 861
Average Annual Change -5.54% -7.35% -6.47%

**Road/Road
PM Peak**

| Year | Date | North Leg | | South Leg | | East Leg | | West Leg | | Total |
|------|----------------|-----------|------|-----------|-----|----------|-----|----------|-----|-------|
| | | SB | NB | NB | SB | WB | EB | EB | WB | |
| 2009 | Tuesday Aug 11 | 593 | 1190 | 647 | 496 | 965 | 432 | 533 | 620 | 5476 |
| 2013 | Thursday May 9 | 390 | 874 | 578 | 321 | 572 | 408 | 662 | 599 | 4404 |
| 2014 | Friday Aug 29 | 403 | 657 | 240 | 306 | 480 | 215 | 392 | 337 | 3030 |
| | | | | | | | | | | |

| Year | Counts | | | | % Change | | | |
|------|--------|-----|-------|------|----------|--------|--------|--------|
| | NB | SB | NB+SB | INT | NB | SB | NB+SB | INT |
| 2009 | 1190 | 593 | 1783 | 5476 | | | | |
| 2013 | 874 | 390 | 1264 | 4404 | -26.6% | -34.2% | -29.1% | -19.6% |
| 2014 | 657 | 403 | 1060 | 3030 | -24.8% | 3.3% | -16.1% | -31.2% |

Regression Estimate 2009 1203 587 1790
 Regression Estimate 2014 710 379 1088
Average Annual Change -10.02% -8.39% -9.47%

| Year | Counts | | | | % Change | | | |
|------|--------|-----|-------|------|----------|--------|--------|--------|
| | EB | WB | EB+WB | INT | EB | WB | EB+WB | INT |
| 2009 | 533 | 620 | 1153 | 5476 | | | | |
| 2013 | 662 | 599 | 1261 | 4404 | 24.2% | -3.4% | 9.4% | -19.6% |
| 2014 | 392 | 337 | 729 | 3030 | -40.8% | -43.7% | -42.2% | -31.2% |

Regression Estimate 2009 562 644 1206
 Regression Estimate 2014 507 435 942
Average Annual Change -2.03% -7.57% -4.83%

| Year | Counts | | | | % Change | | | |
|------|--------|-----|-------|------|----------|--------|--------|--------|
| | EB | WB | EB+WB | INT | EB | WB | EB+WB | INT |
| 2009 | 432 | 965 | 1397 | 5476 | | | | |
| 2013 | 408 | 572 | 980 | 4404 | -5.6% | -40.7% | -29.8% | -19.6% |
| 2014 | 215 | 480 | 695 | 3030 | -47.3% | -16.1% | -29.1% | -31.2% |

Regression Estimate 2009 450 964 1414
 Regression Estimate 2014 286 478 764
Average Annual Change -8.64% -13.11% -11.59%

| Year | Counts | | | | % Change | | | |
|------|--------|-----|-------|------|----------|--------|--------|--------|
| | NB | SB | NB+SB | INT | NB | SB | NB+SB | INT |
| 2009 | 647 | 496 | 1143 | 5476 | | | | |
| 2013 | 578 | 321 | 899 | 4404 | -10.7% | -35.3% | -21.3% | -19.6% |
| 2014 | 240 | 306 | 546 | 3030 | -58.5% | -4.7% | -39.3% | -31.2% |

Regression Estimate 2009 678 493 1171
 Regression Estimate 2014 362 295 657
Average Annual Change -11.77% -9.77% -10.91%

Appendix G

Multimodal Level of Service Analysis: Segments

DRAFT

Multi-Modal Level of Service - Segments Form

| | |
|------------|----------------|
| Consultant | Parsons |
| Scenario | |
| Comments | |

| | |
|--------------|---------------------|
| Project Date | 989 Somerset |
| | |
| | |

| SEGMENTS | Street A | City Centre | Somerset | Spruce | Section | Section | Section | Section | Section | Section |
|-------------------------|---|---------------------|------------------------------|---------------------|----------|---------|---------|---------|---------|---------|
| | | 1 | 2 | 3 | 4 | 5 | 6 | 7 | 8 | 9 |
| Pedestrian | Sidewalk Width | no sidewalk | ≥ 2 m | ≥ 2 m | | | | | | |
| | Boulevard Width | n/a | 0.5 - 2 m | < 0.5 | | | | | | |
| | Avg Daily Curb Lane Traffic Volume | ≤ 3000 | > 3000 | ≤ 3000 | | | | | | |
| | Operating Speed | > 30 to 50 km/h | > 30 to 50 km/h | > 30 to 50 km/h | | | | | | |
| | On-Street Parking | yes | yes | yes | | | | | | |
| | Exposure to Traffic PLoS | - | F | B | B | - | - | - | - | - |
| | Effective Sidewalk Width | | | | | | | | | |
| | Pedestrian Volume | | | | | | | | | |
| Crowding PLoS | | - | - | - | - | - | - | - | - | |
| Level of Service | | - | - | - | - | - | - | - | - | |
| Bicycle | Type of Cycling Facility | Mixed Traffic | Parking beside Bike Lane | Mixed Traffic | | | | | | |
| | Number of Travel Lanes | ≤ 2 (no centreline) | 1 each direction | ≤ 2 (no centreline) | | | | | | |
| | Operating Speed | ≤ 40 km/h | >40 to 50 km/h | ≤ 40 km/h | | | | | | |
| | # of Lanes & Operating Speed LoS | A | B | A | - | - | - | - | - | |
| | Bike Lane (+ Parking Lane) Width | | ≤ 4 m biking + parking width | | | | | | | |
| | Bike Lane Width LoS | - | C | - | - | - | - | - | - | |
| | Bike Lane Blockages | | Rare | | | | | | | |
| | Blockage LoS | - | A | - | - | - | - | - | - | |
| | Median Refuge Width (no median = < 1.8 m) | < 1.8 m refuge | < 1.8 m refuge | < 1.8 m refuge | | | | | | |
| | No. of Lanes at Unsignalized Crossing | ≤ 3 lanes | ≤ 3 lanes | ≤ 3 lanes | | | | | | |
| | Sidestreet Operating Speed | ≤ 40 km/h | >40 to 50 km/h | ≤ 40 km/h | | | | | | |
| | Unsignalized Crossing - Lowest LoS | A | A | A | - | - | - | - | - | |
| Level of Service | | A | C | A | - | - | - | - | | |
| Transit | Facility Type | | Mixed Traffic | | | | | | | |
| | Friction or Ratio Transit:Posted Speed | | Vt/Vp ≥ 0.8 | | | | | | | |
| | Level of Service | - | D | - | - | - | - | - | | |
| Truck | Truck Lane Width | | ≤ 3.5 m | | | | | | | |
| | Travel Lanes per Direction | | 1 | | | | | | | |
| | Level of Service | - | C | - | - | - | - | - | | |

Appendix H

TDM Checklist

DRAFT

TDM-Supportive Development Design and Infrastructure Checklist:
Residential Developments (multi-family or condominium)

| Legend | |
|-----------------|--|
| REQUIRED | The Official Plan or Zoning By-law provides related guidance that must be followed |
| BASIC | The measure is generally feasible and effective, and in most cases would benefit the development and its users |
| BETTER | The measure could maximize support for users of sustainable modes, and optimize development performance |

| TDM-supportive design & infrastructure measures: <i>Residential developments</i> | | Check if completed & add descriptions, explanations or plan/drawing references |
|---|---|--|
| 1. WALKING & CYCLING: ROUTES | | |
| 1.1 Building location & access points | | |
| BASIC | 1.1.1 Locate building close to the street, and do not locate parking areas between the street and building entrances | <input checked="" type="checkbox"/> |
| BASIC | 1.1.2 Locate building entrances in order to minimize walking distances to sidewalks and transit stops/stations | <input checked="" type="checkbox"/> |
| BASIC | 1.1.3 Locate building doors and windows to ensure visibility of pedestrians from the building, for their security and comfort | <input checked="" type="checkbox"/> |
| 1.2 Facilities for walking & cycling | | |
| REQUIRED | 1.2.1 Provide convenient, direct access to stations or major stops along rapid transit routes within 600 metres; minimize walking distances from buildings to rapid transit; provide pedestrian-friendly, weather-protected (where possible) environment between rapid transit accesses and building entrances; ensure quality linkages from sidewalks through building entrances to integrated stops/stations <i>(see Official Plan policy 4.3.3)</i> | <input checked="" type="checkbox"/> |
| REQUIRED | 1.2.2 Provide safe, direct and attractive pedestrian access from public sidewalks to building entrances through such measures as: reducing distances between public sidewalks and major building entrances; providing walkways from public streets to major building entrances; within a site, providing walkways along the front of adjoining buildings, between adjacent buildings, and connecting areas where people may congregate, such as courtyards and transit stops; and providing weather protection through canopies, colonnades, and other design elements wherever possible <i>(see Official Plan policy 4.3.12)</i> | <input checked="" type="checkbox"/> |

| TDM-supportive design & infrastructure measures: <i>Residential developments</i> | | Check if completed & add descriptions, explanations or plan/drawing references |
|--|--|---|
| REQUIRED | 1.2.3 Provide sidewalks of smooth, well-drained walking surfaces of contrasting materials or treatments to differentiate pedestrian areas from vehicle areas, and provide marked pedestrian crosswalks at intersection sidewalks (<i>see Official Plan policy 4.3.10</i>) | <input checked="" type="checkbox"/> |
| REQUIRED | 1.2.4 Make sidewalks and open space areas easily accessible through features such as gradual grade transition, depressed curbs at street corners and convenient access to extra-wide parking spaces and ramps (<i>see Official Plan policy 4.3.10</i>) | <input checked="" type="checkbox"/> |
| REQUIRED | 1.2.5 Include adequately spaced inter-block/street cycling and pedestrian connections to facilitate travel by active transportation. Provide links to the existing or planned network of public sidewalks, multi-use pathways and on-road cycle routes. Where public sidewalks and multi-use pathways intersect with roads, consider providing traffic control devices to give priority to cyclists and pedestrians (<i>see Official Plan policy 4.3.11</i>) | <input checked="" type="checkbox"/> |
| BASIC | 1.2.6 Provide safe, direct and attractive walking routes from building entrances to nearby transit stops | <input checked="" type="checkbox"/> |
| BASIC | 1.2.7 Ensure that walking routes to transit stops are secure, visible, lighted, shaded and wind-protected wherever possible | <input checked="" type="checkbox"/> |
| BASIC | 1.2.8 Design roads used for access or circulation by cyclists using a target operating speed of no more than 30 km/h, or provide a separated cycling facility | <input checked="" type="checkbox"/> |
| 1.3 Amenities for walking & cycling | | |
| BASIC | 1.3.1 Provide lighting, landscaping and benches along walking and cycling routes between building entrances and streets, sidewalks and trails | <input checked="" type="checkbox"/> |
| BASIC | 1.3.2 Provide wayfinding signage for site access (where required, e.g. when multiple buildings or entrances exist) and egress (where warranted, such as when directions to reach transit stops/stations, trails or other common destinations are not obvious) | <input type="checkbox"/> |

| TDM-supportive design & infrastructure measures: <i>Residential developments</i> | | Check if completed & add descriptions, explanations or plan/drawing references |
|---|--|--|
| 2. WALKING & CYCLING: END-OF-TRIP FACILITIES | | |
| 2.1 Bicycle parking | | |
| REQUIRED | 2.1.1 Provide bicycle parking in highly visible and lighted areas, sheltered from the weather wherever possible (see <i>Official Plan policy 4.3.6</i>) | <input checked="" type="checkbox"/> |
| REQUIRED | 2.1.2 Provide the number of bicycle parking spaces specified for various land uses in different parts of Ottawa; provide convenient access to main entrances or well-used areas (see <i>Zoning By-law Section 111</i>) | <input checked="" type="checkbox"/> |
| REQUIRED | 2.1.3 Ensure that bicycle parking spaces and access aisles meet minimum dimensions; that no more than 50% of spaces are vertical spaces; and that parking racks are securely anchored (see <i>Zoning By-law Section 111</i>) | <input checked="" type="checkbox"/> |
| BASIC | 2.1.4 Provide bicycle parking spaces equivalent to the expected number of resident-owned bicycles, plus the expected peak number of visitor cyclists | <input type="checkbox"/> |
| 2.2 Secure bicycle parking | | |
| REQUIRED | 2.2.1 Where more than 50 bicycle parking spaces are provided for a single residential building, locate at least 25% of spaces within a building/structure, a secure area (e.g. supervised parking lot or enclosure) or bicycle lockers (see <i>Zoning By-law Section 111</i>) | <input checked="" type="checkbox"/> |
| BETTER | 2.2.2 Provide secure bicycle parking spaces equivalent to at least the number of units at condominiums or multi-family residential developments | <input type="checkbox"/> |
| 2.3 Bicycle repair station | | |
| BETTER | 2.3.1 Provide a permanent bike repair station, with commonly used tools and an air pump, adjacent to the main bicycle parking area (or secure bicycle parking area, if provided) | <input type="checkbox"/> |
| 3. TRANSIT | | |
| 3.1 Customer amenities | | |
| BASIC | 3.1.1 Provide shelters, lighting and benches at any on-site transit stops | <input type="checkbox"/> |
| BASIC | 3.1.2 Where the site abuts an off-site transit stop and insufficient space exists for a transit shelter in the public right-of-way, protect land for a shelter and/or install a shelter | <input type="checkbox"/> |
| BETTER | 3.1.3 Provide a secure and comfortable interior waiting area by integrating any on-site transit stops into the building | <input type="checkbox"/> |

| TDM-supportive design & infrastructure measures: <i>Residential developments</i> | | Check if completed & add descriptions, explanations or plan/drawing references |
|---|---|--|
| 4. RIDESHARING | | |
| 4.1 Pick-up & drop-off facilities | | |
| BASIC | 4.1.1 Provide a designated area for carpool drivers (plus taxis and ride-hailing services) to drop off or pick up passengers without using fire lanes or other no-stopping zones | <input type="checkbox"/> |
| 5. CARSHARING & BIKESHARING | | |
| 5.1 Carshare parking spaces | | |
| BETTER | 5.1.1 Provide up to three carshare parking spaces in an R3, R4 or R5 Zone for specified residential uses (<i>see Zoning By-law Section 94</i>) | <input type="checkbox"/> |
| 5.2 Bikeshare station location | | |
| BETTER | 5.2.1 Provide a designated bikeshare station area near a major building entrance, preferably lighted and sheltered with a direct walkway connection | <input type="checkbox"/> |
| 6. PARKING | | |
| 6.1 Number of parking spaces | | |
| REQUIRED | 6.1.1 Do not provide more parking than permitted by zoning, nor less than required by zoning, unless a variance is being applied for | <input checked="" type="checkbox"/> |
| BASIC | 6.1.2 Provide parking for long-term and short-term users that is consistent with mode share targets, considering the potential for visitors to use off-site public parking | <input checked="" type="checkbox"/> |
| BASIC | 6.1.3 Where a site features more than one use, provide shared parking and reduce the cumulative number of parking spaces accordingly (<i>see Zoning By-law Section 104</i>) | <input type="checkbox"/> |
| BETTER | 6.1.4 Reduce the minimum number of parking spaces required by zoning by one space for each 13 square metres of gross floor area provided as shower rooms, change rooms, locker rooms and other facilities for cyclists in conjunction with bicycle parking (<i>see Zoning By-law Section 111</i>) | <input type="checkbox"/> |
| 6.2 Separate long-term & short-term parking areas | | |
| BETTER | 6.2.1 Provide separate areas for short-term and long-term parking (using signage or physical barriers) to permit access controls and simplify enforcement (i.e. to discourage residents from parking in visitor spaces, and vice versa) | <input type="checkbox"/> |

Appendix I

Multimodal Level of Service Analysis: Intersections

DRAFT

Multi-Modal Level of Service - Intersections Form

Consultant
Scenario
Comments

| |
|-----------------------|
| Parsons |
| Projected 2025 |
| |
| |

Project
Date

| |
|-------------------------|
| 989 Somerset TIS |
| 4/16/2019 |
| |
| |

| INTERSECTIONS | | Albert / City Centre | | | | |
|-----------------------------|--|--------------------------------------|--------------------------------------|--------------------------------------|--------------------------------------|-----------|
| Crossing Side | | NORTH | SOUTH | EAST | WEST | |
| Pedestrian | Lanes | | 3 | 5 | 4 | |
| | Median | | No Median - 2.4 m | No Median - 2.4 m | No Median - 2.4 m | |
| | Conflicting Left Turns | | Protected/ Permissive | No left turn / Prohib. | Permissive | |
| | Conflicting Right Turns | | Permissive or yield control | Permissive or yield control | No right turn | |
| | Right Turns on Red (RTor) ? | | RTOR allowed | RTOR prohibited | RTOR allowed | |
| | Ped Signal Leading Interval? | | No | Yes | Yes | |
| | Right Turn Channel | | No Channel | No Channel | No Channel | |
| | Corner Radius | | 5-10m | 10-15m | 0-3m | |
| | Crosswalk Type | | Raised crosswalk | Zebra stripe hi-vis markings | Zebra stripe hi-vis markings | |
| | PETSI Score | | 78 | 53 | 66 | |
| | Ped. Exposure to Traffic LoS | | - | B | D | C |
| | Cycle Length | | | 120 | 120 | 120 |
| | Effective Walk Time | | | 39 | 25 | 25 |
| | Average Pedestrian Delay | | | 27 | 38 | 38 |
| Pedestrian Delay LoS | | - | C | D | D | |
| Level of Service | | - | C | D | D | |
| | | D | | | | |
| Approach From | | NORTH | SOUTH | EAST | WEST | |
| Bicycle | Bicycle Lane Arrangement on Approach | Curb Bike Lane, Cycletrack or MUP | Curb Bike Lane, Cycletrack or MUP | Curb Bike Lane, Cycletrack or MUP | Curb Bike Lane, Cycletrack or MUP | |
| | Right Turn Lane Configuration | Not Applicable | Not Applicable | Not Applicable | Not Applicable | |
| | Right Turning Speed | Not Applicable | Not Applicable | Not Applicable | Not Applicable | |
| | Cyclist relative to RT motorists | Not Applicable | Not Applicable | Not Applicable | Not Applicable | |
| | Separated or Mixed Traffic | Separated | Separated | Separated | Separated | |
| | Left Turn Approach | 2-stage, LT box | 2-stage, LT box | 2-stage, LT box | 2-stage, LT box | |
| | Operating Speed | ≥ 60 km/h | ≥ 60 km/h | ≥ 60 km/h | ≥ 60 km/h | |
| | Left Turning Cyclist | A | A | A | A | |
| | Level of Service | A | A | A | A | |
| | | A | | | | |
| Transit | Average Signal Delay | | ≤ 30 sec | ≤ 30 sec | ≤ 30 sec | |
| | Level of Service | - | D | D | D | |
| | | D | | | | |
| Truck | Effective Corner Radius | | 10 - 15 m | | < 10 m | |
| | Number of Receiving Lanes on Departure from Intersection | | ≥ 2 | | 1 | |
| | Level of Service | - | B | - | F | |
| | | F | | | | |
| Auto | Volume to Capacity Ratio | | 0.71 - 0.80 | | | |
| | Level of Service | | C | | | |