





# 1400 UPPER CANADA STREET





**IBI GROUP**  
400 – 333 Preston Street  
Ottawa ON K1S 5N4 Canada  
tel 613 225 1311 fax 613 225 9868  
ibigroup.com



Sheet Number	Sheet Title	Sheet Description
C-000	COVER	
C-001	SITE SERVICING PLAN	
C-010	GENERAL NOTES, LEGEND AND CB DATA TABLE	
C-200	SITE GRADING PLAN	
C-201	EXISTING CONDITIONS	
C-400	SANITARY DRAINAGE AREA PLAN	
C-500	STORM DRAINAGE AREA PLAN	
C-600	PONDING PLAN	
C-900	EROSION AND SEDIMENTATION CONTROL PLAN	




CONTRACT NO. 123987



No.	REVISIONS	By	Date
14			
13			
12			
11			
10			
9			
8			
7			
6			
5			
4			
3	REVISED AS PER CITY COMMENTS	T.R.B.	2020-12-18
2	ISSUED FOR 30% REVIEW	T.R.B.	2020-11-13
1	ISSUED FOR SPA	T.R.B.	2020-09-17



**IBI GROUP**  
 400 - 333 Preston Street  
 Ottawa ON K1S 5N4 Canada  
 tel 613 225 1311 fax 613 225 9888  
 ibigroup.com



Project Title		<b>Purolator</b>	
Drawing Title		<b>SITE SERVICING PLAN</b>	
Scale		1:500	
Design	J.B.	Date	AUG. 2020
Drawn	J.B./D.P.S.	Checked	T.R.B.
Project No.	123987	Drawing No.	C-001

STRUCTURE ID	AREA ID	STRUCTURE	COVER	ELEVATION		OUTLET PIPE		HEAD	FLOW	ICD TYPE
				TOP OF GRATE	INVERT	DIAMETER (mm)	TYPE			
				INLET	OUTLET					
<b>CICB25</b>	CICB25	OPSD 705.010	S22 & S23	<b>105.05</b>	103.550	200	PVC DR-35	1.85	40.0	Tempest HF
<b>CICB21</b>	CICB21	OPSD 705.010	S22 & S23	<b>105.05</b>	103.550	200	PVC DR-35	1.85	50.0	Tempest HF
<b>CICB19</b>	CICB19	OPSD 705.010	S22 & S23	<b>105.05</b>	103.550	200	PVC DR-35	1.85	20.0	Tempest HF
<b>CICB15</b>	CICB 14 15	OPSD 705.010	S22 & S23	<b>105.00</b>	103.410	200	PVC DR-35	1.90	6.0	Tempest Vortex
<b>CICB14</b>	CICB 14 15	OPSD 705.010	S22 & S23	<b>105.00</b>	103.500	200	PVC DR-35			
<b>CICB16</b>	CICB16	OPSD 705.010	S22 & S23	<b>105.00</b>	103.500	200	PVC DR-35	1.85	6.0	Tempest Vortex
<b>CICB17</b>	CICB17	OPSD 705.010	S22 & S23	<b>105.00</b>	103.500	200	PVC DR-35	1.85	6.0	Tempest Vortex
<b>CB12</b>	CB12	OPSD 705.010	S19	<b>104.80</b>	103.300	200	PVC DR-35	1.90	20.0	Tempest HF
<b>CB10</b>	CB10	OPSD 705.010	S19	<b>104.75</b>	103.250	200	PVC DR-35	1.90	20.0	Tempest HF
<b>CB11</b>	CB11	OPSD 705.010	S19	<b>104.70</b>	103.200	200	PVC DR-35	2.00	33.0	Tempest HF
<b>CICB18</b>	CICB18	OPSD 705.010	S22 & S23	<b>104.65</b>	103.150	200	PVC DR-35			
<b>CICB24</b>	CICB24	OPSD 705.010	S22 & S23	<b>104.65</b>	103.150	200	PVC DR-35	1.80	6.0	Tempest Vortex
<b>CICB23</b>	CICB23	OPSD 705.010	S22 & S23	<b>104.65</b>	103.150	200	PVC DR-35	1.80	6.0	Tempest Vortex
<b>CB3</b>	CB3	OPSD 705.010	S19	<b>104.55</b>	103.050	200	PVC DR-35	1.80	65.0	Tempest HF
<b>CICB20</b>	CICB20	OPSD 705.010	S22 & S23	<b>104.40</b>	102.900	200	PVC DR-35			
<b>CB8</b>	CB8	OPSD 705.010	S19	<b>104.40</b>	102.900	200	PVC DR-35	1.85	105.0	Tempest HF
<b>CICB22</b>	CICB22	OPSD 705.010	S22 & S23	<b>104.40</b>	102.900	200	PVC DR-35			
<b>CICB6</b>	CICB 6 7	OPSD 705.010	S22 & S23	<b>104.38</b>	102.880	200	PVC DR-35			
<b>CICB7</b>	CICB 6 7	OPSD 705.010	S22 & S23	<b>104.38</b>	102.880	200	PVC DR-35			
<b>CB26</b>	L1	OPSD 705.010	S19	<b>103.70</b>	102.700	200	PVC DR-35	2.15	6.0	Tempest Vortex
<b>D11</b>	L3	OPSD 705.010	S19	<b>103.45</b>	101.950	200	PVC DR-35	2.70	6.0	Tempest Vortex
<b>D12</b>	L2	OPSD 705.010	S19	<b>103.00</b>	101.500	200	PVC DR-35			
<b>MH8</b>	L2	OPSD701.010	Closed	<b>104.71</b>	101.657	525	CONC 100D	3.52	36.0	Tempest HF

Bold font indicates CB's with ICD's  
 Revision: 2020-12-18

NAME	RIM ELEV.	INVERT IN	INVERT AS-BUILT	INVERT OUT	INVERT OUT AS-BUILT	DESCRIPTION
MH1	104.58	NW101.347 SW101.332		SE101.272		1200mm <sup>Ø</sup> OPSD-701.010
MH2	104.71	SW101.767 NW103.126		NE101.617		1200mm <sup>Ø</sup> OPSD-701.010
MH3	105.13	NW103.043		S103.168 SE103.250		1200mm <sup>Ø</sup> OPSD-701.010
MH4	104.86	SW101.952 NW102.885		NE101.892		1200mm <sup>Ø</sup> OPSD-701.010
MH5	105.24	NW102.223		NE102.148		1200mm <sup>Ø</sup> OPSD-701.010
MH6	104.98			NE102.212		1200mm <sup>Ø</sup> OPSD-701.010
MH7	104.67	SW101.989		NE101.803		1200mm <sup>Ø</sup> OPSD-701.010
MH8	104.71	SW101.657		SE101.657		1200mm <sup>Ø</sup> OPSD-701.010
MH9	104.82	NW101.503		SE101.503		1200mm <sup>Ø</sup> OPSD-701.010
MH10	105.28			SE102.402		1200mm <sup>Ø</sup> OPSD-701.010
MH11	105.08	NW101.579		SE101.579		1200mm <sup>Ø</sup> OPSD-701.010
STM BLKHD	104.38	NW101.171				675mm <sup>Ø</sup> BULKHEAD


Station	Description	Finished Grade	Top of Watermain	Watermain Cover	As Built Watermain
A	0+00.00 REMOVE EXISTING CAP AND CONNECT	104.59	104.46	102.00	2.39
	0+03.00 45 BEND	104.59	104.46	102.06	2.40
	0+06.00 45 BEND	104.59	104.50	102.10	2.40
	0+09.00 45 BEND	104.59	104.77	102.37	2.40
	0+09.75 45 BEND	104.59	105.09	102.69	2.40
	0+07.39 45 BEND	105.27	102.87	102.87	2.40
	0+08.51 45 BEND	105.33	102.93	102.93	2.40
	0+08.24 45 BEND	105.45	103.05	103.05	2.40
B	0+089.70 150mm SERVICE CONNECTION	105.50	103.10	103.10	2.40

NAME	RIM ELEV.	INVERT IN	INVERT AS-BUILT	INVERT OUT	INVERT OUT AS-BUILT	DESCRIPTION
MH1A	104.55	SW100.417		SE100.417		1200mm <sup>Ø</sup> OPSD-701.010
MH2A	104.64	NW101.253		NE101.253		1200mm <sup>Ø</sup> OPSD-701.010
MH3A	105.12	NW102.225		SE101.918		1200mm <sup>Ø</sup> OPSD-701.010
SAN BLKHD	104.38	NW100.337				200MM <sup>Ø</sup> CAP


J:\123987\_KW\puro\123987\_Purolator\_V03\_Production\_V03\_Design\_V03.dwg Layout Name: C-001 SITE SERVICING PLAN Plot Style: IMA STANDARD-PALL-CB Plot Scale: 1:25.4 Printed At: 12/18/2020 11:04 AM User: JAMES.BARTON

CITY PLAN No. D07-12-20-0125


**UTILITY LEGEND**



**SEDIMENT EROSION LEGEND**



**GENERAL LEGEND**



**PAVEMENT STRUCTURE:**


**LIGHT DUTY - CAR PARK AREAS**

50mm	- WEAR COURSE - HL-3 OR SUPERPAVE 12.5 ASPHALTIC CONCRETE
150mm	- BASE - OPSS GRANULAR "A" CRUSHED STONE
300mm	- SUBBASE - OPSS GRANULAR "B" TYPE II


**HEAVY DUTY - TRUCK AREAS**

40mm	- SUPERPAVE 12.5 ASPHALTIC CONCRETE
50mm	- SUPERPAVE 19.0 ASPHALTIC CONCRETE
150mm	- OPSS GRANULAR "A" CRUSHED STONE
450mm	- OPSS GRANULAR "B" TYPE II

**SERVICING LEGEND**




**GRADING LEGEND**



**DRAWING NOTES**


- 1.0 GENERAL**
- CONTRACTOR TO VERIFY ALL DIMENSIONS PRIOR TO CONSTRUCTION.
  - DO NOT SCALE DRAWINGS.
  - CONTRACTOR TO REPORT ALL DISCOVERIES OF ERRORS, OMISSIONS OR DISCREPANCIES TO THE ARCHITECT OR DESIGN ENGINEER AS APPLICABLE.
  - USE ONLY THE LATEST REVISED DRAWINGS OR THOSE THAT ARE MARKED "ISSUED FOR CONSTRUCTION".
  - ALL CONSTRUCTION SHALL COMPLY WITH CURRENT CITY OF OTTAWA STANDARDS AND SPECIFICATIONS.
  - THIS DRAWING SHALL BE READ IN CONJUNCTION WITH ALL RELEVANT DRAWINGS AND SPECIFICATIONS.
  - FOR LEGAL SURVEY INFORMATION REFER TO REGISTERED PLAN.
  - REFER TO SITE PLAN BY N45 ARCHITECTURE.
  - CONTRACTOR TO IMPLEMENT EROSION AND SEDIMENT CONTROL MEASURES AS IDENTIFIED IN THE EROSION AND SEDIMENT CONTROL PLAN TO THE SATISFACTION OF THE CITY OF OTTAWA, PRIOR TO UNDERTAKING ANY SITE ALTERATIONS (FILLING, GRADING, REMOVAL OF VEGETATION, ETC.) DURING ALL PHASES OF THE SITE PREPARATION AND CONSTRUCTION. THE MEASURES ARE TO BE MAINTAINED TO THE SATISFACTION OF THE ENGINEER AND CITY OF OTTAWA IN ACCORDANCE WITH THE BEST MANAGEMENT PRACTICES FOR EROSION AND SEDIMENT CONTROL. SHOULD ANY ADDITIONAL MEASURES BE REQUIRED TO ADDRESS FIELD CONDITIONS THEY SHALL BE INSTALLED AS DIRECTED BY THE ENGINEER OR THE CITY OF OTTAWA. SUCH ADDITIONAL MEASURES MAY INCLUDE BUT NOT BE LIMITED TO INSTALLATION OF FILTER CLOTHS ACROSS MANHOLE AND CATCHBASIN LIDS TO PREVENT SEDIMENT FROM ENTERING THE STRUCTURE AND INSTALLATION AND MAINTENANCE OF A LIGHT DUTY SILT FENCE BARRIER AS REQUIRED.
  - ALL IRON WORK ELEVATIONS SHOWN ARE APPROXIMATE AND ARE SUBJECT TO MINOR ADJUSTMENTS AS DETERMINED BY THE ENGINEER.
  - ALL CONCRETE CURBS AND SIDEWALKS TO CONFORM TO O.P.S. AND CONSTRUCTED TO CITY STANDARDS. ALL ONSITE CURBS TO BE BARRIER TYPE, WITH DEPRESSIONS AS NOTED.
  - ALL CONCRETE SHALL BE "NORMAL PORTLAND CEMENT" IN ACCORDANCE WITH O.P.S. 1350 AND SHALL ACHIEVE A MINIMUM STRENGTH OF 30MPa AT 28 DAYS.
  - ALL CONSTRUCTION TRAFFIC TO ACCESS SITE FROM PALLADIUM DRIVE OR UPPER CANADA STREET.
  - FOR GEOTECHNICAL REPORT SEE GEOTECHNICAL INVESTIGATION PG4783-1 FEB 7, 2019 BY PATERSON GROUP.
  - CONTRACTOR TO PROTECT EXISTING INFRASTRUCTURE AND PROPERTY SUCH AS TREES, PARKING METERS, SIDEWALKS, CURBS, ASPHALT, AND STREET SIGNS FROM DAMAGE DURING CONSTRUCTION. CONTRACTOR TO PAY THE COST TO REINSTATE OR REPLACE ANY DAMAGED INFRASTRUCTURE OR PROPERTY TO THE SATISFACTION OF THE CITY.
  - THE POSITION OF POLE LINES, CONDUITS, WATERMAIN, SEWERS, AND OTHER UNDERGROUND AND ABOVEGROUND UTILITIES AND STRUCTURES ARE NOT NECESSARILY SHOWN ON THE CONTRACT DRAWINGS, AND WHERE SHOWN, THE ACCURACY OF THE POSITION OF SUCH UTILITIES AND STRUCTURES IS NOT GUARANTEED. BEFORE STARTING WORK THE CONTRACTOR SHALL INFORM ITSELF OF THE EXACT LOCATION OF ALL SUCH UTILITIES AND STRUCTURES, SHALL PROTECT ALL UTILITIES AND STRUCTURES, AND SHALL ASSUME ALL LIABILITY FOR DAMAGE TO THEM.
  - CONTRACTOR TO SUPPLY SUITABLE FILL MATERIAL WHERE REQUIRED TO ROUGH GRADE THE SITE. ALL IMPORTED FILL MATERIAL TO BE CERTIFIED AS ACCEPTABLE BY THE GEOTECHNICAL ENGINEER.
  - CONTRACTOR TO HAUL EXCESS MATERIAL OFFSITE AS NECESSARY TO GRADE SITE TO MEET THE PROPOSED GRADES. ALL EXCESS MATERIAL TO BE HAULED OFFSITE AND DISPOSED OF AT AN APPROVED DUMP SITE. SHOULD THE CONTRACTOR DISCOVER ANY HAZARDOUS MATERIAL, CONTRACTOR IS TO NOTIFY ENGINEER. ENGINEER TO DETERMINE APPROPRIATE DISPOSAL METHOD/LOCATION.
  - FILL MATERIAL WITHIN THE PARKING LOT AND BUILDING PAD AREAS, AND SUPPORTING BUILDING FOUNDATIONS SHALL BE COMPACTED TO 98% STANDARD MODIFIED PROCTOR DENSITY AND TO THE SATISFACTION OF THE GEOTECHNICAL ENGINEER.
  - ALL COMPACTION METHODS TO BE PERFORMED TO THE SATISFACTION OF THE GEOTECHNICAL ENGINEER TO INCLUDE BUT NOT BE LIMITED TO THE THICKNESS OF LIFTS, AND COMPACTION EQUIPMENT USED.
  - ALL DISTURBED BOULEVARDS TO BE REINSTATED WITH SOD ON 100mm TOPSOIL.
  - UTILITY DUCTS TO BE INSTALLED PRIOR TO ROAD BASE CONSTRUCTION.
  - CLAY DIKES TO BE INSTALLED WHERE INDICATED ON THE DRAWINGS OR AS APPROVED AND DIRECTED BY THE GEOTECHNICAL ENGINEER ALL IN ACCORDANCE WITH CITY OF OTTAWA STANDARDS AND SPECIFICATIONS.
- 2.0 SANITARY**
- ALL SANITARY SEWER MAINS TO BE CSA CERTIFIED, BELL AND SPIGOT TYPE. ONLY FACTORY FITTINGS TO BE USED. SEWER TO BE INSTALLED AS PER OSPD 1005.01. SANITARY SEWER MATERIALS TO BE: 250mmØ AND SMALLER - PVC DR 35
  - ALL SANITARY MAINTENANCE HOLES TO BE 1.2m DIAMETER AS PER CITY OF OTTAWA STANDARDS COMPLETE WITH BENCHING, RUNGS, FRAME AND COVER, DROP PIPES AND LANDINGS WHERE NEEDED.
  - SANITARY MANHOLE COVERS TO BE CITY OF OTTAWA STD. S25 (MOD. OPSD. 401.020), SANITARY MANHOLE COVER TO BE CLOSED COVER TYPE, AS PER CITY STANDARD S24.
  - SANITARY SEWER LEAKAGE TEST AND CCTV INSPECTION SHALL BE COMPLETED AS PER CITY SPECIFICATIONS PRIOR TO INSTALLATION OF BASE COURSE ASPHALT.
  - ANY SANITARY SEWER WITH LESS THAN 2.0M COVER REQUIRES THERMAL INSULATION AS PER CITY OF OTTAWA STANDARD W22, OR AS APPROVED BY THE ENGINEER.
  - CONNECTION TO THE EXISTING SANITARY SEWER TO BE INCLUDED IN THE COST FOR SANITARY SEWER INSTALLATION. THIS INCLUDES REINSTATEMENT OF ROAD CUTS TO CITY STANDARDS.
- 3.0 STORM**
- ALL STORM SEWERS TO BE CSA CERTIFIED, BELL AND SPIGOT TYPE. ALL STORM SEWERS TO BE INSTALLED PER MANUFACTURER'S INSTRUCTIONS. ONLY FACTORY FITTINGS TO BE USED. STORM SEWER MATERIALS TO BE: 375mmØ AND SMALLER - PVC DR 35, 450mmØ AND LARGER - CONC. CL. 100-D, 825mmØ AND LARGER - CONC. CL. 65-D

- ALL STORM MAINTENANCE HOLES TO BE SIZED IN ACCORDANCE WITH THE PLANS AND AS PER CITY OF OTTAWA STANDARDS COMPLETE WITH BENCHING, RUNGS, DROP PIPES AND FRAME AND COVER.
- STORM MH COVERS TO BE OPEN TYPE, AS PER CITY STANDARD S24, FRAMES TO BE PER CITY OF OTTAWA STD. S25. CONTRACTOR TO INSTALL FILTER FABRIC UNDER STORM MH COVER UNTIL SODDING IS COMPLETE.
- STORM MAINTENANCE HOLES TO BE OPSD. SIZE AS SPECIFIED, TAPER TOP.
- ALL CATCH BASINS TO BE AS PER OPSD 705.010, FRAME & FISH TYPE GRATE AS PER CITY OF OTTAWA STD. S19.1.
- ANY STORM SEWER WITH LESS THAN 2.0M COVER REQUIRES THERMAL INSULATION AS PER CITY OF OTTAWA STANDARD W22, OR AS APPROVED BY THE ENGINEER.
- CONNECTION TO THE EXISTING STORM SEWER TO BE INCLUDED IN THE COST FOR STORM SEWER INSTALLATION.
- CONTRACTOR TO PROVIDE IPEX-TEMPEST HF ICDS SHOP DRAWINGS, OR EQUIVALENT, FOR ENGINEERS REVIEW PRIOR TO ORDERING ICDS.
- 4.0 WATER**
- ALL WATERMANS TO BE PVC DR 18, WITH MINIMUM COVER OF 2.4M AND INSTALLED PER CITY OF OTTAWA STANDARDS. ALL DOMESTIC WATER SERVICES ARE TO BE 200MMØ.
- THRUST BLOCKS TO BE INSTALLED AT ALL BENDS, TEES, AND CAPS ALL AS PER OPSD 1103.01 AND 1103.02.
- CONTRACTOR TO CONDUCT PRESSURE AND LEAKAGE TESTING OF ALL WATERMANS AND DISINFECT AND CHLORINATE ALL WATERMANS TO THE SATISFACTION OF M.O.E. AND THE CITY OF OTTAWA.
- TRACER WIRE TO BE INSTALLED ALONG THE FULL LENGTH OF WATERMAIN AND ATTACHED TO EACH MAIN STOP AS PER CITY OF OTTAWA STANDARDS.
- ALL COMPONENTS OF THE WATER DISTRIBUTION SYSTEM SHALL BE CATHODICALLY PROTECTED AS PER CITY OF OTTAWA STANDARDS.
- ALL VALVES & VALVE BOXES AND CHAMBERS, HYDRANTS, AND HYDRANT VALVES AND ASSEMBLIES SHALL BE INSTALLED AS PER CITY OF OTTAWA STANDARDS.
- ANY WATERMAIN WITH LESS THAN 2.4M COVER REQUIRES THERMAL INSULATION AS PER CITY OF OTTAWA STANDARD W22, OR AS APPROVED BY THE ENGINEER.
- CONTRACTOR IS RESPONSIBLE FOR ACQUIRING THE WATER PERMIT FROM THE CITY OF OTTAWA AND PAYMENT OF ANY FEES ASSOCIATED WITH SECURING THE WATER PERMIT. OWNER IS RESPONSIBLE FOR REIMBURSING THE CONTRACTOR FOR THE ACTUAL COST OF ACQUIRING THE WATER PERMIT.
- CONNECTION TO EXISTING WATERMAIN TO BE INCLUDED IN THE COST FOR THE WATERMAIN INSTALLATION. THIS COST INCLUDES REINSTATEMENT OF ROAD CUTS TO CITY STANDARDS.
- 5.0 PARKING LOT AND WORK IN PUBLIC RIGHTS OF WAY**
- CONTRACTOR TO REINSTATE ROAD CUTS PER CITY OF OTTAWA STANDARD R-10.
- CONTRACTOR SHALL PREPARE A TRAFFIC MANAGEMENT PLAN FOR REVIEW AND APPROVAL BY THE CITY OF OTTAWA. CONTRACTOR TO MAINTAIN TRAFFIC FLOW DURING THE ENTIRE CONSTRUCTION PERIOD. MAINTENANCE OF ROAD CUTS SHALL BE THE RESPONSIBILITY OF THE CONTRACTOR. PROVISION OF FLAGMEN, DETOURS AS NECESSARY, BARRICADES AND SIGNS TO THE FULL SATISFACTION OF THE ENGINEER AND ROAD AUTHORITY SHALL BE THE CONTRACTOR'S RESPONSIBILITY.
- CONTRACTOR TO PREPARE SUBGRADE, INCLUDING PROOFROLLING, TO THE SATISFACTION OF THE GEOTECHNICAL ENGINEER PRIOR TO THE COMMENCEMENT OF PLACEMENT OF GRANULAR B MATERIAL.
- FILL TO BE PLACED AND COMPACTED PER THE GEOTECHNICAL REPORT REQUIREMENTS.
- CONTRACTOR TO SUPPLY, PLACE AND COMPACT GRANULAR B MATERIAL IN ACCORDANCE WITH THE RECOMMENDATIONS OF THE GEOTECHNICAL ENGINEER. CONTRACTOR TO PROVIDE ENGINEER WITH SAMPLES OF GRANULAR B MATERIAL FOR TESTING AND CERTIFICATION FROM THE GEOTECHNICAL ENGINEER THAT THE MATERIAL MEETS THE GRADATION REQUIREMENTS SPECIFIED IN THE GEOTECHNICAL REPORT.
- GRANULAR A MATERIAL TO BE PLACED ONLY UPON APPROVAL BY THE GEOTECHNICAL ENGINEER OF GRANULAR B PLACEMENT.
- CONTRACTOR TO SUPPLY, PLACE AND COMPACT GRANULAR A MATERIAL IN ACCORDANCE WITH THE RECOMMENDATIONS OF THE GEOTECHNICAL ENGINEER. CONTRACTOR TO PROVIDE ENGINEER WITH SAMPLES OF GRANULAR A MATERIAL FOR TESTING AND CERTIFICATION FROM THE GEOTECHNICAL ENGINEER THAT THE MATERIAL MEETS THE GRADATION REQUIREMENTS SPECIFIED IN THE GEOTECHNICAL REPORT.
- ASPHALT MATERIAL TO BE PLACED ONLY UPON APPROVAL BY THE GEOTECHNICAL ENGINEER OF GRANULAR A PLACEMENT.
- CONTRACTOR TO SUPPLY, PLACE AND COMPACT ASPHALT MATERIAL IN ACCORDANCE WITH THE RECOMMENDATIONS OF THE GEOTECHNICAL ENGINEER. CONTRACTOR TO PROVIDE ENGINEER WITH SAMPLES OF ASPHALT MATERIAL FOR TESTING AND CERTIFICATION FROM THE GEOTECHNICAL ENGINEER THAT THE MATERIAL MEETS THE REQUIREMENTS SPECIFIED IN THE GEOTECHNICAL REPORT.
- CONTRACTOR IS RESPONSIBLE FOR ESTABLISHING LINE AND GRADE IN ACCORDANCE WITH THE PLANS, AND FOR PROVIDING THE ENGINEER WITH VERIFICATION PRIOR TO PLACEMENT.
- DITCHES DISTURBED DURING CULVERT INSTALLATION AND GRADING OPERATIONS ARE TO BE REINSTATED TO THEIR ORIGINAL CONDITION AND FLOWLINE GRADES.
- ALL EXCESS MATERIAL TO BE HAULED OFFSITE AND DISPOSED OF AT AN APPROVED DUMP SITE. SHOULD THE CONTRACTOR DISCOVER ANY HAZARDOUS MATERIAL, CONTRACTOR IS TO NOTIFY ENGINEER. ENGINEER TO DETERMINE APPROPRIATE DISPOSAL METHOD/LOCATION.
- PAVEMENT STRUCTURE (MATERIAL TYPES AND THICKNESSES) FOR HEAVY DUTY AND LIGHT DUTY AREAS TO BE AS SPECIFIED IN THE GEOTECHNICAL REPORT AND SHOWN ON THE PLANS.



**IBI GROUP**  
400 - 303 Preston Street  
Ottawa ON K1S 5N4 Canada  
tel 613 225 1311 fax 613 225 9868  
ibigroup.com


Project Title  
**Purolator**  
DISTRIBUTION KANATA  
1400 UPPER CANADA STREET,



Drawing Title  
**GENERAL NOTES, LEGEND AND CB DATA TABLE**


Scale  
N.T.S.

Design	J.B.	Date	AUG. 2020
Drawn	J.B./D.P.S.	Checked	T.R.B.
Project No.	123987	Drawing No.	C-010



77.31

VACANT



**BLOCK 26, 27, AND 30**  
(BLOCK 5 - PHASE 5 REGISTRATION)  
31969.32 m<sup>2</sup>  
7.90 Acres  
PROPOSED BUILDING  
1 STOREY  
F.F.=105.50  
ROOF RELEASE RATE 20 l/s

**BLOCK 33, AND 34**  
(BLOCK 6 - PHASE 5 REGISTRATION)  
ROPOSED INDUSTRIAL DEVELOPMENT "A"  
IBI JOB NUMBER 126643

**BLOCK 19**  
(BLOCK 2 - PHASE 3 REGISTR)  
4856.30 m<sup>2</sup>  
1.20 Acres  
F.F.=104.25

**BLOCK 31**  
(BLOCK 2 - PHASE 5 REGISTRATION)  
DEPRESSED CURB, SIDEWALK AND CURB RETURN AS PER CITY OF OTTAWA STANDARD DETAIL SC7.1  
F.F.=105.80

**UPPER CANADA STREET**  
(IBI JOB NUMBER 14289)


**KINAXIS**  
IBI JOB NUMBER 121693

**BLOCK 24, 25, AND 28**  
(BLOCK 4 - PHASE 5 REGISTRATION)

DEPRESSED CURB, SIDEWALK AND CURB RETURN AS PER CITY OF OTTAWA STANDARD DETAIL SC7.1

EX. GRAVEL ACCESS ROAD  
F.F.=104.25

**NOTES:**  
1. SEE DETAIL DRAWING C-010 FOR ADDITIONAL DETAILS AND NOTES.  
2. SITE BENCHMARK TO BE OBTAINED FROM LEGAL SURVEYOR STANTEC GEOMATICS.




No.	REVISIONS	By	Date
14			
13			
12			
11			
10			
9			
8			
7			
6			
5			
4			
3	REVISED AS PER CITY COMMENTS	T.R.B.	2020-12-18
2	ISSUED FOR 30% REVIEW	T.R.B.	2020-11-13
1	ISSUED FOR SPA	T.R.B.	2020-09-17



**IBI GROUP**  
400 - 333 Preston Street  
Ottawa ON K1S 5N4 Canada  
tel 613 225 1311 fax 613 225 9868  
ibigroup.com

Project Title  
**Purolator**  
DISTRIBUTION KANATA  
1400 UPPER CANADA STREET,  
KANATA, ONTARIO




Drawing Title  
**SITE GRADING PLAN**


Scale  
1:500

Design	J.B.	Date	AUG. 2020
Drawn	J.B./D.P.S.	Checked	T.R.B.
Project No.	123987	Drawing No.	C-200

CITY PLAN No. 18260  
CITY FILE No. D07-12-20-0125



**NOTES:**  
 1. SEE DETAIL DRAWING C-010 FOR ADDITIONAL DETAILS AND NOTES.  
 2. SITE BENCHMARK TO BE OBTAINED FROM LEGAL SURVEYOR STANTEC GEOMATICS.





**KEY PLAN**  
N.T.S.

14		
13		
12		
11		
10		
9		
8		
7		
6		
5		
4		
3	REVISED AS PER CITY COMMENTS	T.R.B. 2020-12-18
2	ISSUED FOR 30% REVIEW	T.R.B. 2020-11-13
1	ISSUED FOR SPA	T.R.B. 2020-09-17
No.	REVISIONS	By Date




**IBI GROUP**  
 400 - 333 Preston Street  
 Ottawa ON K1S 5N4 Canada  
 tel 613 225 1311 fax 613 225 9868  
 ibigroup.com

Project Title  
**Purolator**  
**DISTRIBUTION KANATA**  
 1400 UPPER CANADA STREET,  
 KANATA, ONTARIO



Drawing Title  
**EXISTING CONDITIONS**



Design	J.B.	Date	AUG. 2020
Drawn	J.B./D.P.S.	Checked	T.R.B.
Project No.	123987	Drawing No.	C-201

J:\123987\_KNWPurolator\0\_Production\10\_Production\103\_Design\04\_Civil\Sheets\C-201.dwg Layout Name: C-201 EXISTING CONDITIONS Plot Style: AIA STANDARD-FULL.ctb Plot Scale: 1:25.4 Printed At: 12/18/2020 11:07 AM User: J.B. Saved By: OSUUMA Lant

CITY PLAN No. 18260  
 CITY FILE No. D07-12-20-0125

VACANT

0.30 RESERVE 7.80 m<sup>2</sup>  
BLOCK 50

**NOTES:**

- SEE DETAIL DRAWING C-010 FOR ADDITIONAL DETAILS AND NOTES.
- SITE BENCHMARK TO BE OBTAINED FROM LEGAL SURVEYOR STANTEC GEOMATICS.


**LEGEND :**

- WH → AREA NUMBER
- 1.01 | 0.0 → RUNOFF COEFFICIENT
- AREA IN HECTARES
- AREA IN HECTARES
- 5.14 PBP → LAND USE TYPE

PBP → PRESTIGE BUSINESS  
 PARK - 35 000 l/ha  
 IND → LIGHT INDUSTRIAL - 35 000 l/ha  
 COM → COMMERCIAL - 50 000 l/ha  
 ROW → RIGHT OF WAY (INFILTRATION FLOW ONLY)

→ DRAINAGE AREA LIMITS  
 → EXISTING DRAINAGE AREA LIMITS

SEE 010, FOR NOTES, LEGEND, CB TABLE, STREET SECTIONS AND DETAILS




**KEY PLAN**  
N.T.S.

No.	REVISIONS	By	Date
14			
13			
12			
11			
10			
9			
8			
7			
6			
5			
4			
3	REVISED AS PER CITY COMMENTS	T.R.B.	2020-12-18
2	ISSUED FOR 30% REVIEW	T.R.B.	2020-11-13
1	ISSUED FOR SPA	T.R.B.	2020-09-17




**IBI GROUP**  
 400 - 333 Preston Street  
 Ottawa ON K1S 5N4 Canada  
 tel 613 225 1311 fax 613 225 9868  
 ibigroup.com


Project Title  
**Purolator**  
**DISTRIBUTION KANATA**  
 1400 UPPER CANADA STREET.



Drawing Title  
**SANITARY DRAINAGE**  
**AREA PLAN**




Design	J.B.	Date	AUG. 2020
Drawn	J.B./D.P.S.	Checked	T.R.B.
Project No.	123987	Drawing No.	C-400




J:\123987\_Kanata\AreaPlan\AreaPlan.dwg Layout Name: C-400 SANITARY DRAINAGE AREA PLAN Plot Style: AIA STANDARD-FULLCTE Plot Scale: 1:250.4 Plotted At:

CITY PLAN No. 18260  
CITY FILE No. D07-12-20-0125



- NOTES:**
- SEE DETAIL DRAWING C-010 FOR ADDITIONAL DETAILS AND NOTES.
  - SITE BENCHMARK TO BE OBTAINED FROM LEGAL SURVEYOR STANTEC GEOMATICS.
- LEGEND:**
- WH (Area Number): AREA NUMBER
  - 1.01/0.0: RUNOFF COEFFICIENT
  - AREA IN HECTARES: AREA IN HECTARES
  - WH (Area Number): EXISTING AREA NUMBER
  - AREA IN HECTARES: EXISTING AREA IN HECTARES
  - Tc=11.70, AC=1.23: ESTIMATED TIME OF CONCENTRATION IN MINUTES AND PRODUCT OF AREA AND RUNOFF COEFFICIENT
  - [Symbol]: DRAINAGE AREA LIMITS
  - [Symbol]: EXISTING DRAINAGE AREA LIMITS
  - [Symbol]: EXISTING EMERGENCY OVERLAND FLOW

SEE 010, FOR NOTES, LEGEND, CB TABLE, STREET SECTIONS AND DETAILS





**REVISIONS**

No.	REVISIONS	By	Date
14			
13			
12			
11			
10			
9			
8			
7			
6			
5			
4			
3	REVISED AS PER CITY COMMENTS	T.R.B.	2020-12-18
2	ISSUED FOR 30% REVIEW	T.R.B.	2020-11-13
1	ISSUED FOR SPA	T.R.B.	2020-09-17




**IBI GROUP**  
400 - 303 Preston Street  
Ottawa ON K1S 5N4 Canada  
tel 613 225 1311 fax 613 225 9868  
ibigroup.com

Project Title  
**Purolator**  
DISTRIBUTION KANATA  
1400 UPPER CANADA STREET.



**STORM DRAINAGE  
AREA PLAN**




Design	J.B.	Date	AUG. 2020
Drawn	J.B./D.P.S.	Checked	T.R.B.

Project No.	123987	Drawing No.	C-500
-------------	--------	-------------	-------

J:\123987\_KW\Purolator\Y0\_Production\Y00\_Production\Y00\_Design\Y00\_Civil\Sheets\C-500.dwg Layout Name: C-500 STORM DRAINAGE AREA PLAN Plot Style: AIA STANDARD-FULL.CTB Plot Scale: 1:25.4 Plotted At: 12/19/2020 11:12 AM User: JRE

CITY PLAN No. 18260  
CITY FILE No. D07-12-20-0125



POND ID	1
TOP OF GRATE (m)	103.70
STATIC ELEV (m)	104.65
STATIC DEPTH (m)	0.95
STATIC VOLUME (m³)	297.37

POND ID	3
TOP OF GRATE (m)	103.00
STATIC ELEV (m)	104.65
STATIC DEPTH (m)	1.65
STATIC VOLUME (m³)	310.97

POND ID	4
TOP OF GRATE (m)	104.65
STATIC ELEV (m)	104.75
STATIC DEPTH (m)	0.10
STATIC VOLUME (m³)	6.99

POND ID	17
TOP OF GRATE (m)	105.00
STATIC ELEV (m)	105.15
STATIC DEPTH (m)	0.15
STATIC VOLUME (m³)	5.81

POND ID	16
TOP OF GRATE (m)	105.00
STATIC ELEV (m)	105.15
STATIC DEPTH (m)	0.15
STATIC VOLUME (m³)	12.27

POND ID	15
TOP OF GRATE (m)	105.00
STATIC ELEV (m)	105.10
STATIC DEPTH (m)	0.10
STATIC VOLUME (m³)	7.29

POND ID	14
TOP OF GRATE (m)	105.05
STATIC ELEV (m)	105.20
STATIC DEPTH (m)	0.15
STATIC VOLUME (m³)	7.40

POND ID	12
TOP OF GRATE (m)	105.05
STATIC ELEV (m)	105.20
STATIC DEPTH (m)	0.15
STATIC VOLUME (m³)	3.80

POND ID	10
TOP OF GRATE (m)	105.05
STATIC ELEV (m)	105.20
STATIC DEPTH (m)	0.15
STATIC VOLUME (m³)	5.03

POND ID	13
TOP OF GRATE (m)	104.80
STATIC ELEV (m)	105.00
STATIC DEPTH (m)	0.20
STATIC VOLUME (m³)	20.47


POND ID	11
TOP OF GRATE (m)	104.75
STATIC ELEV (m)	104.95
STATIC DEPTH (m)	0.20
STATIC VOLUME (m³)	22.62

POND ID	9
TOP OF GRATE (m)	104.40
STATIC ELEV (m)	104.55
STATIC DEPTH (m)	0.15
STATIC VOLUME (m³)	5.93


POND ID	8
TOP OF GRATE (m)	104.55
STATIC ELEV (m)	104.65
STATIC DEPTH (m)	0.10
STATIC VOLUME (m³)	1.55

Roof Ponding Information	
i.	16 flow control roof drains proposed
ii.	All drains to be Watts RD100 with flow control or approved equivalent
iii.	Maximum depth of storage 150mm
iv.	Flow per drain to be maximum 1.25 litres/second, total flow from roof 20 litres/second
v.	Scupper locations not yet established

**NOTES:**  
 1. SEE DETAIL DRAWING C-010 FOR ADDITIONAL DETAILS AND NOTES.  
 2. SITE BENCHMARK TO BE OBTAINED FROM LEGAL SURVEYOR STANTEC GEOMATICS.



SEE 010, FOR NOTES, LEGEND, CB TABLE, STREET SECTIONS AND DETAILS





No.	REVISIONS	By	Date
14			
13			
12			
11			
10			
9			
8			
7			
6			
5			
4			
3	REVISED AS PER CITY COMMENTS	T.R.B.	2020-12-18
2	ISSUED FOR 30% REVIEW	T.R.B.	2020-11-13
1	ISSUED FOR SPA	T.R.B.	2020-09-17




**IBI GROUP**  
 400 - 333 Preston Street  
 Ottawa ON K1S 5N4 Canada  
 tel 613 225 1311 fax 613 225 9868  
 ibigroup.com

Project Title  
**Purolator**  
 DISTRIBUTION KANATA  
 1400 UPPER CANADA STREET,  
 KANATA, ONTARIO




Drawing Title  
**PONDING PLAN**




Design	J.B.	Date	AUG. 2020
Drawn	J.B./D.P.S.	Checked	T.R.B.
Project No.	123987	Drawing No.	C-600






**NOTES:**  
 1 Number of bales varies to suit ditch.  
 2 Straw bales to be butted tightly against adjoining bales and shaped to conform to the sides of the ditch to prevent water flow through barrier.  
 A All dimensions are in millimetres unless otherwise shown.

ONTARIO PROVINCIAL STANDARD DRAWING  
 Nov 2006 Rev 1  
**STRAW BALE FLOW CHECK DAM**  
 OPSD 219.180



**NOTE:**  
 A All dimensions are in millimetres unless otherwise shown.

ONTARIO PROVINCIAL STANDARD DRAWING  
 Nov 2006 Rev 1  
**LIGHT-DUTY SILT FENCE BARRIER**  
 OPSD 219.110




**NOTE:**  
 A All dimensions are in millimetres unless otherwise shown.

ONTARIO PROVINCIAL STANDARD DRAWING  
 Nov 2006 Rev 1  
**ROCK FLOW CHECK DAM V-DITCH**  
 OPSD 219.210

- NOTES:**
- SILT FENCE TO BE ERECTED PRIOR TO EARTH WORKS BEING COMMENCED. SILT FENCE TO BE MAINTAINED UNTIL VEGETATION IS ESTABLISHED OR UNTIL START OF SUBSEQUENT PHASE.
  - STRAW BALE SEDIMENT TRAPS TO BE CONSTRUCTED IN EXISTING ROAD SIDE DITCHES. TRAPS TO REMAIN AND BE MAINTAINED UNTIL VEGETATION IS ESTABLISHED.
  - SILT SACK TO BE PLACED AND MAINTAINED UNDER COVER OF ALL CATCHBASINS. GEOTEXTILE SILT SACK IN STREET C/S TO REMAIN UNTIL ALL CURBS ARE CONSTRUCTED. GEOTEXTILE FABRIC IN RYCBs TO REMAIN UNTIL VEGETATION IS ESTABLISHED. ALL CATCHBASINS TO BE REGULARLY INSPECTED AND CLEANED, AS NECESSARY, UNTIL SOD AND CURBS ARE CONSTRUCTED.
  - CONTRACTOR TO PROVIDE DETAILS ON LOCATION(S) AND DESIGN OF DEWATERING TRAP(S) PRIOR TO COMMENCING WORK. CONTRACTOR ALSO RESPONSIBLE FOR MAINTAINING TRAP(S) AND ADJUSTING SIZE(S) IF DEEMED REQUIRED BY THE ENGINEER DURING CONSTRUCTION.
  - CONTRACTOR TO PROTECT EXISTING CATCHBASINS WITH FILTER CLOTH UNDER THE COVERS TO TRAP SEDIMENTATION. REFER TO IDENTIFIED STRUCTURES.


**LEGEND:**

- LIGHT DUTY SILT FENCE AS PER OPSD-219.110
- SNOW FENCE
- STRAW BALE CHECK DAM AS PER OPSD-219.180
- ROCK CHECK DAM AS PER OPSD-219.210
- SILT SACK PLACED UNDER EXISTING CB COVER
- TEMPORARY MUD MAT 0.15m THICK 50mm CLEAR STONE ON NON WOVEN FILTER CLOTH



**KEY PLAN**  
 N.T.S.

14		
13		
12		
11		
10		
9		
8		
7		
6		
5		
4		
3	REVISED AS PER CITY COMMENTS	T.R.B. 2020-12-18
2	ISSUED FOR 30% REVIEW	T.R.B. 2020-11-13
1	ISSUED FOR SPA	T.R.B. 2020-09-17
No.	REVISIONS	By Date



**TAGGART REALTY MANAGEMENT**

**IBI GROUP**  
 400 - 333 Preston Street  
 Ottawa ON K1S 5N4 Canada  
 tel 613 225 1311 fax 613 225 9868  
 ibigroup.com

Project Title  
**Purolator DISTRIBUTION KANATA**  
 1400 UPPER CANADA STREET,  
 BLOCK 19 (BLOCK 2 - PHASE 3 REG)  
 4856.30 m<sup>2</sup>  
 1.20 Acres

PROFESSIONAL ENGINEER  
 T. R. BRULE  
 2020/12/18  
 PROVINCE OF ONTARIO

**EROSION AND SEDIMENTATION CONTROL PLAN**

Design	J.B.	Date	AUG. 2020
Drawn	J.B./P.S.	Checked	T.R.B.
Project No.	123987	Drawing No.	C-900

CITY PLAN No. 18260  
 CITY FILE No. D07-12-20-0125