Appendix A: 120 Den Hagg Phase 1 Zoning Compliance Chart (for site plan revision 1 dated December 2020)

	Zanina	Deserved	Complian with empire	N
Applicable zones from 2008-250 The property known is zoned AM10 [1779]	Zoning Requirement	Proposal	Complies with zoning	Note
Property lies within the Mature Neighbourhood Overlay Zone.				1
				L
Assumed yard locations for Phase 1 Front yard: Montreal Road				
Corner Yard: Don Hagg Drive				1
Interior Side Yard: property line abutting park				1
Rear Yard: south property line				1
				1
Note:applicable provisions highlighted in green given that this zone is subject to requirements from the parent zone, subzone and execption				1
				l
AM Section185 (3) (a) Minimum lot area	no minimum	.596 ha		
(b) Minimum lot width	no minimum	see note		irregular lot
(c) Minimum front and corner side yard side yard setback	no minimum			
(d) Minimum interior side yard setbacks abutting residential zone	7.5 m			
douting residential zone	7.5 m no minimum	0		applicable next to park
(e) Minimum rear side yard setback		-		
abutting a street	3 m			1
abutting residential zone	7.5 m			1
for a residential use building all other cases	7.5 m no minimum			
(g) Maximum building height				
in any area up to and including 20 metres from a property line abutting a R1, R2 or R3 residential zone (By-law 2011-124)	11 m			
in any area up to and including 20 metres from a property line abutting a R4 zone (By-law 2011-124) in any area over 20 metres and up to and including 30 metres from a property line abutting a R1, R2, R3 or R4 zone (By-law 2011-124)	15 m 20 m			
main a rea over 20 metres and up to and including so metres nom a property line additing a K1, K2, K5 of K4 2016 (By-law 2011-124) more than 30 metres from a property line abditing a K1 – R4 20ne	20 m			1
in all other cases	30 m			
(h) Maximum floor space index for all case other than AM, AM1, AM4 ad AM5 as noted in By-law)	no maximum	4.07		
(j) minimum width of landscaped area around a parking lot	see Section 110			not applicable as all parking indoor
AM10 Section 186 (10)				
186 (10) (a) the lot line abutting the designated "Arterial Mainstreet", as per Schedule B of the Official Plan, is the front lot line				
186 (10) (b) despite Table 185(c), the following provisions apply				
the minimum front and corner side yard setback for all buildings is 0 metres, and at least 50% of the frontage along the front lot line and corner side lot line must be occupied by building walls located within 4.5 metres of the frontage for a Residential use building, and within 3.0 metres for Non-residential and Mixed use buildings	no minimum location of walls			
by building wails located within 4.5 metres of the frontage for a kesioential use building, and within 3.0 metres for Non-residential and Mixed use buildings in the case of a phased development, all phases must be shown on a site plan approved pursuant to Section 41 of the Planning Act	location of wails			
				applicable to Phase 2 but shown here to
186 (10) (c) despite Table 185(d)(i), the minimum interior side yard setback from a lot line abutting a residential zone	3 m first 20 m	see note		demonstrate future compliance applicable to Phase 2 but shown here to
	7.5 m after that	see note		demonstrate future compliance
	no majter that	Sec note		
186 (10) (d) despite Table 185(e), sub clauses (ii) and (iii), the minimum rear yard setback is	3 m first 20 m	7.2m		
3.0 metres for any building wall within 20 metres of a lot line abutting a public street	7.5 m after that	8.1m		1
7.5 metres in all other cases				
186 (10)(e) any portion of a building located within 10 metres a front lot line or corner lot line must satisfy the following minimum building heights				
if the building is a non-residential or mixed-use building, the ground floor requires a minimum height of 4.5 metres	4. 5 m ground floor	3.66 m	nö	
the minimum building height required is 7.5 metres, and must contain at least two storeys 186 (10) (g) the ground floor façade facing a public street of a building located within 4.5 metres of the front lot line or corner side lot line must include	7.5 m see exception	28.52 m		
Loo (20) (g) the ground non-race racing a point arcce of obtaining rocated while the interest of the interest of the rocated i	See exception			
In the case of non-residential uses				
a minimum of one active entrance in the case of a residential use building				1
186 (10) (h) a minimum of 50% of the surface area of the ground floor façade, measured from the average grade up to a height of 4.5 metres, facing a public street must be comprised of transparent glazing and active customer or resident entrance access doors	see exception			
Taking a point server must be comprised on cansparent grazing and active customer on escent encance access usons 186 (10) (i)despite Table 185(f) the following maximum building heights apply				
	11 m			
In any area up to and including 20 metres from a rear lot line abutting an R4 zone:	15 m			1
In any area over 20 metres and up to and including 30 metres from a rear lot line abutting a R1, R2, R3, or R4 zone: In any area outside of the areas identified in (i) through (iii) above; and 2. up to 7.5 metres from that part of a side	20 m			1
In any area outside of the areas identified in () of rough (in) address and 2, op to 7.5 medes from that part of a side To the within 20 metres of a street and abutting a R.2, R.2 or R4 zone:	15 m			
In all other cases:	30 m	28.52 m		
Exception 1779				portion of building within 6 m of corner yard is
Minimum front and corner side yard setback for any part of a building above 11 m in height	6m	see note		12.1 meters in height at average grade
Maximum permitted front and corner side yard setback for any part of a building wall 11 m or less in height where the front or side lot abuts		25 m from		
Montreal Road: 25 m from centreline of Montreal Road	25 m from MontrealCL	25 m from MontrealCL		applicable for Montreal Road frontage
				applicable for Den Hagg frontage; not
Other streets: 3.0 m from street lot line	3 m from other street	see note		applicable as building is 12 meter in height
The wall at grade facing a public street shall have 50% of its facade comprised of windows and entrances and, in the case of a corner lot, the entrance may be in an angle at corner walls facing a street intersection	50% glazing and door	75%		
ייייווסא הביוו טו טופוב סר רתוובן אמווז ומרוווג ע זרובר ווורוזברווהוו				
Other Applicable Sections			•	
Section 65 Permited Projections				
(4) Canopies and awnings. (b) All other buildings including a low-rise apartment dwelling and mid-high-rise apartment dwelling.	1.8 m	1.8		l
Section 101				
				126-12=114 *.5=57 spaces required vs 66
Minimum No. of parking spaces per Apartment Dwelling, mid-high rise	0.5	see note		provided (0 for the first 12)
Minimum No. of parking spaces for populational uses under 500 sp. m. per 101/4)	0	cee note		275 cg m of commercial space is progrand
Minimum No. of parking spaces for non-residnetial uses under 500 sq. m per 101(4)	U	see note		275 sq. m. of commercial space is proposed
Section 102				
Minimum No. of Vicitor and ing captor par Apartment Durallian 1-111-11-11-11-11-11-11-11-11-11-11-11-	0.1			126-12=114 *.1=11.4 say 11 spaces required v
Minimum No. of visitor parking spaces per Apartment Dwelling, Low-rise or Mid-High Rise	0.1	see note		12 provided (0 for the first 12)
				Note: 66 plus 12= 78 spaces provided
Section 106				
Parking space width (m) Minimum parking space denth (m)	2.6 min 2.75 max	2.6 min 5.2 m		
Minimum parking space depth (m)	5.2	5.2 m		
Section 107				
Driveway access : min width (m) two way	6 per section 197(8)	6 m		
Fortion 111				
Section 111				126*.5=63 1 per 1500 sq. m for non-res =1 for
Bicycle Parking Space Provisions (per apartment mid-high rise dwelling unit)	0.5	see note		total of 64 vs 65 provided
Section 137				126*6=756 sq. m. required wheras 1143 sq. m.
Total amenity area for Apartment Building , mid-high rise (in sq. m per unit)	6	see note		are provided
Communal amenity area: as % of required total amenity area?	50	206.7 sq. m		