

**Proposed High-Rise Residential Development
1200 Maritime Way**

Serviceability and Stormwater Management Report

Prepared for:

Claridge Homes

Prepared By:

NOVATECH

Suite 200, 240 Michael Cowpland Drive
Ottawa, Ontario
K2M 1P6

January 25, 2021
Amended November 3, 2021
Revised May 31, 2022
Revised October 11, 2022
Revised April 28, 2023

Novatech File: 120144
Ref No. R-2021-012

April 28, 2022

City of Ottawa
Planning, Infrastructure and Economic Development Department
Planning and Infrastructure Approvals Branch
110 Laurier Avenue West, 4th Floor
Ottawa ON, K1P 1J1

Attention: Ms. Laurel McCreight, MCIP, RPP

Dear Laurel:


**Reference: 1200 Maritime Way - Claridge Development (D07-12-21-0017)
Serviceability and Stormwater Management Report**

Enclosed is the Serviceability and Stormwater Management Report for the proposed 1200 Maritime Way development located along the Highway 417, Kanata Avenue and Maritime Way in the City of Ottawa. This report is submitted in support of the site plan application and outlines how the site will be serviced with public infrastructure.

Trusting this report is adequate for your purposes. Should you have any questions, or require additional information, please contact me.

Yours truly,

NOVATECH



Greg MacDonald, P. Eng.
Director, Land Development and Public Sector Infrastructure

cc: Vincent, Denomme, Claridge Homes

TABLE OF CONTENTS

1.0	INTRODUCTION.....	1
2.0	EXISTING CONDITIONS	1
3.0	PROPOSED DEVELOPMENT	1
4.0	SITE CONSTRAINTS.....	2
5.0	SANITARY SEWER.....	3
6.0	STORM SEWER AND STORMWATER MANAGEMENT	4
6.1	Storm Water Management Criteria	4
6.2	Existing Site Drainage	5
6.3	Quantity Control	5
6.4	Water Quality Control	6
6.5	Major Overland Flow Route	6
7.0	WATERMAIN.....	7
8.0	EROSION AND SEDIMENT CONTROL	8
9.0	CONCLUSIONS.....	9

List of Figures

- Figure 1: Key Plan
 Figure 2: Existing Conditions Plan
 Figure 3: Site Plan

List of Tables

- Table 6.1: Stormwater Management Summary
 Table 7.1: Domestic Water Demand Summary
 Table 7.1: Water Boundary Conditions and Hydraulic Analysis Summary

List of Appendices

- Appendix A: Site Plan
 Appendix B: Sanitary Servicing Information
 Appendix C: Stormwater Management Calculations
 Appendix D: Water Servicing Information
 Appendix E: Servicing Study Guidelines Checklist
 Appendix F: Pre-consultation Meeting Minutes

List of Drawings

Notes and Details	120144-ND
General Plan of Services	120144-GP
Grading and Erosion Sediment Control Plan	120144-GR
Erosion and Sediment Control Plan	120144-ESC
Stormwater Management Plan	120144-SWM

1.0 INTRODUCTION

Novatech has been retained by Claridge Homes to prepare a Servicing and Stormwater Management Report for the proposed residential development located 1200 Maritime Way within the City of Ottawa. The site is located between Maritime Way and Highway 417 and is part of the Kanata Town Centre – Central Business District (KTC-CBD). The purpose of this report is to support the site plan application for the subject development. **Figure 1** Key Plan shows the site location.

2.0 EXISTING CONDITIONS

The subject site has an approximate area of 1.24 hectares and is currently undeveloped. The site is bound by Maritime Way and Townplace Suites to the north, Vacant Land to the East, Highway 417 to the south and Timberwalk Retirement Home to the West. The site is generally flat with a gradual slope from the south to the north. The site currently contains a number of fill piles ranging in 1-2m in height in the southern portion of the site from previous development activities within the Business District. It should be noted that the Northern portion of the site also once contained a stormwater management pond which has since been filled in. **Figure 2** depicts the existing site conditions.

The Subject site is part of the Kanata Town Centre, Central Business District which was designed by J.L. Richards and design information is provided in the following reports:


- Kanata Town Centre, Central Business District, Stormwater Management Report, J.L. Richards, January 1999 (Referenced as JLR Report)
- Servicing Brief (Revised) – Kanata Town Centre Central Business District Subdivision, Technical Memorandum, J.L. Richards, June 13, 2012
- Kanata Town Centre Central Business District Master Design Sheet Update – Sanitary Peak Flows Block 4, Block 5 and Block west of Block 9 (Zone 122), J.L. Richards, August 18, 2017 (Referenced as JLR Memo).

3.0 PROPOSED DEVELOPMENT

The proposed development will include two (2) apartment buildings interconnected by a central access and a joint underground parking structure. The proposed buildings will be referred to the East Tower and West Tower for the remainder of the report. It is proposed to develop the site in two (2) phases with Phase 1 including the West Tower, central entrance, and the parking structure outside the footprint of the East Tower, and Phase 2 including the East tower and the parking structure below.

The West Tower will be a total of thirty (30) storeys, complete with a seven (7) storey podium, and a total of 313 units. The East Tower will be a total of twenty-eight (28) storeys, complete with a seven (7) storey podium with a total of 302 units, and 400m² of commercial area. The overall development will provide 634 parking spaces. **Figure 3** shows the proposed development.

Access to the site will be provided from the proposed central entrance from Maritime Way.



M:\2020\120144\CAD\Design\120144-KP.dwg, KP, May 30, 2022 - 7:26pm, rgood



Engineers, Planners & Landscape Architects
 Suite 200, 240 Michael Cowpland Drive
 Ottawa, Ontario, Canada K2M 1P6

Telephone (613) 254-9643
 Facsimile (613) 254-5867
 Website www.novatech-eng.com




1200 MARITIME WAY
 CITY OF OTTAWA

KEYPLAN

SCALE N.T.S.

DATE	JOB	FIGURE
MAY 2022	120144	1

M:\2020\120144\CAD\Design\Figures\Design Brief\120144-EXC.dwg, EXC, May 30, 2022 - 5:56pm, rgood




NOVATECH

Engineers, Planners & Landscape Architects
 Suite 200, 240 Michael Cowpland Drive
 Ottawa, Ontario, Canada K2M 1P6

Telephone (613) 254-9643
 Facsimile (613) 254-5867
 Website www.novatech-eng.com



1200 MARITIME WAY
 CITY OF OTTAWA

EXISTING CONDITIONS PLAN



DATE	JOB	FIGURE
MAY 2022	120144	2

I:\novatech\2018\nova2\2020\120144\CAD\Design\Figures\Design Brief\120144-PRSP.dwg, PRSP, May 30, 2022 - 7:35pm, rgood



NOVATECH

Engineers, Planners & Landscape Architects
 Suite 200, 240 Michael Cowpland Drive
 Ottawa, Ontario, Canada K2M 1P6

Telephone (613) 254-9643
 Facsimile (613) 254-5867
 Website www.novatech-eng.com

1200 MARITIME WAY
 CITY OF OTTAWA

PROPOSED SITE PLAN

SCALE 1 : 750

DATE	JOB	FIGURE
APRIL 2023	120144	3

4.0 SITE CONSTRAINTS

A geotechnical investigation was completed by Paterson Group Inc. and a report prepared entitled 'Geotechnical Investigation, Proposed High-Rise Development', Report PG5281-1, dated July 16, 2020. The report included the following recommendations:

- Inferred bedrock surface was encountered at depths ranging from approximately 3.7 m at the west end of the site, descending to depths of approximately 16.2 m on the east end of the site.
- The long-term groundwater table can be expected at approximately 4 to 5 m below ground surface. It should also be noted that groundwater levels are subject to seasonal fluctuations. Therefore, the groundwater level could vary at the time of construction.
- Due to the presence of the silty clay deposit, a permissible grade raise restriction of 2 m is recommended for grading at the subject site. If higher than permissible grade raises are required, preloading with or without a surcharge, lightweight fill, and/or other measures should be investigated to reduce the risks of unacceptable long-term post construction total and differential settlements.
- The excavation side slopes above the groundwater level extending to a maximum depth of 3 m should be excavated at 1H:1V or shallower. The shallower slope is required for excavation below groundwater level. The subsurface soils are considered to be a Type 2 and 3 soil according to the Occupational Health and Safety Act and Regulations for Construction Projects.
- A temporary Ministry of Environment, Conservation and Parks (MECP) permit to take water (PTTW) may be required if more than 400,000 L/day of ground and/or surface water are to be pumped during the construction phase. At least 4 to 5 months should be allowed for completion of the application and issuance of the permit by the MECP.
- For typical ground or surface water volumes being pumped during the construction phase, typically between 50,000 to 400,000 L/day, it is required to register on the Environmental Activity and Sector Registry (EASR). A minimum of two to four weeks should be allotted for completion of the EASR registration and the Water Taking and Discharge Plan to be prepared by a Qualified Person as stipulated under O.Reg. 63/16. If a project qualifies for a PTTW based upon anticipated conditions, an EASR will not be allowed as a temporary dewatering measure while awaiting the MECP review of the PTTW application.

5.0 SANITARY SEWER

There is an existing 825mm diameter sanitary sewer within the Maritime Way right-of-way along the frontage of the proposed development. It is proposed to service the East and West towers with individual 200mm services. The East Tower service will connect directly to the existing sewer within the Maritime Way right-of-way. The West tower will be serviced by connecting to the existing private service for the neighboring Timberwalk Retirement Home, which ultimately discharges to the Maritime Way sewer.

Sanitary flows for the proposed development were calculated using criteria from Section 4 of the City of Ottawa Sewer Design Guidelines as follows:

- Residential Average Flow = 280 L/capita/day
- 1 Bed apartment = 1.4 Person/unit
- 2 Bed apartment = 2.1 Person/unit
- Commercial flow = 125 L/seat/day
- Residential Peaking Factor = Harmon Equation (max peaking factor = 4.0)
- Commercial Peaking Factor = 1.0
- Peak Extraneous Flows (Infiltration) = 0.33L/s/ha

The peak sanitary flow including infiltration for the proposed development was calculated to be 11.83 L/s with 6.03 L/s for the West Tower, and 5.80L/s for the East Tower. Detailed sanitary flow calculations are provided in **Appendix B** for reference.

The existing 825 mm diameter sanitary trunk sewer on Maritime Way was designed by J.L. Richards in 1998 to accommodate the development of the KTC-CBD subdivision and upstream lands. At the time of the original design of the trunk sewer, the land parcels were designated for commercial use and the sanitary flows were estimated using 50,000 L/ha/day per Ministry guidelines. Subsequently, land uses for various blocks have changed to include residential use.

The original sanitary sewer design sheet for the 825mm diameter trunk sewer has been revised by J.L. Richards within the JLR Memo and is included in **Appendix C** for reference. The JLR Memo included a change in land use for Block 122 (Claridge lands at 1250 Maritime Way) as well as Blocks 4 and 5 east of Maritime Way and north of the stormwater management facility. J.L. Richards noted an increase in the theoretical design flows at the junction of Teron Road and Campeau Drive from 475.94 L/sec to 480.24 L/sec, with a potential capacity of 838.6 L/s.

The proposed site was designated as part of Block 9 in the above analysis and was assumed to be a commercial site with a flow of 50,000L/ha/day. With an area of 1.23ha which equates to an assumed peaked flow of 1.07L/s. Thus, the proposed development will result in an increase of 10.76L/s when compared to the previous design.

In addition to the proposed development, other developments have since been constructed that will impact the capacity of the downstream system. As such we preformed a review of the downstream system, utilizing the available reports and aerial mapping data under two (2) scenarios. The first scenario utilized the same design criteria as the original JLR design. The second scenario was preformed using the current City of Ottawa Guidelines listed above.

The first analysis using the original design guidelines indicates that several downstream pipes would be surcharging with a maximum of 109% of the available pipe capacity. Although the original design parameters were highly conservative which is why the City of Ottawa has since revised the standards.

Utilizing the current design guidelines indicates that all pipes in the downstream system will have capacity with the worst pipe having a flow of 93% of the pipe capacity. It should be noted that even the current design standards are conservative and are not representative of the real-world flow values.

As such we do not anticipate any negative impacts due to the proposed development. Refer to **Appendix C** for detailed calculations.

6.0 STORM SEWER AND STORMWATER MANAGEMENT

There is an existing 1650mm diameter storm sewer within the Maritime Way right-of-way fronting the proposed development. There is also an existing 375mm diameter private storm sewer on the adjacent Timber walk Retirement home property to the west, which ultimately discharges to the 1650mm sewer in Maritime Way. It is proposed to service the subject development with connections to both the existing 1650mm Storm Sewer and the private 375mm sewer. In total there are four (4) proposed connections; one (1) connection to the private 375mm sewer and three (3) connections to the existing 1650mm sewer. The connection to the private sewer will be an uncontrolled 300mm diameter foundation drainage connection for the West Tower. The three (3) connections to the 1650mm sewer include: a 300mm diameter foundation drain connection for the East Tower, a controlled 375mm diameter rear yard drainage system, and a controlled 450mm diameter cistern outlet. Refer to the General Plan of Services (120144-GP) for details.

Through correspondence with the City of Ottawa it is understood that the existing hydraulic Grade line (HGL) within the storm sewer fronting the site varies in elevation from 94.30-94.40m. As such it is proposed to place the service connection inverts at or above the existing HGL at the proposed building connections to mitigate potential backflow issues. It is also proposed to provide a pump within the proposed Cistern maximize the available storage while avoiding potential tailwater issues. Refer to **Appendix C** for details.

6.1 Storm Water Management Criteria

Stormwater management (SWM) design criteria for the proposed development were established by the City of Ottawa Sewer Design Guidelines (October 2012), and the JLR Report. The SWM design criteria are as follows:

- Control post-development peak flows up-to and including the 100-year storm event to the allowable release rate. Provide on-site water quantity control for all flow in excess of the allowable release rate. The allowable release rate is to be determined by applying the following parameters to the site area:
 - A runoff coefficient of 0.8 (refer to Dwg 15712-STM in **Appendix C**)
 - A time of concentration of 20 minutes
 - A 5-year intensity using the City of Ottawa Intensity-Duration-Frequency (IDF) curves
- Minimize the impact on the downstream receiving watercourses by minimizing the potential erosion and volume of sediment entering the watercourses both on a temporary basis (during construction) and on a permanent basis.
- Provide guidelines to ensure that site preparation and construction is in accordance with the current Best Management Practices for Erosion and Sediment Control.

6.2 Existing Site Drainage

As mentioned previously the site is currently undeveloped and contains several fill piles ranging 1-2m in height in the southern portion of the site. The site generally drains towards Maritime Way, with a small amount of drainage directed towards the highway 416 corridor due to obstructions caused by the fill piles.

6.3 Quantity Control

The allowable release rate for the 1.24 ha site was calculated to be 193.4 L/s based on the SWM criteria provided within the JLR report.

Design Storms

The design storms are based on City of Ottawa design storms. Design storms were used for the 5 and 100-year return periods (i.e. storm events).

Model Parameters

Post-development catchments were modelled based on the proposed site plan and grading as shown on **Drawing 120144-SWM**, within **Appendix C**. All the sub-catchments over proposed underground parking areas are assumed to be 100% impervious. The building roofs were assumed to have no depression storage.

The site has been divided into six (6) drainage areas for the post development condition. The drainage areas are as follows:

Area A-01, R-01, R-02

- Flows from the proposed central access, West Tower Roof and East Tower Roof will be conveyed to the existing storm sewer in Maritime Way. These flows will be captured by area drains, and roof drains which will be conveyed to a proposed cistern under the main entrance within the P1 level of underground parking garage. Flows from the cistern to the existing sewer in Maritime Way will be pumped to the proposed service, where the flows will drain by gravity to the existing sewer system. The pump (to be designed by the mechanical consultant) is required to convey flow at 133 L/s. A “stand-by” pump will be provided for emergency and/or maintenance purposes. An emergency back-up power supply will also be provided. The storm service will be equipped with a backflow prevention device to protect the building from any potential sewer back-ups. Storage will be provided for storms up to and including the 100-year event within the cistern. Flows in excess of the 100-year event will overflow through a proposed 150mm overflow pipe, and a vented lid will be provided on the tank for emergencies which will convey flows directly to the Maritime Way right-of-way.

Area A-02:

- Flows from the proposed landscaped area on the southern portion of the property will be captured by a proposed storm system consisting of landscape drains, and catchbasin manholes which will convey flows to the existing Maritime Way sewer system. The proposed system will include a 152mm orifice and will store flows within the underground pipe system. Flows in excess of the 100-year event will overflow through the catch basin lids and be conveyed through the swale system to Maritime Way Right-of-way.

Area D-01:

- The drainage along the frontage of the property will flow uncontrolled to the Maritime Way Right of way

Area D-02:

- A small portion of the landscaped area at the rear of the East Tower will drain uncontrolled to the Highway 416 corridor.

Table 6.1 below summarizes the flow, storage required, and storage provided for each of the site drainage areas.

Table 6.1 Stormwater Management Summary

Area ID	Area (ha)	1.5 Year Weighted Cw	Orifice Size & Type	5 Year Storm Event			100 Year Storm Event		
				Flow (L/s)	Req Vol (cu.m)	Max. Vol. Provided (cu.m.)	Flow (L/s)	Req Vol (cu.m)	Max. Vol. Provided (cu.m.)
D-01	0.029	0.57	N/A	4.8	N/A	N/A	9.2	N/A	N/A
D-02	0.008	0.20	N/A	0.50	N/A	N/A	1.0	N/A	N/A
A-02	0.290	0.38	152mm Plate	32.0	9.65	27.91	49.6	23.81	27.91
A-01, R-01, R-02	0.910	0.90	Pump	133.0	62.57	294.41	133.0	205.72	294.4
Post-Development Release Rate				170.3			192.8		
Allowable Release Rate				193.4			193.4		

Refer to **Appendix C** for Rational and Modified Method calculations, and **Drawing STM** Post Development Drainage Area Plan.

6.4 Water Quality Control

The proposed site is tributary to the downstream SWM facility which has been designed to provide quantity and quality control for the proposed development as detailed within the JLR Report. Refer to **Appendix C** for excerpts.

6.5 Major Overland Flow Route

A major overland flow route will be provided for storms greater than the 100-year storm event. Stormwater will be directed to the Maritime Way right-of-way. The major overland system is shown on the Grading Plan (drawing 120144-GR).

7.0 WATERMAIN

There is an existing 600mm watermain, and a 200mm local watermain within the Maritime Way right-of-way fronting the development. It is proposed to provide servicing to the proposed development by connecting to the existing 200mm local watermain. Each tower will have its own individual twined services separated by an isolation valve to provide redundancy resulting in a total of four (4) proposed watermain connections.

The proposed water services will be sized to provide both the required domestic water demand and fire flow. Shut-off valves will be located on the proposed services at the property line and a water meter and remote water meter will be provided for each tower. The proposed buildings are to be sprinklered and will be equipped with Siamese connections located near the front entrance of each building, within 45m of a fire hydrant. Refer to the General Plan of Services drawing (120144-GP) for servicing details.

Water demand calculations have been calculated using criteria from Section 4 of the City of Ottawa Water Distribution Guidelines and the Ontario Building Code. The required fire demand was calculated using the Fire Underwriters Survey (FUS) Guidelines. The water demand and fire flow calculations are provided in **Appendix D** for reference. A summary of the water demand and fire flows are provided in **Table 7.1**.

Table 7.1: Domestic Water Demand Summary

Building	Population	Commercial Area (m ²)	Ave. Daily Demand (L/s)	Max. Daily Demand (L/s)	Peak Hour Demand (L/s)	Fire Flow (L/s)
West Tower	528	0	1.71	4.28	9.41	100
East Tower	504	400	1.78	4.30	9.37	117
Total Domestic Demands	1032	400	3.49	8.58	18.78	

Detailed calculations are included in **Appendix D**.

The above water demand information was submitted to the City for boundary conditions from the City's water model. These boundary conditions were used for analyzing the performance of the proposed and existing watermain systems for three theoretical conditions:

- 1) High Pressure check under Average Day conditions
- 2) Peak Hour demand
- 3) Maximum Day + Fire Flow demand.

Refer to **Table 7.2** for a summary of the proposed boundary conditions and hydraulic analysis.

Table 7.2: Water Boundary Conditions and Hydraulic Analysis Summary

Criteria	Head (m)	Pressure ¹ (psi)	Pressure Requirements (psi)
Connection 1- West Tower (200mm dia. Maritime Way)			
Max HGL	161.3	94.9	< 80psi
Min HGL	156.1	87.5	> 40psi
Max Day + Fire Flow	148.6	76.8	> 20psi
Connection 2- East Tower (200mm dia. Maritime Way)			
Max HGL	161.3	95.3	< 80psi
Min HGL	156.1	87.9	> 40psi
Max Day + Fire Flow	142.8	69.0	> 20psi

¹Pressure based on service entry elevation of 94.58m for connection #1 and 94.25m for Connection #2

The hydraulic analysis indicates that the system can provide adequate pressures and flow to meet the domestic and fire flow requirements for the site. As the above pressure are above 80 psi pressure reducing valves will be required for the site. Refer to **Appendix D** for detailed water demand calculations, and City of Ottawa boundary conditions.

8.0 EROSION AND SEDIMENT CONTROL

Temporary erosion and sediment control measures will be implemented on-site during construction in accordance with the Best Management Practices for Erosion and Sediment Control. This includes the following temporary measures:

- Filter socks (catchbasin inserts) will be placed in existing and proposed catchbasins and catchbasin manholes, and will remain in place until vegetation has been established and construction is completed;
- Silt fencing will be placed along the surrounding construction limits;
- Mud mats will be installed at the site entrances;
- Strawbale or rock check dams will be installed in swales and ditches;
- The contractor will be required to perform regular street sweeping and cleaning as required, to suppress dust and to provide safe and clean roadways adjacent to the construction site;

Erosion and sediment control measures should be inspected daily and after every rain event to determine maintenance, repair or replacement requirements. Sediments or granulars that enter site sewers shall be removed immediately by the contractor. These measures will be implemented prior to the commencement of construction and maintained in good order until vegetation has been established. Refer to the Erosion and Sediment Control Plan (drawing 120144-ESC) for additional information.

9.0 CONCLUSIONS

Watermain

The analysis of the existing and proposed watermain network confirms the following:

- The four (4) proposed 200mm dia. watermain services which connect to the existing 200mm dia. watermain in Maritime Way will service the proposed development.
- There are adequate pressures in the existing watermain infrastructure to meet the required domestic demands for the development, and pressure reducing valves will be required.
- There is adequate flow to service the proposed fire protections system.

Sanitary Servicing

The analysis of the existing and proposed sanitary system confirms the following:

- It is anticipated that there is adequate capacity within the existing sanitary infrastructure to service the proposed development based on the information provided in the existing JLR Memo, and the available mapping data.

Stormwater Management

The following provides a summary of the storm sewer and stormwater management system:

- The proposed storm sewer system is to connect to the existing 1650mm diameter storm sewer in Maritime Way.
- Underground storage is to be provided within the storm sewer system and underground Cistern.
- Inlet control devices and underground storage have been designed to ensure no static ponding is achieved in the 2-year event.
- Storm flows will be attenuated through the implementation of inlet control devices.
- Parking lots have been graded to ensure that static ponding depths do not exceed 0.30m.
- As per existing conditions a major overland flow route is provided to Maritime Way.
- Quality control of stormwater will be provided in the downstream SWM facility.

Erosion and Sediment control

- Erosion and sediment control measures (i.e. filter fabric, catchbasin inserts, silt fences, etc.) will be implemented prior to construction and are to remain in place until vegetation is established.

Please contact the undersigned should you have questions or require additional information.


NOVATECH

Prepared by:



Anthony Mestwarp, P.Eng
Project Engineer | Land Development


Reviewed by:



Greg MacDonald, P.Eng.
Director | Land Development and Public Sector
Infrastructure

APPENDIX A

Site Plan



KEY PLAN

ZONE AM10		
PROVISION	REQUIRED	PROVIDED
Min Lot Width	no minimum	+/- 59.95 m
Min Lot Area	no minimum	+/- 12 808 m ²
Max Building Height	67m	+/- 93.5 m
Min Front Yard Setback	no minimum	7.50 m / 3.09 m
Min Corner Side Yard Setback	no minimum	5.24 m
Min FSI	2	+/- 4.53
Min Interior Side Yard Setback	no minimum	15.40 m / 15.13 m

SITE AREA :		+/- 12 808 m ² (To be confirmed by surveyor)
SITE COVERAGE :		+/- 2 489 m ² (East Tower)
		+/- 1 968 m ² (West Tower)
		Total +/- 4 457 m ² = 34.8 %
GROUND PARKING AREA :		+/- 1 702 m ² = 13.3 %
LANDSCAPED AREA (EXCLUDING PARKING) :		+/- 6 649 m ² = 51.9 %

RENTAL - EAST TOWER

PROPOSED GROSS FLOOR AREA :	+/- 22 475 m ²
BASEMENT G.F.A. :	+/- 1 507 m ²
GROUND FLOOR G.F.A. :	+/- 1 122 m ²
RENTAL FLOORS G.F.A. (2nd to 28th floor) :	+/- 19 845 m ²
PRIVATE AMENITY AREA (G.F.A.) :	+/- 1 997 m ²
COMMUNAL AMENITY AREA :	+/- 1 197 m ²
NUMBER OF FLOORS AND BUILDING HEIGHT :	28 FLOORS + MECH. / +/- 87.50m
DWELLING UNITS :	302
PARKING STALLS :	303 (288 INSIDE / 4 VIS. OUTSIDE + 11 VIS. INSIDE)
PROVIDED BICYCLE STALLS :	151 (143 INSIDE / 8 OUTSIDE)

NUMBER OF SUITES REQUIRED TO BE BARRIER-FREE :
302 UNITS = 45 UNITS HAVE TO BE BARRIER-FREE
THEY WILL BE DISTRIBUTED BETWEEN THE 28 FLOORS

RENTAL - WEST TOWER


PROPOSED GROSS FLOOR AREA :	+/- 25 617 m ²
BASEMENT G.F.A. :	+/- 631 m ²
GROUND FLOOR G.F.A. :	+/- 437 m ²
RENTAL FLOORS G.F.A. (2nd to 28th floor) :	+/- 24 548 m ²
PRIVATE AMENITY AREA (G.F.A.) :	+/- 1 232 m ²
COMMUNAL AMENITY AREA :	+/- 1 054 m ²
NUMBER OF FLOORS AND BUILDING HEIGHT :	30 FLOORS + MECH. / +/- 93.50m
DWELLING UNITS :	313
PARKING STALLS :	314 (299 INSIDE / 14 VIS. OUTSIDE + 1 VIS. INSIDE)
PROVIDED BICYCLE STALLS :	157 (150 INSIDE / 7 OUTSIDE)

NUMBER OF SUITES REQUIRED TO BE BARRIER-FREE :
313 UNITS = 47 UNITS HAVE TO BE BARRIER-FREE
THEY WILL BE DISTRIBUTED BETWEEN THE 30 FLOORS

- FOR EXISTING SITE CONDITIONS, SEE SURVEY PLAN BY ANNIS, O'SULLIVAN, VOLLEBECK LTD., SUBMITTED SEPARATELY.
- FOR NEW GRADES AND SITE SERVICES, SEE CIVIL ENGINEERING PLAN BY NOVATECH ENGINEERING CONSULTANTS, SUBMITTED SEPARATELY.
- FOR PROPOSED VEGETATION AND LANDSCAPE INFORMATION, SEE LANDSCAPE PLAN BY JAMES B. LENNOX & ASSOCIATES, SUBMITTED SEPARATELY.



SNOW WILL BE HAULED OFF SITE
GARBAGE / RECYCLING PICK-UP BY PRIVATE COMPANY



NOTES GÉNÉRALES / General Notes
1. Ces documents d'architecture sont la propriété exclusive de NEUF architectes et ne pourront être utilisés, reproduits ou copiés sans autorisation écrite préalable. / These architectural documents are the exclusive property of NEUF architects and cannot be used, copied or reproduced without written pre-authorization.
2. Les dimensions apparaissant sur ces documents doivent être vérifiées par l'entrepreneur avant le début des travaux. / All dimensions which appear on the documents must be verified by the contractor before to start the work.
3. Veuillez aviser l'architecte de toute dimension erronée et/ou divergences entre ces documents et ceux des autres professionnels. / The architect must be notified of all errors, omissions and discrepancies between these documents and those of the others professionals.
4. Les dimensions sur ces documents doivent être lues et non mesurées. / The dimensions on these documents must be read and not measured.


STRUCTURE Structural
Goodeve Structural Inc.
1877, Arga Drive, Ottawa ON K2E 7Z7
1 613 226-6556 goodevestructural.ca

ARCHITECTURE DE PAYSAGE Landscape Architect
James B. Lennox & Associates
3332, Carling Avenue, Ottawa ON K2H 5A8
1 613 722 5168 jbla.ca

CIVIL Civil
Novatech Eng. Consultants Ltd.
240, Metcalfe Cleveland Drive, Suite 200, Ottawa ON K2M 1P6
1 613 234 9643 novatech-eng.com

ARCHITECTES Architect
NEUF Architect(es) SENCRL
630, boul. René-Lévesque O. 33e étage, Montréal QC H3B 1S6
1 514 847 1117 NEUFarchitectes.com

SCÉAU / Seal



CLIENT Client
CLARIDGE HOMES

OUVRAGE Project
1200 MARITIME WAY (KANATA RENTAL)

EMPLACEMENT Location NO PROJET No.
OTTAWA 12371.00

NO	REVISION	DATE (aa-mm-jj)
A	FOR COMMENTS	2020.05.28
B	FOR COMMENTS	2020.06.05
C	FOR COMMENTS	2020.07.23
D	IN PROGRESS	2020.09.16
E	SITE PLAN COORDINATION	2020.12.08
F	SITE PLAN COORDINATION	2020.12.16
G	SITE PLAN COORDINATION	2021.02.22
H	PER TRANSPORTATION COMMENTS	2021.05.18
I	PER CITY COMMENTS	2021.05.27
J	PER CITY COMMENTS	2021.11.11
K	REVISED SITE PLAN	2022.03.28
L	REVISED SITE PLAN - COORDINATION	2022.04.07
M	PER CITY COMMENTS	2022.06.03
N	FOR COMMENTS	2023.04.13
O	FOR COMMENTS	2023.04.17
P	SITE PLAN APPROVAL	2023.04.27

DESSINÉ PAR Drawn by PV VERIFIÉ PAR Checked LH
DATE (aa.mm.jj) 05/28/20 ECHELLE Scale 1 : 300
TITRE DU DESSIN Drawing Title

SITE PLAN AT GROUND FLOOR LEVEL



REVISION Revision NO. DESSIN Dwg Number
P A203
#18348

C:\Fichiers Revit\Local\12371_ARCH_OPTION_9_R20_pascalvendelle.rvt

D07-12-21-0017

APPENDIX B

Sanitary Sewer Servicing Information



LEGEND



DRAINAGE AREA (ha)
DRAINAGE AREA ID
NO. OF UNITS / TOTAL POPULATION



SANITARY DRAINAGE AREA BOUNDARY



PROPOSED SANITARY SEWER C/W MANHOLE



EXISTING SANITARY MANHOLE & SEWER




Engineers, Planners & Landscape Architects
Suite 200, 240 Michael Cowpland Drive
Ottawa, Ontario, Canada K2M 1P6

Telephone (613) 254-9643
Facsimile (613) 254-5867
Website www.novatech-eng.com

CITY OF OTTAWA
1200 MARITIME WAY

**SANITARY DRAINAGE
AREA PLAN**



DATE	JOB	FIGURE
APRIL 2023	120144	SAN

\\novatech2018\novatech\2020\120144\CAD\Design\120144 - SAN.dwg, SAN, Apr 28, 2023 - 4:35pm, amestwarp

Novatech Project #: 120144
 Project Name: 1200 Maritime Way
 Date Prepared: 5/30/2022
 Date Revised: 4/28/2023
 Input By: Anthony Mestwarp
 Reviewed By: Greg Macdonald
 Drawing Reference: 120144-SAN

Legend: PROJECT SPECIFIC INFO
 USER DESIGN INPUT
 CUMULATIVE CELL
 CALCULATED DESIGN CELL OUTPUT



LOCATION			DEMAND												DESIGN CAPACITY												
AREA	FROM MH	TO MH	RESIDENTIAL FLOW						COMMERCIAL FLOW					EXTRANEIOUS FLOW			PROPOSED SEWER PIPE SIZING / DESIGN										
			1 Bed Apartment	2 Bed Apartment	POPULATION (in 1000's)	CUMULATIVE POPULATION (in 1000's)	PEAK FACTOR M	AVG POPULATION FLOW (L/s)	PEAKED DESIGN POP FLOW (L/s)	COMMERICAL AREA (m ²)	CUMULATIVE COMMERICAL AREA (m ²)	DESIGN COMMERICAL FLOW (L/s)	COMMERICAL PEAK FACTOR	PEAKED COMMERICAL FLOW	Total Area (ha.)	Accum. Area (ha.)	DESIGN EXTRAN. FLOW (L/s)	TOTAL DESIGN FLOW (L/s)	PIPE LENGTH (m)	PIPE SIZE (mm) AND MATERIAL	PIPE ID ACTUAL (m)	ROUGH. (n)	DESIGN GRADE (%)	CAPACITY (L/s)	FULL FLOW VELOCITY (m/s)	Qpeak Design / Qcap	
CROISSANT FRANCOISE (SANMH 202)																											
WEST	STUB	302	185	128	0.528	0.528	3.37	1.71	5.76	0.000	0.000	0.00	1.00	0.00	0.82	0.82	0.27	6.03	3.7	200 PVC	0.203	0.013	2.00	48.4	1.49	12.5%	
CROISSANT FRANCOISE (SANMH 205)																											
EAST	STUB	301	186	116	0.504	0.504	3.38	1.63	5.52	400.000	400.000	0.14	1.00	0.14	0.42	0.42	0.14	5.80	3.6	200 PVC	0.203	0.013	1.00	34.2	1.06	17.0%	
EAST	301	MAIN			0.000	0.504	3.38	1.63	5.52		400.000	0.14	1.00	0.14	0.00	0.42	0.14	5.80	15.4	200 PVC	0.203	0.013	1.00	34.2	1.06	17.0%	
TOTAL			371	244	1.032	1.032				400.000	400.000				1.24												

Design Parameters:

- Residential Flows
 - 1 Bed Apartment: 1.4 Person/ Unit
 - 2 Bed Apartment: 2.1 Person/ Unit
- Commercial Flow
 - Office: 125 L/seat³/day (Assume 1 seat/4m²)
 - q Avg capita flow: 280 L/per/day
- M = Harmon Formula (maximum of 4.0)
- K = 0.8
- Commercial Peak Factor
 - area > 20% of development: 1.5
 - area < 20% of development: 1.0
- Extraneous Flows = 0.33 L/sec/ha

CAPACITY EQUATION
 $Q_{full} = (1/n) A R^{(2/3)} S_o^{(1/2)}$

Where : Q full = Capacity (L/s)

n = Manning coefficient of roughness (0.013)
 A = Flow area (m²)
 R = Wetted perimeter (m)
 So = Pipe Slope/gradient

LOCATION			RESIDENTIAL												COMMERCIAL/INSTITUTIONAL			PLUGGED FLOW		R + C		PROPOSED SEWER									
STREET	FROM MH	TO MH	NUMBER OF UNITS									INDIVIDUAL		CUMULATIVE		PEAK FACTOR (M)	POPUL. FLOW L/S	ACTUAL AREA ha	CUMM AREA ha	COMM FLOW l/s	FLOW l/s	COMM FLOW l/s	PEAK EXTR. FLOW	PEAK DESIGN FLOW	LENGTH (m)	PIPE SIZE (mm)	SLOPE %	CAPACITY (L/s)	FULL FLOW VELOCITY (m/s)	RATIO (Q/Qfull)	
			Houses			Extended Care		Hotel/Apt				POPUL. People	AREA ha	POPUL. People	AREA ha								l/s	L/S							
			Singles	Stacks	Towns	No. Units	Act Pop	No. Units	Act. Pop	Equ. Pop																					
B	85	87	19									65	1.19	65	1.19	4.000	1.05							0.340	1.39	116.9	250	0.40	37.611	0.77	4%
	87	89			24							65	0.82	130	2.01	4.000	2.11							0.573	2.68	116.7	250	1.41	70.614	1.45	4%
A	89	84			12							32	0.35	5859	43.97	3.181	75.49		28.985	25.161		163.820	20.792	285.26	79.0	825	0.12	497.249	0.94	57%	
C	80	82	19									65	1.08	65	1.08	4.000	1.05							0.308	1.36	120.0	250	0.40	37.611	0.77	4%
	82	84			25							67	0.83	132	1.91	4.000	2.14							0.544	2.68	118.5	250	1.20	65.143	1.34	4%
A	84	79			14							38	0.54	6029	46.42	3.169	77.39		28.985	25.161		163.820	21.490	287.86	79.0	825	0.12	497.249	0.94	58%	
D	75	76			17							46	0.37	46	0.37	4.000	0.75							0.105	0.85	57.0	250	0.40	37.611	0.77	2%
	76	77			20							54	0.29	100	0.66	4.000	1.62							0.188	1.81	78.4	250	0.40	37.611	0.77	5%
	77	79			13							35	0.63	135	1.29	4.000	2.19							0.368	2.56	117.7	250	0.81	53.521	1.10	5%
Park Easement	79	67											0.98	6164	48.69	3.160	78.89		28.985	25.161		163.820	22.099	289.97	55.0	825	0.12	497.249	0.94	58%	
	67	66			6							16	0.33	6180	49.02	3.159	79.07		28.985	25.161		163.820	22.192	290.25	70.0	825	0.12	497.249	0.94	58%	
BELLROCK DRIVE	70	73		12	14							70	2.56	70	2.56	4.000	1.13							0.728	1.86	87.2	250	0.40	37.611	0.77	5%
	73	74			12							32	0.54	102	3.1	4.000	1.65							0.882	2.53	80.3	250	0.40	37.611	0.77	7%
EASEMENT	74	62											0.31	102	3.41	4.000	1.65							0.970	2.62	39.9	250	0.40	37.611	0.77	7%
CAMBRAV LANE	62	66			25							68	0.48	170	3.89	4.000	2.75							1.107	3.86	100.5	250	0.40	37.611	0.77	10%
BISHOPS MILLS WAY	66	65			9							24	0.53	6374	53.44	3.146	81.22		28.985	25.161		163.820	23.450	293.65	62.0	825	0.12	497.249	0.94	59%	
SOUTH OF HWY 7	EX.	65										7792	191.6	7792	191.6	3.061	96.63					37.720	37.720	53.648	188.00	50.2	900	0.11	600.412	0.95	31%
BISHOPS MILLS WAY	65	64			2							5		14171	245.04	2.803	160.91		28.985	25.161		201.540	77.083	464.70	17.0	900	0.11	600.412	0.95	77%	
EDENVALE DRIVE	59	60			8							22	0.50	22	0.50	4.000	0.36							0.141	0.50	77.0	200	1.40	38.808	1.25	1%
KETTLEBY STREET	60	61			22							59	0.62	81	1.12	4.000	1.31							0.315	1.63	103.6	250	0.40	37.611	0.77	4%
CAMBRAV LANE	58	61			5							14	0.41	14	0.41	4.000	0.23							0.115	0.34	74.5	200	0.70	27.441	0.88	1%
KETTLEBY STREET	61	64			25							68	0.42	163	1.95	4.000	2.64							0.549	3.19	105.0	250	0.90	56.416	1.16	6%
BISHOPS MILLS WAY	64	63			3							8		14342	246.99	2.798	162.55		28.985	25.161		201.540	77.632	466.88	13.0	900	0.11	600.412	0.95	78%	
	63	57			10							27	0.68	14369	247.67	2.797	162.81		28.985	25.161		201.540	77.823	467.33	64.9	900	0.11	600.412	0.95	78%	
TER. BUNGALOW Ph. 2	51	53		48								130	0.94	130	0.94	4.000	2.11							0.264	2.37	122.3	200	0.70	27.441	0.88	9%
	53	54		4								11		141	0.94	4.000	2.28							0.264	2.55	13.6	200	0.70	27.441	0.88	9%
	54	55											0.27	141	1.21	4.000	2.28							0.340	2.63	36.7	200	0.70	27.441	0.88	10%
BISHOPS MILLS WAY	55	56	11									37	0.81	178	2.02	4.000	2.88							0.568	3.45	107.1	250	0.40	37.611	0.77	9%
	56	57	7		12							56	0.65	234	2.67	4.000	3.79							0.751	4.54	101.5	250	0.60	46.063	0.95	10%
PARK	57	34			1							3	0.37	14606	250.71	2.790	165.07		28.985	25.161		201.540	78.678	470.45	53.5	900	0.11	600.412	0.95	78%	
	34	33			3							8		14614	250.71	2.790	165.15		28.985	25.161		201.540	78.678	470.53	50.3	900	0.11	600.412	0.95	78%	

LOCATION			RESIDENTIAL												COMMERCIAL/INSTITUTIONAL			PLUGGED FLOW		R + C		PROPOSED SEWER								
STREET	FROM MH	TO MH	NUMBER OF UNITS									INDIVIDUAL		CUMULATIVE		PEAK FACTOR (M)	POPUL. FLOW L/S	ACTUAL AREA ha	CUMM AREA ha	COMM FLOW l/s	FLOW l/s	COMM FLOW l/s	PEAK EXTR. FLOW	PEAK DESIGN FLOW	LENGTH (m)	PIPE SIZE (mm)	SLOPE %	CAPACITY (L/s)	FULL FLOW VELOCITY (m/s)	RATIO (Q/Qfull)
			Houses			Extended Care		Hotel/Apt				POPUL. People	AREA ha	POPUL. People	AREA ha								l/s	L/S						
			Singles	Stacks	Towns	No. Units	Act Pop	No. Units	Act. Pop	Equ. Pop																				
HAWSTONE	43	44		22							59	1.19	59	1.19	4.000	0.96							0.335	1.29	51.0	250	1.00	59.468	1.22	2%
	44	45		8							22	0.09	81	1.28	4.000	1.31							0.360	1.67	29.0	250	0.50	42.050	0.87	4%
EDENVALE	45	35										0.06	81	1.34	4.000	1.31							0.377	1.69	39.8	250	0.50	42.050	0.87	4%
BIRKENDALE DRIVE	35	36	7								24	1.18	105	2.52	4.000	1.70							0.709	2.41	93.2	250	0.37	36.173	0.74	7%
	36	37	13								44	0.79	149	3.31	4.000	2.41							0.931	3.35	77.1	250	0.37	36.173	0.74	9%
	37	33	2		3						15		164	3.31	4.000	2.66							0.931	3.59	17.9	250	0.40	37.611	0.77	10%
BIRKENDALE DRIVE	33	32			10						27	0.56	14805	254.58	2.784	166.96		28.985	25.161		201.540	79.767	473.43	72.7	900	0.11	600.412	0.95	79%	
TEESWATER STREET	30	31			16						43	0.66	43	0.66	4.000	0.70							0.186	0.88	75.1	250	0.40	37.611	0.77	2%
	31	32			19						51	0.41	94	1.07	4.000	1.52							0.301	1.82	77.9	250	0.40	37.611	0.77	5%
BIRKENDALE STREET	32	18			6						16	0.37	14915	256.02	2.781	168.01		28.985	25.161		201.540	80.172	474.88	44.4	900	0.11	600.412	0.95	79%	
	18	16			4						11		14926	256.02	2.780	168.11		28.985	25.161		201.540	80.172	474.99	44.4	900	0.11	600.412	0.95	79%	
COMMERCIAL PLAZA	19	17													4.000	0.00	0.520	0.520	0.451				0.146	0.60	26.5	150	0.90	14.448	0.83	4%
COLCHESTER SQUARE	17	16										0.10		0.10	4.000	0.00		0.520	0.451				0.174	0.63	33.2	250	0.40	37.611	0.77	2%
COLCHESTER SQUARE	16	15			10						27	0.56	14953	256.68	2.780	168.37		29.505	25.612		201.540	80.504	476.03	66.0	900	0.11	600.412	0.95	79%	
	15	14A			2						5		14958	256.68	2.779	168.42		29.505	25.612		201.540	80.504	476.07	25.8	900	0.11	600.412	0.95	79%	
ELSINORE LANE	39	28		32							86	0.53	86	0.53	4.000	1.39							0.149	1.54	56.7	250	1.00	59.468	1.22	3%
	28	24		18							49	1.47	135	2.00	4.000	2.19							0.563	2.75	43.0	250	0.40	37.611	0.77	7%
	24	23		12							32	0.14	167	2.14	4.000	2.71							0.602	3.31	34.0	250	0.40	37.611	0.77	9%
ELSINORE LANE	23	306		8							22	0.24	189	2.38	4.000	3.06							0.669	3.73	48.8	250	0.44	39.446	0.81	9%
ENDENVALE DRIVE	306	14-A										0.45	189	2.83	4.000	3.06							0.796	3.86	46.4	250	0.49	41.627	0.86	9%
COLCHESTER SQUARE	14-A	14											15147	259.51	2.774	170.21		29.505	25.612		201.540	81.300	478.66	14.7	900	0.11	600.412	0.95	80%	
	Church	14															0.520	0.520	0.451				0.146	0.60	35.0	150	1.00	15.229	0.87	4%
COLCHESTER SQUARE	14	11		4							11	0.16	15158	259.67	2.774	170.31		30.025	26.063		201.540	81.491	479.41	72.6	900	0.11	600.412	0.95	80%	
TERON	11	10											15158	259.67	2.774	170.31		30.025	26.063		201.540	81.491	479.41	29.6	900	0.11	600.412	0.95	80%	
	10	EX.										0.25	15158	259.92	2.774	170.31		30.025	26.063		201.540	81.562	479.48	72.3	900	0.11	600.412	0.95	80%	
TERON	O.P.P.	EX.																				0.780	0.780	0.78	100 FORCEMAIN					
TERON	EX.	EX. 2											15158	259.92	2.774	170.31		30.025	26.063		202.320	81.562	480.26	9.400	680.000	0.960	839.974	2.34	57%	

Notes:

LOCATION			RESIDENTIAL											COMMERCIAL/INSTITUTIONAL			PLUGGED FLOW		R + C		PROPOSED SEWER									
STREET	FROM MH	TO MH	NUMBER OF UNITS									INDIVIDUAL		CUMULATIVE		PEAK FACTOR (M)	POPUL. FLOW L/S	ACTUAL AREA ha	CUMM AREA ha	COMM FLOW l/s	FLOW l/s	COMM FLOW l/s	PEAK EXTR. FLOW	PEAK DESIGN FLOW	LENGTH (m)	PIPE SIZE (mm)	SLOPE %	CAPACITY (L/s)	FULL FLOW VELOCITY (m/s)	RATIO (Q/Qfull)
			Houses			Extended Care		Hotel/Apt				POPUL. People	AREA ha	POPUL. People	AREA ha								l/s	L/S						
			Singles	Stacks	Towns	No. Units	Act Pop	No. Units	Act. Pop	Equ. Pop																				

- As per Kanata Town Centre Sanitary Trunk Sewer Study revised March 27, 1996 by Robinson Consultants Inc.
- Park or open space area.
- Equivalent population base on 208 rooms and 20 staff members.
- Allowance for an ultimate flow of 188 l/s to provide flexibility in future development as per Kanata Town Centre Sanitary Trunk Study.
- Additional flow associated with hotel amenities including swimming pool with bathrooms and laundry as per design calculations for Block 1 provided by WSP (October 2016).
- Additional flow associated with overall amenities including beauty salon, staff, dining and laundry as per design calculations for 1250 Maritime Way (Timberwalk Retirement Home) provided by Novatech (July 31, 2017).

Design Parameters:

- $Q(p) = (P \times q \times M / 86,400)$
- $Q(d) = Q(p) + Q(e)$

Definitions:

P = Population
 q = Average per capita flow = 350 L/person/day
 M = Residential Peaking Factor (Harmon Formula from section 4.4.1 of the City Sewer Design Guidelines):
 $M = 1 + [14 / (4 + Pop / 1000)^{1/2}]^2 - 1$ (Maximum of 4.0)

Q(d) = Design Flow (L/sec)
 Q(p) = Population Flow (L/sec)
 Q(r) = Commercial Flow (L/sec)
 Q(e) = Extraneous Flow (L/sec) 0.28 l/s/ha

Units			
Single	3.4	pers/unit	
Town	2.7	pers/unit	
Hotel/ Apartmentt	1.8	pers/unit	
Retirement Home	1.6	pers/unit	
Commercial Flow	50000	L/ha/day	
Commercial Peak Factor	1.5		

**1200 Maritime Way
 SANITARY SEWER DESIGN SHEET**

Date	January 27, 2021				
Design	GMAC				
Job No.	wg. Referenc	Checked and Stamped:			
120144	120144-SAN	--			

1200 Maritime Way
 SANITARY SEWER DESIGN SHEET OF DOWNSTREAM SEWERS - OLD STANDARDS
 JOB# 120144



PENFIELD DR	911	910	1514		1359			118	212		9029	188	9029	188	2.999	109.68	11.23	11.230	9.748			55.78	175.21	64.8	600	610	0.14	239.676	0.83	73%		
																												0.000				
TRUNK	910	909											26674	477.72	2.528	273.12			64.395	55.898			202.320	151.79	683.13	56.4	600	610	1.02	646.934	2.24	106%
	909	908											26674	477.72	2.528	273.12			64.395	55.898			202.320	151.79	683.13	26.5	900	914	0.75	1635.562	2.52	42%
	908	907											26674	477.72	2.528	273.12	16.52	80.915	70.239			202.320	156.42	702.10	41.4	900	914	0.46	1280.900	1.97	55%	

- Notes:**
- As per Kanata Town Centre Sanitary Trunk Sewer Study revised March 27, 1996 by Robinson Consultants Inc.
 - Park or open space area.
 - Equivalent population base on 208 rooms and 20 staff members.
 - Allowance for an ultimate flow of 188 l/s to provide flexibility in future development as per Kanata Town Centre Sanitary Trunk Study.
 - Additional flow associated with hotel amenities including swimming pool with bathrooms and laundry as per design calculations for Block 1 provided by WSP (October 2016).
 - Additional flow associated with overall amenities including beauty salon, staff, dining and laundry as per design calculations for 1250 Maritime Way (Timberwalk Retirement Home) provided by Novatech (July 31, 2017).
 - JLR Spreadsheet up-dated to include development flows from 1200 Maritime Way. Reference Appendix A of Serviceability Report for 1250 Maritime Way attached in Appendix of 1200 Maritime Way Serviceability Report (Novatech January 28, 2021).

Design Parameters:

- $Q(p) = (P \times q \times M) / 86,400$
- $Q(d) = Q(p) + Q(e)$

Definitions:

P = Population
 q = Average per capita flow = 350 L/person/day
 M = Residential Peaking Factor (Harmon Formula from section 4.4.1 of the City Sewer Design Guidelines):
 $M = 1 + [14 / (4 + Pop / 1000)^{1/2}] * 1$ - (Maximum of 4.0)

Q(d) = Design Flow (L/sec)
 Q(p) = Population Flow (L/sec)
 Q(r) = Commercial Flow (L/sec)
 Q(e) = Extraneous Flow (L/sec) 0.28 l/s/ha

Units			
Single	3.4	pers/unit	
Town	2.7	pers/unit	
Hotel/ Apartment	1.8	pers/unit	
Retirement Home	1.6	pers/unit	
Commercial Flow	50000	L/ha/day	
Commercial Peak Factor	1.5		

1200 Maritime Way SANITARY SEWER DESIGN SHEET			
Date March 25, 2022			
Design	GMAC		
Job No.		wg. Referenc	Checked and Stamped:
120144		120144-SAN	--

1200 Maritime Way
 SANITARY SEWER DESIGN SHEET OF DOWNSTREAM SEWERS -CURRENT STANDARDS
 JOB# 120144



BIRKENDALE STREET	32	18		6		16	0.37	15947	257.26	2.201	113.76		27.759	1.000	8.996		201.540	94.06	418.35	44.4	900	914	0.11	626.373	0.96	67%			
	18	16		4		11		15958	257.26	2.201	113.82		27.759	1.000	8.996		201.540	94.06	418.41	44.4	900	914	0.11	626.373	0.96	67%			
COMMERCIAL PLAZA	19	17										0.520	0.520	1.500	0.253			0.17	0.42	26.5	150	152	0.90	15.073	0.84	3%			
COLCHESTER SQUARE	17	16					0.10		0.10				0.520	1.500	0.253			0.20	0.46	33.2	250	254	0.40	39.237	0.78	1%			
COLCHESTER SQUARE	16	15		10		27	0.56	15985	257.92	2.200	113.98		28.279	1.000	9.164		201.540	94.45	419.13	66.0	900	914	0.11	626.373	0.96	67%			
	15	14A		2		5		15990	257.92	2.200	114.01		28.279	1.000	9.164		201.540	94.45	419.16	25.8	900	914	0.11	626.373	0.96	67%			
ELSINORE LANE	39	28		32		86	0.53	86	0.53	3.409	0.95			1.000	0.000			0.17	1.12	56.7	250	254	1.00	62.039	1.24	2%			
	28	24		18		49	1.47	135	2.00	3.364	1.47			1.000	0.000			0.66	2.13	43.0	250	254	0.40	39.237	0.78	5%			
	24	23		12		32	0.14	167	2.14	3.340	1.81			1.000	0.000			0.71	2.51	34.0	250	254	0.40	39.237	0.78	6%			
ELSINORE LANE	23	306		8		22	0.24	189	2.38	3.326	2.04			1.000	0.000			0.79	2.82	48.8	250	254	0.44	41.152	0.82	7%			
ENDENVALE DRIVE	306	14-A					0.45	189	2.83	3.326	2.04			1.000	0.000			0.93	2.97	46.4	250	254	0.49	43.427	0.87	7%			
COLCHESTER SQUARE	14-A	14						16179	260.75	2.196	115.15		28.279	1.000	9.164		201.540	95.38	421.23	14.7	900	914	0.11	626.373	0.96	67%			
	Church	14										0.520	0.520	1.500	0.253			0.17	0.42	35.0	150	152	1.00	15.888	0.88	3%			
COLCHESTER SQUARE	14	11		4		11	0.16	16190	260.91	2.196	115.21		28.799	1.000	9.333		201.540	95.60	421.69	72.6	900	914	0.11	626.373	0.96	67%			
TERON	11	10						16190	260.91	2.196	115.21		28.799	1.000	9.333		201.540	95.60	421.69	29.6	900	914	0.11	626.373	0.96	67%			
	10	EX.					0.25	16190	261.16	2.196	115.21		28.799	1.000	9.333		201.540	95.69	421.77	72.3	900	914	0.11	626.373	0.96	67%			
TERON	O.P.P.	EX.												1.500	0.000	0.780	0.780		0.78	100 FORCEMAIN									
CAMPEAU / TERRON	11833	EX.2		4		14	7.5	14	7.5	3.520	0.16	19.20	19.200	1.500	9.333	0.000	0.000	8.81	18.30	94.7	250	254	1.84	84.153	1.68	22%			
TERON	EX.	EX. 2						16204	268.66	2.196	115.30		47.999	1.000	15.555		202.320	104.50	437.67	9.4	675	686	0.46	594.765	1.63	74%			
	EX.2	***						16204	268.66	2.196	115.30		47.999	1.000	15.555		202.320	104.50	437.67	42.8	675	686	0.77	769.506	2.11	57%			
	***	11837						16204	268.66	2.196	115.30		47.999	1.000	15.555		202.320	104.50	437.67	40.7	675	686	0.57	662.070	1.81	66%			
	11837	11859				194	349	349	349	2.19	16553	270.85	2.188	117.38		50.189	1.000	16.265		202.320	105.94	441.91	89.9	675	686	0.39	547.645	1.50	81%
TERRON (SE)	11841	11859				42	76	76	76	1.12	76	1.12	3.420	0.84		1.00	0.000		0.37	1.21	50.7	250	254	0.410	39.724	0.79	3%		
SALTER CRES.	11859	11839						16629	271.97	2.187	117.83		50.189	1.000	16.265		202.320	106.31	442.73	50.0	675	686	4.86	1933.235	5.29	23%			
	11839	11840						16629	271.97	2.187	117.83		50.189	1.000	16.265		202.320	106.31	442.73	40.3	675	686	0.40	554.621	1.52	80%			
	11840	11844		105		284	1.78	16912	273.75	2.181	119.51		50.189	1.000	16.265		202.320	106.90	445.00	70.5	675	686	0.40	554.621	1.52	80%			
PENFIELD DR.	11844	11838		14		38	0.46	16950	274.21	2.180	119.74		50.189	1.000	16.265		202.320	107.05	445.38	48.7	675	686	0.33	503.760	1.38	88%			
CHECK	11838	20755		4		11	0.21	16961	274.42	2.180	119.80		50.189	1.000	16.265		202.320	107.12	445.51	33.5	675	686	0.30	480.316	1.31	93%			
	20755	11860		52		140	4.45	17101	278.87	2.177	120.63		50.189	1.000	16.265		202.320	108.59	447.81	14.0	675	686	0.36	526.160	1.44	85%			
	11860	11861		8		22	0.32	17123	279.19	2.176	120.76		50.189	1.000	16.265		202.320	108.70	448.04	46.4	675	686	0.35	518.801	1.42	86%			
	11861	11862		7		19	0.36	17142	279.55	2.176	120.87		50.189	1.000	16.265		202.320	108.81	448.27	57.7	675	686	0.66	712.424	1.95	63%			
	11862	11863	3	6		26	0.60	17168	280.15	2.175	121.03		50.189	1.000	16.265		202.320	109.01	448.63	63.2	675	686	0.40	554.621	1.52	81%			
	11863	11864	3	6		26	0.71	17195	280.86	2.175	121.19		50.189	1.000	16.265		202.320	109.25	449.02	73.4	675	686	0.40	554.621	1.52	81%			
BANTING CRES	11856	11864	54		122	403	6.2	403	6.2	3.216	4.20	0.850	0.850	1.000	0.275			2.33	6.80	94.1	250	254	0.51	44.305	0.88	15%			
PENFIELD DR	11864	11865		7		19	0.47	17617	287.53	2.166	123.68		51.039	1.000	16.540		202.320	111.73	454.27	91.7	675	686	0.40	554.621	1.52	82%			
	11865	12091		6		11	0.39	17617	287.92	2.166	123.68	2.09	53.129	1.000	17.218		202.320	112.55	455.76	95.7	675	686	0.65	707.006	1.93	64%			
	12091	910	18	5		75	1.76	17619	289.68	2.166	123.69		53.129	1.000	17.218		202.320	113.13	456.35	56.8	675	686	0.72	744.102	2.04	61%			

1200 Maritime Way
SANITARY SEWER DESIGN SHEET OF DOWNSTREAM SEWERS - CURRENT STANDARDS
JOB# 120144



PENFIELD DR	911	910	1514		1359			118	212		9029	188	9029	188	2.399	70.20	11.23	11.230	1.000	3.639			65.75	139.58	64.8	600	610	0.14	239.676	0.83	58%		
TRUNK	910	909											26648	477.68	2.022	174.66			64.359	1.000	20.857			202.320	178.87	576.71	56.4	600	610	1.02	646.934	2.24	89%
	909	908											26648	477.68	2.022	174.66			64.359	1.000	20.857			202.320	178.87	576.71	26.5	900	914	0.75	1635.562	2.52	35%
	908	907											26648	477.68	2.022	174.66	16.52	80.879	1.000	26.211			202.320	184.32	587.51	41.4	900	914	0.46	1280.900	1.97	46%	

- Notes:**
- As per Kanata Town Centre Sanitary Trunk Sewer Study revised March 27, 1996 by Robinson Consultants Inc.
 - Park or open space area.
 - Equivalent population base on 208 rooms and 20 staff members.
 - Allowance for an ultimate flow of 188 l/s to provide flexibility in future development as per Kanata Town Centre Sanitary Trunk Study.
 - Additional flow associated with hotel amenities including swimming pool with bathrooms and laundry as per design calculations for Block 1 provided by WSP (October 2016).
 - Additional flow associated with overall amenities including beauty salon, staff, dining and laundry as per design calculations for 1250 Maritime Way (Timberwalk Retirement Home) provided by Novatech (July 31, 2017).
 - JLR Spreadsheet up-dated to include development flows from 1200 Maritime Way. Reference Appendix A of Serviceability Report for 1250 Maritime Way attached in Appendix of 1200 Maritime Way Serviceability Report (Novatech January 28, 2021)..

Design Parameters:

- $Q(p) = (P \times q) / 86,400$
- $Q(d) = Q(p) + Q(e)$

Definitions:

P = Population
q = Average per capita flow = 280 L/person/day
M = Residential Peaking Factor (Harmon Formula from section 4.4.1 of the City Sewer Design Guidelines):
 $M = 1 + [14 / (4 + Pop / 1000)^{1/2}] \times 0.8$ - (Maximum of 4.0)

Q(d) = Design Flow (L/sec)
Q(p) = Population Flow (L/sec)
Q(r) = Commercial Flow (L/sec)
Q(e) = Extraneous Flow (L/sec) 0.33 l/s/ha

Units			
Single	3.4		pers/unit
Town	2.7		pers/unit
Hotel/ Apartment	1.8		pers/unit
Retirement Home	1.6		pers/unit
Commercial Flow	28000		L/ha/day
Commercial Peak Factor		1.5	if <20% of area
		1.0	if >20% of area

1200 Maritime Way SANITARY SEWER DESIGN SHEET			
Date	March 25, 2022		
Design	GMAC		
Job No.		wg. Referenc	Checked and Stamped:
120144		120144-SAN	--

MEMORANDUM



**J.L. Richards
& Associates Limited**
864 Lady Ellen Place
Ottawa, ON Canada
K1Z 5M2
Tel: 613 728 3571
Fax: 613 728 6012

Page 1 of 2

To: Greg MacDonald, P.Eng.
Novatech Engineering Consultants Ltd.

Date: August 18, 2017

Job No.: 15712-015.1

CC: Lucie Dalrymple, P.Eng.
J.L. Richards & Associates Ltd.

From: Karla Ferrey, P.Eng.

Re: Kanata Town Centre Central Business District
Master Design Sheet Update - Sanitary Peak Flows
Block 4, Block 5 and Block west of Block 9 (Zone 122)

We understand that the City is requesting an update to the Master Sanitary Sewer Design Sheet for the Kanata Town Centre Central Business District (KTC-CBD) from JL Richards such to incorporate the proposed peak flow revision from Block 4, Block 5, and the parcel west of Block 9 (previously Robinson '96 - Zone 122). Refer to attached JLR Sanitary Drainage Plan and Robinson Consultants Figure 7.1 for locations of Block 4, Block 5 and Zone 122.

We understand that the City will ultimately decide (as the owner of the existing sewers within the KTC-CBD and downstream system) whether the proposed peak flow increase is acceptable and that if accepted, it will not require a reduction of the allowable peak flows for the remaining future development in the KTC-CBD.

As requested, we have incorporated the proposed sanitary peak flow increase associated with your following developments:

a) Proposed Block 4 - Residential development

The proposed development will result in a theoretical increase in peak flow from 3.88 L/s to 4.71 L/s at MH 513 where the Block 4 development outlets to Maritime Way. This represents a theoretical peak flow increase of 0.83 L/s from the anticipated 2012 land use (i.e., hotel use, based on 270 L/pers/day).

b) Proposed Block 5 - Residential development

The proposed development will result in a theoretical increase in peak flow from 3.52 L/s to 5.13 L/s at MH 511 where the Block 5 development outlets to Maritime Way. This represents a theoretical peak flow increase of 1.61 L/s from the anticipated 2012 land use (i.e., hotel use, based on 270 L/pers/day).

c) Proposed parcel west of Block 9 (previously identified in the 1996 Robinson KTC Sanitary Design as Zone 122) – Retirement Home – Claridge Homes

The proposed development will result in a theoretical increase in peak flow from 2.84 L/s to 7.19 L/s at MH 7A where Claridge Homes development outlets to Maritime Way. This represents a theoretical peak flow increase of 3.57 L/s from the anticipated 2012 land use (i.e., Commercial use based on 2787m² office space and Infiltration based 1.5ha). Theoretical flows for Zone 122 were taken from Robinson Consultants Sanitary Trunk Information from Table 4.7 and Figure 7.1, see attached copies.

At the most downstream MH at the intersection of Teron Rd and Campeau Dr (MH Ex. 2) shown on the attached Sanitary Sewer Design Sheet for the Kanata Village Green subdivision (prepared in 1998 by JLR), the proposed 3 developments would result in a theoretical increase in peak flow from 475.94 L/s to 480.24 L/s which corresponds to a 4.3 L/s (0.9%) peak flow increase.

Based on the available theoretical residual capacities noted in the attached updated Master Sanitary Sewer Design Sheet, the existing sanitary sewer system from the intersection of Rock Mountain Gate and Maritime Way to the intersection of Campeau Dr and Teron Rd has the capacity to accommodate the additional theoretical peak flows of Block 4, Block 5 and Zone 122. Downstream of the Campeau Drive intersection, JLR does not have on record design sheets for the City's existing downstream sanitary sewer system.

Should you have any questions or require anything further, please do not hesitate to call.

J.L. RICHARDS & ASSOCIATES LIMITED

Prepared by:



Karla Ferrey, P.Eng.



CITY OF OTTAWA

KANATA TOWN CENTRE
CENTRAL BUSINESS DISTRICT
URBAN DALE CORPORATION
JLR PROJECT NO.: 15712

Commercial Flow = 50000 L/ha/d
q residential = 350 l/cap/d
q hotel = 270 l/cap/d
q retirement homes = 450 l/cap/d
i = 0.28 l/s/ha
SING. HOUSING 3.4 pers/hse
MULT. HOUSING 2.7 pers/hse
Hotel/Appartments 1.8 pers/room
Retirement Homes 1.6 pers/room

MASTER SANITARY SEWER DESIGN SHEET
Designed: L.D.


2017 Update by: KF
2017 Check by: LD

Date: August 15, 2017

Manning's Coefficient (n) = 0.013


STREET	M.H. # FROM TO		RESIDENTIAL											COMMERCIAL / INSTITUTIONAL			PLUGGED FLOW		R+C		2017 Updates to Block 4.5, West of 9 Peak Flows SEWER DATA					CAPACITY								
			SING.	Stacks	Towns	Ext. Care		Hotel/Apart.		POPUL. people	AREA ha	CUMMULATIVE POPUL. people	AREA ha	PEAKING FACTOR	POPUL. FLOW l/s	Actual AREA ha	CUMM. AREA ha	COMM. FLOW l/s	FLOW l/s	CUMM. FLOW l/s	PEAK EXTR. FLOW l/s	PEAK DES. FLOW l/s	DIA. mm	SLOPE %	CAPAC. l/s	VEL. m/s	LENGTH m	Residual (L/s)	% Full					
						No units	Act. pop	No units	Act. pop																					Equ. pop.				
COLCHESTER SQUARE	14	11		4						11	0.16	15158	259.68	2.77	170.31		30.02	26.06		201.54	81.48	479.39	900	0.11	600.38	0.94	72.6	120.99	80%					
TERON	11	10										15158	259.68	2.77	170.31		30.02	26.06		201.54	81.48	479.39	900	0.11	600.38	0.94	29.6	120.99	80%					
	10	EX.									0.25	15158	259.93	2.77	170.31		30.02	26.06		201.54	81.55	479.46	900	0.11	600.38	0.94	72.3	120.92	80%					
TERON	O.P.P.	EX.																					100	Forcemain										
TERON	EX.	EX. 2										15158	259.93	2.77	170.31		30.02	26.06		202.32	81.55	480.24	680	0.96	838.61	2.31	9.4	358.37	57%					
			(1)	As per Kanata Town Centre Sanitary Trunk Sewer Study, revised March 27, 1996, by Robinson Consultants Inc.																														
			(2)	Park or open space area.																														
			(3)	Equivalent population base on 208 rooms and 20 staff members.																														
			(4)	Allowance for an ultimate flow of 188 l/s to provide flexibility in future development as per Kanata Town Centre Sanitary Trunk Study.																														
			(5)	Additional flow associated with hotel amenities including swimming pool with bathrooms and laundry as per design calculations for Block 1 provided by WSP (October 2016)																														
			(6)	Additional flow associated with overall amenities including beauty salon, staff, dining and laundry as per design calculations for 1250 Maritime Way (Timberwalk Retirement Home) provided by Novatech (July 31, 2017)																														





Block currently occupied (October 2017)
 Block with changed sanitary flows (subject of J.L. Richard's updated sanitary design)

DATE	REVISIONS	BY	NO.	DATE	REVISIONS	BY
12/06/12	REVISED CBD DRAINAGE	JLP	5	02/11/06	PER CITY COMMENTS	CSB
24/07/07	REVISED AS PER CITY COMMENTS	CSB	4	13/09/06	ISSUED TO CITY FOR REVIEW	LND
25/05/07	PHASE 2 ISSUED FOR CITY REVIEW	CSB	3	21/07/06	ISSUED TO CITY FOR REVIEW (STREET 'A' NORTH-SOUTH LEG)	LND
08/03/07	ISSUED FOR TENDER	CSB	2	05/11/98	REVISED PER RMOC	LND
		CSB	1	08/06/98	ISSUED FOR MOE APPROVAL (SAN)	LND





J.L. Richards & Associates Limited
 864 Lady Ellen Place
 Ottawa, ON Canada
 K1Z 5M2
 Tel: 613 728 3571
 Fax: 613 728 6012

THIS DRAWING IS COPYRIGHT PROTECTED AND MAY NOT BE REPRODUCED OR USED FOR PURPOSES OTHER THAN EXECUTION OF THE DESCRIBED WORK WITHOUT THE EXPRESS WRITTEN CONSENT OF J.L. RICHARDS & ASSOCIATES LIMITED.

DESIGN: C.B.
 CHECKED: L.N.D.
 DRAWN: T.S.
 CHECKED:
 APPROVED:

KANATA TOWN CENTRE
 CENTRAL BUSINESS DISTRICT
 SANITARY DRAINAGE PLAN

PROJECT No.	15712-NAD 83
STARTED	JUNE 1998
DWG. No.	15712-SAN



NOTE: THIS PLAN WAS PRODUCED ON AN AUTOCAD® DRAFTING SYSTEM

No.	DATE	REVISION	BY	No.	DATE	REVISION	BY
1	05.16.94	REVISED PROFILE	P.A.				
2	06.28.94	GENERAL REVISIONS AND ADDITIONS	P.A.				
3	07.11.94	GENERAL REVISIONS	P.A.				
4	07.28.95	PIPE SIZE PENFIELD DR. AND LOGO	A.J.R.				



SCALES
 1: 4000
 HORIZONTAL
 1: 400
 VERTICAL

Robinson
 Consultants

CONSULTING ENGINEERS
 136, Michael Coulson Dr.
 Kanata, Ontario, K2M 2E9
 Telephone (873) 882-8080

DESIGN P.G.
 CHECKED A.J.R.
 DRAWN I.D.M.
 CHECKED
 APPROVED A.J.R.




Figure 7.1
KANATA TOWN CENTRE
 Trunk Sanitary Sewer Functional Design

PROJECT No. 93055
 CONTRACT No. _____
 DATED OCT. 93
 DWG. No. 93055-C

Table 4.7 - Revised as per RMOC Letter Dated March 27, 1996

KANATA TOWN CENTRE SANITARY TRUNK SEWER STUDY

Ultimate Development Flows Worksheet

Revised March, 1996

Project 93055

SR Pump Strn. Qp= 163 l/s

q (res)= 4.1E-03 l/cap x s 0.35 cu. m/capita/day

q (ret)= 5.8E-05 l/s x m2 5000 l/1000m2 x day

q (com)= 5.8E-05 l/s x m2 5000 l/1000m2 x day

q (hot)= 2.6E-03 l/s x bed 225 l/bed x day

Peaking factor for ret & off & hot= 1.5

Flow Scenario - III

2 beds/room

3.8 persons/dwelling (low & med density)

I= 0.28 l/s/ha

2.2 persons/dwelling (high density)

Zone	Area	Residential Units			Retail		Office		Special Gen.		Peaking Factor	Qp (l/s)	Qi (l/s)	Qtot (l/s)	Cummul. Qtot (l/s)	
		Low	Med	High	GLA (m2)	Emp.	Area (m2)	Emp.	Hotel Rooms	Emp.						
112	1.6		100		2230	47	5574	200								
111	2.2															
109	2.2	200	33						200	88						
115	0.8						1394	50								
116	0.20															
114	0.10															
118	1.7			50			9755	350								
120	1.1		87													
100	7.40				16908	386					4.00	1.47	2.07	3.54	166.62	
101	1.30				4041	87					4.00	0.35	0.36	0.71	167.34	
102	0.80				1579	34					4.00	0.14	0.22	0.36	167.70	
104	1.50			168	10080	217					4.00	6.86	0.42	7.28	174.98	
110	8.20		300								3.68	16.98	2.30	19.28	193.78	
103	13.30				74459	1603					3.68	6.46	3.72	10.19	203.97	
105	2.10			90	8826	190					3.64	3.68	0.59	4.27	208.00	
106	1.50				3298	71					3.64	0.29	0.42	0.71	208.70	
117	0.04										3.64	0.00	0.01	0.01	208.72	
119	2.60			100	2230	47	34838	1250			3.60	6.42	0.73	7.15	215.59	
107	9.10								100	88	3.60	0.78	2.55	3.33	218.53	
113	2.10			300	2230	47	16722	600			3.50	10.99	0.59	11.58	229.31	
121	0.10						19509	700			3.50	1.69	0.03	1.72	231.04	
122	1.50						27870	1000			3.50	2.42	0.42	2.84	233.88	
123	1.70		72	50			1394	50			3.45	5.48	0.48	5.95	239.30	
124	0.60										3.45	0.00	0.17	0.17	239.47	
125	1.40										3.45	0.00	0.39	0.39	239.86	
126	2.80										3.45	0.00	0.78	0.78	240.64	
127	1.80		80				4181	150			3.41	4.56	0.50	5.07	245.27	
128	1.20		36				4181	150			3.39	2.24	0.34	2.58	247.65	
129	1.70		70				6968	250			3.37	4.23	0.48	4.71	251.96	
130	1.10						11148	400			3.37	0.97	0.31	1.28	253.24	
131	2.00										3.37	0.00	0.56	0.56	253.80	
132	0.60		40								3.35	2.06	0.17	2.23	255.80	
133	0.60										3.35	0.00	0.17	0.17	255.97	
134	0.70						4181	150			3.35	0.36	0.20	0.56	256.52	
135	0.60		36								3.34	1.85	0.17	2.02	258.33	
136	1.00		18								3.33	0.92	0.28	1.20	259.43	
137	0.80	10	18								3.32	1.43	0.22	1.65	260.92	
138	1.50		93								3.29	4.71	0.42	5.13	265.50	
139	0.80	18	8								3.28	1.31	0.22	1.54	266.88	
156	1.10		37								3.27	1.86	0.31	2.17	268.82	
140	0.90	8	27								3.26	1.75	0.25	2.01	270.62	
141	1.00		59								3.24	2.94	0.28	3.22	273.48	
142	0.50										3.24	0.00	0.14	0.14	273.62	
144	0.60		34								3.23	1.69	0.17	1.86	275.27	
143	1.10	10	30								3.22	1.98	0.31	2.29	277.31	
145	1.30		92								3.19	4.52	0.36	4.88	281.63	
146	1.00	16	19								3.18	1.71	0.28	1.99	283.41	
108	1.20		34								3.17	1.66	0.34	2.00	285.19	
148	1.00	8	18								3.17	1.27	0.28	1.55	286.58	
150	0.70		11								3.16	0.54	0.20	0.73	287.24	
151	0.30										3.16	0.00	0.08	0.08	287.32	
152	2.00										3.16	0.00	0.56	0.56	287.88	
154	1.20		66								3.15	3.20	0.34	3.53	291.00	
155	1.80						3177	114			3.15	0.28	0.50	0.78	291.78	
147	1.30		49								3.13	2.36	0.36	2.73	294.20	
153	0.80			100							3.12	2.78	0.22	3.00	296.84	
149	0.60				1858	39					3.12	0.16	0.17	0.33	297.17	
Totals	90.84	70	1247	808	125509	2768	134169	5414	100	176						
Total Town Centre Population					6782.2											
Average Persons per Dwelling Unit					3.19		Combined Down Stream Flow					425.64				

Karla Ferrey

From: Lucie Dalrymple
Sent: August 1, 2017 9:43 AM
To: Karla Ferrey
Subject: FW: Kanata Town Centre - Sanitary Flows
Attachments: 1088 San Drainage.pdf; 1136 San Drainage.pdf

...here it is

Lucie Dalrymple, P.Eng.
Associate
Senior Civil Engineer

J.L. Richards & Associates Limited
864 Lady Ellen Place, Ottawa, ON K1Z 5M2
Tel: 613-728-3571 Fax: 613-728-6012



**J.L. Richards
& Associates Limited**
ENGINEERS • ARCHITECTS • PLANNERS



From: Matthew Hrehoriak [mailto:m.hrehoriak@novatech-eng.com]
Sent: July 31, 2017 10:16 AM
To: Lucie Dalrymple
Subject: RE: Kanata Town Centre - Sanitary Flows

Hi Lucie,

The sanitary info for the block 4 and 5 developments are as follows:

1088 Maritime Way (Block 4)

San service connection between SANMH 512-513
San Drainage Area = 1.121 ha
No. Units = 144
Population = 271

1136 Maritime Way (Block 5)

San service connection between SANMH 510-511
San Drainage Area = 0.915 ha
No. Units = 154
Population = 301

Regards,



Matthew Hrehoriak, B.Eng., EIT

NOVATECH Engineers, Planners & Landscape Architects

240 Michael Cowpland Drive, Suite 200, Ottawa, ON, K2M 1P6 | Tel: 613.254.9643 x 273 | Fax: 613.254.5867

The information contained in this email message is confidential and is for exclusive use of the addressee.

M:\2015\115198\cad\design\115198-GP.dwg, SAN, Jul 13, 2017 - 3:58pm, mhrehorlak



LEGEND

- 1.121
1088 - EX
144 | 271 SANITARY DRAINAGE AREA (ha)
- 1088 - EX LOCATION
- 144 | 271 UNITS / POPULATION
- SANMH
- SANITARY MANHOLE
- SANITARY SERVICE WITH FLOW DIRECTION

1088 MARITIME WAY
 FFE = 100.27
 P1 FFE = 96.67
 P2 FFE = 93.47
 USF = 92.45
 PROPOSED BUILDING AREA 3793m²

SANMH 1
 T/G=99.90
 SW.INV=95.15
 NE.INV=95.44
 (WATERTIGHT FRAME AND COVER)

1.3m-200mmØ PVC SAN @ 2.0%
 SAN INV=95.47

13.1m-200mmØ
 SAN @ 2.0%
 TEE CONNECT
 SAN INV = 94.30±

EX SANMH
 T/G=100.35
 SE.INV=96.11

EX SANMH
 T/G=98.89
 NW.INV=94.86
 SE.INV=94.80

EX SANMH
 T/G=97.60
 NW.INV=93.71
 SE.INV=93.38
 W.INV=93.43



Engineers, Planners & Landscape Architects
 Suite 200, 240 Michael Cowpland Drive
 Ottawa, Ontario, Canada K2M 1P6

Telephone (613) 254-9643
 Facsimile (613) 254-5867
 Website www.novatech-eng.com


1088 MARITIME WAY

SANITARY DRAINAGE AREA PLAN

SCALE 1 : 500

DATE JULY 2017 JOB 115198 FIGURE A3


CUT 11V17 DWG 270mm X 132mm



0.915
1136 - EX
154 301

LEGEND

- 0.915
1136 - EX
154 301 SANITARY DRAINAGE AREA (ha)
- LOCATION
- UNITS / POPULATION
- SANMH
- SANITARY MANHOLE
- SANITARY SERVICE WITH FLOW DIRECTION



Engineers, Planners & Landscape Architects
Suite 200, 240 Michael Cowpland Drive
Ottawa, Ontario, Canada K2M 1P6
Telephone (613) 254-9643
Facsimile (613) 254-5867
Website www.novatech-eng.com

1136 MARITIME WAY

SANITARY DRAINAGE AREA PLAN

SCALE 1 : 500 05101520

DATE JULY 2017 JOB 115199 FIGURE A3

M:\2015\115199\CAD\Design\115199-GP.dwg, 11x17 portrait, Jul 18, 2017 - 3:12pm, mhrehorjak

SANITARY SEWER DESIGN SHEET

1250 Maritime Way
 Timberwalk Retirement Home
 Developer: Claridge Homes

Date: 31-Jul-17

Designed: CMS
 Checked: GJM

Location			RESIDENTIAL							INSTITUTIONAL				COMMECIAL			OTHER										INFILTRATION		Total Flow (L/s)	PIPE							
ID	From	To	1 Bedroom		2 Bedroom		Total (Residential)			Assisted Care				Convenience Store			Staff			Beauty Salon			Laundry			Dining				Total Area (ha)	Infil. Flow (L/s)	Size (mm)	Slope (%)	Length (m)	Capacity (l/s)	Full Flow Vel. (m/s)	Q/Q _{full} (%)
			Units	Pop.	Units	Pop.	Pop.	Peak Factor	Flow (L/s)	Units / Bed	Pop.	Peak Factor	Flow (L/s)	Area (m2)	Peak Factor	Flow (L/s)	Pop.	Peak Factor	Flow (L/s)	Stations	Peak Factor	Flow (L/s)	Machines	Peak Factor	Flow (L/s)	Seats	Peak Factor	Flow (L/s)									
Part A (current application)	BLD-1	MH101	92	129.0	8	17.0	146.0	4.0	2.37	54	60.0	1.5	0.47	50	1.5	0.004	20	1.5	0.10	2	1.5	0.02	6	1.5	0.13	55	1.5	0.11	0.48	0.13	3.33	200	2.00	2.5	48.4	1.49	6.9%
Part A (current application)	MH101	TEE-1	0	0.0	0	0.0	146.0	4.0	2.37	0	0.0	1.5	0.47	0	1.5	0.004	0	1.5	0.10	0	1.5	0.02	0	1.5	0.13	0	1.5	0.11	0.00	0.13	3.33	200	2.00	13.4	48.4	1.49	6.9%
Part B (future application)	BLD-2	MH103	0	0.0	110	231.0	231.0	4.0	3.74	0	0.0	1.5	0.00	0	1.5	0.000	0	1.5	0.00	0	1.5	0.00	0	1.5	0.00	0	1.5	0.00	0.41	0.11	3.86	200	2.00	2.5	48.4	1.49	8.0%
Part B (future application)	MH103	TEE-2	0	0.0	0	0.0	231.0	4.0	3.74	0	0.0	1.5	0.00	0	1.5	0.000	0	1.5	0.00	0	1.5	0.00	0	1.5	0.00	0	1.5	0.00	0.00	0.11	3.86	200	2.00	13.4	48.4	1.49	8.0%
TOTAL (Parts A + B)	-	-	92	129.0	118	248.0	377.0	4.0	6.11	54	60.0	1.5	0.47	50	1.5	0.004	20	1.5	0.10	2	1.5	0.02	6	1.5	0.13	55	1.5	0.11	0.89	0.25	7.18	200	2.00	2.5	48.4	1.49	14.8%

Design Parameters:

Residential	350 L/cap/day	Peaking Factor:
Institutional	450 L/bed/day	Residential Harmon Equation (max 4, min 2)
Commercial	5 L/m ² per day	Institutional 1.5
Staff	275 L/cap/day	Commercial 1.5
Beauty Salon	650 L/day per station	Other 1.5
Laundry	1200 L/day per machine	People/Unit:
Dining	115 L/seat/day	1.10 Assisted Care
Infiltration	0.28 L/s/ha	1.40 1 Bedroom
		2.10 2 Bedroom
		1.00 Studio

Notes:

1. The harmon peaking factor calculated for section 507 to 7A is 3.5 per JLR Design Sheet dated October 12th, 2016
2. Residential flows were used for senior apartments (350 L/cap/day, Harmon Peaking Factor)
3. Institutional flow used for assisted care units (450 L/bed/day, Peaking Factor = 1.5)
4. Future building assumed to be a 10 storey building comprised of 110 2 bedroom units

END OF J.L RICHARDS MEMORANDUM

Matthew Linton

From: Mike Traub <mike.traub@claridgehomes.com>
Sent: July-13-17 1:12 PM
To: Matthew Linton
Cc: Pascal Vendette; Conrad Stang
Subject: Re: FW: 1250 Maritime Way - Sanitary

Hi Matt,

There will be two stations in the hair salon and about 55 seats in the main dining room.

Let me know if you have any further questions.

Thanks,

Mike

On Wed, Jul 12, 2017 at 4:40 PM, Matthew Linton <m.linton@novatech-eng.com> wrote:

Pascal/Mike,

Could we obtain some clarifications on the following below? This is for city comments as they are stating our assumed values seem low.

Thanks,

Matthew Linton, CAD Technologist

NOVATECH Engineers, Planners & Landscape Architects

240 Michael Cowpland Drive, Suite 200, Ottawa, ON, K2M 1P6 | Tel: [613.254.9643](tel:613.254.9643) Ext: 207 | Fax: [613.254.5867](tel:613.254.5867)

The information contained in this email message is confidential and is for exclusive use of the addressee.

From: Conrad Stang
Sent: July-12-17 3:55 PM

Matthew Linton

From: Pascal Vendette <pascal@neufarchitectes.com>
Sent: May-01-17 1:39 PM
To: Matthew Linton
Subject: RE: Unit Counts - Timberwalk (Maritime Way)

2nd floor : 28 assisted care units
3rd floor : 26 assisted care units
4th to 7th floor : 25 units
 6 suites
 17 1br
 2 br

NEUF
ARCHITECT(E)S



PASCAL VENDETTE

Technologue senior en architecture
Senior Architectural Technologist
T 514 847 1117 #269 F 514 847 2287 C 514 833 6005
630, boul. René-Lévesque O. 32^e étage, Montréal (QC) H3B 1S6
47 Clarence Street, suite 406, Ottawa (ON) K1N 9K1
NEUF ARCHITECTES SENCRL

Politiques de transmission et de confidentialité de NEUF architect(e)s
NEUF architect(e)s transmission and confidentiality policy

De : Matthew Linton [mailto:m.linton@novatech-eng.com]
Envoyé : 1 mai 2017 11:21
À : Pascal Vendette <pascal@neufarchitectes.com>
Objet : Unit Counts - Timberwalk (Maritime Way)

Pascal,

Can you please send us over either the calculated dwelling units (I see you have the dwelling units on drawing A050 however we need to know 1 bedroom, 2 bedroom, etc.) or floor plans for each of the floors for the retirement home?

Thanks,

Matthew Linton, CAD Technologist

NOVATECH Engineers, Planners & Landscape Architects

240 Michael Cowpland Drive, Suite 200, Ottawa, ON, K2M 1P6 | Tel: 613.254.9643 Ext: 207 | Fax: 613.254.5867

The information contained in this email message is confidential and is for exclusive use of the addressee.

Matthew Linton

From: Pascal Vendette <pascal@neufarchitectes.com>
Sent: July-13-17 9:49 AM
To: Matthew Linton
Cc: mike.traub@claridgehomes.com; Conrad Stang
Subject: RE: 1250 Maritime Way - Sanitary

Follow Up Flag: Follow up
Flag Status: Completed

Hi Matthew.
Sorry for the delay ... it's crazy here.

Here is my response to item #1.
There are commercial washers-dryers in the basement ...

- 2 gas heater tumble dryers 75 lbs
- 1 high-performance washer extractor 65 lbs
- 1 cabinet hardmount washer extractor 20 lbs

... and residential type washer-dryer (one of each) on floors 4 to 7

Mike can you please take care of items #2 & #3.

Best regards,

NEUF
ARCHITECT(E)S



PASCAL VENDETTE

Technologue senior en architecture
Senior Architectural Technologist
T 514 847 1117 #269 F 514 847 2287 C 514 833 6005
630, boul. René-Lévesque O. 32^e étage, Montréal (QC) H3B 1S6
47 Clarence Street, suite 406, Ottawa (ON) K1N 9K1
NEUF ARCHITECTES SENCRL

Politiques de transmission et de confidentialité de NEUF architect(e)s
NEUF architect(e)s transmission and confidentiality policy

De : Matthew Linton [mailto:m.linton@novatech-eng.com]
Envoyé : 13 juillet 2017 09:38
À : Pascal Vendette <pascal@neufarchitectes.com>
Cc : mike.traub@claridgehomes.com; Conrad Stang <c.stang@novatech-eng.com>
Objet : RE: 1250 Maritime Way - Sanitary

Pascal,

Can we have some clarification on this?

SANITARY SEWER DESIGN SHEET

1250 Maritime Way
 Timberwalk Retirement Home
 Developer: Claridge Homes

Date: 30-Nov-17

Designed: CMS
 Revised: JDM
 Checked: GJM

Location			RESIDENTIAL							INSTITUTIONAL				COMMECIAL			OTHER									INFILTRATION		PIPE									
ID	From	To	1 Bedroom		2 Bedroom		Total (Residential)			Assisted Care				Convenience Store			Staff			Beauty Salon			Laundry			Dining			Total Area (ha)	Infiltr. Flow (L/s)	Total Flow (L/s)	Size (mm)	Slope (%)	Length (m)	Capacity (l/s)	Full Flow Vel. (m/s)	Q/Q _{full} (%)
			Units	Pop.	Units	Pop.	Pop.	Peak Factor	Flow (L/s)	Units / Bed	Pop.	Peak Factor	Flow (L/s)	Area (m2)	Peak Factor	Flow (L/s)	Pop.	Peak Factor	Flow (L/s)	Stations	Peak Factor	Flow (L/s)	Machines	Peak Factor	Flow (L/s)	Seats	Peak Factor	Flow (L/s)									
Part A (current application)	BLD1	MH4	92	129.0	8	17.0	146.0	4.0	2.37	54	60.0	1.5	0.47	100	1.5	0.009	20	1.5	0.10	2	1.5	0.02	6	1.5	0.13	55	1.5	0.11	0.48	0.13	3.33	200	2.66	9.6	55.8	1.72	6.0%
Part A (current application)	MH4	MH2	0	0.0	0	0.0	146.0	4.0	2.37	0	0.0	1.5	0.47	0	1.5	0.009	0	1.5	0.10	0	1.5	0.02	0	1.5	0.13	0	1.5	0.11	0.00	0.13	3.33	200	2.70	27.8	56.2	1.73	5.9%
Part B (future application)	FUT-BLD2	MH2	0	0.0	110	231.0	231.0	4.0	3.74	0	0.0	1.5	0.00	0	1.5	0.000	0	1.5	0.00	0	1.5	0.00	0	1.5	0.00	0	1.5	0.00	0.41	0.11	3.86	200	2.00	2.5	48.4	1.49	8.0%
TOTAL (Parts A + B)	MH2	EX MH	92	129.0	118	248.0	377.0	4.0	6.11	54	60.0	1.5	0.47	100	1.5	0.009	20	1.5	0.10	2	1.5	0.02	6	1.5	0.13	55	1.5	0.11	0.89	0.25	7.19	200	1.50	13.8	41.9	1.29	17.2%

Design Parameters:

Residential	350 L/cap/day
Institutional	450 L/bed/day
Commercial	5 L/m ² per day
Staff	275 L/cap/day
Beauty Salon	650 L/day per station
Laundy	1200 L/day per machine
Dining	115 L/seat/day
Infiltration	0.28 L/s/ha

Peaking Factor:

Residential	Harmon Equation (max 4, min 2)
Institutional	1.5
Commercial	1.5
Other	1.5

People/Unit:

1.10	Assisted Care
1.40	1 Bedroom
2.10	2 Bedroom
1.00	Studio



Notes:

1. The harmon peaking factor calculated for section 507 to 7A is 3.5 per JLR Design Sheet dated October 12th, 2016
2. Residential flows were used for senior apartments (350 L/cap/day, Harmon Peaking Factor)
3. Institutional flow used for assisted care units (450 L/bed/day, Peaking Factor = 1.5)
4. Future building assumed to be a 10 storey building comprised of 110 2 bedroom units



APPENDIX C

Stormwater Management Calculations




LEGEND

—	PROPERTY LINE	---	DRAINAGE AREA LIMITS
—	PROPOSED CURB	—	DRAINAGE AREA (ha)
—	PROPOSED DEPRESSED CURB	—	DRAINAGE AREA ID
—	PROPOSED TACTILE WALKING SURFACE INDICATOR (TWSI)	—	RUNOFF COEFFICIENT
—	PROPOSED CAP	○	0.085 A-16 0.78
○	PROPOSED STORM SEWER C/W MANHOLE	○	
○	PROPOSED CATCHBASIN MANHOLE	○	
○	PROPOSED CATCHBASIN	○	
○	PROPOSED LANDSCAPE DRAIN	○	
○	PROPOSED AREA DRAIN	○	
○	PROPOSED INLET CONTROL DEVICE	○	
○	PROPOSED BUILDING ENTRANCE	○	
○	DIRECTION OF FLOW	○	
○	PROPOSED RETAINING WALL C/W GUARD RAIL	○	
○	PROPOSED SWALE	○	
○	PROPOSED TERRACING	○	
○	EXISTING STORM MANHOLE & SEWER	○	
○	EXISTING CATCHBASIN	○	
○	EXISTING OVERHEAD WIRES	○	
○	EXISTING STREETLIGHT	○	


- STORMWATER MANAGEMENT NOTES:**
- REFER TO 'SERVICEABILITY AND STORMWATER MANAGEMENT REPORT' PREPARED BY NOVATECH ENGINEERING CONSULTANTS LTD.
 - NO ROOF TOP CONTROL ALLOWED.
 - TOTAL AREA: 1.24 ha

NOTE:
THE POSITION OF ALL POLE LINES, CONDUITS, WATERMANS, SEWERS AND OTHER UNDERGROUND AND OVERGROUND UTILITIES AND STRUCTURES IS NOT NECESSARILY SHOWN ON THE CONTRACT DRAWINGS, AND WHERE SHOWN, THE ACCURACY OF THE POSITION OF SUCH UTILITIES AND STRUCTURES IS NOT GUARANTEED. BEFORE STARTING WORK, DETERMINE THE EXACT LOCATION OF ALL SUCH UTILITIES AND STRUCTURES AND ASSUME ALL LIABILITY FOR DAMAGE TO THEM.

CLARIDGE HOMES
CLARIDGE HOMES
505 PRESTON STREET,
OTTAWA, ONTARIO
K1S 4N7.



No.	REVISION	DATE	BY
5.	ISSUED FOR SPA	APR 28/23	GJM
4.	REVISED PER CITY COMMENTS	MAY 31/22	GJM
3.	ISSUED FOR COORDINATION BASED ON URDP	OCT20/21	JAG
2.	ISSUED FOR CITY COMMENTS	JUL07/21	JAG
1.	SUBMITTED WITH ZONING/SITE PLAN APPLICATIONS	JAN25/21	JAG



FOR REVIEW ONLY	DESIGN
CHECKED	JAG
DRAWN	GJM
CHECKED	CJF
APPROVED	JAG
	GJM

NOVATECH
Engineers, Planners & Landscape Architects
Suite 200, 240 Michael Cowpland Drive
Ottawa, Ontario, Canada K2M 1P6
Telephone: (613) 254-9643
Facsimile: (613) 254-5867
Website: www.novatech-eng.com

LOCATION CITY OF OTTAWA MARITIME WAY - KANATA RENTAL	PROJECT No. 120144
DRAWING NAME STORM WATER MANAGEMENT PLAN	REV # 5
DRAWING No. 120144-SWM	City Plan #18348

TABLE 1A: Allowable Runoff Coefficient "C"

Area	"C"
Total	0.80
1.238	

TABLE 1B: Allowable Flows

Outlet Options	Area (ha)	"C"	Tc (min)	Q _{5 Year} (L/s)	Q _{ALLOW} (L/s)
	1.238	0.80	20	193.4	193.4

Time of Concentration T_c= 20 min
 Intensity (2 Year Event) I₂= 52.03 mm/hr
 Intensity (5 Year Event) I₅= 70.25 mm/hr
 Intensity (100 Year Event) I₁₀₀= 119.95 mm/hr

Equations:
 Flow Equation
 $Q = 2.78 \times C \times I \times A$

Where:
 C is the runoff coefficient
 I is the rainfall intensity, City of Ottawa IDF
 A is the total drainage area

100 year Intensity = $1735.688 / (\text{Time in min} + 6.014)^{0.820}$
 5 year Intensity = $998.071 / (\text{Time in min} + 6.053)^{0.814}$
 2 year Intensity = $732.951 / (\text{Time in min} + 6.199)^{0.810}$

TABLE 2A: Post-Development Runoff Coefficient "C" - D1

Area	Surface	Ha	"C"	C _{avg}	*C ₁₀₀
Total	Hard	0.015	0.90	0.57	0.65
0.029	Soft	0.013	0.20		

Runoff Coefficient Equation
 $C = (A_{hard} \times 0.9 + A_{soft} \times 0.2) / A_{Tot}$
 * Runoff Coefficient increases by 25% up to a maximum value of 1.00 for the 100-Year event

TABLE 2B: Post-Development D1 Flows

Outlet Options	Area (ha)	C _{avg}	Tc (min)	Q _{2 Year} (L/s)	Q _{5 Year} (L/s)	Q _{100 Year} (L/s)
	0.029	0.57	10	3.5	4.8	9.2

Time of Concentration T_c= 10 min
 Intensity (2 Year Event) I₂= 76.81 mm/hr
 Intensity (5 Year Event) I₅= 104.19 mm/hr
 Intensity (100 Year Event) I₁₀₀= 178.56 mm/hr

Equations:
 Flow Equation
 $Q = 2.78 \times C \times I \times A$
 Where:

C is the runoff coefficient
 I is the rainfall intensity, City of Ottawa IDF
 A is the total drainage area

100 year Intensity = $1735.688 / (\text{Time in min} + 6.014)^{0.820}$
 5 year Intensity = $998.071 / (\text{Time in min} + 6.053)^{0.814}$
 2 year Intensity = $732.951 / (\text{Time in min} + 6.199)^{0.810}$

TABLE 3A: Post-Development Runoff Coefficient "C" - D2

Area	Surface	Ha	"C"	C _{avg}	*C ₁₀₀
Total	Hard	0.000	0.90	0.20	0.25
0.008	Soft	0.008	0.20		

Runoff Coefficient Equation
 $C = (A_{\text{hard}} \times 0.9 + A_{\text{soft}} \times 0.2) / A_{\text{Tot}}$
 * Runoff Coefficient increases by 25% up to a maximum value of 1.00 for the 100-Year event

TABLE 3B: Post-Development D2 Flows

Outlet Options	Area (ha)	C _{avg}	Tc (min)	Q _{2 Year} (L/s)	Q _{5 Year} (L/s)	Q _{100 Year} (L/s)
	0.008	0.20	10	0.3	0.5	1.0

Time of Concentration Tc= 10 min
 Intensity (2 Year Event) I₂= 76.81 mm/hr
 Intensity (5 Year Event) I₅= 104.19 mm/hr
 Intensity (100 Year Event) I₁₀₀= 178.56 mm/hr

Equations:
 Flow Equation
 $Q = 2.78 \times C \times I \times A$
 Where:

C is the runoff coefficient
 I is the rainfall intensity, City of Ottawa IDF
 A is the total drainage area

100 year Intensity = $1735.688 / (\text{Time in min} + 6.014)^{0.820}$
 5 year Intensity = $998.071 / (\text{Time in min} + 6.053)^{0.814}$
 2 year Intensity = $732.951 / (\text{Time in min} + 6.199)^{0.810}$

TABLE 4A: Post-Development Runoff Coefficient "C" - A-02

Area	Surface	Ha	5 Year Event		100 Year Event	
			"C"	C _{avg}	"C" + 25%	*C _{avg}
Total	Hard	0.075	0.90	0.38	1.00	0.44
0.290	Roof	0.000	0.90		1.00	
	Soft	0.215	0.20		0.25	

TABLE 4B: 5 YEAR EVENT QUANTITY STORAGE REQUIREMENT - A-02

0.290 =Area (ha)
 0.38 = C

Return Period	Time (min)	Intensity (mm/hr)	Flow Q (L/s)	Allowable Runoff (L/s)*	Net Flow to be Stored (L/s)	Storage Req'd (m ³)
5 YEAR	0	230.48	70.95	16.000	54.95	0.00
	5	141.18	43.46	16.000	27.46	8.24
	10	104.19	32.08	16.000	16.08	9.65
	15	83.56	25.72	16.000	9.72	8.75
	20	70.25	21.63	16.000	5.63	6.75

TABLE 4C: 100 YEAR EVENT QUANTITY STORAGE REQUIREMENT - A-02

0.290 =Area (ha)
 0.44 = C

Return Period	Time (min)	Intensity (mm/hr)	Flow Q (L/s)	Allowable Runoff (L/s)*	Net Flow to be Stored (L/s)	Storage Req'd (m ³)
100 YEAR	5	242.70	87.05	24.80	62.25	18.67
	10	178.56	64.04	24.80	39.24	23.55
	15	142.89	51.25	24.80	26.45	23.81
	20	119.95	43.02	24.80	18.22	21.87
	25	103.85	37.25	24.80	12.45	18.67

TABLE 4E: 100 YEAR EVENT QUANTITY STORAGE REQUIREMENT - A-02

0.290 =Area (ha)
 0.44 = C

Return Period	Time (min)	Intensity (mm/hr)	Flow Q (L/s)	Allowable Runoff (L/s)*	Net Flow to be Stored (L/s)	Storage Req'd (m ³)
100 YEAR + 20	5	291.24	104.46	29.7	74.76	22.43
	10	214.27	76.85	29.7	47.15	28.29
	15	171.47	61.50	29.7	31.80	28.62
	20	143.94	51.63	29.7	21.93	26.31
	25	124.62	44.69	29.7	14.99	22.49

Equations:

Flow Equation

$$Q = 2.78 \times C \times I \times A$$

Where:

C is the runoff coefficient

I is the rainfall intensity, City of Ottawa IDF

A is the total drainage area

Runoff Coefficient Equation

$$C_s = (A_{hard} \times 0.9 + A_{soft} \times 0.2) / A_{Tot}$$

$$C_{100} = (A_{hard} \times 1.0 + A_{soft} \times 0.25) / A_{Tot}$$

* Allowable run-off is 50% of the actual flow to estimate the required volume as per city of Ottawa Guidelines for underground storage

TABLE 5D: Structure information

Structures	Size Dia.(mm)	Area (m ²)	T/G	Inv IN	Inv OUT
CBMH 105	1200	1.13	95.50	94.36	94.35
CBMH 103	1200	1.13	96.15	94.80	94.74
CBMH 102	1200	1.13	96.20	95.00	94.99
STMMH 101	1200	1.13	96.50	95.13	95.07

TABLE 5D: Landscape drain information

Structures	Size Dia.(mm)	Area (m ²)	T/G	Top of pipe
LD 104	300	0.07	96.10	94.93
LD 100	300	0.07	96.30	95.61

TABLE 5E: Pipe information

Structures	Size Dia.(mm)	Length	Inv UP	Inv DOWN
LD 104 -CBMH 105	375	50.0	94.54	94.36
CBMH 103 - LD 104	375	54.4	94.74	94.55
CBMH 102 - CBMH 103	375	53.8	94.99	94.80
STMMH 101 - CBMH 102	375	20.0	95.07	95.00
LD 100 - STMMH 101	375	29.3	95.23	95.13

TABLE 5F: Storage Provided

Storage Table											
Elevation (m)	System Depth (m)	CBMH 105 Volume (m ³)	CBMH 103 Volume (m ³)	CBMH 102 Volume (m ³)	STMMH 101 Volume (m ³)	LD 104 Volume (m ³)	LD 100 Volume (m ³)	Pipe Storage Volume (m ³)	Underground Volume (m ³)*	Ponding Volume (m ³)	Total Volume (m ³)
94.350	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
94.360	0.01	0.01	0.00	0.00	0.00	0.00	0.00	0.00	0.01	0.00	0.01
94.740	0.39	0.44	0.00	0.00	0.00	0.00	0.00	5.95	6.39	0.00	6.39
94.990	0.64	0.72	0.28	0.00	0.00	0.00	0.00	13.65	14.66	0.00	14.66
95.070	0.72	0.81	0.37	0.09	0.00	0.01	0.00	16.11	17.40	0.00	17.40
95.500	1.15	1.30	0.86	0.58	0.49	0.04	0.00	22.12	25.38	0.00	25.38
95.610	1.26	1.43	0.98	0.70	0.61	0.05	0.00	23.66	27.42	0.28	27.70
95.640	1.29	1.46	1.02	0.74	0.64	0.05	0.00	-	27.56	0.35	27.91
95.700	1.35	-	1.09	0.80	0.71	0.05	0.01	-	27.78	0.35	28.13
95.800	1.45	-	1.20	0.92	0.83	0.06	0.01	-	28.13	0.35	28.48
95.900	1.55	-	1.31	1.03	0.94	0.07	0.02	-	28.48	0.35	28.83

TABLE 2G: Orifice Sizing information - A-1

Control Device							
Round Plate Orifice 152 mm							
Design Event	Flow (L/S)	Head (m)	Elev (m)	Outlet dia. (mm)	Volume (m ³)	Area (m ²)	Dia. (mm)
1:5 Year	32.0	0.41	94.84	375.00	9.65	0.0181	152.0
1:100 Year	49.6	0.99	95.42	375.00	23.81	0.0182	152.0
1:100 + 20 Year	59.4	1.41	95.84	375.00	28.62	0.0182	152.0

Orifice Control Sizing
 $Q = 0.62 \times A \times (2gh) \times 0.5$
 Q is the release rate in m³/s

A is the orifice area in m²
 g is the acceleration due to gravity, 9.81 m/s²
 h is the head of water above the orifice centre in m
 d is the diameter of the orifice in m

The design Head is calculated based on the centre of the orifice at the bottom of the pipe
 ##### Numbers in red are above the system spill elevation

Stage Storage Curve Area A-02




TABLE 6A: Post-Development Runoff Coefficient "C" - A-01,R-01,R-02

Area	Surface	Ha	5 Year Event		100 Year Event	
			"C"	C _{avg}	"C" + 25%	*C _{avg}
Total	Hard	0.443	0.90	0.90	1.00	1.00
0.910	Roof	0.468	0.90		1.00	
		Soft	0.000	0.20	0.25	

TABLE 6B: 2 YEAR EVENT QUANTITY STORAGE REQUIREMENT - A-01,R-01,R-02

0.910 =Area (ha)
 0.90 = C

Return Period	Time (min)	Intensity (mm/hr)	Flow Q (L/s)	Allowable Runoff (L/s)	Net Flow to be Stored (L/s)	Storage Req'd (m ³)
2 YEAR	-5	632.75	1441.00	133.0	1308.00	-392.40
	0	167.22	380.83	133.0	247.83	0.00
	5	103.57	235.87	133.0	102.87	30.86
	10	76.81	174.91	133.0	41.91	25.15
	15	61.77	140.67	133.0	7.67	6.90

TABLE 6C: 5 YEAR EVENT QUANTITY STORAGE REQUIREMENT - A-01,R-01,R-02

0.910 =Area (ha)
 0.90 = C

Return Period	Time (min)	Intensity (mm/hr)	Flow Q (L/s)	Allowable Runoff (L/s)	Net Flow to be Stored (L/s)	Storage Req'd (m ³)
5 YEAR	0	230.48	524.89	133.0	391.89	0.00
	5	141.18	321.52	133.0	188.52	56.55
	10	104.19	237.29	133.0	104.29	62.57
	15	83.56	190.29	133.0	57.29	51.56
	20	70.25	159.99	133.0	26.99	32.39

TABLE 6D: 100 YEAR EVENT QUANTITY STORAGE REQUIREMENT - A-01,R-01,R-02

0.910 =Area (ha)
 1.00 = C

Return Period	Time (min)	Intensity (mm/hr)	Flow Q (L/s)	Allowable Runoff (L/s)	Net Flow to be Stored (L/s)	Storage Req'd (m ³)
100 YEAR	5	242.70	614.14	133.0	481.14	144.34
	10	178.56	451.83	133.0	318.83	191.30
	15	142.89	361.58	133.0	228.58	205.72
	20	119.95	303.52	133.0	170.52	204.63
	25	103.85	262.78	133.0	129.78	194.66

TABLE 6E: 100 YEAR EVENT QUANTITY STORAGE REQUIREMENT - A-01,R-01,R-02

0.910 =Area (ha)
 1.00 = C

Return Period	Time (min)	Intensity (mm/hr)	Flow Q (L/s)	Allowable Runoff (L/s)	Net Flow to be Stored (L/s)	Storage Req'd (m ³)
100 YEAR + 20	10	214.27	542.19	133.0	409.19	245.52
	15	171.47	433.90	133.0	300.90	270.81
	20	143.94	364.23	133.0	231.23	277.47
	25	124.62	315.33	133.0	182.33	273.50
	30	110.24	278.96	133.0	145.96	262.72

Equations:

Flow Equation

$$Q = 2.78 \times C \times I \times A$$

Where:

C is the runoff coefficient

I is the rainfall intensity, City of Ottawa IDF

A is the total drainage area

Runoff Coefficient Equation

$$C_s = (A_{\text{hard}} \times 0.9 + A_{\text{soft}} \times 0.2) / A_{\text{Tot}}$$

$$C_{100} = (A_{\text{hard}} \times 1.0 + A_{\text{soft}} \times 0.25) / A_{\text{Tot}}$$

TABLE 6F: Structure information - A-01,R-01,R-02

Structures	Size Dia.(mm)	Area (m ²)	T/G	Bottom of Tank
Tank	-	118.83	96.45	93.23

TABLE 6G: Storage Provided - A-01,R-01,R-02

Storage Table			
Elevation (m)	System Depth (m)	Tank Volume (m ³)	
93.23	0.00	0.00	
93.330	0.10	11.88	
93.430	0.20	23.77	
93.530	0.30	35.65	
93.630	0.40	47.53	
93.730	0.50	59.41	
93.830	0.60	71.30	
93.930	0.70	83.18	
94.030	0.80	95.06	
94.130	0.90	106.95	
94.230	1.00	118.83	
94.330	1.10	130.71	
94.430	1.20	142.60	
94.530	1.30	154.48	
94.630	1.40	166.36	
94.730	1.50	178.24	
94.830	1.60	190.13	
94.930	1.70	202.01	
95.030	1.80	213.89	
95.130	1.90	225.78	
95.230	2.00	237.66	
95.330	2.10	249.54	
95.430	2.20	261.43	
95.530	2.30	273.31	
95.630	2.40	285.19	
95.700	2.47	293.51	Top of Tank
95.800	2.57	293.62	
95.900	2.67	293.74	
96.000	2.77	293.85	
96.100	2.87	293.96	
96.200	2.97	294.08	
96.300	3.07	294.19	
96.400	3.17	294.30	
96.500	3.27	294.41	Top of Grate

TABLE 6H: Orifice Sizing Information - A-01,R-01,R-02

Design Event	Control Device				
	Flow	Volume Required	Depth	Elevation	Outlet Dia. (mm)
1:2 year	133.00	30.86	0.25	93.48	300
1:5 Year	133.00	62.57	0.53	93.76	300
1:100 Year	133.00	205.72	1.73	94.96	300
1:100 + 20% Year	133.00	277.47	2.33	95.57	300

Stage Storage Curve Area Cistern




Table 15: Post-Development Stormwater Management Summary


Area ID	Area (ha)	1:5 Year Weighted Cw	1:100 Year Weighted Cw	Control Device	Outlet Location	5 Year Storm Event				100 Year Storm Event			
						Release (L/s)	Ponding Depth (m)	Req'd Vol (cu.m)	Max. Vol. Provided (cu.m.)	Release (L/s)	Ponding Depth (m)	Req'd Vol (cu.m)	Max. Vol. Provided (cu.m.)
D-01	0.029	0.57	0.65	N/A	Maritime Way	4.8	N/A	N/A	N/A	9.2	N/A	N/A	N/A
D-02	0.008	0.20	0.25	N/A	Highway 417	0.5	N/A	N/A	N/A	1.0	N/A	N/A	N/A
A-02	0.290	0.38	0.44	152	Maritime Way	32.0	0.414	9.65	27.91	49.6	0.989	23.81	27.91
A-01,R-01,R-02	0.910	0.90	1.00	Pump	Maritime Way	133.0	0.526	62.57	294.41	133.0	1.730	205.72	294.41
Post-Development Flow						170.3	-	72.2	322.3	192.8	-	229.5	322.3
Total Allowable Release Rate						193.4				193.4			

From: Kuruvilla, Santhosh <Santhosh.Kuruvilla@ottawa.ca>
Sent: Friday, May 20, 2022 9:42 AM
To: Anthony Mestwarp <a.mestwarp@novatech-eng.com>
Cc: Greg MacDonald <g.Macdonald@novatech-eng.com>
Subject: RE: D07-12-21-0017 - 1200 Maritime

Hi Anthony,

Following are the HGL data received from our water resources group for your use.

The 100 year HGL on Maritime from MHST13985- 13986 is: 94.40 to 94.30



Thanks,
Santhosh

From: Anthony Mestwarp <a.mestwarp@novatech-eng.com>
Sent: May 16, 2022 2:58 PM
To: Kuruvilla, Santhosh <Santhosh.Kuruvilla@ottawa.ca>
Subject: D07-12-21-0017 - 1200 Maritime

I am reviewing the SWM requirements for the 1200 Maritime site and would like to confirm the HGL within the STM sewer fronting the site.

Based on the design drawings for Maritime way the HGL varies 94.30-94.15 across the site frontage (refer to the attached). City Manhole numbers : MHST13985- 13986. Can you please confirm that this is still the case?

Thanks,

Anthony Mestwarp, P.Eng., Project Engineer | Land Development Engineering

NOVATECH Engineers, Planners & Landscape Architects

240 Michael Cowpland Drive, Suite 200, Ottawa, ON, K2M 1P6 | Tel: 613.254.9643 Ext. 216 | Fax: 613.254.5867

The information contained in this email message is confidential and is for exclusive use of the addressee.

,

This e-mail originates from the City of Ottawa e-mail system. Any distribution, use or copying of this e-mail or the information it contains by other than the intended recipient(s) is unauthorized. Thank you.

Le présent courriel a été expédié par le système de courriels de la Ville d'Ottawa. Toute distribution, utilisation ou reproduction du courriel ou des renseignements qui s'y trouvent par une personne autre que son destinataire prévu est interdite. Je vous remercie de votre collaboration.

,

2.0 STORMWATER MANAGEMENT - MINOR/MAJOR SYSTEM DESIGN

2.1 General

Traditionally, urban drainage systems were designed considering only the "minor system". A more recent trend however is to design the drainage system according to the dual drainage concept which considers both, the "minor" and the "major" systems. The "minor" drainage system is comprised mainly of street gutters, inlet catch basins, storm sewers and manholes. This system is designed to capture and convey runoff during frequent storm events with return periods up to 1:5 year. The major system is formed by swales/ditches, streets, open channels, stormwater management facilities and will accommodate runoff during storms exceeding 1:5 year up to 1:100 year.

Stormwater servicing for all lands included in the Central Business District of the Kanata Town Centre will be designed using the dual drainage concept, also know as the minor/major drainage system. Furthermore, the minor system on Urbandale's lands (and other lands such as the Penex Kanata Ltd. lands) will also be designed allowing the use of inlet control devices (ICD). With the use of ICD's, flows captured by catch basins can be limited to the conveyance capacity of the storm sewers and therefore minimizing the risk of unacceptable surcharges. With the use of ICD's in catch basin inlets, a higher level of protection (1:100 year) against flooding of basements having foundation drains connected to storm sewers is provided.

2.2 Minor System Design

Storm sewers for Urbandale's lands in the Central Business District of the Kanata Town Centre were sized using the Rational Method. An inlet time of 20 minutes and runoff coefficients ranging from 0.2 (parks) to 0.9 (high density commercial) as presented in Table 1.0 were used.

Table 1.0 - Urban Runoff Coefficients

Land Use	Runoff Coefficient
Park	0.20
Residential: - low	0.40
- medium	0.45
- high	0.50 and 0.60
Commercial	0.80 and 0.90

Rainfall intensities required by the Rational Method were taken from the City of Kanata's Intensity-Duration-Curve (IDF). A time of concentration was calculated based on an inlet time of 20 minutes and the 5 year rainfall intensity was extracted using this information. The storm sewer layout (for Street 'A'), drainage area limits and respective runoff coefficients are presented on Drawings 15712-STM (attached in pocket). Plan and profiles for the future Street 'A' are presented on Drawings 15712-01, 15712-02 and 15712-03. The Rational Method storm sewer design sheet for Urbandale's lands (Street 'A') located in the Central Business District is provided in Appendix 'B'.

2.3 Major System Design

A properly designed, constructed and maintained minor/major drainage system is the keystone to good urban drainage. The purpose of the major system is to convey excess runoff generated from severe events which are not captured by the sewer system without causing any damages. With the combination of a properly designed major system and ICD's installed on the minor system, the risk of property damage due to surcharged storm sewer is essentially eliminated, provided that the storm sewer is properly operated and maintained.

Basements in Urbandale's lands in the Central Business District of the Kanata Town Centre will be protected against flooding resulting from a surcharged storm sewer system by setting basement floors 0.3 m above the 1:100 year hydraulic grade line. To achieve this, Scepter Type 'A' ICD's (with a capture of 20 L/s for a head = 1.22 m) will be used in street catch basins to limit the minor system's carrying capacity. Since the road grades for the internal roads have not been designed at this stage, the location of the proposed catch basins have not

been determined. During the detailed design of the internal road grades, the use of Scepter Type 'A' ICD's will be specified. The number of contributing catch basins will be limited to the carrying capacity of the minor system. Furthermore, all storm sewer manholes should be provided with solid covers to limit sources of water which were not accounted for during the design of the minor system.

Overall grading plans will be prepared for Urbandale's lands located in the Central Business District to ensure that the minor/major drainage concept is properly implemented. Overland flow corridors will be carefully selected for these lands. Once the detailed design of these lands is completed, detailed plan and profiles and grading plans will be included in the submission package for a Certificate of Approval by the MOE.

2.4 On-Site Controls

The 1993 Master Drainage Study discussed and recommended the use of the following on-site controls in addition to end of pipe control (stormwater management facility):

1. Rooftop storage on flat roofs and parking lot storage in the commercial area, where feasible, to detain post-development flows.
2. Use of catch basin equipped with ICD's to control the rate of inflow to the storm sewer system.
3. Direction of the building roof downspouts, where possible, to grassed areas to minimize the runoff from hard surfaces and increase the recharge of the groundwater table.
4. Provision of grassed swales along the rear of lots (in residential development) at minimum slope to retard runoff and provide opportunity for infiltration.
5. Use of perforated leads to connect rear yard catch basins to increase groundwater recharge, where soils conditions are favourable.

The above measures should be investigated and evaluated site-specifically during the detailed design of each subdivision. The investigation and evaluation should be incorporated in the individual Stormwater Site Management Plan.

11.0 SUMMARY

- i) This Stormwater Management Report has been prepared to address a number of draft plan conditions for Urbandale's Kanata Town Centre Lands - Central Business District.
- ii) A detailed design for a Stormwater Management Facility, as recommended in the "Kanata Town Centre - Master Drainage Study for Watts Creek" (Cumming Cockburn Limited, May 1993), is presented.

Final approvals are required prior to construction.

- iii) Stormwater servicing for the tributary areas to the SWMF will be designed using the dual drainage concept. The storm sewer system (on Street 'A') has been sized to capture and convey a 1:5 year flow. The surface drainage, grading, and overland flow corridors will be designed to accommodate the flows in excess of 1:5 year up to 1:100 year.
- iv) Basements in future residential development will be protected against flooding during a 1:100 year event by installing Scepter Type 'A' ICD's in catch basins located within the streets and by setting the basement floor elevations 0.3 m above the 1:100 year HGL. As an additional precautionary measure, all lateral storm sewer services will be provided with a backwater valve.
- v) To maintain the integrity of the performance of the storm sewer, storm sewer manholes will be provided with solid manhole covers.
- vi) Building roof downspouts will be discharged onto grassed areas wherever possible, to reduce the volume and velocity of runoff as well as peak flows. This will also improve water quality slightly but, more importantly, will increase groundwater recharge.


Shows that the minor system be designed to 5-year and 100-year can safely be conveyed on the roadway.

SWMF provides quality control for the entire upstream drainage area, therefore no site-specific quality control is required.

- vii) A SWMF will be constructed in the southeast corner of the lands. This facility will incorporate a permanent pool storage of 5949 m³ (between elevations 88.90 m to 89.90 m), an extended detention storage of 2758 m³ (between elevations 89.90 m to 90.20 m) and a water quantity storage of 36491 m³ (between elevations 90.20 m to 93.25 m).
- viii) Landscaping will be incorporated into the pond design to provide a natural appearance and to improve overall performance.
- ix) A monitoring and maintenance program is proposed to demonstrate and ensure long-term acceptable performance. The parameters to be analyzed include total suspended solids (>70% TSS removal), dissolved oxygen, total and dissolved phosphorous, nitrates, nitrites, TKN, ammonia, chlorides, sodium and pH.
- x) Appropriate erosion and sediment control measures during construction will be implemented to trap sediments on-site.

Prepared by: _____
Guy Forget, P.Eng.

Reviewed by: _____
Maria F. Schouten, P.Eng.



1
64.83
65


HIGHWAY NO. 417

SOUTH TRUNK SEWER

LEGEND:

—	SUB-BASIN I.D. NO.	1
—	AREA IN HECTARES	3.75
—	CURVE NUMBER (CN)	12
—	SUB-BASIN I.D. NO.	2
—	AREA IN HECTARES	6.1
—	TOTAL IMPERVIOUSNESS	14.8

NO.	DATE	REVISIONS	BY	NO.	DATE	REVISIONS	BY



J.L. Richards & Associates Limited
 Consulting Engineers, Architect & Planners
 OTTAWA, KINGSTON, SUDBURY, CANADA


CHECKED C.F.
 CHECKED C.F.
 CHECKED T.A.G.'S.
 CHECKED
 APPROVED

CITY OF KANATA
 DEPARTMENT OF ENGINEERING
 AND PUBLIC WORKS


URBANDALE CORPORATION

**KANATA TOWN CENTRE
 EXISTING CONDITIONS**

DATE: JANUARY 1998
 SHEET NO.
FIGURE 2



NO.	DATE	REVISIONS	BY	NO.	DATE	REVISIONS	BY



J.L. Richards & Associates Limited
 Consulting Engineers, Architect & Planners
 OTTAWA, KINGSTON, SUDBURY, CANADA

DESIGN: C.F.
 CHECKED: C.F.
 DRAWN: T.L.O.B.
 DATE: 1/1/88

CITY OF KANATA
 DEPARTMENT OF ENGINEERING AND PUBLIC WORKS

URBANDALE CORPORATION

KANATA TOWN CENTRE
 FUTURE CONDITIONS

DATE: JANUARY 1988
 DRAWN: T.L.
FIGURE 3


LEGEND:

SUB-BASIN I.D. NO.	1
AREA IN HECTARES	3.75
CURVE NUMBER (CN)	12
SUB-BASIN I.D. NO.	2
AREA IN HECTARES	0.1
TOTAL IMPERVIOUSNESS	0.0

LEGEND

- CATCH BASIN
- INTERCONNECTED ROADWAY CB C/W ONE 19.8L/S IPEX TYPE 'A' ICD OR CITY APPROVED EQUIVALENT
- CATCH BASIN WITH INDIVIDUAL 19.8 L/S IPEX TYPE 'A' ICD OR CITY APPROVED EQUIVALENT
- HYDRANT
- STORM SEWER & MANHOLE
- LOT NUMBER
- DRAINAGE BOUNDARY
- AREA IN HECTARES
- RUNOFF COEFFICIENT
- PIPE REACH UPSTREAM MANHOLE TO DOWNSTREAM MANHOLE

NOTE:
MINOR SYSTEM CAPTURED RATE (Q_c)
FOR ALL PRIVATE & PUBLIC DEVELOPMENT,
NOT TO EXCEED 1:5 YEAR PEAK FLOW AT
THE GIVEN RUNOFF COEFFICIENT (REFER
TO DWG 15712-STM) USING AN INLET TIME
OF T_c=20min, IN ACCORDANCE WITH THE
KTC-CBD STORMWATER MANAGEMENT REPORT
PREPARED BY J.L.RICHARDS, JUNE 1999.



DATE	REVISIONS	BY	NO.	DATE	REVISIONS	BY
			5	02/11/06	PER CITY COMMENTS	CB
			4	13/09/06	ISSUED TO CITY FOR REVIEW	LND
8	24/07/07		3	21/07/06	ISSUED TO CITY FOR REVIEW (STREET 'A' NORTH-SOUTH LEG)	LND
7	25/05/07		2	05/11/98	REVISED PER RMOG	MFS
6	08/03/07		1	09/10/98	ISSUED FOR MOE APPROVAL (ST&M)	MFS

J.L. Richards
 ENGINEERS ARCHITECTS PLANNERS

SCALE
 0 10m 20m 30m 40m
 HORIZONTAL 1:1000

J.L. Richards & Associates Limited
 864 Lady Ellen Place
 Ottawa, ON Canada
 K1Z 5M2
 Tel: 613 728 3571
 Fax: 613 728 6012

THIS DRAWING IS COPYRIGHT
 PROTECTED AND MAY NOT BE
 REPRODUCED OR USED FOR
 PURPOSES OTHER THAN EXECUTION
 OF THE DESCRIBED WORK WITHOUT
 THE EXPRESS WRITTEN CONSENT
 OF J.L. RICHARDS & ASSOCIATES
 LIMITED.

DESIGN S.D.
 CHECKED M.F.S.
 DRAWN T.S.
 CHECKED
 APPROVED

URBANDALE CORPORATION
 KANATA TOWN CENTRE
 CENTRAL BUSINESS DISTRICT
 STORM DRAINAGE PLAN

PROJECT No.
 15712-NAD 83
 STARTED JUNE 1998
 DWG. No.
 15712-STM



CITY OF OTTAWA

KANATA TOWN CENTRE
CENTRAL BUSINESS DISTRICT
URBANDEALE CORPORATION
JLR PROJECT NO.: 15712

STORM SEWER DESIGN SHEET
IDF CURVE 1: 5

Designed by: C.B.
Checked by: D.L.


Date: May 25, 2007

5 YEAR IDF CURVE
Manning's Coefficient (n) = 0.013

LEGEND
DENOTES EXISTING SEWERS

MANHOLE NUMBER		DRAINAGE AREAS									1:5 YR PEAK FLOW GENERATION						ACTUAL						SEWER DATA						UPSTREAM						DOWNSTREAM					
From	To	0.20	0.30	0.40	0.50	0.60	0.80	0.80	0.90	area (ha)	cumm area (ha)	2.78AR	2.78AR CUMM	Time min	Intens. mm/hr	Peak Flow L/s	Dia (mm)	Dia (mm)	Slope %	Q full (l/s)	V full (m/s)	Length (m)	Flow Time (min)	Ex. Ground	Pr. Center Line	Obvert Drop	Obvert	Invert	Cover	Ex. Ground	Pr. Center Line	Obvert Drop	Forced Drop	Obvert	Invert	Cover	Dstroom Bend			
13	607	0.75				4.01	15.53	9.57		29.86	29.86	65.59	65.59	28.52	55.80	3659.80	1676.4	1650	0.19	4155.57	1.88	83.20	0.74		96.32			92.656	91.006	3.66		95.47			-0.15	92.497	90.847	2.97		
607	606					5.60	0.23			5.83	35.69	12.97	78.55	29.26	54.85	4308.72	1828.8	1800	0.21	5495.32	2.09	119.10	0.95		95.47			92.647	90.847	2.82		94.80			0.33	92.397	90.597	2.40	15.00	
635	634													20.00	70.25		304.8	300	2.90	171.80	2.35	51.50	0.36		103.38			97.681	97.381	5.70		102.56				96.187	95.887	6.37	13.00	
634	633					0.17	0.29			0.46	0.46	1.02	1.02	20.36	69.46	71.06	304.8	300	1.60	127.61	1.75	64.00	0.61		102.56			96.187	95.887	6.37		101.67				95.163	94.863	6.51	90.00	
633A	633							0.08		0.08	0.08	0.18	0.18	20.00	70.25	12.50	304.8	300	0.87	94.10	1.29	35.10	0.45		101.49			95.122	94.822	6.37				0.30	94.816	94.516	-94.82			
633	632									0.46		1.20	20.97	68.18	81.88		381	375	1.00	182.91	1.50	64.70	0.67		101.67			95.163	94.788	6.51		101.29				94.516	94.141	6.77	13.00	
632	631					1.16	0.31			1.47	1.93	3.27	4.47	21.65	66.83	298.76	533.4	525	1.00	448.66	2.01	74.80	0.62		101.29			94.516	93.991	6.77		97.55				93.768	93.243	3.78	80.00	
636	631							0.25		0.25	0.25	0.56	0.56	20.00	70.25	39.06	304.8	300	2.23	150.65	2.06	93.30	0.75		102.26			95.849	95.549	6.41		97.55				93.768	93.488	3.78		
631	630									2.18		5.03	22.27	65.64	329.91		533.4	525	3.85	880.33	3.94	81.10	0.34		100.65			96.921	96.396	3.73		97.55		0.03	93.798	93.273	3.75			
630	606A	0.36					0.41			0.77	1.11	6.14	22.61	65.00	398.97		533.4	525	1.35	521.29	2.33	88.90	0.64		97.55			93.768	93.243	3.78		94.64		0.03	92.568	92.043	2.07	18.00		
606A	606									0.77		6.14	23.25	63.85	391.91		533.4	525	1.35	521.29	2.33	4.90	0.04		94.64			92.538	92.013	2.10		94.80		0.41	92.472	91.947	2.33	81.00		
606	605						0.35			0.35	36.81	0.78	85.47	30.21	53.66	4587.99	(1) 1828.8	(1) 1800	0.25	6049.60	2.30	110.40	0.80		94.80			92.065	90.590	2.74		94.69		0.02	91.784	90.309	2.91			
605	604					2.94	0.25			3.19	40.00	7.09	92.57	31.00	52.73	4881.44	(1) 1828.8	(1) 1800	0.24	5911.34	2.25	67.40	0.50		94.69			91.765	90.290	2.93		94.50	0.06	-0.02	91.601	90.126	2.90	90.00		
642	641						0.13			0.13	0.13	0.29	0.29	20.00	70.25	20.31	381	375	1.85	248.79	2.18	71.30	0.54		100.26			97.259	96.884	3.00		98.94				95.940	95.565	3.00		
641	640					1.10	0.14			1.24	1.37	2.76	3.05	20.54	69.08	210.47	457.2	450	0.80	266.03	1.62	77.70	0.80		98.94			95.940	95.490	3.00		98.33				95.318	94.868	3.01		
640	612					1.02	0.14			1.16	2.53	2.58	5.63	21.34	67.43	379.43	609.6	600	0.66	520.98	1.79	82.30	0.77		98.33			95.318	94.718	3.01		97.86			-0.04	94.774	94.174	3.09	80.00	
614	613						0.12			0.12	0.12	0.27	0.27	20.00	70.25	18.75	304.8	300	2.16	148.20	2.03	51.20	0.42		100.07			96.938	96.638	3.13		98.96				95.833	95.533	3.13		
613	612					1.12	0.14			1.26	1.38	2.18	2.45	20.42	69.34	169.64	381	375	1.98	257.25	2.26	51.60	0.38		98.96			95.833	95.458	3.13		97.86				94.813	94.438	3.05		
612	611	0.27					0.16			0.43	4.34	0.51	8.58	22.11	65.93	565.64	685.8	675	3.12	1548.97	4.19	49.60	0.20		97.86			94.813	94.138	3.05		96.45		0.03	93.285	92.590	3.18			
611	601					0.90	0.72			1.78	6.12	3.46	12.04	22.31	65.56	789.16	685.8	675	1.60	1109.24	3.00	44.10	0.24		96.45			93.235	92.560	3.21		94.93	0.06			92.530	91.855	2.40	80.00	
601	604						0.07			0.07	6.19	0.16	12.19	22.55	65.10	793.79	685.8	675	1.42	1044.99	2.83	67.50	0.40		94.93			92.470	91.795	2.46		94.50			-0.05	91.511	90.836	2.99	90.00	
604	Chamber										46.19		104.76	31.50	52.16	5464.60	(1) 1828.8	(1) 1800	0.21	5495.32	2.09	14.40	0.11		94.50			91.556	90.081	2.94		94.00			-0.01	91.526	90.051	2.47		
Chamber	Pond										46.19		104.76	31.62	52.03	5451.05	1524	2x1500	0.33	8472.67	2.32	11.50	0.08		94.50			91.539	90.039	2.96		94.00				91.501	90.001	2.50		

(1) The equivalent size of a round pipe is shown to simplify spreadsheet calculations. The actual existing pipe is a horizontal elliptical 1475 x 2310 HE III.



TECHNICAL MEMORANDUM



**J.L. Richards
& Associates Limited**
864 Lady Ellen Place
Ottawa, ON Canada
K1Z 5M2
Tel: 613 728 3571
Fax: 613 728 6012

PAGE 1 OF 4

TO: Urbandale Corporation
c/o Mary Jarvis, MCIP, RPP
Director of Planning

DATE: June 13, 2012

JOB NO.: 15712-10

FROM: Jonathan Párraga, P.Eng.
RE: Servicing Brief (Revised)
Kanata Town Centre
Central Business District Subdivision

CC: J.L. Richards & Associates Limited
Attention: Lucie Dalrymple, P.Eng.

PURPOSE OF UNDERTAKING

This Servicing Brief was prepared, in support of Urbandale Corporation's re-zoning application for the Kanata Town Centre - Central Business District (KTC-CBD) Subdivision. The following confirms that water, sanitary and storm sewer services are readily available to accommodate this subdivision.

DESCRIPTION OF PROPERTY

The subject lands encompass an area of approximately 18.8 hectares within the KTC-CBD, in the City of Ottawa (former City of Kanata). The lands are bounded to the north by Campeau Drive, to the west by a partial of land fronting Castlefrank Drive, south by Hwy. 417 and to the east by the Hydro One corridor (refer to Figure 1 attached). This subdivision is comprised of residential and commercial developments. Civil infrastructure (i.e., local watermains, storm and sanitary sewers) within the ROWs are all existing and in service. The trunk storm sewer, sanitary sewer, and watermain along the south leg of Maritime Way were constructed by Urbandale Corporation in 1998 and the remaining local infrastructure in 2007-2008. The 900 mm dia. feedermain on Great Lakes Avenue was constructed for the City of Ottawa in 2008-2009.


STORM SEWER SERVICING

Outlet:

The KTC-CBD lands are tributary to the KTC-CBD Stormwater Management Facility (SWMF) located in the southeast corner of the subdivision (refer to Figure 1 for Pond location), which subsequently drains to Watts Creek. This SWMF was designed, and subsequently constructed, to accommodate the development of the KTC-CBD subdivision and provides quantity as well as quality control for the stormwater flows. Details of the SWMF can be found in the Stormwater Management Report, Kanata Town Centre, Central Business District, dated January 1999 and prepared by J.L. Richards & Associates Limited.

Minor/Major System:

The KTC-CBD storm drainage system has been designed using the dual drainage concept, consisting of a minor and a major system. The minor system conveys storm runoff generated during frequent storm events (i.e., 1:5 year or less) via a local storm sewer collection system outletting to the KTC-CBD



**KANATA TOWN CENTRE
CENTRAL BUSINESS DISTRICT
(KTC-CBD)**



PROJECT: KTC-CBD
URBANDALE CORPORATION
CITY OF OTTAWA

DRAWING: KEY PLAN



J.L. Richards
& Associates Limited
864 Lady Ellen Place
Ottawa, ON Canada
K1Z 5M2
Tel: 613 728 3571
Fax: 613 728 6012

DESIGN:	DRAWN: T.S.
DATE: OCT. 2006	
SCALE: N.T.S.	

DRAWING No.:	FIG. 1
JOB No.:	

SWMF where, as noted, water quality and quantity treatment is provided. In accordance with the noted SWMF Design Report, the following runoff coefficients were used at detailed design of the local storm sewers

Residential - Low Density	C=0.40
Residential - Medium Density	C=0.45
Residential - High Density	C=0.50 and 0.60
Commercial Area	C=0.80 and 0.90
Parkland	C=0.20

An excerpt from the noted 1999 Stormwater Management Report, indicating assigned runoff coefficients 'C', allowable capture rates, and required on-site storage volumes for the specific land parcels is included in Attachment 1. The servicing design for each Block in the KTC-CBD shall adhere to these SWM design requirements.

The major system was established at the detailed design stage to convey excess runoff generated during severe events which would not be captured in the minor system. The excess runoff will be conveyed via overland routes to the KTC-CBD SWMF. The grading plans of the KTC-CBD lands have been developed with roadway sags. Local Blocks of land are expected to incorporate parking lot, cistern and roof top storage (or a combination thereof) at Site Plan Control, to ensure that the minor / major drainage concept, as specified in the Attachment 1 Table, is properly implemented.

A Hydraulic Grade Line (HGL) Analysis was carried out during detailed design to verify the anticipated amount of freeboard provided between the maximum storm sewer HGL elevations and the building underside of footing elevations. At detailed design of each Block, and as required at Site Plan Control, the on-site HGL clearance will require confirmation. The analysis was based on the estimated maximum water elevations of the KTC-CBD SWMF.

WATER SERVICING

The local network of water servicing for the KTC-CBD Subdivision was originally developed based on the existing 610 mm and 406 mm diameter watermains on Maritime Way. Water servicing specifics for the subdivision were addressed in detail in the Hydraulic Network Analysis (HNA) Report, which was prepared and submitted to the City in conjunction with the detailed servicing design of this project. The HNA Report for KTC-CBD demonstrated that the proposed (now existing) watermain sizing satisfied the water demand during the maximum hourly and fire flow conditions, as per the City of Ottawa Design Guidelines. Furthermore, the analysis included an assessment of pressures during low demand conditions (i.e., high pressure check) ensuring that the system pressures do not exceed the maximum pressure requirements set by the Ontario Building Code (OBC).

Since then a 900 mm diameter feedermain was constructed in 2008-2009 on Great Lakes Avenue, linking the existing 610 mm diameter feedermain on Maritime Way to the existing 900 mm diameter feedermain on Campeau Drive. At detailed design of each Block, and as required at Site Plan Control, the designer will have to obtain boundary conditions from the City of Ottawa and carry out an HNA for their respective Block.

SANITARY SEWER SERVICING

There is an existing 825 mm diameter trunk sanitary sewer along the south leg of Maritime Way and extends easterly along a service easement to Gray Crescent in Village Green. This sanitary trunk sewer was designed by JLR (1998) to accommodate the development of the KTC-CBD subdivision and upstream lands. Local sanitary sewers were subsequently designed by JLR (2007) and constructed. At the time of the original design of the trunk sewer the land parcels were designated for commercial use and the sanitary flows were estimated using 50,000 L/ha/d (MOE guidelines for sanitary flow for commercial zones). Subsequently, the land use was revised to include residential use, as well as commercial use. As such, in 2007, JLR revised the original sanitary flow estimate according to the projected land use to design the local sewers. Currently, Blocks 3, 6 and 8 have been sold and either developed or partially developed. As such, the estimated sanitary flows generated by the local Blocks have currently been updated to reflect exiting conditions and projected development of local Blocks. Table 1 provides a summary of the existing and anticipated land uses.

Table 1 - Kanata Town Centre Existing and Anticipated Land Uses

Block No.	Land Use Description	Number of Units/Rooms	Population	Daily Sewage Flow	Area
1	Hotel Suites	167	301	270 L/pp/d*	1.48
2	Commercial			50,000 L/pp/d	1.36
3	Retirement Home	208	333		1.02
4	Apartments	120	216	350 L/pp/d	1.37
5	Apartments	120	216	350 L/pp/d	1.02
6	Apartments with Community Centre			350 L/pp/d**	2.83
7	Commercial	N/A		50,000 L/pp/d	1.70
8	Hotel	125	225	270 L/pp/d*	1.02
9	Commercial	N/A	N/A	50,000 L/pp/d	4.96
10	Walkway Easement	N/A	N/A	N/A	0.28

Note: * Additional flow of dining room and staff accounted for in design

** Additional flow from Community Centre pool 40 L/pp/d accounted for in design

The current peak flow estimate has been revised in accordance with the land uses presented in Table 1. A comparison of the original peak flow estimate (1998) and the current peak flow estimate is presented in Table 2. The revised peak flow estimate, based on the current land use projections and existing land uses, creates an increase of estimated flow of 4.05 L/s (274.66 L/s – 270.61 L/s) at the Trunk easement. This flow, however, with a reduction in the downstream peaking factor due to the increase in residential units in the CBD, normalizes close to the original (1998) estimated flow and actually estimates a small reduction of 0.15 L/s (475.94 L/s - 475.79L/s) at the end of the residential subdivision at the intersection of Campeau Drive and Teron Road. The original peak flow design estimate (1998) and the updated detailed design spreadsheet, as well as the sanitary drainage boundary plan, can be found in Attachment 2.

Table 2 - Kanata Town Centre Estimated Sanitary Peak Flow

Location	Tributary Area	Up MH	Down MH	Original Assigned Flow Estimate (1998)	Current Flow Estimate (2012)
Trunk Easement	Upstream + KTC-CBD	500	94	270.61	274.66
Total Flow at end of Residential	Upstream + KTC-CBD + Residential to Teron Road	Ex.	Ex. 2	475.94	475.79

SUMMARY

The existing trunk (1998) and local (2007-2008) infrastructure servicing the subject lands, which are referred to as KTC-CBD, have capacity to service the local Blocks, with regards to stormwater and wastewater; based on the SWM design parameters provided in Attachment 1 and wastewater based on the revised existing and proposed land uses as per Table 1 of this report.. Domestic water is available along the frontage of each Block with the understanding that a site specific HNA is to be carried out at Site Plan Control to demonstrate conformance with the City Guidelines

Revised by:

J.L. RICHARDS & ASSOCIATES LIMITED

Jonathan Párraga, P.Eng.


JP:jd
Attach.



ATTACHMENT 1

Kanata Town Centre - Central Business District Stormwater Design Criteria - Tributary Areas to SWMF

DRAINAGE AREA No.	Description	Area (ha)	TIMP (%)	C factor	Allowable Capture Rate	On-Site Storage	Required on-site Storage Volume
1	AMC Site	7.85	85	0.80	1:5 year	Yes	up to 100 yr
2	Park & Ride	1.46	95	0.87	1:5 year	No	
3	Phase IV	3.03	95	0.87	1:5 year	Yes	up to 100 yr
4	Transitway	3.55	95	0.87	1:5 year	No	
5	Hotel Road	0.38	80	0.76	1:5 year	No	
6	Hotel Site	0.80	95	0.87	1:5 year	Yes	up to 100 yr
7	Castlefrank Road	2.84	80	0.76	1:10 year	No	
8	Adjacent Lands	2.77	57	0.60	1:10 year	No	
9	Exist Pond **	0.82	---	0.20	1:10 year	Yes	up to 100 yr
10	Kanata North	4.66	85	0.80	1:5 year	No	
11	Adj Lands (east)	2.16	85	0.80	1:5 year	No	
12	Adj Lands (south-east)	2.11	85	0.80	1:5 year	Yes	up to 100 yr
13	Street "A"	1.32	85	0.80	1:5 year	Limited	up to 10 yr
14	Urbandale North	10.41	85	0.80	1:5 year	Limited	up to 10 yr
15	Urbandale South	4.48	85	0.80	1:5 year	Yes	up to 100 yr
16	Urbandale East	1.82	57	0.60	1:5 year	Limited	up to 10 yr
17	Urbandale East (park)	0.54	---	0.20	1:5 year	No	
18	Queensway	7.87	30	0.41	1:100 year	No	
19	SWMF	0.95	52	0.56	1:100 year	No	



ATTACHMENT 2



CITY OF OTTAWA

KANATA TOWN CENTRE
CENTRAL BUSINESS DISTRICT
URBAN DALE CORPORATION
JLR PROJECT NO.: 15712

Commercial Flow = 50000 L/ha/d
q residential = 350 l/cap/d
q hotel = 270 l/cap/d
q retirement homes = 450 l/cap/d
i = 0.28 l/s/ha
SING. HOUSING 3.4 pers/hse
MULT. HOUSING 2.7 pers/hse
Hotel/Appartments 1.8 pers/room
Retirement Homes 1.6 pers/room

SANITARY SEWER DESIGN SHEET
Designed: C.B.
Revised by: J.L.P.
Checked By: D.L.

Manning's Coefficient (n) = 0.013

Date: May 28, 2012

STREET	M.H. # FROM TO		RESIDENTIAL											COMMERCIAL / INSTITUTIONAL			PLUGGED FLOW		R+C		SEWER DATA																		
			SING.	Stacks	Towns	NUMBER OF UNITS			POPUL. people	AREA ha	POPUL. people	AREA ha	PEAKING FACTOR	POPUL. FLOW l/s	AREA ha	CUMM. AREA ha	COMM. FLOW l/s	FLOW l/s	CUMM. FLOW l/s	PEAK EXTR. FLOW l/s	PEAK DES. FLOW l/s	DIA. mm	SLOPE %	CAPAC. l/s	VEL. m/s	LENGTH m													
						Ext. Care		Hotel/Apart.																			Equ. pop.												
						No units	Act. pop	No units																				Act. pop.											
MARITIME WAY	7A	507										(1) 2588	(1) 28.38	2588	28.38	3.50	36.65	(1) 23.16	23.16	20.10	(1) 162.69	162.69	14.43	233.88	825	0.14	529.34	0.99	81.90										
MARITIME WAY	507	506										125	225	174	174	1.02	2762	29.40	3.47	38.85	4.91	28.07	24.37	162.69	16.09	242.00	825	0.12	500.32	0.94	119.30								
CORDILLERA ST.	534	533																	4.00	0.55							200	1.65	42.13	1.34	66.60								
CANADIAN SHIELD AV.	533	532																	4.00	0.55							200	1.20	35.93	1.14	69.60								
CANADIAN SHIELD AV.	532	531											167	301	234	234	1.48	234	1.48	4.00	3.79				0.57	4.84	200	1.20	35.93	1.14	69.60								
GREAT LAKES AV.	536	531																														200	2.40	50.81	1.62	60.00			
GREAT LAKES AV.	531	530																																					
GREAT LAKES AV.	530	506A																																					
GREAT LAKES AV.	506A	506																																					
MARITIME WAY	506	505											176	316.8	269	269	0.57	3265	32.07	3.41	45.11				162.69	16.99	249.64	825	0.12	486.76	0.91	111.00							
MARITIME WAY	505	504											146	262.8	230	230	0.56	3495	32.63	3.39	47.93	1.75			162.69	17.64	254.62	825	0.11	484.63	0.91	114.40							
MARITIME WAY	504	501																																					
CANADIAN SHIELD AV.	542	541											176	316.8	269	269	0.74	269	0.74	4.00	4.36					0.21	4.57	200	2.20	48.64	1.55	71.30							
CANADIAN SHIELD AV.	541	540											154	277.2	232	232	0.51	501	1.25	3.97	8.06	1.36				0.73	9.98	200	0.90	31.13	0.99	77.70							
	Block 3	540											208	333	428	428	1.02	428	1.02	4.00	6.93					0.29	7.22	200	0.60	25.40	0.81	12.00							
CANADIAN SHIELD AV.	540	512																																					
MARITIME WAY	514	513																																					
MARITIME WAY	513	512											120	216	216	216	1.37	216	1.37	4.00	3.50						0.38	3.88	200	2.28	49.52	1.58	51.90						
MARITIME WAY	512	511																																					
MARITIME WAY	511	510																																					
MARITIME WAY	510	501																																					
TRUNK EASEMENT	501	500																																					
TRUNK EASEMENT	500	94																																					
A	90	92			35								95	0.80	95	0.80	4.00	1.53								0.22	1.76	250	0.60	46.06	0.94	120.0							
	92	94			12								32	1.19	127	1.99	4.00	2.06								0.56	2.61	250	2.20	88.20	1.80	103.0							
	94	95																																					
	95	89			10								27	0.52	5041	40.58	3.24	66.20																					
B	85	87	19										65	1.19	65	1.19	4.00	1.05									0.33	1.38	250	0.40	37.61	0.77	116.9						
	87	89			24								65	0.82	129	2.01	4.00	2.10									0.56	2.66	250	1.41	70.70	1.44	116.7						
A	89	84			12								32	0.35	5230	43.46	3.23	68.36																					
C	80	82	19										65	1.08	65	1.08	4.00	1.05									0.30	1.35	250	0.40	37.61	0.77	120.0						
	82	84			25								68	0.83	132	1.91	4.00	2.14									0.53	2.68	250	1.20	65.18	1.33	118.5						
A	84	79			14								38	0.54	5399	45.91	3.21	70.30																					



CITY OF OTTAWA

KANATA TOWN CENTRE
CENTRAL BUSINESS DISTRICT
URBANDALE CORPORATION
JLR PROJECT NO.: 15712

Commercial Flow = 50000 L/ha/d
q residential= 350 l/cap/d
q hotel = 270 l/cap/d
q retirement homes = 450 l/cap/d
i = 0.28 l/s/ha
SING. HOUSING 3.4 pers/hse
MULT. HOUSING 2.7 pers/hse
Hotel/Appartments 1.8 pers/room
Retirement Homes 1.6 pers/room

SANITARY SEWER DESIGN SHEET
Designed: C.B.
Revised by: J.L.P.
Checked By: D.L.

Manning's Coefficient (n) = 0.013

Date: May 28, 2012

STREET	M.H. # FROM TO		RESIDENTIAL													COMMERCIAL / INSTITUTIONAL			PLUGGED FLOW		R+C		SEWER DATA																			
			SING.	Stacks	Towns	NUMBER OF UNITS			POPUL. people	AREA ha	POPUL. people	AREA ha	PEAKING FACTOR	POPUL. FLOW l/s	AREA ha	CUMM. AREA ha	COMM. FLOW l/s	FLOW l/s	CUMM. FLOW l/s	PEAK EXTR. FLOW l/s	PEAK DES. FLOW l/s	DIA. mm	SLOPE %	CAPAC. l/s	VEL. m/s	LENGTH m																
						Ext. Care No units	Act. pop	Hotel/Apart. No units																			Act. pop.	Equ. pop.														
D	75	76			17					46	0.37	46	0.37	4.00	0.74																											
	76	77			20					54	0.29	100	0.66	4.00	1.62																											
	77	79			13					35	0.63	135	1.29	4.00	2.19																											
PARK EASEMENT	79	67																																								
	67	66			6					16	0.33	5551	48.51	3.20	72.01																											
BELLROCK DRIVE	70	73		12	14					70	2.56	70	2.56	4.00	1.14																											
	73	74			12					32	0.54	103	3.10	4.00	1.66																											
EASEMENT	74	62																																								
CAMBRA Y LANE	62	66			25					68	0.48	170	3.89	4.00	2.76																											
BISHOPS MILLS WAY	66	65			9					24	0.53	5745	52.93	3.19	74.21																											
SOUTH of HWY 417	EX.	65								(1) 7792	(1) 191.60	7792	191.60	3.06	96.63						(4) 37.72	37.72	53.65	188.00	900	0.11	600.38	0.94														
BISHOPS MILLS WAY	65	64			2					5		13542	244.53	2.82	154.86																											
EDENVALE DRIVE	59	60			8					22	0.50	22	0.50	4.00	0.35																											
KETTLEBY STREET	60	61			22					59	0.62	81	1.12	4.00	1.31																											
CAMBRA Y LANE	58	61			5					14	0.41	14	0.41	4.00	0.22																											
KETTLEBY STREET	61	64			25					68	0.42	162	1.95	4.00	2.63																											
BISHOPS MILLS WAY	64	63			3					8		13713	246.48	2.82	156.51																											
	63	57			10					27	0.68	13740	247.16	2.82	156.77																											
TER. BUNGALOW Ph.2	51	53			48					130	0.94	130	0.94	4.00	2.10																											
	53	54			4					11		140	0.94	4.00	2.28																											
	54	55																																								
BISHOPS MILLS WAY	55	56			11					37	0.81	178	2.02	4.00	2.88																											
	56	57			7					56	0.65	234	2.67	4.00	3.79																											
PARK	57	34			1					3	0.37	13976	250.20	2.81	159.04																											
	34	33			3					8		13984	250.20	2.81	159.12																											
HAWKSTONE	43	44			22					59	1.19	59	1.19	4.00	0.96																											
	44	45			8					22	0.09	81	1.28	4.00	1.31																											
ENDENVALE	45	35																																								
BIRKENDALE DRIVE	35	36			7					24	1.18	105	2.54	4.00	1.70																											
	36	37			13					44	0.79	149	3.33	4.00	2.41																											
	37	33			2					15		164	3.33	4.00	2.66																											
BIRKENDALE DRIVE	33	32			10					27	0.56	14175	254.09	2.80	160.95																											
TEESWATER STREET	30	31			16					43	0.66	43	0.66	4.00	0.70																											
	31	32			19					51	0.41	95	1.07	4.00	1.53																											
BIRKENDALE STREET	32	18			6					16	0.37	14286	255.53	2.80	162.01																											



CITY OF OTTAWA

KANATA TOWN CENTRE
CENTRAL BUSINESS DISTRICT
URBAN DALE CORPORATION
JLR PROJECT NO.: 15712



Commercial Flow = 50000 L/ha/d
 q residential = 350 l/cap/d
 q hotel = 270 l/cap/d
 q retirement homes = 450 l/cap/d
 i = 0.28 l/s/ha
 SING. HOUSING 3.4 pers/hse
 MULT. HOUSING 2.7 pers/hse
 Hotel/Appartments 1.8 pers/room
 Retirement Homes 1.6 pers/room

SANITARY SEWER DESIGN SHEET
 Designed: C.B.
 Revised by: J.L.P.
 Checked By: D.L.

Manning's Coefficient (n) = 0.013

Date: May 28, 2012

STREET	M.H. #		RESIDENTIAL													COMMERCIAL / INSTITUTIONAL			PLUGGED FLOW		R+C		SEWER DATA					
			SING.	Stacks	Towns	NUMBER OF UNITS			POPUL. people	AREA ha	POPUL. people	AREA ha	PEAKING FACTOR	POPUL. FLOW l/s	AREA ha	CUMM. AREA ha	COMM. FLOW l/s	FLOW l/s	CUMM. FLOW l/s	PEAK EXTR. FLOW l/s	PEAK DES. FLOW l/s	DIA. mm	SLOPE %	CAPAC. l/s	VEL. m/s	LENGTH m		
						Ext. Care	Hotel/Apart.	Equ. pop.																			No units	Act. pop
	18	16			4					11		14297	255.53	2.80	162.12													
COMMERCIAL PLAZA	19	17												4.00						0.15	0.60	150	0.90	14.45	0.82	26.5		
COLCHESTER SQUARE	17	16										0.10	0.10	4.00						0.17	0.62	250	0.40	37.61	0.77	33.2		
COLCHESTER SQUARE	16	15			10					27	0.56	14324	256.19	2.80	162.38			32.25	27.99	200.41	80.76	471.54	900	0.11	600.38	0.94	66.0	
	15	14 A			2					5		14329	256.19	2.80	162.43			32.25	27.99	200.41	80.76	471.59	900	0.11	600.38	0.94	25.8	
ELSINORE LANE	39	28			32					86	0.53	86	0.53	4.00	1.40													
	28	24			18					49	1.47	135	2.00	4.00	2.19					0.56	2.75	250	0.40	37.61	0.77	43.0		
	24	23			12					32	0.14	167	2.14	4.00	2.71					0.60	3.31	250	0.40	37.61	0.77	34.0		
ELSINORE LANE	23	306			8					22	0.24	189	2.38	4.00	3.06					0.67	3.73	250	0.44	39.41	0.80	48.8		
ENDENVALE DRIVE	306	14 A									0.45	189	2.83	4.00	3.06					0.79	3.85	250	0.49	41.68	0.85	46.4		
COLCHESTER SQUARE	14 A	14										14518	259.02	2.79	164.23			32.25	27.99	200.41	81.56	474.19	900	0.11	600.38	0.94	14.7	
	Church	14												4.00				0.52	0.52	0.45			150	1.00	15.23	0.86	35.0	
COLCHESTER SQUARE	14	11			4					11	0.16	14529	259.18	2.79	164.34			32.77	28.45	200.41	81.75	474.94	900	0.11	600.38	0.94	72.6	
TERON	11	10										14529	259.18	2.79	164.34			32.77	28.45	200.41	81.75	474.94	900	0.11	600.38	0.94	29.6	
	10	EX.										0.25	14529	259.43	2.79	164.34			32.77	28.45	200.41	81.82	475.01	900	0.11	600.38	0.94	72.3
TERON	O.P.P.	EX.												4.00						0.78	0.78		100	Forcemain				
TERON	EX.	EX. 2										14529	259.43	2.79	164.34			32.77	28.45	201.19	81.82	475.79	680	0.96	838.61	2.31	9.4	
			(1) As per Kanata Town Centre Sanitary Trunk Sewer Study, revised March 27, 1996, by Robinson Consultants Inc. (2) Park or open space area. (3) Equivalent population base on 208 rooms and 20 staff members. (4) Allowance for an ultimate flow of 188 l/s to provide flexibility in future development as per Kanata Town Centre Sanitary Trunk Study.																									



CITY OF OTTAWA LANDS
 Q = 233.88 l/s PER
 KANATA TOWN CENTRE
 TRUNK SANITARY SEWER
 DESIGN DATED 1998

VACANT LAND

DATE	REVISIONS	BY	NO.	DATE	REVISIONS	BY
09/03/07	ISSUED FOR TENDER	CSB	1	08/06/98	ISSUED FOR MCE APPROVAL (SAN)	LND
25/05/07	PHASE 2 ISSUED FOR CITY REVIEW	CSB	2	05/11/98	REVISED PER RMOC	LND
24/07/07	REVISED AS PER CITY COMMENTS	CSB	3	21/07/06	ISSUED TO CITY FOR REVIEW (SUBSET 'A', NORTH-SOUTH LEG)	LND
12/06/12	REVISED CSD DRAINAGE	ALP	4	13/09/06	ISSUED TO CITY FOR REVIEW	LND
02/11/06	PER CITY COMMENTS	CSB	5	02/11/06	PER CITY COMMENTS	CSB

1st No. 169380
 By Municipal

SCALE
 0 10m 20m 30m 40m
 HORIZONTAL 1:1000

J.L. Richards & Associates Limited
 884 Lady Ellen Place
 Ottawa, ON Canada
 K1Z 5M2
 Tel: 613 728 8771
 Fax: 613 728 6012

J.L. Richards
 ENGINEERS-ARCHITECTS-PLANNERS

THIS DRAWING IS COPYRIGHTED AND MAY NOT BE REPRODUCED OR USED FOR ANY PURPOSE WITHOUT THE EXPRESS WRITTEN CONSENT OF J.L. RICHARDS & ASSOCIATES LIMITED.

DESIGN	C.B.
CHECKED	L.N.D.
DRAWN	T.S.
CHECKED	
APPROVED	



PROJECT No. 15712-NAD 83
 STARTED LINE 1998
 DWG. No. 15712-SAN

KANATA TOWN CENTRE
 CENTRAL BUSINESS DISTRICT
 SANITARY DRAINAGE PLAN


URBANDALE CORPORATION

Ottawa

HWY 417



DATE	REVISIONS	BY	NO.	DATE	REVISIONS	BY
12/06/12	REVISED CBD DRAINAGE	JP	2			
18/01/08	ISSUED TO CITY FOR REVIEW	CB	1			



V:\15712-NAD81\15712 C OVSAN-NAD81.DWG

J.L. Richards & Associates Limited
 864 Lady Ellen Place
 Ottawa, ON Canada
 K1Z 5M2
 Tel: 613 728 3571
 Fax: 613 728 6012

THIS DRAWING IS COPYRIGHT PROTECTED AND MAY NOT BE REPRODUCED OR USED FOR PURPOSES OTHER THAN EXECUTION OF THE DESCRIBED WORK WITHOUT THE EXPRESS WRITTEN CONSENT OF J.L. RICHARDS & ASSOCIATES LIMITED.

DESIGN	C.B.
CHECKED	L.N.D.
DRAWN	T.S.
CHECKED	
APPROVED	



PROJECT No. 15712-NAD 83
 STARTED DEC. 2007
 DWG. No. 15712-OVSAN

**KANATA TOWN CENTRE
 CENTRAL BUSINESS DISTRICT
 OVERALL SANITARY DRAINAGE PLAN**

APPENDIX D

Water Servicing Information

Table 1 Water Demand								
Occupancy	Unit Type				Total Population	Total Demand (L/s)		
	Retail Area (Seats)	1 Bed Apartment	2 Bed Apartment	Total Units		Avg Day	Max. Daily	Peak Hour
West Apartment (Phase 1)								
Residential		185	128	313	528	1.71	4.28	9.41
Commercial						0.00	0.00	0.00
Total		185	128			1.71	4.28	9.41
East Apartment (Phase 2)								
Residential		186	116	302	504	1.63	4.08	8.98
Commercial	100					0.14	0.22	0.39
Total		186	116			1.78	4.30	9.37
Total Development					1032	3.49	8.58	18.79

Design Parameters:

- 1 Bed Apartment **1.4 persons/unit**
- 2 Bed Apartment **2.1 persons/unit**

City of Ottawa Water Distribution Guidelines

- Average Domestic Flow 280 L/c/day L/person/day
- "Commerical Space A" Café 125 L/day/seat (assume 1 seat/4m²)
- Total:** 399m²


Residential Peaking Factors City of Ottawa Water Distrubution Guidelines:

Conditions	Peaking Factor	Units
Maximum Day	2.5 x avg day	L/c/day
Peak Hour	2.2 x max day	L/c/day





Commercial Peaking Factors City of Ottawa Water Distribution Guidelines


Conditions	Peaking Factor	Units
Maximum Day	1.5 x avg day	L/c/day
Peak Hour	1.8 x max day	L/c/day

M:\2020\120144\CAD\Design\Figures\Hydraulic\120144 - FUS Separation.dwg, 11x17 landscape, Apr 28, 2022 - 10:55am, cferguson



LEGEND

-  PROPERTY LINE
-  PROPOSED TACTILE INDICATOR
-  PROPOSED ENTRANCE
-  PROPOSED DEPRESSED CURB




NOVATECH

Engineers, Planners & Landscape Architects
Suite 200, 240 Michael Cowpland Drive
Ottawa, Ontario, Canada K2M 1P6


Telephone (613) 254-9643
Facsimile (613) 254-5867
Website www.novatech-eng.com

CITY OF OTTAWA
1200 MARITIME WAY


FUS SEPARATION

SCALE 1 : 750 






DATE APRIL 2022 JOB 120144 FIGURE SEP



M:\2020\120144\CAD\Design\Figures\Hydraulic\120144 - Hydrant Separation.dwg, 11x17 landscape, Apr 28, 2022 - 11:14am, cferguson



LEGEND

-  PROPERTY LINE
-  PROPOSED SIAMESE CONNECTION
-  EXISTING CLASS AA HYDRANT
-  PROPOSED PRIVATE HYDRANT
-  DISTANCE FROM HYDRANT TO SIAMESE CONNECTION

NOVATECH

Engineers, Planners & Landscape Architects
Suite 200, 240 Michael Cowpland Drive
Ottawa, Ontario, Canada K2M 1P6

Telephone (613) 254-9643
Facsimile (613) 254-5867
Website www.novatech-eng.com

CITY OF OTTAWA
1200 MARITIME WAY

COVERAGE PLAN

SCALE 1 : 500 

DATE APRIL 2022 JOB 120144 FIGURE HYD

FUS - Fire Flow Calculations

As per 2020 Fire Underwriter's Survey Guidelines



Engineers, Planners & Landscape Architects

Novatech Project #: 120144
 Project Name: 1200 Maritime Way - East Tower
 Date: 4/28/2023
 Input By: Curtis Ferguson, E.I.T.
 Reviewed By: Anthony Mestwarp, P.Eng

Legend
 Input by User
 No Information or Input Required

Building Description: 28 Storey Building with 7 Storey Podium
 Type I - Fire resistive construction (2 hrs)

Step			Choose			Value Used	Total Fire Flow (L/min)
Base Fire Flow							
1	Construction Material			Multiplier		0.6	
	Coefficient related to type of construction C	Type V - Wood frame		1.5			
		Type IV - Mass Timber		Varies			
		Type III - Ordinary construction		1			
		Type II - Non-combustible construction		0.8			
Type I - Fire resistive construction (2 hrs)		Yes	0.6				
2	Floor Area					3,735	8,000
	A	Podium Level Footprint (m ²)	2490				
		Total Floors/Storeys (Podium)	7				
		Tower Footprint (m ²)	652				
		Total Floors/Storeys (Tower)	21				
		Protected Openings (1 hr)	Yes				
		Area of structure considered (m ²)					
F	Base fire flow without reductions						
F = 220 C (A)^{0.5}							
Reductions or Surcharges							
3	Occupancy hazard reduction or surcharge			Reduction/Surcharge		-15%	6,800
	(1)	Non-combustible		-25%			
		Limited combustible	Yes	-15%			
		Combustible		0%			
		Free burning		15%			
Rapid burning			25%				
4	Sprinkler Reduction (100% sprinkler coverage of building used)			Reduction		-50%	-3,400
	(2)	Adequately Designed System (NFPA 13)	Yes	-30%	-30%		
		Standard Water Supply	Yes	-10%	-10%		
		Fully Supervised System	Yes	-10%	-10%		
Cumulative Total							
5	Exposure Surcharge (cumulative %, Maximum Exposure Adjustment Charge Used)			Surcharge		55%	3,740
	(3)	North Side	20.1 - 30 m		10%		
		East Side	3.1 - 10 m		20%		
		South Side	10.1 - 20 m		15%		
		West Side	20.1 - 30 m		10%		
Cumulative Total							
Results							
6	(1) + (2) + (3)	Total Required Fire Flow, rounded to nearest 1000L/min			L/min	7,000	
		(2,000 L/min < Fire Flow < 45,000 L/min)			or	L/s	117
					or	USGPM	1,849
7	Storage Volume	Required Duration of Fire Flow (hours)			Hours	2	
		Required Volume of Fire Flow (m ³)			m ³	840	

FUS - Fire Flow Calculations

As per 2020 Fire Underwriter's Survey Guidelines



Engineers, Planners & Landscape Architects

Novatech Project #: 120144
 Project Name: 1200 Maritime Way - West Tower
 Date: 4/28/2023
 Input By: Curtis Ferguson, E.I.T.
 Reviewed By: Anthony Mestwarp. P.Eng

Legend
 Input by User
 No Information or Input Required

Building Description: 30 Storey Building with 7 Storey Podium
 Type I - Fire resistive construction (2 hrs)

Step		Choose		Value Used	Total Fire Flow (L/min)	
Base Fire Flow						
1	Construction Material			Multiplier	0.6	
	Coefficient related to type of construction C	Type V - Wood frame		1.5		
		Type IV - Mass Timber		Varies		
		Type III - Ordinary construction		1		
		Type II - Non-combustible construction		0.8		
Type I - Fire resistive construction (2 hrs)		Yes	0.6			
2	Floor Area				7,000	
	A	Podium Level Footprint (m ²)	1969			
		Total Floors/Storeys (Podium)	7			
		Tower Footprint (m ²)	892			
		Total Floors/Storeys (Tower)	23			
		Protected Openings (1 hr)	Yes			
		Area of structure considered (m ²)				2,954
F	Base fire flow without reductions					
	$F = 220 C (A)^{0.5}$					
Reductions or Surcharges						
3	Occupancy hazard reduction or surcharge			Reduction/Surcharge	5,950	
	(1)	Non-combustible		-25%		
		Limited combustible	Yes	-15%		
		Combustible		0%		
		Free burning		15%		
Rapid burning			25%			
4	Sprinkler Reduction (100% sprinkler coverage of building used)			Reduction	-2,975	
	(2)	Adequately Designed System (NFPA 13)	Yes	-30%		
		Standard Water Supply	Yes	-10%		
		Fully Supervised System	Yes	-10%		
	Cumulative Total		-50%			
5	Exposure Surcharge (cumulative %, Maximum Exposure Adjustment Charge Used)			Surcharge	2,678	
	(3)	North Side	20.1 - 30 m	10%		
		East Side	10.1 - 20 m	15%		
		South Side	30.1 - 45 m	5%		
		West Side	10.1 - 20 m	15%		
	Cumulative Total		45%			
Results						
6	(1) + (2) + (3)	Total Required Fire Flow, rounded to nearest 1000L/min		L/min	6,000	
		(2,000 L/min < Fire Flow < 45,000 L/min)		or	100	
				or	1,585	
7	Storage Volume	Required Duration of Fire Flow (hours)		Hours	2	
		Required Volume of Fire Flow (m ³)		m ³	720	



EXISTING CONNECTION OF THE 200mm
WATERMAIN TO THE HYDRANT SERVICE

WEST TOWER:
PROPOSED 200mm WATER SERVICE LOCATION.
TWIN-SERVICES SEPARATED BY A PROPOSED
ISOLATION VALVE.
AVG DAY: 1.70
MAX DAY: 4.26
PEAK HOUR: 9.38
FIRE FLOW: 100

EAST TOWER:
PROPOSED 200mm WATER SERVICE LOCATION.
TWIN-SERVICES SEPARATED BY A PROPOSED
ISOLATION VALVE.
AVG DAY: 1.87
MAX DAY: 4.54
PEAK HOUR: 9.89
FIRE FLOW: 117

APPROX. SITE
BOUNDARY

40m

-8448908.500 5670923.885 Meters

From: Kuruvilla, Santhosh <Santhosh.Kuruvilla@ottawa.ca>
Sent: Wednesday, August 17, 2022 8:56 AM
To: Anthony Mestwarp <a.mestwarp@novatech-eng.com>
Cc: Greg MacDonald <g.Macdonald@novatech-eng.com>; Curtis Ferguson <c.ferguson@novatech-eng.com>
Subject: RE: 120144- Boundary Conditions Request - 1200 Maritime Way (D07-12-21-0017)

Hi Anthony,

Please find attached the updated boundary conditions for the subject application.

Thanks,
Santhosh

From: Anthony Mestwarp <a.mestwarp@novatech-eng.com>
Sent: July 22, 2022 11:31 AM
To: Kuruvilla, Santhosh <Santhosh.Kuruvilla@ottawa.ca>
Cc: Greg MacDonald <g.Macdonald@novatech-eng.com>; Curtis Ferguson <c.ferguson@novatech-eng.com>
Subject: RE: 120144- Boundary Conditions Request - 1200 Maritime Way (D07-12-21-0017)

The client has decided to revise the water servicing for the 1200 Maritime Way site to have separate servicing for the east and west towers per the attached.

Can you please provide updated boundary conditions per the following.

West Tower:

Avg Day – 1.70
Max Day – 4.26
Peak Hour – 9.38
Fire Flow 100

East Tower:

Avg Day – 1.87
Max Day – 4.54
Peak Hour – 9.89
Fire Flow - 117

Thanks,

Anthony Mestwarp, P.Eng., Project Engineer | Land Development Engineering

NOVATECH Engineers, Planners & Landscape Architects

240 Michael Cowpland Drive, Suite 200, Ottawa, ON, K2M 1P6 | Tel: 613.254.9643 Ext. 216 | Fax: 613.254.5867

The information contained in this email message is confidential and is for exclusive use of the addressee.

From: Kuruvilla, Santhosh <Santhosh.Kuruvilla@ottawa.ca>
Sent: Wednesday, June 29, 2022 8:02 AM
To: Anthony Mestwarp <a.mestwarp@novatech-eng.com>
Cc: Greg MacDonald <g.Macdonald@novatech-eng.com>; Curtis Ferguson <c.ferguson@novatech-eng.com>
Subject: RE: 120144- Boundary Conditions Request - 1200 Maritime Way (D07-12-21-0017)

Hello Anthony,

Please find attached the water boundary conditions for the subject application for your use.

Thanks,
Santhosh

From: Kuruvilla, Santhosh
Sent: June 07, 2022 11:25 AM
To: Anthony Mestwarp <a.mestwarp@novatech-eng.com>
Cc: Greg MacDonald <g.Macdonald@novatech-eng.com>; Curtis Ferguson <c.ferguson@novatech-eng.com>
Subject: RE: 120144- Boundary Conditions Request - 1200 Maritime Way

Thanks Anthony.

I will send you a meeting invite soon.

Santhosh

From: Anthony Mestwarp <a.mestwarp@novatech-eng.com>
Sent: June 07, 2022 10:00 AM
To: Kuruvilla, Santhosh <Santhosh.Kuruvilla@ottawa.ca>
Cc: Greg MacDonald <g.Macdonald@novatech-eng.com>; Curtis Ferguson <c.ferguson@novatech-eng.com>
Subject: RE: 120144- Boundary Conditions Request - 1200 Maritime Way

I am free after 2:00.

Regards,

Anthony Mestwarp, P.Eng., Project Engineer | Land Development Engineering

NOVATECH Engineers, Planners & Landscape Architects

240 Michael Cowpland Drive, Suite 200, Ottawa, ON, K2M 1P6 | Tel: 613.254.9643 Ext. 216 | Fax: 613.254.5867

The information contained in this email message is confidential and is for exclusive use of the addressee.

From: Kuruvilla, Santhosh <Santhosh.Kuruvilla@ottawa.ca>
Sent: Tuesday, June 7, 2022 8:14 AM
To: Anthony Mestwarp <a.mestwarp@novatech-eng.com>
Cc: Greg MacDonald <g.Macdonald@novatech-eng.com>; Curtis Ferguson <c.ferguson@novatech-eng.com>
Subject: RE: 120144- Boundary Conditions Request - 1200 Maritime Way

Hi Anthony,

Are you available this afternoon between 1:00-3:00 for about 10-15 mins? I would like to ask you a clarification question.

Please let me know and I will send you a Teams meeting invite.

Thanks,
Santhosh

From: Anthony Mestwarp <a.mestwarp@novatech-eng.com>
Sent: May 17, 2022 2:22 PM
To: Kuruvilla, Santhosh <Santhosh.Kuruvilla@ottawa.ca>
Cc: Greg MacDonald <g.Macdonald@novatech-eng.com>; Curtis Ferguson <c.ferguson@novatech-eng.com>
Subject: FW: 120144- Boundary Conditions Request - 1200 Maritime Way

As discussed please find the boundary condition request that was sent on April 28th for the 1200 Maritime Way project.

Please let me know if you require anything further.

Regards,

Anthony Mestwarp, P.Eng., Project Engineer | Land Development Engineering

NOVATECH Engineers, Planners & Landscape Architects

240 Michael Cowpland Drive, Suite 200, Ottawa, ON, K2M 1P6 | Tel: 613.254.9643 Ext. 216 | Fax: 613.254.5867

The information contained in this email message is confidential and is for exclusive use of the addressee.

From: Anthony Mestwarp
Sent: Thursday, April 28, 2022 3:44 PM
To: justin.armstrong@ottawa.ca
Cc: Santhosh.Kuruvilla@ottawa.ca; Greg MacDonald <g.Macdonald@novatech-eng.com>; Curtis Ferguson <c.ferguson@novatech-eng.com>
Subject: FW: 120144- Boundary Conditions Request - 1200 Maritime Way

Hi Justin,

I see that Santhosh is out of the office, I hope he is back soon.
Can you please begin the process for the boundary condition request.

Thanks,

Anthony Mestwarp, P.Eng., Project Engineer | Land Development Engineering

NOVATECH Engineers, Planners & Landscape Architects

240 Michael Cowpland Drive, Suite 200, Ottawa, ON, K2M 1P6 | Tel: 613.254.9643 Ext. 216 | Fax: 613.254.5867

The information contained in this email message is confidential and is for exclusive use of the addressee.

From: Anthony Mestwarp
Sent: Thursday, April 28, 2022 2:29 PM
To: Santhosh.Kuruvilla@ottawa.ca
Cc: Curtis Ferguson <c.ferguson@novatech-eng.com>; Greg MacDonald <g.Macdonald@novatech-eng.com>
Subject: RE: 120144- Boundary Conditions Request - 1200 Maritime Way

Hi Santhosh,

Please find attached the supporting documents for the updated boundary conditions request for 1200 Maritime way.

The proposed site will have a total of 633 units (387 1-bed, & 246 2-bed), and 399m2 of commercial area.

Total demands and fire flows are summarized below;

- Average Daily Demand: 3.57 L/s
- Max Daily Demand: 8.79 L/s
- Peak Hour Demand: 19.25 L/s
- Fire Flow (FUS): 117 L/s

In response to the below the proposed development will have 2 water services connecting to the existing 200mm local watermain separated by an isolation valve. The local watermain was installed as part of the neighboring 1250 Maritime way site and covers the entire frontage of 1200 Maritime way, and is capable of providing redundancy for the site.

Please let us know if you have any questions.

Regards,

Anthony Mestwarp, P.Eng., Project Engineer | Land Development Engineering

NOVATECH Engineers, Planners & Landscape Architects

240 Michael Cowpland Drive, Suite 200, Ottawa, ON, K2M 1P6 | Tel: 613.254.9643 Ext. 216 | Fax: 613.254.5867

The information contained in this email message is confidential and is for exclusive use of the addressee.

From: Greg MacDonald <g.Macdonald@novatech-eng.com>
Sent: Wednesday, February 16, 2022 7:51 AM
To: Anthony Mestwarp <a.mestwarp@novatech-eng.com>
Subject: FW: 120144- Boundary Conditions Request - 1200 Maritime Way

See below

Greg MacDonald, P. Eng.

Director, Land Development and Public Sector Infrastructure

NOVATECH Engineers, Planners & Landscape Architects

240 Michael Cowpland Drive, Suite 200, Ottawa, ON, K2M 1P6 | Tel: 613.254.9643 x279 | Cell: 613.890.9705 | Fax: 613.254.5867

The information contained in this email message is confidential and is for exclusive use of the addressee


From: Kuruvilla, Santhosh <Santhosh.Kuruvilla@ottawa.ca>
Sent: Wednesday, February 16, 2022 6:58 AM
To: Curtis Ferguson <c.ferguson@novatech-eng.com>
Cc: Greg MacDonald <g.Macdonald@novatech-eng.com>
Subject: RE: 120144- Boundary Conditions Request - 1200 Maritime Way

Hi Curtis,

I would like to provide you the following information I received from our Infrastructure Planning unit regarding water service connections for this development

"Hi Santosh

I will wait to receive the updated request. So far, their request only shows a map with service connection from the 200mm watermain on Maritime. They need to establish how they are getting the redundancy. Are they extending the Maritime way watermain further east upto Great lakes Ave and proposing 2 connections separated by a valve? Or is the second connection from the 406mm watermain that I highlighted below?



In the next submission Novatech should provide clarity how the redundancy is met. The request should include a siteplan, proposed watermain extensions (if any), and connection locations."

Santhosh

This e-mail originates from the City of Ottawa e-mail system. Any distribution, use or copying of this e-mail or the information it contains by other than the intended recipient(s) is unauthorized. Thank you.

Le présent courriel a été expédié par le système de courriels de la Ville d'Ottawa. Toute distribution, utilisation ou reproduction du courriel ou des renseignements qui s'y trouvent par une personne autre que son destinataire prévu est interdite. Je vous remercie de votre collaboration.'

Boundary Conditions 1200 Maritime Way

Provided Information

Connection 1 – West Tower	Demand	
	L/min	L/s
Average Daily Demand	102	1.70
Maximum Daily Demand	256	4.26
Peak Hour	563	9.38
Fire Flow Demand #1	6,000	100.00

Connection 2 – East Tower	Demand	
	L/min	L/s
Average Daily Demand	112	1.87
Maximum Daily Demand	272	4.54
Peak Hour	593	9.89
Fire Flow Demand #1	7,000	116.67

Location



Results

Connection 1 (West Tower) – Maritime Way.

Demand Scenario	Head (m)	Pressure ¹ (psi)
Maximum HGL	161.3	92.1
Peak Hour	156.1	84.8
Max Day plus Fire 1	148.6	74.1

Ground Elevation = 96.4 m

Connection 2 (East Tower) – Maritime Way.

Demand Scenario	Head (m)	Pressure ¹ (psi)
Maximum HGL	161.3	93.3
Peak Hour	156.1	86.0
Max Day plus Fire 1	142.8	67.1

Ground Elevation = 95.6 m

Notes

1. A second connection to the watermain, separated by an isolation valve, is required for each tower to decrease vulnerability of the water system in case of breaks.
2. As per the Ontario Building Code in areas that may be occupied, the static pressure at any fixture shall not exceed 552 kPa (80 psi.) Pressure control measures to be considered are as follows, in order of preference:
 - a. If possible, systems to be designed to residual pressures of 345 to 552 kPa (50 to 80 psi) in all occupied areas outside of the public right-of-way without special pressure control equipment.
 - b. Pressure reducing valves to be installed immediately downstream of the isolation valve in the home/ building, located downstream of the meter so it is owner maintained.

Disclaimer

The boundary condition information is based on current operation of the city water distribution system. The computer model simulation is based on the best information available at the time. The operation of the water distribution system can change on a regular basis, resulting in a variation in boundary conditions. The physical properties of watermains deteriorate over time, as such must be assumed in the absence of actual field test data. The variation in physical watermain properties can therefore alter the results of the computer model simulation. Fire Flow analysis is a reflection of available flow in the watermain; there may be additional restrictions that occur between the watermain and the hydrant that the model cannot take into account.

CALCULATED WATER DEMANDS:

West Tower

Average Day (Maximum HGL)= 1.70 L/s
 Maximum Day = 4.26 L/s
 Peak Hour (Minimum HGL) = 9.38 L/s
 Max Day + Fire = 104.26 L/s

East Tower

Average Day (Maximum HGL)= 1.87 L/s
 Maximum Day = 4.54 L/s
 Peak Hour (Minimum HGL) = 9.89 L/s
 Max Day + Fire = 121.54 L/s

City of Ottawa Boundary Conditions:

Boundary conditions based on connection to 203mm dia. Watermain in Maritime Way

Connection # 1 West Tower

Average Day (Maximum HGL)= 161.3 m
 Peak Hour (Minimum HGL) = 156.1 m
 Max Day + Fire = 148.6 m

Connection # 2 East Tower

Average Day (Maximum HGL)= 161.3 m
 Peak Hour (Minimum HGL) = 156.1 m
 Max Day + Fire = 142.8 m

Watermain Analysis (West Tower)

Water Service Elevation = 94.58 m

High Pressure Test = Max. HGL - Water Service Elevation x 1.42197 PSI/m < 80 PSI

High Pressure = 94.9 PSI

Low Pressure Test = Min. HGL - Water Service Elevation x 1.42197 PSI/m > 40 PSI

Low Pressure = 87.5 PSI

Max Day + Fire Test = Max Day + Fire Flow - Water Service Elevation x 1.42197 PSI/m > 20 PSI

Max Day + Fire (Connection #1) = 76.8 PSI

Watermain Analysis (East Tower)

Water Service Elevation = 94.25 m

High Pressure Test = Max. HGL - Water Service Elevation x 1.42197 PSI/m < 80 PSI

High Pressure = 95.3 PSI

Low Pressure Test = Min. HGL - Water Service Elevation x 1.42197 PSI/m > 40 PSI

Low Pressure = 87.9 PSI

Max Day + Fire Test = Max Day + Fire Flow - Water Service Elevation x 1.42197 PSI/m > 20 PSI

Max Day + Fire (Connection #1) = 69.0 PSI

APPENDIX E

Servicing Study Guidelines Checklist

4.1 General Content	Addressed (Y/N/NA)	Comments
Executive Summary (for larger reports only).	NA	
Date and revision number of the report.	Y	
Location map and plan showing municipal address, boundary, and layout of proposed development.	Y	Refer to figure 1
Plan showing the site and location of all existing services.	Y	Refer to Grading and Servicing Plans
Development statistics, land use, density, adherence to zoning and official plan, and reference to applicable subwatershed and watershed plans that provide context to which individual developments must adhere.	Y	Refer to Site Plan
Summary of Pre-consultation Meetings with City and other approval agencies.	Y	Refer to Appendix F
Reference and confirm conformance to higher level studies and reports (Master Servicing Studies, Environmental Assessments, Community Design Plans), or in the case where it is not in conformance, the proponent must provide justification and develop a defensible design criteria.	Y	
Statement of objectives and servicing criteria.	Y	Report Sections: 5.0 Sanitary sewer, 6.0 Storm Sewer and Stormwater Management, 7.0 Water Servicing
Identification of existing and proposed infrastructure available in the immediate area.	Y	
Identification of Environmentally Significant Areas, watercourses and Municipal Drains potentially impacted by the proposed development (Reference can be made to the Natural Heritage Studies, if available).	NA	
Concept level master grading plan to confirm existing and proposed grades in the development. This is required to confirm the feasibility of proposed stormwater management and drainage, soil removal and fill constraints, and potential impacts to neighboring properties. This is also required to confirm that the proposed grading will not impede existing major system flow paths.	Y	Refer to Grading Plan and Stormwater Management Plan

4.1 General Content	Addressed (Y/N/NA)	Comments
Identification of potential impacts of proposed piped services on private services (such as wells and septic fields on adjacent lands) and mitigation required to address potential impacts.	NA	
Proposed phasing of the development, if applicable.	Y	
Reference to geotechnical studies and recommendations concerning servicing.	Y	
All preliminary and formal site plan submissions should have the following information:		
Metric scale	Y	All Drawings
North arrow (including construction North)	Y	All Drawings
Key plan	Y	All Drawings
Name and contact information of applicant and property owner	Y	Drawings/Report
Property limits including bearings and dimensions	Y	Report
Existing and proposed structures and parking areas	Y	All Drawings
Easements, road widening and rights-of-way	Y	All Drawings
Adjacent street names	Y	All Drawings

4.2 Water	Addressed (Y/N/NA)	Comments
Confirm consistency with Master Servicing Study, if available.	NA	
Availability of public infrastructure to service proposed development.	Y	Report Sections: 5.0 Sanitary sewer, 6.0 Storm Sewer and Stormwater Management, 7.0 Water Servicing
Identification of system constraints.	NA	
Identify boundary conditions.	Y	
Confirmation of adequate domestic supply and pressure.	Y	
Confirmation of adequate fire flow protection and confirmation that fire flow is calculated as per the Fire Underwriter's Survey. Output should show available fire flow at locations throughout the development.	Y	
Provide a check of high pressures. If pressure is found to be high, an assessment is required to confirm the application of pressure reducing valves.	Y	
Definition of phasing constraints. Hydraulic modeling is required to confirm servicing for all defined phases of the project including the ultimate design.	NA	
Address reliability requirements such as appropriate location of shut-off valves.	Y	Refer to Grading and Servicing Plans
Check on the necessity of a pressure zone boundary modification.	NA	
Reference to water supply analysis to show that major infrastructure is capable of delivering sufficient water for the proposed land use. This includes data that shows that the expected demands under average day, peak hour and fire flow conditions provide water within the required pressure range.	Y	
Description of the proposed water distribution network, including locations of proposed connections to the existing system, provisions for necessary looping, and appurtenances (valves, pressure reducing valves, valve chambers, and fire hydrants) including special metering provisions.	Y	Report Section 7.0 Water Servicing
Description of off-site required feeder mains, booster pumping stations, and other water infrastructure that will be ultimately required to service proposed development, including financing, interim facilities, and timing of implementation.	NA	
Confirmation that water demands are calculated based on the City of Ottawa Design Guidelines.	Y	Report Section 7.0 Water Servicing
Provision of a model schematic showing the boundary conditions locations, streets, parcels, and building locations for reference.	NA	

4.3 Wastewater	Addressed (Y/N/NA)	Comments
Summary of proposed design criteria (Note: Wet-weather flow criteria should not deviate from the City of Ottawa Sewer Design Guidelines. Monitored flow data from relatively new infrastructure cannot be used to justify capacity requirements for proposed infrastructure).	Y	Refer to report section 5.0 Sanitary sewer
Confirm consistency with Master Servicing Study and/or justifications for deviations.	NA	
Consideration of local conditions that may contribute to extraneous flows that are higher than the recommended flows in the guidelines. This includes groundwater and soil conditions, and age and condition of sewers.	NA	
Description of existing sanitary sewer available for discharge of wastewater from proposed development.	Y	Refer to report section 5.0 Sanitary sewer
Verify available capacity in downstream sanitary sewer and/or identification of upgrades necessary to service the proposed development. (Reference can be made to previously completed Master Servicing Study if applicable)	Y	Refer to Appendix B
Calculations related to dry-weather and wet-weather flow rates from the development in standard MOE sanitary sewer design table (Appendix 'C') format.	NA	
Description of proposed sewer network including sewers, pumping stations, and forcemains.	Y	Refer to report section 5.0 Sanitary sewer
Discussion of previously identified environmental constraints and impact on servicing (environmental constraints are related to limitations imposed on the development in order to preserve the physical condition of watercourses, vegetation, soil cover, as well as protecting against water quantity and quality).	NA	
Pumping stations: impacts of proposed development on existing pumping stations or requirements for new pumping station to service development.	NA	
Forcemain capacity in terms of operational redundancy, surge pressure and maximum flow velocity.	NA	
Identification and implementation of the emergency overflow from sanitary pumping stations in relation to the hydraulic grade line to protect against basement flooding.	NA	
Special considerations such as contamination, corrosive environment etc.	NA	

4.4 Stormwater	Addressed (Y/N/NA)	Comments
Description of drainage outlets and downstream constraints including legality of outlet (i.e. municipal drain, right-of-way, watercourse, or private property).	Y	Refer to report section 6.0 Storm Sewer and Stormwater Management
Analysis of the available capacity in existing public infrastructure.	NA	Stormwater release rates less than or equal to city allowable release rate criteria
A drawing showing the subject lands, its surroundings, the receiving watercourse, existing drainage patterns and proposed drainage patterns.	Y	Refer to Stormwater Management Plan
Water quantity control objective (e.g. controlling post-development peak flows to pre-development level for storm events ranging from the 2 or 5 year event (dependent on the receiving sewer design) to 100 year return period); if other objectives are being applied, a rationale must be included with reference to hydrologic analyses of the potentially affected subwatersheds, taking into account long-term cumulative effects.	Y	Refer to report section 6.0 Storm Sewer and Stormwater Management
Water Quality control objective (basic, normal or enhanced level of protection based on the sensitivities of the receiving watercourse) and storage requirements.	Y	Refer to report section 6.0 Storm Sewer and Stormwater Management
Description of stormwater management concept with facility locations and descriptions with references and supporting information.	Y	Refer to report section 6.0 Storm Sewer and Stormwater Management
Set-back from private sewage disposal systems.	N/A	
Watercourse and hazard lands setbacks.	N/A	
Record of pre-consultation with the Ontario Ministry of Environment and the Conservation Authority that has jurisdiction on the affected watershed.	N/A	
Confirm consistency with sub-watershed and Master Servicing Study, if applicable study exists.	N/A	
Storage requirements (complete with calcs) and conveyance capacity for 5 yr and 100 yr events.	Y	Refer to Appendix C
Identification of watercourse within the proposed development and how watercourses will be protected, or, if necessary, altered by the proposed development with applicable approvals.	NA	
Calculate pre and post development peak flow rates including a description of existing site conditions and proposed impervious areas and drainage catchments in comparison to existing conditions.	Y	Refer to Appendix C
Any proposed diversion of drainage catchment areas from one outlet to another.	NA	
Proposed minor and major systems including locations and sizes of stormwater trunk sewers, and SWM facilities.	N/A	

Development Servicing Study Checklist

Project Name: 1200 Maritime Way

Project Number: 120144

Date: January 2021

Revised : May 2022

Revised: October 2022

If quantity control is not proposed, demonstration that downstream system has adequate capacity for the post-development flows up to and including the 100-year return period storm event.	N/A	
--	-----	--

4.4 Stormwater	Addressed (Y/N/NA)	Comments
Identification of municipal drains and related approval requirements.	N/A	
Description of how the conveyance and storage capacity will be achieved for the development.	Y	Refer to report section 6.0 Storm Sewer and Stormwater Management
100 year flood levels and major flow routing to protect proposed development from flooding for establishing minimum building elevations (MBE) and overall grading.	N/A	
Inclusion of hydraulic analysis including HGL elevations.	N/A	
Description of approach to erosion and sediment control during construction for the protection of receiving watercourse or drainage corridors.	Y	Report Section 8.0 Erosion and Sediment Control
Identification of floodplains – proponent to obtain relevant floodplain information from the appropriate Conservation Authority. The proponent may be required to delineate floodplain elevations to the satisfaction of the Conservation Authority if such information is not available or if information does not match current conditions.	NA	
Identification of fill constrains related to floodplain and geotechnical investigation.	Y	Report section 4.0 Site Constraints

4.5 Approval and Permit Requirements	Addressed (Y/N/NA)	Comments
Conservation Authority as the designated approval agency for modification of floodplain, potential impact on fish habitat, proposed works in or adjacent to a watercourse, cut/fill permits and Approval under Lakes and Rivers Improvement Act. The Conservation Authority is not the approval authority for the Lakes and Rivers Improvement Act. Where there are Conservation Authority regulations in place, approval under the Lakes and Rivers Improvement Act is not required, except in cases of dams as defined in the Act.	NA	
Application for Certificate of Approval (CofA) under the Ontario Water Resources Act.	NA	
Changes to Municipal Drains.	NA	
Other permits (National Capital Commission, Parks Canada, Public Works and Government Services Canada, Ministry of Transportation etc.)	NA	

4.6 Conclusion	Addressed (Y/N/NA)	Comments
Clearly stated conclusions and recommendations.	Y	Report Section 9.0 Conclusions
Comments received from review agencies including the City of Ottawa and information on how the comments were addressed. Final sign-off from the responsible reviewing agency.	NA	
All draft and final reports shall be signed and stamped by a professional Engineer registered in Ontario.	Y	

APPENDIX F

**PRE-CONSULTATION
MEETING MINUTES**

Please refer to the below regarding the Pre-Application meeting held on August 6, 2020 for the property at 1200 Maritime Way for a Site Plan Control Application and Zoning By-law Amendment for a residential development. I have also attached the required Plans & Study List for application submission. Despite the amount of hard copies identified in the list, they may not be required- please confirm with the Planner prior to submission.

Below are staff's preliminary comments based on the information available at the time of the pre-consultation meeting:

Planning / Urban Design

General:

- You are encouraged to contact the Ward Councillor, Councillor [Jenna Sudds](#), regarding the proposal.
- Urban Design Review Panel review is required for the proposed increase in height and site plan control application.
 - A pre-consult with the UDRP is also recommended.
- Cash-in-Lieu of Parkland will be required if proof of payment cannot be provided.

Zoning By-law Amendment:

- Staff do not have a concern with the proposed increase in height provided it meets Official Plan and Secondary Planning requirements and policies.
- Please ensure that adequate tower separation and associated setbacks on-site and from abutting property lines is achieved in accordance with the high-rise design guidelines.
- A zoning schedule and or FSI should be considered as part of the Zoning By-law amendment to increase the height on the subject property.

Site Plan Control:

- Current proposal does not adequately address Maritime Way.
- Please ensure that adequate setbacks (11.5 metres for a tower) are provided from the eastern property line, and the length of a podium is not designed to directly face this property line.
- Please utilize a 6-storey podium in lieu of a 9 storey podium.
- Please consider that if the towers are the same height, they have the same floor plate (pairing) vs. the current proposal.
- If different floor plates are desired for the two towers, they should be different heights.
- Three towers are possible on-site, one at the desired 30 storeys and two at a lower height (ex. 15).
- Need to study massing as it relates to other properties, buildings, shadowing, wind etc.

- Proposal needs to work with grades along Kanata Avenue.
- Connections to the MUP to the south need to be considered.
- Ensure that adequate outdoor amenity space is provided.
- Group “back” of house and functional requirements.
- Reduce surface parking to the greatest extent possible.
- Provide grade related units.
- Please see attached illustration.
- A Design Brief is required.
 - A terms of reference is provided. All applicable elements of the Design Brief have been highlighted.
- Please review the Building Code to make sure the proposed development will meet the accessibility requirements.

Engineering

General:

- It is the sole responsibility of the consultant to investigate the location of existing underground utilities in the proposed servicing area and submit a request for locates. The location of existing utilities and services shall be documented on an **Existing Conditions Plan**.
- All underground and above ground building footprints and permanent walls need to be shown on the plans to confirm that any permanent structure does not encroach within the right-of-way.
- Any easements on the subject site shall be identified and respected by any development proposal and shall adhere to the conditions identified in the easement agreement. A **legal survey plan** shall be provided and all easements shall be shown on the engineering plans.
- Please provide an **Existing Conditions/Removals Plan** as part of the engineering drawing set. Any existing services are to be removed or abandoned in accordance with City standards.
- Please note that the proposed servicing design and site works shall be in accordance with the following documents:
 - Ottawa Sewer Design Guidelines (October 2012)
 - Technical Bulletin PIEDTB-2016-01
 - Technical Bulletins ISTB-2018-01, ISTB-2018-02 and ISTB-2018-03.
 - Ottawa Design Guidelines - Water Distribution (2010)
 - Geotechnical Investigation and Reporting Guidelines for Development Applications in the City of Ottawa (2007)
 - City of Ottawa Slope Stability Guidelines for Development Applications (revised 2012)
 - City of Ottawa Environmental Noise Control Guidelines (January 2016)
 - City of Ottawa Accessibility Design Standards (2012) (City recommends development be in accordance with these standards on private property)
 - Ottawa Standard Tender Documents (latest version)
 - Ontario Provincial Standards for Roads & Public Works (2013)

- Record drawings and utility plans are also available for purchase from the City (Contact the City's Information Centre by email at InformationCentre@ottawa.ca or by phone at (613) 580-424 x.44455).

Stormwater Management Criteria and Information:

- It appears the subject site is located within **the KTC SWM Pond (Phase 2)** catchment (see attached). The consultant should review the attached report and confirm SWM criteria, flow allowance to the existing storm system, design assumptions, etc. Consult Operations staff to determine how the existing facility is currently performing (i.e. ability to achieve targets, condition of infrastructure within the SWM block, etc).
- **Water Quality Control:** Please consult with the local conservation authority regarding water quality criteria prior to submission of a Site Plan Control Proposal application to establish any water quality control restrictions, criteria and measures for the site. Correspondence and clearance shall be provided in the Appendix of the report.
- Please note that foundation drain is to be independently connected to sewermain unless being pumped with appropriate back up power, sufficient sized pump and back flow prevention.
- Please note that as per *Technical Bulletin PIEDTB-2016-01 section 8.3.11.1 (p.12 of 14)* **there shall be no surface ponding on private parking areas during the 2-year storm rainfall event.** Depending on the SWM strategy proposed underground or additional underground storage may be required to satisfy this requirement.
- **Underground Storage:** Please note that the Modified Rational Method for storage computation in the Sewer Design Guidelines was originally intended to be used for above ground storage (i.e. parking lot) where the change in head over the orifice varied from 1.5 m to 1.2 m (assuming a 1.2 m deep CB and a max ponding depth of 0.3 m). This change in head was small and hence the release rate fluctuated little, therefore there was no need to use an average release rate.
- When underground storage is used, the release rate fluctuates from a maximum peak flow based on maximum head down to a release rate of zero. This difference is large and has a significant impact on storage requirements. **We therefore require that an average release rate equal to 50% of the peak allowable rate shall be applied to estimate the required volume. Alternatively, the consultant may choose to use a submersible pump in the design to ensure a constant release rate.**
- In the event that there is a disagreement from the designer regarding the required storage, The City will require that the designer demonstrate their rationale utilizing dynamic modelling, that will then be reviewed by City modellers in the Water Resources Group.

- Note that the above will be added to upcoming revised Sewer Design Guidelines to account for underground storage, which is now widely used.
- Provide sufficient details and information on any proposed underground storage system. A cross-section of any underground storage system is to be provided with sufficient details and information. In case of a pump failure or blockage an overflow should be provided. Backup power supply is required if using a pump.
- Please note that the minimum orifice dia. for a plug style ICD is 83mm and the minimum flow rate from a vortex ICD is 6 L/s in order to reduce the likelihood of plugging.
- Post-development site grading shall match existing property line grades in order to minimize disruption to the adjacent residential properties. A **topographical plan of survey** shall be provided as part of the submission and a note provided on the plans.
- Please provide a **Pre-Development Drainage Area Plan** to define the pre-development drainage areas/patterns. **Existing drainage patterns shall be maintained and discussed as part of the proposed SWM solution.**
- If rooftop control and storage is proposed as part of the SWM solutions sufficient details (Cl. 8.3.8.4) shall be discussed and documented in the report and on the plans. Roof drains are to be connected downstream of any incorporated ICDs within the SWM system and not to the foundation drain system.

Storm Sewer:

- Storm sewer monitoring maintenance holes are required to be installed at the property line (on the private side of the property) as per City of Ottawa Sewer-Use By-Law 2003-514 (14) *Monitoring Devices*.
- As-built drawings of the existing services within the vicinity of the site shall be obtained and reviewed in order to determine proper servicing and SWM plan for the subject site(s).
- Storm service connections are to have backwater valves.

Sanitary Sewer:

- **An analysis and demonstration that there is sufficient/adequate residual capacity to accommodate any increase in wastewater flows in the receiving and downstream wastewater system is required to be provided. The City can provide flows for existing areas and direction on how to estimate future flows for vacant areas within the sewer shed.**
- Please apply the wastewater design flow parameters *in Technical Bulletin PIEDTB-2018-01*.

- Sanitary sewer monitoring maintenance holes are required to be installed at the property line (on the private side of the property) as per City of Ottawa Sewer-Use By-Law 2003-514 (14) *Monitoring Devices*.
- Sanitary service connections are to have backwater valves.

Water:

- **Water Supply Redundancy:** Residential buildings with a basic day demand greater than 50m³/day (0.57 L/s) are required to be connected to a minimum of two water services separated by an isolation valve to avoid a vulnerable service area as per the *Ottawa Design Guidelines - Water Distribution, WDG001, July 2010 Clause 4.3.1 Configuration*. The basic day demand for each site anticipated to exceed 50m³/day therefore 2 water services will be required. There shall be primary water service and a secondary connection.
- Please review Technical Bulletin ISTB-2018-0, maximum fire flow hydrant capacity is provided in Section 3 Table 1 of Appendix I. A **hydrant coverage figure** shall be provided and **demonstrate there is adequate fire protection**.
- Boundary conditions are required to confirm that the require fire flows can be achieved as well as availability of the domestic water pressure on the City street in front of the development. Use Table 3-3 of the MOE Design Guidelines for Drinking-Water System to determine Maximum Day and Maximum Hour peaking factors for 0 to 500 persons and use Table 4.2 of the Ottawa Design Guidelines, Water Distribution for 501 to 3,000 persons. Please provide the following information to the City of Ottawa via email to request water distribution network boundary conditions for the subject site. Please note that once this information has been provided to the City of Ottawa it takes approximately 5-10 business days to receive boundary conditions.
 - Type of Development and Units
 - Site Address
 - A plan showing the proposed water service connection locations.
 - **Average Daily Demand** (L/s)
 - **Maximum Daily Demand** (L/s)
 - **Peak Hour Demand** (L/s)
 - **Fire Flow** (L/min)
 - [*Fire flow demand requirements shall be based on Fire Underwriters Survey (FUS) Water Supply for Public Fire Protection 1999*]
 - *Exposure separation distances shall be defined on a figure to support the FUS calculation and required fore flow (RFF).*
 - Hydrant capacity shall be assessed to demonstrate the RFF can be achieved. Please identify which hydrants are being considered to meet the RFF on a fire hydrant coverage plan as part of the boundary conditions request.
- The subject site is located within the 1E Pressure Zone.

Snow Storage:

- Any portion of the subject property which is intended to be used for permanent or temporary snow storage shall be as shown on the approved site plan and grading plan. Snow storage shall not interfere with approved grading and drainage patterns or servicing. Snow storage areas shall be setback from the property lines, foundations, fencing or landscaping a minimum of 1.5m. Snow storage areas shall not occupy driveways, aisles, required parking spaces or any portion of a road allowance. If snow is to be removed from the site please indicate this on the plan(s).

Permits and Approvals:

- The consultant shall determine if this project will be subject to an Environmental Compliance Approval (ECA) for Private Sewage Works. It shall be determined if the exemptions set out under Ontario Regulation 525/98: *Approval Exemptions* are satisfied. All regulatory approvals shall be documented and discussed in the report.

Geotechnical Investigation:

- A Geotechnical Study/Investigation shall be prepared in support of this development proposal.
- Reducing the groundwater level in this area can lead to potential damages to surrounding structures due to excessive differential settlements of the ground. The impact of groundwater lowering on adjacent properties needs to be discussed and investigated to ensure there will be no short term and long term damages associated with lowering the groundwater in this area.
- Geotechnical Study shall be consistent with the **Geotechnical Investigation and Reporting Guidelines for Development Applications**.
- <https://documents.ottawa.ca/sites/default/files/documents/cap137602.pdf>

Exterior Site Lighting:

- Any proposed light fixtures (both pole-mounted and wall mounted) must be part of the approved Site Plan. All external light fixtures must meet the criteria for Full Cut-off Classification as recognized by the Illuminating Engineering Society of North America (IESNA or IES), and must result in minimal light

spillage onto adjacent properties (as a guideline, 0.5 fc is normally the maximum allowable spillage). In order to satisfy these criteria, the please provide the City with a **Site Lighting Plan, Photometric Plan and Certification (Statement) Letter** from an acceptable professional engineer stating that the design is compliant.

Please contact Infrastructure Project Manager [Ahmed Elsayed](#) for follow-up questions.

Transportation

- Follow Traffic Impact Assessment Guidelines
 - A TIA is required. Please proceed to submit Scoping report.
 - Start this process asap. The application will not be deemed complete until the submission of the draft step 1-4, including the functional draft RMA package (if applicable) and/or monitoring report (if applicable).
 - Request base mapping asap if RMA is required. Contact Engineering Services (<https://ottawa.ca/en/city-hall/planning-and-development/engineering-services>)
- TMP shows:
 - Future BRT along Hwy 417 (affordable network) and future LRT along Hwy 417 (ultimate network); and
 - Plans to widen Kanata Avenue from two to four lanes, between Highway 417 and Campeau Drive (Phase 2: 2020-2025).
- Drive aisle width should be 6.7m wide.
- Reduce number of conflict points as much as possible within internal roadways.
- Noise Impact Studies required for the following:
 - Road
 - Stationary (if there will be any exposed mechanical equipment due to the proximity to neighbouring noise sensitive land uses)
- On site plan:
 - Show all details of the roads abutting the site up to and including the opposite curb; include such items as pavement markings, accesses and/or sidewalks.
 - Show clear throat length dimension on site plan.
 - Turning movement diagrams required for all accesses showing the largest vehicle to access/egress the site.
 - Turning movement diagrams required for internal movements (loading areas, garbage).
 - Show all curb radii measurements; ensure that all curb radii are reduced as much as possible
 - Show lane/aisle widths.
 - Sidewalk is to be continuous across access as per City Specification 7.1.
 - Grey out any area that will not be impacted by this application.
- AODA legislation is in effect for all organizations, please ensure that the design conforms to these standards.

Please contact Transportation Project Manager, [Josiane Gervais](#) for follow-up questions.

Other

Please refer to the links to “[Guide to preparing studies and plans](#)” and [fees](#) for general information. Additional information is available related to [building permits](#), [development charges](#), and the [Accessibility Design Standards](#). Be aware that other fees and permits may be required, outside of the development review process. You may obtain background drawings by contacting informationcentre@ottawa.ca.

These pre-consultation comments are valid for one year. If you submit a development application(s) after this time, you may be required to meet for another pre-consultation meeting and/or the submission requirements may change. You are as well encouraged to contact us for a follow-up meeting if the plan/concept will be further refined.

Please do not hesitate to contact me if you have any questions.

Regards,
Laurel

Laurel McCreight MCIP, RPP

Planner
Development Review West
Urbaniste
Examen des demandes d'aménagement ouest

City of Ottawa | Ville d'Ottawa
613.580.2424 ext./poste 16587
ottawa.ca/planning / ottawa.ca/urbanisme

DRAWINGS

GENERAL NOTES:

- COORDINATE AND SCHEDULE ALL WORK WITH OTHER TRADES AND CONTRACTORS.
- DETERMINE THE EXACT LOCATION, SIZE, MATERIAL AND ELEVATION OF ALL EXISTING UTILITIES PRIOR TO COMMENCING CONSTRUCTION. PROTECT AND ASSUME RESPONSIBILITY FOR ALL EXISTING UTILITIES WHETHER OR NOT SHOWN ON THIS DRAWING.
- OBTAIN ALL NECESSARY PERMITS AND APPROVALS FROM THE CITY OF OTTAWA BEFORE COMMENCING CONSTRUCTION.
- BEFORE COMMENCING CONSTRUCTION OBTAIN AND PROVIDE PROOF OF COMPREHENSIVE, ALL RISK AND OPERATIONAL LIABILITY INSURANCE FOR \$5,000,000.00. INSURANCE POLICY TO NAME OWNERS, ENGINEERS AND ARCHITECTS AS CO-INSURED.
- RESTORE ALL DISTURBED AREAS ON-SITE AND OFF-SITE, INCLUDING TRENCHES AND SURFACES ON PUBLIC ROAD ALLOWANCES TO EXISTING CONDITIONS OR BETTER TO THE SATISFACTION OF THE CITY OF OTTAWA AND ENGINEER.
- REMOVE FROM SITE ALL EXCESS EXCAVATED MATERIAL, ORGANIC MATERIAL AND DEBRIS UNLESS OTHERWISE INSTRUCTED BY ENGINEER. EXCAVATE AND REMOVE FROM SITE ANY CONTAMINATED MATERIAL. ALL CONTAMINATED MATERIAL SHALL BE DISPOSED OF AT A LICENSED LANDFILL FACILITY.
- ALL ELEVATIONS ARE GEODETIC.
- REFER TO GEOTECHNICAL REPORT (No. PGS281-1, DATED JULY 16TH, 2020), PREPARED BY PATERSON, FOR SUBSURFACE CONDITIONS, CONSTRUCTION RECOMMENDATIONS, AND GEOTECHNICAL INSPECTION REQUIREMENTS. THE GEOTECHNICAL CONSULTANT IS TO REVIEW ON-SITE CONDITIONS AFTER EXCAVATION PRIOR TO PLACEMENT OF THE GRANULAR MATERIAL.
- REFER TO ARCHITECTS AND LANDSCAPE ARCHITECTS DRAWINGS FOR BUILDING AND HARDSURFACE AREAS AND DIMENSIONS.
- REFER TO STORMWATER MANAGEMENT REPORT PREPARED BY NOVATECH ENGINEERING CONSULTANTS LTD (20230428).
- SAW CUT AND KEY GRIND ASPHALT AT ALL ROAD CUTS AND ASPHALT TIE IN POINTS AS PER CITY OF OTTAWA STANDARDS (R10).
- PROVIDE LINE/PARKING PAINTING.
- CONTRACTOR TO PROVIDE THE CONSULTANT WITH A GENERAL PLAN OF SERVICES INDICATING ALL SERVING AS-BUILT INFORMATION SHOWN ON THIS PLAN. AS-BUILT INFORMATION MUST INCLUDE: PIPE MATERIAL, SIZES, LENGTHS, SLOPES, INVERT AND TIE ELEVATIONS, STRUCTURE LOCATIONS, VALVE AND HYDRANT LOCATIONS, TIE-IN ELEVATIONS AND ANY ALIGNMENT CHANGES, ETC.

SEWER NOTES:

- | ITEM | SPEC. NO. | REFERENCE |
|--|-------------|-----------------------|
| CATCHBASIN (600x600mm) | 709.010 | OPSD |
| STORM / SANITARY MANHOLE (12000) | 701.010 | OPSD |
| CB, FRAME & COVER | 400.020 | OPSD |
| STORM / SANITARY MH FRAME & COVER | 401.010 | OPSD |
| SEWER TRENCH - BEDDING (GRANULAR A) | S6, S7, W17 | CITY OF OTTAWA / OPSD |
| COVER (GRANULAR A OR GRANULAR B TYPE I, WITH MAXIMUM PARTICLE SIZE $= 25\text{mm}$) | | |
| STORM SEWER | PVC DR 35 | |
| SANITARY SEWER | PVC DR 35 | |
| CATCHBASIN LEAD | PVC DR 35 | |
| SEWER SERVICE CONNECTION - RIGID PIPE | S11 | CITY OF OTTAWA |
| SEWER SERVICE ABANDONMENT | S11.4 | CITY OF OTTAWA |
- INSULATE ALL PIPES (SANSTM) THAT HAVE LESS THAN 1.5m COVER WITH 50mmx1200mm H-40 INSULATION. PROVIDE 150mm CLEARANCE BETWEEN PIPE AND INSULATION.
 - SERVICES ARE TO BE CONSTRUCTED TO 1.0m FROM FACE OF BUILDING AT A MINIMUM SLOPE OF 1.0%.
 - PIPE BEDDING, COVER AND BACKFILL ARE TO BE COMPACTED TO AT LEAST 98% OF THE STANDARD PROCTOR MAXIMUM DRY DENSITY. THE USE OF CLEAR CRUSHED STONE AS A BEDDING LAYER SHALL NOT BE PERMITTED.
 - FLEXIBLE CONNECTIONS ARE REQUIRED FOR CONNECTING PIPES TO MANHOLES (FOR EXAMPLE KOR-N-SEAL, PSX POSITIVE SEAL AND DURASEAL). THE CONCRETE CRADLE FOR THE PIPE CAN BE ELIMINATED.
 - THE OWNER SHALL REQUIRE THAT THE SITE SERVICING CONTRACTOR PERFORM FIELD TESTS FOR QUALITY CONTROL OF ALL SANITARY SEWERS. LEAKAGE TESTING SHALL BE COMPLETED IN ACCORDANCE WITH OPSS 410.07.16, 410.07.16.04 AND 407.07.24. DYE TESTING IS TO BE COMPLETED ON ALL SANITARY SERVICES TO CONFIRM PROPER CONNECTION TO THE SANITARY SEWER MAIN. THE FIELD TESTS SHALL BE PERFORMED IN THE PRESENCE OF A CERTIFIED PROFESSIONAL ENGINEER WHO SHALL SUBMIT A CERTIFIED COPY OF THE TEST RESULTS.
 - STORM MANHOLES AND CBMHs ARE TO HAVE 300mm SUMPS UNLESS OTHERWISE INDICATED.
 - CONTRACTOR TO TELETYPE (CCTV) ALL PROPOSED SEWERS, 200mmØ OR GREATER PRIOR TO BASE COURSE ASPHALT. UPON COMPLETION OF CONTRACT, THE CONTRACTOR IS RESPONSIBLE TO FLUSH AND CLEAN ALL SEWERS & APPURTENANCES.
 - FULL PORT BACKWATER VALVES ARE REQUIRED ON THE SANITARY SERVICES. INSTALLED AS PER THE MANUFACTURERS RECOMMENDATIONS AND A BACKWATER VALVE IS REQUIRED ON THE STORM SERVICES / FOUNDATION DRAINS FOR EACH BUILDING. INSTALLED AS PER STD. DWG514
 - REINSTATE ALL EXISTING PAVEMENT, CURB AND BOULEVARDS AS PER CITY OF OTTAWA R10.
 - ALL EXISTING SANITARY AND STORM SERVICES ARE TO BE CAPPED AT THE PROPERTY LINE TO THE SATISFACTION OF THE CITY OF OTTAWA'S SEWER OPERATION.
 - MONITORING TEST PORTS FOR BUILDING SERVICES TO BE INSTALLED IN PARKING GARAGE.

WATERMAIN NOTES:

- | ITEM | SPEC. NO. | REFERENCE |
|--|-----------|----------------|
| WATERMAIN TRENCHING | W17 | CITY OF OTTAWA |
| THERMAL INSULATION IN SHALLOW TRENCHES | W22 | CITY OF OTTAWA |
| VALVE BOX ASSEMBLY | W24 | CITY OF OTTAWA |
| CONNECTION DETAIL FROM EXISTING TO NEW WM | W25.1 | CITY OF OTTAWA |
| WATERMAIN CROSSINGS BELOW SEWERS | W25 | CITY OF OTTAWA |
| WATERMAIN CROSSING OVER SEWER | W25.2 | CITY OF OTTAWA |
| THERMAL INSULATED AT OPEN STRUCTURE | W23 | CITY OF OTTAWA |
| WATER SERVICE INSULATION AT SEWER CROSSING | W38 | CITY OF OTTAWA |
- SUPPLY AND CONSTRUCT ALL WATERMANS AND APPURTENANCES IN ACCORDANCE WITH THE CITY OF OTTAWA STANDARDS AND SPECIFICATIONS. EXCAVATION, INSTALLATION, BACKFILL, AND RESTORATION OF ALL WATERMANS BY THE CONTRACTOR. CONNECTIONS AND SHUT-OFFS AT THE MAIN AND CHLORINATION OF THE WATER SYSTEM SHALL BE PERFORMED BY CITY OFFICIALS.
 - WATERMAIN SHALL BE MINIMUM 2.4m DEPTH BELOW GRADE UNLESS OTHERWISE INDICATED. OTHERWISE THERMAL INSULATION IS REQUIRED AS PER STD. DWG622.
 - PROVIDE MINIMUM 0.50m CLEARANCE BETWEEN OUTSIDE OF PIPES AT ALL CROSSINGS WHEN WATERMAIN IS BELOW AND MINIMUM 0.25m CLEARANCE WHEN WATERMAIN IS ABOVE.
 - WATER SERVICE IS TO BE CONSTRUCTED TO WITHIN 1.0m OF FOUNDATION WALL AND CAPPED, UNLESS OTHERWISE INDICATED.
 - ALL EXISTING WATER SERVICES TO BE BLANKED AT MAIN BY CITY FORCES. EXCAVATION AND REINSTATEMENT BY CONTRACTOR.

GRADING NOTES:




- ALL TOPSOIL, ORGANIC OR DELETERIOUS MATERIAL SHALL BE ENTIRELY REMOVED FROM BENEATH THE PROPOSED PAVED AREAS AS DIRECTED BY THE SITE ENGINEER OR GEOTECHNICAL ENGINEER.
- EXPOSED SUBGRADES IN PROPOSED PAVED AREAS SHOULD BE PROOF ROLLED WITH A LARGE STEEL DRUM ROLLER AND INSPECTED BY THE GEOTECHNICAL ENGINEER PRIOR TO THE PLACEMENT OF GRANULARS.
- ANY SOFT AREAS EVIDENT FROM THE PROOF ROLLING SHOULD BE SUB-EXCAVATED AND REPLACED WITH SUITABLE MATERIAL THAT IS FROST COMPATIBLE WITH THE EXISTING SOILS AS RECOMMENDED BY THE GEOTECHNICAL ENGINEER.
- THE GRANULAR BASE SHOULD BE COMPACTED TO AT LEAST 98% OF THE STANDARD PROCTOR MAXIMUM DRY DENSITY VALUE. ANY ADDITIONAL GRANULAR FILL USED BELOW THE PROPOSED PAVEMENT SHOULD BE COMPACTED TO AT LEAST 95% OF THE STANDARD PROCTOR MAXIMUM DRY DENSITY VALUE.
- MINIMUM OF 2% GRADE FOR ALL GRASS AREAS UNLESS OTHERWISE NOTED.
- MAXIMUM TERRACING GRADE TO BE 3:1 UNLESS OTHERWISE NOTED.
- ALL CURBS SHALL BE BARRIER CURBS (150mm) UNLESS OTHERWISE NOTED AND CONSTRUCTED AS PER CITY OF OTTAWA STANDARDS (SC1.1).
- REFER TO LANDSCAPE PLAN FOR PLANTING AND OTHER LANDSCAPE FEATURE DETAILS.
- CONTRACTOR TO PROVIDE THE CONSULTANT WITH A GRADING PLAN INDICATING AS-BUILT ELEVATIONS OF ALL DESIGN GRADES SHOWN ON THIS PLAN.

PAVEMENT STRUCTURE:

- | | |
|--|--|
| | LIGHT DUTY
50mm H.L.3
150mm GRAN "A"
300mm GRAN "B" TYPE II |
| | HEAVY DUTY
40mm H.L.3
50mm H.L.3
150mm GRAN "A"
450mm GRAN "B" TYPE II |

EROSION AND SEDIMENT CONTROL NOTES:

- ALL EROSION AND SEDIMENT CONTROLS SHALL BE INSTALLED TO THE SATISFACTION OF THE ENGINEER, CITY OF OTTAWA AND THE CONSERVATION AUTHORITY. THEY SHALL BE APPROPRIATE TO THE SITE CONDITIONS. PRIOR TO UNDERTAKING ANY SITE ALTERATIONS (FILLING, GRADING, REMOVAL OF VEGETATION, ETC.) AND DURING ALL PHASES OF SITE PREPARATION AND CONSTRUCTION, THESE PRACTICES SHALL BE IMPLEMENTED IN ACCORDANCE WITH THE CURRENT BEST MANAGEMENT PRACTICES FOR EROSION AND SEDIMENT CONTROL AND SHOULD INCLUDE AS A MINIMUM THOSE MEASURES INDICATED ON THE PLAN.
- TO PREVENT SURFACE EROSION FROM ENTERING THE DITCH OR STORM SYSTEM DURING CONSTRUCTION, FILTER SOCKS WILL BE PLACED UNDER GRATES OF ALL PROPOSED AND EXISTING CATCHBASINS AND STRUCTURES. A LIGHT DUTY SILT FENCE BARRIER WILL ALSO BE INSTALLED IN SELECTED LOCATIONS, AND STRAW BALE BARRIERS WILL BE INSTALLED WITHIN THE OUTLET DITCHES. THESE CONTROL MEASURES WILL REMAIN IN PLACE UNTIL VEGETATION HAS BEEN ESTABLISHED AND CONSTRUCTION COMPLETE.
- THE SEDIMENT CONTROL MEASURES SHALL ONLY BE REMOVED WHEN, IN THE OPINION OF THE ENGINEER, THE MEASURES ARE NO LONGER REQUIRED. NO CONTROL MEASURES MAY BE PERMANENTLY REMOVED WITHOUT PRIOR AUTHORIZATION FROM THE ENGINEER.
- THE CONTRACTOR SHALL IMMEDIATELY REPORT TO THE ENGINEER ANY ACCIDENTAL DISCHARGES OF SEDIMENT MATERIAL INTO ANY DITCH OR STORM SYSTEM. APPROPRIATE RESPONSE MEASURES, INCLUDING ANY REPAIRS TO EXISTING CONTROL MEASURES OR THE IMPLEMENTATION OF ADDITIONAL CONTROL MEASURES, SHALL BE CARRIED OUT BY THE CONTRACTOR WITHOUT DELAY.
- THE CONTRACTOR ACKNOWLEDGES THAT FAILURE TO IMPLEMENT EROSION AND SEDIMENT CONTROL MEASURES MAY BE SUBJECT TO PENALTIES IMPOSED BY ANY APPLICABLE REGULATORY AGENCY.
- THE CONTRACTOR SHALL PROVIDE DUST CONTROL WITH THE APPLICATION OF WATER AND/OR CALCIUM CHLORIDE AS REQUIRED.



NOTE: THE POSITION OF ALL POLE LINES, CONDUITS, WATERMANS, SEWERS AND OTHER UNDERGROUND AND OVERGROUND UTILITIES AND STRUCTURES IS NOT NECESSARILY SHOWN ON THE CONTRACT DRAWINGS, AND WHERE SHOWN, THE ACCURACY OF THE POSITION OF SUCH UTILITIES AND STRUCTURES IS NOT GUARANTEED. BEFORE STARTING WORK, DETERMINE THE EXACT LOCATION OF ALL SUCH UTILITIES AND STRUCTURES AND ASSUME ALL LIABILITY FOR DAMAGE TO THEM.

NOT FOR CONSTRUCTION

CLARIDGE HOMES
505 PRESTON STREET,
OTTAWA, ONTARIO
K1S 4N7

No.	REVISION	DATE	BY
3.	ISSUED FOR SPA	APR 28/23	GJM
2.	REVISED PER CITY COMMENTS	OCT 11/22	GJM
1.	REVISED PER CITY COMMENTS	MAY 31/22	GJM

STANDARD TRENCH REINSTATEMENT IN PAVED SURFACE



CISTERN SECTION

FOR REVIEW ONLY

ARM/JAG
ARM/GJM
C/JF
ARM/JAG
GJM

NOVATECH
Engineers, Planners & Landscape Architects
Suite 200, 240 Michael Cowpland Drive
Ottawa, Ontario, Canada K2M 1P6
Telephone: (613) 254-9643
Facsimile: (613) 254-5867
Website: www.novatech-eng.com



LOCATION
CITY OF OTTAWA
1200 MARITIME WAY
DRAWING NAME
NOTES AND DETAILS
PROJECT NO.: 120144
REV #3
DRAWING NO.: 120144 - ND1
City Plan #18348



LEGEND

---	PROPERTY LINE	---	PROPOSED TRENCH DRAIN
---	PROPOSED CURB	---	PROPOSED BUILDING ENTRANCE
---	PROPOSED DEPRESSED CURB	---	DIRECTION OF FLOW
---	PROPOSED TACTILE WALKING SURFACE INDICATOR (TWSI)	---	PROPOSED RETAINING WALL CW GUARD RAIL
○	PROPOSED STORM MANHOLE	○	PIPE CROSSING
○	PROPOSED CATCHBASIN MANHOLE	---	PROPOSED SWALE
○	PROPOSED CATCHBASIN	---	PROPOSED TERRACING
○	PROPOSED LANDSCAPE DRAIN	---	EXISTING UTILITY POLE CW GUY WIRES
○	PROPOSED AREA DRAIN	---	EXISTING WATERMAIN CW WATER VALVE
○	PROPOSED MUD MAT	---	EXISTING HYDRANT CW VALVE & LEAD
○	LIGHT DUTY SILT FENCE (OPSD 219.110)	---	EXISTING SANITARY MANHOLE & SEWER
○	PROPOSED FILTER BAGS AT CATCHBASINS, CATCHBASIN MANHOLES AND TRENCHDRAINS	---	EXISTING STORM MANHOLE & SEWER
		---	EXISTING CATCHBASIN
		---	EXISTING OVERHEAD WIRES
		---	EXISTING STREETLIGHT

- EROSION AND SEDIMENT CONTROL NOTES :**
- ALL EROSION AND SEDIMENT CONTROLS SHALL BE INSTALLED TO THE SATISFACTION OF THE ENGINEER, CITY OF OTTAWA AND THE CONSERVATION AUTHORITY. THEY SHALL BE APPROPRIATE TO THE SITE CONDITIONS, PRIOR TO UNDERTAKING ANY SITE ALTERATIONS (FILLING, GRADING, REMOVAL OF VEGETATION, ETC.) AND DURING ALL PHASES OF SITE PREPARATION AND CONSTRUCTION. THESE PRACTICES SHALL BE IMPLEMENTED IN ACCORDANCE WITH THE CURRENT BEST MANAGEMENT PRACTICES FOR EROSION AND SEDIMENT CONTROL AND SHOULD INCLUDE AS A MINIMUM THOSE MEASURES INDICATED ON THE PLAN.
 - TO PREVENT SURFACE EROSION FROM ENTERING THE DITCH OR STORM SYSTEM DURING CONSTRUCTION, FILTER SOCKS WILL BE PLACED UNDER GRATES OF ALL PROPOSED AND EXISTING CATCHBASINS AND STRUCTURES. A LIGHT DUTY SILT FENCE BARRIER WILL ALSO BE INSTALLED IN SELECTED LOCATIONS, AND STRAW BALE BARRIERS WILL BE INSTALLED WITHIN THE OUTLET DITCHES. THESE CONTROL MEASURES WILL REMAIN IN PLACE UNTIL VEGETATION HAS BEEN ESTABLISHED AND CONSTRUCTION COMPLETE.
 - THE SEDIMENT CONTROL MEASURES SHALL ONLY BE REMOVED WHEN, IN THE OPINION OF THE ENGINEER, THE MEASURES ARE NO LONGER REQUIRED. NO CONTROL MEASURES MAY BE PERMANENTLY REMOVED WITHOUT PRIOR AUTHORIZATION FROM THE ENGINEER.
 - THE CONTRACTOR SHALL IMMEDIATELY REPORT TO THE ENGINEER ANY ACCIDENTAL DISCHARGES OF SEDIMENT MATERIAL INTO ANY DITCH OR STORM SEWER SYSTEM. APPROPRIATE RESPONSE MEASURES, INCLUDING ANY REPAIRS TO EXISTING CONTROL MEASURES OR THE IMPLEMENTATION OF ADDITIONAL CONTROL MEASURES, SHALL BE CARRIED OUT BY THE CONTRACTOR WITHOUT DELAY.
 - THE CONTRACTOR ACKNOWLEDGES THAT FAILURE TO IMPLEMENT EROSION AND SEDIMENT CONTROL MEASURES MAY BE SUBJECT TO PENALTIES IMPOSED BY ANY APPLICABLE REGULATORY AGENCY.
 - THE CONTRACTOR SHALL PROVIDE DUST CONTROL WITH THE APPLICATION OF WATER AND/OR CALCIUM CHLORIDE AS REQUIRED.



REFER TO 120144-ND FOR ADDITIONAL NOTES & DETAILS

NOTE:
THE POSITION OF ALL POLE LINES, CONDUITS, WATERMANS, SEWERS AND OTHER UNDERGROUND AND OVERGROUND UTILITIES AND STRUCTURES IS NOT NECESSARILY SHOWN ON THE CONTRACT DRAWINGS, AND WHERE SHOWN, THE ACCURACY OF THE POSITION OF SUCH UTILITIES AND STRUCTURES IS NOT GUARANTEED. BEFORE STARTING WORK, DETERMINE THE EXACT LOCATION OF ALL SUCH UTILITIES AND STRUCTURES AND ASSUME ALL LIABILITY FOR DAMAGE TO THEM.

NOT FOR CONSTRUCTION

CLARIDGE HOMES
CLARIDGE HOMES
505 PRESTON STREET,
OTTAWA, ONTARIO
K1S 4N7.



No.	REVISION	DATE	BY
3.	ISSUED FOR SPA	APR 28/23	GJM
2.	REVISED PER CITY COMMENTS	OCT 11/22	GJM
1.	REVISED PER CITY COMMENTS	MAY 31/22	GJM

SCALE	DESIGN
1:250	ARM/CJF
1:250	ARM/JAG
0 2 4 6 8 10	CJF
	ARM/JAG
	GJM

FOR REVIEW ONLY

ARM/CJF
ARM/JAG
CJF
ARM/JAG
GJM

PROFESSIONAL ENGINEER
A. R. MESTWAP
100201904
APRIL 28, 2023
PROVINCE OF ONTARIO



PROFESSIONAL ENGINEER
G. J. MacDONALD
APR 28, 2023
PROVINCE OF ONTARIO

NOVATECH
Engineers, Planners & Landscape Architects
Suite 200, 240 Michael Cowpland Drive
Ottawa, Ontario, Canada K2M 1P6
Telephone: (613) 254-9643
Facsimile: (613) 254-5867
Website: www.novatech-eng.com

LOCATION
CITY OF OTTAWA
1200 MARITIME WAY

DRAWING NAME
EROSION AND SEDIMENT CONTROL PLAN

PROJECT No.: 120144
REV # 3
DRAWING No.: 120144-ESC
City Plan #18348



LEGEND

---	PROPERTY LINE	---	PROPOSED TRENCH DRAIN
---	PROPOSED CURB	---	PROPOSED BUILDING ENTRANCE
---	PROPOSED DEPRESSED CURB	---	DIRECTION OF FLOW
---	PROPOSED TACTILE WALKING SURFACE INDICATOR (TWSI)	---	PROPOSED RETAINING WALL C/W GUARD RAIL
---	PROPOSED CAP	---	PIPE CROSSING (REFER TO CROSSING TABLE)
---	PROPOSED SANITARY SEWER C/W MANHOLE	---	PROPOSED SWALE
---	PROPOSED STORM SEWER C/W MANHOLE	---	PROPOSED TERRACING
---	PROPOSED CATCHBASIN MANHOLE	---	EXISTING UTILITY POLE C/W GUY WIRES
---	PROPOSED LANDSCAPE DRAIN	---	EXISTING WATERMAIN C/W WATER VALVE
---	PROPOSED AREA DRAIN	---	EXISTING HYDRANT C/W VALVE & LEAD
---	PROPOSED INLET CONTROL DEVICE	---	EXISTING SANITARY MANHOLE & SEWER
---	PROPOSED SIAMSE CONNECTION	---	EXISTING STORM MANHOLE & SEWER
---	PROPOSED WATER MAIN	---	EXISTING CATCHBASIN
---	PROPOSED HYDRANT C/W LEAD & VALVE	---	EXISTING OVERHEAD WIRES
---	PROPOSED VALVE AND VALVE BOX	---	EXISTING STREETLIGHT
---	PROPOSED WATER METER	---	
---	PROPOSED REMOTE WATER METER	---	
---	PROPOSED REMOVAL	---	

PROPOSED WATERMAIN (200mmØ DOMESTIC SERVICE TABLE)

STATION	SURFACE ELEVATION	TWM ELEVATION	COMMENTS
1+000.0	95.31	*92.91	CONNECTION TO EXISTING 200mmØ WM
1+002.5	95.38	92.98	CROSS ABOVE 825mmØ SAN (0.99m CLEARANCE)
1+005.3	95.47	93.12	CROSS ABOVE 165mmØ STM AS PER CITY OF OTTAWA STANDARD W25.2 (0.25m CLEARANCE)
1+008.3	95.40	93.88	CROSS ABOVE 600mmØ WM AS PER CITY OF OTTAWA STANDARD W25.2 (0.25m CLEARANCE)
1+017.7	95.37	92.97	200mmØ VALVE AND VALVE BOX
1+022.0	95.13	92.73	CAP

PROPOSED WATERMAIN (200mmØ DOMESTIC SERVICE TABLE)

STATION	SURFACE ELEVATION	TWM ELEVATION	COMMENTS
2+000.0	95.33	92.93	CONNECTION TO EXISTING 200mmØ WM
2+002.5	95.40	93.00	CROSS ABOVE 825mmØ SAN (0.99m CLEARANCE)
2+004.5	95.47	93.12	CROSS ABOVE 165mmØ STM AS PER CITY OF OTTAWA STANDARD W25.2 (0.25m CLEARANCE)
2+008.3	95.41	93.89	CROSS ABOVE 600mmØ WM (0.25m CLEARANCE)
2+017.7	95.38	92.25	200mmØ VALVE AND VALVE BOX
2+021.4	95.13	95.13	CAP

PROPOSED WATERMAIN (200mmØ DOMESTIC SERVICE TABLE)

STATION	SURFACE ELEVATION	TWM ELEVATION	COMMENTS
3+000.0	96.08	93.68	CONNECTION TO EXISTING 200mmØ WM
3+003.6	96.11	93.71	CROSS ABOVE 825mmØ SAN (1.69m CLEARANCE)
3+008.3	96.08	93.68	CROSS ABOVE 165mmØ STM AS PER CITY OF OTTAWA STANDARD W25.2 (0.25m CLEARANCE)
3+009.0	96.02	94.50	CROSS ABOVE 600mmØ WM (0.25m CLEARANCE)
3+018.2	96.45	94.05	11.25" HORIZONTAL BEND
3+023.7	96.93	94.53	200mmØ VALVE AND VALVE BOX
3+025.0	96.98	94.58	CAP

PROPOSED WATERMAIN (200mmØ DOMESTIC SERVICE TABLE)

STATION	SURFACE ELEVATION	TWM ELEVATION	COMMENTS
4+000.0	96.09	*93.69	CONNECTION TO EXISTING 200mmØ WM
4+004.1	96.13	93.73	CROSS ABOVE 825mmØ SAN (1.69m CLEARANCE)
4+008.7	96.08	93.68	CROSS ABOVE 165mmØ STM AS PER CITY OF OTTAWA STANDARD W25.2 (0.25m CLEARANCE)
4+009.3	96.02	94.50	CROSS ABOVE 600mmØ WM AS PER CITY OF OTTAWA STANDARD W25.2 (0.25m CLEARANCE)
4+012.7	96.17	93.77	11.25" HORIZONTAL BEND
4+024.3	96.93	94.53	200mmØ VALVE AND VALVE BOX
4+025.3	96.98	94.58	CAP

PIPE CROSSING TABLE

CROSSING	LOWER PIPE	HIGHER PIPE	CLEARANCE
①	200mmØ SAN OBV = 93.29	300mmØ STM INV = 94.07*	0.78m
②	600mmØ WM OBV = 93.90	450mmØ STM INV = 94.28*	0.38m
③	165mmØ STM OBV = 92.68*	200mmØ SAN INV = 93.67	0.99m
④	600mmØ WM OBV = 93.45	200mmØ SAN INV = 93.71	0.26m
⑤	600mmØ WM OBV = 93.44	300mmØ STM INV = 93.71	0.27m
⑥	825mmØ SAN OBV = 91.79*	200mmØ WM INV = 92.80	1.01m
⑦	165mmØ STM OBV = 92.67*	200mmØ WM INV = 92.92	0.25m
⑧	600mmØ WM OBV = 93.43	200mmØ WM INV = 93.69	0.26m
⑨	825mmØ SAN OBV = 91.79*	200mmØ WM INV = 92.78	0.99m
⑩	165mmØ STM OBV = 92.67*	200mmØ WM INV = 92.92	0.25m
⑪	600mmØ WM OBV = 93.43	200mmØ WM INV = 93.68	0.25m
⑫	600mmØ WM OBV = 93.41	375mmØ STM INV = 94.24	0.83m
⑬	600mmØ WM OBV = 94.05	200mmØ WM INV = 94.30	0.25m
⑭	165mmØ STM OBV = 92.82*	200mmØ WM INV = 93.48	0.66m
⑮	825mmØ SAN OBV = 91.84*	200mmØ WM INV = 93.53	1.69m

*INVERTS/OBVERTS ON CONCRETE PIPES ARE OUTSIDE DIAMETER

CONTROLS

LOCATION	MODEL NO. / ORifice DIAMETER	5-YEAR FLOW (L/S)	5-YEAR HEAD (m)	100-YEAR FLOW (L/S)	100-YEAR HEAD (m)
CBMH 105	152mm PLATE	32.0	0.414	49.6	0.989
CISTERN	PUMP	133	0.53	133	1.73

REFER TO 120144-ND FOR ADDITIONAL NOTES & DETAILS

NOTE:
THE POSITION OF ALL POLE LINES, CONDUITS, WATERMANS, SEWERS AND OTHER UNDERGROUND AND OVERGROUND UTILITIES AND STRUCTURES IS NOT NECESSARILY SHOWN ON THE CONTRACT DRAWINGS, AND WHERE SHOWN, THE ACCURACY OF THE POSITION OF SUCH UTILITIES AND STRUCTURES IS NOT GUARANTEED. BEFORE STARTING WORK, DETERMINE THE EXACT LOCATION OF ALL SUCH UTILITIES AND STRUCTURES AND ASSUME ALL LIABILITY FOR DAMAGE TO THEM.

CLARIDGE HOMES
CLARIDGE HOMES
505 PRESTON STREET,
OTTAWA, ONTARIO
K1S 4N7.



NOT FOR CONSTRUCTION

No.	REVISION	DATE	BY	No.	REVISION	DATE	BY
8.	REVISED PER CITY COMMENTS	MAY 9/122	GJM	1.	ISSUED FOR COORDINATION	JAN/15/21	GJM
7.	REVISED PER CITY COMMENTS	NOV 19/21	GJM	2.	RE-ISSUED FOR COORDINATION	JAN 22/21	GJM
6.	ISSUED FOR COORDINATION BASED ON URDP	SEPT/23/21	JAG	3.	ISSUED FOR COORDINATION	JAN/15/21	GJM
5.	ISSUED FOR CITY COMMENTS	JUL/07/21	JAG	4.	ISSUED FOR COORDINATION	FEB/17/21	JAG
4.	ISSUED FOR COORDINATION	FEB/17/21	JAG	5.	ISSUED FOR COORDINATION	FEB/17/21	JAG
3.	SUBMITTED WITH ZONING/SITE PLAN APPLICATIONS	JAN/25/21	JAG	6.	ISSUED FOR COORDINATION	FEB/17/21	JAG
2.	RE-ISSUED FOR COORDINATION	JAN 22/21	GJM	7.	ISSUED FOR COORDINATION	FEB/17/21	JAG
10.	ISSUED FOR SPA	APR 28/23	GJM	8.	ISSUED FOR COORDINATION	FEB/17/21	JAG
9.	REVISED PER CITY COMMENTS	OCT 11/22	GJM	9.	ISSUED FOR COORDINATION	JAN/15/21	GJM

SCALE

1:250

FOR REVIEW ONLY

ARM/JAG
ARM/GJM
C/JF
ARM/JAG
GJM

PROFESSIONAL ENGINEER
A.R. MESTWAR
100201694
APRIL 28, 2023
PROVINCE OF ONTARIO



PROFESSIONAL DESIGNER
G.J. MacDONALD
APRIL 28, 2023
PROVINCE OF ONTARIO

NOVATECH
Engineers, Planners & Landscape Architects
Suite 200, 240 Michael Cowpland Drive
Ottawa, Ontario, Canada K2M 1P6
Telephone: (613) 254-6633
Facsimile: (613) 254-5867
Website: www.novatech-eng.com

LOCATION
CITY OF OTTAWA
1200 MARITIME WAY

DRAWING NAME
GENERAL PLAN OF SERVICES

PROJECT NO.: 120144
REV #10
DRAWING NO.: 120144 - GP
City Plan #18348



LEGEND

---	PROPERTY LINE	SAN MH	PROPOSED SANITARY MANHOLE
DC	PROPOSED DEPRESSED CURB	STM MH	PROPOSED STORM MANHOLE
XXXX	PROPOSED TACTILE WALKING SURFACE INDICATOR (TWSI)	○	PROPOSED HYDRANT & VALVE
96.40	PROPOSED ELEVATION	○	PROPOSED VALVE AND VALVE BOX
X 96.40	EXISTING ELEVATION	○	EXISTING VALVE & VALVE BOX
97.79(S)	PROPOSED SHALE ELEVATION	○	EXISTING VALVE & LEAD
97.79(W)	PROPOSED TOP OF WALL ELEVATION	○	EXISTING SANITARY MANHOLE
97.98(W)	PROPOSED BOTTOM OF WALL ELEVATION	○	EXISTING STORM MANHOLE
97.98(C)	PROPOSED TOP OF CURB ELEVATION	○	EXISTING CATCHBASIN
V&V	PROPOSED VALVE AND VALVE BOX	○	EXISTING DITCH CENTERLINE
FDSY	FIRE DEPARTMENT SIAMSE CONNECTION	○	EXISTING UTILITY POLE
---	PROPOSED BUILDING ENTRANCE	○	EXISTING UTILITY POLE ANCHORS
H.P.	PROPOSED HIGH POINT	○	EXISTING STREETLIGHT
---	SWALE OR SUBDRAIN AND DIRECTION OF FLOW		
---	TERRACING 3:1 SLOPE MAX (UNLESS OTHERWISE INDICATED)		
---	PROPOSED RETAINING WALL C/W GUARD RAIL		
---	SLOPE AND DIRECTION		
---	DIRECTION OF MAJOR OVERLAND FLOW		
---	PROPOSED LANDSCAPE DRAIN		
---	PROPOSED CATCHBASIN MANHOLE		
---	PROPOSED CATCHBASIN		
---	PROPOSED TRENCH DRAIN		

PAVEMENT STRUCTURE:


□	LIGHT DUTY 50mm HL3 150mm GRAN "A" 300mm GRAN "B" TYPE II
□	HEAVY DUTY 40mm HL3 50mm HL8 150mm GRAN "A" 450mm GRAN "B" TYPE II

REFER TO 120144-ND FOR ADDITIONAL NOTES & DETAILS

NOTE:
THE POSITION OF ALL POLE LINES, CONDUITS, WATERMANS, SEWERS AND OTHER UNDERGROUND AND OVERGROUND UTILITIES AND STRUCTURES IS NOT NECESSARILY SHOWN ON THE CONTRACT DRAWINGS, AND WHERE SHOWN, THE ACCURACY OF THE POSITION OF SUCH UTILITIES AND STRUCTURES IS NOT GUARANTEED. BEFORE STARTING WORK, DETERMINE THE EXACT LOCATION OF ALL SUCH UTILITIES AND STRUCTURES AND ASSUME ALL LIABILITY FOR DAMAGE TO THEM.

NOT FOR CONSTRUCTION

CLARIDGE HOMES
CLARIDGE HOMES
505 PRESTON STREET,
OTTAWA, ONTARIO
K1S 4N7.



No.	REVISION	DATE	BY	No.	REVISION	DATE	BY
8.	REVISED PER CITY COMMENTS	OCT 11/22	GJM	1.	SITE PLAN COORDINATION	JAN15/21	JAG
7.	REVISED PER CITY COMMENTS	MAY 31/22	GJM	2.	RE-ISSUED FOR COORDINATION	JAN22/21	JAG
6.	ISSUED FOR COORDINATION BASED ON URDP	SEPT23/21	JAG	3.	SUBMITTED WITH ZONING/SITE PLAN APPLICATIONS	JAN25/21	JAG
5.	ISSUED FOR CITY COMMENTS	JUL07/21	JAG	4.	ISSUED FOR COORDINATION	FEB17/21	JAG
4.	ISSUED FOR COORDINATION	JAN25/21	JAG	5.	ISSUED FOR CITY COMMENTS	JUL07/21	JAG
3.	SUBMITTED WITH ZONING/SITE PLAN APPLICATIONS	JAN25/21	JAG	6.	ISSUED FOR COORDINATION BASED ON URDP	SEPT23/21	JAG
2.	RE-ISSUED FOR COORDINATION	JAN22/21	JAG	7.	REVISED PER CITY COMMENTS	MAY 31/22	GJM
1.	SITE PLAN COORDINATION	JAN15/21	JAG	8.	REVISED PER CITY COMMENTS	OCT 11/22	GJM
9.	ISSUED FOR SPA	APR 28/23	GJM				

SCALE

1:250

0 2 4 6 8 10

FOR REVIEW ONLY

ARM/CJF
ARM/JAG
CJF
ARM/JAG
GJM

NOVATECH
Engineers, Planners & Landscape Architects
Suite 200, 240 Michael Cowpland Drive
Ottawa, Ontario, Canada K2M 1P6
Telephone: (613) 254-9643
Facsimile: (613) 254-5867
Website: www.novatech-eng.com

LOCATION
CITY OF OTTAWA
1200 MARITIME WAY

DRAWING NAME
GRADING PLAN

PROJECT No.
120144

REV
REV # 9

DRAWING No.
120144-GR