

PERMEABLE PAVERS

## ARCHITECTS: WOODMAN ARCHITECT & ASSOCIATES LTD. 201-4 Beechwood Avenue, Ottawa, ON. K1L 8L9 Tel : (613) 228 9848 EGEND EXTENT OF -CRITICAL ROOT ZONE EXISTING TREE TO REMAIN EXISTING GRASS TO REMAIN PROPOSED SODDED GRASS AREA \* \* \* PROPOSED RIVERSTONE MULCH 72020202 PROPOSED PRECAST CONCRETE PAVERS PROPOSED PERMEABLE PAVERS PROPOSED CONCRETE WALKWAY PROPOSED ORNAMENTAL GRASSES PROPOSED TREE PROTECTION FENCE 4 PROPOSED TWO SPACE BIKE RACK PROPOSED PLANTER WITH ANNUALS 'BY OWNER' REVISED PER CITY COMMENTS 01/16/2023 ML REVISED PER NEW SITE PLAN 08/23/2022 ML 04/05/2022 ML REVISED PER NEW SITE PLAN 02/18/2022 ML REVISED PER NEW SITE PLAN ORNAMENTAL GRASSES REMOVED 01/07/2022 ML 12/13/2021 ML REVISED PER NEW SITE PLAN ISSUED FOR DISCUSSION AND REVIEW 11/23/2020 ML ISSUED FOR DISCUSSION AND REVIEW 07/24/2020 ML Date DR Cł Issue JAMES B. LENNOX & ASSOCIATES INC. DRAINAGE VOID FILLED WITH MATERIAL LANDSCAPE ARCHITECTS AS RECOMMENDED BY MANUFACTURER 3332 CARLING AVE. OTTAWA, ONTARIO K2H 5A8 Tel. (613) 722-5168 Fax. 1(866) 343-3942 PERMEABLE PAVER UNIT PROJECT 1994 ST. JOSEPH BOULEVARD OTTAWA, ON DRAWING **TREE CONSERVATION REPORT &** LANDSCAPE PLAN 150mm MIN. DEPTH OF GRANULAR 'A' COMPACTED TO 100% S.P.D. SCALE - SUBGRADE COMPACTED TO 95% S.P.D. 25mm LEVELING BED OF COARSE SAND 1:150 OR MATERIAL AS RECOMMENDED BY MANUFACTURER START DATE APRIL 2020 ROJECT NO. 20MIS2031 N PROJECT NORTH DRAWING NO. 0 0 N N 0

CONSULTANTS

## . 800000 WORKMANSHIP PERMEABLE PAVERS BY UNILOCK LIMITED OR APPROVED EQUAL. PAVERS SHALL BE INSTALLED IN STRICT ACCORDANCE WITH THE MANUFACTURER'S RECOMMENDATIONS WITH TIGHT BUTT JOINTS OF APPROXIMATELY 3mm, ON A SAND BASE. SAW CUT PAVERS AS REQUIRED. USE AN APPROVED VIBRATORY COMPACTOR IN A CIRCULAR PATTERN. ALL DAMAGED OR CHIPPED PAVERS MUST BE REPLACED AT THE CONTRACTOR'S COST PREPARATION EXCAVATE AND REMOVE ALL TOPSOIL AND UNSTABLE MATERIALS OFF SITE. SUBGRADE TO BE GRADED TO SIMILAR CONTOURS AS FINISH GRADE. COMPACT SUBGRADE TO 95% S.P.D. PLACE 150mm LAYER OF GRANULAR 'A' COMPACTED TO 100% S.P.D. PLACE MAXIMUM 25mm UNCOMPACTED SAND FOR LEVELING COURSE OR MATERIAL AS RECOMMENDED BY MANUFACTURER INSTALL PERMEABLE UNITS IN THE PATTERN SPECIFIED ON THE PLAN DRAWING OR PER MANUFACTURER'S PATTERN RECOMMENDATION ALL MEASUREMENTS ARE IN MILLIMETRES UNLESS NOTED OTHERWISE

#18575

OT SIZE ARCH-D