



| | | | _ | 4 — |
|---------|-------------|-------------|----|---------|
| LUM NO. | LABEL | MTG. HT. | | LUM NO. |
| | A2B | 18 | | 36 |
| 2 | A2B | 18 | | 37 |
| | A2B1 | 18 | | 38 |
| , | A2B1 | 18 | | 39 |
| 5 | A2B2 | 18 | | 40 |
| ô | A3B8 | 18 | | 41 |
| 7 | A4-2 | 18 | | 42 |
| 8 | A472 | 18 | | 43 |
| 9 | A48 | 18 | | 44 |
| 10 | A48 | 18 | | 45 |
| 1 | A4B1 | 18 | 46 | |
| 12 | A4B1 | 18 | 47 | |
| 13 | A4B1 | 18 | 48 | |
| 14 | A4B1 | 18 | 49 | |
| 15 | BV | 2 | 50 | |
| 16 | BV | 2 | 51 | |
| 17 | BV | 2 | 52 | |
| 18 | BV | 2 | 53 | |
| 19 | BV | 2 | 54 | |
| 20 | BV | 2 | 55 | |
| 21 | BV | 2 | 56 | |
| 22 | CAN | 17.5 | 57 | |
| 23 | CAN | 17.5 | 58 | |
| 24 | CAN | 17.5 | 59 | |
| 25 | CAN | 17.5 | 60 | |
| 26 | CAN | 17.5 | 61 | |
| 27 | CAN | 17.5 | 62 | • |
| 28 | CAN | 17.5 | 63 | |
| 29 | CAN | 17.5 | 64 | |
| 30 | CAN | 17.5 | 65 | |
| 31 | CAN | 17.5 | 66 | |
| 32 | CAN | 17.5 | 67 | |
| 33 | CAN | 17.5 | 68 | |
| 34 | CAN | 17.5 | 69 | |
| 35 | CAN | 17.5 | 70 | |

LUMINAIRE LOCATION SUMMARY

INAIRE LOCATION SUMMARY

- ALL AREA LIGHTS ON NEW 15 FT. POLE MOUNTED ON 3 FT. CONCRETE BASE

- ALL LUMINAIRES HAVE ZERO LUMENS ABOVE 90 DEGREES

| FOOTCANDLE LEVELS CALCULATED AT GRADE USING INITIAL LUMEN VALUES | | | | | | | | | |
|--|-------|------|-----|---------|---------|--|--|--|--|
| LABEL | AVG | MAX | MIN | AVG/MIN | MAX/MIN | | | | |
| PAVED AREA | 2.73 | 12.2 | 0.2 | 13.65 | 61.00 | | | | |
| PROPERTY LINE | 0.11 | 0.5 | 0.0 | N.A. | N.A. | | | | |
| UNDEFINED | 0.46 | 11.7 | 0.0 | N.A. | N.A. | | | | |
| UNDER CANOPY | 21.23 | 28 | 14 | 1.52 | 2.00 | | | | |
| | | | | | | | | | |

| LUM | LUMINAIRE SCHEDULE | | | | | | | | | | | | |
|-----|--------------------|-----|-------|-------------|--------|-------|--------------------------|-------|------------|-----------------|-------------|---------------|--|
| SYN | /IBOL | QTY | LABEL | ARRANGEMENT | LUMENS | LATF | DIMMING LUMEN MULTIPLIER | LLF | BUG RATING | WATTS/LUMINAIRE | TOTAL WATTS | MANUFACTURER | CATALOG LOGIC |
| | | 2 | A2B | SINGLE | 3300 | 1.040 | 1.000 | 1.040 | B1-U0-G1 | 29 | 58 | Cree Inc | OSQ-ML-B-DA-XX + OSQM-B-4L-30K7-2M-UL-NM-XX + OSQ-BLSMF |
| | | 2 | A2B1 | SINGLE | 1820 | 1.040 | 1.000 | 1.040 | B1-U0-G1 | 16 | 32 | Cree Inc | OSQ-ML-B-DA-XX + OSQM-B-4L-30K7-2M-UL-NM-XX-Q1 + OSQ-BLSMF |
| | | 1 | A2B2 | SINGLE | 2150 | 1.040 | 1.000 | 1.040 | B1-U0-G1 | 18 | 18 | Cree Inc | OSQ-ML-B-XX-XX + OSQM-B-4L-30K7-2M-UL-NM-XX-Q2 + OSQ-BLSMF |
| | | 1 | A3B8 | SINGLE | 3250 | 1.040 | 1.000 | 1.040 | B1-U0-G1 | 27 | 27 | Cree Inc | OSQ-ML-B-XX-XX + OSQM-B-4L-30K7-3M-UL-NM-XX-Q8 + OSQ-BLSMF |
| | | 1 | A4-2 | BACK-BACK | 15498 | 1.040 | 1.000 | 1.040 | B3-U0-G3 | 104 | 208 | Cree Inc | OSQ-ML-B-XX-XX + OSQM-B-16L-30K7-4M-UL-NM-XX |
| | 4 | 1 | A472 | BACK-BACK | 3950 | 1.040 | 1.000 | 1.040 | B1-U0-G1 | 26 | 52 | Cree Inc | OSQ-ML-B-XX-XX + OSQM-B-4L-30K7-4M-UL-NM-XX-Q7 |
| | | 2 | A48 | SINGLE | 4120 | 1.040 | 1.000 | 1.040 | B1-U0-G1 | 27 | 54 | Cree Inc | OSQ-ML-B-DA-XX + OSQM-B-4L-30K7-4M-UL-NM-XX-Q8 |
| | | 4 | A4B1 | SINGLE | 1820 | 1.040 | 1.000 | 1.040 | B0-U0-G1 | 16 | 64 | Cree Inc | OSQ-ML-B-DA-XX + OSQM-B-4L-30K7-4M-UL-NM-XX-Q1 + OSQ-BLSMF |
| ** | | 7 | BV | Single | | | | | | | | VISO Lighting | BL1.24 |
| * | — | 24 | CAN | SINGLE | 10999 | 1.040 | 0.550 | 0.572 | B3-U0-G0 | 64.68 | 1552.32 | CREE, INC. | CAN-228-PS-RM-06-E-UL-XX-700-30K (SET DIAL @ 1) |
| | \bigoplus | 9 | L | SINGLE | 1800 | 1.040 | 1.000 | 1.040 | B1-U0-G0 | 20.5 | 184.5 | Cree Lighting | LR6X-18L-30K |
| * | | 6 | WP1 | SINGLE | 3262 | 1.040 | 0.140 | 0.146 | B1-U0-G1 | 5.5 | 33 | Cree Inc. | SEC-EDG-2M-WM-02-E-UL-XX-700-30K-DIM (SET @ 1.1V) |
| * | | 5 | WP3 | SINGLE | 9674 | 1.040 | 0.560 | 0.582 | B2-U0-G2 | 60.3 | 301.5 | Cree Inc. | SEC-EDG-4M-WM-06-E-UL-XX-700-30K-DIM (SET @ 3.9V) |
| * | | 5 | WP4 | SINGLE | 3262 | 1.040 | 0.280 | 0.291 | B1-U0-G1 | 10.5 | 52.5 | Cree Inc. | SEC-EDG-4M-WM-02-E-UL-XX-700-30K-DIM (SET @ 1.9V) |

^{*} LUMENS AREA BASED ON CCT=5700K X .763 SCALE FACTOR FOR CCT=3000K

DISCLAIMER

ANY SITE PLAN(S), FLOOR PLAN(S), RENDERING(S), LIGHTING LAYOUT(S) AND PHOTOMETRIC PLAN(S) INCLUDING BUT NOT LIMITED TO ANY PROJECT(S) CREATED/PRODUCED BY RED LEONARD ASSOCIATES INC., ARE ONLY INTENDED FOR ILLUSTRATION AND QUOTING PURPOSES ONLY. RED LEONARD ASSOCIATES HAS THE RIGHT TO USE THIRD PARTY LASERS, SCANNERS, AND CAMERAS BUT ACTUAL PROJECT CONDITIONS, DIMENSIONS, AND ACCURACY OF MEASUREMENTS MAY DIFFER FROM THESE OR ANY PARAMETERS. RED LEONARD ASSOCIATES INC. ASSUMES NO LIABILITY FOR WHAT IS CREATED/PRODUCED IN THESE RECREATIONS. THIS INCLUDES BUT IS NOT LIMITED TO THE USE OF, INSTALLATION OF AND/OR INTEGRITY OF EXISTING BUILDING(S), SURROUNDING AREA FOR PRODUCT(S) SUCH AS EXISTING POLE(S), ANCHOR BOLT(S), BASE(S), ARCHITECTURAL AND SIGNAGE STRUCTURE(S), LANDSCAPING PLAN(S), LIGHTING PLAN(S), FIXTURE SELECTION(S) AND PLACEMENT, MATERIAL(S), COLOR ACCURACY, TEXTURE(S), AND ANYTHING ATTRIBUTED TO PHOTO REALISM THAT IS CREATED. FURTHERMORE, RED LEONARD ASSOCIATES INC., DOES NOT ASSUME LIABILITY WHATSOEVER FOR ANY PURCHASES MADE BY CLIENT BEFORE, DURING, OR AT THE CONCLUSION OF THE PUBLISHED WORK. THE CUSTOMER, ITS RELATIVE AFFILIATES, AS WELL AS ANY OTHER PERSON(S) IN VIEWING OF THIS PRODUCT IS RESPONSIBLE FOR VERIFYING COMPLIANCE WITH ANY BUT NOT LIMITED TO ALL CODES, PERMITS, RESTRICTIONS, INSTRUCTIONS, PURCHASES, AND INSTALLATIONS OF OBJECTS VIEWED WITHIN THIS DOCUMENT(S) OR PROJECT(S). SYMBOLS ARE NOT DRAWN TO SCALE. SIZE IS FOR CLARITY PURPOSES ONLY. SIZES AND DIMENSIONS ARE APPROXIMATE, ACTUAL MEASUREMENTS MAY VARY. DRAWINGS ARE NOT INTENDED FOR ENGINEERING OR CONSTRUCTION USE. THIS DOCUMENT, ANY RED LEONARD DRAWING(S), OR PROJECT(S) IS NOT TO BE USED AND/OR INTENDED FOR ENGINEERING OR CONSTRUCTION PURPOSES, BUT FOR ILLUSTRATIVE PURPOSES ONLY. ANY LOCATIONS OF EMERGENCY LIGHTING SHOWN WERE PROVIDED BY OTHERS. RED LEONARD ASSOCIATES IS NOT RESPONSIBLE FOR INSUFFICIENT LIGHTING DURING AN EMERGENCY EVENT.

SCALE: LAYOUT BY: 1" = 30' DWG SIZE: DATE: 4/9/21 D

PROJECT NAME:
CIRCLE K OTTAWA, ON RL-7298-S1-R4

1340 Kemper Meadow Dr, Forest Park, OH 45240 513-574-9500 | redleonard.com

R2 FNE

R3 FNE

R4 FNE 3/22/22

8/2/21

DESCRIPTION REVISED AREA LIGHT LOCATIONS TO GET BETTER LIGHTING AT ENTRANCES & REDUCE AMOUNT OF POLES REVISED TO GET 0 FC @ P/L & CHANGE ALL FIXTURES TO 30K REVISED PER UPDATED SITE PLAN, MEET P/L MAX OF .5 FC REVISED PER UPDATED SITE PLAN & ADDED AREA

LIGHTS TO BRING LEVELS UP IN PARKING

ANY USE OF THIS DOCUMENTATION AND/OR OTHER ARTICLES PRODUCED BY RED LEONARD WITHOUT WRITTEN AUTHORIZATION FROM JAYME J. LEONARD IS STRICTLY PROHIBITED.

^{**} NO IES FILE AVAILABLE. CONTRIBUTION NOT SHOWN.