

18 Louisa Street

Transportation Impact Assessment

Step 1 Screening Report

Step 2 Scoping Report

Step 3 Forecasting Report

Step 4 Strategy Report

Prepared for:

Ironwood Fun Limited Partnership
18 Louisa Street, Suite 370
Ottawa, ON K1R 6Y6

Prepared by:



13 Markham Avenue
Ottawa, ON K2G 3Z1

May 2021

PN: 2021-015

Table of Contents

1	Screening	1
2	Existing and Planned Conditions	1
2.1	Proposed Development.....	1
2.2	Existing Conditions	3
2.2.1	Area Road Network	3
2.2.2	Existing Intersections.....	4
2.2.3	Existing Driveways	5
2.2.4	Cycling and Pedestrian Facilities.....	5
2.2.5	Existing Transit.....	7
2.2.6	Existing Area Traffic Management Measures.....	9
2.2.7	Existing Peak Hour Travel Demand.....	9
2.2.8	Collision Analysis	12
2.3	Planned Conditions.....	15
2.3.1	Changes to the Area Transportation Network	15
2.3.2	Other Study Area Developments.....	15
3	Study Area and Time Periods	15
3.1	Study Area	15
3.2	Time Periods	15
3.3	Horizon Years.....	15
4	Exemption Review	15
5	Development-Generated Travel Demand	16
5.1	Trip Generation and Mode Shares	16
5.2	Trip Distribution.....	17
5.3	Trip Assignment.....	17
6	Background Network Travel Demands.....	18
6.1	Transportation Network Plans	18
6.2	Background Growth.....	18
6.3	Other Developments	19
7	Demand Rationalization	19
7.1	2025 Future Background Operations	19
7.2	2030 Future Background Operations	21
7.3	Demand Rationalization Conclusions	22
8	Development Design	23
8.1	Design for Sustainable Modes.....	23
8.2	Circulation and Access.....	23
9	Parking.....	23
9.1	Parking Supply	23
10	Boundary Street Design.....	23
11	Access Intersections Design	24
11.1	Location and Design of Access.....	24
11.2	Intersection Control.....	24
11.3	Access Intersection Design	24

11.3.1	Access Intersection MMLOS	24
11.3.2	Recommended Design Elements	24
12	Transportation Demand Management	24
12.1	Context for TDM	24
12.2	Need and Opportunity.....	25
12.3	TDM Program	25
13	Neighbourhood Traffic Management.....	25
14	Transit.....	26
14.1	Route Capacity.....	26
14.2	Transit Priority	26
15	Network Intersection Design.....	27
15.1	Network Intersection Control.....	27
15.2	Network Intersection Design.....	27
15.2.1	2025 Future Total Network Intersection Operations	27
15.2.2	2030 Future Total Network Intersection Operations	28
15.2.3	Network Intersection MMLOS.....	30
15.2.4	Recommended Design Elements.....	31
16	Summary of Improvements Indicated and Modifications Options	31
17	Conclusion	34

List of Figures

Figure 1:	Area Context Plan	1
Figure 2:	Site Plan	2
Figure 3:	Study Area Pedestrian Facilities	5
Figure 4:	Study Area Cycling Facilities	6
Figure 5:	Existing Pedestrian Counts	7
Figure 6:	Existing Cyclist Counts	7
Figure 7:	Existing Study Area Transit Service.....	8
Figure 8:	Existing Study Area Transit Stops	9
Figure 9:	Existing Traffic Counts	10
Figure 10:	Study Area Collision Records – Representation of 2015-2019.....	13
Figure 11:	New Site Generation Auto Volumes.....	18
Figure 12:	2025 Future Background Volumes	19
Figure 13:	2030 Future Background Volumes	21
Figure 14:	2025 Future Total Volumes	27
Figure 15:	2030 Future Total Volumes	29

Table of Tables

Table 1:	Intersection Count Date.....	9
Table 2:	Existing Intersection Operations.....	10
Table 3:	Study Area Collision Summary, 2015-2019	12
Table 4:	Summary of Collision Locations, 2015-2019	13

Table 5: Bronson Avenue at Arlington Avenue Collision Summary 14

Table 6: Lebreton Street at Gladstone Avenue Collision Summary 14

Table 7: Exemption Review 16

Table 8: Trip Generation Person Trip Rates 16

Table 9: Total Person Trip Generation 16

Table 10: Mode Shares 17

Table 11: Trip Generation by Mode 17

Table 12: OD Survey Distribution – Ottawa Inner 17

Table 13: TRANS Regional Model Projections – Study Area Growth Rates..... 18

Table 14: 2025 Future Background Intersection Operations 20

Table 15: 2030 Future Background Intersection Operations 21

Table 16: Boundary Street MMLOS Analysis 24

Table 17: NTM Review of Internal Study Area Roadways – Relative Threshold Proportions 25

Table 18: NTM Review of External Study Area Roadways 26

Table 19: Trip Generation by Transit Mode 26

Table 20: 2025 Future Total Network Intersection Operations 27

Table 21: 2030 Future Total Network Intersection Operations 29

Table 22: Study Area Intersection MMLOS Analysis 30

List of Appendices

Appendix A – TIA Screening Form and Certification Form

Appendix B – Turning Movement Count Data

Appendix C – Synchro Intersection Worksheets – Existing Conditions

Appendix D – Collision Data

Appendix E – TRANS Model Plots

Appendix F –Synchro Intersection Worksheets – 2025 Future Background Conditions

Appendix G– Synchro Intersection Worksheets – 2030 Future Background Conditions

Appendix H – MMLOS Analysis

Appendix I – TDM Checklists

Appendix J – Synchro Intersection Worksheets – 2025 Future Total Conditions

Appendix K –Synchro Intersection Worksheets – 2030 Future Total Conditions

1 Screening

This study has been prepared according to the City of Ottawa’s 2017 Transportation Impact Assessment (TIA) Guidelines. Accordingly, a Step 1 Screening Form has been prepared and is included as Appendix A, along with the Certification Form for the TIA Study PM. As shown in the Screening Form, a TIA is required for the Trip Generation Trigger and Location Trigger and will include the Design Review component and the Network Impact Component. The TIA will support the zoning bylaw and site plan applications.

2 Existing and Planned Conditions


2.1 Proposed Development

The subject site, zoned as Institutional (I1A), is the location of the Gladstone Sports and Health Centre with a 3-storey building, surface parking and a gym spanning part of the parking area. The existing accesses are located on Louisa Street and Arlington Avenue, with a one-way laneway at the rear of the existing building between Arlington Avenue and Louisa Street. The proposed redevelopment is for the eastern portion of the parcel and replace the surface parking and gyms with a 9-storey residential building, consisting of 139 apartment units, a total of 82 parking spaces in two levels of underground parking, and a total of 70 bike parking spaces will be provided. The two-way access on Louisa Street will be converted to a loading access only and the two-way access on Arlington Avenue will be converted to the underground parking ramp. The development is expected to be completed by 2025.


No changes are contemplated to the existing 3-storey building and rear lane located behind the building.

Figure 1 illustrates the Study Area Context. Figure 2 illustrates the proposed concept plan.

Figure 1: Area Context Plan



Source: <http://maps.ottawa.ca/geoOttawa/> Accessed: March 4, 2021



A1.00 SITE PLAN
 A1.00 1:150

NOTE:
 ALL EXISTING SITE INFORMATION AS PER SITE SURVEY PLAN DATED NOVEMBER 2ND, 2020 AND PREPARED BY ANNIS O'SULLIVAN, VOLLBECK LTD.

BUILDING AREA SUMMARY

BUILDING AREA	12540 SQ.FT.
NUMBER OF STOREYS ABOVE GRADE	9 STOREYS
TOTAL GROSS AREA	105,720 SQ.FT. (EXCLUDES AREA BELOW GRADE)
TOTAL NET/LEASEABLE AREA	86,535 SQ.FT.
RESIDENTIAL COM/RET	- SQ.FT.
TOTAL GFA (AS PER CITY DEF.)	- SQ.FT.
UNIT SUMMARY	
TOTAL UNITS	139

STUDIO	QTY.	RATIO %
STUDIO	34	24.5%
1 BEDROOM	36	26%
VALUE 1 BEDROOM	32	23%
1 BEDROOM + DEN	7	5%
VALUE 2 BEDROOM	3	2%
2 BEDROOM	27	19%
2 BEDROOM + DEN	-	0%

AVERAGE UNIT SIZE 623 SQ.FT.

ZONING NOTES:
 CURRENT ZONING: IIA - Minor Institutional Zone
 LEGAL DESCRIPTION: REGISTERED PLAN XXXXXX CITY OF OTTAWA

DEVELOPMENT STATS	REQUIRED	PROPOSED
LOT AREA : 3,292 m ²	MIN 1150 m ²	3,292 m ²
LOT WIDTH (BELL ST.) : 55.91 m		55.91 m
LOT DEPTH (LOUISA ST.) : 58.86 m		58.86 m
% OF LANDSCAPED AREA		139
LOT OF AREA "A"		24.2%
TOTAL UNITS		139
SETBACK ALONG LOUISA	3 m	2 m
SETBACK ALONG BELL	3 m	3 m
SETBACK ALONG ARLINGTON	3 m	2 m
MAXIMUM HEIGHT	15 m	31 m
NUMBER OF STOREYS		9
BUILDING GFA		9,802 m ²
ZONING GFA (as per city zoning def.)		180

PARKING REQUIREMENTS

1. VEHICLE PARKING

Use	Parking rate	GFA/Units	Parkings
Office	1 per 100m ²	889 sqm.	689
Medical Facility	2 per 100m ²	214 sqm.	422
Industrial Facility	1.50 per 100m ²	111 sqm.	159
Residential	0.8 unit space required for 100 sqm.	139 units	650
Multi Residential	0.8 unit space required for 100 sqm.	139 units	1270

Use	Required
Residential	650
Industrial Facility	159
Office, Medical & Visitor Shared (see chart below)	26.74
Total Required	86

Shared Parking Provisions (Section 104)

Land Use	Required Parking Count (per Section 101)	Weekly - Meeting	Weekly - Access	Weekly - Delivery	Saturday - Meeting	Saturday - Access	Saturday - Delivery	Monthly - Meeting	Monthly - Access	Monthly - Delivery
Office	437	1008	607	1026	1026	208	1219	1019	1019	1019
Medical Facility	432	1008	432	1008	432	1008	208	1008	1008	1008
Visitor Parking	1579	2008	438	438	1008	127	1008	127	1008	127
Total	2048	1716	1444	1934	1438	1474	1474	1385	1385	1329

LAND USE
 RESIDENTIAL: 65 PARKING SPACES PROVIDED
 INSTRUCTIONAL FACILITY: 2 PARKING SPACES PROVIDED
 OFFICE, MEDICAL & VISITOR: 21 PARKING SPACES PROVIDED


TOTAL PARKING PROVIDED: 88 TOTAL PARKING SPACES PROVIDED; 80 UNDERGROUND+8 AT GRADE
 *2020 STANDARDS REQUIRE 4 ACCESSIBLE PARKING STALLS, ALL ARE PROVIDED UNDERGROUND

2. BICYCLE PARKING
 REQUIRED BICYCLE PARKING SPACES (0.5 SPACE/UNIT = 69.5 SPACES REQUIRED FOR 139 UNITS)
 RESIDENTIAL (NEW): 1 SPACE/1,000SQ.M = 0.2 SPACES REQUIRED FOR 308SQ.M
 INSTRUCTIONAL FACILITY (EXISTING): 1 SPACE/1,000SQ.M = 0.2 SPACES REQUIRED FOR 216SQ.M
 MEDICAL FACILITY (EXISTING): 1 SPACE/200SQ.M = 3.8 SPACES REQUIRED FOR 92SQ.M
 OFFICE SPACE (EXISTING): 1 SPACE/200SQ.M = 3.8 SPACES REQUIRED FOR 92SQ.M

PROVIDED BICYCLE PARKING SPACES: 59 INTERIOR+20 EXTERIOR SPACES**
 TOTAL BIKE STALLS must include meeting city requirements

3. AMENITY REQUIREMENTS
 REQUIRED AMENITY SPACE: 6 m² REQUIRED PER UNIT
 139 UNITS X 6 SQ.M = 834 SQ.M. TOTAL AMENITY REQUIRED
 REQUIRED AMENITY SPACE TO BE COMMON = 417 SQ.M.
 PROVIDED COMMON AMENITY SPACE = 457 SQ.M.

PROVIDED AMENITY SPACE BREAKDOWN:
 - GROUND FLOOR COMMON AMENITY = 85 m² (INTERIOR)
 - TOP FLOOR COMMON AMENITY = 85 m² (INTERIOR) + 316 m² (EXTERIOR) = 404 m²
 - PRIVATE BALCONY AMENITY = TBD m²
 TOTAL AMENITY SPACE PROVIDED



LEGEND

[Symbol] PROPOSED FIRE ROUTE	[Symbol] EDGE OF SIDEWALK	[Symbol] P/D PARKING TICKET DISPENSER
[Symbol] PROPOSED BUILDING	[Symbol] PROPOSED PROPERTY LINE	[Symbol] P/D EXISTING PAY & DISPLAY
[Symbol] BUILDING TO BE DEMOLISHED	[Symbol] SETBACK	[Symbol] EXISTING TRANSIT STOP
[Symbol] M/H EXISTING TRAFFIC MAN HOLE	[Symbol] PROPOSED DEPRESSION CURB DETAIL TO STANDARD SC-7	[Symbol] EXISTING CATCH BASIN
[Symbol] M/H EXISTING TRAFFIC MAN HOLE	[Symbol] EXTENT OF PRIVATELY OWNED PUBLIC SPACE	[Symbol] EXISTING CATCH BASIN
[Symbol] TSP EXISTING TRAFFIC LIGHT	[Symbol] CURB TO BE RESULT	[Symbol] EXISTING SIGN
[Symbol] EXISTING FIRE HYDRANT	[Symbol] ROLL CURB	[Symbol] EXISTING BOLLARD
[Symbol] CITY OF OTTAWA STANDARD	[Symbol] EXISTING UTILITY POLE	[Symbol] EXISTING LIGHT POLE
[Symbol] BIKE PARKING SPACE	[Symbol] FIRE DEPARTMENT CONNECTION	[Symbol] NEW LIGHT POLE
		[Symbol] PROPOSED WALL MOUNTED LIGHT
		[Symbol] EXISTING STREET LIGHTING BOX
		[Symbol] EXISTING TRAFFIC SIGNAL BOX

PROJECT TEAM

ARCHITECT
 HOBIN ARCHITECTURE
 David Anderson
 david@hobinarchitect.com
 413.238.7300 ext. 240
 413.238.7300 ext. 240
 413.468.3459
 david@hobinarchitect.com

OWNER
 ANNEBISH DEVELOPMENTS
 Kenneth Jennings
 kenneth@annebishdevelopments.com
 413.468.3459
 chris@annebishdevelopments.com
 413.468.3459

PLANNING
 FORTNER PLANNING + DESIGN
 Julie Carraro
 julie@fortnerplanning.com
 413.732.5709 ext. 240
 413.732.5709 ext. 240
 julie@fortnerplanning.com

CIVIL
 HOVAITECH
 Francesco Truivette
 francesco@hovaitech.com
 413.254.9443 Ext. 219

LANDSCAPE ARCHITECT
 RUSLAND & ASSOCIATES
 Annette Rutland
 annette@rusland.ca
 413.224.4744 x 222

TRANSFORMATION
 COIN TRANSFORMATION
 Andrew Horte
 andrew@cointransformation.com
 413.836.9764 x112

ENVIRONMENTAL
 GRADIENT WIND
 Justin Nataro
 justin@gradientwind.com
 413.836.9764 x112

GEOTECHNICAL
 PATRICKSON GROUP
 Faisal Adnan-Saleh
 faisal@patricksongroup.ca
 (613) 224-7381 Ext. 210
 David Gilbert
 david@patricksongroup.ca
 (613) 224-7381 Ext. 205

no.	date	revision
2	20210525	ISSUED FOR REZONING
2	20210323	ISSUED FOR COORDINATION
1	20210226	ISSUED FOR COORDINATION

It is the responsibility of the appropriate contractor to check and verify all dimensions on site and report all errors and/or omissions to the architect.

All contractors must comply with all pertinent codes and by-laws.
 Do not scale drawings.
 This drawing may not be used for construction until signed.
 Copyright reserved.



PROJECT LOCATION:
 18 LOUISA

DRAWING TITLE:
 SITE PLAN

DRAWN BY:	DATE:	SCALE:
DA	2021-03-23	1:100
PROJECT:	DRAWING NO.:	REVISION NO.:
2023	SP-1	

2.2 Existing Conditions

2.2.1 Area Road Network

Bronson Avenue: Bronson Avenue is a City of Ottawa arterial road with a four-lane urban cross-section, sidewalks on both sides of the road, and no stopping is permitted during the peak hours. The posted speed limit is 50 km/h and the City-protected right-of-way is 23.0 metres. Bronson Avenue is a truck route.

Catherine Street: Catherine Street is a City of Ottawa arterial one-way road with a three-lane urban cross-section, sidewalks on both sides of the road, and no stopping is permitted during the peak hours. The posted speed limit is 50 km/h and the City-protected right-of-way is 23.0 metres. Catherine Street is a truck route.

Raymond Street: Raymond Street is a City of Ottawa arterial one-way road between Bronson Avenue and the Highway 417 on-ramp, and a one-way local road to the west of the on-ramp. The urban cross-section reduces from a three-lane width to a single lane west of the Highway 417 on-ramp with a parking bays located on the north side. Parking is restricted to one-hour between 7AM and 7PM. The unposted speed limit is 50 km/h and the existing right-of-way varies between 12.5 to 20.0 metres. Catherine Street is a truck route.

Booth Street: Booth Street is a City of Ottawa major collector road with a 2-lane urban cross-section, sidewalks on both sides of the road, and parking bays provided on the east side of the road. The posted speed limit is 40 km/h and the existing right-of-way is 20.0 metres.

Gladstone Avenue: Gladstone Avenue is a City of Ottawa City of Ottawa major collector road with a two-lane urban cross-section, sidewalks on both sides of the road and a parking lane located on the north side. The posted speed limit is 40 km/h and the existing right-of-way varies from 20.0 to approximately 36.0 metres. Gladstone Avenue is a truck route.

Arlington Avenue: Arlington Avenue is a City of Ottawa local road with a two-lane urban cross-section, sidewalks on both sides of the road and on-street parking is permitted on the north side of the road. The unposted speed limit is 50 km/h and the existing right-of-way is 15.5 metres.

Bell Street North: Bell Street North is a City of Ottawa local road with a two-lane urban cross-section, sidewalks on both sides of the road and on-street parking is permitted on the west side of the road, with a winter restriction between December 1st and March 31st. Between Arlington Street and Gladstone Avenue, the east side of the road is reserved for permit parking and valet service for the LIV apartments at 207 Bell Street. The unposted speed limit is 50 km/h and the existing right-of-way is 10.5 metres.

Lebreton Street North: Lebreton Street North is a City of Ottawa local road with a two-lane urban cross-section, sidewalks on both sides of the road. on-street parking, signed 1-hour between 7AM and 7PM, is permitted on the west side of the road north of Willow Street within the study area, between Louisa Street and Gladstone Avenue, and south of Arlington Avenue and on the east side of the road between Gladstone Avenue and Willow Street, and between Louisa Street and Arlington Avenue. The posted speed limit is 30 km/h north of Gladstone avenue and the unposted speed limit is 50 km/h to the south, and the existing right-of-way is 20.0 metres.

Louisa Street: Louisa Street is a City of Ottawa local road with a two-lane urban cross-section, sidewalks on both sides of the road and on-street parking is permitted on the south side of the road to the east of Lebreton Street North and on the north side to the west. The parking is signed 1-hour between 7AM and 7PM. The unposted speed limit is 50 km/h and the existing right-of-way is 20.0 metres.

Highway 417 is noted within the study area although no on/off ramp terminal are assessed within the proposed scope of the study.

2.2.2 Existing Intersections

The key signalized area intersections within 400 metres of the site have been summarized below:

<i>Bronson Avenue at Catherine Street/Raymond Street</i>	The intersection of Bronson Avenue at Catherine Street/Raymond Street is a signalized intersection. The northbound approach consists of an auxiliary left-turn lane and two through lanes, the southbound approach consists of a through and shared through/right-turn lane and the westbound approach consists of an auxiliary left-turn lane, an auxiliary shared left-turn/through lane, a through lane and a shared through/right-turn lane. No turn restrictions are noted beyond the one-way on Catherine Street/Raymond Street does not permit any movements from the west side of the intersection.
<i>Bronson Avenue at Arlington Avenue</i>	The intersection of Bronson Avenue at Arlington Avenue is a signalized intersection. The northbound and southbound approaches each consist of a shared left-turn/through lane and shared through/right-turn lane, and the eastbound and westbound approaches each consist of a shared all movement lane. No turn restrictions are noted.
<i>Bronson Avenue at Gladstone Avenue</i>	The intersection of Bronson Avenue at Gladstone Avenue is a signalized intersection. The northbound and southbound approaches each consist of an auxiliary left-turn lane, through lane and shared through/right-turn lane, and the eastbound and westbound approaches each consist of an auxiliary left-turn lane and a shared through/right-turn lane. Right turns on red are restricted at all approaches weekdays between 7:00AM and 7:00PM.
<i>Booth Street at Gladstone Avenue</i>	The intersection of Booth Street at Gladstone Avenue is a signalized intersection. The northbound and southbound approaches each consist of a shared all movement lanes of over five metres which operate as an auxiliary left-turn movement and a shared through/right turn movement, the eastbound approach consists of an auxiliary left-turn lane and a through lane, and the westbound approach consists of an auxiliary left-turn lane and a shared through/right-turn lane. No right-turns are permitted on the eastbound direction from Gladstone Avenue onto Booth Street.
<i>Arthur Street/Arthur Lane at Gladstone Avenue</i>	The intersection of Arthur Street/Arthur Lane at Gladstone Avenue is a signalized intersection. The southbound, eastbound and westbound approaches all consist of a shared all movement lane. No turn restrictions are noted beyond the one-way on Arthur Lane south of Gladstone Avenue does not permit any movements from the south side of the intersection.
<i>Booth Street at Raymond Street</i>	The intersection of Booth Street at Raymond Street is a signalized intersection. The northbound approach consists of an auxiliary left-turn lane and a through lane, the southbound approach consists of a shared through/right-turn lane, and the westbound approach consists of a shared left-turn/through lane and an auxiliary right-turn lane. No turn restrictions are noted beyond the one-way on Catherine

Street/Raymond Street does not permit any movements from the west side of the intersection.

2.2.3 Existing Driveways


Within 200 metres of the site access on study area roadways, driveways to attached, detached, and low-rise residential. On Bell Street North, driveways to a church, private parking, and to a high-rise residential building are additionally present. On Louisa Street, a driveway to the existing site, driveways to a church, private parking, attached, are additionally present. On Arlington Avenue, driveways to an automotive garage, and to private parking are additionally present. On Lebreton Street North, driveways to private parking are additionally present. The existing one-way rear lane to the site accessing Arlington Avenue and Louisa Street is to be maintained.

2.2.4 Cycling and Pedestrian Facilities

Figure 3 illustrates the pedestrian facilities in the study area and Figure 4 illustrates the cycling facilities.

Sidewalks are generally provided along both sides of the study area roadways. Cycling facilities include the designations of Gladstone Avenue, Booth Street and Arlington Avenue as spine routes, and Arthur Lane as a local route. Arthur Lane and Arlington form the Centretown Neighbourhood Bikeway, which continues south on Booth Street from the intersection at Arlington Avenue.

Figure 3: Study Area Pedestrian Facilities



Source: <http://maps.ottawa.ca/geoOttawa/> Accessed: March 4, 2021

Figure 4: Study Area Cycling Facilities



Source: <http://maps.ottawa.ca/geoOttawa/> Accessed: March 4, 2021

Pedestrian and cyclist volumes included in study area intersection counts, presented in Section 2.2.7, have been compiled and are illustrated in Figure 5 and Figure 6 respectively.

Figure 5: Existing Pedestrian Counts





Figure 6: Existing Cyclist Counts



2.2.5 Existing Transit

Within the study area, the routes #10, 14, 55 and 114 area travel in proximity of the proposed site. The frequency of these routes within proximity of the proposed site currently are:

- Route #10 – 15-minute service during the day, 30-minute service during the early morning and evenings
- Route #14 – 15-minute service during the day, 30-minute service during the early morning and evenings
- Route #55 – 15 to 20-minute service during the day, 30-minute service during the evenings
- Route #114 – two trips downtown at 9:30 and 10:30AM, and two trips to Clarington at 1:30 and 2:30PM

Figure 7 illustrates the transit system map in the study area and Figure 8 illustrates nearby transit stops.

Figure 7: Existing Study Area Transit Service



Source: <http://www.octranspo.com/> Accessed: March 4, 2021

Figure 8: Existing Study Area Transit Stops



Source: <http://www.octranspo.com/> Accessed: March 4, 2021

2.2.6 Existing Area Traffic Management Measures

There are no existing area traffic management measures within the Study Area.

2.2.7 Existing Peak Hour Travel Demand

Existing turning movement counts were acquired from the City of Ottawa for the existing Study Area intersection. Table 1 summarizes the intersection count dates.

Table 1: Intersection Count Date

Intersection	Count Date
Bronson Avenue at Catherine Street/Raymond Street	Thursday, April 19, 2018
Bronson Avenue at Arlington Avenue	Wednesday, December 13, 2017
Bronson Avenue at Gladstone Avenue	Wednesday, July 27, 2016
Booth Street at Gladstone Avenue	Wednesday, July 27, 2016
Arthur Street/Arthur Lane at Gladstone Avenue	Wednesday, July 27, 2016
Booth Street at Raymond Street	Thursday, September 1, 2016

Figure 9 illustrates the existing traffic counts and Table 2 summarizes the existing intersection operations. The level of service for signalized intersections is based on HCM 2010 v/c calculations for individual lane movements and HCM 2000 v/c calculations for the overall intersection, and HCM average delay for unsignalized intersections.

Detailed turning movement count data is included in Appendix B and the Synchro worksheets are provided in Appendix C.

Figure 9: Existing Traffic Counts




Table 2: Existing Intersection Operations

Intersection	Lane	AM Peak Hour				PM Peak Hour			
		LOS	V/C	Delay	Q (95 th)	LOS	V/C	Delay	Q (95 th)
Bronson Avenue at Catherine Street/Raymond Street <i>Signalized</i>	WBL	F	1.06	104.4	#168.1	F	1.13	122.4	#180.0
	WBT/R	F	1.01	69.0	#120.8	F	1.09	86.7	#134.1
	NBL	E	0.98	54.6	#142.4	E	0.92	57.8	#95.4
	NBT	A	0.55	12.9	85.5	A	0.42	11.5	55.4
	SBT/R	D	0.82	63.0	#85.8	E	0.92	41.8	#140.8
	Overall	F	1.06	52.3	-	F	1.02	59.9	-
Bronson Avenue at Arlington Avenue <i>Signalized</i>	EB	A	0.22	23.9	12.3	A	0.31	17.4	14.2
	WB	A	0.15	28.6	9.4	A	0.08	10.1	4.0
	NB	A	0.60	5.0	m48.3	A	0.48	3.0	m32.5
	SB	A	0.24	3.4	23.3	A	0.41	2.1	17.1
	Overall	A	0.56	5.2	-	A	0.45	3.1	-

Intersection	Lane	AM Peak Hour				PM Peak Hour			
		LOS	V/C	Delay	Q (95 th)	LOS	V/C	Delay	Q (95 th)
Bronson Avenue at Gladstone Avenue Signalized	EBL	A	0.15	24.5	15.3	A	0.13	17.9	13.2
	EBT/R	C	0.73	38.0	93.3	A	0.57	24.8	86.0
	WBL	A	0.49	36.3	29.5	A	0.51	28.0	41.2
	WBT/R	A	0.36	27.0	44.9	A	0.36	20.5	52.2
	NBL	A	0.32	14.3	25.4	C	0.71	39.3	#46.2
	NBT/R	C	0.78	21.1	126.3	C	0.73	16.2	34.8
	SBL	A	0.14	14.7	4.9	A	0.41	30.9	19.4
	SBT/R	A	0.27	12.0	31.7	B	0.66	24.9	94.5
Overall	C	0.76	22.5	-	B	0.65	22.2	-	
Booth Street at Gladstone Avenue Signalized	EBL	A	0.09	13.5	6.6	A	0.16	14.7	9.7
	EBT/R	B	0.69	22.7	#64.4	A	0.47	16.9	57.6
	WBL	A	0.19	15.6	10.0	A	0.43	29.4	42.3
	WBT/R	A	0.48	17.2	41.3	B	0.66	31.5	114.6
	NBL	A	0.12	9.9	m6.7	A	0.42	24.5	26.5
	NBT/R	B	0.64	13.3	37.1	C	0.74	29.5	#95.4
	SBL	A	0.15	12.5	8.3	A	0.26	21.6	14.2
	SBT/R	A	0.23	11.2	20.6	A	0.59	24.4	72.8
Overall	B	0.65	16.3	-	B	0.70	26.1	-	
Arthur Street / Arthur Lane at Gladstone Avenue Signalized	EB	A	0.37	7.8	53.5	A	0.43	4.4	m25.8
	WB	A	0.27	6.8	36.6	A	0.44	7.9	62.2
	SB	A	0.10	5.0	4.2	A	0.25	12.1	11.9
	Overall	A	0.34	7.3	-	A	0.40	6.6	-
Booth Street at Raymond Street Signalized	WBL/T	B	0.69	25.4	#63.8	F	1.18	127.5	#145.4
	WBR	A	0.22	4.6	8.9	A	0.39	5.5	13.8
	NBL	A	0.09	8.9	6.6	A	0.12	8.5	5.9
	NBT	A	0.49	12.9	49.4	A	0.38	9.9	40.5
	SBT/R	A	0.32	15.0	m27.1	B	0.65	14.2	81.1
Overall	A	0.57	16.2	-	D	0.82	47.6	-	

Notes: Saturation flow rate of 1800 veh/h/lane
PHF = 0.90

m = metered queue
= queue exceeds storage or mid-block length

Capacity issues are noted on several specific movements throughout the study area and generally at the intersection of Bronson Avenue at Catherine Street/Raymond Street. During the AM peak hour at this intersection, the westbound left and westbound through movements are shown to be over capacity with high delays and extended queues, the northbound left movement is shown to be approaching capacity with extended queues, extended queues are noted on the southbound through movement, and the overall intersection is over capacity. During the PM peak hour, the same issues are present, with the southbound through movement approaching capacity as well.

At the intersection of Booth Street and Gladstone Avenue, the eastbound through movement exhibits extended queues during the AM peak hour, and the northbound through/right movement exhibits extended queues during the PM peak hour.

Additionally, within the study area, at the intersection of Bronson Avenue and Gladstone Avenue, the northbound left movement exhibits extended queuing during the PM peak hour, and at the intersection of Booth Street and Raymond Street, the westbound through movement exhibits extended queuing during the AM peak hour and is over capacity with high delays and extended queues during the PM peak hour.

The City may consider signal timing adjustments at the Bronson Avenue at Catherine Street/Raymond Street intersection to shift green time from movements with residual capacity to the over capacity movements. While signal timing adjustments could be made to improve the Booth Street at Raymond Street intersection, it is not recommended to improve the westbound approach as it may increase cut through traffic adjacent to the highway and surrounding community.

2.2.8 Collision Analysis

Collision data have been acquired from the City of Ottawa open data website (data.ottawa.ca) for five years prior to the commencement of this TIA for the surrounding study area road network. Table 3 summarizes the collisions types and conditions in the study area, Figure 10 illustrates the intersections and segments analyzed, and Table 4 summarizes the total collisions for each of these locations. Collision data are included in Appendix D.

Table 3: Study Area Collision Summary, 2015-2019

		Number	%
Total Collisions		84	100%
Classification	Fatality	0	0%
	Non-Fatal Injury	14	17%
	Property Damage Only	70	83%
Initial Impact Type	Angled	32	38%
	Rear end	13	15%
	Sideswipe	7	8%
	Turning Movement	9	11%
	SMV Unattended	17	20%
	SMV Other	4	5%
	Other	2	2%
Road Surface Condition	Dry	58	69%
	Wet	17	20%
	Loose Snow	5	6%
	Slush	2	2%
	Ice	2	2%
Pedestrian Involved		3	4%
Cyclists Involved		5	6%

Figure 10: Study Area Collision Records – Representation of 2015-2019



Table 4: Summary of Collision Locations, 2015-2019

Intersections / Segments	Number	%
	84	100%
Bell Street @ Arlington Avenue	1	1%
Bell Street @ Gladstone Avenue	9	11%
Booth Street @ Arlington Avenue	1	1%
Booth Street @ Louisa Street	4	5%
Bronson Avenue @ Arlington Avenue	20	24%
Lebreton Street @ Gladstone Avenue	21	25%
Lebreton Street @ Louisa Street	1	1%
Lebreton Street @ Raymond Street	2	2%
Arlington Avenue Btwn Arthur Lane N & Cambridge Street N	2	2%
Arlington Avenue Btwn Bell Street N & Arthur Lane N	1	1%
Arlington Avenue Btwn Booth Street & Lebreton Street N	3	4%
Arlington Avenue Btwn Cambridge Street N & Bronson Avenue	2	2%
Bell Street N Btwn Gladstone Avenue & Louisa Street	5	6%
Booth Street Btwn Louisa Street & Arlington Avenue	2	2%
Gladstone Avenue Btwn Lebreton Street N & Bell Street N	3	4%
Lebreton Street N Btwn Gladstone Avenue & Louisa Street	2	2%
Lebreton Street N Btwn Louisa Street & Arlington Avenue	2	2%
Louisa Street Btwn Lebreton Street N & Bell Street N	2	2%
Raymond Street Btwn Lebreton Street N & Bell Street N	1	1%

Within the study area, the intersections of Bronson Avenue at Arlington Avenue and Lebreton Street at Gladstone Avenue was noted to have experienced higher collisions than other intersections. Table 5 and Table 6 summarize the collision types and conditions for the Bronson Avenue at Arlington Avenue and Lebreton Street at Gladstone Avenue intersections.

Table 5: Bronson Avenue at Arlington Avenue Collision Summary

Total Collisions		Number	%
		20	100%
Classification	Fatality	0	0%
	Non-Fatal Injury	3	15%
	Property Damage Only	17	85%
Initial Impact Type	Angle	5	25%
	Rear end	7	35%
	Sideswipe	2	10%
	Turning Movement	6	30%
Road Surface Condition	Dry	13	65%
	Wet	5	25%
	Loose Snow	1	5%
	Slush	1	5%
Pedestrian Involved		0	0%
Cyclists Involved		2	10%

The Bronson Avenue at Arlington Avenue intersection had a total of 20 collisions during the 2015-2019 time period, with 17 involving property damage only and the remaining three having non-fatal injuries. The three primary collision types were rear end (seven collisions), turning movements (six collisions) and angled (five collisions). The distribution of collisions does not identify a geometric concern and is likely due to congestion along Bronson Avenue. Weather conditions do not affect collisions at this location.

Table 6: Lebreton Street at Gladstone Avenue Collision Summary

Total Collisions		Number	%
		21	100%
Classification	Fatality	0	0%
	Non-Fatal Injury	4	19%
	Property Damage Only	17	81%
Initial Impact Type	Angled	20	95%
	Turning Movement	1	5%
Road Surface Condition	Dry	14	67%
	Wet	5	29%
	Loose Snow	1	5%
Pedestrian Involved		0	0%
Cyclists Involved		0	0%

The Lebreton Street at Gladstone Avenue intersection had a total of 21 collisions during the 2015-2019 time period, with 17 involving property damage only and the remaining four having non-fatal injuries. Angled collisions (20 collisions) comprise the majority of the collisions at the intersection. The angled collisions are a result of the north and southbound movements entering Gladstone Avenue, primarily to cross Gladstone Avenue as only three are from left-turning vehicles. The vertical curve to the west of the intersection may influence the collisions with eastbound vehicles (nine total). No geometric issues noted for westbound vehicles. The City may consider restricting the north and southbound through movements at this intersection, likely through signage to mitigate the angled collisions. Weather conditions do not affect collisions at this location.

2.3 Planned Conditions

2.3.1 Changes to the Area Transportation Network

The subject development is not within a CDP or design priority area.

Within the Transportation Master Plan (TMP), the Road Transit and Transit Priority (RTTP) Network's Affordable Network diagram shows a new station along the Trillium LRT line at Gladstone Avenue which is expected to be completed in 2021.

From the Planned Construction Projects portal, Gladstone Avenue is due to receive traffic safety improvements along the corridor to commence within four-to-seven years.

The Chamberlain Avenue, Catherine Street, and Isabella Street Functional Design Study, conducted in 2019, is currently planned for implementation after the build-out horizon, and notably includes pedestrian improvements at the Bronson Avenue at Catherine Street/Raymond Street intersection.

2.3.2 Other Study Area Developments

249-267 Rochester Street, 27-29 Balsam Street

The application includes the site plan for the construction of a three-storey 23-unit residential development with an internal private road. No TIA is available for the application.

3 Study Area and Time Periods

3.1 Study Area

The study area will include the intersections of:

- Bronson Avenue at:
 - Catherine Street/Raymond Street
 - Arlington Avenue
 - Gladstone Avenue
- Booth Street at:
 - Gladstone Avenue
 - Raymond Street
- Arthur Street/Arthur Lane at Gladstone Avenue

The boundary roads will be Bell Street, Louisa Street, and Arlington Avenue and no screenlines are present within proximity to the site.

3.2 Time Periods

As the proposed development is composed entirely of residential units the AM and PM peak hours will be examined.

3.3 Horizon Years

The anticipated build-out year is 2025. As a result, the full build-out plus five years horizon year is 2030.

4 Exemption Review

Table 7 summarizes the exemptions for this TIA.

Table 7: Exemption Review

Module	Element	Explanation	Exempt/Required
Design Review Component			
4.1 Development Design	4.1.2 Circulation and Access	Only required for site plans	Required
	4.1.3 New Street Networks	Only required for plans of subdivision	Exempt
4.2 Parking	4.2.1 Parking Supply	Only required for site plans	Required
	4.2.2 Spillover Parking	Only required for site plans where parking supply is 15% below unconstrained demand	Exempt
Network Impact Component			
4.5 Transportation Demand Management	All Elements	Not required for site plans expected to have fewer than 60 employees and/or students on location at any given time	Required
4.6 Neighbourhood Traffic Management	4.6.1 Adjacent Neighbourhoods	Only required when the development relies on local or collector streets for access and total volumes exceed ATM capacity thresholds	Required
4.8 Network Concept		Only required when proposed development generates more than 200 person-trips during the peak hour in excess of equivalent volume permitted by established zoning	Exempt

5 Development-Generated Travel Demand

5.1 Trip Generation and Mode Shares

This TIA has been prepared using the vehicle and person trip rates for the residential units using the TRANS Trip Generation Study Report (2009). Table 8 summarizes the person trip rates for the proposed land use.

Table 8: Trip Generation Person Trip Rates

Dwelling Type	Land Use Code	Peak Hour	Vehicle Trip Rate	Person Trip Rates
Mid-Rise Apartments	223 (TRANS)	AM	0.24	0.65
		PM	0.28	0.70

Using the above Person Trip rates, the total person trip generation has been estimates. Table 9 below illustrates the total person trip generation for the Mid-Rise Apartment dwelling type.

Table 9: Total Person Trip Generation

Land Use	Units / GFA	AM Peak Hour			PM Peak Hour		
		In	Out	Total	In	Out	Total
Mid-Rise Apartments	139	22	68	90	60	37	97

Using the most recent National Capital Region Origin-Destination survey (OD Survey), the existing mode shares for Ottawa Inner have been determined and compared to various modes share breakdowns identified by City Staff as potential interpretations of the data. As the site is approximately 900 metres walk from the planned Gladstone LRT station and not designated as a TOD zone, no adjustments are recommended to the existing area mode shares targets. Table 10 summarizes these modal shares.

Table 10: Mode Shares

Travel Mode	Ottawa Inner (average)	Ottawa Inner (AM from/within)	Ottawa Inner (PM to/within)
Auto Driver	40%	35%	35%
Auto Passenger	10%	10%	10%
Transit	25%	20%	20%
Cycling	5%	5%	5%
Walking	20%	30%	30%
Total	100%	100%	100%

Using the above mode share targets for the AM/PM shares and person trip rates the person trips by mode have been projected. Table 11 summarizes the trip generation by mode.

Table 11: Trip Generation by Mode

Travel Mode	Mode Share	AM Peak Hour			PM Peak Hour		
		In	Out	Total	In	Out	Total
Auto Driver	35%	8	24	32	21	13	34
Auto Passenger	10%	2	7	9	6	4	10
Transit	20%	4	14	18	12	7	19
Cycling	5%	1	3	5	3	2	5
Walking	30%	7	20	27	18	11	29
Total	100%	22	68	90	60	37	97

As shown above, 32 new AM and 34 new PM peak hour two-way vehicle trips are projected as a result of the proposed development.

5.2 Trip Distribution

To understand the travel patterns of the subject development, the OD Survey has been reviewed to determine the existing district travel and these patterns were applied based on the build-out of Ottawa Inner. Table 12 below summarizes the distributions.


Table 12: OD Survey Distribution – Ottawa Inner

To/From	Residential % of Trips	Inbound Via	Outbound Via
North	30%	10% Booth St, 20% Bronson Ave	10% Booth St, 20% Bronson Ave
South	20%	10% Booth St, 10% Bronson Ave	5% Raymond, 5% Booth St, 10% Bronson Ave
East	40%	10% Gladstone Ave, 30% Catherine St	10% Gladstone Ave, 30% Bronson Ave (S)
West	10%	Booth St (S)	Raymond
Total	100%	-	-

5.3 Trip Assignment

Using the distribution outlined above, turning movement splits, and access to major transportation infrastructure, the trips generated by the site have been assigned to the study area road network. Figure 11 illustrates the new site generated volumes.

Figure 11: New Site Generation Auto Volumes



6 Background Network Travel Demands

6.1 Transportation Network Plans

The transportation network plans were discussed in Section 2.3. The Gladstone Avenue safety improvements are assumed not to change the lane and intersection arrangements.

6.2 Background Growth

A review of the background projections from the City’s TRANS Regional Model for the 2011 and 2031 horizons was completed to determine the background growth for each of the study area roadways. Table 13 summarizes the results of the model, and the projections are provided in Appendix E.

Table 13: TRANS Regional Model Projections – Study Area Growth Rates

Street	Direction Growth % from 2011 to 2031	
	Eastbound	Westbound
Gladstone Ave	2.95%	1.70%
Catherine St	-	1.04%
	Northbound	Southbound
Booth St	0.97%	0.86%
Bronson Ave	0.51%	0.84%

Within the study area, growth within the range of 0.5% to 3.0% is forecasted by the TRANS model on all links. The mainline arterial and major collector volumes throughout the study area, and the northbound and westbound left-turn volumes at the intersection of Bronson Avenue at Catherine Street/Raymond Street will be grown at the

annual rates identified in Table 13, rounded the nearest 0.25%. Growth will be applied in the appropriate directions during the AM peak hour and reversed during the PM peak hour.

6.3 Other Developments

As outlined in Section 6.2, as there are no active background development applications with TIAs, none will be explicitly considered within the future background volumes.

While the existing land use for the portion of the site that is to be redeveloped is estimated to generate 12-to-18 two-way people trips during the PM peak hour, these volumes will not be subtracted from the study area road network.

7 Demand Rationalization

7.1 2025 Future Background Operations

Figure 12 illustrates the 2025 background volumes and Table 14 summarizes the 2024 background intersection operations. The level of service for signalized intersections is based on HCM 2010 v/c calculations for individual lane movements and HCM 2000 v/c calculations for the overall intersection. The synchro worksheets for the 2024 future background horizon are provided in Appendix F.

Figure 12: 2025 Future Background Volumes




Table 14: 2025 Future Background Intersection Operations

Intersection	Lane	AM Peak Hour				PM Peak Hour			
		LOS	V/C	Delay	Q (95 th)	LOS	V/C	Delay	Q (95 th)
Bronson Avenue at Catherine Street/Raymond Street <i>Signalized</i>	WBL	E	1.00	90.9	#156.7	F	1.02	88.2	#156.3
	WBT/R	E	0.95	54.4	#108.0	E	0.98	56.2	#113.2
	NBL	D	0.90	36.8	#111.4	D	0.86	44.5	#79.6
	NBT	A	0.52	12.3	77.2	A	0.40	11.2	51.8
	SBT/R	C	0.77	51.8	77.9	D	0.83	26.0	#128.7
	Overall	E	0.97	42.2	-	-	E	0.94	40.4
Bronson Avenue at Arlington Avenue <i>Signalized</i>	EB	A	0.20	24.3	11.7	A	0.28	17.7	13.3
	WB	A	0.13	29.0	9.0	A	0.07	9.4	3.7
	NB	A	0.56	4.4	m44.5	A	0.45	2.9	m29.4
	SB	A	0.23	3.3	22.0	A	0.38	2.0	16.5
	Overall	A	0.52	4.7	-	-	A	0.42	3.0
Bronson Avenue at Gladstone Avenue <i>Signalized</i>	EBL	A	0.14	24.2	14.2	A	0.12	17.9	12.3
	EBT/R	C	0.75	39.4	#105.5	A	0.56	24.7	85.3
	WBL	A	0.47	36.3	27.4	A	0.46	26.1	36.3
	WBT/R	A	0.36	27.0	45.3	A	0.39	21.0	57.4
	NBL	A	0.28	13.6	22.4	A	0.56	25.1	#34.0
	NBT/R	C	0.73	19.2	111.2	B	0.68	15.6	33.5
	SBL	A	0.10	12.9	4.4	A	0.33	26.0	16.2
	SBT/R	A	0.26	11.8	29.8	B	0.61	23.8	85.7
	Overall	C	0.74	22.0	-	-	B	0.62	21.0
Booth Street at Gladstone Avenue <i>Signalized</i>	EBL	A	0.08	13.4	6.1	A	0.17	15.1	9.2
	EBT/R	C	0.73	25.0	#78.3	A	0.47	16.9	57.6
	WBL	A	0.19	15.7	9.4	A	0.39	28.9	39.0
	WBT/R	A	0.48	17.3	41.6	C	0.72	34.0	124.6
	NBL	A	0.11	9.6	m6.0	A	0.36	22.7	23.4
	NBT/R	A	0.60	12.6	33.8	B	0.70	27.4	86.8
	SBL	A	0.12	12.1	7.5	A	0.21	20.1	12.7
	SBT/R	A	0.22	11.1	19.6	A	0.57	23.8	69.6
Overall	B	0.66	17.1	-	-	C	0.71	26.2	-
Arthur Street / Arthur Lane at Gladstone Avenue <i>Signalized</i>	EB	A	0.40	8.0	60.0	A	0.43	5.8	30.5
	WB	A	0.27	6.7	36.8	A	0.49	8.5	72.5
	SB	A	0.09	4.5	3.7	A	0.23	12.3	11.3
	Overall	A	0.37	7.4	-	-	A	0.43	7.5
Booth Street at Raymond Street <i>Signalized</i>	WBL/T	B	0.62	22.7	54.3	F	1.06	86.0	#127.5
	WBR	A	0.20	4.7	8.4	A	0.36	5.5	13.1
	NBL	A	0.08	8.7	6.1	A	0.10	8.2	5.4
	NBT	A	0.48	12.6	47.1	A	0.36	9.7	38.0
	SBT/R	A	0.30	14.3	m25.1	B	0.62	13.5	75.4
	Overall	A	0.53	15.1	-	-	C	0.77	33.7

Notes: Saturation flow rate of 1800 veh/h/lane
PHF = 1.00

m = metered queue
= queue exceeds storage or mid-block length

During both the AM and PM peak hours, the study area intersections at the 2025 future background horizon operate similarly to existing conditions with operational improvements noted generally with the peak hour factor of 1.00 for forecasted conditions.

The eastbound through/right movement at the intersection of Bronson Avenue and Gladstone Avenue may exhibit extended queuing during the AM peak hour at this horizon.

Signal timing optimization applied throughout the study area at both peak hours may reduce all movements v/c to 1.00 and below.

7.2 2030 Future Background Operations

Figure 13 illustrates the 2030 background volumes and Table 15 summarizes the 2030 background intersection operations. The level of service for signalized intersections is based on HCM 2010 v/c calculations for individual lane movements and HCM 2000 v/c calculations for the overall intersection. The synchro worksheets for the 2030 future background horizon are provided in Appendix G.

Figure 13: 2030 Future Background Volumes




Table 15: 2030 Future Background Intersection Operations

Intersection	Lane	AM Peak Hour				PM Peak Hour			
		LOS	V/C	Delay	Q (95 th)	LOS	V/C	Delay	Q (95 th)
Bronson Avenue at Catherine Street/Raymond Street <i>Signalized</i>	WBL	F	1.04	99.8	#164.0	F	1.02	88.2	#156.3
	WBT/R	E	0.99	62.0	#115.8	E	0.98	56.2	#113.2
	NBL	E	0.93	42.2	#122.5	D	0.90	51.7	#88.2
	NBT	A	0.53	12.5	80.0	A	0.42	11.4	54.2
	SBT/R	C	0.79	56.6	80.6	D	0.85	29.0	#131.6
	Overall	F	1.01	47.1	-	E	0.96	41.6	-
Bronson Avenue at Arlington Avenue <i>Signalized</i>	EB	A	0.20	24.3	11.7	A	0.28	17.7	13.3
	WB	A	0.13	29.0	9.0	A	0.07	9.4	3.7
	NB	A	0.57	4.4	m44.6	A	0.46	2.9	m30.0
	SB	A	0.23	3.4	22.9	A	0.39	1.9	15.2
	Overall	A	0.54	4.7	-	A	0.43	2.9	-

Intersection	Lane	AM Peak Hour				PM Peak Hour			
		LOS	V/C	Delay	Q (95 th)	LOS	V/C	Delay	Q (95 th)
Bronson Avenue at Gladstone Avenue <i>Signalized</i>	EBL	A	0.15	24.4	14.3	A	0.13	18.2	12.4
	EBT/R	D	0.84	46.0	#125.4	A	0.60	25.7	93.0
	WBL	A	0.58	45.8	#33.2	A	0.49	27.8	37.8
	WBT/R	A	0.39	27.6	48.8	A	0.45	22.1	67.1
	NBL	A	0.28	13.7	22.6	A	0.58	26.9	#37.4
	NBT/R	C	0.74	19.6	115.1	B	0.70	16.0	34.2
	SBL	A	0.11	13.2	4.5	A	0.35	27.3	16.7
	SBT/R	A	0.27	11.9	31.0	B	0.63	24.1	88.4
Overall	C	0.78	23.9	-	B	0.65	21.7	-	
Booth Street at Gladstone Avenue <i>Signalized</i>	EBL	A	0.08	13.5	6.2	A	0.22	17.3	10.0
	EBT/R	D	0.83	31.6	#95.5	A	0.51	17.6	63.5
	WBL	A	0.23	17.4	9.9	A	0.41	29.5	39.9
	WBT/R	A	0.51	18.1	45.5	D	0.83	39.2	#150.1
	NBL	A	0.11	10.0	m6.0	A	0.37	23.0	23.6
	NBT/R	B	0.63	13.3	36.8	C	0.72	28.3	90.5
	SBL	A	0.13	12.3	7.6	A	0.22	20.5	12.8
	SBT/R	A	0.22	11.2	20.2	A	0.60	24.5	73.3
Overall	C	0.72	19.8	-	C	0.78	28.4	-	
Arthur Street / Arthur Lane at Gladstone Avenue <i>Signalized</i>	EB	A	0.46	9.0	74.0	A	0.47	6.0	31.6
	WB	A	0.30	6.9	40.8	A	0.57	9.8	92.5
	SB	A	0.09	4.5	3.7	A	0.23	12.3	11.3
	Overall	A	0.42	8.0	-	A	0.50	8.3	-
Booth Street at Raymond Street <i>Signalized</i>	WBL/T	B	0.62	22.7	54.3	F	1.06	86.0	#127.5
	WBR	A	0.20	4.7	8.4	A	0.36	5.5	13.1
	NBL	A	0.08	8.7	6.1	A	0.11	8.3	5.4
	NBT	A	0.50	13.0	50.2	A	0.37	9.9	39.6
	SBT/R	A	0.31	14.6	m25.7	B	0.64	14.1	80.4
Overall	A	0.55	15.3	-	C	0.78	33.5	-	

Notes: Saturation flow rate of 1800 veh/h/lane
PHF = 1.00

m = metered queue
= queue exceeds storage or mid-block length

During both the AM and PM peak hours, the study area intersections at the 2030 future background horizon operate similarly to the 2025 background and existing conditions.

In addition to the queueing noted at the 2025 horizon, extended queueing may be exhibited at this horizon on the westbound left movement at the intersection of Bronson Avenue and Gladstone Avenue during the AM peak hour, and on the westbound through/right movement at the intersection of Booth Street and Gladstone Avenue during the PM peak hour.

As in the existing conditions, the westbound left movement and the overall intersection are over theoretical capacity during the AM peak hour at the intersection of Bronson Avenue at Catherine Street/Raymond Street.

As in the 2025 background conditions, signal timing optimization may reduce all movements v/c to 1.00 and below.

7.3 Demand Rationalization Conclusions

While a few capacity constraints have been noted during both peak hours at the intersection of Bronson Avenue and Catherine Street/Raymond Street, and during the PM peak hour at the intersection of Booth Street and Raymond Street, signal optimization is a potential option to mitigate these constraints present at all horizons.

Given the unmodified district mode shares were applied, no further rationalization for the adjusted demand based upon the subject development is required.

8 Development Design

8.1 Design for Sustainable Modes

The proposed development is a residential building. Parking is proposed across two underground levels and bike parking is proposed in a secure room adjacent to the Arlington Avenue access, in the underground parking facilities via the Arlington Avenue access, and in open racks adjacent to the loading bay and adjacent to the rear lane. Hard surface connections are provided between all building entrances and the surrounding pedestrian facilities. All local bus routes referenced in Section 2.2.5 are within 400 metres walk of the building entrances except for the eastbound route #55, and the future Gladstone LRT station is within 900 metres walk of the main building entrance.

8.2 Circulation and Access

The site access is proposed via a full-movements access onto Arlington Avenue accessing the underground parking, and via a full-movements access onto Louisa Street accessing a loading bay and garbage storage.

Garbage collection is assumed to take place on Louisa Street, and as property fronts three public roadways, emergency services are assumed to be able to access the site via these rights of way.

9 Parking

9.1 Parking Supply

The site proposes the addition of 80 underground parking spaces across two parking levels and the retention of eight surface vehicle parking spaces in the rear lane for a total of 88 parking spaces.

The required vehicle parking for the entire site includes 64 residential tenants spaces, 13 residential visitor spaces, and 13 spaces for the existing land use. The shared use parking provisions reduce the existing land use (excluding 1.4 spaces for the instructional facility) and residential visitor parking to 21 total spots. As a result, the site requires a total of 86 required parking spaces. Therefore, proposed redevelopment exceeds the minimum vehicle parking requirements.

Bicycle parking is proposed to include 79 spaces within the secure storage room on the first floor, in storage rooms within the two parking levels, and the surface racks located near entrance locations.

The required bicycle parking for the proposed residential land use per the zoning by-law is 70 spaces and existing land use parking requirements are approximately four spaces for a total of 74 bicycle parking spaces. Therefore, the proposed redevelopment exceeds the minimum bicycle parking requirements.

The site plan provides a full breakdown of the parking requirements and numbers.

10 Boundary Street Design

Table 16 summarizes the MMLOS analysis for the boundary streets of Bell Street, Louisa Street, and Arlington Avenue. The existing and future conditions for both streets will be the same and are considered in one row. The boundary street analysis is based on the policy area of “Within 300m of a school” as each is within this distance of St. Anthony School. The MMLOS worksheets has been provided in Appendix H.

Table 16: Boundary Street MMLOS Analysis

Segment	Pedestrian LOS		Bicycle LOS		Transit LOS		Truck LOS	
	PLOS	Target	BLOS	Target	TLOS	Target	TrLOS	Target
Bell Street	C	A	B	D	-	-	-	-
Louisa Street	E	A	B	D	-	-	-	-
Arlington Avenue	E	A	B	D	-	-	-	-

The boundary streets do not meet the pedestrian LOS targets. The existing sidewalks are 1.5-metres-wide, and to meet targets, sidewalks of 2.0 metres in width or more with boulevards of 0.5 metres in width or more would be required.

Given the local road context with low operating speeds and on-street parking, the boundary road pedestrian facilities are not recommended to be reconstructed. It is noted that the right-of-way may also reduce the ability to provide pedestrian facility upgrades, should the City explore those further in the future.

Crowding PLOS is not considered in the PLOS due to the excessively high-volume threshold. At the lowest threshold given, of 250 pedestrians per hour, the minimum effective sidewalk width required to achieve LOS A would be 3.0 metres, whereby nearly any sidewalk considered for installation in the City would not be able to meet this target.

11 Access Intersections Design

11.1 Location and Design of Access

The site plan uses the existing access locations on Arlington Avenue and Louisa Street. The Arlington Avenue access is a 6.0-metre full-movement access to the underground parking and the Louisa Avenue access will be reduced to a 4.5-metre full-movement access for the loading area.

11.2 Intersection Control

All accesses are assumed as being stop-controlled on the minor approaches with Louisa Street and Arlington Avenue operating under free-flow conditions.

11.3 Access Intersection Design

Due to the low site volumes at the site access and lack of pre-pandemic volumes for the local road network, the site access was not assessed for operational performance.

11.3.1 Access Intersection MMLOS

As the access intersections are unsignalized, no access intersection MMLOS analysis has been performed.

11.3.2 Recommended Design Elements

No design elements for the access intersections are proposed outside of the typical application of the provisions from the private approach by-law (by-law no. 2003-447).

12 Transportation Demand Management

12.1 Context for TDM

The mode shares used within the TIA represent the unmodified district mode shares. Overall, the modal shares are likely to be achieved and supporting TDM measures should be provided.

The subject site is not within a design priority area.

One hundred nine studio or one-bedroom units and 30 two-bedroom units are included in the site plan for a total bedroom count of 169. No age restrictions are noted.

12.2 Need and Opportunity

The subject site has been assumed to rely predominantly on auto travel followed by walking and transit. As the development is anticipated to generate 90 AM and 97 PM peak hour two-way person trips, risks associated with failure to achieve the area mode share targets are considered to be low for other network users.

12.3 TDM Program

The “suite of post occupancy TDM measures” has been summarized in the TDM checklists for the residential land uses. The checklist is provided in Appendix I. The key TDM measures recommended include:

- Display local area information with walking/cycling maps and relevant transit schedules and route maps
- Provide a multimodal travel option information package to new residents
- Inclusion of a 1-year Presto card for first time new townhome purchase and apartment rental, with a set time frame for this offer (e.g. 6-months) from the initial opening of the site
- Unbundle parking cost from purchase or rental costs

13 Neighbourhood Traffic Management

The proposed development will connect to the arterial road network through the local roads of Arlington Avenue, Bell Street, and Raymond Street, and the major collector roads of Gladstone Avenue and Booth Street. For the purposes of the NTM analysis, Booth Street, Gladstone Avenue, Raymond Street, and Bronson Avenue are considered the external study area roadways and Arlington Avenue, and Bell Street are considered the internal study area roadways.

As existing volumes are not available for Arlington Avenue west of the Bronson Avenue intersection, for Louisa Street, or for Bell Street, the projected site-generated proportion of total local road thresholds will be assessed for the internal study area roadways. The TIA guidelines prescribe a 120 vehicle per peak hour threshold for local road classification, which are considered two-way volumes per City guidance. The results of this analysis are summarized in Table 17.

Table 17: NTM Review of Internal Study Area Roadways – Relative Threshold Proportions

Segment	AM Peak				PM Peak			
	EB	WB	Two-Way	Threshold %	EB	WB	Two-Way	Threshold %
Arlington Ave (east of access)	17	5	22	18%	9	14	23	19%
Arlington Ave (west of access)	3	7	10	8%	7	4	11	9%
Segment	AM Peak				PM Peak			
	NB	SB	Two-Way	Threshold %	NB	SB	Two-Way	Threshold %
Bell St	0	6	6	5%	0	3	3	3%

Volumes along Arlington Avenue east of the site access represent the most concentrated impacts of site-generated traffic comprising up to 19% of the local road classification thresholds. In the 2030 future total conditions, two-way volumes along Arlington Avenue on the west leg of its intersection with Bronson Avenue are forecasted to be 66 AM and 103 PM vehicles, or 55% of the thresholds during the AM peak and 86% during the

PM peak. Therefore, the site traffic along Arlington Avenue will not increase the local traffic beyond the TIA thresholds for a local road.

The external study area roadways of Gladstone Avenue and Booth Street are subject to the major collector thresholds, and Raymond Street to the local road thresholds. The TIA guidelines prescribe a 600 vehicle per peak hour threshold for major collector road classification, and a 120 vehicle per peak hour threshold for local road classification, which are considered two-way volumes per City guidance. The results of this analysis are summarized in Table 18.

Table 18: NTM Review of External Study Area Roadways

Segment	AM Peak			PM Peak		
	EB	WB	Two-Way	EB	WB	Two-Way
Gladstone Ave (east of Booth St)	415	303	718	408	609	1017
Gladstone Ave (west of Bronson Ave)	383	317	700	409	400	809
Raymond St (east of Booth St)	-	448	448	-	702	702
Segment	AM Peak			PM Peak		
	NB	SB	Two-Way	NB	SB	Two-Way
Booth St (south of Gladstone Ave)	458	243	701	526	507	1033
Booth St (north of Raymond St)	486	237	723	526	558	1084

All external study area roadways are over the thresholds for their classifications prescribed by the TIA guidelines. It is additionally noteworthy that one-way volumes on Raymond Street, a local road, are above even the major collector road thresholds. As the site-generated volumes are less than 1% of the existing two-way volumes on all study area roadways during both peak hours, and that no resultant functional change in the roadway classification is possible, no further NTM analysis is considered to be required.

14 Transit

14.1 Route Capacity

In Section 5.1 the trip generation by mode was estimated, including an estimate of the number of transit trips that will be generated by the proposed development. Table 19 summarizes the transit trip generation.

Table 19: Trip Generation by Transit Mode

Travel Mode	Mode Share	AM Peak Period			PM Peak Period		
		In	Out	Total	In	Out	Total
Transit	20%	4	14	18	12	7	19

The proposed development is anticipated to generate an additional 18 AM peak hour transit trips and 19 PM peak hour transit trips. Of these trips, 14 outbound AM trips and 12 inbound PM trips are anticipated. Given the number of area routes the increase in ridership anticipated is an averaged one-to-two riders per bus per route/direction.

14.2 Transit Priority

No transit priority is required explicitly for this study.

15 Network Intersection Design

15.1 Network Intersection Control

No change to the existing signalized control is recommended for the network intersections.

15.2 Network Intersection Design

15.2.1 2025 Future Total Network Intersection Operations

The 2025 future total intersection volumes are illustrated in Figure 14 and the 2025 future total network intersection operations are summarized below in Table 20. The level of service for signalized intersections is based on HCM 2010 v/c calculations for individual lane movements and HCM 2000 v/c calculations for the overall intersection, and HCM average delay for unsignalized intersections. The synchro worksheets have been provided in Appendix J.

Figure 14: 2025 Future Total Volumes




Table 20: 2025 Future Total Network Intersection Operations

Intersection	Lane	AM Peak Hour				PM Peak Hour			
		LOS	V/C	Delay	Q (95 th)	LOS	V/C	Delay	Q (95 th)
Bronson Avenue at Catherine Street/Raymond Street <i>Signalized</i>	WBL	E	1.00	90.9	#156.7	F	1.02	88.2	#156.3
	WBT/R	E	0.95	55.0	#108.7	E	0.98	57.7	#114.4
	NBL	D	0.90	38.0	#112.8	D	0.87	46.0	#81.5
	NBT	A	0.52	12.3	77.2	A	0.40	11.2	51.8
	SBT/R	C	0.78	53.4	79.7	D	0.84	27.0	#129.7
Overall		E	0.98	42.9	-	E	0.95	41.3	-

Intersection	Lane	AM Peak Hour				PM Peak Hour			
		LOS	V/C	Delay	Q (95 th)	LOS	V/C	Delay	Q (95 th)
Bronson Avenue at Arlington Avenue <i>Signalized</i>	EB	A	0.23	21.7	13.1	A	0.31	17.6	14.0
	WB	A	0.12	28.1	9.0	A	0.07	9.4	3.7
	NB	A	0.57	4.9	m44.5	A	0.45	2.9	m29.4
	SB	A	0.23	3.7	22.0	A	0.39	2.0	16.3
	Overall	A	0.52	5.2	-	A	0.42	3.0	-
Bronson Avenue at Gladstone Avenue <i>Signalized</i>	EBL	A	0.15	24.5	15.2	A	0.13	18.0	12.5
	EBT/R	C	0.76	39.9	#106.6	A	0.56	24.8	85.6
	WBL	A	0.49	37.1	27.8	A	0.47	26.5	37.0
	WBT/R	A	0.36	27.0	45.3	A	0.39	21.0	57.4
	NBL	A	0.28	13.6	22.5	A	0.56	25.4	#36.5
	NBT/R	C	0.73	19.3	111.5	B	0.69	15.6	33.5
	SBL	A	0.10	12.9	4.4	A	0.33	26.1	16.3
	SBT/R	A	0.26	11.8	30.0	B	0.62	23.9	86.4
Overall	C	0.74	22.1	-	B	0.62	21.1	-	
Booth Street at Gladstone Avenue <i>Signalized</i>	EBL	A	0.08	13.4	6.1	A	0.17	15.1	9.2
	EBT/R	C	0.74	25.2	#78.6	A	0.47	16.9	57.7
	WBL	A	0.19	15.8	9.5	A	0.39	29.1	39.2
	WBT/R	A	0.48	17.3	41.6	C	0.72	34.0	124.5
	NBL	A	0.11	9.6	m6.0	A	0.36	22.7	23.4
	NBT/R	B	0.61	12.7	34.1	B	0.70	27.6	87.2
	SBL	A	0.13	12.2	7.7	A	0.22	20.4	13.0
	SBT/R	A	0.22	11.1	19.6	A	0.57	23.8	69.6
Overall	B	0.66	17.1	-	C	0.71	26.3	-	
Arthur Street / Arthur Lane at Gladstone Avenue <i>Signalized</i>	EB	A	0.40	8.1	61.1	A	0.43	5.9	31.0
	WB	A	0.27	6.7	36.9	A	0.49	8.5	72.5
	SB	A	0.09	4.5	3.7	A	0.23	12.4	11.3
	Overall	A	0.37	7.4	-	A	0.43	7.6	-
Booth Street at Raymond Street <i>Signalized</i>	WBL/T	B	0.62	22.9	54.6	F	1.06	86.7	#127.8
	WBR	A	0.20	4.7	8.4	A	0.36	5.5	13.1
	NBL	A	0.08	8.7	6.1	A	0.10	8.2	5.4
	NBT	A	0.48	12.6	47.5	A	0.36	9.8	38.5
	SBT/R	A	0.30	14.3	m25.2	B	0.62	13.5	75.8
Overall	A	0.54	15.2	-	C	0.77	33.8	-	

Notes: Saturation flow rate of 1800 veh/h/lane
PHF = 1.00

m = metered queue
= queue exceeds storage or mid-block length

The network intersections at the 2025 future total horizon operate similarly to the 2025 future background conditions. No new operational issues are noted.

15.2.2 2030 Future Total Network Intersection Operations

The 2030 future total intersection volumes are illustrated in Figure 15 and the 2030 future total network intersection operations are summarized below in Table 21. The level of service for signalized intersections is based on HCM 2010 v/c calculations for individual lane movements and HCM 2000 v/c calculations for the overall intersection, and HCM average delay for unsignalized intersections. The synchro worksheets have been provided in Appendix K.

Figure 15: 2030 Future Total Volumes




Table 21: 2030 Future Total Network Intersection Operations

Intersection	Lane	AM Peak Hour				PM Peak Hour			
		LOS	V/C	Delay	Q (95 th)	LOS	V/C	Delay	Q (95 th)
Bronson Avenue at Catherine Street/Raymond Street <i>Signalized</i>	WBL	F	1.04	99.8	#164.0	F	1.02	88.2	#156.3
	WBT/R	E	0.99	62.9	#116.6	E	0.98	57.7	#114.4
	NBL	E	0.94	43.7	#124.3	D	0.90	53.0	#89.5
	NBT	A	0.53	12.5	80.0	A	0.42	11.4	54.2
	SBT/R	D	0.81	58.0	#83.0	D	0.86	30.2	#132.5
	Overall	F	1.02	47.9	-	E	0.97	42.5	-
Bronson Avenue at Arlington Avenue <i>Signalized</i>	EB	A	0.23	21.7	13.1	A	0.31	17.6	14.0
	WB	A	0.12	28.1	9.0	A	0.07	9.4	3.7
	NB	A	0.58	4.9	m44.6	A	0.47	2.9	m30.0
	SB	A	0.24	3.8	23.0	A	0.40	1.9	15.0
	Overall	A	0.54	5.2	-	A	0.44	2.9	-
Bronson Avenue at Gladstone Avenue <i>Signalized</i>	EBL	A	0.16	24.6	15.2	A	0.14	18.3	12.7
	EBT/R	D	0.85	46.8	#126.9	A	0.60	25.8	93.2
	WBL	A	0.60	47.3	#34.0	A	0.51	28.3	38.5
	WBT/R	A	0.39	27.6	48.8	A	0.45	22.1	67.1
	NBL	A	0.28	13.7	22.6	A	0.59	27.7	#37.9
	NBT/R	C	0.74	19.7	115.3	C	0.71	16.1	34.6
	SBL	A	0.11	13.2	4.5	A	0.35	27.5	16.8
	SBT/R	A	0.27	11.9	31.1	B	0.63	24.2	88.8
Overall	C	0.78	24.1	-	B	0.65	21.8	-	

Intersection	Lane	AM Peak Hour				PM Peak Hour			
		LOS	V/C	Delay	Q (95 th)	LOS	V/C	Delay	Q (95 th)
Booth Street at Gladstone Avenue Signalized	EBL	A	0.08	13.5	6.2	A	0.22	17.3	10.0
	EBT/R	D	0.83	31.8	#95.7	A	0.51	17.7	63.5
	WBL	A	0.23	17.4	9.9	A	0.42	29.7	39.9
	WBT/R	A	0.52	18.1	45.5	D	0.83	39.2	#150.0
	NBL	A	0.11	10.0	m6.0	A	0.37	23.0	23.6
	NBT/R	B	0.63	13.4	37.2	C	0.72	28.5	90.9
	SBL	A	0.14	12.3	7.7	A	0.23	20.8	13.2
	SBT/R	A	0.22	11.2	20.2	A	0.60	24.5	73.3
Overall	C	0.72	19.8	-	-	C	0.78	28.5	-
Arthur Street / Arthur Lane at Gladstone Avenue Signalized	EB	A	0.46	9.1	#75.3	A	0.47	6.1	32.0
	WB	A	0.30	6.9	40.8	A	0.57	9.8	92.5
	SB	A	0.09	4.5	3.7	A	0.23	12.4	11.3
	Overall	A	0.43	8.1	-	A	0.50	8.4	-
Booth Street at Raymond Street Signalized	WBL/T	B	0.62	22.9	54.6	F	1.06	86.7	#127.8
	WBR	A	0.20	4.7	8.4	A	0.36	5.5	13.1
	NBL	A	0.08	8.7	6.1	A	0.11	8.4	5.4
	NBT	A	0.50	13.0	50.6	A	0.37	9.9	40.2
	SBT/R	A	0.31	14.6	m0.0	B	0.65	14.2	81.2
	Overall	A	0.55	15.3	-	-	C	0.79	33.6

Notes: Saturation flow rate of 1800 veh/h/lane
PHF = 1.00

m = metered queue
= queue exceeds storage or mid-block length

The network intersections at the 2030 future total horizon operate similarly to the 2030 future background conditions.

As in the existing conditions, during the AM peak hour at this horizon at the intersection of Bronson Avenue at Catherine Street/Raymond Street, the southbound through/right movement may exhibit extended queues.

The intersection of Arthur Street/Arthur Lane at Gladstone Avenue may also exhibit extended queues at this horizon.

15.2.3 Network Intersection MMLOS

Table 22 summarizes the MMLOS analysis for the network intersections of Bronson Avenue at Catherine Street/Raymond Street, Bronson Avenue at Arlington Avenue, Bronson Avenue at Gladstone Avenue, Arthur Street/Arthur Lane at Gladstone Avenue, Booth Street at Gladstone Avenue and Booth Street at Raymond Street. Where the existing and future conditions will be the same (all intersections except for Bronson Avenue at Catherine Street/Raymond Street), they are considered in one row. The intersection analysis is based on the policy area of “Within 300m of a school” (as being within this distance of either St. Anthony School or Cambridge Street Community Public School) for all but the Bronson Avenue at Catherine Street/Raymond Street intersection which will be based upon the land use designation of “Traditional Main Street”. The MMLOS worksheets has been provided in Appendix H.

Table 22: Study Area Intersection MMLOS Analysis

Intersection	Pedestrian LOS		Bicycle LOS		Transit LOS		Truck LOS		Auto LOS	
	PLOS	Target	BLOS	Target	TLOS	Target	TrLOS	Target	ALOS	Target
Bronson Ave at Catherine St / Raymond St (Ex.)	E	B	E	D	F	D	D	D	F	D

Intersection	Pedestrian LOS		Bicycle LOS		Transit LOS		Truck LOS		Auto LOS	
	PLOS	Target	BLOS	Target	TLOS	Target	TrLOS	Target	ALOS	Target
Bronson Ave at Catherine St / Raymond St (Fut.)	D	B	E	D	F	D	D	D	F	D
Bronson Ave at Arlington Ave	D	A	C	C	B	D	-	-	A	E
Bronson Ave at Gladstone Ave	D	A	E	C	F	D	F	D	C	E
Arthur St / Arthur Ln at Gladstone Ave	B	A	C	B	B	D	-	-	A	E
Booth St at Gladstone Ave	D	A	C	B	E	D	-	-	F	E
Booth St at Raymond St	C	A	C	B	-	-	-	-	E	E

The MMLOS targets will not be met for the pedestrian LOS at all study area network intersections, bicycle LOS at all intersections except Bronson Avenue at Arlington Avenue, transit LOS at the Bronson Avenue at Catherine Street/Raymond Street, Bronson Avenue at Gladstone Avenue, and Booth Street at Gladstone Avenue intersection, truck LOS at the Bronson Avenue at Gladstone Avenue intersection, and auto LOS at the Bronson Avenue at Catherine Street/Raymond Street and Booth Street at Gladstone Avenue intersections.

For pedestrian LOS, a maximum crossing distance of two lane-widths at each crossing would be required to meet LOS A and a maximum crossing distance of three lane-widths would be required to meet LOS B.

Left-turn configurations govern the bicycle LOS on all approaches, and two-stage left turns or left-turn boxes would be required to meet LOS targets on all below-target approaches under the existing and planned lane arrangements.

To meet transit LOS, delay on the transit movements of the southbound and eastbound through movements at the Bronson Avenue at Catherine Street/Raymond Street intersection, the eastbound through and westbound through movements at the Bronson at Gladstone intersection, and the westbound through movement at the intersection of Booth Street at Gladstone Avenue would need to be reduced to 30 seconds or less.

To meet the truck LOS targets would require two receiving lanes on the Gladstone Avenue legs at its intersection with Bronson Avenue.

Pedestrian delay LOS is not considered in the PLOS calculation as it is not a suitable metric for the assessment of pedestrian LOS as formulated. This exclusion is consistent with City direction since 2015, and no alternative methodology has been provided for its assessment.

15.2.4 Recommended Design Elements

No study area intersection design elements are proposed as part of this study.

16 Summary of Improvements Indicated and Modifications Options

The following summarizes the analysis and results presented in this TIA report:

Proposed Site and Screening

- The proposed site includes 139 mid-rise apartment units

- Accesses to the underground parking will be provided onto Arlington Avenue, and a loading access is proposed onto Louisa Street, each at the location of an existing site access
- The development is proposed to be completed as a single phase by 2025
- The Trip Generation and Location Triggers were met for the TIA Screening
- This TIA is in support of a zoning by-law amendment and site plan application

Existing Conditions

- Bronson Avenue, Catherine Street, and Raymond Street east of the 417 on-ramp are arterial roads, and Booth Street and Gladstone Avenue are major collector roads in the study area
- Sidewalks are generally provided on both sides of the study area roadways, Gladstone Avenue, Booth Street, and Arlington Avenue are spine cycling routes, Arthur Street/Arthur Lane is a local route, and Arlington Avenue and Arthur Street/Arthur Lane are neighbourhood bikeways
- The high volumes roadways have produced a high number of collisions at the intersection of Bronson Avenue and Arlington Avenue, and the geometry may contribute to collisions at the intersection of Lebreton Street at Gladstone Avenue where the City may wish to restrict north-south through movements
- Some high delays and capacity issues are noted at the intersection of Bronson Avenue at Catherine Street/Raymond Street during both peak hours, and on the westbound movement at the intersection of Booth Street at Raymond Street during the PM peak hour

Development Generated Travel Demand

- The proposed development is forecasted produce 90 two-way people trips during the AM peak hour and 97 two-way people trips during the PM peak hour
- Of the forecasted people trips, 32 two-way trips will be vehicle trips during the AM peak hour and 34 two-way trips will be vehicle trips during the PM peak hour based on a 35% auto modal share target
- Of the forecasted trips, 30% are anticipated to travel north, 20% to travel south, 40% to travel east, and 10% to travel west

Background Conditions

- No background developments are within the study area, and an annual background growth rate based upon the TRANS model horizons was applied to the AM peak hour volumes and reversed for the PM peak hour for the mainline arterial and collector volumes
- The study area intersections at both horizons will operate similarly to the existing conditions additional queueing noted along Gladstone Avenue
- Signal timing optimization may be required for the network intersections to reduce all study area movements v/c ratios to 1.00 or below, should City Operations deem it to be required

Development Design

- Vehicle parking is proposed as being underground across two levels, bike parking as being located in secure storage on the first floor, in storage rooms on the parking levels and via surface racks
- Pedestrian connections will be made from all building entrances to the surrounding sidewalk facilities
- A full-movement access is proposed each onto Arlington Avenue to the underground parking and onto Louisa Street to a loading area, each in existing access locations
- Garbage collection is assumed to be on Louisa Street and emergency service access to the building is facilitated by its three public road frontages

Parking

- Vehicle parking of 80 underground spaces for vehicles is proposed along with the retention of eight surface vehicle parking spaces, and 79 bicycle spaces are proposed within a secure bike room, in the underground parking facilities, and on surface racks, meeting the minimum parking rates from the zoning by-law

Boundary Street Design

- The boundary streets will not meet pedestrian LOS targets due partly to their sidewalk and boulevard widths and partly due to the high targets set by the policy area
- Given the street context, the existing facilities, and the presence of on-street parking, no improvements are recommended as part of this study

Access Intersections Design

- An existing 6.0-metre full-movement access to underground parking is proposed to be conserved onto Arlington Avenue and a narrowing of an existing access to a 4.5-metre full-movement access to a loading area is proposed onto Louisa Street
- Stop-control on the accesses is assumed with the intersecting roadways operating under free flow
- No access intersection operational analysis has been performed due to unavailability of pre-pandemic data
- No specific recommendations or design elements are required outside of typical site design

TDM

- Supportive TDM measures to be included within the proposed development should include:
 - Display local area information with walking/cycling maps and relevant transit schedules and route maps
 - Provide a multimodal travel option information package to new residents
 - Inclusion of a 1-year Presto card for first time new townhome purchase and apartment rental, with a set time frame for this offer (e.g. 6-months) from the initial opening of the site
 - Unbundle parking cost from purchase or rental costs

NTM

- Volumes along Arlington Avenue will be lower than the TIA local road thresholds for local roads, and comprise less than 10% of the local road threshold volumes for Bell Street and Louisa Street
- Gladstone Avenue, Booth Street (major collector roads), and Raymond Street (local road) are above major collector road threshold volumes
- Site-generated volumes are less than 1% of volumes on Gladstone Avenue, Booth Street, and Raymond Street, and are considered negligible with respect to roadway classification

Transit

- Site-generated transit trips are forecasted to be 18 new AM and 19 new PM two-way transit trips based upon a 20% transit mode share target
- Ridership increases are anticipated to be one-to-two riders per bus per route/direction
- No specific transit priority measures were considered as part of this development

Network Intersection Design

- Network intersections at the future total horizons will perform similarly to the existing and future background horizons with additional queuing possible along Gladstone Avenue
- The MMLOS targets will not be met for the pedestrian LOS at all study area intersections, bicycle LOS at all but the intersection of Bronson Avenue at Arlington Avenue, transit LOS at the Bronson Avenue/Catherine Street/Raymond Street, the Bronson Avenue at Gladstone Avenue, and Booth Street at Gladstone Avenue intersections, truck LOS at the Bronson Avenue at Gladstone Avenue intersection, and auto LOS at the intersection of Bronson Avenue at Catherine Street/Raymond Street and Booth Street at Gladstone Avenue
- Improved cycling facilities, including left-turn configurations out of mixed flow could meet the LOS targets but due to the crossing distances, the pedestrian LOS cannot be met

17 Conclusion

It is recommended that, from a transportation perspective, the proposed development applications proceed.

Prepared By:

Reviewed By:



John Kingsley, EIT
Transportation Engineering-Intern



Andrew Harte, P.Eng.
Senior Transportation Engineer

Appendix A

TIA Screening Form and PM Certification Form

City of Ottawa 2017 TIA Guidelines
Step 1 - Screening Form

Date: 03-Mar-21
Project Number: 2021-015
Project Reference: Jennings 18 Louisa

1.1 Description of Proposed Development	
Municipal Address	18 Louisa Street
Description of Location	Existing Gladstone Sports & Health Centre
Land Use Classification	Institutional (I1A)
Development Size	137 apartment units, in addition to existing Gladstone Sports & Health Centre
Accesses	Existing accesses on Louisa St and Arlington Ave will remain. New access proposed to underground garage on Bell St, south of Louisa St intersection.
Phase of Development	Single Phase
Buildout Year	2025
TIA Requirement	Full TIA Required

1.2 Trip Generation Trigger	
Land Use Type	Townhomes or apartments
Development Size	138 Units
Trip Generation Trigger	Yes

1.3 Location Triggers	
Does the development propose a new driveway to a boundary street that is designated as part of the City's Transit Priority, Rapid Transit or Spine Bicycle Networks?	Yes
Is the development in a Design Priority Area (DPA) or Transit-oriented Development (TOD) zone?	No
Location Trigger	Yes

1.4. Safety Triggers	
Are posted speed limits on a boundary street 80 km/hr or greater?	No
Are there any horizontal/vertical curvatures on a boundary street limits sight lines at a proposed driveway?	No
Is the proposed driveway within the area of influence of an adjacent traffic signal or roundabout (i.e. within 300 m of intersection in rural conditions, or within 150 m of intersection in urban/ suburban conditions)?	No
Is the proposed driveway within auxiliary lanes of an intersection?	No
Does the proposed driveway make use of an existing median break that serves an existing site?	No
Is there is a documented history of traffic operations or safety concerns on the boundary streets within 500 m of the development?	No Bronson, Gladstone, Booth and Hwy 417 have collisions, considered a result of the road classification rather than indicative of a "safety concern"
Does the development include a drive-thru facility?	No
Safety Trigger	No



TIA Plan Reports

On 14 June 2017, the Council of the City of Ottawa adopted new Transportation Impact Assessment (TIA) Guidelines. In adopting the guidelines, Council established a requirement for those preparing and delivering transportation impact assessments and reports to sign a letter of certification.

Individuals submitting TIA reports will be responsible for all aspects of development-related transportation assessment and reporting, and undertaking such work, in accordance and compliance with the City of Ottawa's Official Plan, the Transportation Master Plan and the Transportation Impact Assessment (2017) Guidelines.

By submitting the attached TIA report (and any associated documents) and signing this document, the individual acknowledges that s/he meets the four criteria listed below.

CERTIFICATION

1. I have reviewed and have a sound understanding of the objectives, needs and requirements of the City of Ottawa's Official Plan, Transportation Master Plan and the Transportation Impact Assessment (2017) Guidelines;
2. I have a sound knowledge of industry standard practice with respect to the preparation of transportation impact assessment reports, including multi modal level of service review;
3. I have substantial experience (more than 5 years) in undertaking and delivering transportation impact studies (analysis, reporting and geometric design) with strong background knowledge in transportation planning, engineering or traffic operations; and
4. I am either a licensed¹ or registered² professional in good standing, whose field of expertise [check appropriate field(s)] is either transportation engineering or transportation planning .

1,2 License of registration body that oversees the profession is required to have a code of conduct and ethics guidelines that will ensure appropriate conduct and representation for transportation planning and/or transportation engineering works.

City Of Ottawa
Infrastructure Services and Community
Sustainability
Planning and Growth Management
110 Laurier Avenue West, 4th fl.
Ottawa, ON K1P 1J1
Tel. : 613-580-2424
Fax: 613-560-6006

Ville d'Ottawa
Services d'infrastructure et Viabilité des
collectivités
Urbanisme et Gestion de la croissance
110, avenue Laurier Ouest
Ottawa (Ontario) K1P 1J1
Tél. : 613-580-2424
Télécopieur: 613-560-6006

Dated at Ottawa this 20 day of September, 2018.
(City)

Name: Andrew Harte
(Please Print)

Professional Title: Professional Engineer



Signature of Individual certifier that s/he meets the above four criteria

Office Contact Information (Please Print)
Address: 13 Markham Avenue
City / Postal Code: Ottawa / K2G 3Z1
Telephone / Extension: (613) 697-3797
E-Mail Address: Andrew.Harte@CGHTransportation.com



Appendix B

Turning Movement Counts



Transportation Services - Traffic Services

Turning Movement Count - Study Results

BRONSON AVE @ CATHERINE ST/RAYMOND ST


Survey Date: Thursday, April 19, 2018

WO No: 39598

Start Time: 07:00

Device: Miovision

Full Study Diagram



W.O. 5365004 - THURS APR 19TH - CONSULTANT - 48 HRS (REIMPORT - 8HR STANDARD)



Transportation Services - Traffic Services

Turning Movement Count - Study Results

BRONSON AVE @ CATHERINE ST/RAYMOND ST


Survey Date: Thursday, April 19, 2018

WO No: 39598

Start Time: 07:00

Device: Miovision

Full Study Peak Hour Diagram



W.O. 5365004 - THURS APR 19TH - CONSULTANT - 48 HRS (REIMPORT - 8HR STANDARD)




Transportation Services - Traffic Services

Turning Movement Count - Peak Hour Diagram

BRONSON AVE @ CATHERINE ST/RAYMOND ST

Survey Date: Thursday, April 19, 2018
Start Time: 07:00

WO No: 39598
Device: Miovision



Comments W.O. 5365004 - THURS APR 19TH - CONSULTANT - 48 HRS (REIMPORT - 8HR STANDAR




Transportation Services - Traffic Services

Turning Movement Count - Peak Hour Diagram

BRONSON AVE @ CATHERINE ST/RAYMOND ST

Survey Date: Thursday, April 19, 2018
Start Time: 07:00

WO No: 39598
Device: Miovision



Comments W.O. 5365004 - THURS APR 19TH - CONSULTANT - 48 HRS (REIMPORT - 8HR STANDAR




Transportation Services - Traffic Services

Turning Movement Count - Peak Hour Diagram

BRONSON AVE @ CATHERINE ST/RAYMOND ST

Survey Date: Thursday, April 19, 2018
Start Time: 07:00

WO No: 39598
Device: Miovision



Comments W.O. 5365004 - THURS APR 19TH - CONSULTANT - 48 HRS (REIMPORT - 8HR STANDAR



Transportation Services - Traffic Services

Turning Movement Count - Study Results

BRONSON AVE @ CATHERINE ST/RAYMOND ST

Survey Date: Thursday, April 19, 2018
Start Time: 07:00

WO No: 39598
Device: Miovision

Full Study Summary (8 HR Standard)

Survey Date: Thursday, April 19, 2018

Total Observed U-Turns **AADT Factor**

Northbound: 0 Southbound: 0 .90

Eastbound: 0 Westbound: 0

Period	BRONSON AVE								CATHERINE ST/RAYMOND ST								Grand Total		
	Northbound				Southbound				Eastbound				Westbound						
	LT	ST	RT	NB TOT	LT	ST	RT	SB TOT	LT	ST	RT	EB TOT	LT	ST	RT	WB TOT			
07:00-08:00	478	846	0	1324	0	428	140	568	1892	0	0	0	0	465	446	345	1256	1256	3148
08:00-09:00	519	1038	0	1557	0	428	118	546	2103	0	0	0	0	492	479	346	1317	1317	3420
09:00-10:00	387	699	0	1086	0	406	133	539	1625	0	0	0	0	480	403	329	1212	1212	2837
11:30-12:30	382	620	0	1002	0	527	173	700	1702	0	0	0	0	471	401	301	1173	1173	2875
12:30-13:30	349	568	0	917	0	560	167	727	1644	0	0	0	0	484	321	310	1115	1115	2759
15:00-16:00	299	747	0	1046	0	783	177	960	2006	0	0	0	0	697	517	299	1513	1513	3519
16:00-17:00	265	813	0	1078	0	733	130	863	1941	0	0	0	0	677	638	248	1563	1563	3504
17:00-18:00	281	725	0	1006	0	727	147	874	1880	0	0	0	0	662	438	310	1410	1410	3290
Sub Total	2960	6056	0	9016	0	4592	1185	5777	14793	0	0	0	0	4428	3643	2488	10559	10559	25352
U Turns	0				0				0				0				0	0	0
Total	2960	6056	0	9016	0	4592	1185	5777	14793	0	0	0	0	4428	3643	2488	10559	10559	25352
EQ 12Hr	4114	8418	0	12532	0	6383	1647	8030	20562	0	0	0	0	6155	5064	3458	14677	14677	35239
Note: These values are calculated by multiplying the totals by the appropriate expansion factor. 1.39																			
AVG 12Hr	3490	7140	0	10630	0	5414	1397	6811	18506	0	0	0	0	5221	4295	2933	12449	13209	31715
Note: These volumes are calculated by multiplying the Equivalent 12 hr. totals by the AADT factor. 0.9																			
AVG 24Hr	4572	9353	0	13925	0	7092	1830	8923	22848	0	0	0	0	6839	5627	3843	16308	16308	39156
Note: These volumes are calculated by multiplying the Average Daily 12 hr. totals by 12 to 24 expansion factor. 1.31																			
Note: U-Turns provided for approach totals. Refer to 'U-Turn' Report for specific breakdown.																			



Transportation Services - Traffic Services

Turning Movement Count - Study Results

BRONSON AVE @ CATHERINE ST/RAYMOND ST

Survey Date: Thursday, April 19, 2018

WO No: 39598

Start Time: 07:00

Device: Miovision

Full Study 15 Minute Increments

Table with columns for Time Period, Northbound, Southbound, Eastbound, Westbound, and Grand Total. Rows show 15-minute intervals from 07:00 to 18:00.

Note: U-Turns are included in Totals.



Transportation Services - Traffic Services

Turning Movement Count - Study Results

BRONSON AVE @ CATHERINE ST/RAYMOND ST

Survey Date: Thursday, April 19, 2018

WO No: 39598

Start Time: 07:00

Device: Miovision

Full Study Cyclist Volume

Table with columns for Time Period, Northbound, Southbound, Street Total, Eastbound, Westbound, Street Total, and Grand Total. Rows show 15-minute intervals from 07:00 to 18:00.



Transportation Services - Traffic Services

Turning Movement Count - Study Results

BRONSON AVE @ CATHERINE ST/RAYMOND ST

Survey Date: Thursday, April 19, 2018

WO No: 39598

Start Time: 07:00

Device: Miovision

Full Study Pedestrian Volume

BRONSON AVE

CATHERINE ST/RAYMOND ST

Table with columns: Time Period, NB Approach (E or W Crossing), SB Approach (E or W Crossing), Total, EB Approach (N or S Crossing), WB Approach (N or S Crossing), Total, Grand Total. Rows show pedestrian volume for various time intervals from 07:00 to 18:00.

W.O. 5365004 - THURS APR 19TH - CONSULTANT - 48 HRS (REIMPORT - 8HR STANDARD)



Transportation Services - Traffic Services

Turning Movement Count - Study Results

BRONSON AVE @ CATHERINE ST/RAYMOND ST

Survey Date: Thursday, April 19, 2018

WO No: 39598

Start Time: 07:00

Device: Miovision

Full Study Heavy Vehicles

BRONSON AVE

CATHERINE ST/RAYMOND ST

Table with columns: Time Period, Northbound (LT, ST, RT, N TOT), Southbound (LT, ST, RT, S TOT), Eastbound (LT, ST, RT, E TOT), Westbound (LT, ST, RT, W TOT), STR TOT, Grand Total. Rows show heavy vehicle volume for various time intervals from 07:00 to 18:00.



Transportation Services - Traffic Services

Turning Movement Count - Study Results

BRONSON AVE @ CATHERINE ST/RAYMOND ST

Survey Date: Thursday, April 19, 2018

WO No: 39598

Start Time: 07:00

Device: Miovision

Full Study 15 Minute U-Turn Total

Time Period	BRONSON AVE		CATHERINE ST/RAYMOND ST		Total
	Northbound U-Turn Total	Southbound U-Turn Total	Eastbound U-Turn Total	Westbound U-Turn Total	
07:00 - 07:15	0	0	0	0	0
07:15 - 07:30	0	0	0	0	0
07:30 - 07:45	0	0	0	0	0
07:45 - 08:00	0	0	0	0	0
08:00 - 08:15	0	0	0	0	0
08:15 - 08:30	0	0	0	0	0
08:30 - 08:45	0	0	0	0	0
08:45 - 09:00	0	0	0	0	0
09:00 - 09:15	0	0	0	0	0
09:15 - 09:30	0	0	0	0	0
09:30 - 09:45	0	0	0	0	0
09:45 - 10:00	0	0	0	0	0
11:30 - 11:45	0	0	0	0	0
11:45 - 12:00	0	0	0	0	0
12:00 - 12:15	0	0	0	0	0
12:15 - 12:30	0	0	0	0	0
12:30 - 12:45	0	0	0	0	0
12:45 - 13:00	0	0	0	0	0
13:00 - 13:15	0	0	0	0	0
13:15 - 13:30	0	0	0	0	0
15:00 - 15:15	0	0	0	0	0
15:15 - 15:30	0	0	0	0	0
15:30 - 15:45	0	0	0	0	0
15:45 - 16:00	0	0	0	0	0
16:00 - 16:15	0	0	0	0	0
16:15 - 16:30	0	0	0	0	0
16:30 - 16:45	0	0	0	0	0
16:45 - 17:00	0	0	0	0	0
17:00 - 17:15	0	0	0	0	0
17:15 - 17:30	0	0	0	0	0
17:30 - 17:45	0	0	0	0	0
17:45 - 18:00	0	0	0	0	0
Total	0	0	0	0	0



Transportation Services - Traffic Services

Turning Movement Count - Study Results

ARLINGTON AVE @ BRONSON AVE


Survey Date: Wednesday, December 13, 2017

WO No: 37368

Start Time: 07:00

Device: Miovision

Full Study Diagram





Transportation Services - Traffic Services

Turning Movement Count - Study Results

ARLINGTON AVE @ BRONSON AVE


Survey Date: Wednesday, December 13, 2017

WO No: 37368

Start Time: 07:00

Device: Miovision

Full Study Peak Hour Diagram



Transportation Services - Traffic Services

Turning Movement Count - Peak Hour Diagram


ARLINGTON AVE @ BRONSON AVE

Survey Date: Wednesday, December 13, 2017

WO No: 37368

Start Time: 07:00

Device: Miovision



Comments




Transportation Services - Traffic Services

Turning Movement Count - Peak Hour Diagram

ARLINGTON AVE @ BRONSON AVE

Survey Date: Wednesday, December 13, 2017
Start Time: 07:00

WO No: 37368
Device: Miovision



Comments




Transportation Services - Traffic Services

Turning Movement Count - Peak Hour Diagram

ARLINGTON AVE @ BRONSON AVE

Survey Date: Wednesday, December 13, 2017
Start Time: 07:00

WO No: 37368
Device: Miovision



Comments



Transportation Services - Traffic Services

Turning Movement Count - Study Results

ARLINGTON AVE @ BRONSON AVE

Survey Date: Wednesday, December 13, 2017 WO No: 37368
Start Time: 07:00 Device: Miovision

Full Study Summary (8 HR Standard)

Survey Date: Wednesday, December 13, 2017 Total Observed U-Turns AADT Factor
Northbound: 1 Southbound: 1 Eastbound: 0 Westbound: 1 1.00

Table with columns for Period, Northbound, Southbound, Eastbound, Westbound, and Grand Total. Includes sub-totals for U-Turns, EQ 12Hr, and AVG 24Hr.



Transportation Services - Traffic Services

Turning Movement Count - Study Results

ARLINGTON AVE @ BRONSON AVE

Survey Date: Wednesday, December 13, 2017 WO No: 37368
Start Time: 07:00 Device: Miovision

Full Study 15 Minute Increments

Table with columns for Time Period, Northbound, Southbound, Eastbound, Westbound, and Grand Total. Includes sub-totals for U-Turns, EQ 12Hr, and AVG 24Hr.

Note: U-Turns are included in Totals.



Transportation Services - Traffic Services

Turning Movement Count - Study Results

ARLINGTON AVE @ BRONSON AVE

Survey Date: Wednesday, December 13, 2017

WO No: 37368

Start Time: 07:00

Device: Miovision

Full Study Cyclist Volume

Time Period	BRONSON AVE			ARLINGTON AVE			Grand Total
	Northbound	Southbound	Street Total	Eastbound	Westbound	Street Total	
07:00 07:15	2	0	2	0	0	0	2
07:15 07:30	0	0	0	0	1	1	1
07:30 07:45	1	0	1	0	0	0	1
07:45 08:00	0	0	0	0	0	0	0
08:00 08:15	0	0	0	0	0	0	0
08:15 08:30	0	0	0	0	0	0	0
08:30 08:45	0	0	0	0	0	0	0
08:45 09:00	0	1	1	0	0	0	1
09:00 09:15	0	0	0	1	0	1	1
09:15 09:30	1	0	1	0	0	0	1
09:30 09:45	0	0	0	0	0	0	0
09:45 10:00	0	0	0	0	0	0	0
11:30 11:45	0	0	0	0	0	0	0
11:45 12:00	0	0	0	0	0	0	0
12:00 12:15	0	0	0	0	0	0	0
12:15 12:30	0	0	0	0	0	0	0
12:30 12:45	0	0	0	0	0	0	0
12:45 13:00	0	0	0	0	0	0	0
13:00 13:15	0	0	0	0	0	0	0
13:15 13:30	0	0	0	0	0	0	0
15:00 15:15	0	0	0	0	0	0	0
15:15 15:30	0	0	0	0	0	0	0
15:30 15:45	0	0	0	0	0	0	0
15:45 16:00	0	0	0	0	1	1	1
16:00 16:15	1	0	1	0	0	0	1
16:15 16:30	0	0	0	0	1	1	1
16:30 16:45	0	1	1	0	2	2	3
16:45 17:00	0	0	0	0	0	0	0
17:00 17:15	0	0	0	0	0	0	0
17:15 17:30	0	0	0	0	0	0	0
17:30 17:45	0	0	0	0	0	0	0
17:45 18:00	0	0	0	0	0	0	0
Total	5	2	7	1	5	6	13



Transportation Services - Traffic Services

Turning Movement Count - Study Results

ARLINGTON AVE @ BRONSON AVE

Survey Date: Wednesday, December 13, 2017

WO No: 37368

Start Time: 07:00

Device: Miovision

Full Study Pedestrian Volume

Time Period	BRONSON AVE			ARLINGTON AVE			Grand Total
	NB Approach (E or W Crossing)	SB Approach (E or W Crossing)	Total	EB Approach (N or S Crossing)	WB Approach (N or S Crossing)	Total	
07:00 07:15	2	0	2	4	3	7	9
07:15 07:30	0	0	0	4	2	6	6
07:30 07:45	3	3	6	5	7	12	18
07:45 08:00	3	1	4	5	6	11	15
08:00 08:15	4	1	5	5	4	9	14
08:15 08:30	4	3	7	10	8	18	25
08:30 08:45	8	5	13	8	12	20	33
08:45 09:00	5	5	10	10	5	15	25
09:00 09:15	7	4	11	2	2	4	15
09:15 09:30	3	5	8	7	2	9	17
09:30 09:45	5	5	10	5	5	10	20
09:45 10:00	2	1	3	3	3	6	9
11:30 11:45	7	3	10	4	10	14	24
11:45 12:00	11	2	13	6	6	12	25
12:00 12:15	3	1	4	7	7	14	18
12:15 12:30	3	2	5	2	7	9	14
12:30 12:45	3	2	5	3	5	8	13
12:45 13:00	6	8	14	3	3	6	20
13:00 13:15	0	3	3	1	3	4	7
13:15 13:30	2	3	5	5	1	6	11
15:00 15:15	5	2	7	10	5	15	22
15:15 15:30	5	4	9	20	14	34	43
15:30 15:45	7	7	14	5	4	9	23
15:45 16:00	2	7	9	4	6	10	19
16:00 16:15	5	7	12	3	7	10	22
16:15 16:30	7	7	14	7	9	16	30
16:30 16:45	0	2	2	1	5	6	8
16:45 17:00	5	7	12	6	9	15	27
17:00 17:15	6	1	7	6	26	32	39
17:15 17:30	1	6	7	7	5	12	19
17:30 17:45	13	7	20	14	7	21	41
17:45 18:00	13	5	18	7	11	18	36
Total	150	119	269	189	209	398	667



Transportation Services - Traffic Services

Turning Movement Count - Study Results

ARLINGTON AVE @ BRONSON AVE

Survey Date: Wednesday, December 13, 2017

WO No: 37368

Start Time: 07:00

Device: Miovision

Full Study Heavy Vehicles

Table with columns for Time Period, Northbound (LT, ST, RT, N TOT, STR TOT), Southbound (LT, ST, RT, S TOT, STR TOT), Eastbound (LT, ST, RT, E TOT, STR TOT), Westbound (LT, ST, RT, W TOT, STR TOT), and Grand Total. Rows represent 15-minute intervals from 07:00 to 18:00.



Transportation Services - Traffic Services

Turning Movement Count - Study Results

ARLINGTON AVE @ BRONSON AVE

Survey Date: Wednesday, December 13, 2017

WO No: 37368

Start Time: 07:00

Device: Miovision

Full Study 15 Minute U-Turn Total

Table with columns for Time Period, Northbound U-Turn Total, Southbound U-Turn Total, Eastbound U-Turn Total, Westbound U-Turn Total, and Total. Rows represent 15-minute intervals from 07:00 to 18:00.



Transportation Services - Traffic Services

Turning Movement Count - Study Results

BRONSON AVE @ GLADSTONE AVE


Survey Date: Wednesday, July 27, 2016

WO No: 36090

Start Time: 07:00

Device: Miovision

Full Study Diagram



Transportation Services - Traffic Services

Turning Movement Count - Study Results

BRONSON AVE @ GLADSTONE AVE


Survey Date: Wednesday, July 27, 2016

WO No: 36090

Start Time: 07:00

Device: Miovision

Full Study Peak Hour Diagram






Transportation Services - Traffic Services

Turning Movement Count - Peak Hour Diagram

BRONSON AVE @ GLADSTONE AVE

Survey Date: Wednesday, July 27, 2016
Start Time: 07:00

WO No: 36090
Device: Miovision



Comments




Transportation Services - Traffic Services

Turning Movement Count - Peak Hour Diagram

BRONSON AVE @ GLADSTONE AVE

Survey Date: Wednesday, July 27, 2016
Start Time: 07:00

WO No: 36090
Device: Miovision



Comments




Transportation Services - Traffic Services

Turning Movement Count - Peak Hour Diagram

BRONSON AVE @ GLADSTONE AVE

Survey Date: Wednesday, July 27, 2016
Start Time: 07:00

WO No: 36090
Device: Miovision



Comments



Transportation Services - Traffic Services

Turning Movement Count - Study Results

BRONSON AVE @ GLADSTONE AVE

Survey Date: Wednesday, July 27, 2016
Start Time: 07:00

WO No: 36090
Device: Miovision

Full Study Summary (8 HR Standard)

Survey Date: Wednesday, July 27, 2016

Total Observed U-Turns
Northbound: 0 Southbound: 0
Eastbound: 0 Westbound: 0

ADT Factor .90

Period	BRONSON AVE								GLADSTONE AVE								Grand Total		
	Northbound				Southbound				Eastbound				Westbound						
	LT	ST	RT	TOT	LT	ST	RT	TOT	LT	ST	RT	TOT	LT	ST	RT	TOT			
07:00-08:00	76	1075	109	1260	13	441	21	475	1735	37	190	58	285	112	103	8	223	508	2243
08:00-09:00	123	1076	150	1349	13	419	39	471	1820	46	248	97	391	90	155	18	263	654	2474
09:00-10:00	103	794	144	1041	10	419	32	461	1502	38	215	81	334	122	132	18	272	606	2108
11:30-12:30	103	625	186	914	28	485	30	543	1457	39	262	122	423	177	189	17	383	806	2263
12:30-13:30	108	621	181	910	25	494	28	547	1457	67	300	110	477	175	198	28	401	878	2335
15:00-16:00	86	757	145	988	50	862	70	982	1970	52	283	85	420	172	193	17	382	802	2772
16:00-17:00	108	757	150	1015	38	676	109	823	1638	39	273	80	392	144	311	25	480	872	2710
17:00-18:00	101	772	151	1024	29	671	85	785	1809	47	283	77	407	171	230	17	418	825	2634
Sub Total	808	6477	1216	8501	206	4467	414	5087	13588	365	2054	710	3129	1163	1511	148	2822	5951	19539
U Turns	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Total	808	6477	1216	8501	206	4467	414	5087	13588	365	2054	710	3129	1163	1511	148	2822	5951	19539
EQ 12Hr	1123	9003	1690	11816	286	6209	575	7070	18886	507	2855	987	4349	1617	2100	206	3923	8272	27158
Note: These values are calculated by multiplying the totals by the appropriate expansion factor.													1.39						
AVG 12Hr	1011	8103	1521	10635	257	5588	518	6363	16998	456	2570	888	3914	1455	1890	185	3530	7444	24442
Note: These volumes are calculated by multiplying the Equivalent 12 hr. totals by the AADT factor.													.90						
AVG 24Hr	1324	10615	1993	13932	337	7320	679	8336	22268	597	3367	1163	5127	1906	2476	242	4624	9751	32019
Note: These volumes are calculated by multiplying the Average Daily 12 hr. totals by 12 to 24 expansion factor.													1.31						
Note: U-Turns provided for approach totals. Refer to 'U-Turn' Report for specific breakdown.																			



Transportation Services - Traffic Services

Turning Movement Count - Study Results

BRONSON AVE @ GLADSTONE AVE

Survey Date: Wednesday, July 27, 2016

WO No: 36090

Start Time: 07:00

Device: Miovision

Full Study 15 Minute Increments

Table with columns for Time Period, Northbound, Southbound, Eastbound, Westbound, and Grand Total. Rows show 15-minute intervals from 07:00 to 18:00.

Note: U-Turns are included in Totals.



Transportation Services - Traffic Services

Turning Movement Count - Study Results

BRONSON AVE @ GLADSTONE AVE

Survey Date: Wednesday, July 27, 2016

WO No: 36090

Start Time: 07:00

Device: Miovision

Full Study Cyclist Volume

Table with columns for Time Period, Northbound, Southbound, Street Total, Eastbound, Westbound, Street Total, and Grand Total. Rows show 15-minute intervals from 07:00 to 18:00.



Transportation Services - Traffic Services

Turning Movement Count - Study Results

BRONSON AVE @ GLADSTONE AVE

Survey Date: Wednesday, July 27, 2016

WO No: 36090

Start Time: 07:00

Device: Miovision

Full Study Pedestrian Volume

BRONSON AVE

GLADSTONE AVE

Table with columns: Time Period, NB Approach (E or W Crossing), SB Approach (E or W Crossing), Total, EB Approach (N or S Crossing), WB Approach (N or S Crossing), Total, Grand Total. Rows show pedestrian counts for various time intervals from 07:00 to 18:00.



Transportation Services - Traffic Services

Turning Movement Count - Study Results

BRONSON AVE @ GLADSTONE AVE

Survey Date: Wednesday, July 27, 2016

WO No: 36090

Start Time: 07:00

Device: Miovision

Full Study Heavy Vehicles

BRONSON AVE

GLADSTONE AVE

Table with columns: Time Period, Northbound (LT, ST, RT, N TOT, STR TOT), Southbound (LT, ST, RT, S TOT, STR TOT), Eastbound (LT, ST, RT, E TOT), Westbound (LT, ST, RT, W TOT, STR TOT), Grand Total. Rows show heavy vehicle counts for various time intervals from 07:00 to 18:00.



Transportation Services - Traffic Services

Turning Movement Count - Study Results

BRONSON AVE @ GLADSTONE AVE

Survey Date: Wednesday, July 27, 2016

WO No: 36090

Start Time: 07:00

Device: Miovision

Full Study 15 Minute U-Turn Total

BRONSON AVE GLADSTONE AVE

Time Period	Northbound U-Turn Total	Southbound U-Turn Total	Eastbound U-Turn Total	Westbound U-Turn Total	Total
07:00 - 07:15	0	0	0	0	0
07:15 - 07:30	0	0	0	0	0
07:30 - 07:45	0	0	0	0	0
07:45 - 08:00	0	0	0	0	0
08:00 - 08:15	0	0	0	0	0
08:15 - 08:30	0	0	0	0	0
08:30 - 08:45	0	0	0	0	0
08:45 - 09:00	0	0	0	0	0
09:00 - 09:15	0	0	0	0	0
09:15 - 09:30	0	0	0	0	0
09:30 - 09:45	0	0	0	0	0
09:45 - 10:00	0	0	0	0	0
11:30 - 11:45	0	0	0	0	0
11:45 - 12:00	0	0	0	0	0
12:00 - 12:15	0	0	0	0	0
12:15 - 12:30	0	0	0	0	0
12:30 - 12:45	0	0	0	0	0
12:45 - 13:00	0	0	0	0	0
13:00 - 13:15	0	0	0	0	0
13:15 - 13:30	0	0	0	0	0
15:00 - 15:15	0	0	0	0	0
15:15 - 15:30	0	0	0	0	0
15:30 - 15:45	0	0	0	0	0
15:45 - 16:00	0	0	0	0	0
16:00 - 16:15	0	0	0	0	0
16:15 - 16:30	0	0	0	0	0
16:30 - 16:45	0	0	0	0	0
16:45 - 17:00	0	0	0	0	0
17:00 - 17:15	0	0	0	0	0
17:15 - 17:30	0	0	0	0	0
17:30 - 17:45	0	0	0	0	0
17:45 - 18:00	0	0	0	0	0
Total	0	0	0	0	0



Transportation Services - Traffic Services

Turning Movement Count - Study Results

BOOTH ST @ GLADSTONE AVE


Survey Date: Wednesday, July 27, 2016

WO No: 36092

Start Time: 07:00

Device: Miovision

Full Study Diagram





Transportation Services - Traffic Services

Turning Movement Count - Study Results

BOOTH ST @ GLADSTONE AVE


Survey Date: Wednesday, July 27, 2016

WO No: 36092

Start Time: 07:00

Device: Miovision

Full Study Peak Hour Diagram



Transportation Services - Traffic Services

Turning Movement Count - Peak Hour Diagram


BOOTH ST @ GLADSTONE AVE

Survey Date: Wednesday, July 27, 2016

WO No: 36092

Start Time: 07:00

Device: Miovision



Comments




Transportation Services - Traffic Services

Turning Movement Count - Peak Hour Diagram

BOOTH ST @ GLADSTONE AVE

Survey Date: Wednesday, July 27, 2016
Start Time: 07:00

WO No: 36092
Device: Miovision



Comments




Transportation Services - Traffic Services

Turning Movement Count - Peak Hour Diagram

BOOTH ST @ GLADSTONE AVE

Survey Date: Wednesday, July 27, 2016
Start Time: 07:00

WO No: 36092
Device: Miovision



Comments



Transportation Services - Traffic Services

Turning Movement Count - Study Results

BOOTH ST @ GLADSTONE AVE

Survey Date: Wednesday, July 27, 2016

WO No: 36092

Start Time: 07:00

Device: Miovision

Full Study Summary (8 HR Standard)

Survey Date: Wednesday, July 27, 2016

Total Observed U-Turns AADT Factor
Northbound: 0 Southbound: 0 Eastbound: 0 Westbound: 0 .90

Table with columns for Period, Northbound, Southbound, Eastbound, Westbound, and Grand Total. Includes sub-totals for U-Turns, EQ 12Hr, and AVG 24Hr.



Transportation Services - Traffic Services

Turning Movement Count - Study Results

BOOTH ST @ GLADSTONE AVE

Survey Date: Wednesday, July 27, 2016

WO No: 36092

Start Time: 07:00

Device: Miovision

Full Study 15 Minute Increments

Table with columns for Time Period, Northbound, Southbound, Eastbound, Westbound, and Grand Total. Shows 15-minute increments from 07:00 to 18:00.

Note: U-Turns are included in Totals.



Transportation Services - Traffic Services

Turning Movement Count - Study Results

BOOTH ST @ GLADSTONE AVE

Survey Date: Wednesday, July 27, 2016

WO No: 36092

Start Time: 07:00

Device: Miovision

Full Study Cyclist Volume

Time Period	BOOTH ST			GLADSTONE AVE			Grand Total
	Northbound	Southbound	Street Total	Eastbound	Westbound	Street Total	
07:00 07:15	3	2	5	4	0	4	9
07:15 07:30	1	2	3	5	5	10	13
07:30 07:45	5	3	8	13	8	21	29
07:45 08:00	4	2	6	8	8	16	22
08:00 08:15	0	1	1	13	6	19	20
08:15 08:30	0	2	2	8	17	25	27
08:30 08:45	3	0	3	12	10	22	25
08:45 09:00	2	0	2	16	10	26	28
09:00 09:15	3	5	8	4	8	12	20
09:15 09:30	3	0	3	2	11	13	16
09:30 09:45	0	0	0	1	6	7	7
09:45 10:00	1	0	1	3	4	7	8
11:30 11:45	2	0	2	0	4	4	6
11:45 12:00	1	0	1	4	2	6	7
12:00 12:15	2	0	2	3	2	5	7
12:15 12:30	1	1	2	3	4	7	9
12:30 12:45	1	0	1	7	0	7	8
12:45 13:00	0	2	2	3	1	4	6
13:00 13:15	0	0	0	3	3	6	6
13:15 13:30	0	0	0	2	2	4	4
15:00 15:15	0	0	0	2	6	8	8
15:15 15:30	1	1	2	0	3	3	5
15:30 15:45	1	0	1	4	5	9	10
15:45 16:00	2	2	4	0	9	9	13
16:00 16:15	1	0	1	8	2	10	11
16:15 16:30	1	0	1	4	3	7	8
16:30 16:45	1	0	1	8	8	16	17
16:45 17:00	4	0	4	9	10	19	23
17:00 17:15	1	2	3	11	5	16	19
17:15 17:30	5	1	6	6	15	21	27
17:30 17:45	4	2	6	9	6	15	21
17:45 18:00	1	2	3	5	8	13	16
Total	54	30	84	180	191	371	455



Transportation Services - Traffic Services

Turning Movement Count - Study Results

BOOTH ST @ GLADSTONE AVE

Survey Date: Wednesday, July 27, 2016

WO No: 36092

Start Time: 07:00

Device: Miovision

Full Study Pedestrian Volume

Time Period	BOOTH ST			GLADSTONE AVE			Grand Total
	NB Approach (E or W Crossing)	SB Approach (E or W Crossing)	Total	EB Approach (N or S Crossing)	WB Approach (N or S Crossing)	Total	
07:00 07:15	2	2	4	5	3	8	12
07:15 07:30	2	3	5	4	5	9	14
07:30 07:45	8	9	17	7	4	11	28
07:45 08:00	6	8	14	4	12	16	30
08:00 08:15	9	7	16	2	10	12	28
08:15 08:30	17	6	23	0	6	6	29
08:30 08:45	9	8	17	0	15	15	32
08:45 09:00	9	10	19	0	6	6	25
09:00 09:15	8	4	12	4	2	6	18
09:15 09:30	7	5	12	7	6	13	25
09:30 09:45	22	16	38	17	18	35	73
09:45 10:00	12	9	21	6	9	15	36
11:30 11:45	7	4	11	4	1	5	16
11:45 12:00	10	5	15	5	4	9	24
12:00 12:15	18	0	18	9	1	10	28
12:15 12:30	7	3	10	11	1	12	22
12:30 12:45	18	8	26	3	12	15	41
12:45 13:00	5	7	12	4	1	5	17
13:00 13:15	4	2	6	5	2	7	13
13:15 13:30	11	4	15	1	1	2	17
15:00 15:15	3	5	8	3	3	6	14
15:15 15:30	4	6	10	4	2	6	16
15:30 15:45	9	2	11	1	9	10	21
15:45 16:00	11	7	18	3	9	12	30
16:00 16:15	11	10	21	6	5	11	32
16:15 16:30	9	7	16	11	3	14	30
16:30 16:45	9	10	19	4	4	8	27
16:45 17:00	18	9	27	9	9	18	45
17:00 17:15	10	15	25	3	11	14	39
17:15 17:30	11	11	22	5	8	13	35
17:30 17:45	12	6	18	5	4	9	27
17:45 18:00	5	7	12	2	3	5	17
Total	303	215	518	154	189	343	861



Transportation Services - Traffic Services

Turning Movement Count - Study Results

BOOTH ST @ GLADSTONE AVE

Survey Date: Wednesday, July 27, 2016

WO No: 36092

Start Time: 07:00

Device: Miovision

Full Study Heavy Vehicles

BOOTH ST										GLADSTONE AVE										Grand Total				
Northbound			Southbound			Eastbound			Westbound			Northbound			Southbound			Eastbound			Westbound			
Time Period	LT	ST	RT	N TOT	LT	ST	RT	S TOT	STR TOT	LT	ST	RT	E TOT	LT	ST	RT	W TOT	STR TOT	Grand Total					
07:00	07:15	0	0	0	0	0	0	0	0	0	2	1	3	0	4	0	4	7	7					
07:15	07:30	0	0	0	0	0	0	0	0	0	4	0	4	0	4	0	4	8	8					
07:30	07:45	0	1	0	1	1	1	0	2	3	0	3	0	3	0	2	0	2	5	8				
07:45	08:00	0	1	0	1	0	0	0	0	1	0	3	0	3	0	0	0	0	3	4				
08:00	08:15	1	0	1	2	0	0	0	0	2	1	4	0	5	0	5	1	6	11	13				
08:15	08:30	0	0	0	0	0	0	0	0	0	0	9	0	9	0	3	0	3	12	12				
08:30	08:45	0	1	0	1	0	0	0	0	1	1	4	0	5	0	3	1	4	9	10				
08:45	09:00	0	1	0	1	0	0	0	0	1	0	2	0	2	0	4	0	4	6	7				
09:00	09:15	0	0	0	0	0	0	0	0	0	0	3	0	3	0	2	0	2	5	5				
09:15	09:30	0	2	0	2	0	1	0	1	3	0	6	0	6	0	3	0	3	9	12				
09:30	09:45	1	3	0	4	0	0	0	0	4	0	2	0	2	0	1	0	1	3	7				
09:45	10:00	0	0	0	0	0	1	0	1	1	0	4	0	4	0	3	0	3	7	8				
11:30	11:45	0	1	0	1	1	0	0	1	2	0	1	1	2	0	5	0	5	7	9				
11:45	12:00	0	0	0	0	0	1	0	1	1	0	1	0	1	0	4	0	4	5	6				
12:00	12:15	0	0	0	0	0	1	0	1	1	1	4	0	5	1	4	0	5	10	11				
12:15	12:30	0	1	0	1	0	1	0	1	2	0	8	0	8	0	5	0	5	13	15				
12:30	12:45	1	0	0	1	2	0	1	3	4	0	3	1	4	0	2	0	2	6	10				
12:45	13:00	0	3	0	3	1	0	1	2	5	0	4	0	4	0	2	0	2	6	11				
13:00	13:15	2	0	1	3	0	4	0	4	7	0	5	0	5	1	1	0	2	7	14				
13:15	13:30	0	0	0	0	0	0	0	0	0	1	5	0	6	1	5	0	6	12	12				
15:00	15:15	0	1	0	1	1	0	0	1	2	0	3	1	4	0	1	0	1	5	7				
15:15	15:30	0	0	0	0	0	0	1	1	1	0	4	0	4	0	4	0	4	8	9				
15:30	15:45	2	0	0	2	0	1	0	1	3	0	5	0	5	1	0	0	1	6	9				
15:45	16:00	0	0	1	1	0	0	1	1	2	1	3	0	4	0	1	1	2	6	8				
16:00	16:15	0	1	0	1	0	3	1	4	5	0	3	0	3	0	1	0	1	4	9				
16:15	16:30	0	0	0	0	0	0	0	0	0	0	2	0	2	0	2	0	2	4	4				
16:30	16:45	0	0	0	0	0	0	0	0	0	0	4	0	4	0	1	0	1	5	5				
16:45	17:00	0	0	0	0	0	0	0	0	0	0	1	1	2	0	5	0	5	7	7				
17:00	17:15	0	0	0	0	0	0	0	0	0	0	2	0	2	0	1	0	1	3	3				
17:15	17:30	0	2	0	2	0	0	0	0	2	0	5	0	5	0	2	0	2	7	9				
17:30	17:45	0	1	0	1	0	0	0	0	1	0	3	0	3	0	5	0	5	8	9				
17:45	18:00	0	0	0	0	0	0	0	0	0	0	1	0	1	0	4	0	4	5	5				
Total:	None	7	19	3	29	6	14	5	25	54	5	113	5	123	4	89	3	96	219	273				



Transportation Services - Traffic Services

Turning Movement Count - Study Results

BOOTH ST @ GLADSTONE AVE

Survey Date: Wednesday, July 27, 2016

WO No: 36092

Start Time: 07:00

Device: Miovision

Full Study 15 Minute U-Turn Total

BOOTH ST		GLADSTONE AVE				Total
Time Period	Northbound U-Turn Total	Southbound U-Turn Total	Eastbound U-Turn Total	Westbound U-Turn Total		
07:00	07:15	0	0	0	0	0
07:15	07:30	0	0	0	0	0
07:30	07:45	0	0	0	0	0
07:45	08:00	0	0	0	0	0
08:00	08:15	0	0	0	0	0
08:15	08:30	0	0	0	0	0
08:30	08:45	0	0	0	0	0
08:45	09:00	0	0	0	0	0
09:00	09:15	0	0	0	0	0
09:15	09:30	0	0	0	0	0
09:30	09:45	0	0	0	0	0
09:45	10:00	0	0	0	0	0
11:30	11:45	0	0	0	0	0
11:45	12:00	0	0	0	0	0
12:00	12:15	0	0	0	0	0
12:15	12:30	0	0	0	0	0
12:30	12:45	0	0	0	0	0
12:45	13:00	0	0	0	0	0
13:00	13:15	0	0	0	0	0
13:15	13:30	0	0	0	0	0
15:00	15:15	0	0	0	0	0
15:15	15:30	0	0	0	0	0
15:30	15:45	0	0	0	0	0
15:45	16:00	0	0	0	0	0
16:00	16:15	0	0	0	0	0
16:15	16:30	0	0	0	0	0
16:30	16:45	0	0	0	0	0
16:45	17:00	0	0	0	0	0
17:00	17:15	0	0	0	0	0
17:15	17:30	0	0	0	0	0
17:30	17:45	0	0	0	0	0
17:45	18:00	0	0	0	0	0
Total		0	0	0	0	0



Transportation Services - Traffic Services


Turning Movement Count - Study Results

GLADSTONE AVE @ ARTHUR ST/ARTHUR LANE

Survey Date: Wednesday, July 27, 2016
Start Time: 07:00

WO No: 36094
Device: Miovision

Full Study Diagram



Transportation Services - Traffic Services


Turning Movement Count - Study Results

GLADSTONE AVE @ ARTHUR ST/ARTHUR LANE

Survey Date: Wednesday, July 27, 2016
Start Time: 07:00

WO No: 36094
Device: Miovision

Full Study Peak Hour Diagram






Transportation Services - Traffic Services

Turning Movement Count - Peak Hour Diagram

GLADSTONE AVE @ ARTHUR ST/ARTHUR LANE

Survey Date: Wednesday, July 27, 2016
Start Time: 07:00

WO No: 36094
Device: Miovision




Transportation Services - Traffic Services

Turning Movement Count - Peak Hour Diagram

GLADSTONE AVE @ ARTHUR ST/ARTHUR LANE

Survey Date: Wednesday, July 27, 2016
Start Time: 07:00

WO No: 36094
Device: Miovision






Transportation Services - Traffic Services

Turning Movement Count - Peak Hour Diagram

GLADSTONE AVE @ ARTHUR ST/ARTHUR LANE

Survey Date: Wednesday, July 27, 2016
Start Time: 07:00

WO No: 36094
Device: Miovision



Transportation Services - Traffic Services

Turning Movement Count - Study Results

GLADSTONE AVE @ ARTHUR ST/ARTHUR LANE

Survey Date: Wednesday, July 27, 2016
Start Time: 07:00

WO No: 36094
Device: Miovision

Full Study Summary (8 HR Standard)

Survey Date: Wednesday, July 27, 2016

Total Observed U-Turns
Northbound: 0 Southbound: 0
Eastbound: 1 Westbound: 0

AADT Factor .90

Period	ARTHUR ST/ARTHUR LANE									GLADSTONE AVE									Grand Total
	Northbound			NB TOT	Southbound			SB TOT	STR TOT	Eastbound			Westbound			WB TOT	STR TOT		
	LT	ST	RT		LT	ST	RT			LT	ST	RT	LT	ST	RT				
07:00-08:00	0	0	0	0	1	0	8	9	9	9	291	1	301	0	195	4	199	500	509
08:00-09:00	0	0	0	0	11	0	13	24	24	24	405	2	431	1	287	9	297	728	752
09:00-10:00	0	0	0	0	9	0	24	33	33	27	339	6	372	1	246	15	262	634	667
11:30-12:30	0	0	0	0	16	0	38	54	54	25	422	4	451	3	301	10	314	765	819
12:30-13:30	0	0	1	1	9	0	26	35	36	20	475	2	497	2	315	14	331	828	864
15:00-16:00	0	0	0	0	16	1	28	45	45	18	403	4	425	0	340	12	352	777	822
16:00-17:00	0	0	0	0	11	2	50	63	63	26	393	6	425	1	516	11	528	953	1016
17:00-18:00	0	0	0	0	19	2	37	58	58	27	406	0	433	1	406	11	418	851	909
Sub Total	0	0	1	1	92	5	224	321	322	176	3134	25	3335	9	2606	86	2701	6036	6358
U Turns	0	0	0	0	0	0	0	0	0	1	0	0	1	0	0	0	1	1	1
Total	0	0	1	1	92	5	224	321	322	177	3134	25	3336	9	2606	86	2701	6037	6359
EQ 12Hr	0	0	1	1	128	7	311	446	447	246	4356	35	4637	13	3622	120	3755	8392	8839
Note: These values are calculated by multiplying the totals by the appropriate expansion factor.															1.39				
AVG 12Hr	0	0	1	1	115	6	280	401	402	221	3920	32	4173	12	3260	108	3380	7553	7955
Note: These volumes are calculated by multiplying the Equivalent 12 hr. totals by the AADT factor.															.90				
AVG 24Hr	0	0	1	1	151	8	367	526	527	290	5135	42	5467	16	4271	141	4428	9895	10422
Note: These volumes are calculated by multiplying the Average Daily 12 hr. totals by 12 to 24 expansion factor.															1.31				
Note: U-Turns provided for approach totals. Refer to 'U-Turn' Report for specific breakdown.																			



Transportation Services - Traffic Services

Turning Movement Count - Study Results

GLADSTONE AVE @ ARTHUR ST/ARTHUR LANE

Survey Date: Wednesday, July 27, 2016

WO No: 36094

Start Time: 07:00

Device: Miovision

Full Study 15 Minute Increments

Table with columns for Time Period, Northbound (LT, ST, RT, N TOT, STR TOT), Southbound (LT, ST, RT, S TOT, STR TOT), Eastbound (LT, ST, RT, E TOT), Westbound (LT, ST, RT, W TOT, STR TOT), Grand Total. Rows show 15-minute intervals from 07:00 to 18:00.

Note: U-Turns are included in Totals.



Transportation Services - Traffic Services

Turning Movement Count - Study Results

GLADSTONE AVE @ ARTHUR ST/ARTHUR LANE

Survey Date: Wednesday, July 27, 2016

WO No: 36094

Start Time: 07:00

Device: Miovision

Full Study Cyclist Volume

Table with columns for Time Period, Northbound, Southbound, Street Total, Eastbound, Westbound, Street Total, Grand Total. Rows show 15-minute intervals from 07:00 to 18:00.



Transportation Services - Traffic Services

Turning Movement Count - Study Results

GLADSTONE AVE @ ARTHUR ST/ARTHUR LANE

Survey Date: Wednesday, July 27, 2016

WO No: 36094

Start Time: 07:00

Device: Miovision

Full Study Pedestrian Volume

ARTHUR ST/ARTHUR LANE GLADSTONE AVE

Table with columns: Time Period, NB Approach (E or W Crossing), SB Approach (E or W Crossing), Total, EB Approach (N or S Crossing), WB Approach (N or S Crossing), Total, Grand Total. Rows show pedestrian volume data from 07:00 to 18:00.



Transportation Services - Traffic Services

Turning Movement Count - Study Results

GLADSTONE AVE @ ARTHUR ST/ARTHUR LANE

Survey Date: Wednesday, July 27, 2016

WO No: 36094

Start Time: 07:00

Device: Miovision

Full Study Heavy Vehicles

ARTHUR ST/ARTHUR LANE GLADSTONE AVE

Table with columns: Time Period, Northbound (LT, ST, RT, N TOT), Southbound (LT, ST, RT, S TOT, STR TOT), Eastbound (LT, ST, RT, E TOT), Westbound (LT, ST, RT, W TOT, STR TOT), Grand Total. Rows show heavy vehicle volume data from 07:00 to 18:00.



Transportation Services - Traffic Services

Turning Movement Count - Study Results

GLADSTONE AVE @ ARTHUR ST/ARTHUR LANE

Survey Date: Wednesday, July 27, 2016

WO No: 36094

Start Time: 07:00

Device: Miovision

Full Study 15 Minute U-Turn Total

Time Period	ARTHUR ST/ARTHUR LANE		GLADSTONE AVE		Total
	Northbound U-Turn Total	Southbound U-Turn Total	Eastbound U-Turn Total	Westbound U-Turn Total	
07:00 - 07:15	0	0	0	0	0
07:15 - 07:30	0	0	0	0	0
07:30 - 07:45	0	0	0	0	0
07:45 - 08:00	0	0	0	0	0
08:00 - 08:15	0	0	0	0	0
08:15 - 08:30	0	0	1	0	1
08:30 - 08:45	0	0	0	0	0
08:45 - 09:00	0	0	0	0	0
09:00 - 09:15	0	0	0	0	0
09:15 - 09:30	0	0	0	0	0
09:30 - 09:45	0	0	0	0	0
09:45 - 10:00	0	0	0	0	0
11:30 - 11:45	0	0	0	0	0
11:45 - 12:00	0	0	0	0	0
12:00 - 12:15	0	0	0	0	0
12:15 - 12:30	0	0	0	0	0
12:30 - 12:45	0	0	0	0	0
12:45 - 13:00	0	0	0	0	0
13:00 - 13:15	0	0	0	0	0
13:15 - 13:30	0	0	0	0	0
15:00 - 15:15	0	0	0	0	0
15:15 - 15:30	0	0	0	0	0
15:30 - 15:45	0	0	0	0	0
15:45 - 16:00	0	0	0	0	0
16:00 - 16:15	0	0	0	0	0
16:15 - 16:30	0	0	0	0	0
16:30 - 16:45	0	0	0	0	0
16:45 - 17:00	0	0	0	0	0
17:00 - 17:15	0	0	0	0	0
17:15 - 17:30	0	0	0	0	0
17:30 - 17:45	0	0	0	0	0
17:45 - 18:00	0	0	0	0	0
Total	0	0	1	0	1



Transportation Services - Traffic Services

Turning Movement Count - Study Results

BOOTH ST @ RAYMOND ST


Survey Date: Thursday, September 01, 2016

WO No: 36266

Start Time: 07:00

Device: Miovision

Full Study Diagram





Transportation Services - Traffic Services

Turning Movement Count - Study Results

BOOTH ST @ RAYMOND ST


Survey Date: Thursday, September 01, 2016

WO No: 36266

Start Time: 07:00

Device: Miovision

Full Study Peak Hour Diagram



Transportation Services - Traffic Services

Turning Movement Count - Study Results

BOOTH ST @ RAYMOND ST

Survey Date: Thursday, September 01, 2016

WO No: 36266

Start Time: 07:00

Device: Miovision

Full Study Summary (8 HR Standard)

Survey Date: Thursday, September 01, 2016

Total Observed U-Turns

Northbound:	0	Southbound:	1
Eastbound:	0	Westbound:	0

AADT Factor

1.00

Period	BOOTH ST				RAYMOND ST								Grand Total						
	Northbound		Southbound		Eastbound				Westbound										
	LT	ST	RT	NB TOT	LT	ST	RT	SB TOT	STR TOT	LT	ST	RT	EB TOT	LT	ST	RT	WB TOT	STR TOT	
07:00 08:00	19	251	0	270	0	149	25	174	444	0	0	0	0	94	190	99	383	383	827
08:00 09:00	37	373	0	410	0	186	32	218	628	0	0	0	0	124	218	108	450	450	1078
09:00 10:00	29	250	0	279	0	144	31	175	454	0	0	0	0	106	201	102	409	409	863
11:30 12:30	33	264	0	297	0	128	45	173	470	0	0	0	0	69	172	105	346	346	816
12:30 13:30	28	268	0	296	0	145	55	200	496	0	0	0	0	69	156	101	326	326	822
15:00 16:00	35	323	0	358	0	284	84	368	726	0	0	0	0	160	273	163	596	596	1322
16:00 17:00	38	343	0	381	0	427	89	516	897	0	0	0	0	160	341	170	671	671	1568
17:00 18:00	16	328	0	344	0	386	69	455	799	0	0	0	0	173	299	208	680	680	1479
Sub Total	235	2400	0	2635	0	1849	430	2279	4914	0	0	0	0	955	1850	1056	3861	3861	8775
U Turns				0				1	1				0				0	0	1
Total	235	2400	0	2635	0	1849	430	2280	4915	0	0	0	0	955	1850	1056	3861	3861	8776
EQ 12Hr	327	3336	0	3663	0	2570	598	3169	6832	0	0	0	0	1327	2572	1468	5367	5367	12199
Note: These values are calculated by multiplying the totals by the appropriate expansion factor.													1.39						
AVG 12Hr	308	3144	0	3452	0	2422	563	2987	6832	0	0	0	0	1251	2424	1383	5058	5367	12199
Note: These volumes are calculated by multiplying the Equivalent 12 hr. totals by the AADT factor.													1						
AVG 24Hr	403	4119	0	4522	0	3173	738	3913	8435	0	0	0	0	1639	3175	1812	6626	6626	15061
Note: These volumes are calculated by multiplying the Average Daily 12 hr. totals by 12 to 24 expansion factor.													1.31						
Note: U-Turns provided for approach totals. Refer to 'U-Turn' Report for specific breakdown.																			




Transportation Services - Traffic Services

Turning Movement Count - Peak Hour Diagram

BOOTH ST @ RAYMOND ST

Survey Date: Thursday, September 01, 2016
Start Time: 07:00

WO No: 36266
Device: Miovision




Transportation Services - Traffic Services

Turning Movement Count - Peak Hour Diagram

BOOTH ST @ RAYMOND ST

Survey Date: Thursday, September 01, 2016
Start Time: 07:00

WO No: 36266
Device: Miovision






Transportation Services - Traffic Services
Turning Movement Count - Peak Hour Diagram
BOOTH ST @ RAYMOND ST

Survey Date: Thursday, September 01, 2016
Start Time: 07:00

WO No: 36266
Device: Miovision



Comments



Transportation Services - Traffic Services
Turning Movement Count - Study Results
BOOTH ST @ RAYMOND ST

Survey Date: Thursday, September 01, 2016
Start Time: 07:00

WO No: 36266
Device: Miovision

Full Study 15 Minute Increments

		BOOTH ST				RAYMOND ST														
		Northbound		Southbound		Eastbound		Westbound												
Time Period		LT	ST	RT	N TOT	LT	ST	RT	S TOT	STR TOT	LT	ST	RT	E TOT	LT	ST	RT	W TOT	STR TOT	Grand Total
07:00	07:15	4	54	0	58	0	24	4	28	0	0	0	0	0	16	37	23	76	0	162
07:15	07:30	3	58	0	61	0	27	9	37	6	0	0	0	0	24	40	22	86	6	184
07:30	07:45	4	52	0	56	0	44	4	48	0	0	0	0	0	26	53	26	105	0	209
07:45	08:00	8	87	0	95	0	54	8	62	6	0	0	0	0	28	60	28	116	6	273
08:00	08:15	7	83	0	90	0	49	12	61	0	0	0	0	0	39	36	34	109	0	260
08:15	08:30	9	111	0	120	0	51	7	58	0	0	0	0	0	31	64	25	120	0	298
08:30	08:45	14	97	0	111	0	49	7	56	3	0	0	0	0	24	58	21	103	3	270
08:45	09:00	7	82	0	89	0	37	6	43	0	0	0	0	0	30	60	28	118	0	250
09:00	09:15	12	65	0	77	0	37	12	49	1	0	0	0	0	28	59	26	113	1	239
09:15	09:30	6	75	0	81	0	42	5	47	5	0	0	0	0	26	53	28	107	5	235
09:30	09:45	7	52	0	59	0	31	6	37	0	0	0	0	0	31	43	24	98	0	194
09:45	10:00	4	58	0	62	0	34	8	42	5	0	0	0	0	21	46	24	91	5	195
11:30	11:45	10	58	0	68	0	27	5	32	1	0	0	0	0	17	37	24	78	1	178
11:45	12:00	7	70	0	77	0	27	14	41	3	0	0	0	0	19	44	27	90	3	208
12:00	12:15	8	74	0	82	0	41	14	55	1	0	0	0	0	17	52	27	96	1	233
12:15	12:30	8	62	0	70	0	33	12	45	0	0	0	0	0	16	39	27	82	0	197
12:30	12:45	13	73	0	86	0	33	11	44	3	0	0	0	0	14	46	16	76	3	206
12:45	13:00	4	65	0	69	0	36	10	46	3	0	0	0	0	15	37	21	73	3	188
13:00	13:15	6	66	0	72	0	38	17	55	3	0	0	0	0	20	35	37	92	3	219
13:15	13:30	5	64	0	69	0	38	17	55	4	0	0	0	0	20	38	27	85	4	209
15:00	15:15	18	86	0	104	0	53	18	71	2	0	0	0	0	45	75	49	169	2	344
15:15	15:30	5	65	0	70	0	87	25	112	0	0	0	0	0	45	72	39	156	0	338
15:30	15:45	8	84	0	92	0	61	22	83	0	0	0	0	0	24	64	36	124	0	299
15:45	16:00	4	88	0	92	0	83	19	102	2	0	0	0	0	46	62	39	147	2	341
16:00	16:15	10	95	0	105	0	75	18	93	1	0	0	0	0	30	86	36	152	1	350
16:15	16:30	10	98	0	108	0	112	19	131	2	0	0	0	0	44	84	50	178	2	417
16:30	16:45	8	67	0	75	0	120	27	147	1	0	0	0	0	40	79	38	157	1	379
16:45	17:00	10	83	0	93	0	120	25	145	2	0	0	0	0	46	92	46	184	2	422
17:00	17:15	3	84	0	87	0	116	19	135	1	0	0	0	0	47	76	60	183	1	405
17:15	17:30	3	78	0	81	0	104	12	116	0	0	0	0	0	53	76	47	176	0	373
17:30	17:45	5	70	0	75	0	83	12	95	0	0	0	0	0	43	74	48	165	0	335
17:45	18:00	5	96	0	101	0	83	26	109	3	0	0	0	0	30	73	53	156	3	366
Total:		235	2400	0	2635	0	1849	430	2280	58	0	0	0	0	955	1850	1056	3861	58	8,776

Note: U-Turns are included in Totals.



Transportation Services - Traffic Services

Turning Movement Count - Study Results

BOOTH ST @ RAYMOND ST

Survey Date: Thursday, September 01, 2016

WO No: 36266

Start Time: 07:00

Device: Miovision

Full Study Cyclist Volume

Table with columns: Time Period, Northbound, Southbound, Street Total, Eastbound, Westbound, Street Total, Grand Total. Rows show cyclist volume data from 07:00 to 18:00.



Transportation Services - Traffic Services

Turning Movement Count - Study Results

BOOTH ST @ RAYMOND ST

Survey Date: Thursday, September 01, 2016

WO No: 36266

Start Time: 07:00

Device: Miovision

Full Study Pedestrian Volume

Table with columns: Time Period, NB Approach, SB Approach, Total, EB Approach, WB Approach, Total, Grand Total. Rows show pedestrian volume data from 07:00 to 18:00.



Transportation Services - Traffic Services

Turning Movement Count - Study Results

BOOTH ST @ RAYMOND ST

Survey Date: Thursday, September 01, 2016

WO No: 36266

Start Time: 07:00

Device: Miovision

Full Study Heavy Vehicles

Table with columns for Time Period, Northbound (LT, ST, RT, N TOT, STR TOT), Southbound (LT, ST, RT, S TOT, STR TOT), Eastbound (LT, ST, RT, E TOT), Westbound (LT, ST, RT, W TOT, STR TOT), and Grand Total. Rows represent 15-minute intervals from 07:00 to 18:00.



Transportation Services - Traffic Services

Turning Movement Count - Study Results

BOOTH ST @ RAYMOND ST

Survey Date: Thursday, September 01, 2016

WO No: 36266

Start Time: 07:00

Device: Miovision

Full Study 15 Minute U-Turn Total

Table with columns for Time Period, Northbound U-Turn Total, Southbound U-Turn Total, Eastbound U-Turn Total, Westbound U-Turn Total, and Total. Rows represent 15-minute intervals from 07:00 to 18:00.

Appendix C

Synchro Intersection Worksheets – Existing Conditions

Lanes, Volumes, Timings
1: Bronson & Raymond/Catherine

Existing AM Peak Hour
18 Louisa Street

Lane Group	WBL	WBT	NBL	NBT	SBT	Ø5	Ø9
Lane Configurations	↔↔↔	↔↔↔	↔↔	↔↔	↔↔		
Traffic Volume (vph)	492	479	519	1038	428		
Future Volume (vph)	492	479	519	1038	428		
Lane Group Flow (vph)	372	1091	577	1153	607		
Turn Type	Perm	NA	pm+pt	NA	NA		
Protected Phases		8	5 9	2	6	5	9
Permitted Phases	8		2	9			
Detector Phase	8	8	5 9	2	6		
Switch Phase							
Minimum Initial (s)	10.0	10.0		10.0	10.0	5.0	5.0
Minimum Split (s)	28.3	28.3		24.8	24.8	11.8	11.8
Total Split (s)	34.0	34.0		53.0	33.0	20.0	23.0
Total Split (%)	30.9%	30.9%		48.2%	30.0%	18%	21%
Maximum Green (s)	27.7	27.7		46.2	26.2	13.2	16.8
Yellow Time (s)	3.3	3.3		3.3	3.3	3.3	3.3
All-Red Time (s)	3.0	3.0		3.5	3.5	3.5	2.9
Lost Time Adjust (s)	0.0	0.0		0.0	0.0		
Total Lost Time (s)	6.3	6.3		6.8	6.8		
Lead/Lag				Lead	Lag		
Lead-Lag Optimize?				Yes	Yes		
Vehicle Extension (s)	3.0	3.0		3.0	3.0	3.0	3.0
Recall Mode	Max	Max		C-Max	C-Max	Max	Max
Walk Time (s)	7.0	7.0		7.0	7.0		
Flash Dont Walk (s)	15.0	15.0		10.0	10.0		
Pedestrian Calls (#/hr)	40	40		45	26		
Act Effct Green (s)	27.7	27.7		62.4	69.2	26.2	
Actuated g/C Ratio	0.25	0.25		0.57	0.63	0.24	
v/c Ratio	1.06	1.01		0.98	0.55	0.82	
Control Delay	104.4	69.0		54.6	12.9	45.3	
Queue Delay	0.0	0.0		0.0	0.0	17.7	
Total Delay	104.4	69.0		54.6	12.9	63.0	
LOS	F	E		D	B	E	
Approach Delay		78.0			26.8	63.0	
Approach LOS		E			C	E	
Queue Length 50th (m)	~102.0	~87.7		65.1	68.4	62.4	
Queue Length 95th (m)	#168.1	#120.8		#142.4	85.5	#85.8	
Internal Link Dist (m)		247.5			81.5	56.5	
Turn Bay Length (m)	110.0			45.0			
Base Capacity (vph)	352	1077		586	2086	741	
Starvation Cap Reductn	0	0		0	0	136	
Spillback Cap Reductn	0	0		0	0	52	
Storage Cap Reductn	0	0		0	0	0	
Reduced v/c Ratio	1.06	1.01		0.98	0.57	1.00	

Intersection Summary


Cycle Length: 110
Actuated Cycle Length: 110
Offset: 38 (35%), Referenced to phase 2:NBT and 6:SBT, Start of Green
Natural Cycle: 110

Lanes, Volumes, Timings
1: Bronson & Raymond/Catherine

Existing AM Peak Hour
18 Louisa Street

Control Type: Actuated-Coordinated	
Maximum v/c Ratio: 1.06	
Intersection Signal Delay: 52.3	Intersection LOS: D
Intersection Capacity Utilization 86.2%	ICU Level of Service E
Analysis Period (min) 15	
~ Volume exceeds capacity, queue is theoretically infinite. Queue shown is maximum after two cycles.	
# 95th percentile volume exceeds capacity, queue may be longer. Queue shown is maximum after two cycles.	

Splits and Phases: 1: Bronson & Raymond/Catherine



Lanes, Volumes, Timings
2: Bronson & Arlington

Existing AM Peak Hour
18 Louisa Street

	↖	→	↗	←	↖	↑	↗	↓
Lane Group	EBL	EBT	WBL	WBT	NBL	NBT	SBL	SBT
Lane Configurations		↕		↕		↕		↕
Traffic Volume (vph)	9	4	8	2	13	1365	2	514
Future Volume (vph)	9	4	8	2	13	1365	2	514
Lane Group Flow (vph)	0	41	0	23	0	1538	0	589
Turn Type	Perm	NA	Perm	NA	Perm	NA	Perm	NA
Protected Phases		4		8		2		6
Permitted Phases	4		8		2		6	
Detector Phase	4	4	8	8	2	2	6	6
Switch Phase								
Minimum Initial (s)	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0
Minimum Split (s)	22.6	22.6	22.6	22.6	17.2	17.2	17.2	17.2
Total Split (s)	23.0	23.0	23.0	23.0	87.0	87.0	87.0	87.0
Total Split (%)	20.9%	20.9%	20.9%	20.9%	79.1%	79.1%	79.1%	79.1%
Maximum Green (s)	17.4	17.4	17.4	17.4	81.8	81.8	81.8	81.8
Yellow Time (s)	3.3	3.3	3.3	3.3	3.3	3.3	3.3	3.3
All-Red Time (s)	2.3	2.3	2.3	2.3	1.9	1.9	1.9	1.9
Lost Time Adjust (s)		0.0		0.0		0.0		0.0
Total Lost Time (s)		5.6		5.6		5.2		5.2
Lead/Lag								
Lead-Lag Optimize?								
Vehicle Extension (s)	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0
Recall Mode	None	None	None	None	C-Max	C-Max	C-Max	C-Max
Walk Time (s)	7.0	7.0	7.0	7.0	7.0	7.0	7.0	7.0
Flash Dont Walk (s)	10.0	10.0	10.0	10.0	5.0	5.0	5.0	5.0
Pedestrian Calls (#/hr)	23	23	19	19	21	21	27	27
Act Effct Green (s)		12.8		12.8		90.6		90.6
Actuated g/C Ratio		0.12		0.12		0.82		0.82
v/c Ratio		0.22		0.15		0.60		0.24
Control Delay		23.9		28.6		5.0		3.3
Queue Delay		0.0		0.0		0.0		0.0
Total Delay		23.9		28.6		5.0		3.4
LOS		C		C		A		A
Approach Delay		23.9		28.6		5.0		3.4
Approach LOS		C		C		A		A
Queue Length 50th (m)		2.8		2.2		32.8		11.9
Queue Length 95th (m)		12.3		9.4		m48.3		23.3
Internal Link Dist (m)		0.1		230.9		56.5		207.2
Turn Bay Length (m)								
Base Capacity (vph)		243		210		2556		2462
Starvation Cap Reductn		0		0		97		0
Spillback Cap Reductn		3		1		0		456
Storage Cap Reductn		0		0		0		0
Reduced v/c Ratio		0.17		0.11		0.63		0.29

Intersection Summary


Cycle Length: 110
Actuated Cycle Length: 110
Offset: 11 (10%), Referenced to phase 2:NBT and 6:SBTL, Start of Green
Natural Cycle: 60

Lanes, Volumes, Timings
2: Bronson & Arlington

Existing AM Peak Hour
18 Louisa Street

Control Type: Actuated-Coordinated
Maximum v/c Ratio: 0.60
Intersection Signal Delay: 5.2
Intersection LOS: A
Intersection Capacity Utilization 70.1%
ICU Level of Service C
Analysis Period (min) 15
Volume for 95th percentile queue is metered by upstream signal.

Splits and Phases: 2: Bronson & Arlington



Lanes, Volumes, Timings
3: Bronson & Gladstone

Existing AM Peak Hour
18 Louisa Street

	↖	→	↗	←	↖	↑	↗	↓
Lane Group	EBL	EBT	WBL	WBT	NBL	NBT	SBL	SBT
Lane Configurations	↖	↗	↖	↗	↖	↗	↖	↗
Traffic Volume (vph)	46	248	83	155	123	1076	13	384
Future Volume (vph)	46	248	83	155	123	1076	13	384
Lane Group Flow (vph)	51	375	92	192	137	1363	14	470
Turn Type	Perm	NA	Perm	NA	Perm	NA	Perm	NA
Protected Phases		4		8		2		6
Permitted Phases	4		8		2		6	
Detector Phase	4	4	8	8	2	2	6	6
Switch Phase								
Minimum Initial (s)	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0
Minimum Split (s)	28.2	28.2	28.2	28.2	25.0	25.0	25.0	25.0
Total Split (s)	37.0	37.0	37.0	37.0	58.0	58.0	58.0	58.0
Total Split (%)	38.9%	38.9%	38.9%	38.9%	61.1%	61.1%	61.1%	61.1%
Maximum Green (s)	30.8	30.8	30.8	30.8	52.0	52.0	52.0	52.0
Yellow Time (s)	3.0	3.0	3.0	3.0	3.3	3.3	3.3	3.3
All-Red Time (s)	3.2	3.2	3.2	3.2	2.7	2.7	2.7	2.7
Lost Time Adjust (s)	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
Total Lost Time (s)	6.2	6.2	6.2	6.2	6.0	6.0	6.0	6.0
Lead/Lag								
Lead-Lag Optimize?								
Vehicle Extension (s)	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0
Recall Mode	Max	Max	Max	Max	C-Max	C-Max	C-Max	C-Max
Walk Time (s)	7.0	7.0	7.0	7.0	7.0	7.0	7.0	7.0
Flash Dont Walk (s)	15.0	15.0	15.0	15.0	12.0	12.0	12.0	12.0
Pedestrian Calls (/hr)	85	85	36	36	36	36	31	31
Act Effct Green (s)	30.8	30.8	30.8	30.8	52.0	52.0	52.0	52.0
Actuated g/C Ratio	0.32	0.32	0.32	0.32	0.55	0.55	0.55	0.55
v/c Ratio	0.15	0.73	0.49	0.36	0.32	0.78	0.14	0.27
Control Delay	24.5	38.0	36.3	27.0	14.3	21.1	14.7	12.0
Queue Delay	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
Total Delay	24.5	38.0	36.3	27.0	14.3	21.1	14.7	12.0
LOS	C	D	D	C	B	C	B	B
Approach Delay		36.4		30.0		20.5		12.0
Approach LOS		D		C		C		B
Queue Length 50th (m)	6.6	60.3	13.4	26.7	13.0	98.0	1.2	22.7
Queue Length 95th (m)	15.3	93.3	29.5	44.9	25.4	126.3	4.9	31.7
Internal Link Dist (m)		139.3		203.3		207.2		176.5
Turn Bay Length (m)	20.0		20.0		35.0		45.0	
Base Capacity (vph)	331	516	189	533	431	1742	101	1722
Starvation Cap Reductn	0	0	0	0	0	0	0	0
Spillback Cap Reductn	0	0	0	0	0	0	0	0
Storage Cap Reductn	0	0	0	0	0	0	0	0
Reduced v/c Ratio	0.15	0.73	0.49	0.36	0.32	0.78	0.14	0.27

Intersection Summary

Cycle Length: 95
 Actuated Cycle Length: 95
 Offset: 42 (44%), Referenced to phase 2:NBL and 6:SBTL, Start of Green
 Natural Cycle: 65

Lanes, Volumes, Timings
3: Bronson & Gladstone

Existing AM Peak Hour
18 Louisa Street

Control Type: Actuated-Coordinated	
Maximum v/c Ratio: 0.78	
Intersection Signal Delay: 22.5	Intersection LOS: C
Intersection Capacity Utilization 94.8%	ICU Level of Service F
Analysis Period (min) 15	

Splits and Phases: 3: Bronson & Gladstone



Lanes, Volumes, Timings
4: Booth & Gladstone

Existing AM Peak Hour
18 Louisa Street

	↖	→	↗	←	↖	↑	↗	↓
Lane Group	EBL	EBT	WBL	WBT	NBL	NBT	SBL	SBT
Lane Configurations	↖	↗	↖	↗	↖	↗	↖	↗
Traffic Volume (vph)	26	300	42	230	51	330	38	130
Future Volume (vph)	26	300	42	230	51	330	38	130
Lane Group Flow (vph)	29	412	47	290	57	453	42	166
Turn Type	Perm	NA	Perm	NA	Perm	NA	Perm	NA
Protected Phases		2		6		4		8
Permitted Phases	2		6		4		8	
Detector Phase	2	2	6	6	4	4	8	8
Switch Phase								
Minimum Initial (s)	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0
Minimum Split (s)	22.1	22.1	22.1	22.1	23.9	23.9	23.9	23.9
Total Split (s)	28.0	28.0	28.0	28.0	32.0	32.0	32.0	32.0
Total Split (%)	46.7%	46.7%	46.7%	46.7%	53.3%	53.3%	53.3%	53.3%
Maximum Green (s)	21.9	21.9	21.9	21.9	25.1	25.1	25.1	25.1
Yellow Time (s)	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0
All-Red Time (s)	3.1	3.1	3.1	3.1	3.9	3.9	3.9	3.9
Lost Time Adjust (s)	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
Total Lost Time (s)	6.1	6.1	6.1	6.1	6.9	6.9	6.9	6.9
Lead/Lag								
Lead-Lag Optimize?								
Vehicle Extension (s)	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0
Recall Mode	C-Max	C-Max	C-Max	C-Max	Max	Max	Max	Max
Walk Time (s)	7.0	7.0	7.0	7.0	7.0	7.0	7.0	7.0
Flash Dont Walk (s)	9.0	9.0	9.0	9.0	10.0	10.0	10.0	10.0
Pedestrian Calls (#/hr)	43	43	28	28	29	29	0	0
Act Effct Green (s)	21.9	21.9	21.9	21.9	25.1	25.1	25.1	25.1
Actuated g/C Ratio	0.36	0.36	0.36	0.36	0.42	0.42	0.42	0.42
v/c Ratio	0.09	0.69	0.19	0.48	0.12	0.64	0.15	0.23
Control Delay	13.5	22.7	15.6	17.2	9.9	13.3	12.5	11.2
Queue Delay	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
Total Delay	13.5	22.7	15.6	17.2	9.9	13.3	12.5	11.2
LOS	B	C	B	B	A	B	B	B
Approach Delay		22.1		16.9		12.9		11.4
Approach LOS		C		B		B		B
Queue Length 50th (m)	2.0	35.3	3.4	22.6	2.3	17.3	2.7	10.1
Queue Length 95th (m)	6.6	#64.4	10.0	41.3	m6.7	37.1	8.3	20.6
Internal Link Dist (m)		79.0		246.0		206.0		98.4
Turn Bay Length (m)	40.0		25.0		8.0		8.0	
Base Capacity (vph)	332	597	243	609	473	712	288	721
Starvation Cap Reductn	0	0	0	0	0	0	0	0
Spillback Cap Reductn	0	0	0	0	0	0	0	0
Storage Cap Reductn	0	0	0	0	0	0	0	0
Reduced v/c Ratio	0.09	0.69	0.19	0.48	0.12	0.64	0.15	0.23

Intersection Summary


Cycle Length: 60
 Actuated Cycle Length: 60
 Offset: 16 (27%), Referenced to phase 2:EBTL and 6:WBTL, Start of Green
 Natural Cycle: 50

Lanes, Volumes, Timings
4: Booth & Gladstone

Existing AM Peak Hour
18 Louisa Street

Control Type: Actuated-Coordinated	
Maximum v/c Ratio: 0.69	
Intersection Signal Delay: 16.3	Intersection LOS: B
Intersection Capacity Utilization 84.0%	ICU Level of Service E
Analysis Period (min) 15	
# 95th percentile volume exceeds capacity, queue may be longer.	
Queue shown is maximum after two cycles.	
m Volume for 95th percentile queue is metered by upstream signal.	

Splits and Phases: 4: Booth & Gladstone



Lanes, Volumes, Timings
5: Arthur & Gladstone

Existing AM Peak Hour
18 Louisa Street

	↖	→	←	↓
Lane Group	EBL	EBT	WBT	SBT
Lane Configurations		↕	↕	↕
Traffic Volume (vph)	30	380	293	0
Future Volume (vph)	30	380	293	0
Lane Group Flow (vph)	0	456	342	40
Turn Type	Perm	NA	NA	NA
Protected Phases		2	6	8
Permitted Phases	2			
Detector Phase	2	2	6	8
Switch Phase				
Minimum Initial (s)	10.0	10.0	10.0	10.0
Minimum Split (s)	29.5	29.5	29.5	23.2
Total Split (s)	31.8	31.8	31.8	23.2
Total Split (%)	57.8%	57.8%	57.8%	42.2%
Maximum Green (s)	26.3	26.3	26.3	18.0
Yellow Time (s)	3.0	3.0	3.0	3.0
All-Red Time (s)	2.5	2.5	2.5	2.2
Lost Time Adjust (s)		0.0	0.0	0.0
Total Lost Time (s)		5.5	5.5	5.2
Lead/Lag				
Lead-Lag Optimize?				
Vehicle Extension (s)	3.0	3.0	3.0	3.0
Recall Mode	Max	Max	Max	None
Walk Time (s)	19.0	19.0	19.0	10.0
Flash Dont Walk (s)	5.0	5.0	5.0	8.0
Pedestrian Calls (#/hr)	84	84	44	35
Act Effct Green (s)		41.3	41.3	13.1
Actuated g/C Ratio		0.74	0.74	0.24
v/c Ratio		0.37	0.27	0.10
Control Delay		7.8	6.8	5.0
Queue Delay		0.0	0.0	0.0
Total Delay		7.8	6.8	5.0
LOS		A	A	A
Approach Delay		7.8	6.8	5.0
Approach LOS		A	A	A
Queue Length 50th (m)		19.5	13.1	0.0
Queue Length 95th (m)		53.5	36.6	4.2
Internal Link Dist (m)		246.0	139.3	183.9
Turn Bay Length (m)				
Base Capacity (vph)		1229	1246	523
Starvation Cap Reductn		0	0	0
Spillback Cap Reductn		0	0	0
Storage Cap Reductn		0	0	0
Reduced v/c Ratio		0.37	0.27	0.08

Intersection Summary	
Cycle Length:	55
Actuated Cycle Length:	55.5
Natural Cycle:	55
Control Type:	Actuated-Uncoordinated

Lanes, Volumes, Timings
5: Arthur & Gladstone

Existing AM Peak Hour
18 Louisa Street

Maximum v/c Ratio: 0.37	Intersection LOS: A
Intersection Signal Delay: 7.3	ICU Level of Service C
Intersection Capacity Utilization 67.6%	
Analysis Period (min) 15	

Splits and Phases: 5: Arthur & Gladstone



Lanes, Volumes, Timings
6: Booth & Raymond

Existing AM Peak Hour
18 Louisa Street

	←	↙	↘	↑	↓
Lane Group	WBT	WBR	NBL	NBT	SBT
Lane Configurations	↔	↔	↔	↔	↔
Traffic Volume (vph)	218	108	38	378	203
Future Volume (vph)	218	108	38	378	203
Lane Group Flow (vph)	378	120	42	420	264
Turn Type	NA	Perm	Perm	NA	NA
Protected Phases	8			2	6
Permitted Phases		8	2		
Detector Phase	8	8	2	2	6
Switch Phase					
Minimum Initial (s)	10.0	10.0	10.0	10.0	10.0
Minimum Split (s)	25.5	25.5	25.2	25.2	25.2
Total Split (s)	25.5	25.5	34.5	34.5	34.5
Total Split (%)	42.5%	42.5%	57.5%	57.5%	57.5%
Maximum Green (s)	20.0	20.0	29.3	29.3	29.3
Yellow Time (s)	3.3	3.3	3.3	3.3	3.3
All-Red Time (s)	2.2	2.2	1.9	1.9	1.9
Lost Time Adjust (s)	0.0	0.0	0.0	0.0	0.0
Total Lost Time (s)	5.5	5.5	5.2	5.2	5.2
Lead/Lag					
Lead-Lag Optimize?					
Vehicle Extension (s)	3.0	3.0	3.0	3.0	3.0
Recall Mode	Max	Max	C-Max	C-Max	C-Max
Walk Time (s)	11.0	11.0	15.0	15.0	15.0
Flash Dont Walk (s)	9.0	9.0	5.0	5.0	5.0
Pedestrian Calls (#/hr)	15	15	48	48	38
Act Effct Green (s)	20.0	20.0	29.3	29.3	29.3
Actuated g/C Ratio	0.33	0.33	0.49	0.49	0.49
v/c Ratio	0.69	0.22	0.09	0.49	0.32
Control Delay	25.4	4.6	8.9	12.9	14.2
Queue Delay	0.0	0.0	0.0	0.0	0.0
Total Delay	25.4	4.6	8.9	12.9	14.2
LOS	C	A	A	B	B
Approach Delay	20.4			12.5	14.2
Approach LOS	C			B	B
Queue Length 50th (m)	35.3	0.0	2.3	28.9	15.7
Queue Length 95th (m)	#63.8	8.9	6.6	49.4	m26.2
Internal Link Dist (m)	302.1			65.0	206.0
Turn Bay Length (m)		75.0	25.0		
Base Capacity (vph)	549	541	486	852	835
Starvation Cap Reductn	0	0	0	0	0
Spillback Cap Reductn	0	0	0	0	0
Storage Cap Reductn	0	0	0	0	0
Reduced v/c Ratio	0.69	0.22	0.09	0.49	0.32

Intersection Summary
 Cycle Length: 60
 Actuated Cycle Length: 60
 Offset: 35 (58%), Referenced to phase 2:NBL and 6:SBT, Start of Green
 Natural Cycle: 55

Lanes, Volumes, Timings
6: Booth & Raymond

Existing AM Peak Hour
18 Louisa Street

Control Type: Actuated-Coordinated
 Maximum v/c Ratio: 0.69
 Intersection Signal Delay: 16.1
 Intersection LOS: B
 Intersection Capacity Utilization 64.2%
 ICU Level of Service C
 Analysis Period (min) 15
 # 95th percentile volume exceeds capacity, queue may be longer.
 Queue shown is maximum after two cycles.
 m Volume for 95th percentile queue is metered by upstream signal.



Lanes, Volumes, Timings
1: Bronson & Raymond/Catherine

Existing PM Peak Hour
18 Louisa Street

Lane Group	WBL	WBT	NBL	NBT	SBT
Lane Configurations	↔	↔↔↔	↔	↔↔	↔↔
Traffic Volume (vph)	690	573	292	762	801
Future Volume (vph)	690	573	292	762	801
Lane Group Flow (vph)	430	1274	324	847	1073
Turn Type	Perm	NA	pm+pt	NA	NA
Protected Phases		8	5	2	6
Permitted Phases	8		2		
Detector Phase	8	8	5	2	6
Switch Phase					
Minimum Initial (s)	10.0	10.0	5.0	10.0	10.0
Minimum Split (s)	28.3	28.3	11.8	24.8	24.8
Total Split (s)	33.0	33.0	25.0	67.0	42.0
Total Split (%)	33.0%	33.0%	25.0%	67.0%	42.0%
Maximum Green (s)	26.7	26.7	18.2	60.2	35.2
Yellow Time (s)	3.3	3.3	3.3	3.3	3.3
All-Red Time (s)	3.0	3.0	3.5	3.5	3.5
Lost Time Adjust (s)	0.0	0.0	0.0	0.0	0.0
Total Lost Time (s)	6.3	6.3	6.8	6.8	6.8
Lead/Lag			Lead		Lag
Lead-Lag Optimize?			Yes		Yes
Vehicle Extension (s)	3.0	3.0	3.0	3.0	3.0
Recall Mode	Max	Max	None	C-Max	C-Max
Walk Time (s)	7.0	7.0		7.0	7.0
Flash Dont Walk (s)	15.0	15.0		10.0	10.0
Pedestrian Calls (#/hr)	24	24		29	41
Act Effct Green (s)	26.7	26.7	60.2	60.2	36.1
Actuated g/C Ratio	0.27	0.27	0.60	0.60	0.36
v/c Ratio	1.13	1.09	0.92	0.42	0.92
Control Delay	122.4	86.7	57.8	11.5	29.8
Queue Delay	0.0	0.0	0.0	0.0	12.0
Total Delay	122.4	86.7	57.8	11.5	41.8
LOS	F	F	E	B	D
Approach Delay		95.7		24.3	41.8
Approach LOS		F		C	D
Queue Length 50th (m)	~113.0	~103.8	46.8	42.7	90.5
Queue Length 95th (m)	#180.0	#134.1	#95.4	55.4	#140.8
Internal Link Dist (m)		247.5		81.5	56.5
Turn Bay Length (m)	110.0		45.0		
Base Capacity (vph)	380	1173	366	1996	1166
Starvation Cap Reductn	0	0	0	0	100
Spillback Cap Reductn	0	0	0	0	0
Storage Cap Reductn	0	0	0	0	0
Reduced v/c Ratio	1.13	1.09	0.89	0.42	1.01

Intersection Summary


Cycle Length: 100
 Actuated Cycle Length: 100
 Offset: 60 (60%), Referenced to phase 2:NBT and 6:SBT, Start of Green
 Natural Cycle: 100

Lanes, Volumes, Timings
1: Bronson & Raymond/Catherine

Existing PM Peak Hour
18 Louisa Street

Control Type: Actuated-Coordinated	
Maximum v/c Ratio: 1.13	
Intersection Signal Delay: 59.9	Intersection LOS: E
Intersection Capacity Utilization 88.2%	ICU Level of Service E
Analysis Period (min) 15	
~ Volume exceeds capacity, queue is theoretically infinite. Queue shown is maximum after two cycles.	
# 95th percentile volume exceeds capacity, queue may be longer. Queue shown is maximum after two cycles.	

Splits and Phases: 1: Bronson & Raymond/Catherine



Lanes, Volumes, Timings
2: Bronson & Arlington

Existing PM Peak Hour
18 Louisa Street


Lane Group	EBL	EBT	WBL	WBT	NBL	NBT	SBL	SBT
Lane Configurations		↕		↕		↕		↕
Traffic Volume (vph)	11	2	2	0	24	996	3	914
Future Volume (vph)	11	2	2	0	24	996	3	914
Lane Group Flow (vph)	0	70	0	15	0	1147	0	1037
Turn Type	Perm	NA	Perm	NA	Perm	NA	Perm	NA
Protected Phases		4		8		2		6
Permitted Phases	4		8		2		6	
Detector Phase	4	4	8	8	2	2	6	6
Switch Phase								
Minimum Initial (s)	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0
Minimum Split (s)	22.6	22.6	22.6	22.6	17.2	17.2	17.2	17.2
Total Split (s)	23.0	23.0	23.0	23.0	77.0	77.0	77.0	77.0
Total Split (%)	23.0%	23.0%	23.0%	23.0%	77.0%	77.0%	77.0%	77.0%
Maximum Green (s)	17.4	17.4	17.4	17.4	71.8	71.8	71.8	71.8
Yellow Time (s)	3.3	3.3	3.3	3.3	3.3	3.3	3.3	3.3
All-Red Time (s)	2.3	2.3	2.3	2.3	1.9	1.9	1.9	1.9
Lost Time Adjust (s)		0.0		0.0		0.0		0.0
Total Lost Time (s)		5.6		5.6		5.2		5.2
Lead/Lag								
Lead-Lag Optimize?								
Vehicle Extension (s)	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0
Recall Mode	None	None	None	None	C-Max	C-Max	C-Max	C-Max
Walk Time (s)	7.0	7.0	7.0	7.0	7.0	7.0	7.0	7.0
Flash Dont Walk (s)	10.0	10.0	10.0	10.0	5.0	5.0	5.0	5.0
Pedestrian Calls (#/hr)	19	19	20	20	29	29	39	39
Act Effct Green (s)		12.8		12.8		80.6		80.6
Actuated g/C Ratio		0.13		0.13		0.81		0.81
v/c Ratio		0.31		0.08		0.48		0.41
Control Delay		17.3		10.1		3.0		2.0
Queue Delay		0.0		0.0		0.0		0.1
Total Delay		17.4		10.1		3.0		2.1
LOS		B		B		A		A
Approach Delay		17.4		10.1		3.0		2.1
Approach LOS		B		B		A		A
Queue Length 50th (m)		2.5		0.0		15.0		14.1
Queue Length 95th (m)		14.2		4.0		m32.5		17.1
Internal Link Dist (m)		0.1		230.9		56.5		207.2
Turn Bay Length (m)								
Base Capacity (vph)		288		253		2395		2504
Starvation Cap Reductn		0		0		140		0
Spillback Cap Reductn		4		0		0		259
Storage Cap Reductn		0		0		0		0
Reduced v/c Ratio		0.25		0.06		0.51		0.46

Intersection Summary
 Cycle Length: 100
 Actuated Cycle Length: 100
 Offset: 29 (29%), Referenced to phase 2:NBT and 6:SBTL, Start of Green
 Natural Cycle: 60

Lanes, Volumes, Timings
2: Bronson & Arlington

Existing PM Peak Hour
18 Louisa Street

Control Type: Actuated-Coordinated
 Maximum v/c Ratio: 0.48
 Intersection Signal Delay: 3.1
 Intersection LOS: A
 Intersection Capacity Utilization 67.8%
 ICU Level of Service C
 Analysis Period (min) 15
 m Volume for 95th percentile queue is metered by upstream signal.



Lanes, Volumes, Timings
3: Bronson & Gladstone

Existing PM Peak Hour
18 Louisa Street

	↖	→	↗	←	↖	↑	↗	↓
Lane Group	EBL	EBT	WBL	WBT	NBL	NBT	SBL	SBT
Lane Configurations	↖	↗	↖	↗	↖	↗	↖	↗
Traffic Volume (vph)	46	291	137	220	96	761	49	758
Future Volume (vph)	46	291	137	220	96	761	49	758
Lane Group Flow (vph)	51	403	152	263	107	998	54	935
Turn Type	Perm	NA	Perm	NA	Perm	NA	Perm	NA
Protected Phases		4		8		2		6
Permitted Phases	4		8		2		6	
Detector Phase	4	4	8	8	2	2	6	6
Switch Phase								
Minimum Initial (s)	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0
Minimum Split (s)	28.2	28.2	28.2	28.2	25.0	25.0	25.0	25.0
Total Split (s)	50.0	50.0	50.0	50.0	50.0	50.0	50.0	50.0
Total Split (%)	50.0%	50.0%	50.0%	50.0%	50.0%	50.0%	50.0%	50.0%
Maximum Green (s)	43.8	43.8	43.8	43.8	44.0	44.0	44.0	44.0
Yellow Time (s)	3.0	3.0	3.0	3.0	3.3	3.3	3.3	3.3
All-Red Time (s)	3.2	3.2	3.2	3.2	2.7	2.7	2.7	2.7
Lost Time Adjust (s)	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
Total Lost Time (s)	6.2	6.2	6.2	6.2	6.0	6.0	6.0	6.0
Lead/Lag								
Lead-Lag Optimize?								
Vehicle Extension (s)	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0
Recall Mode	Max	Max	Max	Max	C-Max	C-Max	C-Max	C-Max
Walk Time (s)	7.0	7.0	7.0	7.0	7.0	7.0	7.0	7.0
Flash Dont Walk (s)	15.0	15.0	15.0	15.0	12.0	12.0	12.0	12.0
Pedestrian Calls (#/hr)	69	69	68	68	44	44	47	47
Act Effct Green (s)	43.8	43.8	43.8	43.8	44.0	44.0	44.0	44.0
Actuated g/C Ratio	0.44	0.44	0.44	0.44	0.44	0.44	0.44	0.44
v/c Ratio	0.13	0.57	0.51	0.36	0.71	0.73	0.41	0.66
Control Delay	17.9	24.8	28.0	20.5	39.3	16.2	30.9	24.9
Queue Delay	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
Total Delay	17.9	24.8	28.0	20.5	39.3	16.2	30.9	24.9
LOS	B	C	C	C	D	B	C	C
Approach Delay		24.1		23.2		18.4		25.2
Approach LOS		C		C		B		C
Queue Length 50th (m)	5.8	56.7	20.8	33.1	11.1	55.3	6.9	73.3
Queue Length 95th (m)	13.2	86.0	41.2	52.2	#46.2	34.8	19.4	94.5
Internal Link Dist (m)		139.3		203.3		207.2		176.5
Turn Bay Length (m)	20.0		20.0		35.0		45.0	
Base Capacity (vph)	395	713	296	736	151	1372	132	1416
Starvation Cap Reductn	0	0	0	0	0	0	0	0
Spillback Cap Reductn	0	0	0	0	0	0	0	0
Storage Cap Reductn	0	0	0	0	0	0	0	0
Reduced v/c Ratio	0.13	0.57	0.51	0.36	0.71	0.73	0.41	0.66


Intersection Summary

Cycle Length: 100
 Actuated Cycle Length: 100
 Offset: 40 (40%), Referenced to phase 2:NBT and 6:SBTL, Start of Green
 Natural Cycle: 60

Lanes, Volumes, Timings
3: Bronson & Gladstone

Existing PM Peak Hour
18 Louisa Street

Control Type: Actuated-Coordinated
 Maximum v/c Ratio: 0.73
 Intersection Signal Delay: 22.2
 Intersection LOS: C
 Intersection Capacity Utilization 86.1%
 ICU Level of Service E
 Analysis Period (min) 15
 # 95th percentile volume exceeds capacity, queue may be longer.
 Queue shown is maximum after two cycles.



Lanes, Volumes, Timings
4: Booth & Gladstone

Existing PM Peak Hour
18 Louisa Street

	↖	→	↗	←	↖	↑	↗	↓
Lane Group	EBL	EBT	WBL	WBT	NBL	NBT	SBL	SBT
Lane Configurations	↖	↖	↖	↖	↖	↖	↖	↖
Traffic Volume (vph)	37	287	138	431	99	353	47	327
Future Volume (vph)	37	287	138	431	99	353	47	327
Lane Group Flow (vph)	41	366	153	523	110	474	52	385
Turn Type	Perm	NA	Perm	NA	Perm	NA	Perm	NA
Protected Phases		2		6		4		8
Permitted Phases	2		6		4		8	
Detector Phase	2	2	6	6	4	4	8	8
Switch Phase								
Minimum Initial (s)	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0
Minimum Split (s)	22.1	22.1	22.1	22.1	23.9	23.9	23.9	23.9
Total Split (s)	43.0	43.0	43.0	43.0	37.0	37.0	37.0	37.0
Total Split (%)	53.8%	53.8%	53.8%	53.8%	46.3%	46.3%	46.3%	46.3%
Maximum Green (s)	36.9	36.9	36.9	36.9	30.1	30.1	30.1	30.1
Yellow Time (s)	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0
All-Red Time (s)	3.1	3.1	3.1	3.1	3.9	3.9	3.9	3.9
Lost Time Adjust (s)	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
Total Lost Time (s)	6.1	6.1	6.1	6.1	6.9	6.9	6.9	6.9
Lead/Lag								
Lead-Lag Optimize?								
Vehicle Extension (s)	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0
Recall Mode	C-Max	C-Max	C-Max	C-Max	Max	Max	Max	Max
Walk Time (s)	7.0	7.0	7.0	7.0	7.0	7.0	7.0	7.0
Flash Dont Walk (s)	9.0	9.0	9.0	9.0	10.0	10.0	10.0	10.0
Pedestrian Calls (#/hr)	46	46	41	41	27	27	27	27
Act Effct Green (s)	36.9	36.9	36.9	36.9	30.1	30.1	30.1	30.1
Actuated g/C Ratio	0.46	0.46	0.46	0.46	0.38	0.38	0.38	0.38
v/c Ratio	0.16	0.47	0.43	0.66	0.42	0.74	0.26	0.59
Control Delay	14.7	16.9	29.4	31.5	24.5	29.5	21.6	24.4
Queue Delay	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
Total Delay	14.7	16.9	29.4	31.5	24.5	29.5	21.6	24.4
LOS	B	B	C	C	C	C	C	C
Approach Delay		16.7		31.0		28.5		24.1
Approach LOS		B		C		C		C
Queue Length 50th (m)	3.5	35.4	23.6	83.9	12.1	59.0	5.3	45.5
Queue Length 95th (m)	9.7	57.6	42.3	114.6	26.5	#95.4	14.2	72.8
Internal Link Dist (m)		79.0		246.0		206.0		98.4
Turn Bay Length (m)	40.0		25.0		8.0		8.0	
Base Capacity (vph)	251	772	357	789	264	639	200	650
Starvation Cap Reductn	0	0	0	0	0	0	0	0
Spillback Cap Reductn	0	0	0	0	0	0	0	0
Storage Cap Reductn	0	0	0	0	0	0	0	0
Reduced v/c Ratio	0.16	0.47	0.43	0.66	0.42	0.74	0.26	0.59

Intersection Summary


Cycle Length: 80
 Actuated Cycle Length: 80
 Offset: 51 (64%), Referenced to phase 2:EBTL and 6:WBTL, Start of Green
 Natural Cycle: 55

Lanes, Volumes, Timings
4: Booth & Gladstone

Existing PM Peak Hour
18 Louisa Street

Control Type: Actuated-Coordinated	
Maximum v/c Ratio: 0.74	
Intersection Signal Delay: 26.1	Intersection LOS: C
Intersection Capacity Utilization 89.9%	ICU Level of Service E
Analysis Period (min) 15	
# 95th percentile volume exceeds capacity, queue may be longer.	
Queue shown is maximum after two cycles.	

Splits and Phases: 4: Booth & Gladstone



Lanes, Volumes, Timings
5: Arthur & Gladstone

Existing PM Peak Hour
18 Louisa Street

	↖	→	↙	←	↓
Lane Group	EBL	EBT	WBL	WBT	SBT
Lane Configurations		↕		↕	↕
Traffic Volume (vph)	31	426	1	499	1
Future Volume (vph)	31	426	1	499	1
Lane Group Flow (vph)	0	514	0	565	75
Turn Type	Perm	NA	Perm	NA	NA
Protected Phases		2		6	8
Permitted Phases	2		6		
Detector Phase	2	2	6	6	8
Switch Phase					
Minimum Initial (s)	10.0	10.0	10.0	10.0	10.0
Minimum Split (s)	29.5	29.5	29.5	29.5	23.2
Total Split (s)	56.8	56.8	56.8	56.8	23.2
Total Split (%)	71.0%	71.0%	71.0%	71.0%	29.0%
Maximum Green (s)	51.3	51.3	51.3	51.3	18.0
Yellow Time (s)	3.0	3.0	3.0	3.0	3.0
All-Red Time (s)	2.5	2.5	2.5	2.5	2.2
Lost Time Adjust (s)		0.0		0.0	0.0
Total Lost Time (s)		5.5		5.5	5.2
Lead/Lag					
Lead-Lag Optimize?					
Vehicle Extension (s)	3.0	3.0	3.0	3.0	3.0
Recall Mode	C-Max	C-Max	C-Max	C-Max	None
Walk Time (s)	19.0	19.0	19.0	19.0	10.0
Flash Dont Walk (s)	5.0	5.0	5.0	5.0	8.0
Pedestrian Calls (#/hr)	75	75	59	59	45
Act Effct Green (s)		58.6		58.6	14.8
Actuated g/C Ratio		0.73		0.73	0.18
v/c Ratio		0.43		0.44	0.25
Control Delay		6.2		7.6	12.1
Queue Delay		0.0		0.2	0.0
Total Delay		6.2		7.9	12.1
LOS		A		A	B
Approach Delay		6.2		7.9	12.1
Approach LOS		A		A	B
Queue Length 50th (m)		21.6		40.0	1.8
Queue Length 95th (m)		32.6		62.2	11.9
Internal Link Dist (m)		246.0		139.3	183.9
Turn Bay Length (m)					
Base Capacity (vph)		1202		1273	352
Starvation Cap Reductn		0		193	0
Spillback Cap Reductn		0		0	0
Storage Cap Reductn		0		0	0
Reduced v/c Ratio		0.43		0.52	0.21

Intersection Summary


Cycle Length: 80
 Actuated Cycle Length: 80
 Offset: 65 (81%), Referenced to phase 2:EBTL and 6:WBTL, Start of Green
 Natural Cycle: 55

Lanes, Volumes, Timings
5: Arthur & Gladstone

Existing PM Peak Hour
18 Louisa Street

Control Type: Actuated-Coordinated
 Maximum v/c Ratio: 0.44
 Intersection Signal Delay: 7.4
 Intersection LOS: A
 Intersection Capacity Utilization 73.3%
 ICU Level of Service D
 Analysis Period (min) 15

Splits and Phases: 5: Arthur & Gladstone



Lanes, Volumes, Timings
6: Booth & Raymond

Existing PM Peak Hour
18 Louisa Street

Lane Group	WBT	WBR	NBL	NBT	SBT
Lane Configurations	↔	↔	↔	↔	↔
Traffic Volume (vph)	331	194	31	332	468
Future Volume (vph)	331	194	31	332	468
Lane Group Flow (vph)	565	216	34	369	620
Turn Type	NA	Perm	Perm	NA	NA
Protected Phases	8			2	6
Permitted Phases		8	2		
Detector Phase	8	8	2	2	6
Switch Phase					
Minimum Initial (s)	10.0	10.0	10.0	10.0	10.0
Minimum Split (s)	25.5	25.5	25.2	25.2	25.2
Total Split (s)	25.5	25.5	44.5	44.5	44.5
Total Split (%)	36.4%	36.4%	63.6%	63.6%	63.6%
Maximum Green (s)	20.0	20.0	39.3	39.3	39.3
Yellow Time (s)	3.3	3.3	3.3	3.3	3.3
All-Red Time (s)	2.2	2.2	1.9	1.9	1.9
Lost Time Adjust (s)	0.0	0.0	0.0	0.0	0.0
Total Lost Time (s)	5.5	5.5	5.2	5.2	5.2
Lead/Lag					
Lead-Lag Optimize?					
Vehicle Extension (s)	3.0	3.0	3.0	3.0	3.0
Recall Mode	Max	Max	C-Max	C-Max	C-Max
Walk Time (s)	11.0	11.0	15.0	15.0	15.0
Flash Dont Walk (s)	9.0	9.0	5.0	5.0	5.0
Pedestrian Calls (#/hr)	14	14	47	47	32
Act Effct Green (s)	20.0	20.0	39.3	39.3	39.3
Actuated g/C Ratio	0.29	0.29	0.56	0.56	0.56
v/c Ratio	1.18	0.39	0.12	0.38	0.65
Control Delay	127.5	5.5	8.5	9.9	14.2
Queue Delay	0.0	0.0	0.0	0.0	0.0
Total Delay	127.5	5.5	8.5	9.9	14.2
LOS	F	A	A	A	B
Approach Delay	93.7			9.8	14.2
Approach LOS	F			A	B
Queue Length 50th (m)	~90.7	0.0	1.9	24.4	49.0
Queue Length 95th (m)	#145.4	13.8	5.9	40.5	81.1
Internal Link Dist (m)	302.1			65.0	206.0
Turn Bay Length (m)		75.0	25.0		
Base Capacity (vph)	479	558	287	979	954
Starvation Cap Reductn	0	0	0	0	0
Spillback Cap Reductn	0	0	0	0	0
Storage Cap Reductn	0	0	0	0	0
Reduced v/c Ratio	1.18	0.39	0.12	0.38	0.65

Intersection Summary


Cycle Length: 70
 Actuated Cycle Length: 70
 Offset: 39 (56%), Referenced to phase 2:NBL and 6:SBT, Start of Green
 Natural Cycle: 65

Lanes, Volumes, Timings
6: Booth & Raymond

Existing PM Peak Hour
18 Louisa Street

Control Type: Actuated-Coordinated
 Maximum v/c Ratio: 1.18
 Intersection Signal Delay: 47.6
 Intersection LOS: D
 Intersection Capacity Utilization 76.5%
 ICU Level of Service D
 Analysis Period (min) 15
 ~ Volume exceeds capacity, queue is theoretically infinite.
 Queue shown is maximum after two cycles.
 # 95th percentile volume exceeds capacity, queue may be longer.
 Queue shown is maximum after two cycles.

Splits and Phases: 6: Booth & Raymond



Appendix D

Collision Data

Accident Date	Accident Year	Accident Time	Location	Environment Condition	Light	Traffic Control	Traffic Control Condition	Classification Of Accident	Initial Impact Type	Road Surface Condition
2018-01-24	2018	23:29	ARLINGTON AVE @ BELL ST	01 - Clear	07 - Dark	02 - Stop sign		02 - Non-fatal injury	07 - SMV other	03 - Loose snow
2017-04-18	2017	21:00	ARLINGTON AVE @ BOOTH ST	01 - Clear	07 - Dark	02 - Stop sign		03 - P.D. only	03 - Rear end	01 - Dry
2015-01-12	2015	6:35	ARLINGTON AVE @ BRONSON AVE	03 - Snow	07 - Dark	01 - Traffic signal		02 - Non-fatal injury	05 - Turning movement	03 - Loose snow
2015-03-28	2015	15:49	ARLINGTON AVE @ BRONSON AVE	01 - Clear	01 - Daylight	01 - Traffic signal		03 - P.D. only	05 - Turning movement	01 - Dry
2015-05-24	2015	16:07	ARLINGTON AVE @ BRONSON AVE	01 - Clear	01 - Daylight	01 - Traffic signal		02 - Non-fatal injury	02 - Angle	01 - Dry
2015-08-26	2015	11:45	ARLINGTON AVE @ BRONSON AVE	01 - Clear	01 - Daylight	01 - Traffic signal		03 - P.D. only	03 - Rear end	01 - Dry
2015-11-08	2015	15:00	ARLINGTON AVE @ BRONSON AVE	01 - Clear	01 - Daylight	01 - Traffic signal		03 - P.D. only	02 - Angle	01 - Dry
2015-12-17	2015	11:46	ARLINGTON AVE @ BRONSON AVE	01 - Clear	01 - Daylight	01 - Traffic signal		03 - P.D. only	02 - Angle	01 - Dry
2016-02-04	2016	10:18	ARLINGTON AVE @ BRONSON AVE	01 - Clear	01 - Daylight	01 - Traffic signal		03 - P.D. only	04 - Sideswipe	02 - Wet
2016-06-01	2016	18:20	ARLINGTON AVE @ BRONSON AVE	01 - Clear	01 - Daylight	01 - Traffic signal		03 - P.D. only	03 - Rear end	01 - Dry
2015-10-16	2015	11:56	ARLINGTON AVE @ BRONSON AVE	02 - Rain	01 - Daylight	01 - Traffic signal		03 - P.D. only	05 - Turning movement	01 - Dry
2016-12-02	2016	19:42	ARLINGTON AVE @ BRONSON AVE	02 - Rain	07 - Dark	01 - Traffic signal		03 - P.D. only	03 - Rear end	02 - Wet
2017-01-08	2017	12:33	ARLINGTON AVE @ BRONSON AVE	01 - Clear	01 - Daylight	01 - Traffic signal		03 - P.D. only	05 - Turning movement	01 - Dry
2017-03-10	2017	12:42	ARLINGTON AVE @ BRONSON AVE	01 - Clear	01 - Daylight	01 - Traffic signal		03 - P.D. only	05 - Turning movement	01 - Dry
2017-05-23	2017	19:42	ARLINGTON AVE @ BRONSON AVE	01 - Clear	01 - Daylight	01 - Traffic signal		02 - Non-fatal injury	02 - Angle	01 - Dry
2017-06-05	2017	18:01	ARLINGTON AVE @ BRONSON AVE	01 - Clear	01 - Daylight	01 - Traffic signal		03 - P.D. only	03 - Rear end	01 - Dry
2017-06-30	2017	15:33	ARLINGTON AVE @ BRONSON AVE	02 - Rain	01 - Daylight	01 - Traffic signal		03 - P.D. only	03 - Rear end	02 - Wet
2017-12-14	2017	13:50	ARLINGTON AVE @ BRONSON AVE	03 - Snow	01 - Daylight	01 - Traffic signal		03 - P.D. only	02 - Angle	01 - Dry
2019-02-19	2019	15:30	ARLINGTON AVE @ BRONSON AVE	01 - Clear	01 - Daylight	01 - Traffic signal		03 - P.D. only	03 - Rear end	01 - Dry
2019-03-14	2019	15:30	ARLINGTON AVE @ BRONSON AVE	02 - Rain	01 - Daylight	01 - Traffic signal		03 - P.D. only	04 - Sideswipe	02 - Wet
2019-06-26	2019	15:35	ARLINGTON AVE @ BRONSON AVE	01 - Clear	01 - Daylight	01 - Traffic signal		03 - P.D. only	05 - Turning movement	01 - Dry
2019-12-22	2019	10:28	ARLINGTON AVE @ BRONSON AVE	01 - Clear	01 - Daylight	01 - Traffic signal		03 - P.D. only	03 - Rear end	01 - Dry
2017-06-28	2017	19:56	ARLINGTON AVE btwn ARTHUR LANE N & CAMBRIDGE ST N	01 - Clear	01 - Daylight	10 - No control		03 - P.D. only	04 - Sideswipe	01 - Dry
2018-04-03	2018	20:00	ARLINGTON AVE btwn ARTHUR LANE N & CAMBRIDGE ST N	01 - Clear	07 - Dark	10 - No control		03 - P.D. only	06 - SMV unattended vehicle	01 - Dry
2018-01-07	2018	Unknown	ARLINGTON AVE btwn BELL ST N & ARTHUR LANE N	01 - Clear	00 - Unknown	10 - No control		03 - P.D. only	06 - SMV unattended vehicle	03 - Loose snow
2016-05-10	2016	0:00	ARLINGTON AVE btwn BOOTH ST & LEBRETTON ST N	01 - Clear	00 - Unknown	10 - No control		03 - P.D. only	06 - SMV unattended vehicle	01 - Dry
2017-09-24	2017	0:00	ARLINGTON AVE btwn BOOTH ST & LEBRETTON ST N	01 - Clear	00 - Unknown	10 - No control		03 - P.D. only	06 - SMV unattended vehicle	01 - Dry
2019-01-09	2019	12:00	ARLINGTON AVE btwn BOOTH ST & LEBRETTON ST N	01 - Clear	01 - Daylight	10 - No control		03 - P.D. only	06 - SMV unattended vehicle	01 - Dry
2015-02-27	2015	12:15	ARLINGTON AVE btwn CAMBRIDGE ST N & BRONSON AVE	01 - Clear	01 - Daylight	10 - No control		03 - P.D. only	04 - Sideswipe	01 - Dry
2015-09-08	2015	22:03	ARLINGTON AVE btwn CAMBRIDGE ST N & BRONSON AVE	01 - Clear	07 - Dark	10 - No control		03 - P.D. only	06 - SMV unattended vehicle	01 - Dry
2015-03-13	2015	11:51	BELL ST @ GLADSTONE AVE	03 - Snow	01 - Daylight	02 - Stop sign		03 - P.D. only	02 - Angle	02 - Wet
2015-03-30	2015	18:18	BELL ST @ GLADSTONE AVE	03 - Snow	05 - Dusk	02 - Stop sign		03 - P.D. only	02 - Angle	02 - Wet
2016-03-07	2016	8:01	BELL ST @ GLADSTONE AVE	03 - Snow	01 - Daylight	02 - Stop sign		03 - P.D. only	06 - SMV unattended vehicle	06 - Ice
2015-08-12	2016	14:07	BELL ST @ GLADSTONE AVE	01 - Clear	01 - Daylight	02 - Stop sign		03 - P.D. only	03 - Rear end	01 - Dry
2016-12-14	2016	15:30	BELL ST @ GLADSTONE AVE	01 - Clear	01 - Daylight	02 - Stop sign		03 - P.D. only	03 - Rear end	02 - Wet
2017-08-21	2017	20:16	BELL ST @ GLADSTONE AVE	01 - Clear	05 - Dusk	02 - Stop sign		02 - Non-fatal injury	05 - Turning movement	01 - Dry
2017-09-08	2017	16:58	BELL ST @ GLADSTONE AVE	01 - Clear	01 - Daylight	02 - Stop sign		03 - P.D. only	02 - Angle	01 - Dry
2017-11-06	2017	17:00	BELL ST @ GLADSTONE AVE	01 - Clear	05 - Dusk	02 - Stop sign		02 - Non-fatal injury	05 - Turning movement	01 - Dry
2019-10-01	2019	17:00	BELL ST @ GLADSTONE AVE	01 - Clear	01 - Daylight	02 - Stop sign		03 - P.D. only	03 - Rear end	01 - Dry
2015-05-27	2015	15:58	BELL ST N btwn GLADSTONE AVE & LOUISA ST	01 - Clear	01 - Daylight	10 - No control		03 - P.D. only	06 - SMV unattended vehicle	01 - Dry
2017-09-06	2017	0:00	BELL ST N btwn GLADSTONE AVE & LOUISA ST	01 - Clear	00 - Unknown	10 - No control		03 - P.D. only	06 - SMV unattended vehicle	01 - Dry
2018-06-14	2018	19:51	BELL ST N btwn GLADSTONE AVE & LOUISA ST	01 - Clear	01 - Daylight	10 - No control		03 - P.D. only	06 - SMV unattended vehicle	01 - Dry
2018-08-24	2018	22:29	BELL ST N btwn GLADSTONE AVE & LOUISA ST	01 - Clear	07 - Dark	10 - No control		03 - P.D. only	06 - SMV unattended vehicle	01 - Dry
2019-05-29	2019	16:30	BELL ST N btwn GLADSTONE AVE & LOUISA ST	01 - Clear	01 - Daylight	10 - No control		03 - P.D. only	99 - Other	01 - Dry
2015-08-18	2015	13:49	BOOTH ST @ LOUISA ST	01 - Clear	01 - Daylight	02 - Stop sign		03 - P.D. only	02 - Angle	01 - Dry
2015-12-27	2015	3:28	BOOTH ST @ LOUISA ST	03 - Snow	07 - Dark	02 - Stop sign		03 - P.D. only	02 - Angle	04 - Slush
2017-02-28	2017	9:32	BOOTH ST @ LOUISA ST	01 - Clear	01 - Daylight	02 - Stop sign		02 - Non-fatal injury	03 - Rear end	01 - Dry
2017-11-01	2017	15:26	BOOTH ST @ LOUISA ST	01 - Clear	01 - Daylight	02 - Stop sign		02 - Non-fatal injury	03 - Rear end	02 - Wet
2017-03-15	2017	11:11	BOOTH ST btwn LOUISA ST & ARLINGTON AVE	03 - Snow	01 - Daylight	10 - No control		03 - P.D. only	06 - SMV unattended vehicle	03 - Loose snow
2017-12-06	2017	11:46	BOOTH ST btwn LOUISA ST & ARLINGTON AVE	01 - Clear	01 - Daylight	10 - No control		03 - P.D. only	04 - Sideswipe	01 - Dry
2015-02-02	2015	7:18	GLADSTONE AVE @ LEBRETTON ST	03 - Snow	01 - Daylight	02 - Stop sign		02 - Non-fatal injury	05 - Turning movement	03 - Loose snow
2015-07-08	2015	15:57	GLADSTONE AVE @ LEBRETTON ST	01 - Clear	01 - Daylight	02 - Stop sign		03 - P.D. only	02 - Angle	01 - Dry
2015-09-21	2015	16:56	GLADSTONE AVE @ LEBRETTON ST	01 - Clear	01 - Daylight	02 - Stop sign		03 - P.D. only	02 - Angle	01 - Dry
2016-06-11	2016	19:30	GLADSTONE AVE @ LEBRETTON ST	01 - Clear	01 - Daylight	02 - Stop sign		03 - P.D. only	02 - Angle	01 - Dry
2017-03-17	2017	17:40	GLADSTONE AVE @ LEBRETTON ST	01 - Clear	01 - Daylight	02 - Stop sign		03 - P.D. only	02 - Angle	01 - Dry
2017-04-07	2017	8:50	GLADSTONE AVE @ LEBRETTON ST	02 - Rain	01 - Daylight	02 - Stop sign		03 - P.D. only	02 - Angle	02 - Wet
2017-05-20	2017	14:38	GLADSTONE AVE @ LEBRETTON ST	01 - Clear	01 - Daylight	02 - Stop sign		03 - P.D. only	02 - Angle	01 - Dry
2017-12-31	2017	9:27	GLADSTONE AVE @ LEBRETTON ST	01 - Clear	01 - Daylight	02 - Stop sign		03 - P.D. only	02 - Angle	01 - Dry
2018-05-24	2018	23:54	GLADSTONE AVE @ LEBRETTON ST	01 - Clear	07 - Dark	02 - Stop sign		03 - P.D. only	02 - Angle	01 - Dry
2018-06-09	2018	22:31	GLADSTONE AVE @ LEBRETTON ST	01 - Clear	07 - Dark	02 - Stop sign		03 - P.D. only	02 - Angle	01 - Dry
2018-07-28	2018	19:34	GLADSTONE AVE @ LEBRETTON ST	01 - Clear	01 - Daylight	02 - Stop sign		02 - Non-fatal injury	02 - Angle	01 - Dry
2018-08-08	2018	18:36	GLADSTONE AVE @ LEBRETTON ST	01 - Clear	01 - Daylight	02 - Stop sign		02 - Non-fatal injury	02 - Angle	01 - Dry
2018-10-30	2018	17:43	GLADSTONE AVE @ LEBRETTON ST	01 - Clear	01 - Daylight	02 - Stop sign		03 - P.D. only	02 - Angle	01 - Dry
2019-02-16	2019	15:30	GLADSTONE AVE @ LEBRETTON ST	01 - Clear	01 - Daylight	02 - Stop sign		03 - P.D. only	02 - Angle	02 - Wet
2019-05-23	2019	1:34	GLADSTONE AVE @ LEBRETTON ST	01 - Clear	07 - Dark	02 - Stop sign		03 - P.D. only	02 - Angle	01 - Dry
2019-05-28	2019	9:59	GLADSTONE AVE @ LEBRETTON ST	02 - Rain	01 - Daylight	02 - Stop sign		03 - P.D. only	02 - Angle	02 - Wet
2019-06-09	2019	17:20	GLADSTONE AVE @ LEBRETTON ST	01 - Clear	01 - Daylight	02 - Stop sign		02 - Non-fatal injury	02 - Angle	01 - Dry
2019-06-19	2019	16:16	GLADSTONE AVE @ LEBRETTON ST	01 - Clear	01 - Daylight	02 - Stop sign		03 - P.D. only	02 - Angle	02 - Wet
2019-06-27	2019	13:45	GLADSTONE AVE @ LEBRETTON ST	01 - Clear	01 - Daylight	02 - Stop sign		03 - P.D. only	02 - Angle	01 - Dry
2019-10-31	2019	9:15	GLADSTONE AVE @ LEBRETTON ST	02 - Rain	01 - Daylight	02 - Stop sign		03 - P.D. only	02 - Angle	02 - Wet
2019-12-20	2019	16:20	GLADSTONE AVE @ LEBRETTON ST	01 - Clear	05 - Dusk	02 - Stop sign		03 - P.D. only	02 - Angle	02 - Wet
2017-05-21	2017	10:12	GLADSTONE AVE btwn LEBRETTON ST N & BELL ST N	01 - Clear	01 - Daylight	10 - No control		03 - P.D. only	06 - SMV unattended vehicle	01 - Dry
2018-03-15	2018	13:45	GLADSTONE AVE btwn LEBRETTON ST N & BELL ST N	01 - Clear	01 - Daylight	10 - No control		03 - P.D. only	02 - Angle	01 - Dry
2019-08-08	2019	10:06	GLADSTONE AVE btwn LEBRETTON ST N & BELL ST N	01 - Clear	01 - Daylight	10 - No control		03 - P.D. only	99 - Other	01 - Dry
2019-01-17	2019	12:20	LEBRETON ST @ LOUISA ST	01 - Clear	01 - Daylight	02 - Stop sign		03 - P.D. only	02 - Angle	06 - Ice
2016-10-20	2016	12:46	LEBRETON ST @ RAYMOND ST	02 - Rain	01 - Daylight	02 - Stop sign		03 - P.D. only	04 - Sideswipe	02 - Wet
2017-07-25	2017	16:12	LEBRETON ST @ RAYMOND ST	01 - Clear	01 - Daylight	02 - Stop sign		03 - P.D. only	04 - Sideswipe	01 - Dry
2017-09-11	2017	10:00	LEBRETON ST N btwn GLADSTONE AVE & LOUISA ST	01 - Clear	01 - Daylight	10 - No control		03 - P.D. only	06 - SMV unattended vehicle	01 - Dry
2019-12-13	2019	0:00	LEBRETON ST N btwn GLADSTONE AVE & LOUISA ST	01 - Clear	00 - Unknown	10 - No control		03 - P.D. only	06 - SMV unattended vehicle	02 - Wet
2017-04-16	2017	0:00	LEBRETON ST N btwn LOUISA ST & ARLINGTON AVE	01 - Clear	00 - Unknown	10 - No control		03 - P.D. only	06 - SMV unattended vehicle	01 - Dry
2019-08-16	2019	0:00	LEBRETON ST N btwn LOUISA ST & ARLINGTON AVE	01 - Clear	00 - Unknown	10 - No control		03 - P.D. only	06 - SMV unattended vehicle	01 - Dry
2015-10-23	2015	23:45	LOUISA ST btwn LEBRETTON ST N & BELL ST N	01 - Clear	07 - Dark	10 - No control		02 - Non-fatal injury	07 - SMV other	01 - Dry
2018-05-07	2018	22:04	LOUISA ST btwn LEBRETTON ST N & BELL ST N	01 - Clear	07 - Dark	10 - No control		03 - P.D. only	07 - SMV other	01 - Dry
2018-10-24	2018	19:26	RAYMOND ST btwn LEBRETTON ST N & BELL ST N	01 - Clear	07 - Dark	10 - No control		02 - Non-fatal injury	07 - SMV other	01 - Dry

Appendix E

TRANS Model Plots

TRANS Regional Model

Version 2.15 - Assigned June 16, 2020

AM Peak Hour Total Traffic Volume

18 Louisa Street

2011 Model - Basecase


N/A

User Initials: TIMW
Plot Prepared: Feb 2, 2020
EMME Scenario: 21711




Legend

AM Peak Hour Total Traffic Volume



Distance (m)



The TRANS model is continuously refined & maintained, and all information is provided in good faith. However, model outputs are provided "as is", and no warranty or guarantee is provided as to the accuracy, reliability or reasonableness of the results. In using this data, you agree to accept any and all risks arising from any incorrect, incomplete, or misleading information.

Recipients are required to use caution and professional judgement in using and interpreting model outputs. In particular, caution should be used when focusing on a geographically limited area (such as a single road or intersection), as the model is primarily designed to simulate regional-scale phenomena and has been calibrated at a regional level.

As a general good practice, it is recommended that the user confirm the network coding within the area of interest, and compare base year forecasts against traffic count data to assess the extent to which the model may be over- or under-estimating the travel demand.

TRANS Regional Model

Version 2.15 - Assigned June 16, 2020

AM Peak Hour Total Traffic Volume

18 Louisa Street

2031 Model - Basecase


N/A

User Initials: TIMW
Plot Prepared: Feb 2, 2020
EMME Scenario: 21711




Legend

AM Peak Hour Total Traffic Volume



Distance (m)



The TRANS model is continuously refined & maintained, and all information is provided in good faith. However, model outputs are provided "as is", and no warranty or guarantee is provided as to the accuracy, reliability or reasonableness of the results. In using this data, you agree to accept any and all risks arising from any incorrect, incomplete, or misleading information.

Recipients are required to use caution and professional judgement in using and interpreting model outputs. In particular, caution should be used when focusing on a geographically limited area (such as a single road or intersection), as the model is primarily designed to simulate regional-scale phenomena and has been calibrated at a regional level.

As a general good practice, it is recommended that the user confirm the network coding within the area of interest, and compare base year forecasts against traffic count data to assess the extent to which the model may be over- or under-estimating the travel demand.

Appendix F

Synchro Intersection Worksheets – 2025 Future Background Conditions

Lanes, Volumes, Timings
1: Bronson & Raymond/Catherine

Future Background 2025AM Peak Hour
18 Louisa Street


Lane Group	WBL	WBT	NBL	NBT	SBT	Ø5	Ø9
Lane Configurations	↔↔↔	↔↔↔	↔↔	↔↔	↔↔		
Traffic Volume (vph)	527	514	537	1075	451		
Future Volume (vph)	527	514	537	1075	451		
Lane Group Flow (vph)	353	1034	537	1075	569		
Turn Type	Perm	NA	pm+pt	NA	NA		
Protected Phases		8	5 9	2	6	5	9
Permitted Phases	8		2	9			
Detector Phase	8	8	5 9	2	6		
Switch Phase							
Minimum Initial (s)	10.0	10.0		10.0	10.0	5.0	5.0
Minimum Split (s)	28.3	28.3		24.8	24.8	11.8	11.8
Total Split (s)	34.0	34.0		53.0	33.0	20.0	23.0
Total Split (%)	30.9%	30.9%		48.2%	30.0%	18%	21%
Maximum Green (s)	27.7	27.7		46.2	26.2	13.2	16.8
Yellow Time (s)	3.3	3.3		3.3	3.3	3.3	3.3
All-Red Time (s)	3.0	3.0		3.5	3.5	3.5	2.9
Lost Time Adjust (s)	0.0	0.0		0.0	0.0		
Total Lost Time (s)	6.3	6.3		6.8	6.8		
Lead/Lag				Lead	Lag		
Lead-Lag Optimize?				Yes	Yes		
Vehicle Extension (s)	3.0	3.0		3.0	3.0	3.0	3.0
Recall Mode	Max	Max		C-Max	C-Max	Max	Max
Walk Time (s)	7.0	7.0		7.0	7.0		
Flash Dont Walk (s)	15.0	15.0		10.0	10.0		
Pedestrian Calls (#/hr)	40	40		45	26		
Act Effct Green (s)	27.7	27.7		62.4	69.2	26.2	
Actuated g/C Ratio	0.25	0.25		0.57	0.63	0.24	
v/c Ratio	1.00	0.95		0.90	0.52	0.77	
Control Delay	90.9	54.4		36.8	12.3	42.4	
Queue Delay	0.0	0.0		0.0	0.0	9.4	
Total Delay	90.9	54.4		36.8	12.3	51.8	
LOS	F	D		D	B	D	
Approach Delay		63.6		20.5	51.8		
Approach LOS		E		C	D		
Queue Length 50th (m)	~88.8	78.2		58.5	61.5	57.7	
Queue Length 95th (m)	#156.7	#108.0		#111.4	77.2	77.9	
Internal Link Dist (m)		247.5		81.5	56.5		
Turn Bay Length (m)	110.0			45.0			
Base Capacity (vph)	352	1092		600	2086	741	
Starvation Cap Reductn	0	0		0	0	144	
Spillback Cap Reductn	0	0		0	39	0	
Storage Cap Reductn	0	0		0	0	0	
Reduced v/c Ratio	1.00	0.95		0.90	0.53	0.95	

Intersection Summary
 Cycle Length: 110
 Actuated Cycle Length: 110
 Offset: 38 (35%), Referenced to phase 2:NBT and 6:SBT, Start of Green
 Natural Cycle: 90

Lanes, Volumes, Timings
1: Bronson & Raymond/Catherine

Future Background 2025AM Peak Hour
18 Louisa Street

Control Type: Actuated-Coordinated
 Maximum v/c Ratio: 1.00
 Intersection Signal Delay: 42.2
 Intersection LOS: D
 Intersection Capacity Utilization 88.9%
 ICU Level of Service E
 Analysis Period (min) 15
 ~ Volume exceeds capacity, queue is theoretically infinite.
 Queue shown is maximum after two cycles.
 # 95th percentile volume exceeds capacity, queue may be longer.
 Queue shown is maximum after two cycles.



Lanes, Volumes, Timings
2: Bronson & Arlington

Future Background 2025AM Peak Hour
18 Louisa Street


Lane Group	EBL	EBT	WBL	WBT	NBL	NBT	SBL	SBT
Lane Configurations		↕		↕		↕		↕
Traffic Volume (vph)	9	4	8	2	13	1413	2	542
Future Volume (vph)	9	4	8	2	13	1413	2	542
Lane Group Flow (vph)	0	37	0	21	0	1432	0	558
Turn Type	Perm	NA	Perm	NA	Perm	NA	Perm	NA
Protected Phases		4		8		2		6
Permitted Phases	4		8		2		6	
Detector Phase	4	4	8	8	2	2	6	6
Switch Phase								
Minimum Initial (s)	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0
Minimum Split (s)	22.6	22.6	22.6	22.6	17.2	17.2	17.2	17.2
Total Split (s)	23.0	23.0	23.0	23.0	87.0	87.0	87.0	87.0
Total Split (%)	20.9%	20.9%	20.9%	20.9%	79.1%	79.1%	79.1%	79.1%
Maximum Green (s)	17.4	17.4	17.4	17.4	81.8	81.8	81.8	81.8
Yellow Time (s)	3.3	3.3	3.3	3.3	3.3	3.3	3.3	3.3
All-Red Time (s)	2.3	2.3	2.3	2.3	1.9	1.9	1.9	1.9
Lost Time Adjust (s)		0.0		0.0		0.0		0.0
Total Lost Time (s)		5.6		5.6		5.2		5.2
Lead/Lag								
Lead-Lag Optimize?								
Vehicle Extension (s)	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0
Recall Mode	None	None	None	None	C-Max	C-Max	C-Max	C-Max
Walk Time (s)	7.0	7.0	7.0	7.0	7.0	7.0	7.0	7.0
Flash Dont Walk (s)	10.0	10.0	10.0	10.0	5.0	5.0	5.0	5.0
Pedestrian Calls (#/hr)	23	23	19	19	21	21	27	27
Act Effct Green (s)		12.8		12.8		90.6		90.6
Actuated g/C Ratio		0.12		0.12		0.82		0.82
v/c Ratio		0.20		0.13		0.56		0.23
Control Delay		24.3		29.0		4.4		3.3
Queue Delay		0.0		0.0		0.0		0.0
Total Delay		24.3		29.0		4.4		3.3
LOS		C		C		A		A
Approach Delay		24.3		29.0		4.4		3.3
Approach LOS		C		C		A		A
Queue Length 50th (m)		2.6		2.0		29.8		11.2
Queue Length 95th (m)		11.7		9.0		m44.5		22.0
Internal Link Dist (m)		0.1		230.9		56.5		207.2
Turn Bay Length (m)								
Base Capacity (vph)		242		211		2559		2462
Starvation Cap Reductn		0		0		96		0
Spillback Cap Reductn		2		0		0		345
Storage Cap Reductn		0		0		0		0
Reduced v/c Ratio		0.15		0.10		0.58		0.26

Intersection Summary
 Cycle Length: 110
 Actuated Cycle Length: 110
 Offset: 11 (10%), Referenced to phase 2:NBT and 6:SBTL, Start of Green
 Natural Cycle: 60

Lanes, Volumes, Timings
2: Bronson & Arlington

Future Background 2025AM Peak Hour
18 Louisa Street

Control Type: Actuated-Coordinated
 Maximum v/c Ratio: 0.56
 Intersection Signal Delay: 4.7
 Intersection LOS: A
 Intersection Capacity Utilization 71.5%
 ICU Level of Service C
 Analysis Period (min) 15
 m Volume for 95th percentile queue is metered by upstream signal.



Lanes, Volumes, Timings
3: Bronson & Gladstone

Future Background 2025AM Peak Hour
18 Louisa Street

	EBL	EBT	WBL	WBT	NBL	NBT	SBL	SBT
Lane Group	EBL	EBT	WBL	WBT	NBL	NBT	SBL	SBT
Lane Configurations	↔	↔	↔	↔	↔	↔	↔	↔
Traffic Volume (vph)	46	305	83	175	123	1114	13	405
Future Volume (vph)	46	305	83	175	123	1114	13	405
Lane Group Flow (vph)	46	394	83	193	123	1264	13	444
Turn Type	Perm	NA	Perm	NA	Perm	NA	Perm	NA
Protected Phases		4		8		2		6
Permitted Phases	4		8		2		6	
Detector Phase	4	4	8	8	2	2	6	6
Switch Phase								
Minimum Initial (s)	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0
Minimum Split (s)	28.2	28.2	28.2	28.2	25.0	25.0	25.0	25.0
Total Split (s)	37.0	37.0	37.0	37.0	58.0	58.0	58.0	58.0
Total Split (%)	38.9%	38.9%	38.9%	38.9%	61.1%	61.1%	61.1%	61.1%
Maximum Green (s)	30.8	30.8	30.8	30.8	52.0	52.0	52.0	52.0
Yellow Time (s)	3.0	3.0	3.0	3.0	3.3	3.3	3.3	3.3
All-Red Time (s)	3.2	3.2	3.2	3.2	2.7	2.7	2.7	2.7
Lost Time Adjust (s)	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
Total Lost Time (s)	6.2	6.2	6.2	6.2	6.0	6.0	6.0	6.0
Lead/Lag								
Lead-Lag Optimize?								
Vehicle Extension (s)	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0
Recall Mode	Max	Max	Max	Max	C-Max	C-Max	C-Max	C-Max
Walk Time (s)	7.0	7.0	7.0	7.0	7.0	7.0	7.0	7.0
Flash Dont Walk (s)	15.0	15.0	15.0	15.0	12.0	12.0	12.0	12.0
Pedestrian Calls (/hr)	85	85	36	36	36	36	31	31
Act Effct Green (s)	30.8	30.8	30.8	30.8	52.0	52.0	52.0	52.0
Actuated g/C Ratio	0.32	0.32	0.32	0.32	0.55	0.55	0.55	0.55
v/c Ratio	0.14	0.75	0.47	0.36	0.28	0.73	0.10	0.26
Control Delay	24.2	39.4	36.3	27.0	13.6	19.2	12.9	11.8
Queue Delay	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
Total Delay	24.2	39.4	36.3	27.0	13.6	19.2	12.9	11.8
LOS	C	D	D	C	B	B	B	B
Approach Delay		37.8		29.8		18.7		11.9
Approach LOS		D		C		B		B
Queue Length 50th (m)	5.9	64.1	12.0	26.9	11.3	86.1	1.1	21.2
Queue Length 95th (m)	14.2	#105.5	27.4	45.3	22.4	111.2	4.4	29.8
Internal Link Dist (m)		139.3		203.3		207.2		176.5
Turn Bay Length (m)	20.0		20.0		35.0		45.0	
Base Capacity (vph)	330	523	176	534	445	1743	125	1724
Starvation Cap Reductn	0	0	0	0	0	0	0	0
Spillback Cap Reductn	0	0	0	0	0	0	0	0
Storage Cap Reductn	0	0	0	0	0	0	0	0
Reduced v/c Ratio	0.14	0.75	0.47	0.36	0.28	0.73	0.10	0.26

Intersection Summary


Cycle Length: 95
 Actuated Cycle Length: 95
 Offset: 42 (44%), Referenced to phase 2:NBT and 6:SBTL, Start of Green
 Natural Cycle: 60

Lanes, Volumes, Timings
3: Bronson & Gladstone

Future Background 2025AM Peak Hour
18 Louisa Street

Control Type: Actuated-Coordinated
 Maximum v/c Ratio: 0.75
 Intersection Signal Delay: 22.0
 Intersection LOS: C
 Intersection Capacity Utilization 98.8%
 ICU Level of Service F
 Analysis Period (min) 15
 # 95th percentile volume exceeds capacity, queue may be longer.
 Queue shown is maximum after two cycles.

Splits and Phases: 3: Bronson & Gladstone



Lanes, Volumes, Timings
4: Booth & Gladstone

Future Background 2025AM Peak Hour
18 Louisa Street

	EBL	EBT	WBL	WBT	NBL	NBT	SBL	SBT
Lane Group	EBL	EBT	WBL	WBT	NBL	NBT	SBL	SBT
Lane Configurations	↔	↕	↔	↕	↔	↕	↔	↕
Traffic Volume (vph)	26	369	42	260	51	354	38	137
Future Volume (vph)	26	369	42	260	51	354	38	137
Lane Group Flow (vph)	26	440	42	291	51	431	38	157
Turn Type	Perm	NA	Perm	NA	Perm	NA	Perm	NA
Protected Phases		2		6		4		8
Permitted Phases	2		6		4		8	
Detector Phase	2	2	6	6	4	4	8	8
Switch Phase								
Minimum Initial (s)	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0
Minimum Split (s)	22.1	22.1	22.1	22.1	23.9	23.9	23.9	23.9
Total Split (s)	28.0	28.0	28.0	28.0	32.0	32.0	32.0	32.0
Total Split (%)	46.7%	46.7%	46.7%	46.7%	53.3%	53.3%	53.3%	53.3%
Maximum Green (s)	21.9	21.9	21.9	21.9	25.1	25.1	25.1	25.1
Yellow Time (s)	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0
All-Red Time (s)	3.1	3.1	3.1	3.1	3.9	3.9	3.9	3.9
Lost Time Adjust (s)	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
Total Lost Time (s)	6.1	6.1	6.1	6.1	6.9	6.9	6.9	6.9
Lead/Lag								
Lead-Lag Optimize?								
Vehicle Extension (s)	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0
Recall Mode	C-Max	C-Max	C-Max	C-Max	Max	Max	Max	Max
Walk Time (s)	7.0	7.0	7.0	7.0	7.0	7.0	7.0	7.0
Flash Dont Walk (s)	9.0	9.0	9.0	9.0	10.0	10.0	10.0	10.0
Pedestrian Calls (#/hr)	43	43	28	28	29	29	0	0
Act Effct Green (s)	21.9	21.9	21.9	21.9	25.1	25.1	25.1	25.1
Actuated g/C Ratio	0.36	0.36	0.36	0.36	0.42	0.42	0.42	0.42
v/c Ratio	0.08	0.73	0.19	0.48	0.11	0.60	0.12	0.22
Control Delay	13.4	25.0	15.7	17.3	9.6	12.6	12.1	11.1
Queue Delay	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
Total Delay	13.4	25.0	15.7	17.3	9.6	12.6	12.1	11.1
LOS	B	C	B	B	A	B	B	B
Approach Delay		24.4		17.1		12.3		11.3
Approach LOS		C		B		B		B
Queue Length 50th (m)	1.8	39.1	3.1	22.9	2.0	16.4	2.5	9.5
Queue Length 95th (m)	6.1	#78.3	9.4	41.6	m6.0	33.8	7.5	19.6
Internal Link Dist (m)		79.0		246.0		206.0		98.4
Turn Bay Length (m)	40.0		25.0		8.0		8.0	
Base Capacity (vph)	330	600	223	609	477	713	304	721
Starvation Cap Reductn	0	0	0	0	0	0	0	0
Spillback Cap Reductn	0	0	0	0	0	0	0	0
Storage Cap Reductn	0	0	0	0	0	0	0	0
Reduced v/c Ratio	0.08	0.73	0.19	0.48	0.11	0.60	0.13	0.22

Intersection Summary


Cycle Length: 60
 Actuated Cycle Length: 60
 Offset: 16 (27%), Referenced to phase 2:EBTL and 6:WBTL, Start of Green
 Natural Cycle: 50

Lanes, Volumes, Timings
4: Booth & Gladstone

Future Background 2025AM Peak Hour
18 Louisa Street

Control Type: Actuated-Coordinated
 Maximum v/c Ratio: 0.73
 Intersection Signal Delay: 17.1
 Intersection LOS: B
 Intersection Capacity Utilization 86.8%
 ICU Level of Service E
 Analysis Period (min) 15
 # 95th percentile volume exceeds capacity, queue may be longer.
 Queue shown is maximum after two cycles.
 m Volume for 95th percentile queue is metered by upstream signal.

Splits and Phases: 4: Booth & Gladstone



Lanes, Volumes, Timings
5: Arthur & Gladstone

Future Background 2025AM Peak Hour
18 Louisa Street

Lane Group	EBL	EBT	WBT	SBT
Lane Configurations		↔	↔	↔
Traffic Volume (vph)	30	467	331	0
Future Volume (vph)	30	467	331	0
Lane Group Flow (vph)	0	498	345	36
Turn Type	Perm	NA	NA	NA
Protected Phases		2	6	8
Permitted Phases	2			
Detector Phase	2	2	6	8
Switch Phase				
Minimum Initial (s)	10.0	10.0	10.0	10.0
Minimum Split (s)	29.5	29.5	29.5	23.2
Total Split (s)	31.8	31.8	31.8	23.2
Total Split (%)	57.8%	57.8%	57.8%	42.2%
Maximum Green (s)	26.3	26.3	26.3	18.0
Yellow Time (s)	3.0	3.0	3.0	3.0
All-Red Time (s)	2.5	2.5	2.5	2.2
Lost Time Adjust (s)		0.0	0.0	0.0
Total Lost Time (s)		5.5	5.5	5.2
Lead/Lag				
Lead-Lag Optimize?				
Vehicle Extension (s)	3.0	3.0	3.0	3.0
Recall Mode	Max	Max	Max	None
Walk Time (s)	19.0	19.0	19.0	10.0
Flash Dont Walk (s)	5.0	5.0	5.0	8.0
Pedestrian Calls (#/hr)	84	84	44	35
Act Effct Green (s)		42.0	42.0	13.2
Actuated g/C Ratio		0.75	0.75	0.23
v/c Ratio		0.40	0.27	0.09
Control Delay		8.0	6.7	4.5
Queue Delay		0.0	0.0	0.0
Total Delay		8.0	6.7	4.5
LOS		A	A	A
Approach Delay		8.0	6.7	4.5
Approach LOS		A	A	A
Queue Length 50th (m)		22.1	13.3	0.0
Queue Length 95th (m)		60.0	36.8	3.7
Internal Link Dist (m)		246.0	139.3	183.9
Turn Bay Length (m)				
Base Capacity (vph)		1246	1256	519
Starvation Cap Reductn		0	0	0
Spillback Cap Reductn		0	0	0
Storage Cap Reductn		0	0	0
Reduced v/c Ratio		0.40	0.27	0.07

Intersection Summary
 Cycle Length: 55
 Actuated Cycle Length: 56.2
 Natural Cycle: 55
 Control Type: Actuated-Uncoordinated

Lanes, Volumes, Timings
5: Arthur & Gladstone

Future Background 2025AM Peak Hour
18 Louisa Street

Maximum v/c Ratio: 0.40
 Intersection Signal Delay: 7.4
 Intersection Capacity Utilization 72.3%
 Analysis Period (min) 15
 Intersection LOS: A
 ICU Level of Service C

Splits and Phases: 5: Arthur & Gladstone



Lanes, Volumes, Timings
6: Booth & Raymond

Future Background 2025AM Peak Hour
18 Louisa Street


Lane Group	WBT	WBR	NBL	NBT	SBT
Lane Configurations	↖ ↗	↖ ↗	↖ ↗	↖ ↗	↖ ↗
Traffic Volume (vph)	218	108	38	405	214
Future Volume (vph)	218	108	38	405	214
Lane Group Flow (vph)	340	108	38	405	248
Turn Type	NA	Perm	Perm	NA	NA
Protected Phases	8			2	6
Permitted Phases		8	2		
Detector Phase	8	8	2	2	6
Switch Phase					
Minimum Initial (s)	10.0	10.0	10.0	10.0	10.0
Minimum Split (s)	25.5	25.5	25.2	25.2	25.2
Total Split (s)	25.5	25.5	34.5	34.5	34.5
Total Split (%)	42.5%	42.5%	57.5%	57.5%	57.5%
Maximum Green (s)	20.0	20.0	29.3	29.3	29.3
Yellow Time (s)	3.3	3.3	3.3	3.3	3.3
All-Red Time (s)	2.2	2.2	1.9	1.9	1.9
Lost Time Adjust (s)	0.0	0.0	0.0	0.0	0.0
Total Lost Time (s)	5.5	5.5	5.2	5.2	5.2
Lead/Lag					
Lead-Lag Optimize?					
Vehicle Extension (s)	3.0	3.0	3.0	3.0	3.0
Recall Mode	Max	Max	C-Max	C-Max	C-Max
Walk Time (s)	11.0	11.0	15.0	15.0	15.0
Flash Dont Walk (s)	9.0	9.0	5.0	5.0	5.0
Pedestrian Calls (#/hr)	15	15	48	48	38
Act Effct Green (s)	20.0	20.0	29.3	29.3	29.3
Actuated g/C Ratio	0.33	0.33	0.49	0.49	0.49
v/c Ratio	0.62	0.20	0.08	0.48	0.30
Control Delay	22.7	4.7	8.7	12.6	14.3
Queue Delay	0.0	0.0	0.0	0.0	0.0
Total Delay	22.7	4.7	8.7	12.6	14.3
LOS	C	A	A	B	B
Approach Delay	18.4			12.2	14.3
Approach LOS	B			B	B
Queue Length 50th (m)	30.8	0.0	2.1	27.5	15.0
Queue Length 95th (m)	54.3	8.4	6.1	47.1	m25.1
Internal Link Dist (m)	302.1			65.0	206.0
Turn Bay Length (m)		75.0	25.0		
Base Capacity (vph)	549	533	500	852	835
Starvation Cap Reductn	0	0	0	0	0
Spillback Cap Reductn	0	0	0	0	0
Storage Cap Reductn	0	0	0	0	0
Reduced v/c Ratio	0.62	0.20	0.08	0.48	0.30

Intersection Summary
 Cycle Length: 60
 Actuated Cycle Length: 60
 Offset: 35 (58%), Referenced to phase 2:NBT and 6:SBT, Start of Green
 Natural Cycle: 55

Lanes, Volumes, Timings
6: Booth & Raymond

Future Background 2025AM Peak Hour
18 Louisa Street

Control Type: Actuated-Coordinated
 Maximum v/c Ratio: 0.62
 Intersection Signal Delay: 15.1
 Intersection LOS: B
 Intersection Capacity Utilization 64.2%
 ICU Level of Service C
 Analysis Period (min) 15
 m Volume for 95th percentile queue is metered by upstream signal.



Lanes, Volumes, Timings
1: Bronson & Raymond/Catherine

Future Background 2025PM Peak Hour
18 Louisa Street

Lane Group	WBL	WBT	NBL	NBT	SBT
Lane Configurations	↔↔↔	↔↔↔	↔↔↔	↕↕↕	↕↕↕
Traffic Volume (vph)	690	573	308	803	829
Future Volume (vph)	690	573	308	803	829
Lane Group Flow (vph)	386	1147	308	803	994
Turn Type	Perm	NA	pm+pt	NA	NA
Protected Phases		8	5	2	6
Permitted Phases		8	2		
Detector Phase	8	8	5	2	6
Switch Phase					
Minimum Initial (s)	10.0	10.0	5.0	10.0	10.0
Minimum Split (s)	28.3	28.3	11.8	24.8	24.8
Total Split (s)	33.0	33.0	25.0	67.0	42.0
Total Split (%)	33.0%	33.0%	25.0%	67.0%	42.0%
Maximum Green (s)	26.7	26.7	18.2	60.2	35.2
Yellow Time (s)	3.3	3.3	3.3	3.3	3.3
All-Red Time (s)	3.0	3.0	3.5	3.5	3.5
Lost Time Adjust (s)	0.0	0.0	0.0	0.0	0.0
Total Lost Time (s)	6.3	6.3	6.8	6.8	6.8
Lead/Lag			Lead		Lag
Lead-Lag Optimize?			Yes		Yes
Vehicle Extension (s)	3.0	3.0	3.0	3.0	3.0
Recall Mode	Max	Max	None	C-Max	C-Max
Walk Time (s)	7.0	7.0		7.0	7.0
Flash Dont Walk (s)	15.0	15.0		10.0	10.0
Pedestrian Calls (#/hr)	24	24		29	41
Act Effct Green (s)	26.7	26.7	60.2	60.2	37.1
Actuated g/C Ratio	0.27	0.27	0.60	0.60	0.37
v/c Ratio	1.02	0.98	0.86	0.40	0.83
Control Delay	88.2	56.2	44.5	11.2	21.9
Queue Delay	0.0	0.0	0.0	0.0	4.0
Total Delay	88.2	56.2	44.5	11.2	26.0
LOS	F	E	D	B	C
Approach Delay		64.2		20.4	26.0
Approach LOS		E		C	C
Queue Length 50th (m)	~89.1	80.8	38.2	39.8	64.4
Queue Length 95th (m)	#156.3	#113.2	#79.6	51.8	#128.7
Internal Link Dist (m)		247.5		81.5	56.5
Turn Bay Length (m)	110.0		45.0		
Base Capacity (vph)	380	1173	385	1996	1200
Starvation Cap Reductn	0	0	0	0	138
Spillback Cap Reductn	0	0	0	0	0
Storage Cap Reductn	0	0	0	0	0
Reduced v/c Ratio	1.02	0.98	0.80	0.40	0.94

Intersection Summary

Cycle Length: 100
Actuated Cycle Length: 100
Offset: 60 (60%), Referenced to phase 2:NBT and 6:SBT, Start of Green
Natural Cycle: 90

Lanes, Volumes, Timings
1: Bronson & Raymond/Catherine

Future Background 2025PM Peak Hour
18 Louisa Street

Control Type: Actuated-Coordinated	
Maximum v/c Ratio: 1.02	
Intersection Signal Delay: 40.4	Intersection LOS: D
Intersection Capacity Utilization 89.9%	ICU Level of Service E
Analysis Period (min) 15	
~ Volume exceeds capacity, queue is theoretically infinite. Queue shown is maximum after two cycles.	
# 95th percentile volume exceeds capacity, queue may be longer. Queue shown is maximum after two cycles.	

Splits and Phases: 1: Bronson & Raymond/Catherine



Lanes, Volumes, Timings
2: Bronson & Arlington

Future Background 2025PM Peak Hour
18 Louisa Street

Lane Group	EBL	EBT	WBL	WBT	NBL	NBT	SBL	SBT
Lane Configurations		↕		↕		↕		↕
Traffic Volume (vph)	11	2	2	0	24	1049	3	946
Future Volume (vph)	11	2	2	0	24	1049	3	946
Lane Group Flow (vph)	0	63	0	14	0	1085	0	965
Turn Type	Perm	NA	Perm	NA	Perm	NA	Perm	NA
Protected Phases		4		8		2		6
Permitted Phases	4		8		2		6	
Detector Phase	4	4	8	8	2	2	6	6
Switch Phase								
Minimum Initial (s)	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0
Minimum Split (s)	22.6	22.6	22.6	22.6	17.2	17.2	17.2	17.2
Total Split (s)	23.0	23.0	23.0	23.0	77.0	77.0	77.0	77.0
Total Split (%)	23.0%	23.0%	23.0%	23.0%	77.0%	77.0%	77.0%	77.0%
Maximum Green (s)	17.4	17.4	17.4	17.4	71.8	71.8	71.8	71.8
Yellow Time (s)	3.3	3.3	3.3	3.3	3.3	3.3	3.3	3.3
All-Red Time (s)	2.3	2.3	2.3	2.3	1.9	1.9	1.9	1.9
Lost Time Adjust (s)		0.0		0.0		0.0		0.0
Total Lost Time (s)		5.6		5.6		5.2		5.2
Lead/Lag								
Lead-Lag Optimize?								
Vehicle Extension (s)	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0
Recall Mode	None	None	None	None	C-Max	C-Max	C-Max	C-Max
Walk Time (s)	7.0	7.0	7.0	7.0	7.0	7.0	7.0	7.0
Flash Dont Walk (s)	10.0	10.0	10.0	10.0	5.0	5.0	5.0	5.0
Pedestrian Calls (#/hr)	19	19	20	20	29	29	39	39
Act Effct Green (s)		12.8		12.8		80.6		80.6
Actuated g/C Ratio		0.13		0.13		0.81		0.81
v/c Ratio		0.28		0.07		0.45		0.38
Control Delay		17.7		9.4		2.8		2.0
Queue Delay		0.0		0.0		0.1		0.0
Total Delay		17.7		9.4		2.9		2.0
LOS		B		A		A		A
Approach Delay		17.7		9.4		2.9		2.0
Approach LOS		B		A		A		A
Queue Length 50th (m)		2.3		0.0		13.6		13.6
Queue Length 95th (m)		13.3		3.7		m29.4		16.5
Internal Link Dist (m)		0.1		230.9		56.5		207.2
Turn Bay Length (m)								
Base Capacity (vph)		284		253		2419		2507
Starvation Cap Reductn		0		0		239		0
Spillback Cap Reductn		3		0		0		223
Storage Cap Reductn		0		0		0		0
Reduced v/c Ratio		0.22		0.06		0.50		0.42

Intersection Summary


Cycle Length: 100
 Actuated Cycle Length: 100
 Offset: 29 (29%), Referenced to phase 2:NBT and 6:SBTL, Start of Green
 Natural Cycle: 55

Lanes, Volumes, Timings
2: Bronson & Arlington

Future Background 2025PM Peak Hour
18 Louisa Street

Control Type: Actuated-Coordinated
 Maximum v/c Ratio: 0.45
 Intersection Signal Delay: 3.0
 Intersection LOS: A
 Intersection Capacity Utilization 69.4%
 ICU Level of Service C
 Analysis Period (min) 15
 m Volume for 95th percentile queue is metered by upstream signal.

Splits and Phases: 2: Bronson & Arlington



Lanes, Volumes, Timings
3: Bronson & Gladstone


Future Background 2025PM Peak Hour
18 Louisa Street

	↖	→	↗	←	↖	↑	↗	↓
Lane Group	EBL	EBT	WBL	WBT	NBL	NBT	SBL	SBT
Lane Configurations	↖	↗	↖	↗	↖	↗	↖	↗
Traffic Volume (vph)	46	329	137	271	96	802	49	785
Future Volume (vph)	46	329	137	271	96	802	49	785
Lane Group Flow (vph)	46	401	137	288	96	939	49	869
Turn Type	Perm	NA	Perm	NA	Perm	NA	Perm	NA
Protected Phases		4		8		2		6
Permitted Phases	4		8		2		6	
Detector Phase	4	4	8	8	2	2	6	6
Switch Phase								
Minimum Initial (s)	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0
Minimum Split (s)	28.2	28.2	28.2	28.2	25.0	25.0	25.0	25.0
Total Split (s)	50.0	50.0	50.0	50.0	50.0	50.0	50.0	50.0
Total Split (%)	50.0%	50.0%	50.0%	50.0%	50.0%	50.0%	50.0%	50.0%
Maximum Green (s)	43.8	43.8	43.8	43.8	44.0	44.0	44.0	44.0
Yellow Time (s)	3.0	3.0	3.0	3.0	3.3	3.3	3.3	3.3
All-Red Time (s)	3.2	3.2	3.2	3.2	2.7	2.7	2.7	2.7
Lost Time Adjust (s)	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
Total Lost Time (s)	6.2	6.2	6.2	6.2	6.0	6.0	6.0	6.0
Lead/Lag								
Lead-Lag Optimize?								
Vehicle Extension (s)	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0
Recall Mode	Max	Max	Max	Max	C-Max	C-Max	C-Max	C-Max
Walk Time (s)	7.0	7.0	7.0	7.0	7.0	7.0	7.0	7.0
Flash Dont Walk (s)	15.0	15.0	15.0	15.0	12.0	12.0	12.0	12.0
Pedestrian Calls (#/hr)	69	69	68	68	44	44	47	47
Act Effct Green (s)	43.8	43.8	43.8	43.8	44.0	44.0	44.0	44.0
Actuated g/C Ratio	0.44	0.44	0.44	0.44	0.44	0.44	0.44	0.44
v/c Ratio	0.12	0.56	0.46	0.39	0.56	0.68	0.33	0.61
Control Delay	17.9	24.7	26.1	21.0	25.1	15.6	26.0	23.8
Queue Delay	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
Total Delay	17.9	24.7	26.1	21.0	25.1	15.6	26.0	23.8
LOS	B	C	C	C	C	B	C	C
Approach Delay		24.0		22.7		16.5		23.9
Approach LOS		C		C		B		C
Queue Length 50th (m)	5.2	56.4	18.2	36.8	9.2	51.0	6.0	66.1
Queue Length 95th (m)	12.3	85.3	36.3	57.4	#34.0	33.5	16.2	85.7
Internal Link Dist (m)		139.3		203.3		207.2		176.5
Turn Bay Length (m)	20.0		20.0		35.0		45.0	
Base Capacity (vph)	377	716	298	738	171	1375	150	1418
Starvation Cap Reductn	0	0	0	0	0	0	0	0
Spillback Cap Reductn	0	0	0	0	0	0	0	0
Storage Cap Reductn	0	0	0	0	0	0	0	0
Reduced v/c Ratio	0.12	0.56	0.46	0.39	0.56	0.68	0.33	0.61
Intersection Summary								
Cycle Length: 100								
Actuated Cycle Length: 100								
Offset: 40 (40%), Referenced to phase 2:NBT and 6:SBTL, Start of Green								
Natural Cycle: 60								

Lanes, Volumes, Timings
3: Bronson & Gladstone

Future Background 2025PM Peak Hour
18 Louisa Street

Control Type: Actuated-Coordinated	
Maximum v/c Ratio: 0.68	
Intersection Signal Delay: 21.0	Intersection LOS: C
Intersection Capacity Utilization 89.3%	ICU Level of Service E
Analysis Period (min) 15	
# 95th percentile volume exceeds capacity, queue may be longer.	
Queue shown is maximum after two cycles.	



Lanes, Volumes, Timings
4: Booth & Gladstone

Future Background 2025PM Peak Hour
18 Louisa Street

Lane Group	EBL	EBT	WBL	WBT	NBL	NBT	SBL	SBT
Lane Configurations	↔	↗	↖	↘	↙	↕	↗	↖
Traffic Volume (vph)	37	324	138	530	99	372	47	351
Future Volume (vph)	37	324	138	530	99	372	47	351
Lane Group Flow (vph)	37	366	138	570	99	446	47	371
Turn Type	Perm	NA	Perm	NA	Perm	NA	Perm	NA
Protected Phases		2		6		4		8
Permitted Phases	2		6		4		8	
Detector Phase	2	2	6	6	4	4	8	8
Switch Phase								
Minimum Initial (s)	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0
Minimum Split (s)	22.1	22.1	22.1	22.1	23.9	23.9	23.9	23.9
Total Split (s)	43.0	43.0	43.0	43.0	37.0	37.0	37.0	37.0
Total Split (%)	53.8%	53.8%	53.8%	53.8%	46.3%	46.3%	46.3%	46.3%
Maximum Green (s)	36.9	36.9	36.9	36.9	30.1	30.1	30.1	30.1
Yellow Time (s)	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0
All-Red Time (s)	3.1	3.1	3.1	3.1	3.9	3.9	3.9	3.9
Lost Time Adjust (s)	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
Total Lost Time (s)	6.1	6.1	6.1	6.1	6.9	6.9	6.9	6.9
Lead/Lag								
Lead-Lag Optimize?								
Vehicle Extension (s)	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0
Recall Mode	C-Max	C-Max	C-Max	C-Max	Max	Max	Max	Max
Walk Time (s)	7.0	7.0	7.0	7.0	7.0	7.0	7.0	7.0
Flash Dont Walk (s)	9.0	9.0	9.0	9.0	10.0	10.0	10.0	10.0
Pedestrian Calls (#/hr)	46	46	41	41	27	27	27	27
Act Effct Green (s)	36.9	36.9	36.9	36.9	30.1	30.1	30.1	30.1
Actuated g/C Ratio	0.46	0.46	0.46	0.46	0.38	0.38	0.38	0.38
v/c Ratio	0.17	0.47	0.39	0.72	0.36	0.70	0.21	0.57
Control Delay	15.1	16.9	28.9	34.0	22.7	27.4	20.1	23.8
Queue Delay	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
Total Delay	15.1	16.9	28.9	34.0	22.7	27.4	20.1	23.8
LOS	B	B	C	C	C	C	C	C
Approach Delay		16.7		33.0		26.5		23.4
Approach LOS		B		C		C		C
Queue Length 50th (m)	3.2	35.4	21.4	93.2	10.6	54.4	4.7	43.3
Queue Length 95th (m)	9.2	57.6	39.0	124.6	23.4	86.8	12.7	69.6
Internal Link Dist (m)		79.0		246.0		206.0		98.4
Turn Bay Length (m)	40.0		25.0		8.0		8.0	
Base Capacity (vph)	220	775	357	791	277	639	220	650
Starvation Cap Reductn	0	0	0	0	0	0	0	0
Spillback Cap Reductn	0	0	0	0	0	0	0	0
Storage Cap Reductn	0	0	0	0	0	0	0	0
Reduced v/c Ratio	0.17	0.47	0.39	0.72	0.36	0.70	0.21	0.57

Intersection Summary


Cycle Length: 80
 Actuated Cycle Length: 80
 Offset: 51 (64%), Referenced to phase 2:EBTL and 6:WBTL, Start of Green
 Natural Cycle: 55

Lanes, Volumes, Timings
4: Booth & Gladstone

Future Background 2025PM Peak Hour
18 Louisa Street

Control Type: Actuated-Coordinated
 Maximum v/c Ratio: 0.72
 Intersection Signal Delay: 26.2
 Intersection Capacity Utilization 96.4%
 Analysis Period (min) 15
 Intersection LOS: C
 ICU Level of Service F

Splits and Phases: 4: Booth & Gladstone



Lanes, Volumes, Timings
5: Arthur & Gladstone

Future Background 2025PM Peak Hour
18 Louisa Street

	↖	→	↙	←	↓
Lane Group	EBL	EBT	WBL	WBT	SBT
Lane Configurations		↕		↕	↕
Traffic Volume (vph)	31	481	1	614	1
Future Volume (vph)	31	481	1	614	1
Lane Group Flow (vph)	0	518	0	624	68
Turn Type	Perm	NA	Perm	NA	NA
Protected Phases		2		6	8
Permitted Phases	2		6		
Detector Phase	2	2	6	6	8
Switch Phase					
Minimum Initial (s)	10.0	10.0	10.0	10.0	10.0
Minimum Split (s)	29.5	29.5	29.5	29.5	23.2
Total Split (s)	56.8	56.8	56.8	56.8	23.2
Total Split (%)	71.0%	71.0%	71.0%	71.0%	29.0%
Maximum Green (s)	51.3	51.3	51.3	51.3	18.0
Yellow Time (s)	3.0	3.0	3.0	3.0	3.0
All-Red Time (s)	2.5	2.5	2.5	2.5	2.2
Lost Time Adjust (s)		0.0		0.0	0.0
Total Lost Time (s)		5.5		5.5	5.2
Lead/Lag					
Lead-Lag Optimize?					
Vehicle Extension (s)	3.0	3.0	3.0	3.0	3.0
Recall Mode	C-Max	C-Max	C-Max	C-Max	None
Walk Time (s)	19.0	19.0	19.0	19.0	10.0
Flash Dont Walk (s)	5.0	5.0	5.0	5.0	8.0
Pedestrian Calls (#/hr)	75	75	59	59	45
Act Effct Green (s)		58.6		58.6	14.8
Actuated g/C Ratio		0.73		0.73	0.18
v/c Ratio		0.43		0.49	0.23
Control Delay		5.8		8.3	12.3
Queue Delay		0.0		0.3	0.0
Total Delay		5.8		8.5	12.3
LOS		A		A	B
Approach Delay		5.8		8.5	12.3
Approach LOS		A		A	B
Queue Length 50th (m)		19.9		46.6	1.7
Queue Length 95th (m)		30.5		72.5	11.3
Internal Link Dist (m)		246.0		139.3	183.9
Turn Bay Length (m)					
Base Capacity (vph)		1205		1274	348
Starvation Cap Reductn		0		182	0
Spillback Cap Reductn		0		0	0
Storage Cap Reductn		0		0	0
Reduced v/c Ratio		0.43		0.57	0.20
Intersection Summary					
Cycle Length: 80					
Actuated Cycle Length: 80					
Offset: 65 (81%), Referenced to phase 2:EBTL and 6:WBTL, Start of Green					
Natural Cycle: 60					

Lanes, Volumes, Timings
5: Arthur & Gladstone

Future Background 2025PM Peak Hour
18 Louisa Street

Control Type: Actuated-Coordinated	
Maximum v/c Ratio: 0.49	
Intersection Signal Delay: 7.5	Intersection LOS: A
Intersection Capacity Utilization 76.5%	ICU Level of Service D
Analysis Period (min) 15	
Splits and Phases: 5: Arthur & Gladstone	

Lanes, Volumes, Timings
6: Booth & Raymond

Future Background 2025PM Peak Hour
18 Louisa Street

Lane Group	WBT	WBR	NBL	NBT	SBT
Lane Configurations	↔	↔	↔	↔	↔
Traffic Volume (vph)	331	194	31	350	502
Future Volume (vph)	331	194	31	350	502
Lane Group Flow (vph)	508	194	31	350	592
Turn Type	NA	Perm	Perm	NA	NA
Protected Phases	8			2	6
Permitted Phases		8	2		
Detector Phase	8	8	2	2	6
Switch Phase					
Minimum Initial (s)	10.0	10.0	10.0	10.0	10.0
Minimum Split (s)	25.5	25.5	25.2	25.2	25.2
Total Split (s)	25.5	25.5	44.5	44.5	44.5
Total Split (%)	36.4%	36.4%	63.6%	63.6%	63.6%
Maximum Green (s)	20.0	20.0	39.3	39.3	39.3
Yellow Time (s)	3.3	3.3	3.3	3.3	3.3
All-Red Time (s)	2.2	2.2	1.9	1.9	1.9
Lost Time Adjust (s)	0.0	0.0	0.0	0.0	0.0
Total Lost Time (s)	5.5	5.5	5.2	5.2	5.2
Lead/Lag					
Lead-Lag Optimize?					
Vehicle Extension (s)	3.0	3.0	3.0	3.0	3.0
Recall Mode	Max	Max	C-Max	C-Max	C-Max
Walk Time (s)	11.0	11.0	15.0	15.0	15.0
Flash Dont Walk (s)	9.0	9.0	5.0	5.0	5.0
Pedestrian Calls (#/hr)	14	14	47	47	32
Act Effct Green (s)	20.0	20.0	39.3	39.3	39.3
Actuated g/C Ratio	0.29	0.29	0.56	0.56	0.56
v/c Ratio	1.06	0.36	0.10	0.36	0.62
Control Delay	86.0	5.5	8.2	9.7	13.5
Queue Delay	0.0	0.0	0.0	0.0	0.0
Total Delay	86.0	5.5	8.2	9.7	13.5
LOS	F	A	A	A	B
Approach Delay	63.8			9.6	13.5
Approach LOS	E			A	B
Queue Length 50th (m)	~74.8	0.0	1.7	22.9	45.6
Queue Length 95th (m)	#127.5	13.1	5.4	38.0	75.4
Internal Link Dist (m)	302.1			65.0	206.0
Turn Bay Length (m)		75.0	25.0		
Base Capacity (vph)	479	542	308	979	955
Starvation Cap Reductn	0	0	0	0	0
Spillback Cap Reductn	0	0	0	0	0
Storage Cap Reductn	0	0	0	0	0
Reduced v/c Ratio	1.06	0.36	0.10	0.36	0.62

Intersection Summary
 Cycle Length: 70
 Actuated Cycle Length: 70
 Offset: 39 (56%), Referenced to phase 2:NBT and 6:SBT, Start of Green
 Natural Cycle: 60

Lanes, Volumes, Timings
6: Booth & Raymond

Future Background 2025PM Peak Hour
18 Louisa Street

Control Type: Actuated-Coordinated
 Maximum v/c Ratio: 1.06
 Intersection Signal Delay: 33.7
 Intersection LOS: C
 Intersection Capacity Utilization 78.4%
 ICU Level of Service D
 Analysis Period (min) 15
 ~ Volume exceeds capacity, queue is theoretically infinite.
 Queue shown is maximum after two cycles.
 # 95th percentile volume exceeds capacity, queue may be longer.
 Queue shown is maximum after two cycles.



Appendix G

Synchro Intersection Worksheets – 2030 Future Background Conditions

Lanes, Volumes, Timings
1: Bronson & Raymond/Catherine

Future Background 2030AM Peak Hour
18 Louisa Street


Lane Group	WBL	WBT	NBL	NBT	SBT	Ø5	Ø9
Lane Configurations	↔↔↔	↔↔↔	↔↔	↔↔	↔↔		
Traffic Volume (vph)	554	540	551	1102	468		
Future Volume (vph)	554	540	551	1102	468		
Lane Group Flow (vph)	366	1074	551	1102	586		
Turn Type	Perm	NA	pm+pt	NA	NA		
Protected Phases		8	5 9	2	6	5	9
Permitted Phases	8		2	9			
Detector Phase	8	8	5 9	2	6		
Switch Phase							
Minimum Initial (s)	10.0	10.0		10.0	10.0	5.0	5.0
Minimum Split (s)	28.3	28.3		24.8	24.8	11.8	11.8
Total Split (s)	34.0	34.0		53.0	33.0	20.0	23.0
Total Split (%)	30.9%	30.9%		48.2%	30.0%	18%	21%
Maximum Green (s)	27.7	27.7		46.2	26.2	13.2	16.8
Yellow Time (s)	3.3	3.3		3.3	3.3	3.3	3.3
All-Red Time (s)	3.0	3.0		3.5	3.5	3.5	2.9
Lost Time Adjust (s)	0.0	0.0		0.0	0.0		
Total Lost Time (s)	6.3	6.3		6.8	6.8		
Lead/Lag				Lead	Lag		
Lead-Lag Optimize?				Yes	Yes		
Vehicle Extension (s)	3.0	3.0		3.0	3.0	3.0	3.0
Recall Mode	Max	Max		C-Max	C-Max	Max	Max
Walk Time (s)	7.0	7.0		7.0	7.0		
Flash Dont Walk (s)	15.0	15.0		10.0	10.0		
Pedestrian Calls (#/hr)	40	40		45	26		
Act Effct Green (s)	27.7	27.7		62.4	69.2	26.2	
Actuated g/C Ratio	0.25	0.25		0.57	0.63	0.24	
v/c Ratio	1.04	0.99		0.93	0.53	0.79	
Control Delay	99.8	62.0		42.2	12.5	43.7	
Queue Delay	0.0	0.0		0.0	0.0	12.9	
Total Delay	99.8	62.0		42.2	12.5	56.6	
LOS	F	E		D	B	E	
Approach Delay		71.6			22.4	56.6	
Approach LOS		E			C	E	
Queue Length 50th (m)	~98.9	83.0		60.7	63.8	60.1	
Queue Length 95th (m)	#164.0	#115.8		#122.5	80.0	80.6	
Internal Link Dist (m)		247.5			81.5	56.5	
Turn Bay Length (m)	110.0			45.0			
Base Capacity (vph)	352	1090		594	2086	741	
Starvation Cap Reductn	0	0		0	0	142	
Spillback Cap Reductn	0	0		0	0	40	0
Storage Cap Reductn	0	0		0	0	0	
Reduced v/c Ratio	1.04	0.99		0.93	0.54	0.98	

Intersection Summary
 Cycle Length: 110
 Actuated Cycle Length: 110
 Offset: 38 (35%), Referenced to phase 2:NBT and 6:SBT, Start of Green
 Natural Cycle: 100

Lanes, Volumes, Timings
1: Bronson & Raymond/Catherine

Future Background 2030AM Peak Hour
18 Louisa Street

Control Type: Actuated-Coordinated
 Maximum v/c Ratio: 1.04
 Intersection Signal Delay: 47.1
 Intersection LOS: D
 Intersection Capacity Utilization 91.0%
 ICU Level of Service F
 Analysis Period (min) 15
 ~ Volume exceeds capacity, queue is theoretically infinite.
 Queue shown is maximum after two cycles.
 # 95th percentile volume exceeds capacity, queue may be longer.
 Queue shown is maximum after two cycles.



Lanes, Volumes, Timings
2: Bronson & Arlington

Future Background 2030AM Peak Hour
18 Louisa Street

Lane Group	EBL	EBT	WBL	WBT	NBL	NBT	SBL	SBT
Lane Configurations		↕		↕		↕		↕
Traffic Volume (vph)	9	4	8	2	13	1449	2	562
Future Volume (vph)	9	4	8	2	13	1449	2	562
Lane Group Flow (vph)	0	37	0	21	0	1468	0	578
Turn Type	Perm	NA	Perm	NA	Perm	NA	Perm	NA
Protected Phases		4		8		2		6
Permitted Phases	4		8		2		6	
Detector Phase	4	4	8	8	2	2	6	6
Switch Phase								
Minimum Initial (s)	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0
Minimum Split (s)	22.6	22.6	22.6	22.6	17.2	17.2	17.2	17.2
Total Split (s)	23.0	23.0	23.0	23.0	87.0	87.0	87.0	87.0
Total Split (%)	20.9%	20.9%	20.9%	20.9%	79.1%	79.1%	79.1%	79.1%
Maximum Green (s)	17.4	17.4	17.4	17.4	81.8	81.8	81.8	81.8
Yellow Time (s)	3.3	3.3	3.3	3.3	3.3	3.3	3.3	3.3
All-Red Time (s)	2.3	2.3	2.3	2.3	1.9	1.9	1.9	1.9
Lost Time Adjust (s)		0.0		0.0		0.0		0.0
Total Lost Time (s)		5.6		5.6		5.2		5.2
Lead/Lag								
Lead-Lag Optimize?								
Vehicle Extension (s)	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0
Recall Mode	None	None	None	None	C-Max	C-Max	C-Max	C-Max
Walk Time (s)	7.0	7.0	7.0	7.0	7.0	7.0	7.0	7.0
Flash Dont Walk (s)	10.0	10.0	10.0	10.0	5.0	5.0	5.0	5.0
Pedestrian Calls (#/hr)	23	23	19	19	21	21	27	27
Act Effct Green (s)		12.8		12.8		90.6		90.6
Actuated g/C Ratio		0.12		0.12		0.82		0.82
v/c Ratio		0.20		0.13		0.57		0.23
Control Delay		24.3		29.0		4.4		3.3
Queue Delay		0.0		0.0		0.0		0.0
Total Delay		24.3		29.0		4.4		3.4
LOS		C		C		A		A
Approach Delay		24.3		29.0		4.4		3.4
Approach LOS		C		C		A		A
Queue Length 50th (m)		2.6		2.0		28.4		11.6
Queue Length 95th (m)		11.7		9.0		m44.6		22.9
Internal Link Dist (m)		0.1		230.9		56.5		207.2
Turn Bay Length (m)								
Base Capacity (vph)		242		211		2559		2463
Starvation Cap Reductn		0		0		96		0
Spillback Cap Reductn		2		1		0		400
Storage Cap Reductn		0		0		0		0
Reduced v/c Ratio		0.15		0.10		0.60		0.28

Intersection Summary

Cycle Length: 110
 Actuated Cycle Length: 110
 Offset: 11 (10%), Referenced to phase 2:NBT and 6:SBTL, Start of Green
 Natural Cycle: 60

Lanes, Volumes, Timings
2: Bronson & Arlington

Future Background 2030AM Peak Hour
18 Louisa Street

Control Type: Actuated-Coordinated
 Maximum v/c Ratio: 0.57
 Intersection Signal Delay: 4.7
 Intersection Capacity Utilization 72.6%
 Analysis Period (min) 15
 m Volume for 95th percentile queue is metered by upstream signal.

Splits and Phases: 2: Bronson & Arlington



Lanes, Volumes, Timings
3: Bronson & Gladstone

Future Background 2030AM Peak Hour
18 Louisa Street

	EBL	EBT	WBL	WBT	NBL	NBT	SBL	SBT
Lane Configurations	↖	↗	↖	↗	↖	↗	↖	↗
Traffic Volume (vph)	46	354	83	191	123	1142	13	420
Future Volume (vph)	46	354	83	191	123	1142	13	420
Lane Group Flow (vph)	46	443	83	209	123	1292	13	459
Turn Type	Perm	NA	Perm	NA	Perm	NA	Perm	NA
Protected Phases		4		8		2		6
Permitted Phases	4		8		2		6	
Detector Phase	4	4	8	8	2	2	6	6
Switch Phase								
Minimum Initial (s)	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0
Minimum Split (s)	28.2	28.2	28.2	28.2	25.0	25.0	25.0	25.0
Total Split (s)	37.0	37.0	37.0	37.0	58.0	58.0	58.0	58.0
Total Split (%)	38.9%	38.9%	38.9%	38.9%	61.1%	61.1%	61.1%	61.1%
Maximum Green (s)	30.8	30.8	30.8	30.8	52.0	52.0	52.0	52.0
Yellow Time (s)	3.0	3.0	3.0	3.0	3.3	3.3	3.3	3.3
All-Red Time (s)	3.2	3.2	3.2	3.2	2.7	2.7	2.7	2.7
Lost Time Adjust (s)	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
Total Lost Time (s)	6.2	6.2	6.2	6.2	6.0	6.0	6.0	6.0
Lead/Lag								
Lead-Lag Optimize?								
Vehicle Extension (s)	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0
Recall Mode	Max	Max	Max	Max	C-Max	C-Max	C-Max	C-Max
Walk Time (s)	7.0	7.0	7.0	7.0	7.0	7.0	7.0	7.0
Flash Dont Walk (s)	15.0	15.0	15.0	15.0	12.0	12.0	12.0	12.0
Pedestrian Calls (/hr)	85	85	36	36	36	36	31	31
Act Effct Green (s)	30.8	30.8	30.8	30.8	52.0	52.0	52.0	52.0
Actuated g/C Ratio	0.32	0.32	0.32	0.32	0.55	0.55	0.55	0.55
v/c Ratio	0.15	0.84	0.58	0.39	0.28	0.74	0.11	0.27
Control Delay	24.4	46.0	45.8	27.6	13.7	19.6	13.2	11.9
Queue Delay	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
Total Delay	24.4	46.0	45.8	27.6	13.7	19.6	13.2	11.9
LOS	C	D	D	C	B	B	B	B
Approach Delay		44.0		32.7		19.1		11.9
Approach LOS		D		C		B		B
Queue Length 50th (m)	5.9	74.9	12.6	29.4	11.4	89.3	1.1	22.1
Queue Length 95th (m)	14.3	#125.4	#33.2	48.8	22.6	115.1	4.5	31.0
Internal Link Dist (m)		139.3		203.3		207.2		176.5
Turn Bay Length (m)	20.0		20.0		35.0		45.0	
Base Capacity (vph)	317	527	143	534	437	1745	118	1725
Starvation Cap Reductn	0	0	0	0	0	0	0	0
Spillback Cap Reductn	0	0	0	0	0	0	0	0
Storage Cap Reductn	0	0	0	0	0	0	0	0
Reduced v/c Ratio	0.15	0.84	0.58	0.39	0.28	0.74	0.11	0.27

Intersection Summary


Cycle Length: 95
 Actuated Cycle Length: 95
 Offset: 42 (44%), Referenced to phase 2:NBT and 6:SBTL, Start of Green
 Natural Cycle: 60

Lanes, Volumes, Timings
3: Bronson & Gladstone

Future Background 2030AM Peak Hour
18 Louisa Street

Control Type: Actuated-Coordinated
 Maximum v/c Ratio: 0.84
 Intersection Signal Delay: 23.9
 Intersection LOS: C
 Intersection Capacity Utilization 102.2%
 ICU Level of Service G
 Analysis Period (min) 15
 # 95th percentile volume exceeds capacity, queue may be longer.
 Queue shown is maximum after two cycles.

Splits and Phases: 3: Bronson & Gladstone



Lanes, Volumes, Timings
4: Booth & Gladstone

Future Background 2030AM Peak Hour
18 Louisa Street

	↖	→	↗	←	↖	↑	↗	↓
Lane Group	EBL	EBT	WBL	WBT	NBL	NBT	SBL	SBT
Lane Configurations	↖	↗	↖	↗	↖	↗	↖	↗
Traffic Volume (vph)	26	428	42	283	51	372	38	142
Future Volume (vph)	26	428	42	283	51	372	38	142
Lane Group Flow (vph)	26	499	42	314	51	449	38	162
Turn Type	Perm	NA	Perm	NA	Perm	NA	Perm	NA
Protected Phases		2		6		4		8
Permitted Phases	2		6		4		8	
Detector Phase	2	2	6	6	4	4	8	8
Switch Phase								
Minimum Initial (s)	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0
Minimum Split (s)	22.1	22.1	22.1	22.1	23.9	23.9	23.9	23.9
Total Split (s)	28.0	28.0	28.0	28.0	32.0	32.0	32.0	32.0
Total Split (%)	46.7%	46.7%	46.7%	46.7%	53.3%	53.3%	53.3%	53.3%
Maximum Green (s)	21.9	21.9	21.9	21.9	25.1	25.1	25.1	25.1
Yellow Time (s)	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0
All-Red Time (s)	3.1	3.1	3.1	3.1	3.9	3.9	3.9	3.9
Lost Time Adjust (s)	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
Total Lost Time (s)	6.1	6.1	6.1	6.1	6.9	6.9	6.9	6.9
Lead/Lag								
Lead-Lag Optimize?								
Vehicle Extension (s)	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0
Recall Mode	C-Max	C-Max	C-Max	C-Max	Max	Max	Max	Max
Walk Time (s)	7.0	7.0	7.0	7.0	7.0	7.0	7.0	7.0
Flash Dont Walk (s)	9.0	9.0	9.0	9.0	10.0	10.0	10.0	10.0
Pedestrian Calls (#/hr)	43	43	28	28	29	29	0	0
Act Effct Green (s)	21.9	21.9	21.9	21.9	25.1	25.1	25.1	25.1
Actuated g/C Ratio	0.36	0.36	0.36	0.36	0.42	0.42	0.42	0.42
v/c Ratio	0.08	0.83	0.23	0.51	0.11	0.63	0.13	0.22
Control Delay	13.5	31.6	17.4	18.1	10.0	13.3	12.3	11.2
Queue Delay	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
Total Delay	13.5	31.6	17.4	18.1	10.0	13.3	12.3	11.2
LOS	B	C	B	B	A	B	B	B
Approach Delay		30.7		18.0		12.9		11.4
Approach LOS		C		B		B		B
Queue Length 50th (m)	1.8	47.0	3.1	25.3	2.0	17.0	2.5	9.8
Queue Length 95th (m)	6.2	#95.5	9.9	45.5	m6.0	36.8	7.6	20.2
Internal Link Dist (m)		79.0		246.0		206.0		98.4
Turn Bay Length (m)	40.0		25.0		8.0		8.0	
Base Capacity (vph)	312	601	181	610	475	713	291	721
Starvation Cap Reductn	0	0	0	0	0	0	0	0
Spillback Cap Reductn	0	0	0	0	0	0	0	0
Storage Cap Reductn	0	0	0	0	0	0	0	0
Reduced v/c Ratio	0.08	0.83	0.23	0.51	0.11	0.63	0.13	0.22

Intersection Summary

Cycle Length: 60
 Actuated Cycle Length: 60
 Offset: 16 (27%), Referenced to phase 2:EBTL and 6:WBTL, Start of Green
 Natural Cycle: 55

Lanes, Volumes, Timings
4: Booth & Gladstone

Future Background 2030AM Peak Hour
18 Louisa Street

Control Type: Actuated-Coordinated	
Maximum v/c Ratio: 0.83	
Intersection Signal Delay: 19.8	Intersection LOS: B
Intersection Capacity Utilization 87.8%	ICU Level of Service E
Analysis Period (min) 15	
# 95th percentile volume exceeds capacity, queue may be longer.	
Queue shown is maximum after two cycles.	
m Volume for 95th percentile queue is metered by upstream signal.	

Splits and Phases: 4: Booth & Gladstone



Lanes, Volumes, Timings
5: Arthur & Gladstone

Future Background 2030AM Peak Hour
18 Louisa Street

Lane Group	EBL	EBT	WBT	SBT
Lane Configurations		↕	↕	↕
Traffic Volume (vph)	30	542	361	0
Future Volume (vph)	30	542	361	0
Lane Group Flow (vph)	0	573	375	36
Turn Type	Perm	NA	NA	NA
Protected Phases		2	6	8
Permitted Phases	2			
Detector Phase	2	2	6	8
Switch Phase				
Minimum Initial (s)	10.0	10.0	10.0	10.0
Minimum Split (s)	29.5	29.5	29.5	23.2
Total Split (s)	31.8	31.8	31.8	23.2
Total Split (%)	57.8%	57.8%	57.8%	42.2%
Maximum Green (s)	26.3	26.3	26.3	18.0
Yellow Time (s)	3.0	3.0	3.0	3.0
All-Red Time (s)	2.5	2.5	2.5	2.2
Lost Time Adjust (s)		0.0	0.0	0.0
Total Lost Time (s)		5.5	5.5	5.2
Lead/Lag				
Lead-Lag Optimize?				
Vehicle Extension (s)	3.0	3.0	3.0	3.0
Recall Mode	Max	Max	Max	None
Walk Time (s)	19.0	19.0	19.0	10.0
Flash Dont Walk (s)	5.0	5.0	5.0	8.0
Pedestrian Calls (#/hr)	84	84	44	35
Act Effct Green (s)		42.0	42.0	13.2
Actuated g/C Ratio		0.75	0.75	0.23
v/c Ratio		0.46	0.30	0.09
Control Delay		9.0	6.9	4.5
Queue Delay		0.0	0.0	0.0
Total Delay		9.0	6.9	4.5
LOS		A	A	A
Approach Delay		9.0	6.9	4.5
Approach LOS		A	A	A
Queue Length 50th (m)		27.2	14.7	0.0
Queue Length 95th (m)		74.0	40.8	3.7
Internal Link Dist (m)		246.0	139.3	183.9
Turn Bay Length (m)				
Base Capacity (vph)		1249	1256	519
Starvation Cap Reductn		0	0	0
Spillback Cap Reductn		0	0	0
Storage Cap Reductn		0	0	0
Reduced v/c Ratio		0.46	0.30	0.07
Intersection Summary				
Cycle Length: 55				
Actuated Cycle Length: 56.2				
Natural Cycle: 60				
Control Type: Actuated-Uncoordinated				

Lanes, Volumes, Timings
5: Arthur & Gladstone

Future Background 2030AM Peak Hour
18 Louisa Street

Maximum v/c Ratio: 0.46	Intersection LOS: A
Intersection Signal Delay: 8.0	ICU Level of Service D
Intersection Capacity Utilization 76.4%	
Analysis Period (min) 15	

Splits and Phases: 5: Arthur & Gladstone



Lanes, Volumes, Timings
6: Booth & Raymond

Future Background 2030AM Peak Hour
18 Louisa Street


Lane Group	WBT	WBR	NBL	NBT	SBT
Lane Configurations	↖	↗	↖	↗	↖
Traffic Volume (vph)	218	108	38	426	222
Future Volume (vph)	218	108	38	426	222
Lane Group Flow (vph)	340	108	38	426	256
Turn Type	NA	Perm	Perm	NA	NA
Protected Phases	8			2	6
Permitted Phases		8	2		
Detector Phase	8	8	2	2	6
Switch Phase					
Minimum Initial (s)	10.0	10.0	10.0	10.0	10.0
Minimum Split (s)	25.5	25.5	25.2	25.2	25.2
Total Split (s)	25.5	25.5	34.5	34.5	34.5
Total Split (%)	42.5%	42.5%	57.5%	57.5%	57.5%
Maximum Green (s)	20.0	20.0	29.3	29.3	29.3
Yellow Time (s)	3.3	3.3	3.3	3.3	3.3
All-Red Time (s)	2.2	2.2	1.9	1.9	1.9
Lost Time Adjust (s)	0.0	0.0	0.0	0.0	0.0
Total Lost Time (s)	5.5	5.5	5.2	5.2	5.2
Lead/Lag					
Lead-Lag Optimize?					
Vehicle Extension (s)	3.0	3.0	3.0	3.0	3.0
Recall Mode	Max	Max	C-Max	C-Max	C-Max
Walk Time (s)	11.0	11.0	15.0	15.0	15.0
Flash Dont Walk (s)	9.0	9.0	5.0	5.0	5.0
Pedestrian Calls (#/hr)	15	15	48	48	38
Act Effct Green (s)	20.0	20.0	29.3	29.3	29.3
Actuated g/C Ratio	0.33	0.33	0.49	0.49	0.49
v/c Ratio	0.62	0.20	0.08	0.50	0.31
Control Delay	22.7	4.7	8.7	13.0	14.6
Queue Delay	0.0	0.0	0.0	0.0	0.0
Total Delay	22.7	4.7	8.7	13.0	14.6
LOS	C	A	A	B	B
Approach Delay	18.4			12.6	14.6
Approach LOS	B			B	B
Queue Length 50th (m)	30.8	0.0	2.1	29.5	15.8
Queue Length 95th (m)	54.3	8.4	6.1	50.2	m25.7
Internal Link Dist (m)	302.1			65.0	206.0
Turn Bay Length (m)		75.0	25.0		
Base Capacity (vph)	549	533	502	852	835
Starvation Cap Reductn	0	0	0	0	0
Spillback Cap Reductn	0	0	0	0	0
Storage Cap Reductn	0	0	0	0	0
Reduced v/c Ratio	0.62	0.20	0.08	0.50	0.31

Intersection Summary
 Cycle Length: 60
 Actuated Cycle Length: 60
 Offset: 35 (58%), Referenced to phase 2:NBTL and 6:SBT, Start of Green
 Natural Cycle: 55

Lanes, Volumes, Timings
6: Booth & Raymond

Future Background 2030AM Peak Hour
18 Louisa Street

Control Type: Actuated-Coordinated
 Maximum v/c Ratio: 0.62
 Intersection Signal Delay: 15.3
 Intersection Capacity Utilization 64.2%
 Analysis Period (min) 15
 m Volume for 95th percentile queue is metered by upstream signal.



Lanes, Volumes, Timings
1: Bronson & Raymond/Catherine

Future Background 2030PM Peak Hour
18 Louisa Street


Lane Group	WBL	WBT	NBL	NBT	SBT
Lane Configurations	↔	↔↔↔	↔	↔↔	↔↔
Traffic Volume (vph)	690	573	319	833	850
Future Volume (vph)	690	573	319	833	850
Lane Group Flow (vph)	386	1147	319	833	1015
Turn Type	Perm	NA	pm+pt	NA	NA
Protected Phases		8	5	2	6
Permitted Phases	8		2		
Detector Phase	8	8	5	2	6
Switch Phase					
Minimum Initial (s)	10.0	10.0	5.0	10.0	10.0
Minimum Split (s)	28.3	28.3	11.8	24.8	24.8
Total Split (s)	33.0	33.0	25.0	67.0	42.0
Total Split (%)	33.0%	33.0%	25.0%	67.0%	42.0%
Maximum Green (s)	26.7	26.7	18.2	60.2	35.2
Yellow Time (s)	3.3	3.3	3.3	3.3	3.3
All-Red Time (s)	3.0	3.0	3.5	3.5	3.5
Lost Time Adjust (s)	0.0	0.0	0.0	0.0	0.0
Total Lost Time (s)	6.3	6.3	6.8	6.8	6.8
Lead/Lag			Lead		Lag
Lead-Lag Optimize?			Yes		Yes
Vehicle Extension (s)	3.0	3.0	3.0	3.0	3.0
Recall Mode	Max	Max	None	C-Max	C-Max
Walk Time (s)	7.0	7.0		7.0	7.0
Flash Dont Walk (s)	15.0	15.0		10.0	10.0
Pedestrian Calls (#/hr)	24	24		29	41
Act Effct Green (s)	26.7	26.7	60.2	60.2	36.7
Actuated g/C Ratio	0.27	0.27	0.60	0.60	0.37
v/c Ratio	1.02	0.98	0.90	0.42	0.85
Control Delay	88.2	56.2	51.7	11.4	23.5
Queue Delay	0.0	0.0	0.0	0.0	5.5
Total Delay	88.2	56.2	51.7	11.4	29.0
LOS	F	E	D	B	C
Approach Delay		64.2		22.5	29.0
Approach LOS		E		C	C
Queue Length 50th (m)	~89.1	80.8	42.7	41.7	67.1
Queue Length 95th (m)	#156.3	#113.2	#88.2	54.2	#131.6
Internal Link Dist (m)		247.5		81.5	56.5
Turn Bay Length (m)	110.0		45.0		
Base Capacity (vph)	380	1173	377	1996	1188
Starvation Cap Reductn	0	0	0	0	128
Spillback Cap Reductn	0	0	0	0	0
Storage Cap Reductn	0	0	0	0	0
Reduced v/c Ratio	1.02	0.98	0.85	0.42	0.96

Intersection Summary
 Cycle Length: 100
 Actuated Cycle Length: 100
 Offset: 60 (60%), Referenced to phase 2:NBT and 6:SBT, Start of Green
 Natural Cycle: 90

Lanes, Volumes, Timings
1: Bronson & Raymond/Catherine

Future Background 2030PM Peak Hour
18 Louisa Street

Control Type: Actuated-Coordinated	
Maximum v/c Ratio: 1.02	
Intersection Signal Delay: 41.6	Intersection LOS: D
Intersection Capacity Utilization 91.2%	ICU Level of Service F
Analysis Period (min) 15	
~ Volume exceeds capacity, queue is theoretically infinite. Queue shown is maximum after two cycles.	
# 95th percentile volume exceeds capacity, queue may be longer. Queue shown is maximum after two cycles.	



Lanes, Volumes, Timings
2: Bronson & Arlington

Future Background 2030PM Peak Hour
18 Louisa Street

Lane Group	EBL	EBT	WBL	WBT	NBL	NBT	SBL	SBT
Lane Configurations		↕		↕		↕		↕
Traffic Volume (vph)	11	2	2	0	24	1089	3	970
Future Volume (vph)	11	2	2	0	24	1089	3	970
Lane Group Flow (vph)	0	63	0	14	0	1125	0	989
Turn Type	Perm	NA	Perm	NA	Perm	NA	Perm	NA
Protected Phases		4		8		2		6
Permitted Phases	4		8		2		6	
Detector Phase	4	4	8	8	2	2	6	6
Switch Phase								
Minimum Initial (s)	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0
Minimum Split (s)	22.6	22.6	22.6	22.6	17.2	17.2	17.2	17.2
Total Split (s)	23.0	23.0	23.0	23.0	77.0	77.0	77.0	77.0
Total Split (%)	23.0%	23.0%	23.0%	23.0%	77.0%	77.0%	77.0%	77.0%
Maximum Green (s)	17.4	17.4	17.4	17.4	71.8	71.8	71.8	71.8
Yellow Time (s)	3.3	3.3	3.3	3.3	3.3	3.3	3.3	3.3
All-Red Time (s)	2.3	2.3	2.3	2.3	1.9	1.9	1.9	1.9
Lost Time Adjust (s)		0.0		0.0		0.0		0.0
Total Lost Time (s)		5.6		5.6		5.2		5.2
Lead/Lag								
Lead-Lag Optimize?								
Vehicle Extension (s)	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0
Recall Mode	None	None	None	None	C-Max	C-Max	C-Max	C-Max
Walk Time (s)	7.0	7.0	7.0	7.0	7.0	7.0	7.0	7.0
Flash Dont Walk (s)	10.0	10.0	10.0	10.0	5.0	5.0	5.0	5.0
Pedestrian Calls (#/hr)	19	19	20	20	29	29	39	39
Act Effct Green (s)		12.8		12.8		80.6		80.6
Actuated g/C Ratio		0.13		0.13		0.81		0.81
v/c Ratio		0.28		0.07		0.46		0.39
Control Delay		17.7		9.4		2.9		1.9
Queue Delay		0.0		0.0		0.0		0.0
Total Delay		17.7		9.4		2.9		1.9
LOS		B		A		A		A
Approach Delay		17.7		9.4		2.9		1.9
Approach LOS		B		A		A		A
Queue Length 50th (m)		2.3		0.0		13.8		12.3
Queue Length 95th (m)		13.3		3.7		m30.0		15.2
Internal Link Dist (m)		0.1		230.9		56.5		207.2
Turn Bay Length (m)								
Base Capacity (vph)		284		253		2420		2507
Starvation Cap Reductn		0		0		175		0
Spillback Cap Reductn		3		0		0		230
Storage Cap Reductn		0		0		0		0
Reduced v/c Ratio		0.22		0.06		0.50		0.43

Intersection Summary

Cycle Length: 100
 Actuated Cycle Length: 100
 Offset: 29 (29%), Referenced to phase 2:NBTL and 6:SBTL, Start of Green
 Natural Cycle: 55

Lanes, Volumes, Timings
2: Bronson & Arlington

Future Background 2030PM Peak Hour
18 Louisa Street

Control Type: Actuated-Coordinated
 Maximum v/c Ratio: 0.46
 Intersection Signal Delay: 2.9
 Intersection LOS: A
 Intersection Capacity Utilization 70.5%
 ICU Level of Service C
 Analysis Period (min) 15
 m Volume for 95th percentile queue is metered by upstream signal.

Splits and Phases: 2: Bronson & Arlington



Lanes, Volumes, Timings
3: Bronson & Gladstone

Future Background 2030PM Peak Hour
18 Louisa Street

	↖	→	↗	←	↖	↑	↗	↓
Lane Group	EBL	EBT	WBL	WBT	NBL	NBT	SBL	SBT
Lane Configurations	↖	↗	↖	↗	↖	↗	↖	↗
Traffic Volume (vph)	46	358	137	314	96	832	49	805
Future Volume (vph)	46	358	137	314	96	832	49	805
Lane Group Flow (vph)	46	430	137	331	96	969	49	889
Turn Type	Perm	NA	Perm	NA	Perm	NA	Perm	NA
Protected Phases		4		8		2		6
Permitted Phases	4		8		2		6	
Detector Phase	4	4	8	8	2	2	6	6
Switch Phase								
Minimum Initial (s)	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0
Minimum Split (s)	28.2	28.2	28.2	28.2	25.0	25.0	25.0	25.0
Total Split (s)	50.0	50.0	50.0	50.0	50.0	50.0	50.0	50.0
Total Split (%)	50.0%	50.0%	50.0%	50.0%	50.0%	50.0%	50.0%	50.0%
Maximum Green (s)	43.8	43.8	43.8	43.8	44.0	44.0	44.0	44.0
Yellow Time (s)	3.0	3.0	3.0	3.0	3.3	3.3	3.3	3.3
All-Red Time (s)	3.2	3.2	3.2	3.2	2.7	2.7	2.7	2.7
Lost Time Adjust (s)	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
Total Lost Time (s)	6.2	6.2	6.2	6.2	6.0	6.0	6.0	6.0
Lead/Lag								
Lead-Lag Optimize?								
Vehicle Extension (s)	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0
Recall Mode	Max	Max	Max	Max	C-Max	C-Max	C-Max	C-Max
Walk Time (s)	7.0	7.0	7.0	7.0	7.0	7.0	7.0	7.0
Flash Dont Walk (s)	15.0	15.0	15.0	15.0	12.0	12.0	12.0	12.0
Pedestrian Calls (#/hr)	69	69	68	68	44	44	47	47
Act Effct Green (s)	43.8	43.8	43.8	43.8	44.0	44.0	44.0	44.0
Actuated g/C Ratio	0.44	0.44	0.44	0.44	0.44	0.44	0.44	0.44
v/c Ratio	0.13	0.60	0.49	0.45	0.58	0.70	0.35	0.63
Control Delay	18.2	25.7	27.8	22.1	26.9	16.0	27.3	24.1
Queue Delay	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
Total Delay	18.2	25.7	27.8	22.1	26.9	16.0	27.3	24.1
LOS	B	C	C	C	C	B	C	C
Approach Delay		25.0		23.8		17.0		24.3
Approach LOS		C		C		B		C
Queue Length 50th (m)	5.2	61.8	18.5	43.6	9.2	52.6	6.1	68.3
Queue Length 95th (m)	12.4	93.0	37.8	67.1	#37.4	34.2	16.7	88.4
Internal Link Dist (m)		139.3		203.3		207.2		176.5
Turn Bay Length (m)	20.0		20.0		35.0		45.0	
Base Capacity (vph)	346	719	277	740	165	1377	141	1419
Starvation Cap Reductn	0	0	0	0	0	0	0	0
Spillback Cap Reductn	0	0	0	0	0	0	0	0
Storage Cap Reductn	0	0	0	0	0	0	0	0
Reduced v/c Ratio	0.13	0.60	0.49	0.45	0.58	0.70	0.35	0.63

Intersection Summary


Cycle Length: 100
 Actuated Cycle Length: 100
 Offset: 40 (40%), Referenced to phase 2:NBT and 6:SBTL, Start of Green
 Natural Cycle: 60

Lanes, Volumes, Timings
3: Bronson & Gladstone

Future Background 2030PM Peak Hour
18 Louisa Street

Control Type: Actuated-Coordinated	
Maximum v/c Ratio: 0.70	
Intersection Signal Delay: 21.7	Intersection LOS: C
Intersection Capacity Utilization 91.7%	ICU Level of Service F
Analysis Period (min) 15	
# 95th percentile volume exceeds capacity, queue may be longer.	
Queue shown is maximum after two cycles.	

Splits and Phases: 3: Bronson & Gladstone



Lanes, Volumes, Timings
4: Booth & Gladstone

Future Background 2030PM Peak Hour
18 Louisa Street

Lane Group	EBL	EBT	WBL	WBT	NBL	NBT	SBL	SBT
Lane Configurations	↖	↗	↖	↗	↖	↗	↖	↗
Traffic Volume (vph)	37	353	138	615	99	386	47	368
Future Volume (vph)	37	353	138	615	99	386	47	368
Lane Group Flow (vph)	37	395	138	655	99	460	47	388
Turn Type	Perm	NA	Perm	NA	Perm	NA	Perm	NA
Protected Phases		2		6		4		8
Permitted Phases	2		6		4		8	
Detector Phase	2	2	6	6	4	4	8	8
Switch Phase								
Minimum Initial (s)	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0
Minimum Split (s)	22.1	22.1	22.1	22.1	23.9	23.9	23.9	23.9
Total Split (s)	43.0	43.0	43.0	43.0	37.0	37.0	37.0	37.0
Total Split (%)	53.8%	53.8%	53.8%	53.8%	46.3%	46.3%	46.3%	46.3%
Maximum Green (s)	36.9	36.9	36.9	36.9	30.1	30.1	30.1	30.1
Yellow Time (s)	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0
All-Red Time (s)	3.1	3.1	3.1	3.1	3.9	3.9	3.9	3.9
Lost Time Adjust (s)	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
Total Lost Time (s)	6.1	6.1	6.1	6.1	6.9	6.9	6.9	6.9
Lead/Lag								
Lead-Lag Optimize?								
Vehicle Extension (s)	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0
Recall Mode	C-Max	C-Max	C-Max	C-Max	Max	Max	Max	Max
Walk Time (s)	7.0	7.0	7.0	7.0	7.0	7.0	7.0	7.0
Flash Dont Walk (s)	9.0	9.0	9.0	9.0	10.0	10.0	10.0	10.0
Pedestrian Calls (#/hr)	46	46	41	41	27	27	27	27
Act Effct Green (s)	36.9	36.9	36.9	36.9	30.1	30.1	30.1	30.1
Actuated g/C Ratio	0.46	0.46	0.46	0.46	0.38	0.38	0.38	0.38
v/c Ratio	0.22	0.51	0.41	0.83	0.37	0.72	0.22	0.60
Control Delay	17.3	17.6	29.5	39.2	23.0	28.3	20.5	24.5
Queue Delay	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
Total Delay	17.3	17.6	29.5	39.2	23.0	28.3	20.5	24.5
LOS	B	B	C	D	C	C	C	C
Approach Delay		17.6		37.5		27.4		24.1
Approach LOS		B		D		C		C
Queue Length 50th (m)	3.2	39.3	22.0	108.5	10.7	56.8	4.8	45.9
Queue Length 95th (m)	10.0	63.5	39.9	#150.1	23.6	90.5	12.8	73.3
Internal Link Dist (m)		79.0		246.0		206.0		98.4
Turn Bay Length (m)	40.0		25.0		8.0		8.0	
Base Capacity (vph)	166	776	337	793	270	640	211	651
Starvation Cap Reductn	0	0	0	0	0	0	0	0
Spillback Cap Reductn	0	0	0	0	0	0	0	0
Storage Cap Reductn	0	0	0	0	0	0	0	0
Reduced v/c Ratio	0.22	0.51	0.41	0.83	0.37	0.72	0.22	0.60

Intersection Summary


Cycle Length: 80
 Actuated Cycle Length: 80
 Offset: 51 (64%), Referenced to phase 2:EBTL and 6:WBTL, Start of Green
 Natural Cycle: 60

Lanes, Volumes, Timings
4: Booth & Gladstone

Future Background 2030PM Peak Hour
18 Louisa Street

Control Type: Actuated-Coordinated
 Maximum v/c Ratio: 0.83
 Intersection Signal Delay: 28.4
 Intersection LOS: C
 Intersection Capacity Utilization 101.9%
 ICU Level of Service G
 Analysis Period (min) 15
 # 95th percentile volume exceeds capacity, queue may be longer.
 Queue shown is maximum after two cycles.

Splits and Phases: 4: Booth & Gladstone



Lanes, Volumes, Timings
5: Arthur & Gladstone

Future Background 2030PM Peak Hour
18 Louisa Street


	↖	→	↙	←	↓
Lane Group	EBL	EBT	WBL	WBT	SBT
Lane Configurations		↕		↕	↕
Traffic Volume (vph)	31	525	1	711	1
Future Volume (vph)	31	525	1	711	1
Lane Group Flow (vph)	0	562	0	721	68
Turn Type	Perm	NA	Perm	NA	NA
Protected Phases		2		6	8
Permitted Phases	2		6		
Detector Phase	2	2	6	6	8
Switch Phase					
Minimum Initial (s)	10.0	10.0	10.0	10.0	10.0
Minimum Split (s)	29.5	29.5	29.5	29.5	23.2
Total Split (s)	56.8	56.8	56.8	56.8	23.2
Total Split (%)	71.0%	71.0%	71.0%	71.0%	29.0%
Maximum Green (s)	51.3	51.3	51.3	51.3	18.0
Yellow Time (s)	3.0	3.0	3.0	3.0	3.0
All-Red Time (s)	2.5	2.5	2.5	2.5	2.2
Lost Time Adjust (s)		0.0		0.0	0.0
Total Lost Time (s)		5.5		5.5	5.2
Lead/Lag					
Lead-Lag Optimize?					
Vehicle Extension (s)	3.0	3.0	3.0	3.0	3.0
Recall Mode	C-Max	C-Max	C-Max	C-Max	None
Walk Time (s)	19.0	19.0	19.0	19.0	10.0
Flash Dont Walk (s)	5.0	5.0	5.0	5.0	8.0
Pedestrian Calls (#/hr)	75	75	59	59	45
Act Effct Green (s)		58.6		58.6	14.8
Actuated g/C Ratio		0.73		0.73	0.18
v/c Ratio		0.47		0.57	0.23
Control Delay		6.0		9.5	12.3
Queue Delay		0.0		0.3	0.0
Total Delay		6.0		9.8	12.3
LOS		A		A	B
Approach Delay		6.0		9.8	12.3
Approach LOS		A		A	B
Queue Length 50th (m)		21.0		58.9	1.7
Queue Length 95th (m)		31.6		92.5	11.3
Internal Link Dist (m)		246.0		139.3	183.9
Turn Bay Length (m)					
Base Capacity (vph)		1204		1274	348
Starvation Cap Reductn		0		164	0
Spillback Cap Reductn		0		0	0
Storage Cap Reductn		0		0	0
Reduced v/c Ratio		0.47		0.65	0.20
Intersection Summary					
Cycle Length: 80					
Actuated Cycle Length: 80					
Offset: 65 (81%), Referenced to phase 2:EBTL and 6:WBTL, Start of Green					
Natural Cycle: 60					

Lanes, Volumes, Timings
5: Arthur & Gladstone

Future Background 2030PM Peak Hour
18 Louisa Street

Control Type: Actuated-Coordinated	
Maximum v/c Ratio: 0.57	
Intersection Signal Delay: 8.3	Intersection LOS: A
Intersection Capacity Utilization 79.1%	ICU Level of Service D
Analysis Period (min) 15	

Splits and Phases: 5: Arthur & Gladstone



Lanes, Volumes, Timings
6: Booth & Raymond

Future Background 2030PM Peak Hour
18 Louisa Street

Lane Group	WBT	WBR	NBL	NBT	SBT
Lane Configurations	↔	↔	↔	↔	↔
Traffic Volume (vph)	331	194	31	363	527
Future Volume (vph)	331	194	31	363	527
Lane Group Flow (vph)	508	194	31	363	617
Turn Type	NA	Perm	Perm	NA	NA
Protected Phases	8			2	6
Permitted Phases		8	2		
Detector Phase	8	8	2	2	6
Switch Phase					
Minimum Initial (s)	10.0	10.0	10.0	10.0	10.0
Minimum Split (s)	25.5	25.5	25.2	25.2	25.2
Total Split (s)	25.5	25.5	44.5	44.5	44.5
Total Split (%)	36.4%	36.4%	63.6%	63.6%	63.6%
Maximum Green (s)	20.0	20.0	39.3	39.3	39.3
Yellow Time (s)	3.3	3.3	3.3	3.3	3.3
All-Red Time (s)	2.2	2.2	1.9	1.9	1.9
Lost Time Adjust (s)	0.0	0.0	0.0	0.0	0.0
Total Lost Time (s)	5.5	5.5	5.2	5.2	5.2
Lead/Lag					
Lead-Lag Optimize?					
Vehicle Extension (s)	3.0	3.0	3.0	3.0	3.0
Recall Mode	Max	Max	C-Max	C-Max	C-Max
Walk Time (s)	11.0	11.0	15.0	15.0	15.0
Flash Dont Walk (s)	9.0	9.0	5.0	5.0	5.0
Pedestrian Calls (#/hr)	14	14	47	47	32
Act Effct Green (s)	20.0	20.0	39.3	39.3	39.3
Actuated g/C Ratio	0.29	0.29	0.56	0.56	0.56
v/c Ratio	1.06	0.36	0.11	0.37	0.64
Control Delay	86.0	5.5	8.3	9.9	14.1
Queue Delay	0.0	0.0	0.0	0.0	0.0
Total Delay	86.0	5.5	8.3	9.9	14.1
LOS	F	A	A	A	B
Approach Delay	63.8			9.8	14.1
Approach LOS	E			A	B
Queue Length 50th (m)	~74.8	0.0	1.7	24.0	48.7
Queue Length 95th (m)	#127.5	13.1	5.4	39.6	80.4
Internal Link Dist (m)	302.1			65.0	206.0
Turn Bay Length (m)		75.0	25.0		
Base Capacity (vph)	479	542	294	979	957
Starvation Cap Reductn	0	0	0	0	0
Spillback Cap Reductn	0	0	0	0	0
Storage Cap Reductn	0	0	0	0	0
Reduced v/c Ratio	1.06	0.36	0.11	0.37	0.64

Intersection Summary

Cycle Length: 70
Actuated Cycle Length: 70
Offset: 39 (56%), Referenced to phase 2:NBL and 6:SBT, Start of Green
Natural Cycle: 60

Lanes, Volumes, Timings
6: Booth & Raymond

Future Background 2030PM Peak Hour
18 Louisa Street

Control Type: Actuated-Coordinated
Maximum v/c Ratio: 1.06
Intersection Signal Delay: 33.5
Intersection LOS: C
Intersection Capacity Utilization 79.8%
ICU Level of Service D
Analysis Period (min) 15
~ Volume exceeds capacity, queue is theoretically infinite.
Queue shown is maximum after two cycles.
95th percentile volume exceeds capacity, queue may be longer.
Queue shown is maximum after two cycles.

Splits and Phases: 6: Booth & Raymond



Appendix H

MMLOS Analysis

Multi-Modal Level of Service - Segments Form

Consultant
Scenario
Comments

CGH Transportation Inc.
Existing/Future

Project
Date

2021-015
2021-05-19

SEGMENTS		Bell Street	Louisa Street	Arlington Avenue
Pedestrian	Sidewalk Width	1.5 m	1.5 m	1.5 m
	Boulevard Width	0.5 - 2 m	< 0.5 m	< 0.5 m
	Avg Daily Curb Lane Traffic Volume	≤ 3000	≤ 3000	≤ 3000
	Operating Speed	> 30 to 50 km/h	> 30 to 50 km/h	> 30 to 50 km/h
	On-Street Parking	yes	yes	yes
	Exposure to Traffic PLoS	C	E	E
	Effective Sidewalk Width			
Pedestrian Volume				
Crowding PLoS	A	A	A	
Level of Service	C	E	E	
Bicycle	Type of Cycling Facility	Mixed Traffic	Mixed Traffic	Mixed Traffic
	Number of Travel Lanes	≤ 2 (no centreline)	≤ 2 (no centreline)	≤ 2 (no centreline)
	Operating Speed	>40 to <50 km/h	>40 to <50 km/h	>40 to <50 km/h
	# of Lanes & Operating Speed LoS	B	B	B
	Bike Lane (+ Parking Lane) Width			
	Bike Lane Width LoS	-	-	-
	Bike Lane Blockages			
	Blockage LoS	-	-	-
	Median Refuge Width (no median = < 1.8 m)	< 1.8 m refuge	< 1.8 m refuge	< 1.8 m refuge
	No. of Lanes at Unsignalized Crossing	≤ 3 lanes	≤ 3 lanes	≤ 3 lanes
	Sidestreet Operating Speed	≤ 40 km/h	≤ 40 km/h	≤ 40 km/h
Unsignalized Crossing - Lowest LoS	A	A	A	
Level of Service	B	B	B	
Transit	Facility Type			
	Friction or Ratio Transit:Posted Speed			
	Level of Service	-	-	-
Truck	Truck Lane Width			
	Travel Lanes per Direction			
Level of Service	-	-	-	

Multi-Modal Level of Service - Intersections Form

Consultant
Scenario
Comments

CGH Transportation Inc.
Existing/Future

Project
Date

2021-015
2021-05-19

INTERSECTIONS													
		Bronson Ave @ Catherine St/Raymond St (Existing)				Bronson Ave @ Arlington Ave				Bronson Ave @ Gladstone Ave			
Crossing Side		NORTH	SOUTH	EAST	WEST	NORTH	SOUTH	EAST	WEST	NORTH	SOUTH	EAST	WEST
Pedestrian	Lanes	5		5	5	4	4	0 - 2	0 - 2	5	5	4	4
	Median	No Median - 2.4 m		No Median - 2.4 m	No Median - 2.4 m	No Median - 2.4 m	No Median - 2.4 m	No Median - 2.4 m	No Median - 2.4 m	No Median - 2.4 m	No Median - 2.4 m	No Median - 2.4 m	No Median - 2.4 m
	Conflicting Left Turns	No left turn / Prohib.		No left turn / Prohib.	Protected/ Permissive	Permissive	Permissive	Permissive	Permissive	Permissive	Permissive	Permissive	Permissive
	Conflicting Right Turns	Permissive or yield control		No right turn	Permissive or yield control								
	Right Turns on Red (RTOR) ?	RTOR allowed		RTOR allowed	RTOR prohibited	RTOR allowed	RTOR allowed	RTOR allowed	RTOR allowed	RTOR prohibited	RTOR prohibited	RTOR prohibited	RTOR prohibited
	Ped Signal Leading Interval?	No		No	No	No	No	No	No	Yes	Yes	Yes	Yes
	Right Turn Channel	No Channel		No Right Turn	No Channel								
	Corner Radius	5-10m		10-15m	0-3m	3-5m	3-5m	3-5m	3-5m	3-5m	5-10m	5-10m	3-5m
	Crosswalk Type	Std transverse markings		Std transverse markings	Std transverse markings	Textured/coloured pavement							
	PETSI Score	46		54	43	58	58	90	90	47	46	62	63
	Ped. Exposure to Traffic LoS	D	-	D	E	D	D	A	A	D	D	C	C
Cycle Length													
Effective Walk Time													
Average Pedestrian Delay													
Pedestrian Delay LoS													
Level of Service	D	-	D	E	D	D	A	A	D	D	C	C	
	E				D				D				
Approach From		NORTH	SOUTH	EAST	WEST	NORTH	SOUTH	EAST	WEST	NORTH	SOUTH	EAST	WEST
Bicycle	Bicycle Lane Arrangement on Approach												
	Right Turn Lane Configuration												
	Right Turning Speed												
	Cyclist relative to RT motorists	-	A	A	-	A							
	Separated or Mixed Traffic	-	-	-	-	-	-	-	-	-	-	-	-
	Left Turn Approach		One lane crossed	One lane crossed		No lane crossed	No lane crossed	No lane crossed	No lane crossed	One lane crossed	One lane crossed	No lane crossed	No lane crossed
	Operating Speed		> 50 to < 60 km/h	> 50 to < 60 km/h		> 50 to < 60 km/h	> 50 to < 60 km/h	> 40 to ≤ 50 km/h	> 40 to ≤ 50 km/h	> 50 to < 60 km/h			
Left Turning Cyclist	-	E	E	-	C	C	B	B	E	E	C	C	
Level of Service	-	E	E	-	C	C	B	B	E	E	C	C	
	E				C				E				
Transit	Average Signal Delay	> 40 sec	≤ 20 sec	> 40 sec		≤ 10 sec	≤ 10 sec			≤ 30 sec	≤ 20 sec	> 40 sec	> 40 sec
	Level of Service	F	C	F	-	B	B	-	-	D	C	F	F
	F				B				F				
Truck	Effective Corner Radius	10 - 15 m		< 10 m						< 10 m	< 10 m		< 10 m
	Number of Receiving Lanes on Departure from Intersection	≥ 2		≥ 2						1	1		≥ 2
Level of Service	B	-	D	-	-	-	-	-	F	F	-	D	
	D				-				F				
Auto	Volume to Capacity Ratio		> 1.00				0.0 - 0.60				0.71 - 0.80		
	Level of Service		F				A				C		

Arthur St/Arthur Ln @ Gladstone Ave				Booth St @ Gladstone Ave				Booth St @ Raymond St				Bronson Ave @ Catherine St/Raymond St (Future)			
NORTH	SOUTH	EAST	WEST	NORTH	SOUTH	EAST	WEST	NORTH	SOUTH	EAST	WEST	NORTH	SOUTH	EAST	WEST
0 - 2	0 - 2	3	3	3	4	4	4	3	4	0 - 2	3	5		5	5
No Median - 2.4 m	No Median - 2.4 m	No Median - 2.4 m	No Median - 2.4 m	No Median - 2.4 m	No Median - 2.4 m	No Median - 2.4 m	No Median - 2.4 m	No Median - 2.4 m	No Median - 2.4 m	No Median - 2.4 m	No Median - 2.4 m	No Median - 2.4 m		No Median - 2.4 m	No Median - 2.4 m
Permissive	Permissive	Permissive	No left turn / Prohib.	Permissive	Permissive	Permissive	Permissive	No left turn / Prohib.	Permissive	No left turn / Prohib.	Permissive	No left turn / Prohib.		No left turn / Prohib.	Protected/ Permissive
Permissive or yield control	Permissive or yield control	No right turn	Permissive or yield control	Permissive or yield control	Permissive or yield control	Permissive or yield control	Permissive or yield control	Permissive or yield control	No right turn	No right turn	Permissive or yield control	Permissive or yield control		No right turn	Permissive or yield control
RTOR allowed	RTOR prohibited	RTOR allowed	RTOR allowed	RTOR allowed	RTOR allowed	RTOR allowed	RTOR allowed	RTOR allowed	RTOR prohibited	RTOR allowed	RTOR prohibited	RTOR allowed		RTOR allowed	RTOR prohibited
No	No	No	No	Yes	Yes	Yes	Yes	No	No	No	No	No		No	No
No Channel	No Channel	No Right Turn	No Channel	No Channel	Smart Channel	No Channel	No Channel	No Channel	No Channel	No Channel	No Channel	No Channel		No Right Turn	No Channel
3-5m	0-3m	0-3m	3-5m	5-10m	5-10m	5-10m	5-10m	3-5m	3-5m	0-3m	5-10m	5-10m		10-15m	0-3m
Std transverse markings	Std transverse markings	Std transverse markings	Std transverse markings	Zebra stripe hi-vis markings	Zebra stripe hi-vis markings	Zebra stripe hi-vis markings	Zebra stripe hi-vis markings	Std transverse markings	Std transverse markings	Std transverse markings	Std transverse markings	Zebra stripe hi-vis markings		Zebra stripe hi-vis markings	Zebra stripe hi-vis markings
87	91	82	80	76	65	59	59	80	63	101	74	49		57	46
B	A	B	B	B	C	D	D	B	C	A	C	D	-	D	D
B	A	B	B	B	C	D	D	B	C	A	C	D	-	D	D
B				D				C				D			
NORTH	SOUTH	EAST	WEST	NORTH	SOUTH	EAST	WEST	NORTH	SOUTH	EAST	WEST	NORTH	SOUTH	EAST	WEST
A	A	A	A	A	A	A	A	-	A	A	-	-	A	A	-
-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
No lane crossed	No lane crossed	No lane crossed	No lane crossed	No lane crossed	No lane crossed	No lane crossed	No lane crossed	No lane crossed	No lane crossed	No lane crossed	No lane crossed	One lane crossed		One lane crossed	
> 40 to ≤ 50 km/h	≤ 40 km/h	> 50 to < 60 km/h	> 50 to < 60 km/h	> 50 to < 60 km/h	> 50 to < 60 km/h	> 50 to < 60 km/h	> 50 to < 60 km/h	> 40 to ≤ 50 km/h	> 50 to < 60 km/h	> 50 to < 60 km/h	> 50 to < 60 km/h	> 50 to < 60 km/h		> 50 to < 60 km/h	> 50 to < 60 km/h
B	B	C	C	C	C	C	C	-	B	C	-	-	E	E	-
B	B	C	C	C	C	C	C	-	B	C	-	-	E	E	-
C				C				C				E			
		≤ 10 sec	≤ 10 sec			≤ 40 sec	≤ 30 sec					> 40 sec	≤ 20 sec	> 40 sec	
-	-	B	B	-	-	E	D	-	-	-	-	F	C	F	-
B				E				-				F			
												10 - 15 m		< 10 m	
												≥ 2		≥ 2	
-	-	-	-	-	-	-	-	-	-	-	-	B	-	D	-
-				-				-				D			
0.0 - 0.60				> 1.00				0.91 - 1.00				> 1.00			
A				F				E				F			

Appendix I

TDM Checklists

TDM Measures Checklist:
Residential Developments (multi-family, condominium or subdivision)

Legend	
BASIC	The measure is generally feasible and effective, and in most cases would benefit the development and its users
BETTER	The measure could maximize support for users of sustainable modes, and optimize development performance
★	The measure is one of the most dependably effective tools to encourage the use of sustainable modes

TDM measures: Residential developments		Check if proposed & add descriptions
1. TDM PROGRAM MANAGEMENT		
1.1 Program coordinator		
BASIC ★	1.1.1 Designate an internal coordinator, or contract with an external coordinator	<input type="checkbox"/>
1.2 Travel surveys		
BETTER	1.2.1 Conduct periodic surveys to identify travel-related behaviours, attitudes, challenges and solutions, and to track progress	<input type="checkbox"/>
2. WALKING AND CYCLING		
2.1 Information on walking/cycling routes & destinations		
BASIC	2.1.1 Display local area maps with walking/cycling access routes and key destinations at major entrances (multi-family, condominium)	<input checked="" type="checkbox"/>
2.2 Bicycle skills training		
BETTER	2.2.1 Offer on-site cycling courses for residents, or subsidize off-site courses	<input type="checkbox"/>

TDM measures: Residential developments		Check if proposed & add descriptions
3. TRANSIT		
3.1 Transit information		
BASIC	3.1.1 Display relevant transit schedules and route maps at entrances (multi-family, condominium)	<input checked="" type="checkbox"/>
BETTER	3.1.2 Provide real-time arrival information display at entrances (multi-family, condominium)	<input type="checkbox"/>
3.2 Transit fare incentives		
BASIC ★	3.2.1 Offer PRESTO cards preloaded with one monthly transit pass on residence purchase/move-in, to encourage residents to use transit	<input checked="" type="checkbox"/>
BETTER	3.2.2 Offer at least one year of free monthly transit passes on residence purchase/move-in	<input type="checkbox"/>
3.3 Enhanced public transit service		
BETTER ★	3.3.1 Contract with OC Transpo to provide early transit services until regular services are warranted by occupancy levels (subdivision)	<input type="checkbox"/>
3.4 Private transit service		
BETTER	3.4.1 Provide shuttle service for seniors homes or lifestyle communities (e.g. scheduled mall or supermarket runs)	<input type="checkbox"/>
4. CARSHARING & BIKESHARING		
4.1 Bikeshare stations & memberships		
BETTER	4.1.1 Contract with provider to install on-site bikeshare station (multi-family)	<input type="checkbox"/>
BETTER	4.1.2 Provide residents with bikeshare memberships, either free or subsidized (multi-family)	<input type="checkbox"/>
4.2 Carshare vehicles & memberships		
BETTER	4.2.1 Contract with provider to install on-site carshare vehicles and promote their use by residents	<input type="checkbox"/>
BETTER	4.2.2 Provide residents with carshare memberships, either free or subsidized	<input type="checkbox"/>
5. PARKING		
5.1 Priced parking		
BASIC ★	5.1.1 Unbundle parking cost from purchase price (condominium)	<input checked="" type="checkbox"/>
BASIC ★	5.1.2 Unbundle parking cost from monthly rent (multi-family)	<input checked="" type="checkbox"/>

TDM measures: Residential developments		Check if proposed & add descriptions
6. TDM MARKETING & COMMUNICATIONS		
6.1 Multimodal travel information		
BASIC ★	6.1.1 Provide a multimodal travel option information package to new residents	<input checked="" type="checkbox"/>
6.2 Personalized trip planning		
BETTER ★	6.2.1 Offer personalized trip planning to new residents	<input type="checkbox"/>

TDM-Supportive Development Design and Infrastructure Checklist:
Residential Developments (multi-family or condominium)

Legend	
REQUIRED	The Official Plan or Zoning By-law provides related guidance that must be followed
BASIC	The measure is generally feasible and effective, and in most cases would benefit the development and its users
BETTER	The measure could maximize support for users of sustainable modes, and optimize development performance

TDM-supportive design & infrastructure measures: <i>Residential developments</i>		Check if completed & add descriptions, explanations or plan/drawing references
1. WALKING & CYCLING: ROUTES		
1.1 Building location & access points		
BASIC	1.1.1 Locate building close to the street, and do not locate parking areas between the street and building entrances	<input checked="" type="checkbox"/>
BASIC	1.1.2 Locate building entrances in order to minimize walking distances to sidewalks and transit stops/stations	<input checked="" type="checkbox"/>
BASIC	1.1.3 Locate building doors and windows to ensure visibility of pedestrians from the building, for their security and comfort	<input checked="" type="checkbox"/>
1.2 Facilities for walking & cycling		
REQUIRED	1.2.1 Provide convenient, direct access to stations or major stops along rapid transit routes within 600 metres; minimize walking distances from buildings to rapid transit; provide pedestrian-friendly, weather-protected (where possible) environment between rapid transit accesses and building entrances; ensure quality linkages from sidewalks through building entrances to integrated stops/stations (see <i>Official Plan policy 4.3.3</i>)	<input checked="" type="checkbox"/>
REQUIRED	1.2.2 Provide safe, direct and attractive pedestrian access from public sidewalks to building entrances through such measures as: reducing distances between public sidewalks and major building entrances; providing walkways from public streets to major building entrances; within a site, providing walkways along the front of adjoining buildings, between adjacent buildings, and connecting areas where people may congregate, such as courtyards and transit stops; and providing weather protection through canopies, colonnades, and other design elements wherever possible (see <i>Official Plan policy 4.3.12</i>)	<input checked="" type="checkbox"/>

TDM-supportive design & infrastructure measures: <i>Residential developments</i>		Check if completed & add descriptions, explanations or plan/drawing references
REQUIRED	1.2.3 Provide sidewalks of smooth, well-drained walking surfaces of contrasting materials or treatments to differentiate pedestrian areas from vehicle areas, and provide marked pedestrian crosswalks at intersection sidewalks (see <i>Official Plan policy 4.3.10</i>)	<input checked="" type="checkbox"/>
REQUIRED	1.2.4 Make sidewalks and open space areas easily accessible through features such as gradual grade transition, depressed curbs at street corners and convenient access to extra-wide parking spaces and ramps (see <i>Official Plan policy 4.3.10</i>)	<input checked="" type="checkbox"/>
REQUIRED	1.2.5 Include adequately spaced inter-block/street cycling and pedestrian connections to facilitate travel by active transportation. Provide links to the existing or planned network of public sidewalks, multi-use pathways and on-road cycle routes. Where public sidewalks and multi-use pathways intersect with roads, consider providing traffic control devices to give priority to cyclists and pedestrians (see <i>Official Plan policy 4.3.11</i>)	<input checked="" type="checkbox"/>
BASIC	1.2.6 Provide safe, direct and attractive walking routes from building entrances to nearby transit stops	<input type="checkbox"/>
BASIC	1.2.7 Ensure that walking routes to transit stops are secure, visible, lighted, shaded and wind-protected wherever possible	<input type="checkbox"/>
BASIC	1.2.8 Design roads used for access or circulation by cyclists using a target operating speed of no more than 30 km/h, or provide a separated cycling facility	<input type="checkbox"/>
1.3 Amenities for walking & cycling		
BASIC	1.3.1 Provide lighting, landscaping and benches along walking and cycling routes between building entrances and streets, sidewalks and trails	<input type="checkbox"/>
BASIC	1.3.2 Provide wayfinding signage for site access (where required, e.g. when multiple buildings or entrances exist) and egress (where warranted, such as when directions to reach transit stops/stations, trails or other common destinations are not obvious)	<input type="checkbox"/>

TDM-supportive design & infrastructure measures: <i>Residential developments</i>		Check if completed & add descriptions, explanations or plan/drawing references
2. WALKING & CYCLING: END-OF-TRIP FACILITIES		
2.1 Bicycle parking		
REQUIRED	2.1.1 Provide bicycle parking in highly visible and lighted areas, sheltered from the weather wherever possible (see <i>Official Plan policy 4.3.6</i>)	<input checked="" type="checkbox"/>
REQUIRED	2.1.2 Provide the number of bicycle parking spaces specified for various land uses in different parts of Ottawa; provide convenient access to main entrances or well-used areas (see <i>Zoning By-law Section 111</i>)	<input checked="" type="checkbox"/>
REQUIRED	2.1.3 Ensure that bicycle parking spaces and access aisles meet minimum dimensions; that no more than 50% of spaces are vertical spaces; and that parking racks are securely anchored (see <i>Zoning By-law Section 111</i>)	<input checked="" type="checkbox"/>
BASIC	2.1.4 Provide bicycle parking spaces equivalent to the expected number of resident-owned bicycles, plus the expected peak number of visitor cyclists	<input type="checkbox"/>
2.2 Secure bicycle parking		
REQUIRED	2.2.1 Where more than 50 bicycle parking spaces are provided for a single residential building, locate at least 25% of spaces within a building/structure, a secure area (e.g. supervised parking lot or enclosure) or bicycle lockers (see <i>Zoning By-law Section 111</i>)	<input checked="" type="checkbox"/>
BETTER	2.2.2 Provide secure bicycle parking spaces equivalent to at least the number of units at condominiums or multi-family residential developments	<input type="checkbox"/>
2.3 Bicycle repair station		
BETTER	2.3.1 Provide a permanent bike repair station, with commonly used tools and an air pump, adjacent to the main bicycle parking area (or secure bicycle parking area, if provided)	<input type="checkbox"/>
3. TRANSIT		
3.1 Customer amenities		
BASIC	3.1.1 Provide shelters, lighting and benches at any on-site transit stops	<input type="checkbox"/>
BASIC	3.1.2 Where the site abuts an off-site transit stop and insufficient space exists for a transit shelter in the public right-of-way, protect land for a shelter and/or install a shelter	<input type="checkbox"/>
BETTER	3.1.3 Provide a secure and comfortable interior waiting area by integrating any on-site transit stops into the building	<input type="checkbox"/>

TDM-supportive design & infrastructure measures: <i>Residential developments</i>		Check if completed & add descriptions, explanations or plan/drawing references
4. RIDESHARING		
4.1 Pick-up & drop-off facilities		
BASIC	4.1.1 Provide a designated area for carpool drivers (plus taxis and ride-hailing services) to drop off or pick up passengers without using fire lanes or other no-stopping zones	<input type="checkbox"/>
5. CARSHARING & BIKESHARING		
5.1 Carshare parking spaces		
BETTER	5.1.1 Provide up to three carshare parking spaces in an R3, R4 or R5 Zone for specified residential uses (see <i>Zoning By-law Section 94</i>)	<input type="checkbox"/>
5.2 Bikeshare station location		
BETTER	5.2.1 Provide a designated bikeshare station area near a major building entrance, preferably lighted and sheltered with a direct walkway connection	<input type="checkbox"/>
6. PARKING		
6.1 Number of parking spaces		
REQUIRED	6.1.1 Do not provide more parking than permitted by zoning, nor less than required by zoning, unless a variance is being applied for	<input checked="" type="checkbox"/>
BASIC	6.1.2 Provide parking for long-term and short-term users that is consistent with mode share targets, considering the potential for visitors to use off-site public parking	<input type="checkbox"/>
BASIC	6.1.3 Where a site features more than one use, provide shared parking and reduce the cumulative number of parking spaces accordingly (see <i>Zoning By-law Section 104</i>)	<input type="checkbox"/>
BETTER	6.1.4 Reduce the minimum number of parking spaces required by zoning by one space for each 13 square metres of gross floor area provided as shower rooms, change rooms, locker rooms and other facilities for cyclists in conjunction with bicycle parking (see <i>Zoning By-law Section 111</i>)	<input type="checkbox"/>
6.2 Separate long-term & short-term parking areas		
BETTER	6.2.1 Provide separate areas for short-term and long-term parking (using signage or physical barriers) to permit access controls and simplify enforcement (i.e. to discourage residents from parking in visitor spaces, and vice versa)	<input type="checkbox"/>

Appendix J

Synchro Intersection Worksheets – 2025 Future Total Conditions

Lanes, Volumes, Timings
1: Bronson & Raymond/Catherine

Future Total 2025AM Peak Hour
18 Louisa Street

Lane Group	WBL	WBT	NBL	NBT	SBT	Ø5	Ø9
Lane Configurations	↔↔↔↔	↔↔↔↔	↔↔↔↔	↔↔↔↔	↔↔↔↔		
Traffic Volume (vph)	527	516	538	1075	461		
Future Volume (vph)	527	516	538	1075	461		
Lane Group Flow (vph)	353	1036	538	1075	579		
Turn Type	Perm	NA	pm+pt	NA	NA		
Protected Phases		8	5 9	2	6	5	9
Permitted Phases	8			2	9		
Detector Phase	8	8	5 9	2	6		
Switch Phase							
Minimum Initial (s)	10.0	10.0		10.0	10.0	5.0	5.0
Minimum Split (s)	28.3	28.3		24.8	24.8	11.8	11.8
Total Split (s)	34.0	34.0		53.0	33.0	20.0	23.0
Total Split (%)	30.9%	30.9%		48.2%	30.0%	18%	21%
Maximum Green (s)	27.7	27.7		46.2	26.2	13.2	16.8
Yellow Time (s)	3.3	3.3		3.3	3.3	3.3	3.3
All-Red Time (s)	3.0	3.0		3.5	3.5	3.5	2.9
Lost Time Adjust (s)	0.0	0.0		0.0	0.0		
Total Lost Time (s)	6.3	6.3		6.8	6.8		
Lead/Lag				Lead	Lag		
Lead-Lag Optimize?				Yes	Yes		
Vehicle Extension (s)	3.0	3.0		3.0	3.0	3.0	3.0
Recall Mode	Max	Max		C-Max	C-Max	Max	Max
Walk Time (s)	7.0	7.0		7.0	7.0		
Flash Dont Walk (s)	15.0	15.0		10.0	10.0		
Pedestrian Calls (#/hr)	43	43		48	31		
Act Effct Green (s)	27.7	27.7	62.4	69.2	26.2		
Actuated g/C Ratio	0.25	0.25	0.57	0.63	0.24		
v/c Ratio	1.00	0.95	0.90	0.52	0.78		
Control Delay	90.9	55.0	38.0	12.3	43.0		
Queue Delay	0.0	0.0	0.0	0.0	10.3		
Total Delay	90.9	55.0	38.0	12.3	53.4		
LOS	F	D	D	B	D		
Approach Delay		64.1		20.9	53.4		
Approach LOS		E		C	D		
Queue Length 50th (m)	~88.8	78.6		58.6	59.0		
Queue Length 95th (m)	#156.7	#108.7	#112.8	77.2	79.7		
Internal Link Dist (m)		247.5		81.5	56.5		
Turn Bay Length (m)	110.0		45.0				
Base Capacity (vph)	352	1090	596	2086	739		
Starvation Cap Reductn	0	0	0	0	137		
Spillback Cap Reductn	0	0	0	0	75		
Storage Cap Reductn	0	0	0	0	0		
Reduced v/c Ratio	1.00	0.95	0.90	0.53	0.96		

Intersection Summary


Cycle Length: 110
Actuated Cycle Length: 110
Offset: 38 (35%), Referenced to phase 2:NBT and 6:SBT, Start of Green
Natural Cycle: 90

Lanes, Volumes, Timings
1: Bronson & Raymond/Catherine

Future Total 2025AM Peak Hour
18 Louisa Street

Control Type: Actuated-Coordinated
Maximum v/c Ratio: 1.00
Intersection Signal Delay: 42.9
Intersection LOS: D
Intersection Capacity Utilization 89.4%
ICU Level of Service E
Analysis Period (min) 15
~ Volume exceeds capacity, queue is theoretically infinite.
Queue shown is maximum after two cycles.
95th percentile volume exceeds capacity, queue may be longer.
Queue shown is maximum after two cycles.

Splits and Phases: 1: Bronson & Raymond/Catherine



Lanes, Volumes, Timings
2: Bronson & Arlington

Future Total 2025AM Peak Hour
18 Louisa Street


Lane Group	EBL	EBT	WBL	WBT	NBL	NBT	SBL	SBT
Lane Configurations		↕		↕		↕		↕
Traffic Volume (vph)	10	4	8	2	13	1413	2	542
Future Volume (vph)	10	4	8	2	13	1413	2	542
Lane Group Flow (vph)	0	48	0	21	0	1432	0	560
Turn Type	Perm	NA	Perm	NA	Perm	NA	Perm	NA
Protected Phases		4		8		2		6
Permitted Phases	4		8		2		6	
Detector Phase	4	4	8	8	2	2	6	6
Switch Phase								
Minimum Initial (s)	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0
Minimum Split (s)	22.6	22.6	22.6	22.6	17.2	17.2	17.2	17.2
Total Split (s)	23.0	23.0	23.0	23.0	87.0	87.0	87.0	87.0
Total Split (%)	20.9%	20.9%	20.9%	20.9%	79.1%	79.1%	79.1%	79.1%
Maximum Green (s)	17.4	17.4	17.4	17.4	81.8	81.8	81.8	81.8
Yellow Time (s)	3.3	3.3	3.3	3.3	3.3	3.3	3.3	3.3
All-Red Time (s)	2.3	2.3	2.3	2.3	1.9	1.9	1.9	1.9
Lost Time Adjust (s)		0.0		0.0		0.0		0.0
Total Lost Time (s)		5.6		5.6		5.2		5.2
Lead/Lag								
Lead-Lag Optimize?								
Vehicle Extension (s)	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0
Recall Mode	None	None	None	None	C-Max	C-Max	C-Max	C-Max
Walk Time (s)	7.0	7.0	7.0	7.0	7.0	7.0	7.0	7.0
Flash Dont Walk (s)	10.0	10.0	10.0	10.0	5.0	5.0	5.0	5.0
Pedestrian Calls (#/hr)	26	26	22	22	21	21	28	28
Act Effct Green (s)		14.2		14.2		89.2		89.2
Actuated g/C Ratio		0.13		0.13		0.81		0.81
v/c Ratio		0.23		0.12		0.57		0.23
Control Delay		21.6		28.1		4.8		3.7
Queue Delay		0.0		0.0		0.0		0.0
Total Delay		21.7		28.1		4.9		3.7
LOS		C		C		A		A
Approach Delay		21.7		28.1		4.9		3.7
Approach LOS		C		C		A		A
Queue Length 50th (m)		2.6		1.9		40.0		16.4
Queue Length 95th (m)		13.1		9.0		m44.5		22.0
Internal Link Dist (m)		0.1		230.9		56.5		207.2
Turn Bay Length (m)								
Base Capacity (vph)		250		211		2520		2424
Starvation Cap Reductn		0		0		78		0
Spillback Cap Reductn		4		0		0		378
Storage Cap Reductn		0		0		0		0
Reduced v/c Ratio		0.20		0.10		0.59		0.27
Intersection Summary								
Cycle Length: 110								
Actuated Cycle Length: 110								
Offset: 11 (10%), Referenced to phase 2:NBT and 6:SBTL, Start of Green								
Natural Cycle: 60								

Lanes, Volumes, Timings
2: Bronson & Arlington

Future Total 2025AM Peak Hour
18 Louisa Street

Control Type: Actuated-Coordinated
Maximum v/c Ratio: 0.57
Intersection Signal Delay: 5.2
Intersection LOS: A
Intersection Capacity Utilization 71.8%
ICU Level of Service C
Analysis Period (min) 15
m Volume for 95th percentile queue is metered by upstream signal.

Splits and Phases: 2: Bronson & Arlington



Lanes, Volumes, Timings
3: Bronson & Gladstone

Future Total 2025AM Peak Hour
18 Louisa Street

	↖	→	↗	←	↖	↑	↗	↓
Lane Group	EBL	EBT	WBL	WBT	NBL	NBT	SBL	SBT
Lane Configurations	↖	↖	↖	↖	↖	↖	↖	↖
Traffic Volume (vph)	50	307	84	175	123	1115	13	407
Future Volume (vph)	50	307	84	175	123	1115	13	407
Lane Group Flow (vph)	50	396	84	193	123	1265	13	446
Turn Type	Perm	NA	Perm	NA	Perm	NA	Perm	NA
Protected Phases		4		8		2		6
Permitted Phases	4		8		2		6	
Detector Phase	4	4	8	8	2	2	6	6
Switch Phase								
Minimum Initial (s)	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0
Minimum Split (s)	28.2	28.2	28.2	28.2	25.0	25.0	25.0	25.0
Total Split (s)	37.0	37.0	37.0	37.0	58.0	58.0	58.0	58.0
Total Split (%)	38.9%	38.9%	38.9%	38.9%	61.1%	61.1%	61.1%	61.1%
Maximum Green (s)	30.8	30.8	30.8	30.8	52.0	52.0	52.0	52.0
Yellow Time (s)	3.0	3.0	3.0	3.0	3.3	3.3	3.3	3.3
All-Red Time (s)	3.2	3.2	3.2	3.2	2.7	2.7	2.7	2.7
Lost Time Adjust (s)	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
Total Lost Time (s)	6.2	6.2	6.2	6.2	6.0	6.0	6.0	6.0
Lead/Lag								
Lead-Lag Optimize?								
Vehicle Extension (s)	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0
Recall Mode	Max	Max	Max	Max	C-Max	C-Max	C-Max	C-Max
Walk Time (s)	7.0	7.0	7.0	7.0	7.0	7.0	7.0	7.0
Flash Dont Walk (s)	15.0	15.0	15.0	15.0	12.0	12.0	12.0	12.0
Pedestrian Calls (#/hr)	96	96	39	39	41	41	34	34
Act Effct Green (s)	30.8	30.8	30.8	30.8	52.0	52.0	52.0	52.0
Actuated g/C Ratio	0.32	0.32	0.32	0.32	0.55	0.55	0.55	0.55
v/c Ratio	0.15	0.76	0.49	0.36	0.28	0.73	0.10	0.26
Control Delay	24.5	39.9	37.1	27.0	13.6	19.3	12.9	11.8
Queue Delay	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
Total Delay	24.5	39.9	37.1	27.0	13.6	19.3	12.9	11.8
LOS	C	D	D	C	B	B	B	B
Approach Delay		38.2		30.1		18.8		11.9
Approach LOS		D		C		B		B
Queue Length 50th (m)	6.5	64.6	12.2	26.9	11.3	86.5	1.1	21.3
Queue Length 95th (m)	15.2	#106.6	27.8	45.3	22.5	111.5	4.4	30.0
Internal Link Dist (m)		139.3		203.3		207.2		176.5
Turn Bay Length (m)	20.0		20.0		35.0		45.0	
Base Capacity (vph)	328	521	173	533	442	1740	125	1723
Starvation Cap Reductn	0	0	0	0	0	0	0	0
Spillback Cap Reductn	0	0	0	0	0	0	0	0
Storage Cap Reductn	0	0	0	0	0	0	0	0
Reduced v/c Ratio	0.15	0.76	0.49	0.36	0.28	0.73	0.10	0.26

Intersection Summary


Cycle Length: 95
 Actuated Cycle Length: 95
 Offset: 42 (44%), Referenced to phase 2:NBT and 6:SBTL, Start of Green
 Natural Cycle: 60

Lanes, Volumes, Timings
3: Bronson & Gladstone

Future Total 2025AM Peak Hour
18 Louisa Street

Control Type: Actuated-Coordinated	
Maximum v/c Ratio: 0.76	
Intersection Signal Delay: 22.1	Intersection LOS: C
Intersection Capacity Utilization 99.1%	ICU Level of Service F
Analysis Period (min) 15	
# 95th percentile volume exceeds capacity, queue may be longer.	
Queue shown is maximum after two cycles.	

Splits and Phases: 3: Bronson & Gladstone



Lanes, Volumes, Timings
4: Booth & Gladstone

Future Total 2025AM Peak Hour
18 Louisa Street


	EBL	EBT	WBL	WBT	NBL	NBT	SBL	SBT
Lane Group	EBL	EBT	WBL	WBT	NBL	NBT	SBL	SBT
Lane Configurations	↔	↕	↔	↕	↔	↕	↔	↕
Traffic Volume (vph)	26	369	42	260	51	356	39	137
Future Volume (vph)	26	369	42	260	51	356	39	137
Lane Group Flow (vph)	26	440	42	291	51	433	39	157
Turn Type	Perm	NA	Perm	NA	Perm	NA	Perm	NA
Protected Phases		2		6		4		8
Permitted Phases	2		6		4		8	
Detector Phase	2	2	6	6	4	4	8	8
Switch Phase								
Minimum Initial (s)	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0
Minimum Split (s)	22.1	22.1	22.1	22.1	23.9	23.9	23.9	23.9
Total Split (s)	28.0	28.0	28.0	28.0	32.0	32.0	32.0	32.0
Total Split (%)	46.7%	46.7%	46.7%	46.7%	53.3%	53.3%	53.3%	53.3%
Maximum Green (s)	21.9	21.9	21.9	21.9	25.1	25.1	25.1	25.1
Yellow Time (s)	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0
All-Red Time (s)	3.1	3.1	3.1	3.1	3.9	3.9	3.9	3.9
Lost Time Adjust (s)	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
Total Lost Time (s)	6.1	6.1	6.1	6.1	6.9	6.9	6.9	6.9
Lead/Lag								
Lead-Lag Optimize?								
Vehicle Extension (s)	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0
Recall Mode	C-Max	C-Max	C-Max	C-Max	Max	Max	Max	Max
Walk Time (s)	7.0	7.0	7.0	7.0	7.0	7.0	7.0	7.0
Flash Dont Walk (s)	9.0	9.0	9.0	9.0	10.0	10.0	10.0	10.0
Pedestrian Calls (#/hr)	53	53	32	32	36	36	6	6
Act Effct Green (s)	21.9	21.9	21.9	21.9	25.1	25.1	25.1	25.1
Actuated g/C Ratio	0.36	0.36	0.36	0.36	0.42	0.42	0.42	0.42
v/c Ratio	0.08	0.74	0.19	0.48	0.11	0.61	0.13	0.22
Control Delay	13.4	25.2	15.8	17.3	9.6	12.7	12.2	11.1
Queue Delay	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
Total Delay	13.4	25.2	15.8	17.3	9.6	12.7	12.2	11.1
LOS	B	C	B	B	A	B	B	B
Approach Delay		24.5		17.1		12.4		11.3
Approach LOS		C		B		B		B
Queue Length 50th (m)	1.8	39.1	3.1	22.9	2.0	16.4	2.5	9.5
Queue Length 95th (m)	6.1	#78.6	9.5	41.6	m6.0	34.1	7.7	19.6
Internal Link Dist (m)		79.0		246.0		206.0		98.4
Turn Bay Length (m)	40.0		25.0		8.0		8.0	
Base Capacity (vph)	328	598	221	609	476	711	301	721
Starvation Cap Reductn	0	0	0	0	0	0	0	0
Spillback Cap Reductn	0	0	0	0	0	0	0	0
Storage Cap Reductn	0	0	0	0	0	0	0	0
Reduced v/c Ratio	0.08	0.74	0.19	0.48	0.11	0.61	0.13	0.22
Intersection Summary								
Cycle Length: 60								
Actuated Cycle Length: 60								
Offset: 16 (27%), Referenced to phase 2:EBTL and 6:WBTL, Start of Green								
Natural Cycle: 50								

Lanes, Volumes, Timings
4: Booth & Gladstone

Future Total 2025AM Peak Hour
18 Louisa Street

Control Type: Actuated-Coordinated	
Maximum v/c Ratio: 0.74	
Intersection Signal Delay: 17.1	Intersection LOS: B
Intersection Capacity Utilization 87.0%	ICU Level of Service E
Analysis Period (min) 15	
# 95th percentile volume exceeds capacity, queue may be longer.	
Queue shown is maximum after two cycles.	
m Volume for 95th percentile queue is metered by upstream signal.	

Splits and Phases: 4: Booth & Gladstone



Lanes, Volumes, Timings
5: Arthur & Gladstone

Future Total 2025AM Peak Hour
18 Louisa Street

Lane Group	EBL	EBT	WBT	SBT
Lane Configurations		↔	↔	↔
Traffic Volume (vph)	30	473	331	0
Future Volume (vph)	30	473	331	0
Lane Group Flow (vph)	0	504	345	36
Turn Type	Perm	NA	NA	NA
Protected Phases		2	6	8
Permitted Phases	2			
Detector Phase	2	2	6	8
Switch Phase				
Minimum Initial (s)	10.0	10.0	10.0	10.0
Minimum Split (s)	29.5	29.5	29.5	23.2
Total Split (s)	31.8	31.8	31.8	23.2
Total Split (%)	57.8%	57.8%	57.8%	42.2%
Maximum Green (s)	26.3	26.3	26.3	18.0
Yellow Time (s)	3.0	3.0	3.0	3.0
All-Red Time (s)	2.5	2.5	2.5	2.2
Lost Time Adjust (s)		0.0	0.0	0.0
Total Lost Time (s)		5.5	5.5	5.2
Lead/Lag				
Lead-Lag Optimize?				
Vehicle Extension (s)	3.0	3.0	3.0	3.0
Recall Mode	Max	Max	Max	None
Walk Time (s)	19.0	19.0	19.0	10.0
Flash Dont Walk (s)	5.0	5.0	5.0	8.0
Pedestrian Calls (#/hr)	92	92	49	43
Act Effct Green (s)		42.0	42.0	13.2
Actuated g/C Ratio		0.75	0.75	0.23
v/c Ratio		0.40	0.27	0.09
Control Delay		8.1	6.7	4.5
Queue Delay		0.0	0.0	0.0
Total Delay		8.1	6.7	4.5
LOS		A	A	A
Approach Delay		8.1	6.7	4.5
Approach LOS		A	A	A
Queue Length 50th (m)		22.4	13.3	0.0
Queue Length 95th (m)		61.1	36.9	3.7
Internal Link Dist (m)		246.0	139.3	183.9
Turn Bay Length (m)				
Base Capacity (vph)		1246	1255	513
Starvation Cap Reductn		0	0	0
Spillback Cap Reductn		0	0	0
Storage Cap Reductn		0	0	0
Reduced v/c Ratio		0.40	0.27	0.07

Intersection Summary
 Cycle Length: 55
 Actuated Cycle Length: 56.2
 Natural Cycle: 55
 Control Type: Actuated-Uncoordinated

Lanes, Volumes, Timings
5: Arthur & Gladstone

Future Total 2025AM Peak Hour
18 Louisa Street

Maximum v/c Ratio: 0.40	Intersection LOS: A
Intersection Signal Delay: 7.4	ICU Level of Service D
Intersection Capacity Utilization 73.7%	
Analysis Period (min) 15	

Splits and Phases: 5: Arthur & Gladstone



Lanes, Volumes, Timings
6: Booth & Raymond

Future Total 2025AM Peak Hour
18 Louisa Street

Lane Group	WBT	WBR	NBL	NBT	SBT
Lane Configurations	↔	↔	↔	↔	↔
Traffic Volume (vph)	220	108	38	407	215
Future Volume (vph)	220	108	38	407	215
Lane Group Flow (vph)	342	108	38	407	250
Turn Type	NA	Perm	Perm	NA	NA
Protected Phases	8			2	6
Permitted Phases		8	2		
Detector Phase	8	8	2	2	6
Switch Phase					
Minimum Initial (s)	10.0	10.0	10.0	10.0	10.0
Minimum Split (s)	25.5	25.5	25.2	25.2	25.2
Total Split (s)	25.5	25.5	34.5	34.5	34.5
Total Split (%)	42.5%	42.5%	57.5%	57.5%	57.5%
Maximum Green (s)	20.0	20.0	29.3	29.3	29.3
Yellow Time (s)	3.3	3.3	3.3	3.3	3.3
All-Red Time (s)	2.2	2.2	1.9	1.9	1.9
Lost Time Adjust (s)	0.0	0.0	0.0	0.0	0.0
Total Lost Time (s)	5.5	5.5	5.2	5.2	5.2
Lead/Lag					
Lead-Lag Optimize?					
Vehicle Extension (s)	3.0	3.0	3.0	3.0	3.0
Recall Mode	Max	Max	C-Max	C-Max	C-Max
Walk Time (s)	11.0	11.0	15.0	15.0	15.0
Flash Dont Walk (s)	9.0	9.0	5.0	5.0	5.0
Pedestrian Calls (#/hr)	16	16	51	51	41
Act Effct Green (s)	20.0	20.0	29.3	29.3	29.3
Actuated g/C Ratio	0.33	0.33	0.49	0.49	0.49
v/c Ratio	0.62	0.20	0.08	0.48	0.30
Control Delay	22.9	4.7	8.7	12.6	14.3
Queue Delay	0.0	0.0	0.0	0.0	0.0
Total Delay	22.9	4.7	8.7	12.6	14.3
LOS	C	A	A	B	B
Approach Delay	18.5			12.3	14.3
Approach LOS	B			B	B
Queue Length 50th (m)	31.0	0.0	2.1	27.7	15.2
Queue Length 95th (m)	54.6	8.4	6.1	47.5	m25.2
Internal Link Dist (m)	302.1			65.0	206.0
Turn Bay Length (m)		75.0	25.0		
Base Capacity (vph)	548	532	498	852	834
Starvation Cap Reductn	0	0	0	0	0
Spillback Cap Reductn	0	0	0	0	0
Storage Cap Reductn	0	0	0	0	0
Reduced v/c Ratio	0.62	0.20	0.08	0.48	0.30

Intersection Summary
 Cycle Length: 60
 Actuated Cycle Length: 60
 Offset: 35 (58%), Referenced to phase 2:NBTL and 6:SBT, Start of Green
 Natural Cycle: 55

Lanes, Volumes, Timings
6: Booth & Raymond

Future Total 2025AM Peak Hour
18 Louisa Street

Control Type: Actuated-Coordinated
 Maximum v/c Ratio: 0.62
 Intersection Signal Delay: 15.2
 Intersection Capacity Utilization 64.3%
 Analysis Period (min) 15
 m Volume for 95th percentile queue is metered by upstream signal.



Lanes, Volumes, Timings
1: Bronson & Raymond/Catherine

Future Total 2025PM Peak Hour
18 Louisa Street


Lane Group	WBL	WBT	NBL	NBT	SBT
Lane Configurations	↔	↔↔↔	↔	↔↔	↔↔
Traffic Volume (vph)	690	579	310	803	834
Future Volume (vph)	690	579	310	803	834
Lane Group Flow (vph)	386	1153	310	803	999
Turn Type	Perm	NA	pm+pt	NA	NA
Protected Phases		8	5	2	6
Permitted Phases		8	2		
Detector Phase	8	8	5	2	6
Switch Phase					
Minimum Initial (s)	10.0	10.0	5.0	10.0	10.0
Minimum Split (s)	28.3	28.3	11.8	24.8	24.8
Total Split (s)	33.0	33.0	25.0	67.0	42.0
Total Split (%)	33.0%	33.0%	25.0%	67.0%	42.0%
Maximum Green (s)	26.7	26.7	18.2	60.2	35.2
Yellow Time (s)	3.3	3.3	3.3	3.3	3.3
All-Red Time (s)	3.0	3.0	3.5	3.5	3.5
Lost Time Adjust (s)	0.0	0.0	0.0	0.0	0.0
Total Lost Time (s)	6.3	6.3	6.8	6.8	6.8
Lead/Lag			Lead		Lag
Lead-Lag Optimize?			Yes		Yes
Vehicle Extension (s)	3.0	3.0	3.0	3.0	3.0
Recall Mode	Max	Max	None	C-Max	C-Max
Walk Time (s)	7.0	7.0		7.0	7.0
Flash Dont Walk (s)	15.0	15.0		10.0	10.0
Pedestrian Calls (#/hr)	27	27		32	47
Act Effct Green (s)	26.7	26.7	60.2	60.2	37.1
Actuated g/C Ratio	0.27	0.27	0.60	0.60	0.37
v/c Ratio	1.02	0.98	0.87	0.40	0.84
Control Delay	88.2	57.7	46.0	11.2	22.5
Queue Delay	0.0	0.0	0.0	0.0	4.5
Total Delay	88.2	57.7	46.0	11.2	27.0
LOS	F	E	D	B	C
Approach Delay		65.4		20.9	27.0
Approach LOS		E		C	C
Queue Length 50th (m)	~89.1	81.5	39.1	39.8	67.5
Queue Length 95th (m)	#156.3	#114.4	#81.5	51.8	#129.7
Internal Link Dist (m)		247.5		81.5	56.5
Turn Bay Length (m)	110.0		45.0		
Base Capacity (vph)	380	1171	383	1996	1195
Starvation Cap Reductn	0	0	0	0	136
Spillback Cap Reductn	0	0	0	0	0
Storage Cap Reductn	0	0	0	0	0
Reduced v/c Ratio	1.02	0.98	0.81	0.40	0.94

Intersection Summary
 Cycle Length: 100
 Actuated Cycle Length: 100
 Offset: 60 (60%), Referenced to phase 2:NBT and 6:SBT, Start of Green
 Natural Cycle: 90

Lanes, Volumes, Timings
1: Bronson & Raymond/Catherine

Future Total 2025PM Peak Hour
18 Louisa Street

Control Type: Actuated-Coordinated
 Maximum v/c Ratio: 1.02
 Intersection Signal Delay: 41.3
 Intersection LOS: D
 Intersection Capacity Utilization 90.4%
 ICU Level of Service E
 Analysis Period (min) 15
 ~ Volume exceeds capacity, queue is theoretically infinite.
 Queue shown is maximum after two cycles.
 # 95th percentile volume exceeds capacity, queue may be longer.
 Queue shown is maximum after two cycles.



Lanes, Volumes, Timings
2: Bronson & Arlington

Future Total 2025PM Peak Hour
18 Louisa Street


Lane Group	EBL	EBT	WBL	WBT	NBL	NBT	SBL	SBT
Lane Configurations		↕		↕		↕		↕
Traffic Volume (vph)	12	2	2	0	24	1049	3	946
Future Volume (vph)	12	2	2	0	24	1049	3	946
Lane Group Flow (vph)	0	69	0	14	0	1085	0	971
Turn Type	Perm	NA	Perm	NA	Perm	NA	Perm	NA
Protected Phases		4		8		2		6
Permitted Phases	4		8		2		6	
Detector Phase	4	4	8	8	2	2	6	6
Switch Phase								
Minimum Initial (s)	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0
Minimum Split (s)	22.6	22.6	22.6	22.6	17.2	17.2	17.2	17.2
Total Split (s)	23.0	23.0	23.0	23.0	77.0	77.0	77.0	77.0
Total Split (%)	23.0%	23.0%	23.0%	23.0%	77.0%	77.0%	77.0%	77.0%
Maximum Green (s)	17.4	17.4	17.4	17.4	71.8	71.8	71.8	71.8
Yellow Time (s)	3.3	3.3	3.3	3.3	3.3	3.3	3.3	3.3
All-Red Time (s)	2.3	2.3	2.3	2.3	1.9	1.9	1.9	1.9
Lost Time Adjust (s)		0.0		0.0		0.0		0.0
Total Lost Time (s)		5.6		5.6		5.2		5.2
Lead/Lag								
Lead-Lag Optimize?								
Vehicle Extension (s)	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0
Recall Mode	None	None	None	None	C-Max	C-Max	C-Max	C-Max
Walk Time (s)	7.0	7.0	7.0	7.0	7.0	7.0	7.0	7.0
Flash Dont Walk (s)	10.0	10.0	10.0	10.0	5.0	5.0	5.0	5.0
Pedestrian Calls (#/hr)	22	22	23	23	29	29	40	40
Act Effct Green (s)		12.8		12.8		80.6		80.6
Actuated g/C Ratio		0.13		0.13		0.81		0.81
v/c Ratio		0.31		0.07		0.45		0.39
Control Delay		17.6		9.4		2.8		2.0
Queue Delay		0.0		0.0		0.1		0.0
Total Delay		17.6		9.4		2.9		2.0
LOS		B		A		A		A
Approach Delay		17.6		9.4		2.9		2.0
Approach LOS		B		A		A		A
Queue Length 50th (m)		2.5		0.0		13.4		13.4
Queue Length 95th (m)		14.0		3.7		m29.4		16.3
Internal Link Dist (m)		0.1		230.9		56.5		207.2
Turn Bay Length (m)								
Base Capacity (vph)		286		252		2419		2502
Starvation Cap Reductn		0		0		239		0
Spillback Cap Reductn		3		0		0		229
Storage Cap Reductn		0		0		0		0
Reduced v/c Ratio		0.24		0.06		0.50		0.43

Intersection Summary
 Cycle Length: 100
 Actuated Cycle Length: 100
 Offset: 29 (29%), Referenced to phase 2:NBTL and 6:SBTL, Start of Green
 Natural Cycle: 55

Lanes, Volumes, Timings
2: Bronson & Arlington

Future Total 2025PM Peak Hour
18 Louisa Street

Control Type: Actuated-Coordinated
 Maximum v/c Ratio: 0.45
 Intersection Signal Delay: 3.0 Intersection LOS: A
 Intersection Capacity Utilization 69.6% ICU Level of Service C
 Analysis Period (min) 15
 m Volume for 95th percentile queue is metered by upstream signal.



Lanes, Volumes, Timings
3: Bronson & Gladstone

Future Total 2025PM Peak Hour
18 Louisa Street

	↖	→	↗	←	↖	↑	↗	↓
Lane Group	EBL	EBT	WBL	WBT	NBL	NBT	SBL	SBT
Lane Configurations	↖	↗	↖	↗	↖	↗	↖	↗
Traffic Volume (vph)	48	330	139	271	96	803	49	789
Future Volume (vph)	48	330	139	271	96	803	49	789
Lane Group Flow (vph)	48	402	139	288	96	940	49	873
Turn Type	Perm	NA	Perm	NA	Perm	NA	Perm	NA
Protected Phases		4		8		2		6
Permitted Phases	4		8		2		6	
Detector Phase	4	4	8	8	2	2	6	6
Switch Phase								
Minimum Initial (s)	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0
Minimum Split (s)	28.2	28.2	28.2	28.2	25.0	25.0	25.0	25.0
Total Split (s)	50.0	50.0	50.0	50.0	50.0	50.0	50.0	50.0
Total Split (%)	50.0%	50.0%	50.0%	50.0%	50.0%	50.0%	50.0%	50.0%
Maximum Green (s)	43.8	43.8	43.8	43.8	44.0	44.0	44.0	44.0
Yellow Time (s)	3.0	3.0	3.0	3.0	3.3	3.3	3.3	3.3
All-Red Time (s)	3.2	3.2	3.2	3.2	2.7	2.7	2.7	2.7
Lost Time Adjust (s)	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
Total Lost Time (s)	6.2	6.2	6.2	6.2	6.0	6.0	6.0	6.0
Lead/Lag								
Lead-Lag Optimize?								
Vehicle Extension (s)	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0
Recall Mode	Max	Max	Max	Max	C-Max	C-Max	C-Max	C-Max
Walk Time (s)	7.0	7.0	7.0	7.0	7.0	7.0	7.0	7.0
Flash Dont Walk (s)	15.0	15.0	15.0	15.0	12.0	12.0	12.0	12.0
Pedestrian Calls (#/hr)	81	81	71	71	50	50	50	50
Act Effct Green (s)	43.8	43.8	43.8	43.8	44.0	44.0	44.0	44.0
Actuated g/C Ratio	0.44	0.44	0.44	0.44	0.44	0.44	0.44	0.44
v/c Ratio	0.13	0.56	0.47	0.39	0.56	0.69	0.33	0.62
Control Delay	18.0	24.8	26.5	21.0	25.4	15.6	26.1	23.9
Queue Delay	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
Total Delay	18.0	24.8	26.5	21.0	25.4	15.6	26.1	23.9
LOS	B	C	C	C	C	B	C	C
Approach Delay		24.0		22.8		16.5		24.0
Approach LOS		C		C		B		C
Queue Length 50th (m)	5.4	56.6	18.6	36.8	9.2	50.8	6.0	66.5
Queue Length 95th (m)	12.5	85.6	37.0	57.4	#36.5	33.5	16.3	86.4
Internal Link Dist (m)		139.3		203.3		207.2		176.5
Turn Bay Length (m)	20.0		20.0		35.0		45.0	
Base Capacity (vph)	376	714	295	738	170	1372	149	1417
Starvation Cap Reductn	0	0	0	0	0	0	0	0
Spillback Cap Reductn	0	0	0	0	0	0	0	0
Storage Cap Reductn	0	0	0	0	0	0	0	0
Reduced v/c Ratio	0.13	0.56	0.47	0.39	0.56	0.69	0.33	0.62


Intersection Summary

Cycle Length: 100
 Actuated Cycle Length: 100
 Offset: 40 (40%), Referenced to phase 2:NBT and 6:SBTL, Start of Green
 Natural Cycle: 60

Lanes, Volumes, Timings
3: Bronson & Gladstone

Future Total 2025PM Peak Hour
18 Louisa Street

Control Type: Actuated-Coordinated
 Maximum v/c Ratio: 0.69
 Intersection Signal Delay: 21.1 Intersection LOS: C
 Intersection Capacity Utilization 89.5% ICU Level of Service E
 Analysis Period (min) 15
 # 95th percentile volume exceeds capacity, queue may be longer.
 Queue shown is maximum after two cycles.



Lanes, Volumes, Timings
4: Booth & Gladstone

Future Total 2025PM Peak Hour
18 Luisa Street

	↖	→	↗	←	↖	↑	↗	↓
Lane Group	EBL	EBT	WBL	WBT	NBL	NBT	SBL	SBT
Lane Configurations	↖	↗	↖	↗	↖	↗	↖	↗
Traffic Volume (vph)	37	324	138	530	99	373	49	351
Future Volume (vph)	37	324	138	530	99	373	49	351
Lane Group Flow (vph)	37	366	138	570	99	447	49	371
Turn Type	Perm	NA	Perm	NA	Perm	NA	Perm	NA
Protected Phases		2		6		4		8
Permitted Phases	2		6		4		8	
Detector Phase	2	2	6	6	4	4	8	8
Switch Phase								
Minimum Initial (s)	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0
Minimum Split (s)	22.1	22.1	22.1	22.1	23.9	23.9	23.9	23.9
Total Split (s)	43.0	43.0	43.0	43.0	37.0	37.0	37.0	37.0
Total Split (%)	53.8%	53.8%	53.8%	53.8%	46.3%	46.3%	46.3%	46.3%
Maximum Green (s)	36.9	36.9	36.9	36.9	30.1	30.1	30.1	30.1
Yellow Time (s)	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0
All-Red Time (s)	3.1	3.1	3.1	3.1	3.9	3.9	3.9	3.9
Lost Time Adjust (s)	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
Total Lost Time (s)	6.1	6.1	6.1	6.1	6.9	6.9	6.9	6.9
Lead/Lag								
Lead-Lag Optimize?								
Vehicle Extension (s)	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0
Recall Mode	C-Max	C-Max	C-Max	C-Max	Max	Max	Max	Max
Walk Time (s)	7.0	7.0	7.0	7.0	7.0	7.0	7.0	7.0
Flash Dont Walk (s)	9.0	9.0	9.0	9.0	10.0	10.0	10.0	10.0
Pedestrian Calls (#/hr)	57	57	45	45	34	34	29	29
Act Effct Green (s)	36.9	36.9	36.9	36.9	30.1	30.1	30.1	30.1
Actuated g/C Ratio	0.46	0.46	0.46	0.46	0.38	0.38	0.38	0.38
v/c Ratio	0.17	0.47	0.39	0.72	0.36	0.70	0.22	0.57
Control Delay	15.1	16.9	29.1	34.0	22.7	27.6	20.4	23.8
Queue Delay	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
Total Delay	15.1	16.9	29.1	34.0	22.7	27.6	20.4	23.8
LOS	B	B	C	C	C	C	C	C
Approach Delay		16.8		33.1		26.7		23.4
Approach LOS		B		C		C		C
Queue Length 50th (m)	3.2	35.4	21.5	93.2	10.6	54.6	5.0	43.3
Queue Length 95th (m)	9.2	57.7	39.2	124.5	23.4	87.2	13.0	69.6
Internal Link Dist (m)		79.0		246.0		206.0		98.4
Turn Bay Length (m)	40.0		25.0		8.0		8.0	
Base Capacity (vph)	219	772	351	791	276	637	218	650
Starvation Cap Reductn	0	0	0	0	0	0	0	0
Spillback Cap Reductn	0	0	0	0	0	0	0	0
Storage Cap Reductn	0	0	0	0	0	0	0	0
Reduced v/c Ratio	0.17	0.47	0.39	0.72	0.36	0.70	0.22	0.57


Intersection Summary
 Cycle Length: 80
 Actuated Cycle Length: 80
 Offset: 51 (64%), Referenced to phase 2:EBTL and 6:WBTL, Start of Green
 Natural Cycle: 55

Lanes, Volumes, Timings
4: Booth & Gladstone

Future Total 2025PM Peak Hour
18 Luisa Street

Control Type: Actuated-Coordinated
 Maximum v/c Ratio: 0.72
 Intersection Signal Delay: 26.3 Intersection LOS: C
 Intersection Capacity Utilization 96.6% ICU Level of Service F
 Analysis Period (min) 15

Splits and Phases: 4: Booth & Gladstone



Lanes, Volumes, Timings
5: Arthur & Gladstone

Future Total 2025PM Peak Hour
18 Louisa Street


	↖	→	↗	←	↓
Lane Group	EBL	EBT	WBL	WBT	SBT
Lane Configurations		↕		↕	↕
Traffic Volume (vph)	31	484	1	614	1
Future Volume (vph)	31	484	1	614	1
Lane Group Flow (vph)	0	521	0	624	68
Turn Type	Perm	NA	Perm	NA	NA
Protected Phases		2		6	8
Permitted Phases	2		6		
Detector Phase	2	2	6	6	8
Switch Phase					
Minimum Initial (s)	10.0	10.0	10.0	10.0	10.0
Minimum Split (s)	29.5	29.5	29.5	29.5	23.2
Total Split (s)	56.8	56.8	56.8	56.8	23.2
Total Split (%)	71.0%	71.0%	71.0%	71.0%	29.0%
Maximum Green (s)	51.3	51.3	51.3	51.3	18.0
Yellow Time (s)	3.0	3.0	3.0	3.0	3.0
All-Red Time (s)	2.5	2.5	2.5	2.5	2.2
Lost Time Adjust (s)		0.0		0.0	0.0
Total Lost Time (s)		5.5		5.5	5.2
Lead/Lag					
Lead-Lag Optimize?					
Vehicle Extension (s)	3.0	3.0	3.0	3.0	3.0
Recall Mode	C-Max	C-Max	C-Max	C-Max	None
Walk Time (s)	19.0	19.0	19.0	19.0	10.0
Flash Dont Walk (s)	5.0	5.0	5.0	5.0	8.0
Pedestrian Calls (#/hr)	86	86	67	67	56
Act Effct Green (s)		58.6		58.6	14.8
Actuated g/C Ratio		0.73		0.73	0.18
v/c Ratio		0.43		0.49	0.23
Control Delay		5.9		8.3	12.4
Queue Delay		0.0		0.3	0.0
Total Delay		5.9		8.5	12.4
LOS		A		A	B
Approach Delay		5.9		8.5	12.4
Approach LOS		A		A	B
Queue Length 50th (m)		20.3		46.6	1.7
Queue Length 95th (m)		31.0		72.5	11.3
Internal Link Dist (m)		246.0		139.3	183.9
Turn Bay Length (m)					
Base Capacity (vph)		1206		1274	341
Starvation Cap Reductn		0		182	0
Spillback Cap Reductn		0		0	0
Storage Cap Reductn		0		0	0
Reduced v/c Ratio		0.43		0.57	0.20
Intersection Summary					
Cycle Length: 80					
Actuated Cycle Length: 80					
Offset: 65 (81%), Referenced to phase 2:EBTL and 6:WBTL, Start of Green					
Natural Cycle: 60					

Lanes, Volumes, Timings
5: Arthur & Gladstone

Future Total 2025PM Peak Hour
18 Louisa Street

Control Type: Actuated-Coordinated	
Maximum v/c Ratio: 0.49	
Intersection Signal Delay: 7.6	Intersection LOS: A
Intersection Capacity Utilization 76.9%	ICU Level of Service D
Analysis Period (min) 15	

Splits and Phases: 5: Arthur & Gladstone



Lanes, Volumes, Timings
6: Booth & Raymond

Future Total 2025PM Peak Hour
18 Louisa Street

Lane Group	WBT	WBR	NBL	NBT	SBT
Lane Configurations	↔	↔	↔	↔	↔
Traffic Volume (vph)	332	194	31	354	503
Future Volume (vph)	332	194	31	354	503
Lane Group Flow (vph)	509	194	31	354	594
Turn Type	NA	Perm	Perm	NA	NA
Protected Phases	8			2	6
Permitted Phases		8	2		
Detector Phase	8	8	2	2	6
Switch Phase					
Minimum Initial (s)	10.0	10.0	10.0	10.0	10.0
Minimum Split (s)	25.5	25.5	25.2	25.2	25.2
Total Split (s)	25.5	25.5	44.5	44.5	44.5
Total Split (%)	36.4%	36.4%	63.6%	63.6%	63.6%
Maximum Green (s)	20.0	20.0	39.3	39.3	39.3
Yellow Time (s)	3.3	3.3	3.3	3.3	3.3
All-Red Time (s)	2.2	2.2	1.9	1.9	1.9
Lost Time Adjust (s)	0.0	0.0	0.0	0.0	0.0
Total Lost Time (s)	5.5	5.5	5.2	5.2	5.2
Lead/Lag					
Lead-Lag Optimize?					
Vehicle Extension (s)	3.0	3.0	3.0	3.0	3.0
Recall Mode	Max	Max	C-Max	C-Max	C-Max
Walk Time (s)	11.0	11.0	15.0	15.0	15.0
Flash Dont Walk (s)	9.0	9.0	5.0	5.0	5.0
Pedestrian Calls (#/hr)	15	15	50	50	35
Act Effct Green (s)	20.0	20.0	39.3	39.3	39.3
Actuated g/C Ratio	0.29	0.29	0.56	0.56	0.56
v/c Ratio	1.06	0.36	0.10	0.36	0.62
Control Delay	86.7	5.5	8.2	9.8	13.5
Queue Delay	0.0	0.0	0.0	0.0	0.0
Total Delay	86.7	5.5	8.2	9.8	13.5
LOS	F	A	A	A	B
Approach Delay	64.3			9.6	13.5
Approach LOS	E			A	B
Queue Length 50th (m)	~75.2	0.0	1.7	23.2	45.9
Queue Length 95th (m)	#127.8	13.1	5.4	38.5	75.8
Internal Link Dist (m)	302.1			65.0	206.0
Turn Bay Length (m)		75.0	25.0		
Base Capacity (vph)	479	542	306	979	955
Starvation Cap Reductn	0	0	0	0	0
Spillback Cap Reductn	0	0	0	0	0
Storage Cap Reductn	0	0	0	0	0
Reduced v/c Ratio	1.06	0.36	0.10	0.36	0.62
Intersection Summary					
Cycle Length: 70					
Actuated Cycle Length: 70					
Offset: 39 (56%), Referenced to phase 2:NBT and 6:SBT, Start of Green					
Natural Cycle: 60					

Lanes, Volumes, Timings
6: Booth & Raymond

Future Total 2025PM Peak Hour
18 Louisa Street

Control Type: Actuated-Coordinated	
Maximum v/c Ratio: 1.06	
Intersection Signal Delay: 33.8	Intersection LOS: C
Intersection Capacity Utilization 78.6%	ICU Level of Service D
Analysis Period (min) 15	
~ Volume exceeds capacity, queue is theoretically infinite. Queue shown is maximum after two cycles.	
# 95th percentile volume exceeds capacity, queue may be longer. Queue shown is maximum after two cycles.	



Appendix K

Synchro Intersection Worksheets – 2030 Future Total Conditions

Lanes, Volumes, Timings
1: Bronson & Raymond/Catherine

Future Total 2030AM Peak Hour
18 Louisa Street


Lane Group	WBL	WBT	NBL	NBT	SBT	Ø5	Ø9
Lane Configurations	↔↔↔	↔↔↔	↔↔↔	↔↔↔	↔↔↔		
Traffic Volume (vph)	554	542	552	1102	478		
Future Volume (vph)	554	542	552	1102	478		
Lane Group Flow (vph)	366	1076	552	1102	596		
Turn Type	Perm	NA	pm+pt	NA	NA		
Protected Phases		8	5 9	2	6	5	9
Permitted Phases	8			2	9		
Detector Phase	8	8	5 9	2	6		
Switch Phase							
Minimum Initial (s)	10.0	10.0		10.0	10.0	5.0	5.0
Minimum Split (s)	28.3	28.3		24.8	24.8	11.8	11.8
Total Split (s)	34.0	34.0		53.0	33.0	20.0	23.0
Total Split (%)	30.9%	30.9%		48.2%	30.0%	18%	21%
Maximum Green (s)	27.7	27.7		46.2	26.2	13.2	16.8
Yellow Time (s)	3.3	3.3		3.3	3.3	3.3	3.3
All-Red Time (s)	3.0	3.0		3.5	3.5	3.5	2.9
Lost Time Adjust (s)	0.0	0.0		0.0	0.0		
Total Lost Time (s)	6.3	6.3		6.8	6.8		
Lead/Lag				Lead	Lag		
Lead-Lag Optimize?				Yes	Yes		
Vehicle Extension (s)	3.0	3.0		3.0	3.0	3.0	3.0
Recall Mode	Max	Max		C-Max	C-Max	Max	Max
Walk Time (s)	7.0	7.0		7.0	7.0		
Flash Dont Walk (s)	15.0	15.0		10.0	10.0		
Pedestrian Calls (#/hr)	43	43		48	31		
Act Effct Green (s)	27.7	27.7		62.4	69.2	26.2	
Actuated g/C Ratio	0.25	0.25		0.57	0.63	0.24	
v/c Ratio	1.04	0.99		0.94	0.53	0.81	
Control Delay	99.8	62.9		43.7	12.5	44.5	
Queue Delay	0.0	0.0		0.0	0.0	13.5	
Total Delay	99.8	62.9		43.7	12.5	58.0	
LOS	F	E		D	B	E	
Approach Delay		72.3			22.9	58.0	
Approach LOS		E			C	E	
Queue Length 50th (m)	~98.9	83.4		60.9	63.8	61.5	
Queue Length 95th (m)	#164.0	#116.6		#124.3	80.0	#83.0	
Internal Link Dist (m)		247.5			81.5	56.5	
Turn Bay Length (m)	110.0			45.0			
Base Capacity (vph)	352	1088		590	2086	739	
Starvation Cap Reductn	0	0		0	0	133	
Spillback Cap Reductn	0	0		0	80	0	
Storage Cap Reductn	0	0		0	0	0	
Reduced v/c Ratio	1.04	0.99		0.94	0.55	0.98	

Intersection Summary
 Cycle Length: 110
 Actuated Cycle Length: 110
 Offset: 38 (35%), Referenced to phase 2:NBT and 6:SBT, Start of Green
 Natural Cycle: 90

Lanes, Volumes, Timings
1: Bronson & Raymond/Catherine

Future Total 2030AM Peak Hour
18 Louisa Street

Control Type: Actuated-Coordinated
 Maximum v/c Ratio: 1.04
 Intersection Signal Delay: 47.9
 Intersection Capacity Utilization 91.5%
 Analysis Period (min) 15
 ~ Volume exceeds capacity, queue is theoretically infinite.
 Queue shown is maximum after two cycles.
 # 95th percentile volume exceeds capacity, queue may be longer.
 Queue shown is maximum after two cycles.



Lanes, Volumes, Timings
2: Bronson & Arlington

Future Total 2030AM Peak Hour
18 Louisa Street

Lane Group	EBL	EBT	WBL	WBT	NBL	NBT	SBL	SBT
Lane Configurations		↔		↔		↕		↕
Traffic Volume (vph)	10	4	8	2	13	1449	2	562
Future Volume (vph)	10	4	8	2	13	1449	2	562
Lane Group Flow (vph)	0	48	0	21	0	1468	0	580
Turn Type	Perm	NA	Perm	NA	Perm	NA	Perm	NA
Protected Phases		4		8		2		6
Permitted Phases	4		8		2		6	
Detector Phase	4	4	8	8	2	2	6	6
Switch Phase								
Minimum Initial (s)	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0
Minimum Split (s)	22.6	22.6	22.6	22.6	17.2	17.2	17.2	17.2
Total Split (s)	23.0	23.0	23.0	23.0	87.0	87.0	87.0	87.0
Total Split (%)	20.9%	20.9%	20.9%	20.9%	79.1%	79.1%	79.1%	79.1%
Maximum Green (s)	17.4	17.4	17.4	17.4	81.8	81.8	81.8	81.8
Yellow Time (s)	3.3	3.3	3.3	3.3	3.3	3.3	3.3	3.3
All-Red Time (s)	2.3	2.3	2.3	2.3	1.9	1.9	1.9	1.9
Lost Time Adjust (s)		0.0		0.0		0.0		0.0
Total Lost Time (s)		5.6		5.6		5.2		5.2
Lead/Lag								
Lead-Lag Optimize?								
Vehicle Extension (s)	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0
Recall Mode	None	None	None	None	C-Max	C-Max	C-Max	C-Max
Walk Time (s)	7.0	7.0	7.0	7.0	7.0	7.0	7.0	7.0
Flash Dont Walk (s)	10.0	10.0	10.0	10.0	5.0	5.0	5.0	5.0
Pedestrian Calls (#/hr)	26	26	22	22	21	21	28	28
Act Effct Green (s)		14.2		14.2		89.2		89.2
Actuated g/C Ratio		0.13		0.13		0.81		0.81
v/c Ratio		0.23		0.12		0.58		0.24
Control Delay		21.6		28.1		4.9		3.7
Queue Delay		0.0		0.0		0.0		0.0
Total Delay		21.7		28.1		4.9		3.8
LOS		C		C		A		A
Approach Delay		21.7		28.1		4.9		3.8
Approach LOS		C		C		A		A
Queue Length 50th (m)		2.6		1.9		40.6		17.2
Queue Length 95th (m)		13.1		9.0		m44.6		23.0
Internal Link Dist (m)		0.1		230.9		56.5		207.2
Turn Bay Length (m)								
Base Capacity (vph)		250		211		2520		2424
Starvation Cap Reductn		0		0		78		0
Spillback Cap Reductn		4		1		0		437
Storage Cap Reductn		0		0		0		0
Reduced v/c Ratio		0.20		0.10		0.60		0.29

Intersection Summary

Cycle Length: 110
 Actuated Cycle Length: 110
 Offset: 11 (10%), Referenced to phase 2:NBT and 6:SBTL, Start of Green
 Natural Cycle: 60

Lanes, Volumes, Timings
2: Bronson & Arlington

Future Total 2030AM Peak Hour
18 Louisa Street

Control Type: Actuated-Coordinated
 Maximum v/c Ratio: 0.58
 Intersection Signal Delay: 5.2
 Intersection Capacity Utilization 72.8%
 Analysis Period (min) 15
 m Volume for 95th percentile queue is metered by upstream signal.

Splits and Phases: 2: Bronson & Arlington



Lanes, Volumes, Timings
3: Bronson & Gladstone

Future Total 2030AM Peak Hour
18 Louisa Street

	↖	→	↗	←	↖	↑	↗	↓
Lane Group	EBL	EBT	WBL	WBT	NBL	NBT	SBL	SBT
Lane Configurations	↖	↗	↖	↗	↖	↗	↖	↗
Traffic Volume (vph)	50	356	84	191	123	1143	13	422
Future Volume (vph)	50	356	84	191	123	1143	13	422
Lane Group Flow (vph)	50	445	84	209	123	1293	13	461
Turn Type	Perm	NA	Perm	NA	Perm	NA	Perm	NA
Protected Phases		4		8		2		6
Permitted Phases	4		8		2		6	
Detector Phase	4	4	8	8	2	2	6	6
Switch Phase								
Minimum Initial (s)	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0
Minimum Split (s)	28.2	28.2	28.2	28.2	25.0	25.0	25.0	25.0
Total Split (s)	37.0	37.0	37.0	37.0	58.0	58.0	58.0	58.0
Total Split (%)	38.9%	38.9%	38.9%	38.9%	61.1%	61.1%	61.1%	61.1%
Maximum Green (s)	30.8	30.8	30.8	30.8	52.0	52.0	52.0	52.0
Yellow Time (s)	3.0	3.0	3.0	3.0	3.3	3.3	3.3	3.3
All-Red Time (s)	3.2	3.2	3.2	3.2	2.7	2.7	2.7	2.7
Lost Time Adjust (s)	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
Total Lost Time (s)	6.2	6.2	6.2	6.2	6.0	6.0	6.0	6.0
Lead/Lag								
Lead-Lag Optimize?								
Vehicle Extension (s)	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0
Recall Mode	Max	Max	Max	Max	C-Max	C-Max	C-Max	C-Max
Walk Time (s)	7.0	7.0	7.0	7.0	7.0	7.0	7.0	7.0
Flash Dont Walk (s)	15.0	15.0	15.0	15.0	12.0	12.0	12.0	12.0
Pedestrian Calls (#/hr)	96	96	39	39	41	41	34	34
Act Effct Green (s)	30.8	30.8	30.8	30.8	52.0	52.0	52.0	52.0
Actuated g/C Ratio	0.32	0.32	0.32	0.32	0.55	0.55	0.55	0.55
v/c Ratio	0.16	0.85	0.60	0.39	0.28	0.74	0.11	0.27
Control Delay	24.6	46.8	47.3	27.6	13.7	19.7	13.2	11.9
Queue Delay	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
Total Delay	24.6	46.8	47.3	27.6	13.7	19.7	13.2	11.9
LOS	C	D	D	C	B	B	B	B
Approach Delay		44.5		33.2		19.2		11.9
Approach LOS		D		C		B		B
Queue Length 50th (m)	6.5	75.4	12.8	29.4	11.4	89.5	1.1	22.2
Queue Length 95th (m)	15.2	#126.9	#34.0	48.8	22.6	115.3	4.5	31.1
Internal Link Dist (m)		139.3		203.3		207.2		176.5
Turn Bay Length (m)	20.0		20.0		35.0		45.0	
Base Capacity (vph)	316	525	141	534	435	1742	118	1724
Starvation Cap Reductn	0	0	0	0	0	0	0	0
Spillback Cap Reductn	0	0	0	0	0	0	0	0
Storage Cap Reductn	0	0	0	0	0	0	0	0
Reduced v/c Ratio	0.16	0.85	0.60	0.39	0.28	0.74	0.11	0.27

Intersection Summary


Cycle Length: 95
 Actuated Cycle Length: 95
 Offset: 42 (44%), Referenced to phase 2:NBT and 6:SBTL, Start of Green
 Natural Cycle: 60

Lanes, Volumes, Timings
3: Bronson & Gladstone

Future Total 2030AM Peak Hour
18 Louisa Street

Control Type: Actuated-Coordinated	
Maximum v/c Ratio: 0.85	
Intersection Signal Delay: 24.1	Intersection LOS: C
Intersection Capacity Utilization 102.5%	ICU Level of Service G
Analysis Period (min) 15	
# 95th percentile volume exceeds capacity, queue may be longer.	
Queue shown is maximum after two cycles.	

Splits and Phases: 3: Bronson & Gladstone



Lanes, Volumes, Timings
4: Booth & Gladstone

Future Total 2030AM Peak Hour
18 Louisa Street

Lane Group	EBL	EBT	WBL	WBT	NBL	NBT	SBL	SBT
Lane Configurations	↔	↕	↔	↕	↔	↕	↔	↕
Traffic Volume (vph)	26	428	42	283	51	374	39	142
Future Volume (vph)	26	428	42	283	51	374	39	142
Lane Group Flow (vph)	26	499	42	314	51	451	39	162
Turn Type	Perm	NA	Perm	NA	Perm	NA	Perm	NA
Protected Phases		2		6		4		8
Permitted Phases	2		6		4		8	
Detector Phase	2	2	6	6	4	4	8	8
Switch Phase								
Minimum Initial (s)	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0
Minimum Split (s)	22.1	22.1	22.1	22.1	23.9	23.9	23.9	23.9
Total Split (s)	28.0	28.0	28.0	28.0	32.0	32.0	32.0	32.0
Total Split (%)	46.7%	46.7%	46.7%	46.7%	53.3%	53.3%	53.3%	53.3%
Maximum Green (s)	21.9	21.9	21.9	21.9	25.1	25.1	25.1	25.1
Yellow Time (s)	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0
All-Red Time (s)	3.1	3.1	3.1	3.1	3.9	3.9	3.9	3.9
Lost Time Adjust (s)	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
Total Lost Time (s)	6.1	6.1	6.1	6.1	6.9	6.9	6.9	6.9
Lead/Lag								
Lead-Lag Optimize?								
Vehicle Extension (s)	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0
Recall Mode	C-Max	C-Max	C-Max	C-Max	Max	Max	Max	Max
Walk Time (s)	7.0	7.0	7.0	7.0	7.0	7.0	7.0	7.0
Flash Dont Walk (s)	9.0	9.0	9.0	9.0	10.0	10.0	10.0	10.0
Pedestrian Calls (#/hr)	53	53	32	32	36	36	6	6
Act Effct Green (s)	21.9	21.9	21.9	21.9	25.1	25.1	25.1	25.1
Actuated g/C Ratio	0.36	0.36	0.36	0.36	0.42	0.42	0.42	0.42
v/c Ratio	0.08	0.83	0.23	0.52	0.11	0.63	0.14	0.22
Control Delay	13.5	31.8	17.4	18.1	10.0	13.4	12.3	11.2
Queue Delay	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
Total Delay	13.5	31.8	17.4	18.1	10.0	13.4	12.3	11.2
LOS	B	C	B	B	B	B	B	B
Approach Delay		30.9		18.0		13.0		11.4
Approach LOS		C		B		B		B
Queue Length 50th (m)	1.8	47.0	3.1	25.3	2.0	17.1	2.5	9.8
Queue Length 95th (m)	6.2	#95.7	9.9	45.5	m6.0	37.2	7.7	20.2
Internal Link Dist (m)		79.0		246.0		206.0		98.4
Turn Bay Length (m)	40.0		25.0		8.0		8.0	
Base Capacity (vph)	310	600	180	609	474	712	288	721
Starvation Cap Reductn	0	0	0	0	0	0	0	0
Spillback Cap Reductn	0	0	0	0	0	0	0	0
Storage Cap Reductn	0	0	0	0	0	0	0	0
Reduced v/c Ratio	0.08	0.83	0.23	0.52	0.11	0.63	0.14	0.22

Intersection Summary


Cycle Length: 60
Actuated Cycle Length: 60
Offset: 16 (27%), Referenced to phase 2:EBTL and 6:WBTL, Start of Green
Natural Cycle: 55

Lanes, Volumes, Timings
4: Booth & Gladstone

Future Total 2030AM Peak Hour
18 Louisa Street

Control Type: Actuated-Coordinated	
Maximum v/c Ratio: 0.83	
Intersection Signal Delay: 19.8	Intersection LOS: B
Intersection Capacity Utilization 88.0%	ICU Level of Service E
Analysis Period (min) 15	
# 95th percentile volume exceeds capacity, queue may be longer.	
Queue shown is maximum after two cycles.	
m Volume for 95th percentile queue is metered by upstream signal.	

Splits and Phases: 4: Booth & Gladstone



Lanes, Volumes, Timings
5: Arthur & Gladstone

Future Total 2030AM Peak Hour
18 Louisa Street

	↖	→	←	↓
Lane Group	EBL	EBT	WBT	SBT
Lane Configurations		↕	↕	↕
Traffic Volume (vph)	30	548	361	0
Future Volume (vph)	30	548	361	0
Lane Group Flow (vph)	0	579	375	36
Turn Type	Perm	NA	NA	NA
Protected Phases		2	6	8
Permitted Phases	2			
Detector Phase	2	2	6	8
Switch Phase				
Minimum Initial (s)	10.0	10.0	10.0	10.0
Minimum Split (s)	29.5	29.5	29.5	23.2
Total Split (s)	31.8	31.8	31.8	23.2
Total Split (%)	57.8%	57.8%	57.8%	42.2%
Maximum Green (s)	26.3	26.3	26.3	18.0
Yellow Time (s)	3.0	3.0	3.0	3.0
All-Red Time (s)	2.5	2.5	2.5	2.2
Lost Time Adjust (s)		0.0	0.0	0.0
Total Lost Time (s)		5.5	5.5	5.2
Lead/Lag				
Lead-Lag Optimize?				
Vehicle Extension (s)	3.0	3.0	3.0	3.0
Recall Mode	Max	Max	Max	None
Walk Time (s)	19.0	19.0	19.0	10.0
Flash Dont Walk (s)	5.0	5.0	5.0	8.0
Pedestrian Calls (#/hr)	92	92	49	43
Act Effct Green (s)		42.0	42.0	13.2
Actuated g/C Ratio		0.75	0.75	0.23
v/c Ratio		0.46	0.30	0.09
Control Delay		9.1	6.9	4.5
Queue Delay		0.0	0.0	0.0
Total Delay		9.1	6.9	4.5
LOS		A	A	A
Approach Delay		9.1	6.9	4.5
Approach LOS		A	A	A
Queue Length 50th (m)		27.6	14.7	0.0
Queue Length 95th (m)		#75.3	40.8	3.7
Internal Link Dist (m)		246.0	139.3	183.9
Turn Bay Length (m)				
Base Capacity (vph)		1251	1256	513
Starvation Cap Reductn		0	0	0
Spillback Cap Reductn		0	0	0
Storage Cap Reductn		0	0	0
Reduced v/c Ratio		0.46	0.30	0.07
Intersection Summary				
Cycle Length: 55				
Actuated Cycle Length: 56.2				
Natural Cycle: 60				
Control Type: Actuated-Uncoordinated				

Lanes, Volumes, Timings
5: Arthur & Gladstone

Future Total 2030AM Peak Hour
18 Louisa Street

Maximum v/c Ratio: 0.46	Intersection LOS: A
Intersection Signal Delay: 8.1	ICU Level of Service D
Intersection Capacity Utilization 77.7%	
Analysis Period (min) 15	
# 95th percentile volume exceeds capacity, queue may be longer.	
Queue shown is maximum after two cycles.	

Splits and Phases: 5: Arthur & Gladstone



Lanes, Volumes, Timings
6: Booth & Raymond

Future Total 2030AM Peak Hour
18 Louisa Street


Lane Group	WBT	WBR	NBL	NBT	SBT
Lane Configurations	↔	↔	↔	↔	↔
Traffic Volume (vph)	220	108	38	428	223
Future Volume (vph)	220	108	38	428	223
Lane Group Flow (vph)	342	108	38	428	258
Turn Type	NA	Perm	Perm	NA	NA
Protected Phases	8			2	6
Permitted Phases		8	2		
Detector Phase	8	8	2	2	6
Switch Phase					
Minimum Initial (s)	10.0	10.0	10.0	10.0	10.0
Minimum Split (s)	25.5	25.5	25.2	25.2	25.2
Total Split (s)	25.5	25.5	34.5	34.5	34.5
Total Split (%)	42.5%	42.5%	57.5%	57.5%	57.5%
Maximum Green (s)	20.0	20.0	29.3	29.3	29.3
Yellow Time (s)	3.3	3.3	3.3	3.3	3.3
All-Red Time (s)	2.2	2.2	1.9	1.9	1.9
Lost Time Adjust (s)	0.0	0.0	0.0	0.0	0.0
Total Lost Time (s)	5.5	5.5	5.2	5.2	5.2
Lead/Lag					
Lead-Lag Optimize?					
Vehicle Extension (s)	3.0	3.0	3.0	3.0	3.0
Recall Mode	Max	Max	C-Max	C-Max	C-Max
Walk Time (s)	11.0	11.0	15.0	15.0	15.0
Flash Dont Walk (s)	9.0	9.0	5.0	5.0	5.0
Pedestrian Calls (#/hr)	16	16	51	51	41
Act Effct Green (s)	20.0	20.0	29.3	29.3	29.3
Actuated g/C Ratio	0.33	0.33	0.49	0.49	0.49
v/c Ratio	0.62	0.20	0.08	0.50	0.31
Control Delay	22.9	4.7	8.7	13.0	14.6
Queue Delay	0.0	0.0	0.0	0.0	0.0
Total Delay	22.9	4.7	8.7	13.0	14.6
LOS	C	A	A	B	B
Approach Delay	18.5			12.6	14.6
Approach LOS	B			B	B
Queue Length 50th (m)	31.0	0.0	2.1	29.6	16.4
Queue Length 95th (m)	54.6	8.4	6.1	50.6	m0.0
Internal Link Dist (m)	302.1			65.0	206.0
Turn Bay Length (m)		75.0	25.0		
Base Capacity (vph)	548	532	500	852	835
Starvation Cap Reductn	0	0	0	0	0
Spillback Cap Reductn	0	0	0	0	0
Storage Cap Reductn	0	0	0	0	0
Reduced v/c Ratio	0.62	0.20	0.08	0.50	0.31

Intersection Summary
 Cycle Length: 60
 Actuated Cycle Length: 60
 Offset: 35 (58%), Referenced to phase 2:NBT and 6:SBT, Start of Green
 Natural Cycle: 55

Lanes, Volumes, Timings
6: Booth & Raymond

Future Total 2030AM Peak Hour
18 Louisa Street

Control Type: Actuated-Coordinated
 Maximum v/c Ratio: 0.62
 Intersection Signal Delay: 15.3
 Intersection Capacity Utilization 64.3%
 Analysis Period (min) 15
 m Volume for 95th percentile queue is metered by upstream signal.



Lanes, Volumes, Timings
1: Bronson & Raymond/Catherine

Future Total 2030PM Peak Hour
18 Louisa Street


Lane Group	WBL	WBT	NBL	NBT	SBT
Lane Configurations	↔	↔↔↔	↔	↔↔	↔↔
Traffic Volume (vph)	690	579	321	833	855
Future Volume (vph)	690	579	321	833	855
Lane Group Flow (vph)	386	1153	321	833	1020
Turn Type	Perm	NA	pm+pt	NA	NA
Protected Phases		8	5	2	6
Permitted Phases	8		2		
Detector Phase	8	8	5	2	6
Switch Phase					
Minimum Initial (s)	10.0	10.0	5.0	10.0	10.0
Minimum Split (s)	28.3	28.3	11.8	24.8	24.8
Total Split (s)	33.0	33.0	25.0	67.0	42.0
Total Split (%)	33.0%	33.0%	25.0%	67.0%	42.0%
Maximum Green (s)	26.7	26.7	18.2	60.2	35.2
Yellow Time (s)	3.3	3.3	3.3	3.3	3.3
All-Red Time (s)	3.0	3.0	3.5	3.5	3.5
Lost Time Adjust (s)	0.0	0.0	0.0	0.0	0.0
Total Lost Time (s)	6.3	6.3	6.8	6.8	6.8
Lead/Lag			Lead		Lag
Lead-Lag Optimize?			Yes		Yes
Vehicle Extension (s)	3.0	3.0	3.0	3.0	3.0
Recall Mode	Max	Max	None	C-Max	C-Max
Walk Time (s)	7.0	7.0		7.0	7.0
Flash Dont Walk (s)	15.0	15.0		10.0	10.0
Pedestrian Calls (#/hr)	27	27		32	47
Act Effct Green (s)	26.7	26.7	60.2	60.2	36.7
Actuated g/C Ratio	0.27	0.27	0.60	0.60	0.37
v/c Ratio	1.02	0.98	0.90	0.42	0.86
Control Delay	88.2	57.7	53.0	11.4	24.1
Queue Delay	0.0	0.0	0.0	0.0	6.1
Total Delay	88.2	57.7	53.0	11.4	30.2
LOS	F	E	D	B	C
Approach Delay		65.4		22.9	30.2
Approach LOS		E		C	C
Queue Length 50th (m)	~89.1	81.5	43.5	41.7	70.8
Queue Length 95th (m)	#156.3	#114.4	#89.5	54.2	#132.5
Internal Link Dist (m)		247.5		81.5	56.5
Turn Bay Length (m)	110.0		45.0		
Base Capacity (vph)	380	1171	376	1996	1184
Starvation Cap Reductn	0	0	0	0	126
Spillback Cap Reductn	0	0	0	0	0
Storage Cap Reductn	0	0	0	0	0
Reduced v/c Ratio	1.02	0.98	0.85	0.42	0.96

Intersection Summary
 Cycle Length: 100
 Actuated Cycle Length: 100
 Offset: 60 (60%), Referenced to phase 2:NBT and 6:SBT, Start of Green
 Natural Cycle: 90

Lanes, Volumes, Timings
1: Bronson & Raymond/Catherine

Future Total 2030PM Peak Hour
18 Louisa Street

Control Type: Actuated-Coordinated
 Maximum v/c Ratio: 1.02
 Intersection Signal Delay: 42.5
 Intersection LOS: D
 Intersection Capacity Utilization 91.6%
 ICU Level of Service F
 Analysis Period (min) 15
 ~ Volume exceeds capacity, queue is theoretically infinite.
 Queue shown is maximum after two cycles.
 # 95th percentile volume exceeds capacity, queue may be longer.
 Queue shown is maximum after two cycles.



Lanes, Volumes, Timings
2: Bronson & Arlington

Future Total 2030PM Peak Hour
18 Louisa Street


Lane Group	EBL	EBT	WBL	WBT	NBL	NBT	SBL	SBT
Lane Configurations		↔		↔		↕		↕
Traffic Volume (vph)	12	2	2	0	24	1089	3	970
Future Volume (vph)	12	2	2	0	24	1089	3	970
Lane Group Flow (vph)	0	69	0	14	0	1125	0	995
Turn Type	Perm	NA	Perm	NA	Perm	NA	Perm	NA
Protected Phases		4		8		2		6
Permitted Phases	4		8		2		6	
Detector Phase	4	4	8	8	2	2	6	6
Switch Phase								
Minimum Initial (s)	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0
Minimum Split (s)	22.6	22.6	22.6	22.6	17.2	17.2	17.2	17.2
Total Split (s)	23.0	23.0	23.0	23.0	77.0	77.0	77.0	77.0
Total Split (%)	23.0%	23.0%	23.0%	23.0%	77.0%	77.0%	77.0%	77.0%
Maximum Green (s)	17.4	17.4	17.4	17.4	71.8	71.8	71.8	71.8
Yellow Time (s)	3.3	3.3	3.3	3.3	3.3	3.3	3.3	3.3
All-Red Time (s)	2.3	2.3	2.3	2.3	1.9	1.9	1.9	1.9
Lost Time Adjust (s)		0.0		0.0		0.0		0.0
Total Lost Time (s)		5.6		5.6		5.2		5.2
Lead/Lag								
Lead-Lag Optimize?								
Vehicle Extension (s)	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0
Recall Mode	None	None	None	None	C-Max	C-Max	C-Max	C-Max
Walk Time (s)	7.0	7.0	7.0	7.0	7.0	7.0	7.0	7.0
Flash Dont Walk (s)	10.0	10.0	10.0	10.0	5.0	5.0	5.0	5.0
Pedestrian Calls (#/hr)	22	22	23	23	29	29	40	40
Act Effct Green (s)		12.8		12.8		80.6		80.6
Actuated g/C Ratio		0.13		0.13		0.81		0.81
v/c Ratio		0.31		0.07		0.47		0.40
Control Delay		17.6		9.4		2.9		1.9
Queue Delay		0.0		0.0		0.0		0.0
Total Delay		17.6		9.4		2.9		1.9
LOS		B		A		A		A
Approach Delay		17.6		9.4		2.9		1.9
Approach LOS		B		A		A		A
Queue Length 50th (m)		2.5		0.0		13.7		12.2
Queue Length 95th (m)		14.0		3.7		m30.0		15.0
Internal Link Dist (m)		0.1		230.9		56.5		207.2
Turn Bay Length (m)								
Base Capacity (vph)		286		252		2419		2502
Starvation Cap Reductn		0		0		174		0
Spillback Cap Reductn		3		0		0		232
Storage Cap Reductn		0		0		0		0
Reduced v/c Ratio		0.24		0.06		0.50		0.44

Intersection Summary
 Cycle Length: 100
 Actuated Cycle Length: 100
 Offset: 29 (29%), Referenced to phase 2:NBTL and 6:SBTL, Start of Green
 Natural Cycle: 55

Lanes, Volumes, Timings
2: Bronson & Arlington

Future Total 2030PM Peak Hour
18 Louisa Street

Control Type: Actuated-Coordinated
 Maximum v/c Ratio: 0.47
 Intersection Signal Delay: 2.9 Intersection LOS: A
 Intersection Capacity Utilization 70.8% ICU Level of Service C
 Analysis Period (min) 15
 m Volume for 95th percentile queue is metered by upstream signal.



Lanes, Volumes, Timings
3: Bronson & Gladstone

Future Total 2030PM Peak Hour
18 Louisa Street

	↖	→	↗	←	↖	↑	↗	↓
Lane Group	EBL	EBT	WBL	WBT	NBL	NBT	SBL	SBT
Lane Configurations	↖	↗	↖	↗	↖	↗	↖	↗
Traffic Volume (vph)	48	359	139	314	96	833	49	809
Future Volume (vph)	48	359	139	314	96	833	49	809
Lane Group Flow (vph)	48	431	139	331	96	970	49	893
Turn Type	Perm	NA	Perm	NA	Perm	NA	Perm	NA
Protected Phases		4		8		2		6
Permitted Phases	4		8		2		6	
Detector Phase	4	4	8	8	2	2	6	6
Switch Phase								
Minimum Initial (s)	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0
Minimum Split (s)	28.2	28.2	28.2	28.2	25.0	25.0	25.0	25.0
Total Split (s)	50.0	50.0	50.0	50.0	50.0	50.0	50.0	50.0
Total Split (%)	50.0%	50.0%	50.0%	50.0%	50.0%	50.0%	50.0%	50.0%
Maximum Green (s)	43.8	43.8	43.8	43.8	44.0	44.0	44.0	44.0
Yellow Time (s)	3.0	3.0	3.0	3.0	3.3	3.3	3.3	3.3
All-Red Time (s)	3.2	3.2	3.2	3.2	2.7	2.7	2.7	2.7
Lost Time Adjust (s)	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
Total Lost Time (s)	6.2	6.2	6.2	6.2	6.0	6.0	6.0	6.0
Lead/Lag								
Lead-Lag Optimize?								
Vehicle Extension (s)	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0
Recall Mode	Max	Max	Max	Max	C-Max	C-Max	C-Max	C-Max
Walk Time (s)	7.0	7.0	7.0	7.0	7.0	7.0	7.0	7.0
Flash Dont Walk (s)	15.0	15.0	15.0	15.0	12.0	12.0	12.0	12.0
Pedestrian Calls (#/hr)	81	81	71	71	50	50	50	50
Act Effct Green (s)	43.8	43.8	43.8	43.8	44.0	44.0	44.0	44.0
Actuated g/C Ratio	0.44	0.44	0.44	0.44	0.44	0.44	0.44	0.44
v/c Ratio	0.14	0.60	0.51	0.45	0.59	0.71	0.35	0.63
Control Delay	18.3	25.8	28.3	22.1	27.7	16.1	27.5	24.2
Queue Delay	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
Total Delay	18.3	25.8	28.3	22.1	27.7	16.1	27.5	24.2
LOS	B	C	C	C	C	B	C	C
Approach Delay		25.1		23.9		17.1		24.3
Approach LOS		C		C		B		C
Queue Length 50th (m)	5.4	62.0	18.9	43.6	9.3	52.6	6.1	68.6
Queue Length 95th (m)	12.7	93.2	38.5	67.1	#37.9	34.6	16.8	88.8
Internal Link Dist (m)		139.3		203.3		207.2		176.5
Turn Bay Length (m)	20.0		20.0		35.0		45.0	
Base Capacity (vph)	346	717	275	740	163	1374	140	1418
Starvation Cap Reductn	0	0	0	0	0	0	0	0
Spillback Cap Reductn	0	0	0	0	0	0	0	0
Storage Cap Reductn	0	0	0	0	0	0	0	0
Reduced v/c Ratio	0.14	0.60	0.51	0.45	0.59	0.71	0.35	0.63


Intersection Summary

Cycle Length: 100
 Actuated Cycle Length: 100
 Offset: 40 (40%), Referenced to phase 2:NBT and 6:SBTL, Start of Green
 Natural Cycle: 60

Lanes, Volumes, Timings
3: Bronson & Gladstone

Future Total 2030PM Peak Hour
18 Louisa Street

Control Type: Actuated-Coordinated
 Maximum v/c Ratio: 0.71
 Intersection Signal Delay: 21.8
 Intersection Capacity Utilization 91.9%
 Analysis Period (min) 15
 # 95th percentile volume exceeds capacity, queue may be longer.
 Queue shown is maximum after two cycles.



Lanes, Volumes, Timings
4: Booth & Gladstone

Future Total 2030PM Peak Hour
18 Louisa Street


	↖	→	↗	←	↖	↑	↗	↓
Lane Group	EBL	EBT	WBL	WBT	NBL	NBT	SBL	SBT
Lane Configurations	↖	↗	↖	↗	↖	↗	↖	↗
Traffic Volume (vph)	37	353	138	615	99	387	49	368
Future Volume (vph)	37	353	138	615	99	387	49	368
Lane Group Flow (vph)	37	395	138	655	99	461	49	388
Turn Type	Perm	NA	Perm	NA	Perm	NA	Perm	NA
Protected Phases		2		6		4		8
Permitted Phases	2		6		4		8	
Detector Phase	2	2	6	6	4	4	8	8
Switch Phase								
Minimum Initial (s)	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0
Minimum Split (s)	22.1	22.1	22.1	22.1	23.9	23.9	23.9	23.9
Total Split (s)	43.0	43.0	43.0	43.0	37.0	37.0	37.0	37.0
Total Split (%)	53.8%	53.8%	53.8%	53.8%	46.3%	46.3%	46.3%	46.3%
Maximum Green (s)	36.9	36.9	36.9	36.9	30.1	30.1	30.1	30.1
Yellow Time (s)	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0
All-Red Time (s)	3.1	3.1	3.1	3.1	3.9	3.9	3.9	3.9
Lost Time Adjust (s)	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
Total Lost Time (s)	6.1	6.1	6.1	6.1	6.9	6.9	6.9	6.9
Lead/Lag								
Lead-Lag Optimize?								
Vehicle Extension (s)	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0
Recall Mode	C-Max	C-Max	C-Max	C-Max	Max	Max	Max	Max
Walk Time (s)	7.0	7.0	7.0	7.0	7.0	7.0	7.0	7.0
Flash Dont Walk (s)	9.0	9.0	9.0	9.0	10.0	10.0	10.0	10.0
Pedestrian Calls (#/hr)	57	57	45	45	34	34	29	29
Act Effct Green (s)	36.9	36.9	36.9	36.9	30.1	30.1	30.1	30.1
Actuated g/C Ratio	0.46	0.46	0.46	0.46	0.38	0.38	0.38	0.38
v/c Ratio	0.22	0.51	0.42	0.83	0.37	0.72	0.23	0.60
Control Delay	17.3	17.7	29.7	39.2	23.0	28.5	20.8	24.5
Queue Delay	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
Total Delay	17.3	17.7	29.7	39.2	23.0	28.5	20.8	24.5
LOS	B	B	C	D	C	C	C	C
Approach Delay		17.6		37.6		27.5		24.1
Approach LOS		B		D		C		C
Queue Length 50th (m)	3.2	39.3	22.0	108.5	10.7	56.9	5.0	45.9
Queue Length 95th (m)	10.0	63.5	39.9	#150.0	23.6	90.9	13.2	73.3
Internal Link Dist (m)		79.0		246.0		206.0		98.4
Turn Bay Length (m)	40.0		25.0		8.0		8.0	
Base Capacity (vph)	166	774	332	793	270	638	209	650
Starvation Cap Reductn	0	0	0	0	0	0	0	0
Spillback Cap Reductn	0	0	0	0	0	0	0	0
Storage Cap Reductn	0	0	0	0	0	0	0	0
Reduced v/c Ratio	0.22	0.51	0.42	0.83	0.37	0.72	0.23	0.60

Intersection Summary	
Cycle Length:	80
Actuated Cycle Length:	80
Offset:	51 (64%), Referenced to phase 2:EBTL and 6:WBTL, Start of Green
Natural Cycle:	65

Lanes, Volumes, Timings
4: Booth & Gladstone

Future Total 2030PM Peak Hour
18 Louisa Street

Control Type:	Actuated-Coordinated
Maximum v/c Ratio:	0.83
Intersection Signal Delay:	28.5
Intersection LOS:	C
Intersection Capacity Utilization:	102.0%
ICU Level of Service:	G
Analysis Period (min):	15
# 95th percentile volume exceeds capacity, queue may be longer.	
Queue shown is maximum after two cycles.	



Lanes, Volumes, Timings
5: Arthur & Gladstone

Future Total 2030PM Peak Hour
18 Louisa Street

	↖	→	↗	←	↓
Lane Group	EBL	EBT	WBL	WBT	SBT
Lane Configurations		↕		↕	↕
Traffic Volume (vph)	31	528	1	711	1
Future Volume (vph)	31	528	1	711	1
Lane Group Flow (vph)	0	565	0	721	68
Turn Type	Perm	NA	Perm	NA	NA
Protected Phases		2		6	8
Permitted Phases	2		6		
Detector Phase	2	2	6	6	8
Switch Phase					
Minimum Initial (s)	10.0	10.0	10.0	10.0	10.0
Minimum Split (s)	29.5	29.5	29.5	29.5	23.2
Total Split (s)	56.8	56.8	56.8	56.8	23.2
Total Split (%)	71.0%	71.0%	71.0%	71.0%	29.0%
Maximum Green (s)	51.3	51.3	51.3	51.3	18.0
Yellow Time (s)	3.0	3.0	3.0	3.0	3.0
All-Red Time (s)	2.5	2.5	2.5	2.5	2.2
Lost Time Adjust (s)		0.0		0.0	0.0
Total Lost Time (s)		5.5		5.5	5.2
Lead/Lag					
Lead-Lag Optimize?					
Vehicle Extension (s)	3.0	3.0	3.0	3.0	3.0
Recall Mode	C-Max	C-Max	C-Max	C-Max	None
Walk Time (s)	19.0	19.0	19.0	19.0	10.0
Flash Dont Walk (s)	5.0	5.0	5.0	5.0	8.0
Pedestrian Calls (#/hr)	86	86	67	67	56
Act Effct Green (s)		58.6		58.6	14.8
Actuated g/C Ratio		0.73		0.73	0.18
v/c Ratio		0.47		0.57	0.23
Control Delay		6.1		9.5	12.4
Queue Delay		0.0		0.3	0.0
Total Delay		6.1		9.8	12.4
LOS		A		A	B
Approach Delay		6.1		9.8	12.4
Approach LOS		A		A	B
Queue Length 50th (m)		21.5		58.9	1.7
Queue Length 95th (m)		32.0		92.5	11.3
Internal Link Dist (m)		246.0		139.3	183.9
Turn Bay Length (m)					
Base Capacity (vph)		1203		1274	341
Starvation Cap Reductn		0		164	0
Spillback Cap Reductn		0		0	0
Storage Cap Reductn		0		0	0
Reduced v/c Ratio		0.47		0.65	0.20
Intersection Summary					
Cycle Length: 80					
Actuated Cycle Length: 80					
Offset: 65 (81%), Referenced to phase 2:EBTL and 6:WBTL, Start of Green					
Natural Cycle: 60					

Lanes, Volumes, Timings
5: Arthur & Gladstone

Future Total 2030PM Peak Hour
18 Louisa Street

Control Type: Actuated-Coordinated	
Maximum v/c Ratio: 0.57	
Intersection Signal Delay: 8.4	Intersection LOS: A
Intersection Capacity Utilization 79.4%	ICU Level of Service D
Analysis Period (min) 15	
Splits and Phases: 5: Arthur & Gladstone	

Lanes, Volumes, Timings
6: Booth & Raymond

Future Total 2030PM Peak Hour
18 Louisa Street

Lane Group	WBT	WBR	NBL	NBT	SBT
Lane Configurations	↔	↔	↔	↔	↔
Traffic Volume (vph)	332	194	31	367	528
Future Volume (vph)	332	194	31	367	528
Lane Group Flow (vph)	509	194	31	367	619
Turn Type	NA	Perm	Perm	NA	NA
Protected Phases	8			2	6
Permitted Phases		8	2		
Detector Phase	8	8	2	2	6
Switch Phase					
Minimum Initial (s)	10.0	10.0	10.0	10.0	10.0
Minimum Split (s)	25.5	25.5	25.2	25.2	25.2
Total Split (s)	25.5	25.5	44.5	44.5	44.5
Total Split (%)	36.4%	36.4%	63.6%	63.6%	63.6%
Maximum Green (s)	20.0	20.0	39.3	39.3	39.3
Yellow Time (s)	3.3	3.3	3.3	3.3	3.3
All-Red Time (s)	2.2	2.2	1.9	1.9	1.9
Lost Time Adjust (s)	0.0	0.0	0.0	0.0	0.0
Total Lost Time (s)	5.5	5.5	5.2	5.2	5.2
Lead/Lag					
Lead-Lag Optimize?					
Vehicle Extension (s)	3.0	3.0	3.0	3.0	3.0
Recall Mode	Max	Max	C-Max	C-Max	C-Max
Walk Time (s)	11.0	11.0	15.0	15.0	15.0
Flash Dont Walk (s)	9.0	9.0	5.0	5.0	5.0
Pedestrian Calls (#/hr)	15	15	50	50	35
Act Effct Green (s)	20.0	20.0	39.3	39.3	39.3
Actuated g/C Ratio	0.29	0.29	0.56	0.56	0.56
v/c Ratio	1.06	0.36	0.11	0.37	0.65
Control Delay	86.7	5.5	8.4	9.9	14.2
Queue Delay	0.0	0.0	0.0	0.0	0.0
Total Delay	86.7	5.5	8.4	9.9	14.2
LOS	F	A	A	A	B
Approach Delay	64.3			9.8	14.2
Approach LOS	E			A	B
Queue Length 50th (m)	~75.2	0.0	1.7	24.2	49.1
Queue Length 95th (m)	#127.8	13.1	5.4	40.2	81.2
Internal Link Dist (m)	302.1			65.0	206.0
Turn Bay Length (m)		75.0	25.0		
Base Capacity (vph)	479	542	293	979	956
Starvation Cap Reductn	0	0	0	0	0
Spillback Cap Reductn	0	0	0	0	0
Storage Cap Reductn	0	0	0	0	0
Reduced v/c Ratio	1.06	0.36	0.11	0.37	0.65

Intersection Summary
 Cycle Length: 70
 Actuated Cycle Length: 70
 Offset: 39 (56%), Referenced to phase 2:NBT and 6:SBT, Start of Green
 Natural Cycle: 60

Lanes, Volumes, Timings
6: Booth & Raymond

Future Total 2030PM Peak Hour
18 Louisa Street

Control Type: Actuated-Coordinated
 Maximum v/c Ratio: 1.06
 Intersection Signal Delay: 33.6
 Intersection LOS: C
 Intersection Capacity Utilization 80.0%
 ICU Level of Service D
 Analysis Period (min) 15
 ~ Volume exceeds capacity, queue is theoretically infinite.
 Queue shown is maximum after two cycles.
 # 95th percentile volume exceeds capacity, queue may be longer.
 Queue shown is maximum after two cycles.

