

KANATA-SUD ELEMENTARY SCHOOL TRANSPORTATION IMPACT ASSESSMENT STRATEGY REPORT

JUNE 10, 2022

DRAFT





KANATA-SUD ELEMENTARY SCHOOL TRANSPORTATION IMPACT ASSESSMENT STRATEGY REPORT

STRATEGY REPORT
DRAFT

PROJECT NO.: OUR REF. NO. 219-00014-00
CLIENT REF:
DATE: JUNE 10, 2022

WSP
SUITE 300
2611 QUEENSVIEW DRIVE
OTTAWA, ON, CANADA K2B 8K2

T: +1 613 829-2800
F: +1 613 829-8299
WSP.COM



TABLE OF CONTENTS

1	SCREENING	1
2	SCOPING.....	2
2.1	Screening Form	2
2.2	Description of Proposed Development	2
2.3	Existing Conditions.....	3
2.3.1	Roadways	3
2.3.2	Intersections	3
2.3.3	Driveways	4
2.3.4	Pedestrian and Cycling Facilities	5
2.3.5	Transit Facilities	5
2.3.6	Area Traffic Management Measures.....	6
2.3.7	Peak Hour Travel Demands	6
2.3.8	Five-year Collision History	9
2.4	Planned Conditions.....	9
2.4.1	Changes to the Study Area Transportation Network.....	9
2.4.2	Other Study Area Developments.....	10
2.5	Study Area and Time Period	12
2.6	Horizon Years	13
2.7	Exemptions Review.....	13
3	FORECASTING	1
3.1	Development Generated Traffic	1
3.1.1	Trip Generation	1
3.1.2	Trip Distribution and Assignment	4
3.2	Background Network Traffic	6
3.2.1	Changes to the Background Transportation Network	6
3.2.2	General Background Growth Rates	6
3.2.3	Other Area Developments	6
3.3	Demand Rationalization.....	10
3.3.1	Description of Capacity Issues	10
3.3.2	Adjustment to Development Generated Travel Demands	10
3.3.3	Adjustments to Background Network Travel Demands	10



4	STRATEGY	13
4.1	Development Design	13
4.1.1	Design for Sustainable Modes.....	13
4.1.2	Circulation and Site Access	13
4.2	Parking	14
4.2.1	Parking Supply	14
4.3	Boundary Streets Design	15
4.3.1	Mobility.....	15
4.3.2	Road Safety	16
4.4	Access Intersections Design	17
4.4.1	Location and Design of Access	17
4.4.2	Intersection Control	18
4.4.3	Intersection Design	19
4.5	Transportation Demand Management.....	19
4.5.1	Context for TDM	19
4.5.2	Need and Opportunity	19
4.5.3	TDM Program	19
4.6	Neighbourhood Traffic Management	20
4.6.1	Adjacent Neighbourhoods	20
4.7	Transit.....	20
4.8	Review of Network Concept	20
4.9	Intersection Design	20
4.9.1	Intersection Control	20
4.9.2	Intersection Design	21
4.10	Summary of Improvements Indicated and Modification Options.....	33

TABLES

TABLE 1-1. TRANSPORTATION IMPACT ASSESSMENT (TIA) SCREENING TRIGGERS	1
TABLE 2-1. DESCRIPTION OF STUDY AREA INTERSECTIONS.....	3
TABLE 2-2. PEAK HOUR TRIPS BY PRIMARY TRAVEL MODE – TRANS KANATA/STITTSVILLE	6
TABLE 2-3. TRAFFIC DATA DATES AND SOURCES ..	7
TABLE 2-4. FIVE-YEAR COLLISION HISTORY SUMMARY (2015-2019).....	9
TABLE 2-5. EXEMPTIONS SUMMARY.....	13
TABLE 3-1: PROPOSED SCHOOL SITE PERSON TRIP GENERATION AND MODE SHARE ...	2
TABLE 3-2: TOTAL SITE VEHICLE TRIP GENERATION	3
TABLE 4-1: SWEEP PATH ASSESSMENT	13
TABLE 4-2: MINIMUM ZONING BY-LAW REQUIREMENTS FOR PARKING AND PROPOSED DEVELOPMENT PARKING SUPPLY	15
TABLE 4-3: SEGMENT MMLOS ALONG COPE DRIVE BETWEEN DAGENHAM STREET AND ROBERT GRANT AVENUE.....	16
TABLE 4-4: SEGMENT MMLOS ALONG DAGENHAM STREET BETWEEN BOBOLINK RIDGE AND COPE DRIVE.....	ERROR!
	BOOKMARK NOT DEFINED.
TABLE 4-5: ACCESS INTERSECTION DESIGN ELEMENTS	17
TABLE 4-6: OTM BOOK 12 SIGNAL WARRANT JUSTIFICATION 7 - PROPOSED SCHOOL.....	18
TABLE 4-7: SUMMARY OF INTERSECTION MULTI-MODAL LEVEL OF SERVICE (MMLOS) ANALYSIS – ROBERT GRANT AVENUE / FERNBANK ROAD	21
TABLE 4-8: CITY OF OTTAWA MMLOS GUIDELINES, LOS CRITERIA – SIGNALIZED INTERSECTIONS.....	22
TABLE 4-9: HIGHWAY CAPACITY MANUAL 2010, LOS CRITERIA – ALL-WAY STOP CONTROL INTERSECTIONS.....	22

TABLE 4-10: SUMMARY OF TRAFFIC OPERATIONS ANALYSIS – EXISTING CONDITIONS (2022).....	23
TABLE 4-11: SUMMARY OF TRAFFIC OPERATIONS ANALYSIS – FUTURE BACKGROUND (2023).....	24
TABLE 4-12: SUMMARY OF TRAFFIC OPERATIONS ANALYSIS – FUTURE BACKGROUND (2028).....	26
TABLE 4-13: SUMMARY OF TRAFFIC OPERATIONS ANALYSIS – FUTURE TOTAL (2023)	28
TABLE 4-14: SUMMARY OF TRAFFIC OPERATIONS ANALYSIS – FUTURE TOTAL (2028)	30

FIGURES

FIGURE 2-1. SITE AREA CONTEXT	2
FIGURE 2-2: EXISTING CYCLING FACILITIES (SOURCE: GEOOTTAWA).....	5
FIGURE 2-3: OC TRANSPO BUS STOPS AND ROUTES (SOURCE: OC TRANSPO WEBSITE)	6
FIGURE 2-4. EXISTING PEAK HOUR TRAFFIC VOLUMES	8
FIGURE 2-5: PLANNED ROADWAY NETWORK (SOURCE: FERNBANK COMMUNITY DESIGN PLAN (JULY 2006))	10
FIGURE 2-6: STUDY AREA.....	12
FIGURE 3-1: DEVELOPMENT GENERATED AUTO TRIPS	5
FIGURE 3-2: 2023 BACKGROUND TRAFFIC VOLUMES	8
FIGURE 3-3: 2028 BACKGROUND TRAFFIC VOLUMES	9
FIGURE 3-4: 2023 TOTAL TRAFFIC VOLUMES	11
FIGURE 3-5: 2028 TOTAL TRAFFIC VOLUMES	12

APPENDICES

A	SCREENING FORM
B	DRAFT SITE PLAN
C	TRANS O-D SURVEY



D	COPE DRIVE CROSS-SECTION
E	RELATED TIA EXCERPTS
F	TDM CHECKLISTS
G	AUTOTURN SWEPT PATHS
H	MMLOS SHEETS
I	SYNCHRO AND SIDRA RESULTS

1 SCREENING

This Transportation Impact Assessment (TIA) has been prepared to support the Site Plan Control application for the development at located at the northeast corner of Cope Drive and Dagenham Street municipally addressed as 755 Cope Drive in Ottawa. The TIA follows the City of Ottawa (the City) TIA Guidelines (2017) which include up to five steps:

- 1 Screening
- 2 Scoping
- 3 Forecasting
- 4 Analysis
- 5 TIA Submission

The Screening Step determines the need to continue with a Transportation Impact Assessment (TIA) Study. The development is assessed against three triggers: trip generation, location, and safety to identify the next step of the study. If one or more of the triggers is satisfied, the Scoping Step must be completed. If none of the triggers are satisfied, the TIA is deemed complete. If one or more triggers are satisfied, specific TIA components are required to be carried out depending on the combination of triggers (**Table 1-1**) that have been satisfied.

The proposed development at 755 Cope Drive **satisfies the Trip Generation and Location triggers** indicating that, as part of Steps Two through Five of the TIA process, the Design Review and Network Impact components should be completed. For reference, the completed Screening Form is provided in **Appendix A**.

Table 1-1. Transportation Impact Assessment (TIA) Screening Triggers

Next Step of the TIA Process	TIA TRIGGERS SATISFIED		
	Trip Generation	Location	Safety
<i>Design Review and Network Impact</i>	Yes	Yes	No

2 SCOPING

2.1 SCREENING FORM

The completed Screening Form is provided in **Appendix A**.

2.2 DESCRIPTION OF PROPOSED DEVELOPMENT

The Conseil des écoles publiques de l'Est Ontario (CEPEO) proposes to build a new elementary school located on the north side of Cope Drive and east of Dagenham Street on the property municipally addressed as 755 Cope Drive in Ottawa. The subject site is currently undeveloped greenfield with an area of approximately 2.88 hectares (28,889 m²) and zoned as Minor Institutional Zone, Sub-zone B (I1B) and Residential First Density, Sub-zone Z (R1Z). As per the I1B zone, a school and a daycare are permitted uses. The subject site is bordered by Cope Drive along the south side, Dagenham Street on the west side, and low-density residential dwellings on both north and east sides. Residential developments are planned south of the subject site, while a community park is planned to the west of the site. The future Ottawa-Carleton District School Board (OCDSB) Stittsville High School, which is planned to open in 2022, will be located southeast of the subject development site at 700 Cope Drive.

The proposed school will include a two-storey building, with a Gross Floor Area (GFA) of approximately 3,803 m², providing capacity for 800 students and consisting of one (1) library, one (1) gymnasium, one (1) multi-purpose room, 12 portable classrooms, and 20 classrooms among which five (5) classrooms will be for daycare use. The most up-to-date draft site plan (December 1, 2021) is attached as **Appendix B**. The proposed vehicle accesses include:

- a passenger vehicle access from Dagenham Street to the 60-space surface parking lot
- an access laneway off Cope Drive for delivery vehicles
- pick-up/drop-off laybys along the north side of Cope Drive and east side of Dagenham Street

Forty-eight parking spaces will be provided for bicycles within the subject site. **Figure 2-1** illustrates the Study Area Context. The development will be built as a single phase with an estimated date of completion in 2023.




Figure 2-1. Site Area Context

2.3 EXISTING CONDITIONS

2.3.1 ROADWAYS

The existing roadways in proximity to the subject development site that will be considered in the TIA include the following. The road classification for City of Ottawa roadways is defined in the City of Ottawa Official Plan, 2021, Volume 1, Section 7, Annex 1 Road Classifications and Rights-of-Way.

Robert Grant Avenue is an urban municipal arterial roadway running on a north-south alignment between Fernbank Road and Abbott Street E. Robert Grant Avenue currently features an undivided two-lane cross-section with wide buffer and sidewalk on both sides. The road right-of-way is approximately 44.5m and the posted speed limit is 60 km/h.

Abbott Street E. is identified as a city-owned major collector road running on an east-west alignment between Terry Fox Drive and Stittsville Main Street with a posted speed limit of 50 km/h. It is an undivided two-lane collector road with sidewalk on the north side and on-street bike lanes on both sides.

Bobolink Ridge is identified as an east-west local road between Goldhawk Drive and Asturcon Street with a posted speed limit of 40 km/h.


Cope Drive is designated as a city-owned major collector road on the section west of Terry Fox Drive. Cope Drive runs on an east-west alignment with a two-lane cross-section and currently terminates at Goldhawk Drive on the west end. The speed limit is unposted and assumed to be 50 km/h.

Fernbank Road is a city-owned arterial road currently remains with a two-lane rural arterial cross-section and paved shoulders on both sides. The section of Fernbank Road designated as arterial road runs east-west between Eagleson Road and Stittsville Main Street with a posted speed limit of 60 km/h.

2.3.2 INTERSECTIONS

The TIA will assess four (4) intersections as described in Table 2-1. The unconstructed intersection of Cope Drive and Dagenham Street is not described in Table 2-1 but will be assessed in the TIA.

Table 2-1. Description of Study Area Intersections

INTERSECTION (DESCRIPTION)	LANE CONFIGURATION
<p>Robert Grant Avenue @ Abbott Street E.</p> <ul style="list-style-type: none"> - Currently a three-leg roundabout with one travel lane for each direction - Level 2 Type D pedestrian crossover (PXO) installed over the south and west legs, and crosswalk over the east leg 	

INTERSECTION (DESCRIPTION)

LANE CONFIGURATION

Robert Grant Avenue @ Bobolink Ridge

- A four-leg roundabout with one travel lane for each direction
- Level 2 Type D PXO over each leg




Robert Grant Avenue @ Cope Drive

- A four-leg roundabout with one travel lane for each direction
- Level 2 Type D PXO over each leg



Robert Grant Avenue @ Fernbank Road

- Signalized T-intersection
- One left-turn lane and one right-turn lane for southbound direction
- One left turn lane and one through lane for eastbound direction
- One through lane and one right-turn lane for westbound direction
- Crosswalks on all approaches with bi-directional cross-ride on the north approach



2.3.3 DRIVEWAYS

The area within 200m of the subject development site is under construction, thus there are no existing active driveways nearby.

There will be residential driveways on the west side of Dagenham Street, south side of Cope Drive in vicinity of the subject site, two sides on Finsbury Avenue and Bobolink Ridge. The future OCDSB Stittsville High School located at 700 Cope Drive will have a two-way access and a one-way access from Cope Drive.

2.3.4 PEDESTRIAN AND CYCLING FACILITIES



Pathways and unidirectional cycle tracks are in place along both sides of Robert Grant Avenue, and the Trans Canada Trail runs along the south side of Abbott Street E. There are existing paved shoulders on both sides of Fernbank Road.

Cope Drive will include a MUP on the north side and a sidewalk on the south side based on the OCDSB Stittsville High School (700 Cope Drive) Traffic Plans approved on August 28, 2020, which is attached as **Appendix D**. **Figure 2-2** illustrates the existing cycling facilities in the vicinity of the subject development site.

Figure 2-2: Existing Cycling Facilities
(Source: GeoOttawa)

2.3.5 TRANSIT FACILITIES

OC Transpo Route 167 and Route 252 provide transit service along Robert Grant Avenue and Cope Drive.

- Route 167 is a Local Route running between Terry Fox and Cope Drive and providing service only on weekdays with a 30-minute frequency during weekday peak hours and 60-minute frequency during off-peak hours.
- Route 252 is a Connexion Route providing connection to the O-Train via Tunney's Pasture Station. Route 252 operates during peak hours on weekdays only at a 30-min frequency.

The bus stop closest to the subject development site is Stop #5527 located approximately 350m from the development site at the southeast corner of Robert Grant Avenue and Cope Drive servicing Route 167 and Route 252.

Figure 2-3 highlights the OC Transpo bus routes and bus stops on adjacent roadways in proximity of the proposed development site.




Figure 2-3: OC Transpo Bus Stops and Routes (Source: OC Transpo Website)

2.3.6 AREA TRAFFIC MANAGEMENT MEASURES

The subject site is within a subdivision area currently under construction. There are no existing traffic management measures being implemented in proximity of the subject site.

2.3.7 PEAK HOUR TRAVEL DEMANDS

The TRANS Committee was established to co-ordinate transportation planning efforts among various planning agencies located within the National Capital Region. The proposed development is located in Kanata/Stittsville. The complete TRANS O-D results (including a map of the district area) is provided in **Appendix C**. The most recent Origin-Destination (O-D) survey was completed by TRANS in the Fall of 2011. The TRANS trip data for South Nepean is summarized in **Table 2-2**.

Table 2-2. Peak Hour Trips by Primary Travel Mode – TRANS Kanata/Stittsville

TRAVEL MODE	AM PEAK PERIOD (6:30 A.M. – 8:59 A.M.)			PM PEAK PERIOD (3:30 P.M. – 5:59 P.M.)		
	FROM DISTRICT	TO DISTRICT	WITHIN DISTRICT	FROM DISTRICT	TO DISTRICT	WITHIN DISTRICT
Auto-Driver	59%	74%	45%	73%	61%	57%
Auto-Passenger	9%	7%	17%	17%	15%	23%
Transit	24%	8%	4%	7%	21%	2%
Bicycle	0%	1%	1%	0%	0%	1%
Walk	0%	0%	19%	0%	0%	12%
Other	7%	10%	15%	3%	3%	6%

TRAVEL MODE	AM PEAK PERIOD (6:30 A.M. – 8:59 A.M.)			PM PEAK PERIOD (3:30 P.M. – 5:59 P.M.)		
	FROM DISTRICT	TO DISTRICT	WITHIN DISTRICT	FROM DISTRICT	TO DISTRICT	WITHIN DISTRICT
Total Vehicles	25,970	15,660	30,350	18,960	28,920	37,470

Source: TRANS 2011 O-D Survey Report, Kanata/Stittsville

Reviewing the Trans 2011 O-D Survey, a majority of trips use personal vehicles as the main source of transport to and from the district. During both AM and PM peak hour periods, auto-driver and auto-passenger modes account for between 68% to 90% of the total vehicles that are travelling to and from the Kanata/Stittsville district. The remaining 10% to 22% are split between transit, bicycle, walk, or other unindicated modes of transportation.


Within the district, travel modes are more diversified. Although auto trips still represent the majority (62% in AM peak, 80% in PM peak), more people tend to choose other modes especially by walking.

The existing peak hour turning movement counts of the intersections within the study area are illustrated in Figure 2-4. These were obtained from other approved TIAs for adjacent developments. The date and source of traffic counts are summarized in Table 2-3 and the relevant pages from other TIAs are included in **Appendix E**.

Table 2-3. Traffic Data Dates and Sources

INTERSECTION	DATE	SOURCE
Robert Grant Ave / Abbott St E	June 2019	700 Cope Drive TIA
Robert Grant Ave / Bobolink Ridge	March 2021	360 Bobolink Ridge TIA
Robert Grant Ave / Cope Dr	June 2019	700 Cope Drive TIA
Robert Grant Ave / Fernbank Rd	August 2018	City of Ottawa

Figure 2-4. Existing Peak Hour Traffic Volumes



2.3.8 FIVE-YEAR COLLISION HISTORY

The boundary road for the proposed development is Cope Drive and Dagenham Street, which either have not been constructed or have only been opened to public traffic for a short period.

The latest past five years (January 1, 2015 through December 31, 2019) collision history were reviewed. The collision history was obtained from the City of Ottawa Open Data website and provides yearly total collisions by locations. **Table 2-4** summarizes the five-year collision history for Robert Grant Avenue.

More detailed five-year collision data will be required to identify if any collision pattern and/or safety concern exists. A more thorough collision review will be conducted upon the request from the City.

Table 2-4. Five-Year Collision History Summary (2015-2019)

Location		Pedestrian Collision	Cyclists Collision	Total Collisions by Year				
				2015	2016	2017	2018	2019
Segment:	Robert Grant Avenue [Fernbank Road – Abbott Street E.]	0	0	0	0	0	0	0
Intersection:	Robert Grant Avenue @ Fernbank Road	0	0	0	1	0	0	0
Intersection:	Robert Grant Avenue @ Bobolink Ridge	0	1	0	0	0	1	2
Intersection:	Robert Grant Avenue @ Abbott Street E.	0	0	0	0	1	0	1
Five-year Total Collisions				6				

2.4 PLANNED CONDITIONS

2.4.1 CHANGES TO THE STUDY AREA TRANSPORTATION NETWORK

The City of Ottawa Official Plan, Transportation Master Plan (TMP) (2013), and the Fernbank Community Design Plan (July 2006) were reviewed to identify potential future roadway upgrades in the vicinity of the subject development site.

Robert Grant Avenue is identified as a future Transit Priority Corridor with isolated measures and ultimately a BRT route with at-grade crossings based on the Rapid Transit and Transit Priority Network – 2031 Affordable Network and 2031 Network Concept Network (Map 5 and Map 4 of TMP). Park and Ride facilities are proposed near the intersection of Abbott Street E. and Robert Grant Avenue and the intersection of Fernbank Road and Robert Grant Avenue. A concept design was completed for Robert Grant Avenue as part of the West Transitway Connections EA study. The section of Robert Grant Avenue between Fernbank Road and Abbott Street East will ultimately be widened to four lanes and include dedicated bus lanes running in the middle of the road. Robert Grant Avenue currently terminates at Abbott Street E and will be extended northwards to connect to Hazeldean Road. The extension was planned to be part of Phase 2 (2022 – 2025) network improvements per the TMP, however the timeline has been postponed to beyond 2030 due to funding limitations. The City and area developers have worked collaboratively to explore alternative funding solutions and conducted a Development Charges Amendment Background Study in 2019. **Figure 2-5** shows the planned area transportation network.

Fernbank Road is identified on the Rapid Transit and Transit Priority Network – 2031 Network Concept Network (Map 4 of the TMP) as a future Transit Priority Corridor with isolated measures. Widening of Fernbank Road between Stittsville Main Street and Terry Fox Drive is anticipated in the future per the Road Network – 2031 Network Concept (Map 10 of TMP).

Cope Drive as an area collector road will be extended westwards to eventually connect to Shea Road. The extension is expected to be completed as part of Claridge Richcraft Tamarack (CRT) Westwood Phase 1 and Phase 2 subdivision.

There are no other major changes expected to the study area transportation network.




Figure 2-5: Planned Roadway Network (Source: Fernbank Community Design Plan (July 2006))

2.4.2 OTHER STUDY AREA DEVELOPMENTS

The subject school site is located within a new subdivision area where many new developments are occurring. Based on a search through the City of Ottawa’s Development Application Search tool, developments that will likely occur within the proposed horizon years of the subject development and could have direct influences on the study area are noted below:

- 620 Bobolink Ridge (D07-12-21-0107): An ongoing Site Plan Control application for development of seven stacked townhouse blocks each containing 12 units for a total of 84 units. The development forms part of the Claridge Richcraft Tamarack (CRT) Westwood subdivision (CRT Phase 1 &2). Build out of the development is expected in 2023.
- 360 Bobolink Ridge (App# D07-12-21-0163): A Site Plan Control application for four six-storey apartment buildings consisting of 354 total rental units and a two-storey building providing office space, ground-floor

commercial units and tenant amenity. Full built-out horizon is anticipated to be 2024. The supporting TIA (August 30, 2021) was prepared by J.L Richards.

- 5725 Fernbank Road, CRT Phase 3 (App# D07-16-20-0033): A Zoning By-law Amendment and Subdivision application for 600 residential units with mix of detached and townhome dwellings and a park. CRT Phase 3 is anticipated to be constructed in a single phase with full occupancy by end of 2025. The supporting TIA (April 8, 2021) was prepared by IBI Group.
- 700 Cope Drive (App# D07-12-19-0144): A Site Plan Control application for the development of a four-storey OCDSB secondary school with approximately 8,415 m² area and a capacity to accommodate 1,460 students at full built-out anticipated in 2024. The development proposes two accesses from Cope Drive. The supporting TIA (December 4, 2019) was prepared by Parsons.
- 60 Defence Street (App# D07-12-21-0120): A Site Plan Control application for an elementary school and daycare with capacity for 507 students and 36 staff. Anticipated built-out year is 2023. The supporting TIA (August 2021) was prepared by Dillon Consulting.
- 5786 Fernbank Road, CRT Phase 1&2 (App# D07-16-11-0003): A Subdivision application for low density residential, minimal amount of medium density residential, open space, parks, institutional, and stormwater management pond. The land being subdivided is the parent property of the subject development site. The supporting Transportation Study (January 28, 2021) was prepared by IBI Group.
- 360 Haliburton Heights, Fernbank Crossing, Block 135, Phase 3: A Subdivision application for 58 units of townhomes. Full built-out horizon was anticipated to be 2021. The supporting TIA (March 2019) was prepared by Novatech.

2.5 STUDY AREA AND TIME PERIOD

The limits for the Transportation Impact Assessment (TIA) study area and study intersections are shown in **Figure 2-6**. The boundary roads Cope Drive and Dagenham Street will be reviewed. Three roundabouts and two intersections will be analyzed including:

- Robert Grant Avenue and Abbott Street E.
- Robert Grant Avenue and Bobolink Ridge
- Robert Grant Avenue and Cope Drive
- Robert Grant Avenue and Fernbank Road
- Cope Drive and Dagenham Street



Figure 2-6: Study Area

It is noted that the afternoon peak of elementary schools is usually earlier than the regular PM peak hour of the roadway network, but the school's morning peak will generally align with the AM peak hour of the roadway traffic. The study time periods identified for the traffic analysis are weekday AM and PM peak hours as these represent the time periods with the highest traffic volumes that would govern the design of study area roadways and intersections.

CEPEO has indicated that operation hours of the elementary school will be from 7:30 AM to 4:00 PM, and the daycare will operate between 6:00 AM to 5:00 PM. The start and end time of the school and daycare service generally align with the peak hours of the adjacent street traffic, but it is noted that the provided school operating hours may include before and after care times and may not align with concentrated trip arrivals and departures

around bell times. The identification of the alignment between commuter peak hours and school operations are assessed in more detail as part of the Forecasting analysis below.

2.6 HORIZON YEARS

The proposed facility is expected to be completed in one phase with a target build-out year of 2023. In accordance with the City of Ottawa TIA Guidelines (2017), the following horizons will be considered for analysis.

- 2023, which represents the anticipated buildout horizon,
- 2028, which represents the buildout year plus five years.

2.7 EXEMPTIONS REVIEW

Based on the review of the development and network conditions, the following elements shown in **Table 2-5** qualify for an exemption from this Transportation Impact Assessment.

Table 2-5. Exemptions Summary

MODULE	ELEMENT	EXEMPTIONS
DESIGN REVIEW COMPONENT		
4.1 Development Design	4.1.2 Circulation and Access	Not Exempted. This element is only required for site plans.
	4.1.3 New Street Networks	Exempted This element is only required for plans of subdivision.
4.2 Parking	4.2.1 Parking Supply	Not Exempted. This element is required for site plans.
	4.2.2 Spillover Parking	Exempted This element is only required for site plans where parking supply is 15% below unconstrained demand.
NETWORK IMPACT COMPONENT		
4.5 Transportation Demand Management	All Elements	Not Exempted Not required for site plans expected to have fewer than 60 employees and/or students on location at any given time.
4.6 Neighborhood Traffic Management	4.6.1 Adjacent Neighbourhoods	Not Exempted Required when the development relies on local or collector access and total volumes exceed ATM capacity threshold.
4.8 Network Concept		Exempted Required when proposed development generates more than 200 person-trips during the peak hour in excess of the equivalent volume permitted by established zoning.

Based on the above, the TIA report will include the following modules:

- Module 4.1: Development Design
- Module 4.2: Parking
- Module 4.3: Boundary Streets
- Module 4.4: Access Design
- Module 4.5: Transportation Demand Management
- Module 4.6: Neighbourhood Traffic Management
- Module 4.7: Transit
- Module 4.9: Intersection Design

DRAFT

3 FORECASTING

3.1 DEVELOPMENT GENERATED TRAFFIC

3.1.1 TRIP GENERATION

The proposed development consists of two primary trip generator land uses which are elementary school and daycare services. Trips generated by the elementary school and daycare service have been estimated based on the most up-to-date information provided by the school board. The elementary school is anticipated to provide capacity for 751 students, while the daycare service will provide capacity for 49 children. A total of 51 staff, including teachers, custodians, and office staff, are expected to work for the school and daycare. There is a plan for a future addition to the school providing extra capacity for 200 students, but this addition was not included in this TIA study as it is not part of the current Site Plan Application and no timeline has been defined.

SCHOOL PERSON TRIP GENERATION (STUDENTS)

Trip generation for the student population at the proposed school has been developed using first principles analysis based on information provided by CEPEO. The 2020 TRANS Trip Generation Manual does include mode share assumptions for elementary and high schools but recommends that mode shares be developed on a site-specific basis if additional information is available from the school or school board. Information from CEPEO indicates that approximately 85% of the student population is anticipated to arrive by school bus, with the remainder by other modes. These remaining trips have been split as 10% by auto and 5% by active transportation modes, recognizing a portion of the student population will be within walking distance of the school.

SCHOOL PERSON TRIP GENERATION (STAFF)

Staff trip generation to the proposed school is based on the anticipated 51 staff. The Mode share for these trips has been based on the Employment Generator Mode Shares from the 2020 TRANS Trip Generation Manual for the South Nepean District.

DAYCARE PERSON TRIP GENERATION

Daycare person Trip Generation is based on the capacity of 49 children provided by CEPEO. A 100% auto passenger mode share has been adopted for daycare children, assuming that all children will be dropped off by parents.

TOTAL PERSON TRIP GENERATION AND MODE SHARE

Table 3-1 provides a summary of the person trip generation for all of the uses on the site.

Table 3-1: Proposed School Site Person Trip Generation and Mode Share

	AUTO DRIVER	AUTO PASSENGER	SCHOOL BUS	PUBLIC TRANSIT	WALKING & CYCLING
	Mode Shares				
School Students	0%	10%	85%	0%	5%
Staff	80%	10%	0%	5%	5%
Daycare Children	0%	100%	0%	0%	0%
	Person Trips				
School Students	0	75	638	0	38
Staff	41	5	0	3	3
Daycare Children	0	49	0	0	0
TOTAL PERSON TRIPS	41	129	638	3	41

CONVERSION TO VEHICLE TRIPS

The person trip generation above represents the student and staff trip generation in terms of arrivals to the school site in the morning and departures in the afternoon but do not reflect the vehicle volumes added to the surrounding road network. The conversion of the person trips to vehicle trips is based on the following:

- Auto passenger trips for student and daycare drop-offs represent one auto arrival and one auto departure from the site during the AM and PM peak hours. Vehicle trips were calculated from the auto passenger person trips assuming a vehicle occupancy of 1.2, reflecting some families who will drop off multiple children in one trip.
- Auto driver trips by staff represent one vehicle arrival in the morning and one departure in the afternoon. Staff auto trips have been calculated based on a vehicle occupancy of 1.0. No additional vehicle trips have been added to reflect staff auto passenger trips as it is anticipated these will be combined with staff auto driver arrivals (carpooling).
- School bus capacity ranges from 48-72 students based on 2-3 students per seat. School bus volumes have been estimated based on an average of 60 students per bus.

PEAK HOUR DISTRIBUTION

The person trip generation above is based on total trips made by the students and staff to and from the site. CEPEO has indicated that operation hours of the elementary school will be from 7:30 AM to 4:00 PM, and the daycare will operate between 6:00 AM to 5:00 PM. It is anticipated that the school hours provided represent before and after care in addition to classes; most CEPEO schools in Ottawa operate with morning and afternoon bell times at approximately 8:30-9:00 AM and 3:00 PM. While school student arrivals will be concentrated just before and after the opening and closing bells, trips by staff, before and after care students and daycare children may be more distributed. Given the commuter peak hours of 7:15-8:15 AM and 4:45-5:45 PM from the provided traffic count, the

proportions of the site generated vehicle trips falling within the commuter peak hours have been estimated based on the following:

- 80% of auto trips arriving during the AM peak hour, reflecting a portion of the staff arrivals, before school care and daycare drop-offs that arrive earlier in the morning.
- 50% of auto trips departing the school during the PM peak hour, reflecting a wider distribution of parent pickup between the end of the school day and end of daycare and after school programs and a wider distribution in staff departure times at the end of the day.
- 100% of school bus arrivals during the AM peak hour, corresponding with a concentration in drop-offs just before the morning bell.
- 0% of bus departures during the PM peak hour, reflecting that bus departures will occur at the end of the school day before the commuter PM peak hour.

DAYCARE DIVERTED TRIP ESTIMATION

In many cases, school and daycare drop-offs by parents will be planned as part of a parent’s commute; these diverted trips will be reflected in the background traffic volumes on the road network but will divert to the school before continuing on their original path. The ITE Trip Generation Manual 3rd Edition indicates an average diverted trip proportion of 56% specific to daycare centres; this proportion has been applied as diverted trips in the site generated traffic. The same handbook does not indicate a diverted trip proportion for the elementary school land use; to be conservative, this analysis is based on all auto trips generated by the school to be primary trips added to the road network.

TOTAL VEHICLE TRIPS

The total peak hour vehicle trips generated by the proposed school are summarized in Table 3-2.

Table 3-2: Total Site Vehicle Trip Generation

	AM PEAK HOUR		PM PEAK HOUR	
	IN	OUT	IN	OUT
Auto Trips	115	83	52	72
School Buses	11	11	0	0
Diverted Auto Trips (included in auto total above)	18	18	11	11

3.1.2 TRIP DISTRIBUTION AND ASSIGNMENT

The overall trip distribution of the site generated trips has been adopted from the TIA for the 700 Cope Road TIA immediately to the east of the subject site developed by Parsons, this trip generation is based on the TRANS 2011 travel survey distribution and is estimated at 45% of traffic to/from the north, 25% of traffic to/from the east, and 30% of traffic to/from the west. While the catchment of the proposed school was not provided, the prominence of students on school buses suggests that the catchment area will extend beyond the local neighbourhood, and thus trip distribution based on the TRANS district level distribution is an appropriate estimate. Based on the surrounding road network configuration and existing traffic patterns, the overall distribution has been assigned to the network as follows:

- 45% to/ from the North
 - 25% to/from Iber via Abbot
 - 20% to/from Terry Fox via Abbott
- 25% to/from the East
 - 5% to/from Cope
 - 20% to/from Fernbank
- 30% to/from the West
 - 25% to/from Abbott
 - 5% to/from Fernbank
- Site Access Distribution
 - Inbound trips from Robert Grant NB and Cope Drive WB 100% via Cope WB to Dagenham NB (to align with car drop off area on east side)
 - Inbound trips from north 75% via Cope Drive (to align with car drop off area on east side), 25% via Bobolink Ridge (destined to school parking access).
 - Outbound Trips towards Abbott Street 100% via Bobolink Ridge.
 - Outbound Trips towards Cope / Fernbank 75% via Bobolink Ridge, 25% via Cope Road (reflecting that many parents will continue NB after pickup/drop-off).

The site generated trip distribution is illustrated in Figure 3.1.

Figure 3-1: Development Generated Auto Trips



3.2 BACKGROUND NETWORK TRAFFIC

3.2.1 CHANGES TO THE BACKGROUND TRANSPORTATION NETWORK

The Robert Grant Avenue extension from Abbott Street E. to Palladium Drive was identified as one of the Phase 2 (2022-2025) projects in the City of Ottawa Transportation Master Plan (2013), this project is not part of the City affordable network and is not anticipated until after 2031.

Due to the interests expressed by the area developers in working with the City explore alternative funding solutions, the City conducted a 2019 Development Charges Amendment Background Study and introduced an area specific charge to accelerate improvements in the Stittsville area including the extension of Robert Grant Avenue. In this study, it was assumed that Robert Grant Avenue extension would not be completed by the 2028 horizon.

The existing Cope Drive ends at a cul-de-sac at the location of the future intersection with Angel Heights / Goldhawk Drive. These roads and resulting intersection will be developed as the buildout of CRT Phases 1 and 2 continue. This study is based on the cul-de-sac remaining in place for the 2023 horizon, and the full intersection and connections to CRT phase 2 to the south of Cope Drive being in place by the 2028 horizon.

3.2.2 GENERAL BACKGROUND GROWTH RATES

A 2.0% annual growth in traffic on study area roads was adopted to account for traffic generated by future developments that are not currently under the development application process (Section 2.4.2). The 2.0% increase was consistent with the growth assumptions used in the approved TIA studies prepared supporting the other area developments.

3.2.3 OTHER AREA DEVELOPMENTS

Other study area developments identified in Section 2.4.2 were accounted in the estimation of future background traffic of 2023 and 2028 study horizons. The TIA approved in April 2021 for the development of CRT Phase 3 captured traffic generated by most of the identified area developments, including the following:

- CRT Phase 1&2 (5786 Fernbank Road) and Phase 3 (5725 Fernbank Road)
- Fernbank Crossing Phase 3 Block 129 and Block 135 (*90% of Phase 3 was constructed in 2019 per Stantec's TIA, therefore associated development generated trips will be reflected in existing traffic counts*)
- Fernbank Crossing Phase 4.
- Blackstone Phases 4 – 8
- Development (René's Court) at 1000 Robert Grant Avenue
- New Stittsville High School at 700 Cope Drive

The Fernbank Crossing Phase 3 Block 129 and Block 135 was not explicitly counted in this TIA, but it is noted that 90% of Phase 3 was constructed in 2019 per Stantec's TIA, therefore associated development generated trips will be reflected in existing traffic counts.

It is noted that traffic volumes associated with the residential development at 360 Bobolink Ridge were not considered in the CRT Phase 3 TIA and have also been added to the background development traffic. The CRT Phase 3 TIA also did not include the intersection of Robert Grant Avenue and Abbott Street E, volumes at this intersection were based on the 700 Cope Drive (Stittsville High School) TIA. Volumes at the intersection of Bobolink Ridge and Robert Grant Avenue were based on a review of projected volumes in the 360 Bobolink Ridge TIA balanced to reflect the projected volumes at the adjacent intersections resulting from the projected development volumes in the area.

The proposed Stittsville High school is scheduled to begin classes in 2023, but the other area developments listed above are expected to be built-out either in or after 2023. For the purposes of this study, the 2023 background traffic volumes include the annual 2% background traffic growth and 700 Cope Drive developments only, while the 2028 background volumes consist of both the general annual growth and other developments generated traffic. 2023 background traffic is shown in Figure 3-2, and 2028 background traffic is shown in Figure 3-3.

DRAFT

Figure 3-2: 2023 Background Traffic Volumes





Figure 3-3: 2028 Background Traffic Volumes



3.3 DEMAND RATIONALIZATION

3.3.1 DESCRIPTION OF CAPACITY ISSUES

Total traffic volumes for the 2023 and 2028 study horizons were estimated by:

- Applying a 2% background annual growth to the existing traffic volumes.
- Adding trips generated by the proposed development on top of the general background growth to get 2023 total volumes
- Adding trips generated by other area developments and the proposed development on top of the general background growth to get 2028 total volumes

The estimated 2023 and 2028 total traffic volumes are presented in Figure 3-4 and Figure 3-5. A detailed assessment of intersection and roadway capacities by using Synchro (version 11) for 2023 and 2028 horizons have been carried out in Section 4.

3.3.2 ADJUSTMENT TO DEVELOPMENT GENERATED TRAVEL DEMANDS

The development generated trips are not anticipated to result in new over-capacity movements within the study area, therefore no adjustment to development generated traffic has been proposed yet. A detailed review will be carried out as part of the Strategy/Analysis Report and may include recommended adjustments as needed.

3.3.3 ADJUSTMENTS TO BACKGROUND NETWORK TRAVEL DEMANDS

Adjustments to background network demands have not been proposed since the projected future traffic are not expected to adversely impact the intersections and roadways within the study area. A detailed review will be carried out as part of the Strategy/Analysis stage and may include recommended adjustments as needed.

Figure 3-4: 2023 Total Traffic Volumes





Figure 3-5: 2028 Total Traffic Volumes



4 STRATEGY

4.1 DEVELOPMENT DESIGN

4.1.1 DESIGN FOR SUSTAINABLE MODES

The City of Ottawa’s TDM-Supportive Development Design and Infrastructure Checklist for Non-Residential Developments was completed to assess the opportunity to implement facilities that are supportive of sustainable modes, including cycling, walking and transit. The completed checklist is attached as **Appendix F**.

As indicated in the TDM checklist and shown on the site plan (**Appendix B**), the proposed site accommodates sustainable modes in the following ways:

- 48 dedicated bicycle parking spaces
- Walking distance between site and nearest transit stop is within 400m
- Provision of pedestrian walkways at the vehicle access on Dagenham Street, access laneway on Cope Drive and crossing the drop-off area in the parking lot

It is assumed that upon completion that the intersection of Cope Drive / Dagenham Street will be all-way stop controlled for pedestrian safety and that crosswalks will be provided at all legs.

4.1.2 CIRCULATION AND SITE ACCESS

The proposed school drop-off area, which is situated in the parking lot, is designed to operate with traffic circulation in a counter-clockwise direction. Unidirectional vehicle movements are indicated in the site plan at the west and south sides of the drop-off area and bidirectional vehicle movements are permitted on the east side of the drop-off area to access parking spaces. School staff and parents dropping off and picking up students will primarily utilize the site access and parking area.

Site circulation at the proposed access and drop-off area was assessed using AutoTURN 11 to confirm the suitability of the layout for a variety of design vehicles. The results are provided in Table 4-1 and the AutoTURN swept paths are provided in **Appendix G**.

Table 4-1: Swept Path Assessment

DESIGN VEHICLE	VEHICLE REPRESENTING	FINDINGS
HSU (TAC 2017)	Municipal Services / Waste Removal	<p>Access: The proposed access configuration on Dagenham Street can accommodate the movements of an HSU design vehicle without impacting any built features but will require the vehicle to encroach on the opposing vehicle lane.</p> <p>Circulation: An HSU design vehicle will be able to maneuver to and from the waste containers located at the north-east corner of the drop-off area without conflicting with curbs upon reversing into the drop-off area. Parking spaces will not be impacted.</p>

DESIGN VEHICLE	VEHICLE REPRESENTING	FINDINGS
Aerial Fire (REDG Toronto 2017)	Fire Truck	<p>Access: The proposed access configuration on Dagenham Street can accommodate the movements of a fire truck without impacting any built features but will require the vehicle to encroach on the opposing vehicle lane.</p> <p>Circulation: A fire truck will not be able to maneuver around the drop-off area to access the rear school entrances across from the crosswalk without conflicting with curbs. Vehicle-curb conflict is identified at the south-west corner of the drop-off area. In addition, parking spaces will not be impacted.</p>
2020 Blue Bird Vision (AutoTurn City-Transit)	School Bus	<p>Access: The proposed access configuration on Dagenham Street can accommodate the movements of a school bus without impacting any built features but will require the vehicle to encroach on the opposing vehicle lane.</p> <p>Circulation: A school bus will not be able to maneuver around the drop-off area without conflicting with curbs. Vehicle-curb conflict is identified at the south-west corner of the drop-off area. In addition, parking spaces will not be impacted. School buses will be utilizing the laybys on the north side of Cope Drive and east side of Dagenham Street, but in the event of additional school bus circulation measures in the future, a school bus will not be able to properly circulate around the drop-off area.</p>

Despite the drop-off area primarily being intended to be used by school staff and parents, the overall configuration should consider use by larger vehicles in the event of an emergency or should circulation patterns change in the future due to a potential school expansion and changes to the transportation network. To do so, it is recommended that the site plan be updated such that the radius of the exterior curb at the south-west corner of the drop-off area be increased to accommodate larger vehicles and their wide turning movements.

4.2 PARKING

4.2.1 PARKING SUPPLY

Based on the location of the proposed development, the minimum parking space requirements will be assessed in accordance with the Suburban Area (Area 'C') as part of Schedule 1A to the City of Ottawa's Zoning By-Law 2008-250. The Zoning By-Law requires that a school and daycare in Area 'C' provide a minimum parking space rate of 1.5 per classroom (includes portables) and 2 per 100 sq. m. of gross floor area, respectively. In addition, the Zoning By-Law requires that bicycle parking is provided for a school and daycare at a bicycle parking space rate of 1 per 100 sq. m. of gross floor area and 1 per 250 sq. m. of gross floor area, respectively.

The minimum parking space rates can be found in Section 101 of the Zoning By-Law and off-street motor vehicle parking must be provided for any land use at the rate set out in Table 101. Bicycle parking spaces rates and provisions can be found in Section 111 of the Zoning By-Law and bicycle parking must be provided for the land uses and at the rate set out in Table 111A.

The minimum parking supply requirements for this development compared with the proposed parking supply are highlighted in Table 4-2 below.

Table 4-2: Minimum Zoning By-Law Requirements for Parking and Proposed Development Parking Supply

PARKING TYPE	LAND USE	SIZE	REQUIRED SPACES (ZONING BY-LAW)	PROVIDED SPACES (SITE PLAN)
Auto Parking	School	20 classrooms, 12 portables	48	60
	Daycare	327 GFA	3	
Bicycle Parking	School	4,741 GFA	47	48
	Daycare	327 GFA	1	

Based on the provided number of auto and bicycle parking spaces for the proposed development, the auto parking supply exceeds the minimum requirements of the Zoning By-Law by 9 parking spaces and the bicycle parking supply meets the minimum requirements of the Zoning By-Law. It is noted that the parking rate used for the site plan slightly differs from the Zoning By-Law rate such that the minimum required parking spaces determined within the site plan exceeds that of the Zoning By-Law.

4.3 BOUNDARY STREETS DESIGN

4.3.1 MOBILITY

The City of Ottawa’s Multi-Modal Level of Service (MMLOS) targets consider road classification, adjacent land-use designation, and special policy areas and are intended to evaluate how the proposed school users will be accommodated by the boundary streets bordering the site to the south and west. It is acknowledged that Road Segments as defined in City of Ottawa’s MMLOS Guidelines (2015) refers to a roadway link between signalized intersections. However, in the absence of signalized intersections in proximity to the school, segment analyses have been adapted for Cope Drive and Dagenham Street between unsignalized intersections to evaluate the level of service of the planned multi-modal facilities.

4.3.1.1 COPE DRIVE

The segment of Cope Drive under evaluation is between Dagenham Street and Robert Grant Avenue. Cope Drive borders the school in the south and is a designated collector road. Therefore, the study segment of Cope Drive was evaluated as a collector within 300m of a school with the corresponding LOS targets taken from Exhibit 22 of the MMLOS Guidelines. The segment of Cope Drive being evaluated is the west leg of the intersection with Robert Grant Avenue and is currently under construction. Cope Drive is not a designated truck or transit route and therefore no targets have been assigned in this regard; only PLOS and BLOS have been evaluated for the segment analysis. The segment MMLOS results are summarized in Table 4-3 below and the detailed MMLOS spreadsheets are provided in **Appendix H**.

Table 4-3: Segment MMLOS along Cope Drive between Dagenham Street and Robert Grant Avenue

	PLOS	BLOS
Target	A	C
Cope Dr between Dagenham St and Robert Grant Ave (2022 Existing Conditions)	F	E
Cope Dr between Dagenham St and Robert Grant Ave (2028 Future Background Conditions)	B	B
Cope Dr between Dagenham St and Robert Grant Ave (2028 Horizon Conditions)	B	B

The results of the segment analysis indicate that neither the PLOS nor the BLOS meet the target under existing conditions. This is because Cope Drive is currently under construction and has no pedestrian or bicycle facilities; only 50m of it has been developed at the roundabout. Under the future 2028 plans, the cross-section of Cope Drive will have a 2m sidewalk on the south side and a 3m multi-use pathway with a 3m boulevard on the north side. The provision of the multi-use pathway with a boulevard will ensure a BLOS B which exceeds the target C. The PLOS B recorded on the segment does not meet the target A; for a PLOS A, the width of the south sidewalk would have to be increased from 2m to 3m.

4.3.1.2 DAGENHAM STREET

The segment of Dagenham Street under evaluation is between Bobolink Ridge and Cope Drive. Dagenham Street borders the school in the west and is a local street serving the neighbourhood. Hence, the study segment was evaluated as a local road within 300m of a school with the corresponding LOS targets taken from Exhibit 22 of the MMLOS Guidelines. The segment of Dagenham Street being evaluated is currently under construction; no general traffic uses this road, only construction vehicles. Therefore, no MMLOS evaluation has been carried out for existing conditions.

There are no concept plans available for the Dagenham Street segment as at the time of writing this report. Therefore, to meet the MMLOS targets for a local street within 300m of a school, the 2028 future conditions will require the provision of 3m sidewalks with a minimum of 0.5m boulevard to meet PLOS A; a BLOS B can be met with bicycles operating in mixed traffic if the posted speed limit is 40 km/h or lower.

Like Cope Drive, Dagenham Street is neither a planned transit route nor a truck route; only PLOS and BLOS have been considered for the segment analysis.

4.3.2 ROAD SAFETY

4.3.2.1 COPE DRIVE

No collisions have been documented along Cope Drive between Dagenham Street and Robert Grant Avenue due to the underdeveloped nature of the road within the study area. Therefore, no collision reduction measures have been identified for this section of roadway.

4.3.2.2 DAGENHAM STREET

No collisions have been documented along Dagenham Street between Cope Drive and the proposed site access due to the underdeveloped nature of the road. Therefore, no collision reduction measures have been identified for this section of roadway.

4.4 ACCESS INTERSECTIONS DESIGN

4.4.1 LOCATION AND DESIGN OF ACCESS

There are two access points proposed for this development and are indicated in the site plan (**Appendix B**); one located off of Dagenham Street at the north-west corner of the site (main vehicle access) and the second one located off of Cope Drive at the south-east corner of the site (delivery access). The three-legged vehicle access is proposed as a two-way, full movement access with stop-control on the side approach (access) and free-flow for the north and south approaches along Dagenham Street.

A design compliance check was carried out for the proposed school's main vehicle access on Dagenham Street for a variety of interrelated design elements for driveways following the Transportation Association of Canada's Geometric Design Guidelines for Canadian Roads (2017). The design compliance check is summarized in Table 4-4.

Table 4-4: Access Intersection Design Elements

DESIGN ELEMENTS	MINIMUM REQUIRED	DAGENHAM STREET ACCESS
Access Type	-	Full Movement
One-way vs. Two-way Operation	>750 veh/d or >100 peak hour trips = high volume two-way driveway	>100 peak hour trips Two-way
Entrance Width* (Two-way)	Residential: 2.0m-7.3m Commercial: 7.2m-12.0m Industrial: 9.0m-15.0m 6.0m for a parking lot (City of Ottawa Zoning By-law)	8.0m
Right Turn Radius*	Residential: 3.0m-4.5m Commercial: 4.5m-12.0m Industrial: 9.0m-15.0m	6.0m
Corner Clearance	15m for Local Roads	>15m
Sight Distance (Intersections with Stop Control on Minor Road)	Case B1 – Left Turns from Minor Road = 105m Case B2 – Right Turns from Minor Road = 95m	No obstructions; be advised of parked vehicles on the east side of Dagenham Street. School buses will be parked on-street within curb extensions (bulb-outs) and the additional car drop off area on Dagenham Street adjacent to the site access is meant for short duration stops.
Throat Length	N/A	Located on a local road 18.5m
Angle of Intersection	At or near 90°	Access intersects Dagenham Street at 90°
Proximity to Adjacent Driveways	N/A	No private driveways along the east side of Dagenham Street between Cope Drive and the proposed school access

DESIGN ELEMENTS	MINIMUM REQUIRED	DAGENHAM STREET ACCESS
Pedestrian + Cycling Crossing Considerations	Small curb return radii (must be suitable for design turning vehicle) with narrow driveway to minimize crossing distance	8.0m pedestrian crossing No cycling crossing

*Minimum requirements for institutional developments are the same as commercial developments as per the definition listed in TAC 2017 where the development primarily serves passenger vehicles but occasionally accommodates service trucks.

Overall, the design elements for the site access on Dagenham Street meet the minimum requirements of TAC 2017 to be considered as good design practice.

4.4.2 INTERSECTION CONTROL

Ontario Traffic Manual (OTM) Book 12 (2012) Justification 7 includes two warrants (1 and 2) for signalization with two evaluation criteria (A and B) for each:

- 1A – total volume entering the intersection from all approaches.
- 1B – total volume entering the intersection from the minor approaches only.
- 2A – total volume entering the intersection from the main road only.
- 2B – total volume crossing major road, calculated as the left turns from the minor approaches, pedestrian crossings, highest through volume from one of the minor approaches and 50% of the heavier left turn from the main road if it exceeds 120 vehicles/hr and the opposing traffic exceeds 720 veh/hr.

Signalization can be warranted based on Warrant 1 or 2, but only if both conditions A and B are 100% met.

Based on Section 3.1.1, the site is estimated to generate 115 and 83 auto vehicle trips in and out of the access during the AM Peak Hour, respectively. During the PM Peak Hour, the site is estimated to generate 52 and 72 auto vehicle trips in and out of the access, respectively.

Provided that the school access is considered a T-intersection with one vehicle travel lane in both directions and that it is a future intersection, thresholds are raised for the consideration of traffic signals as a result of using average hourly volumes instead of eight-hour volumes as they are unavailable.

In accordance with OTM Book 12, the site generated volumes listed above are below the minimum requirements for a traffic signal based on Justification 7 – Projected Volumes, as shown in Table 4-5. Therefore, the projected site generated volumes indicate that signalization at the access intersection is not warranted since the volumes fall below the minimum requirements when considering the adjusted volume thresholds for all evaluation criteria.

Table 4-5: OTM Book 12 Signal Warrant Justification 7 - Proposed School

JUSTIFICATION 7	MINIMUM REQUIREMENT	
	FLOW ¹	ADJ. FLOW ²
1A - All Approaches	480	1080
1B - Minor Road	120	270
2A - Major Road	480	1080
2B - Crossing Major Road	50	115
Notes ¹ Base Volume Thresholds are based on a 1-lane major road with free flow conditions. ² Adjusted Volume Thresholds are based on the following requirements in the OTM Warrant Methodology:		

JUSTIFICATION 7	MINIMUM REQUIREMENT	
	FLOW ¹	ADJ. FLOW ²
<ul style="list-style-type: none"> x1.5 for Justification 7, based on a new intersection x1.5 for a T-intersection 		

The proposed school access will be located on a low-volume local road such that stop-control on the minor road (site access) is sufficient.

4.4.3 INTERSECTION DESIGN

According to the City of Ottawa’s MMLOS Guidelines (2015), only signalized intersections are evaluated against the LOS measures for intersections. As such, no formal MMLOS evaluation has been applied to the proposed site access due to its unsignalized traffic control.

4.5 TRANSPORTATION DEMAND MANAGEMENT

4.5.1 CONTEXT FOR TDM

The proposed elementary school is anticipated to have 751 students and the on-site daycare service will accommodate 49 children. In addition, a total of 51 staff, including teachers, custodians, and office staff, are expected to work for the school and daycare.

The development is not located within a Design Priority Area (DPA) or Transit-oriented Development (TOD) zone and the majority of staff (80%) will be auto drivers and the majority of students (85%) will arrive and depart by school bus. Between all school users, approximately 15% are anticipated to be auto passengers, 5% to use active modes (walking and cycling), and less than 1% to take public transit.

The school board (CEPEO) has indicated that operation hours of the elementary school will be from 7:30 AM to 4:00 PM, and the daycare will operate between 6:00 AM to 5:00 PM. It is anticipated that the school hours provided account for the daycare hours for before and after care, which are outside of morning and afternoon school bells. The start time of the school generally aligns with AM peak hour of the adjacent street traffic, whereas the school end time is before the PM peak hour of the adjacent street traffic such that there will be more variation in site generated vehicle trips coinciding with the commuter PM peak hour.

4.5.2 NEED AND OPPORTUNITY

The existing road network has available capacity should the mode share targets not be met, as indicated in Section 4.9.2.

4.5.3 TDM PROGRAM

The TDM Measures Checklist for non-residential developments was completed to allow and encourage travel by sustainable modes to and from the proposed development at the time of occupancy. The completed checklist is provided in **Appendix F**.

The following TDM measures are recommended for the proposed development:

- Display local area maps with walking/cycling access routes and key destinations at major entrances
- Display relevant transit schedules and route maps at entrances

4.6 NEIGHBOURHOOD TRAFFIC MANAGEMENT

4.6.1 ADJACENT NEIGHBOURHOODS

The proposed school forms part of the Fernbank Community Design Plan and is located within the Claridge Richcraft Tamarack (CRT) Westwood Phase 1 and Phase 2 subdivision. The access routes to and from the proposed development contain local and collector roads, such that the boundary streets of Cope Drive and Dagenham Street have been identified as a major collector road and local road, respectively. As per the City of Ottawa Area Traffic Management (ATM) guidelines, the thresholds for local roads and major collector roads are a maximum of 1,000 vehicles per day or 120 vehicles during the peak hour and a maximum of 5,000 vehicles per day or 600 vehicles during the peak hour, respectively.

The 2023 and 2028 total traffic volumes, as shown in Figure 3-4 and Figure 3-5, indicate that the addition of development-related traffic to these access roads (Cope Drive and Dagenham Street) will be below their road classification threshold during the peak hour for the 2023 future total conditions, but the threshold for Cope Drive is exceeded during the peak hour for the 2028 future total conditions. However, the 2028 future background volumes, as shown in Figure 3-3, indicate that the threshold is exceeded for Cope Drive prior to adding development-generated trips as the volumes account for the other area developments identified in Section 3.2.3.

Despite the road classification vehicle thresholds being exceeded, the Multi-Modal Level of Service Analysis (MMLOS) and intersection capacity analysis provided in Section 4.9.2 indicate that the Vehicle LOS target for the study area is met and that the study area intersections operate at an acceptable LOS. Based on this, the proposed school is expected to have a minimal impact on the access roads. Therefore, no change to the existing road classification is required and a Neighbourhood Traffic Management plan is not required.

4.7 TRANSIT

Based on Section 3.1.1, the proposed school is anticipated to generate only 3 person trips from the 5% of staff expected to use public transit and the existing transit routes do not coincide with the boundary street segments bordering the proposed site. Therefore, transit service will not be impacted according to development-generated demand.

4.8 REVIEW OF NETWORK CONCEPT

This module has been exempted based on Section 2.7.

4.9 INTERSECTION DESIGN

4.9.1 INTERSECTION CONTROL

Of the four study area intersections analyzed, the intersection of Fernbank Road / Robert Grant Avenue is signalized, and the intersections of Robert Grant Avenue / Cope Drive, Robert Grant Avenue / Bobolink Ridge and Robert Grant Avenue / Abbott Street E are roundabouts. The detailed operational analysis provided in Section 4.8.2 below indicates that all four study area intersections and their associated vehicle movements operate at a LOS of B or better for both the AM and PM Peak Hours from existing conditions to the 2023 future total traffic scenario; no signal modification is required in 2023 since the traffic operations at all the intersections perform well below capacity. During the 2028 future background and future total scenarios, westbound through (WBT) and southbound left (SBL) movements at the Robert Grant Avenue / Fernbank Road signalized intersection start to operate at LOS C

and D respectively during the PM peak period. Although these levels of service remain acceptable, particular attention should be paid to the signal timing plan to ensure the intersection continues to perform within capacity in the years beyond 2028 as traffic demand increases.

4.9.2 INTERSECTION DESIGN

4.9.2.1 MULTI-MODAL LEVEL OF SERVICE ANALYSIS

A Multi-Modal Level of Service (MMLOS) analysis was carried out in accordance with the methodology outlined in the City of Ottawa’s MMLOS Guidelines (2015). The Guidelines state that intersection LOS measures are to be evaluated at signalized intersections. Within the study area, Robert Grant Avenue / Fernbank Road is the only intersection that is signalized. The MMLOS analysis evaluates the 2022 existing conditions, 2028 future background and 2028 future total time horizon to provide a comparison between the baseline and future conditions (beyond the development period). The road configuration remains the same between 2023 opening year and 2028 horizon year and hence the ultimate year was considered in the MMLOS evaluation.

The intersection of Robert Grant Avenue / Fernbank Road was evaluated as an *Arterial in a Developing Community* with the corresponding LOS targets taken from Exhibit 22 of the MMLOS Guidelines. The targets for Fernbank Road / Robert Grant Avenue intersection includes Bicycle Level of Service (BLOS) target for a spine route and Transit Level of Service (TLOS) target for transit priority isolated measures; there are no truck routes in the study area and therefore no assigned targets. The intersection MMLOS results are summarized in Table 4-6 and the detailed MMLOS spreadsheets are provided in **Appendix H**.

Table 4-6: Summary of Intersection Multi-Modal Level of Service (MMLOS) Analysis – Robert Grant Avenue / Fernbank Road

	PLOS	BLOS	TLOS	TKLOS	VLOS
Target	C	C	D	-	D
2022 Existing Conditions	E	A	E	-	A
2028 Future Background	E	A	F	-	D
2028 Future Total	E	A	C	-	D

The MMLOS targets that were not met are highlighted in red text in Table 4-6 and explained below:

Pedestrian Level of Service (PLOS) for signalized intersections is based on the consideration of individual level of service related to the exposure to traffic and average pedestrian delay at the intersection. Pedestrian Exposure to Traffic at Signalized Intersections (PETSIT) LOS considers number of lanes crossed, left and right turning conflicts, Right Turn On Red (RTOR) restrictions, corner radius and type, and crosswalk treatment type. Pedestrian Delay LOS considers the cycle length at the intersection and the effective walk time on the crossing side. The PLOS target C was not met because currently, pedestrian delay on all legs is greater than 30s. For the target C to be met, effective walk time will have to be increased without increasing cycle length so that pedestrian delay can be reduced to less than 30s.

The **Transit Level of Service (TLOS)** at signalized intersections is based on individual transit delay on intersection approaches that include transit routes. With no dedicated transit priority measures at the intersection, OC Transpo buses experience the same delays as general vehicles in the westbound right and southbound left directions. The TLOS target of D is not met under the 2022 and 2028 future background scenarios because the average signal delay in the southbound direction during PM peak is greater than 30s.

Under the 2028 future total scenario, the signal timing is modified to an actuated-coordinated signal with 100s of cycle time. EBL phase is maintained as a protected and permitted phase with all other movements proceeding as

existing. The signal modification reduces the southbound left turning delays to less than 30s during AM and PM peak hour and therefore TLOS under 2028 future total conditions will meet the target.

4.9.2.2 DETAILED PERFORMANCE ANALYSIS

The existing and future conditions were analyzed based upon the weekday peak hour traffic volumes presented in Sections 2.3.7, 3.2.3, and 3.3.3. The City of Ottawa’s MMLOS Guidelines assigns the vehicle level of service (VLOS) based on ranges of volume to capacity ratio, as indicated in **Error! Reference source not found.** The VLOS for the intersection of Robert Grant Avenue and Fernbank Road was evaluated using the volume to capacity ratio.

Table 4-7: City of Ottawa MMLOS Guidelines, LOS Criteria – Signalized Intersections

VLOS	VOLUME TO CAPACITY RATIO
A	0 – 0.60
B	0.61 – 0.70
C	0.71 – 0.80
D	0.80 – 0.90
E	0.91 – 1.00
F	> 1.00

For unsignalized intersections, VLOS is based on control delay, as indicated in Table 4-8. Unsignalized intersections include roundabouts and all-way stop control intersections. All the intersections with the exception of Robert Grant Avenue / Fernbank Road were evaluated using the control delay.

Table 4-8: Highway Capacity Manual 2010, LOS Criteria – All-Way Stop Control Intersections

VLOS	CONTROL DELAY (S)
A	0 – 10
B	> 10 – 15
C	> 15 – 25
D	> 25 – 35
E	> 35 – 50
F	> 50

The following tables present the results of the intersection capacity analysis. Robert Grant Avenue / Fernbank Road signalized and the proposed All Way Stop Controlled (AWSC) intersection at Cope Drive / Dagenham Street were analyzed using Synchro 11; the signalized intersection was analyzed following the analysis parameters in the TIA Guidelines while the AWSC intersection followed the HCM 2010 LOS criteria for all-way stop control intersections. The roundabouts were analyzed with SIDRA 7 based on HCM 6 methodology. **Appendix I** contains the detailed Synchro and SIDRA analysis sheets.

EXISTING CONDITIONS

The existing conditions (2022) intersection operations analysis results are summarized in Table 4-9.

Table 4-9: Summary of Traffic Operations Analysis – Existing Conditions (2022)

MOVEMENT	AM PEAK HOUR				PM PEAK HOUR			
	LOS	V/C	DELAY (S)	95 TH %ILE QUEUE (M)	LOS	V/C	DELAY (S)	95 TH %ILE QUEUE (M)
Robert Grant Avenue / Fernbank Road (Signalized)								
EBL	A	0.10	29.8	12.5	A	0.08	41.1	11.3
EBT	A	0.37	12.1	47.5	A	0.27	9.4	37.0
WBT	A	0.46	28.3	52.4	B	0.69	29.4	118.2
WBR	A	0.46	9.3	16.5	A	0.33	4.9	14.7
SBL	A	0.29	21.8	44.0	A	0.36	31.3	61.4
SBR	A	0.05	8.3	6.3	A	0.06	11.4	7.5
Intersection LOS	A				A			
Robert Grant Avenue / Cope Drive (Roundabout)								
EB	A	0.00	3.2	0.2	A	0.01	3.5	0.2
WB	A	0.04	3.7	1.3	A	0.06	3.6	2.0
NB	A	0.19	4.3	6.8	A	0.13	3.8	4.3
SB	A	0.11	3.6	3.6	A	0.17	4.2	6.1
Intersection LOS	A				A			
Robert Grant Avenue / Bobolink Ridge (Roundabout)								
EB	A	0.07	3.7	2.0	A	0.08	4.1	2.3
WB	A	0.07	4.1	2.0	A	0.06	3.7	1.8
NB	A	0.20	4.6	7.0	A	0.14	4.2	4.6

MOVEMENT	AM PEAK HOUR				PM PEAK HOUR			
	LOS	V/C	DELAY (S)	95 TH %ILE QUEUE (M)	LOS	V/C	DELAY (S)	95 TH %ILE QUEUE (M)
SB	A	0.14	3.9	4.8	A	0.23	4.7	8.7
Intersection LOS	A				A			
Robert Grant Avenue / Abbott Street E. (Roundabout)								
EB	A	0.14	4.0	4.7	A	0.30	6.1	11.4
WB	A	0.14	4.7	4.1	A	0.22	5.3	7.8
NB	A	0.38	6.2	17.2	A	0.25	5.0	9.6
Intersection LOS	A				A			
Notes:								
<ol style="list-style-type: none"> 1. Movement LOS at the signalized intersection is based on Synchro V/C ratios and the LOS thresholds in Section 6.1 of the City of Ottawa's Multi-Modal Level of Service (MMLoS) Guidelines for signalized intersections. 2. Movement LOS at the roundabouts is based on delay calculations from HCM 6 Roundabouts report that is generated in SIDRA. 3. The overall intersection LOS at the signalized intersection is based on the overall intersection V/C ratio which is derived from the volumes and capacities of the critical movement at the intersection. 4. The overall intersection LOS at the roundabouts is based on overall delay from HCM 6 Roundabouts report generated in SIDRA. 								

The results of the synchro analysis indicate that all study intersections operate at acceptable levels of service under existing conditions. All the roundabouts operate at LOS A with minimal delays and queues experienced on all approaches. All movements at the signalized intersection of Robert Grant Avenue / Fernbank Road operate at LOS B or better. Given the relatively large westbound through volumes (app. 440 vehicles) during the PM peak, this movement shows a v/c ratio of 0.69 (LOS B) with queues of approximately 120m. The westbound through queue does not block westbound right turning traffic as the adjacent westbound right storage lane is 130m long and provides enough space for turning vehicles to access this lane.

FUTURE BACKGROUND

The 2023 and 2028 future background intersection operations analysis results are summarized in Table 4-10 and Table 4-11, respectively.

Table 4-10: Summary of Traffic Operations Analysis – Future Background (2023)

MOVEMENT	AM PEAK HOUR				PM PEAK HOUR			
	LOS	V/C	DELAY (S)	95 TH %ILE QUEUE (M)	LOS	V/C	DELAY (S)	95 TH %ILE QUEUE (M)
Robert Grant Avenue / Fernbank Road								

MOVEMENT	AM PEAK HOUR				PM PEAK HOUR			
	LOS	V/C	DELAY (S)	95 TH %ILE QUEUE (M)	LOS	V/C	DELAY (S)	95 TH %ILE QUEUE (M)
EBL	A	0.13	29.9	14.4	A	0.10	39.6	11.8
EBT	A	0.35	12.1	43.5	A	0.26	9.6	34.0
WBT	A	0.43	27.6	47.6	B	0.66	28.6	105.1
WBR	A	0.47	9.7	16.5	A	0.33	5.3	14.6
SBL	A	0.27	20.4	40.3	A	0.34	28.6	55.9
SBR	A	0.05	7.8	6.3	A	0.06	10.2	7.7
Intersection LOS	A				A			
Robert Grant Avenue / Cope Drive								
EB	A	0.04	3.5	1.3	A	0.05	3.9	1.6
WB	A	0.06	4.0	1.7	A	0.07	3.8	2.3
NB	A	0.22	4.6	7.9	A	0.14	4.0	4.9
SB	A	0.14	4.0	4.8	A	0.19	4.5	6.8
Intersection LOS	A				A			
Robert Grant Avenue / Bobolink Ridge								
EB	A	0.07	3.8	2.1	A	0.08	4.3	2.4
WB	A	0.07	4.3	2.1	A	0.06	3.8	1.8
NB	A	0.22	4.8	7.9	A	0.16	4.4	5.4
SB	A	0.17	4.2	6.1	A	0.25	4.9	1.3
Intersection LOS	A				A			

MOVEMENT	AM PEAK HOUR				PM PEAK HOUR			
	LOS	V/C	DELAY (S)	95 TH %ILE QUEUE (M)	LOS	V/C	DELAY (S)	95 TH %ILE QUEUE (M)
Robert Grant Avenue / Abbott Street E.								
EB	A	0.16	4.3	5.3	A	0.32	6.4	12.2
WB	A	0.16	5.0	5.0	A	0.24	5.5	8.5
NB	A	0.40	6.5	19.0	A	0.27	5.2	10.9
Intersection LOS	A				A			
Notes:								
<ol style="list-style-type: none"> 1. Movement LOS at the signalized intersection is based on Synchro V/C ratios and the LOS thresholds in Section 6.1 of the City of Ottawa's Multi-Modal Level of Service (MMLoS) Guidelines for signalized intersections. 2. Movement LOS at the roundabouts is based on delay calculations from HCM 6 Roundabouts report that is generated in SIDRA. 3. The overall intersection LOS at the signalized intersection is based on the overall intersection V/C ratio which is derived from the volumes and capacities of the critical movement at the intersection. 4. The overall intersection LOS at the roundabouts is based on overall delay from HCM 6 Roundabouts report generated in SIDRA. 								

Table 4-11: Summary of Traffic Operations Analysis – Future Background (2028)

MOVEMENT	AM PEAK HOUR				PM PEAK HOUR			
	LOS	V/C	DELAY (S)	95 TH %ILE QUEUE (M)	LOS	V/C	DELAY (S)	95 TH %ILE QUEUE (M)
Robert Grant Avenue / Fernbank Road								
EBL	A	0.23	35.7	27.4	A	0.25	45.9	26.4
EBT	A	0.46	12.2	68.0	A	0.34	9.2	50.3
WBT	A	0.56	29.9	77.4	C	0.80	35.1	176.7
WBR	A	0.56	7.2	20.4	A	0.53	4.9	21.2
SBL	B	0.74	39.9	#135.8	D	0.82	54.3	#147.7
SBR	A	0.14	7.5	10.9	A	0.14	9.2	11.5

MOVEMENT	AM PEAK HOUR				PM PEAK HOUR			
	LOS	V/C	DELAY (S)	95 TH %ILE QUEUE (M)	LOS	V/C	DELAY (S)	95 TH %ILE QUEUE (M)
Intersection LOS	B				D			
Robert Grant Avenue / Cope Drive								
EB	A	0.39	8.3	14.9	A	0.30	7.5	10.2
WB	A	0.29	8.7	8.9	A	0.17	6.4	5.1
NB	A	0.51	10.6	27.6	A	0.40	7.7	16.1
SB	A	0.45	8.0	21.2	A	0.52	9.0	27.1
Intersection LOS	A				A			
Robert Grant Avenue / Bobolink Ridge								
EB	A	0.11	5.8	3.2	A	0.14	6.9	3.8
WB	A	0.17	7.6	4.7	A	0.12	5.8	3.4
NB	A	0.58	9.9	33.8	A	0.46	8.0	21.0
SB	A	0.45	7.4	22.5	A	0.56	9.1	34.4
Intersection LOS	A				A			
Robert Grant Avenue / Abbott Street E.								
EB	A	0.23	5.3	8.3	B	0.62	14.0	47.6
WB	A	0.27	7.0	8.9	A	0.49	9.5	22.5
NB	B	0.69	12.3	60.2	A	0.49	8.2	24.7
Intersection LOS	B				B			

MOVEMENT	AM PEAK HOUR				PM PEAK HOUR			
	LOS	V/C	DELAY (S)	95 TH %ILE QUEUE (M)	LOS	V/C	DELAY (S)	95 TH %ILE QUEUE (M)
Notes:								
1. Movement LOS at the signalized intersection is based on Synchro V/C ratios and the LOS thresholds in Section 6.1 of the City of Ottawa's Multi-Modal Level of Service (MMLOS) Guidelines for signalized intersections.								
2. Movement LOS at the roundabouts is based on delay calculations from HCM 6 Roundabouts report that is generated in SIDRA.								
3. The overall intersection LOS at the signalized intersection is based on the overall intersection V/C ratio which is derived from the volumes and capacities of the critical movement at the intersection.								
4. The overall intersection LOS at the roundabouts is based on overall delay from HCM 6 Roundabouts report generated in SIDRA.								

The results of the future background scenario analyses indicate that 2023 traffic operations remain similar to 2022 existing conditions. All intersections operate with all movements at LOS A except for the WB through movements which operate at LOS B during the PM peak period.

With expected traffic growth in the area between the 2022 existing analysis period and the 2028 horizon analysis period, 2028 background traffic operations indicate an increase in delays and queues on the Robert Grant Avenue corridor. With the same cycle length maintained at Robert Grant Avenue / Fernbank Road signalized intersection, the LOS of WBT movements increase from LOS B to C during the PM peak period with a 175m queue in the 2028 future horizon analysis. WBT queues will extend past the adjacent WBR storage lanes, preventing right turning vehicles held up in the queues from accessing the 130m storage lane in the PM peak hour. Southbound left (SBL) movements at the intersection will increase from LOS A in the AM and PM peak hours to LOS B in the AM and LOS D in the PM. The 135m and 150m queues indicated during the AM and PM peak scenarios respectively, are longer than the 105m southbound right storage lane; southbound left movement queues will extend past the adjacent 105m southbound right storage lane, blocking turning vehicles from accessing the storage lane in morning and evening peak periods in the 2028 future background scenario.

At the Robert Grant Avenue / Abbott Street East roundabout north of the site, traffic operations in the northbound (NB) direction will increase from LOS A to LOS B in the AM peak period as a result of the expected traffic growth in the 2028 future background scenario. NB traffic will experience a 12s delay with 60m queue queues forming on the approach in the AM peak period. Eastbound (EB) movements will increase from LOS A to LOS B in the PM peak hour with 14s delays and 50m queues on this approach. The roundabout will continue to operate at acceptable levels of service.

FUTURE TOTAL

The 2023 and 2028 future total intersection operations analysis results are summarized in Table 4-12 and Table 4-13, respectively.

Table 4-12: Summary of Traffic Operations Analysis – Future Total (2023)

MOVEMENT	AM PEAK HOUR				PM PEAK HOUR			
	LOS	V/C	DELAY (S)	95 TH %ILE QUEUE (M)	LOS	V/C	DELAY (S)	95 TH %ILE QUEUE (M)
Robert Grant Avenue / Fernbank Road (Signalized)								
EBL	A	0.15	30.2	15.7	A	0.10	39.6	12.4
EBT	A	0.35	12.1	43.5	A	0.26	9.6	34.0

MOVEMENT	AM PEAK HOUR				PM PEAK HOUR			
	LOS	V/C	DELAY (S)	95 TH %ILE QUEUE (M)	LOS	V/C	DELAY (S)	95 TH %ILE QUEUE (M)
WBT	A	0.43	27.6	47.6	B	0.66	28.6	105.1
WBR	A	0.50	9.7	17.5	A	0.34	5.3	14.9
SBL	A	0.29	20.7	43.7	A	0.36	28.9	59.3
SBR	A	0.06	7.4	6.6	A	0.07	9.9	8.0
Intersection LOS	A				A			
Robert Grant Avenue / Cope Drive (Roundabout)								
EB	A	0.05	3.6	1.5	A	0.06	4.0	1.8
WB	A	0.07	4.1	1.9	A	0.08	3.9	2.3
NB	A	0.24	4.9	8.9	A	0.15	4.1	5.2
SB	A	0.22	4.8	7.7	A	0.23	4.9	8.4
Intersection LOS	A				A			
Robert Grant Avenue / Bobolink Ridge (Roundabout)								
EB	A	0.16	4.9	5.0	A	0.15	5.0	4.7
WB	A	0.08	4.5	2.2	A	0.07	4.0	1.9
NB	A	0.22	5.1	7.9	A	0.17	4.6	5.6
SB	A	0.08	4.8	8.7	A	0.27	5.1	10.7
Intersection LOS	A				A			
Robert Grant Avenue / Abbott Street E. (Roundabout)								
EB	A	0.21	4.8	7.2	A	0.34	6.7	13.2

MOVEMENT	AM PEAK HOUR				PM PEAK HOUR			
	LOS	V/C	DELAY (S)	95 TH %ILE QUEUE (M)	LOS	V/C	DELAY (S)	95 TH %ILE QUEUE (M)
WB	A	0.19	5.5	6.0	A	0.25	5.7	8.9
NB	A	0.45	7.0	22.3	A	0.30	5.4	11.9
Intersection LOS	A				A			
Cope Drive / Dagenham Street (Stop-Controlled)								
EB	-	-	-	-	-	-	-	-
WB	A	0.10	6.7	-	A	0.04	6.5	-
SB	A	0.01	7.4	-	A	0.01	7.2	-
Intersection LOS	A				A			
Notes:								
1. Movement LOS at the signalized intersection is based on Synchro V/C ratios and the LOS thresholds in Section 6.1 of the City of Ottawa's Multi-Modal Level of Service (MMLoS) Guidelines for signalized intersections.								
2. Movement LOS at the roundabouts is based on delay calculations from HCM 6 Roundabouts report that is generated in SIDRA.								
3. The overall intersection LOS at the signalized intersection is based on the overall intersection V/C ratio which is derived from the volumes and capacities of the critical movement at the intersection.								
4. The overall intersection LOS at the roundabouts is based on overall delay from HCM 6 Roundabouts report generated in SIDRA.								

Table 4-13: Summary of Traffic Operations Analysis – Future Total (2028)

MOVEMENT	AM PEAK HOUR				PM PEAK HOUR			
	LOS	V/C	DELAY (S)	95 TH %ILE QUEUE (M)	LOS	V/C	DELAY (S)	95 TH %ILE QUEUE (M)
Robert Grant Avenue / Fernbank Road (Signalized)								
EBL	A	0.51	54.7	30.5	A	0.27	13.0	11.3
EBT	C	0.71	31.6	100.2	A	0.46	18.6	67.3
WBT	C	0.73	44.4	85.8	D	0.90	44.8	#175.1

MOVEMENT	AM PEAK HOUR				PM PEAK HOUR			
	LOS	V/C	DELAY (S)	95 TH %ILE QUEUE (M)	LOS	V/C	DELAY (S)	95 TH %ILE QUEUE (M)
WBR	A	0.55	6.6	20.6	A	0.52	4.1	18.0
SBL	A	0.49	20.4	97.0	A	0.58	29.6	101.1
SBR	A	0.10	4.4	8.6	A	0.11	6.1	9.2
Intersection LOS	C				C			
Robert Grant Avenue / Cope Drive (Roundabout)								
EB	A	0.41	8.6	15.5	A	0.31	7.7	10.6
WB	A	0.30	9.2	9.4	A	0.18	6.5	5.3
NB	A	0.54	11.3	32.6	A	0.41	7.9	16.8
SB	A	0.55	9.9	28.0	A	0.57	9.9	31.0
Intersection LOS	A				A			
Robert Grant Avenue / Bobolink Ridge (Roundabout)								
EB	A	0.24	7.7	7.3	A	0.24	8.4	7.1
WB	A	0.16	8.1	4.9	A	0.12	6.1	3.5
NB	B	0.61	11.1	34.6	A	0.47	8.6	21.7
SB	A	0.51	8.3	28.1	A	0.58	9.5	37.4
Intersection LOS	A				A			
Robert Grant Avenue / Abbott Street E. (Roundabout)								
EB	A	0.29	6.0	10.7	C	0.66	15.1	54.0
WB	A	0.31	7.8	10.3	B	0.51	10.2	27.3

MOVEMENT	AM PEAK HOUR				PM PEAK HOUR			
	LOS	V/C	DELAY (S)	95 TH %ILE QUEUE (M)	LOS	V/C	DELAY (S)	95 TH %ILE QUEUE (M)
NB	B	0.73	13.7	71.9	A	0.52	8.8	28.0
Intersection LOS	B				B			
Cope Drive / Dagenham Street (Stop-Controlled)								
EB	A	0.04	7.4	-	A	0.03	7.3	-
WB	A	0.11	7.0	-	A	0.16	7.7	-
SB	A	0.06	6.9	-	A	0.05	6.9	-
NB	A	0.02	7.6	-	A	0.02	7.6	-
Intersection LOS	A				A			
Notes:								
1. Movement LOS at the signalized intersection is based on Synchro V/C ratios and the LOS thresholds in Section 6.1 of the City of Ottawa's Multi-Modal Level of Service (MMLoS) Guidelines for signalized intersections.								
2. Movement LOS at the roundabouts is based on delay calculations from HCM 6 Roundabouts report that is generated in SIDRA.								
3. The overall intersection LOS at the signalized intersection is based on the overall intersection V/C ratio which is derived from the volumes and capacities of the critical movement at the intersection.								
4. The overall intersection LOS at the roundabouts is based on overall delay from HCM 6 Roundabouts report generated in SIDRA.								

The result of the future total analysis indicates an increase in traffic operations in comparison to the future background scenarios. 2023 future total traffic operations remain similar to 2023 future background scenario; all movements at all intersections operate at LOS A except WBT movements at Robert Grant Avenue / Fernbank Road intersection which indicate LOS B because of the higher PM peak hour volume (approximately 200 vehicles). The new 3-leg all-way stop controlled Cope Drive / Dagenham Street intersection will operate at LOS A with an intersection delay of 6.6s recorded at the intersection.

The addition of the site generated traffic to the projected 2028 traffic on the corridor is realized in the increase in vehicle delay and queuing at the signalized intersection and the roundabouts. All movements at the intersection operate at LOS D or better under optimized signal timings. At the Robert Grant Avenue / Fernbank Road signalized intersection, LOS increases from B to C in the SBL direction with the addition of the site generated traffic; these movements will experience 42s delays and 145m queues in the 2028 future total scenario. At the Robert Grant Avenue / Bobolink Ridge roundabout, LOS for NB traffic will increase from A to B during the AM peak hour with an associated 11s delay and 35m queues on this approach. At the Robert Grant Avenue / Abbott Street East intersection, LOS for EB traffic will increase from B to C during the PM peak hour; traffic in the EB direction will experience 15s delays and 55m queues. Westbound (WB) traffic will also experience an LOS increase from A to B during the PM peak period with 10s delays and 30m queues. The queues at the roundabouts are not expected to spillover into accesses or intersections upstream. The AWSC Cope Drive / Dagenham intersection will continue to operate at optimum LOS in 2028 with the introduction of a south leg; a 7s intersection delay is recorded at this intersection. In general, all intersections will continue to operate at acceptable levels of service.

4.10 SUMMARY OF IMPROVEMENTS INDICATED AND MODIFICATION OPTIONS

A summary of transportation improvements proposed as part of this Transportation Impact Assessment carried out and the proposed modifications are presented as follows:

1. Development Design

- Sustainable modes have been accounted for on-site through the provision of internal sidewalks, bicycle parking, and direct connections and access to an existing adjacent transit stop.
- The site plan was assessed using AutoTurn 11 for various design vehicles (waste removal, fire truck and school bus) accessing and circulating around the site. The AutoTurn swept paths indicate that the site access on Dagenham Street can accommodate the movements of these design vehicles entering and exiting the site without conflicting with built features but encroach on the opposing vehicle lane. The drop-off area, however, cannot accommodate the wide turning movements of these design vehicles when circulating around it without conflicting with the curb.
- Based on the site plan, it is recommended that the radius of the exterior curb at the south-west corner of the drop-off area be increased to accommodate larger vehicles.

2. Parking

- The 60 auto parking and 48 bicycle parking spaces provided in the site plan meet the minimum requirements of the City of Ottawa's Zoning By-Law.

3. Boundary Streets Design

- Cope Drive does not meet the PLOS target nor the BLOS the target under existing conditions. However, the BLOS target will be met for the 2028 future conditions with the provision of a multi-use pathway with a boulevard.
- Due to Dagenham Street currently being under construction, no MMLOS evaluation has been carried out for existing conditions. There are no concept plans available for the Dagenham Street segment and to meet the MMLOS targets for a local street within 300m of a school, the 2028 future conditions MMLOS analysis will require the provision of 3m sidewalks with a minimum of 0.5m boulevard for pedestrians. In addition, the posted speed limit will need to be maintained at 40km/h to keep cyclists operating in mixed traffic comfortable.

4. Access Intersections Design

- The site access on Dagenham Street meets the requirements set out for driveways in TAC 2017 to be considered as part of good design practice.
- In accordance with OTM Book 12, the site generated volumes are below the minimum requirements for a traffic signal to be warranted based on Justification 7 – Projected Volumes.
- Stop-control on the minor road (site access) is sufficient.

5. Transportation Demand Management

- The existing road network has available capacity should the mode share targets not be met.
- The TDM measures recommended for the proposed development include displaying local area maps with walking/cycling access routes and transit schedules with route maps.

6. Neighbourhood Traffic Management

- Despite the future traffic volumes along the access routes being above the thresholds for local and major collector roads during the peak hour, the proposed school will have a minimal impact on the access roads since the traffic operations are below the capacity and within an acceptable LOS.

7. Transit

- Transit service along Cope Drive (east of Robert Grant Avenue) and Robert Grant Avenue (south of Cope Drive) will not be impacted according to the low projected development-generated demand.

8. Intersection Design

- Intersection of Fernbank Road / Robert Grant Avenue (signalized): No proposed modifications. Control type, configuration, and capacity are sufficient. Particular attention should be paid to the signal timing plan to ensure the intersection continues to perform within capacity in the years beyond 2028 as traffic demand increases.
- Intersection of Robert Grant Avenue / Cope Drive (roundabout): No proposed modifications. Control type, configuration, and capacity are sufficient.
- Intersection of Robert Grant Avenue / Bobolink Ridge (roundabout): No proposed modifications. Control type, configuration, and capacity are sufficient.
- Intersection of Robert Grant Avenue / Abbott Street E. (roundabout): No proposed modifications. Control type, configuration, and capacity are sufficient.

Based on the results of this Transportation Impact Assessment, the transportation network surrounding the proposed elementary school by CEPEO located at 755 Cope Drive can accommodate the development without adverse impacts to future traffic operations during the 2023 built-out year and 2028 planning horizon.

APPENDIX

A SCREENING FORM





City of Ottawa 2017 TIA Guidelines Screening Form

1. Description of Proposed Development

Municipal Address	755 Cope Drive, Stittsville, Ontario, K2S 1S3
Description of Location	Located at the north-east corner of Cope Dr and Dagenham St.
Land Use Classification	Institutional - School
Development Size (units)	800 students and staff
Development Size (m ²)	5,455 (building area)
Number of Accesses and Locations	Access from Dagenham Street, service access from Cope Drive
Phase of Development	Single Phase
Buildout Year	2022

If available, please attach a sketch of the development or site plan to this form.

2. Trip Generation Trigger

Considering the Development's Land Use type and Size (as filled out in the previous section), please refer to the Trip Generation Trigger checks below.

Land Use Type	Minimum Development Size
Single-family homes	40 units
Townhomes or apartments	90 units
Office	3,500 m ²
Industrial	5,000 m ²
Fast-food restaurant or coffee shop	100 m ²
Destination retail	1,000 m ²
Gas station or convenience market	75 m ²

** If the development has a land use type other than what is presented in the table above, estimates of person-trip generation may be made based on average trip generation characteristics represented in the current edition of the Institute of Transportation Engineers (ITE) Trip Generation Manual.*

If the proposed development size is greater than the sizes identified above, the Trip Generation Trigger is satisfied.

800 students and staff will generate > 60 vehicle trips, Trip Generation trigger is satisfied.



Transportation Impact Assessment Guidelines

3. Location Triggers

	Yes	No
Does the development propose a new driveway to a boundary street that is designated as part of the City’s Transit Priority, Rapid Transit or Spine Bicycle Networks?	X	
Is the development in a Design Priority Area (DPA) or Transit-oriented Development (TOD) zone?*		X

**DPA and TOD are identified in the City of Ottawa Official Plan (DPA in Section 2.5.1 and Schedules A and B; TOD in Annex 6). See Chapter 4 for a list of City of Ottawa Planning and Engineering documents that support the completion of TIA).*

If any of the above questions were answered with ‘Yes,’ the Location Trigger is satisfied.

4. Safety Triggers

	Yes	No
Are posted speed limits on a boundary street are 80 km/hr or greater?		X
Are there any horizontal/vertical curvatures on a boundary street limits sight lines at a proposed driveway?		X
Is the proposed driveway within the area of influence of an adjacent traffic signal or roundabout (i.e. within 300 m of intersection in rural conditions, or within 150 m of intersection in urban/ suburban conditions)?		X
Is the proposed driveway within auxiliary lanes of an intersection?		X
Does the proposed driveway make use of an existing median break that serves an existing site?		X
Is there is a documented history of traffic operations or safety concerns on the boundary streets within 500 m of the development?		X
Does the development include a drive-thru facility?		X

If any of the above questions were answered with ‘Yes,’ the Safety Trigger is satisfied.

5. Summary


	Yes	No
Does the development satisfy the Trip Generation Trigger?	X	
Does the development satisfy the Location Trigger?	X	
Does the development satisfy the Safety Trigger?		X

If none of the triggers are satisfied, the TIA Study is complete. If one or more of the triggers is satisfied, the TIA Study must continue into the next stage (Screening and Scoping).


APPENDIX

B DRAFT SITE
PLAN





2 ENLARGED DAYCARE SITE PLAN
A1.0
1:200



1 GENERAL SITE PLAN
A1.0
1:400

SITE AND PARKING INFORMATION		PARKING CALCULATION
TYPE OF BUILDING OR USE SCHOOL (GROUP 2 OCCUPANCY)		20 CLASSROOMS X 1.5 = 30 2 PERSON FOR ADMIN & 3 CHILD CARE X 1.5 = 7 TOTAL PARKING REQUIRED = 37 BARRIER-FREE PARKING SPACES REQUIRED = 1 BARRIER-FREE PARKING SPACES PROVIDED = 2 TOTAL PARKING PROVIDED = 39
ZONING ZONING = I1B - MINOR INSTITUTIONAL ZONE, SUBZONE B/ R1Z RESIDENTIAL FIRST DENSITY, SUBZONE Z	REQUIREMENT 1000m ²	BUILDING AREA BUILDING AREA = 3,802.07m ²
MINIMUM LOT AREA: SEC. 170, TABLE 170B (b)	30.0m	SITE AREA SITE AREA = 28,889m ²
MINIMUM LOT FRONTAGE: SEC. 170, TABLE 170B (a)	6.0m	
MINIMUM FRONT YARD: SEC. 170, TABLE 170B (c)	7.5m	
MINIMUM REAR YARD: SEC. 170, TABLE 170B (d)	NO REQUIREMENT	
MINIMUM EXTERIOR SIDE YARD:	7.5m	
MINIMUM INTERIOR SIDE YARD: SEC. 170, TABLE 170B (e)	7.5m	
MINIMUM CORNER SIDE YARD: SEC. 170, TABLE 170B (f)	7.5m	
MINIMUM LANDSCAPED OPEN SPACE	NO REQUIREMENT	
MAXIMUM LOT COVERAGE	NO REQUIREMENT	
MAXIMUM BUILDING HEIGHT: SEC. 170, TABLE 170B (g)	18.0m	
MINIMUM REQUIRED PARKING FOR NEW ELEMENTARY SCHOOL: SEC. 101, TABLE 101, NB1	1.5 PER CLASSROOM (w/ PORTABLES)	
MINIMUM REQ. WIDTH OF A LANDSCAPED BUFFER FOR PARKING LOT: SEC. 110, TABLE 110(a)	3.0m	
MINIMUM NUMBER OF BARRIER-FREE PARKING SPACES: BY LAW NO. 2017-301, SECTION 111	NO. OF REGULAR PARKING SPACES - MIN. NO. OF BARRIER-FREE PARKING SPACES -	
MINIMUM NUMBER OF BICYCLE PARKING SPACES: SEC. 111, TABLE 111A (b)	SCHOOL: 1 PER 100m ² OF GFA OFFICE: 474/1000 = 47/1000 ROUNDED TO 47 DAY CARE: 1 PER 250m ² OF GFA = 327/250 = 1.3 ROUNDED TO 1 TOTAL = 48	
BICYCLE PARKING DIMENSIONS: SEC. 111, TABLE 11B	HORIZONTAL: 0.5m by 1.8m VERTICAL: 0.5m by 1.5m	

- GENERAL SITE PLAN NOTES**
- OBC 3.2.5.5 (1) LOCATION OF ACCESS ROUTES
ACCESS ROUTES REQUIRED BY ARTICLE 3.2.5.4 SHALL BE LOCATED SO THAT THE PRINCIPLE ENTRANCE AND EVERY ACCESS OPENING REQUIRED BY ARTICLE 3.2.5.1 AND 3.2.5.2 ARE LOCATED NOT LESS THAN 3M AND NOT MORE THAN 15M FROM THE CLOSEST PORTION OF THE ACCESS ROUTE REQUIRED FOR FIRE DEPARTMENT USE, MEASURED HORIZONTALLY FROM THE FACE OF THE BUILDING.
 - OBC 3.2.5.6 (1) ACCESS ROUTE DESIGN
A PORTION OF A ROADWAY OR YARD PROVIDED AS A REQUIRED ACCESS ROUTE FOR FIRE DEPARTMENT USE SHALL: (a) HAVE A CLEAR WIDTH OF NOT LESS THAN 3M, UNLESS IT CAN BE SHOWN THAT A LESSER WIDTH IS SATISFACTORY; (b) HAVE A CENTERLINE RADIUS NOT LESS THAN 12M; (c) HAVE AN OVERHEAD CLEARANCE OF NOT LESS THAN 2M; (d) HAVE A CHANGE OF GRADIENT NOT MORE THAN 1% IN 12.5 OVER A MINIMUM DISTANCE OF 15M; (e) BE DESIGNED TO SUPPORT THE EXPECTED LOADS IMPOSED BY FIRE FIGHTING EQUIPMENT AND BE SURFACED WITH CONCRETE ASPHALT OR OTHER MATERIAL DESIGNED TO PERMIT ACCESSIBILITY UNDER ALL CLIMATIC CONDITIONS.
 - PROVIDE 75mm THK HI-40 UNDER ALL EXTERIOR CONCRETE SIDEWALK AT ALL ENTRANCES/EXITS. EXTEND RIGID INSULATION MIN 1200 PAST THE EDGE OF CONCRETE SIDEWALKS.
 - FOR CONCRETE SIDEWALK EXPANSION AND CONTRACTION JOINTS, REFER TO CIVIL DETAIL AND SPECIFICATIONS.
 - REFER TO LANDSCAPING PLAN AND CIVIL PLANS FOR LOCATION OF SOD. ALL REMAINING AREAS NOT SLATED FOR SOD TO RECEIVE TOPSOIL AND SEED.
 - REFER TO CIVIL DRAWINGS FOR LOCATIONS OF FIRE ROUTE SIGNAGE.
 - REFER TO CIVIL DRAWINGS FOR TACTILE INDICATORS.
 - ALL CURBS ADJACENT TO PARKING AREAS AND CURBS FORMING PART OF SIDEWALKS ADJACENT TO PARKING AREAS TO BE PAINTED YELLOW.
 - ENSURE FINAL PLACEMENT OF FIRE DEPARTMENT CONNECTION IS NOT MORE THAN 45 m FROM THE NEAREST FIRE HYDRANT AS PER OBC 3.2.5.16 (2).

- SITE PLAN SYMBOLS LEGEND**
- ▲ - ENTRANCE
 - ▼ - EXIT
 - ⊕ - MANHOLE, CATCH BASIN, ETC. REFER TO CIVIL
 - ⚡ - LS, LIGHT STANDARD, REFER TO ELECTRICAL AND STRUCTURAL
 - ▭ - DENOTES SLOPED GRADE, REFER TO CIVIL
 - ⚡ - DENOTES FIRE TRUCK ACCESS ROUTE, REFER TO CIVIL DRAWINGS
 - - PROPERTY LINE
 - - SURVEY BAR
 - - UTILITY POLE
 - ⚡ - FIRE HYDRANT
 - BN - BASKETBALL NET
 - ▭ - SIDEWALK/ CONCRETE SURFACE
 - ▭ - PEDESTRIAN WALKWAY
 - S - SWALE, REFER TO CIVIL DRAWINGS
 - - - - SETBACK LINE
 - BH - BOREHOLE LOCATION
 - GRASS
 - X - FENCE LINE
 - LANDSCAPING
 - ASPHALT
 - PAINTED LINES
 - MH - NEW MANHOLE FOR PORTABLE
 - TRANSFORMER

ARCHITECTURE 49

1345 ROSEMOUNT AVENUE
OTTAWA, ONTARIO, CANADA K1B 3Z5
PHONE: 613 933 9664 | FAX: 613 936 0335 | WWW.ARCHITECTURE49.COM

WSP

300-911 QUEENSWAY DRIVE
OTTAWA, ONTARIO, CANADA K2B 8K2
PHONE: 613 932-3600 | WWW.WSP.COM

Conseil des écoles publiques de l'Est de l'Ontario

ÉCOLE ÉLÉMENTAIRE KANATA - STITTSVILLE

6	14 JAN 2022	ISSUED FOR 99% CD REVIEW
5	10 NOV 2021	ISSUED FOR 85% CD REVIEW
4	20 SEP 2021	ISSUED FOR INFORMATION
3	24 SEP 2021	ISSUED FOR 60% CD REVIEW
2	27 AUG 2021	RE-ISSUED FOR 30% CD REVIEW
1	04 AUG 2021	30% CD REVIEW

PROJECT NO: 219-0014-00 DATE: 13 JAN 2022

DESIGNED BY: NMM SDI AS

CHECKED BY: NMM SDI AS

DATE OF: 14 JAN 2022

ISSUED FOR 99% CD REVIEW

C TRANS O-D
SURVEY

Kanata - Stittsville


Demographic Characteristics

Population	105,210	Actively Travelled	83,460
Employed Population	49,640	Number of Vehicles	64,540
Households	38,010	Area (km ²)	82.6

Occupation Status (age 5+)	Male	Female	Total
Full Time Employed	24,670	19,590	44,260
Part Time Employed	1,540	3,840	5,380
Student	13,630	13,410	27,040
Retiree	6,480	8,350	14,820
Unemployed	850	940	1,790
Homemaker	160	3,310	3,470
Other	350	1,010	1,360
Total:	47,690	50,440	98,120

Traveller Characteristics	Male	Female	Total
Transit Pass Holders	5,940	6,920	12,860
Licensed Drivers	36,280	36,790	73,070
Telecommuters	200	380	580
Trips made by residents	135,300	143,330	278,630



Selected Indicators	
Daily Trips per Person (age 5+)	2.84
Vehicles per Person	0.61
Number of Persons per Household	2.77
Daily Trips per Household	7.33
Vehicles per Household	1.70
Workers per Household	1.31
Population Density (Pop/km ²)	1270



Household Size		
1 person	5,810	15%
2 persons	11,660	31%
3 persons	7,490	20%
4 persons	8,890	23%
5+ persons	4,160	11%
Total:	38,010	100%

Households by Vehicle Availability		
0 vehicles	1,050	3%
1 vehicle	14,090	37%
2 vehicles	19,110	50%
3 vehicles	3,000	8%
4+ vehicles	770	2%
Total:	38,010	100%

Households by Dwelling Type		
Single-detached	21,610	57%
Semi-detached	3,890	10%
Townhouse	10,550	28%
Apartment/Condo	1,960	5%
Total:	38,010	100%




* In 2005 data was only collected for household members aged 11+ therefore these results cannot be compared to the 2011 data.

Travel Patterns

Top Five Destinations of Trips from Kanata - Stittsville

AM Peak Period



Summary of Trips to and from Kanata - Stittsville

AM Peak Period (6:30 - 8:59)

Districts	Destinations of Trips From		Origins of Trips To	
	District	% Total	District	% Total
Ottawa Centre	4,560	8%	140	0%
Ottawa Inner Area	3,350	6%	970	2%
Ottawa East	660	1%	260	1%
Beacon Hill	280	0%	170	0%
Alta Vista	1,810	3%	660	1%
Hunt Club	490	1%	420	1%
Merivale	3,410	6%	1,200	3%
Ottawa West	2,020	4%	840	2%
Bayshore / Cedarview	5,010	9%	2,420	5%
Orléans	290	1%	500	1%
Rural East	100	0%	30	0%
Rural Southeast	50	0%	260	1%
South Gloucester / Leitrim	60	0%	140	0%
South Nepean	690	1%	1,800	4%
Rural Southwest	1,130	2%	1,850	4%
Kanata / Stittsville	30,360	54%	30,360	66%
Rural West	1,050	2%	3,250	7%
Île de Hull	670	1%	30	0%
Hull Périphérie	160	0%	30	0%
Plateau	100	0%	230	0%
Aylmer	0	0%	190	0%
Rural Northwest	20	0%	60	0%
Pointe Gatineau	20	0%	80	0%
Gatineau Est	0	0%	60	0%
Rural Northeast	30	0%	50	0%
Buckingham / Masson-Angers	30	0%	10	0%
Ontario Sub-Total:	55,320	98%	45,270	98%
Québec Sub-Total:	1,030	2%	740	2%
Total:	56,350	100%	46,010	100%

Trips by Trip Purpose

24 Hours	From District		To District		Within District	
Work or related	27,180	29%	17,020	18%	14,550	9%
School	7,070	7%	2,500	3%	15,110	9%
Shopping	6,070	6%	9,150	10%	22,480	14%
Leisure	8,450	9%	10,590	11%	17,090	11%
Medical	2,520	3%	1,170	1%	2,660	2%
Pick-up / drive passenger	6,570	7%	5,470	6%	15,190	9%
Return Home	33,610	35%	45,620	48%	65,770	41%
Other	3,560	4%	3,590	4%	8,440	5%
Total:	95,030	100%	95,110	100%	161,290	100%

AM Peak (06:30 - 08:59)	From District		To District		Within District	
Work or related	18,030	69%	11,020	70%	7,430	24%
School	4,890	19%	2,280	15%	11,740	39%
Shopping	170	1%	320	2%	760	3%
Leisure	340	1%	400	3%	780	3%
Medical	330	1%	230	1%	350	1%
Pick-up / drive passenger	1,260	5%	580	4%	4,760	16%
Return Home	290	1%	380	2%	1,980	7%
Other	670	3%	430	3%	2,560	8%
Total:	25,980	100%	15,640	100%	30,360	100%

PM Peak (15:30 - 17:59)	From District		To District		Within District	
Work or related	390	2%	350	1%	930	2%
School	370	2%	0	0%	90	0%
Shopping	1,030	5%	1,910	7%	5,100	14%
Leisure	2,140	11%	3,080	11%	4,130	11%
Medical	230	1%	180	1%	400	1%
Pick-up / drive passenger	1,980	10%	1,980	7%	3,410	9%
Return Home	12,130	64%	20,550	71%	21,560	58%
Other	680	4%	860	3%	1,850	5%
Total:	18,950	100%	28,910	100%	37,470	100%

Peak Period (%)	Total:	% of 24 Hours	Within District (%)
24 Hours	351,430		46%
AM Peak Period	71,980	20%	42%
PM Peak Period	85,330	24%	44%

Trips by Primary Travel Mode

24 Hours	From District		To District		Within District	
Auto Driver	63,470	67%	63,830	67%	92,190	57%
Auto Passenger	15,220	16%	14,920	16%	31,880	20%
Transit	12,200	13%	12,270	13%	4,050	3%
Bicycle	360	0%	410	0%	960	1%
Walk	40	0%	50	0%	21,080	13%
Other	3,730	4%	3,660	4%	11,130	7%
Total:	95,020	100%	95,140	100%	161,290	100%

AM Peak (06:30 - 08:59)	From District		To District		Within District	
Auto Driver	15,360	59%	11,530	74%	13,630	45%
Auto Passenger	2,450	9%	1,160	7%	5,050	17%
Transit	6,230	24%	1,290	8%	1,210	4%
Bicycle	30	0%	80	1%	220	1%
Walk	0	0%	40	0%	5,730	19%
Other	1,900	7%	1,560	10%	4,510	15%
Total:	25,970	100%	15,660	100%	30,350	100%

PM Peak (15:30 - 17:59)	From District		To District		Within District	
Auto Driver	13,850	73%	17,660	61%	21,240	57%
Auto Passenger	3,240	17%	4,270	15%	8,570	23%
Transit	1,270	7%	5,980	21%	670	2%
Bicycle	40	0%	100	0%	260	1%
Walk	40	0%	0	0%	4,570	12%
Other	520	3%	910	3%	2,160	6%
Total:	18,960	100%	28,920	100%	37,470	100%

Avg Vehicle Occupancy	From District		To District		Within District	
24 Hours	1.24		1.23		1.35	
AM Peak Period	1.16		1.10		1.37	
PM Peak Period	1.23		1.24		1.40	

Transit Modal Split	From District		To District		Within District	
24 Hours	13%		13%		3%	
AM Peak Period	26%		9%		6%	
PM Peak Period	7%		21%		2%	

D COPE DRIVE
CROSS-SECTION



NOTE: The location of utilities is approximate only, the exact location should be determined by consulting the municipal authorities and utility companies concerned. The contractor shall prove the location of utilities and shall be responsible for adequate protection from damage.

No.	Description	By	Date (dd/mm/yy)

APPROVED REFUSED

THIS 28 DAY OF August, 2020

ERIN O'CONNELL, MCIP, RPP, MANAGER (A)
DEVELOPMENT REVIEW, WEST
PLANNING, INFRASTRUCTURE AND ECONOMIC
DEVELOPMENT DEPARTMENT, CITY OF OTTAWA





NOTE: The location of utilities is approximate only, the exact location should be determined by consulting the municipal authorities and utility companies concerned. The contractor shall prove the location of utilities and shall be responsible for adequate protection from damage.

No.	Description	By	Date (dd/mm/yy)


APPROVED REFUSED

THIS 28 DAY OF August, 2020

ERIN O'CONNELL, MCIP, RPP, MANAGER (A)
DEVELOPMENT REVIEW, WEST
PLANNING, INFRASTRUCTURE AND ECONOMIC
DEVELOPMENT DEPARTMENT, CITY OF OTTAWA



E RELATED TIA
EXCERPTS



LEGEND
 xx AM Peak Hour veh/h
 (yy) PM Peak Hour veh/h




Figure 8: Existing Vehicular Volumes AM(PM)

Figure 9: 'New' 2022 Site Trip Generation




Figure 10: 'New' 2024 Site Trip Generation




Figure 11: 'New' 2029 Site Trip Generation




Figure 12: Future Background 2022




Figure 13: Future Background 2024





Figure 14: Future Background 2029



3.2.3. OTHER DEVELOPMENTS

The additional traffic associated with the surrounding developments mentioned above in Section 2.1.3 is shown below in Figure 15, Figure 16, Figure 17, and Figure 18. These trips will be included in the foregoing traffic analysis. As a conservative estimate of the build-out of the area it has been assumed that all of the developments would occur by the 2022 horizon. See Appendix F for the trip distribution analysis for Figure 15, Figure 16, and Figure 17 and Appendix G for the trip distribution analysis for Figure 18.

3.2.4. TOTAL BACKGROUND TRAFFIC

With the addition of the 2% background traffic growth rate and the other area development traffic, the resultant 2022, 2024, and 2029 background traffic volumes are depicted in Figure 19, Figure 20, and Figure 21 respectively.

3.3. DEMAND RATIONALIZATION

The study area road network is expected to accommodate projected volumes. There are currently no anticipated capacity issues. The capacity of the roadways will be further explored in a more detailed review of the total projected traffic volumes and intersection design in the ensuing Strategy Report.

Figure 15: Fernbank Crossing, Phases 3 and 4




Figure 17: Lépine Fernbank, 1000 Robert Grant Ave




Figure 16: Blackstone Subdivision, Phases 4-8





Figure 18: CRT Lands, Phases 1 and 2



Source: CRT Lands Phase 1 and 2 Fernbank Community Transportation Letter, IBI Group

Figure 19: 2022 Total Background Traffic Volume




Figure 20: 2024 Total Background Traffic Volume





Figure 21: 2029 Total Background Traffic Volume



4. ANALYSIS

4.1. DEVELOPMENT DESIGN

Vehicle parking is proposed in a surface parking lot and bicycle parking is proposed in exterior bike racks. A total of 118 parking spaces will be provided at the initial build-out, meeting the minimum of spaces required outlined in the Parking By-Law. With regard to bicycle parking, 180 spaces will be provided which meets the City’s Bylaw Requirements. Additionally, an interim bus loop has been provided for school buses to pick-up/drop-off students and turn around on-site. Should the school expand and the road along the south frontage be built, the bus loop will be replaced with a through-roadway and additional parking lot.

Existing sidewalk facilities are provided along the Robert Grant Avenue frontage. The Cope Drive extension west of Robert Grant Avenue will include a sidewalk on the south side of the roadway and a MUP on the north side of the roadway.

Transit service within the area is provided by OC Transpo. Additional service and/or stop locations may be required as the school increases in size.


4.1.1. DESIGN FOR SUSTAINABLE MODES

Vehicle and Bicycle Parking

Refer to Section 4.2.1




NORTH



LEGEND

- Permitted Movements
- xxx (xxx)
xxx (xxx)
xxx (xxx) Weekday AM (PM) Peak Hour Vehicular Volume






LEGEND

↔ ↑ ↘ Permitted Movements

xxx (xxx) Weekday AM (PM) Peak Hour Vehicular Volume






LEGEND

- Permitted Movements
- xxx (xxx)
xxx (xxx)
xxx (xxx) Weekday AM (PM) Peak Hour Vehicular Volume

* Nominal volumes





LEGEND

- Permitted Movements
- xxx (xxx)
xxx (xxx)
xxx (xxx) Weekday AM (PM) Peak Hour Vehicular Volume

* Nominal volumes



F

TDM

CHECKLISTS

TDM-Supportive Development Design and Infrastructure Checklist:
Non-Residential Developments (office, institutional, retail or industrial)

Legend	
REQUIRED	The Official Plan or Zoning By-law provides related guidance that must be followed
BASIC	The measure is generally feasible and effective, and in most cases would benefit the development and its users
BETTER	The measure could maximize support for users of sustainable modes, and optimize development performance

TDM-supportive design & infrastructure measures: <i>Non-residential developments</i>		Check if completed & add descriptions, explanations or plan/drawing references
1. WALKING & CYCLING: ROUTES		
1.1 Building location & access points		
BASIC	1.1.1 Locate building close to the street, and do not locate parking areas between the street and building entrances	<input checked="" type="checkbox"/>
BASIC	1.1.2 Locate building entrances in order to minimize walking distances to sidewalks and transit stops/stations	<input checked="" type="checkbox"/>
BASIC	1.1.3 Locate building doors and windows to ensure visibility of pedestrians from the building, for their security and comfort	<input checked="" type="checkbox"/>
1.2 Facilities for walking & cycling		
REQUIRED	1.2.1 Provide convenient, direct access to stations or major stops along rapid transit routes within 600 metres; minimize walking distances from buildings to rapid transit; provide pedestrian-friendly, weather-protected (where possible) environment between rapid transit accesses and building entrances; ensure quality linkages from sidewalks through building entrances to integrated stops/stations (see <i>Official Plan policy 4.3.3</i>)	<input checked="" type="checkbox"/> Bus Stop #5527 is located within 400m of site.
REQUIRED	1.2.2 Provide safe, direct and attractive pedestrian access from public sidewalks to building entrances through such measures as: reducing distances between public sidewalks and major building entrances; providing walkways from public streets to major building entrances; within a site, providing walkways along the front of adjoining buildings, between adjacent buildings, and connecting areas where people may congregate, such as courtyards and transit stops; and providing weather protection through canopies, colonnades, and other design elements wherever possible (see <i>Official Plan policy 4.3.12</i>)	<input checked="" type="checkbox"/>

TDM-supportive design & infrastructure measures: <i>Non-residential developments</i>		Check if completed & add descriptions, explanations or plan/drawing references
REQUIRED	1.2.3 Provide sidewalks of smooth, well-drained walking surfaces of contrasting materials or treatments to differentiate pedestrian areas from vehicle areas, and provide marked pedestrian crosswalks at intersection sidewalks (<i>see Official Plan policy 4.3.10</i>)	<input checked="" type="checkbox"/>
REQUIRED	1.2.4 Make sidewalks and open space areas easily accessible through features such as gradual grade transition, depressed curbs at street corners and convenient access to extra-wide parking spaces and ramps (<i>see Official Plan policy 4.3.10</i>)	<input checked="" type="checkbox"/>
REQUIRED	1.2.5 Include adequately spaced inter-block/street cycling and pedestrian connections to facilitate travel by active transportation. Provide links to the existing or planned network of public sidewalks, multi-use pathways and on-road cycle routes. Where public sidewalks and multi-use pathways intersect with roads, consider providing traffic control devices to give priority to cyclists and pedestrians (<i>see Official Plan policy 4.3.11</i>)	<input checked="" type="checkbox"/>
BASIC	1.2.6 Provide safe, direct and attractive walking routes from building entrances to nearby transit stops	<input checked="" type="checkbox"/>
BASIC	1.2.7 Ensure that walking routes to transit stops are secure, visible, lighted, shaded and wind-protected wherever possible	<input checked="" type="checkbox"/>
BASIC	1.2.8 Design roads used for access or circulation by cyclists using a target operating speed of no more than 30 km/h, or provide a separated cycling facility	<input type="checkbox"/> N/A
1.3 Amenities for walking & cycling		
BASIC	1.3.1 Provide lighting, landscaping and benches along walking and cycling routes between building entrances and streets, sidewalks and trails	<input type="checkbox"/> N/A
BASIC	1.3.2 Provide wayfinding signage for site access (where required, e.g. when multiple buildings or entrances exist) and egress (where warranted, such as when directions to reach transit stops/stations, trails or other common destinations are not obvious)	<input type="checkbox"/> N/A

TDM-supportive design & infrastructure measures: <i>Non-residential developments</i>		Check if completed & add descriptions, explanations or plan/drawing references
2. WALKING & CYCLING: END-OF-TRIP FACILITIES		
2.1 Bicycle parking		
REQUIRED	2.1.1 Provide bicycle parking in highly visible and lighted areas, sheltered from the weather wherever possible (see <i>Official Plan policy 4.3.6</i>)	<input checked="" type="checkbox"/>
REQUIRED	2.1.2 Provide the number of bicycle parking spaces specified for various land uses in different parts of Ottawa; provide convenient access to main entrances or well-used areas (see <i>Zoning By-law Section 111</i>)	<input checked="" type="checkbox"/>
REQUIRED	2.1.3 Ensure that bicycle parking spaces and access aisles meet minimum dimensions; that no more than 50% of spaces are vertical spaces; and that parking racks are securely anchored (see <i>Zoning By-law Section 111</i>)	<input checked="" type="checkbox"/>
BASIC	2.1.4 Provide bicycle parking spaces equivalent to the expected number of commuter cyclists (assuming the cycling mode share target is met), plus the expected peak number of customer/visitor cyclists	<input checked="" type="checkbox"/>
BETTER	2.1.5 Provide bicycle parking spaces equivalent to the expected number of commuter and customer/visitor cyclists, plus an additional buffer (e.g. 25 percent extra) to encourage other cyclists and ensure adequate capacity in peak cycling season	<input type="checkbox"/>
2.2 Secure bicycle parking		
REQUIRED	2.2.1 Where more than 50 bicycle parking spaces are provided for a single office building, locate at least 25% of spaces within a building/structure, a secure area (e.g. supervised parking lot or enclosure) or bicycle lockers (see <i>Zoning By-law Section 111</i>)	<input type="checkbox"/> N/A
BETTER	2.2.2 Provide secure bicycle parking spaces equivalent to the expected number of commuter cyclists (assuming the cycling mode share target is met)	<input type="checkbox"/> N/A
2.3 Shower & change facilities		
BASIC	2.3.1 Provide shower and change facilities for the use of active commuters	<input type="checkbox"/>
BETTER	2.3.2 In addition to shower and change facilities, provide dedicated lockers, grooming stations, drying racks and laundry facilities for the use of active commuters	<input type="checkbox"/>
2.4 Bicycle repair station		
BETTER	2.4.1 Provide a permanent bike repair station, with commonly used tools and an air pump, adjacent to the main bicycle parking area (or secure bicycle parking area, if provided)	<input type="checkbox"/>

TDM-supportive design & infrastructure measures: <i>Non-residential developments</i>		Check if completed & add descriptions, explanations or plan/drawing references
3. TRANSIT		
3.1 Customer amenities		
BASIC	3.1.1 Provide shelters, lighting and benches at any on-site transit stops	<input type="checkbox"/> Nearest transit stop located off-site
BASIC	3.1.2 Where the site abuts an off-site transit stop and insufficient space exists for a transit shelter in the public right-of-way, protect land for a shelter and/or install a shelter	<input type="checkbox"/>
BETTER	3.1.3 Provide a secure and comfortable interior waiting area by integrating any on-site transit stops into the building	<input type="checkbox"/> N/A
4. RIDESHARING		
4.1 Pick-up & drop-off facilities		
BASIC	4.1.1 Provide a designated area for carpool drivers (plus taxis and ride-hailing services) to drop off or pick up passengers without using fire lanes or other no-stopping zones	<input type="checkbox"/>
4.2 Carpool parking		
BASIC	4.2.1 Provide signed parking spaces for carpools in a priority location close to a major building entrance, sufficient in number to accommodate the mode share target for carpools	<input type="checkbox"/> N/A
BETTER	4.2.2 At large developments, provide spaces for carpools in a separate, access-controlled parking area to simplify enforcement	<input type="checkbox"/> N/A
5. CARSHARING & BIKESHARING		
5.1 Carshare parking spaces		
BETTER	5.1.1 Provide carshare parking spaces in permitted non-residential zones, occupying either required or provided parking spaces (<i>see Zoning By-law Section 94</i>)	<input type="checkbox"/> N/A
5.2 Bikeshare station location		
BETTER	5.2.1 Provide a designated bikeshare station area near a major building entrance, preferably lighted and sheltered with a direct walkway connection	<input type="checkbox"/> N/A

TDM-supportive design & infrastructure measures: <i>Non-residential developments</i>		Check if completed & add descriptions, explanations or plan/drawing references
6. PARKING		
6.1 Number of parking spaces		
REQUIRED	6.1.1 Do not provide more parking than permitted by zoning, nor less than required by zoning, unless a variance is being applied for	<input type="checkbox"/> Parking meets zoning requirements
BASIC	6.1.2 Provide parking for long-term and short-term users that is consistent with mode share targets, considering the potential for visitors to use off-site public parking	<input type="checkbox"/> N/A
BASIC	6.1.3 Where a site features more than one use, provide shared parking and reduce the cumulative number of parking spaces accordingly (<i>see Zoning By-law Section 104</i>)	<input type="checkbox"/> N/A
BETTER	6.1.4 Reduce the minimum number of parking spaces required by zoning by one space for each 13 square metres of gross floor area provided as shower rooms, change rooms, locker rooms and other facilities for cyclists in conjunction with bicycle parking (<i>see Zoning By-law Section 111</i>)	<input type="checkbox"/> N/A
6.2 Separate long-term & short-term parking areas		
BETTER	6.2.1 Separate short-term and long-term parking areas using signage or physical barriers, to permit access controls and simplify enforcement (i.e. to discourage employees from parking in visitor spaces, and vice versa)	<input type="checkbox"/> N/A
7. OTHER		
7.1 On-site amenities to minimize off-site trips		
BETTER	7.1.1 Provide on-site amenities to minimize mid-day or mid-commute errands	<input type="checkbox"/> N/A

TDM Measures Checklist:
Non-Residential Developments (office, institutional, retail or industrial)

Legend	
BASIC	The measure is generally feasible and effective, and in most cases would benefit the development and its users
BETTER	The measure could maximize support for users of sustainable modes, and optimize development performance
★	The measure is one of the most dependably effective tools to encourage the use of sustainable modes

TDM measures: <i>Non-residential developments</i>		Check if proposed & add descriptions
1. TDM PROGRAM MANAGEMENT		
1.1 Program coordinator		
BASIC	★	1.1.1 Designate an internal coordinator, or contract with an external coordinator <input type="checkbox"/>
1.2 Travel surveys		
BETTER		1.2.1 Conduct periodic surveys to identify travel-related behaviours, attitudes, challenges and solutions, and to track progress <input type="checkbox"/>
2. WALKING AND CYCLING		
2.1 Information on walking/cycling routes & destinations		
BASIC		2.1.1 Display local area maps with walking/cycling access routes and key destinations at major entrances <input checked="" type="checkbox"/>
2.2 Bicycle skills training		
<i>Commuter travel</i>		
BETTER	★	2.2.1 Offer on-site cycling courses for commuters, or subsidize off-site courses <input type="checkbox"/>
2.3 Valet bike parking		
<i>Visitor travel</i>		
BETTER		2.3.1 Offer secure valet bike parking during public events when demand exceeds fixed supply (e.g. for festivals, concerts, games) <input type="checkbox"/>

TDM measures: <i>Non-residential developments</i>		Check if proposed & add descriptions
3. TRANSIT		
3.1 Transit information		
BASIC	3.1.1 Display relevant transit schedules and route maps at entrances	<input checked="" type="checkbox"/>
BASIC	3.1.2 Provide online links to OC Transpo and STO information	<input type="checkbox"/>
BETTER	3.1.3 Provide real-time arrival information display at entrances	<input type="checkbox"/>
3.2 Transit fare incentives		
<i>Commuter travel</i>		
BETTER	3.2.1 Offer preloaded PRESTO cards to encourage commuters to use transit	<input type="checkbox"/>
BETTER ★	3.2.2 Subsidize or reimburse monthly transit pass purchases by employees	<input type="checkbox"/>
<i>Visitor travel</i>		
BETTER	3.2.3 Arrange inclusion of same-day transit fare in price of tickets (e.g. for festivals, concerts, games)	<input type="checkbox"/>
3.3 Enhanced public transit service		
<i>Commuter travel</i>		
BETTER	3.3.1 Contract with OC Transpo to provide enhanced transit services (e.g. for shift changes, weekends)	<input type="checkbox"/>
<i>Visitor travel</i>		
BETTER	3.3.2 Contract with OC Transpo to provide enhanced transit services (e.g. for festivals, concerts, games)	<input type="checkbox"/>
3.4 Private transit service		
<i>Commuter travel</i>		
BETTER	3.4.1 Provide shuttle service when OC Transpo cannot offer sufficient quality or capacity to serve demand (e.g. for shift changes, weekends)	<input type="checkbox"/>
<i>Visitor travel</i>		
BETTER	3.4.2 Provide shuttle service when OC Transpo cannot offer sufficient quality or capacity to serve demand (e.g. for festivals, concerts, games)	<input type="checkbox"/>

TDM measures: <i>Non-residential developments</i>		Check if proposed & add descriptions
4. RIDESHARING		
4.1 Ridematching service		
<i>Commuter travel</i>		
BASIC	★ 4.1.1 Provide a dedicated ridematching portal at OttawaRideMatch.com	<input type="checkbox"/>
4.2 Carpool parking price incentives		
<i>Commuter travel</i>		
BETTER	4.2.1 Provide discounts on parking costs for registered carpools	<input type="checkbox"/>
4.3 Vanpool service		
<i>Commuter travel</i>		
BETTER	4.3.1 Provide a vanpooling service for long-distance commuters	<input type="checkbox"/>
5. CARSHARING & BIKESHARING		
5.1 Bikeshare stations & memberships		
BETTER	5.1.1 Contract with provider to install on-site bikeshare station for use by commuters and visitors	<input type="checkbox"/>
<i>Commuter travel</i>		
BETTER	5.1.2 Provide employees with bikeshare memberships for local business travel	<input type="checkbox"/>
5.2 Carshare vehicles & memberships		
<i>Commuter travel</i>		
BETTER	5.2.1 Contract with provider to install on-site carshare vehicles and promote their use by tenants	<input type="checkbox"/>
BETTER	5.2.2 Provide employees with carshare memberships for local business travel	<input type="checkbox"/>
6. PARKING		
6.1 Priced parking		
<i>Commuter travel</i>		
BASIC	★ 6.1.1 Charge for long-term parking (daily, weekly, monthly)	<input type="checkbox"/>
BASIC	6.1.2 Unbundle parking cost from lease rates at multi-tenant sites	<input type="checkbox"/>
<i>Visitor travel</i>		
BETTER	6.1.3 Charge for short-term parking (hourly)	<input type="checkbox"/>

TDM measures: <i>Non-residential developments</i>		Check if proposed & add descriptions
7. TDM MARKETING & COMMUNICATIONS		
7.1 Multimodal travel information		
<i>Commuter travel</i>		
BASIC ★	7.1.1 Provide a multimodal travel option information package to new/relocating employees and students	<input type="checkbox"/>
<i>Visitor travel</i>		
BETTER ★	7.1.2 Include multimodal travel option information in invitations or advertising that attract visitors or customers (e.g. for festivals, concerts, games)	<input type="checkbox"/>
7.2 Personalized trip planning		
<i>Commuter travel</i>		
BETTER ★	7.2.1 Offer personalized trip planning to new/relocating employees	<input type="checkbox"/>
7.3 Promotions		
<i>Commuter travel</i>		
BETTER	7.3.1 Deliver promotions and incentives to maintain awareness, build understanding, and encourage trial of sustainable modes	<input type="checkbox"/>
8. OTHER INCENTIVES & AMENITIES		
8.1 Emergency ride home		
<i>Commuter travel</i>		
BETTER ★	8.1.1 Provide emergency ride home service to non-driving commuters	<input type="checkbox"/>
8.2 Alternative work arrangements		
<i>Commuter travel</i>		
BASIC ★	8.2.1 Encourage flexible work hours	<input type="checkbox"/>
BETTER	8.2.2 Encourage compressed workweeks	<input type="checkbox"/>
BETTER ★	8.2.3 Encourage telework	<input type="checkbox"/>
8.3 Local business travel options		
<i>Commuter travel</i>		
BASIC ★	8.3.1 Provide local business travel options that minimize the need for employees to bring a personal car to work	<input type="checkbox"/>
8.4 Commuter incentives		
<i>Commuter travel</i>		
BETTER	8.4.1 Offer employees a taxable, mode-neutral commuting allowance	<input type="checkbox"/>
8.5 On-site amenities		
<i>Commuter travel</i>		
BETTER	8.5.1 Provide on-site amenities/services to minimize mid-day or mid-commute errands	<input type="checkbox"/>

G AUTOTURN
SWEPT PATHS

rue Dagenham St



HSU

Width : 2.60
 Track : 2.60
 Lock to Lock Time : 6.0
 Steering Angle : 40.0

meters

DROP-OFF AREA



2611 QUEENSVIEW DRIVE
 OTTAWA ONTARIO CANADA K2B 8K2
 TEL.: 613-829-2800 | WWW.WSP.COM

IS.	RV.	DATE	DESCRIPTION

SEAL:

CLIENT:  Conseil des écoles publiques de l'Est de l'Ontario

CLIENT REF. #: -

PROJECT: **ÉCOLE ÉLÉMENTAIRE KANATA - STITTSVILLE**

PROJECT NO: 219-00014-00
 DESIGNED BY: NS/NT
 DRAWN BY: NS
 CHECKED BY: AH
 DRAWING NO: 01

DATE / DATE: 2022-05-05

SCALE: 1:300

TITLE: **TURNING MOVEMENT ANALYSIS GARBAGE TRUCK**

DISCIPLINE: **TRANSPORTATION PLANNING**


ISSUE: --
 DATE OF: 2022-05-05

RV. # **0**

rue Dagengham St

Aerial Fire
REDO Toronto 2017 (CA)

Aerial Fire
REDO Toronto 2017 (CA)



Aerial Fire

	units
Width	: 2.54
Track	: 2.54
Lock to Lock Time	: 6.0
Steering Angle	: 37.0

DROP-OFF AREA

CONFLICT: FIRE TRUCK TRACKS OVER CURB

DROP-OFF AREA



2611 QUEENSVIEW DRIVE
OTTAWA ONTARIO CANADA K2B 8K2
TEL.: 613-829-2800 | WWW.WSP.COM

IS.	RV.	DATE	DESCRIPTION

SEAL:

CLIENT:  Conseil des écoles publiques de l'Est de l'Ontario

CLIENT REF. #: --

PROJECT: **ÉCOLE ÉLÉMENTAIRE KANATA - STITTSVILLE**

PROJECT NO: 219-00014-00

DESIGNED BY: NS/NT

DRAWN BY: NS

CHECKED BY: AH

DRAWING NO: 02

DATE / DATE: 2022-05-05

SCALE: 1:300

TITLE: **TURNING MOVEMENT ANALYSIS FIRE TRUCK**

DISCIPLINE: **TRANSPORTATION PLANNING**


ISSUE: --

DATE OF: **2022-05-09**

RV. # **0**

rue Dagengham St

2020 Blue Bird Vision
CITY - TRANSIT



2020 Blue Bird Vision

	meters
Width	: 2.44
Track	: 2.44
Lock to Lock Time	: 6.0
Steering Angle	: 49.8

DROP-OFF AREA

CONFLICT: BUS TRACKS OVER CURB

DROP-OFF AREA



2611 QUEENSVIEW DRIVE
OTTAWA ONTARIO CANADA K2B 8K2
TEL.: 613-829-2800 | WWW.WSP.COM

IS.	RV.	DATE	DESCRIPTION

SEAL:

CLIENT: Conseil des écoles publiques de l'Est de l'Ontario

CLIENT REF. #: --

PROJECT: **ÉCOLE ÉLÉMENTAIRE KANATA - STITTSVILLE**

PROJECT NO: 219-00014-00

DESIGNED BY: NS/NT

DRAWN BY: NS

CHECKED BY: AH

DRAWING NO: 02

DATE / DATE: 2022-05-05

SCALE: 1:300

TITLE: **TURNING MOVEMENT ANALYSIS SCHOOL BUS**

DISCIPLINE: **TRANSPORTATION PLANNING**

ISSUE: --

DATE OF: 2022-05-05

RV. # **0**

APPENDIX

H MMLOS SHEETS

Multi-Modal Level of Service - Intersections Form

Consultant	WSP Canada Inc.
Scenario	2022 Existing Conditions AM
Comments	

Project	Kanata-Sud School
Date	26-05-2022

To add intersections
 Select columns LMNO, right-click and *Copy*;
 Then select column P, right-click and *Insert Copied Cells*

INTERSECTIONS													
Crossing Side		Fernbank Rd / Robert Grant Ave				Intersection B				Intersection C			
		NORTH	SOUTH	EAST	WEST	NORTH	SOUTH	EAST	WEST	NORTH	SOUTH	EAST	WEST
Pedestrian	Lanes	3		3		3							
	Median	No Median - 2.4 m		No Median - 2.4 m		No Median - 2.4 m							
	Conflicting Left Turns	Protected		Permissive		No left turn / Prohib.							
	Conflicting Right Turns	Protected/ Permissive		No right turn		Permissive or yield control							
	Right Turns on Red (RTOR) ?	RTOR allowed		RTOR allowed		RTOR prohibited							
	Ped Signal Leading Interval?	No		Yes		Yes							
	Right Turn Channel	No Channel		No Channel		No Right Turn							
	Corner Radius	10-15m		10-15m		No Right Turn							
	Crosswalk Type	Std transverse markings		Std transverse markings		Std transverse markings							
	PETSI Score	78		77		93							
	Ped. Exposure to Traffic LoS	B		B		A							
	Cycle Length	119		119		119							
Effective Walk Time	35		13		13								
Average Pedestrian Delay	30		47		47								
Pedestrian Delay LoS	D		E		E								
Level of Service	D		E		E								
Approach From		NORTH	SOUTH	EAST	WEST	NORTH	SOUTH	EAST	WEST	NORTH	SOUTH	EAST	WEST
Bicycle	Bicycle Lane Arrangement on Approach	Curb Bike Lane, Cycletrack or MUP		Curb Bike Lane, Cycletrack or MUP		Curb Bike Lane, Cycletrack or MUP							
	IF Dedicated Right Turn Lane, THEN Right Turn Configuration, ELSE <blank>												
	Dedicated Right Turning Speed												
	Cyclist Through Movement Separated or Mixed Traffic	Not Applicable		Not Applicable		Not Applicable							
	Left Turning Cyclist	A		A		A							
	Level of Service	A		A		A							
Transit	Average Signal Delay	≤ 30 sec		≤ 10 sec									
	Level of Service	D		B									
Truck	Effective Corner Radius	10 - 15 m		10 - 15 m									
	Number of Receiving Lanes on Departure from Intersection	1		1									
Level of Service	E		E										
Auto	Volume to Capacity Ratio	0.0 - 0.60											
	Level of Service	A											

Multi-Modal Level of Service - Intersections Form

Consultant	WSP Canada Inc.
Scenario	2022 Existing Conditions PM
Comments	

Project	Kanata-Sud School
Date	26-05-2022

To add intersections
 Select columns LMNO, right-click and *Copy*;
 Then select column P, right-click and *Insert Copied Cells*

INTERSECTIONS													
Crossing Side		Fernbank Rd / Robert Grant Ave				Intersection B				Intersection C			
		NORTH	SOUTH	EAST	WEST	NORTH	SOUTH	EAST	WEST	NORTH	SOUTH	EAST	WEST
Pedestrian	Lanes	3		3		3							
	Median	No Median - 2.4 m		No Median - 2.4 m		No Median - 2.4 m							
	Conflicting Left Turns	Protected		Permissive		No left turn / Prohib.							
	Conflicting Right Turns	Protected/ Permissive		No right turn		Permissive or yield control							
	Right Turns on Red (RTOR) ?	RTOR allowed		RTOR allowed		RTOR prohibited							
	Ped Signal Leading Interval?	No		Yes		Yes							
	Right Turn Channel	No Channel		No Channel		No Right Turn							
	Corner Radius	10-15m		10-15m		No Right Turn							
	Crosswalk Type	Std transverse markings		Std transverse markings		Std transverse markings							
	PETSI Score	78		77		93							
	Ped. Exposure to Traffic LoS	B		B		A							
	Cycle Length	119		119		119							
Effective Walk Time	35		13		13								
Average Pedestrian Delay	30		47		47								
Pedestrian Delay LoS	D		E		E								
Level of Service	D		E		E								
		E				-				-			
Approach From		NORTH	SOUTH	EAST	WEST	NORTH	SOUTH	EAST	WEST	NORTH	SOUTH	EAST	WEST
Bicycle	Bicycle Lane Arrangement on Approach	Curb Bike Lane, Cycletrack or MUP		Curb Bike Lane, Cycletrack or MUP		Curb Bike Lane, Cycletrack or MUP							
	IF Dedicated Right Turn Lane, THEN Right Turn Configuration, ELSE <blank>												
	Dedicated Right Turning Speed												
	Cyclist Through Movement Separated or Mixed Traffic	Not Applicable		Not Applicable		Not Applicable							
	Separated or Mixed Traffic	Separated		Separated		Separated							
	Left Turn Approach	2-stage, LT box		2-stage, LT box		2-stage, LT box							
	Operating Speed	≥ 60 km/h		≥ 60 km/h		≥ 60 km/h							
Left Turning Cyclist	A		A		A								
Level of Service	A		A		A								
		A				-				-			
Transit	Average Signal Delay	≤ 40 sec		≤ 10 sec									
	Level of Service	E		B		-							
		E				-				-			
Truck	Effective Corner Radius	10 - 15 m		10 - 15 m									
	Number of Receiving Lanes on Departure from Intersection	1		1									
Level of Service	E		E		-								
		E				-				-			
Auto	Volume to Capacity Ratio	0.0 - 0.60											
	Level of Service	A											
		A				-				-			

Multi-Modal Level of Service - Intersections Form

Consultant	WSP Canada Inc.
Scenario	2028 Background Conditions AM
Comments	

Project	Kanata-Sud School
Date	26-05-2022

To add intersections
 Select columns LMNO, right-click and *Copy*;
 Then select column P, right-click and *Insert Copied Cells*

INTERSECTIONS													
Crossing Side		Fernbank Rd / Robert Grant Ave				Intersection B				Intersection C			
		NORTH	SOUTH	EAST	WEST	NORTH	SOUTH	EAST	WEST	NORTH	SOUTH	EAST	WEST
Pedestrian	Lanes	3		3		3							
	Median	No Median - 2.4 m		No Median - 2.4 m		No Median - 2.4 m							
	Conflicting Left Turns	Protected		Permissive		No left turn / Prohib.							
	Conflicting Right Turns	Protected/ Permissive		No right turn		Permissive or yield control							
	Right Turns on Red (RTOR) ?	RTOR allowed		RTOR allowed		RTOR prohibited							
	Ped Signal Leading Interval?	No		Yes		Yes							
	Right Turn Channel	No Channel		No Channel		No Right Turn							
	Corner Radius	10-15m		10-15m		No Right Turn							
	Crosswalk Type	Std transverse markings		Std transverse markings		Std transverse markings							
	PETSI Score	78		77		93							
	Ped. Exposure to Traffic LoS	B		B		A							
	Cycle Length	119		119		119							
Effective Walk Time	35		13		13								
Average Pedestrian Delay	30		47		47								
Pedestrian Delay LoS	D		E		E								
Level of Service	D		E		E								
Approach From		NORTH	SOUTH	EAST	WEST	NORTH	SOUTH	EAST	WEST	NORTH	SOUTH	EAST	WEST
Bicycle	Bicycle Lane Arrangement on Approach	Curb Bike Lane, Cycletrack or MUP		Curb Bike Lane, Cycletrack or MUP		Curb Bike Lane, Cycletrack or MUP							
	IF Dedicated Right Turn Lane, THEN Right Turn Configuration, ELSE <blank>												
	Dedicated Right Turning Speed												
	Cyclist Through Movement Separated or Mixed Traffic	Not Applicable		Not Applicable		Not Applicable							
	Left Turning Cyclist	A		A		A							
	Level of Service	A		A		A							
Transit	Average Signal Delay	≤ 30 sec		≤ 10 sec									
	Level of Service	D		B									
Truck	Effective Corner Radius	10 - 15 m		10 - 15 m									
	Number of Receiving Lanes on Departure from Intersection	1		1									
Level of Service	E		E										
Auto	Volume to Capacity Ratio	0.71 - 0.80											
	Level of Service	C											

Multi-Modal Level of Service - Intersections Form

Consultant	WSP Canada Inc.
Scenario	2028 Background Conditions PM
Comments	

Project	Kanata-Sud School
Date	26-05-2022

To add intersections
 Select columns LMNO, right-click and *Copy*;
 Then select column P, right-click and *Insert Copied Cells*

INTERSECTIONS		Fernbank Rd / Robert Grant Ave				Intersection B				Intersection C			
Crossing Side		NORTH	SOUTH	EAST	WEST	NORTH	SOUTH	EAST	WEST	NORTH	SOUTH	EAST	WEST
Pedestrian	Lanes	3		3		3							
	Median	No Median - 2.4 m		No Median - 2.4 m		No Median - 2.4 m							
	Conflicting Left Turns	Protected		Permissive		No left turn / Prohib.							
	Conflicting Right Turns	Protected/ Permissive		No right turn		Permissive or yield control							
	Right Turns on Red (RTOR) ?	RTOR allowed		RTOR allowed		RTOR prohibited							
	Ped Signal Leading Interval?	No		Yes		Yes							
	Right Turn Channel	No Channel		No Channel		No Right Turn							
	Corner Radius	10-15m		10-15m		No Right Turn							
	Crosswalk Type	Std transverse markings		Std transverse markings		Std transverse markings							
	PETSI Score	78		77		93							
	Ped. Exposure to Traffic LoS	B		B		A							
	Cycle Length	119		119		119							
Effective Walk Time	35		13		13								
Average Pedestrian Delay	30		47		47								
Pedestrian Delay LoS	D		E		E								
Level of Service	D		E		E								
Approach From		NORTH	SOUTH	EAST	WEST	NORTH	SOUTH	EAST	WEST	NORTH	SOUTH	EAST	WEST
Bicycle	Bicycle Lane Arrangement on Approach	Curb Bike Lane, Cycletrack or MUP		Curb Bike Lane, Cycletrack or MUP		Curb Bike Lane, Cycletrack or MUP							
	IF Dedicated Right Turn Lane, THEN Right Turn Configuration, ELSE <blank>												
	Dedicated Right Turning Speed												
	Cyclist Through Movement Separated or Mixed Traffic	Not Applicable		Not Applicable		Not Applicable							
	Level of Service	A		A		A							
	Level of Service	A		A		A							
Transit	Average Signal Delay	> 40 sec		≤ 10 sec									
	Level of Service	F		B									
Truck	Effective Corner Radius	10 - 15 m		10 - 15 m									
	Number of Receiving Lanes on Departure from Intersection	1		1									
Level of Service	E		E										
Auto	Volume to Capacity Ratio	0.81 - 0.90											
	Level of Service	D											

Multi-Modal Level of Service - Intersections Form

Consultant	WSP Canada Inc.
Scenario	2028 Horizon Conditions AM
Comments	

Project	Kanata-Sud School
Date	26-05-2022

To add intersections
 Select columns LMNO, right-click and *Copy*;
 Then select column P, right-click and *Insert Copied Cells*

INTERSECTIONS		Fernbank Rd / Robert Grant Ave				Intersection B				Intersection C			
Crossing Side		NORTH	SOUTH	EAST	WEST	NORTH	SOUTH	EAST	WEST	NORTH	SOUTH	EAST	WEST
Pedestrian	Lanes	3		3		3							
	Median	No Median - 2.4 m		No Median - 2.4 m		No Median - 2.4 m							
	Conflicting Left Turns	Protected		Permissive		No left turn / Prohib.							
	Conflicting Right Turns	Protected/ Permissive		No right turn		Permissive or yield control							
	Right Turns on Red (RTOR) ?	RTOR allowed		RTOR allowed		RTOR prohibited							
	Ped Signal Leading Interval?	No		Yes		Yes							
	Right Turn Channel	No Channel		No Channel		No Right Turn							
	Corner Radius	10-15m		10-15m		No Right Turn							
	Crosswalk Type	Std transverse markings		Std transverse markings		Std transverse markings							
	PETSI Score	78		77		93							
Ped. Exposure to Traffic LoS	B		B		A								
Cycle Length	119		119		119								
Effective Walk Time	29		13		13								
Average Pedestrian Delay	34		47		47								
Pedestrian Delay LoS	D		E		E								
Level of Service	D		E		E								
Approach From		NORTH	SOUTH	EAST	WEST	NORTH	SOUTH	EAST	WEST	NORTH	SOUTH	EAST	WEST
Bicycle	Bicycle Lane Arrangement on Approach	Curb Bike Lane, Cycletrack or MUP		Curb Bike Lane, Cycletrack or MUP		Curb Bike Lane, Cycletrack or MUP							
	IF Dedicated Right Turn Lane, THEN Right Turn Configuration, ELSE <blank>												
	Dedicated Right Turning Speed												
	Cyclist Through Movement Separated or Mixed Traffic	Not Applicable		Not Applicable		Not Applicable							
	Level of Service	A		A		A							
	Level of Service	A		A		A							
Transit	Average Signal Delay	≤ 20 sec		≤ 10 sec									
	Level of Service	C		B									
Truck	Effective Corner Radius	10 - 15 m		10 - 15 m									
	Number of Receiving Lanes on Departure from Intersection	1		1									
Level of Service	E		E										
Auto	Volume to Capacity Ratio	0.71 - 0.80											
	Level of Service	C											

Multi-Modal Level of Service - Intersections Form

Consultant	WSP Canada Inc.
Scenario	2028 Horizon Conditions PM
Comments	

Project	Kanata-Sud School
Date	26-05-2022

To add intersections
 Select columns LMNO, right-click and *Copy*;
 Then select column P, right-click and *Insert Copied Cells*

INTERSECTIONS		Fernbank Rd / Robert Grant Ave				Intersection B				Intersection C			
Crossing Side		NORTH	SOUTH	EAST	WEST	NORTH	SOUTH	EAST	WEST	NORTH	SOUTH	EAST	WEST
Pedestrian	Lanes	3		3		3							
	Median	No Median - 2.4 m		No Median - 2.4 m		No Median - 2.4 m							
	Conflicting Left Turns	Protected		Permissive		No left turn / Prohib.							
	Conflicting Right Turns	Protected/ Permissive		No right turn		Permissive or yield control							
	Right Turns on Red (RTOR) ?	RTOR allowed		RTOR allowed		RTOR prohibited							
	Ped Signal Leading Interval?	No		Yes		Yes							
	Right Turn Channel	No Channel		No Channel		No Right Turn							
	Corner Radius	10-15m		10-15m		No Right Turn							
	Crosswalk Type	Std transverse markings		Std transverse markings		Std transverse markings							
	PETSI Score	78		77		93							
	Ped. Exposure to Traffic LoS	B		B		A							
	Cycle Length	119		119		119							
Effective Walk Time	35		13		13								
Average Pedestrian Delay	30		47		47								
Pedestrian Delay LoS	D		E		E								
Level of Service	D		E		E								
Approach From		NORTH	SOUTH	EAST	WEST	NORTH	SOUTH	EAST	WEST	NORTH	SOUTH	EAST	WEST
Bicycle	Bicycle Lane Arrangement on Approach	Curb Bike Lane, Cycletrack or MUP		Curb Bike Lane, Cycletrack or MUP		Curb Bike Lane, Cycletrack or MUP							
	IF Dedicated Right Turn Lane, THEN Right Turn Configuration, ELSE <blank>												
	Dedicated Right Turning Speed												
	Cyclist Through Movement Separated or Mixed Traffic	Not Applicable		Not Applicable		Not Applicable							
	Left Turning Cyclist	A		A		A							
	Level of Service	A		A		A							
Transit	Average Signal Delay	≤ 20 sec		≤ 10 sec									
	Level of Service	C		B									
Truck	Effective Corner Radius	10 - 15 m		10 - 15 m									
	Number of Receiving Lanes on Departure from Intersection	1		1									
Level of Service	E		E										
Auto	Volume to Capacity Ratio	0.81 - 0.90											
	Level of Service	D											

Multi-Modal Level of Service - Segments Form

Consultant	WSP Canada Inc.
Scenario	2022 Existing Conditions
Comments	


Project	Kanata-Sud School
Date	26-05-2022

SEGMENTS		Cope Drive	Dagenham Street to Robert Grant Avenue			Section	Section	Section	Section	Section	Section
			EB	WB	-	4	5	6	7	8	9
Pedestrian	Sidewalk Width	F	no sidewalk	no sidewalk							
	Boulevard Width		n/a	n/a							
	Avg Daily Curb Lane Traffic Volume		≤ 3000	≤ 3000							
	Operating Speed		> 30 to 50 km/h	> 30 to 50 km/h							
	On-Street Parking		no	no							
	Exposure to Traffic PLoS		F	F	-	-	-	-	-	-	-
	Effective Sidewalk Width		1.2 m	1.2 m							
Pedestrian Volume	250 ped/hr	250 ped/hr									
Crowding PLoS	B	B	-	-	-	-	-	-	-		
Level of Service	F	F	-	-	-	-	-	-	-		
Bicycle	Type of Cycling Facility	E	Mixed Traffic	Mixed Traffic							
	Number of Travel Lanes		2-3 lanes total	2-3 lanes total							
	Operating Speed		≥ 50 to 60 km/h	≥ 50 to 60 km/h							
	# of Lanes & Operating Speed LoS		E	E	-	-	-	-	-	-	
	Bike Lane (+ Parking Lane) Width										
	Bike Lane Width LoS		-	-	-	-	-	-	-	-	
	Bike Lane Blockages										
	Blockage LoS		-	-	-	-	-	-	-	-	
	Median Refuge Width (no median = < 1.8 m)		< 1.8 m refuge	< 1.8 m refuge							
	No. of Lanes at Unsignalized Crossing		≤ 3 lanes	≤ 3 lanes							
Sidestreet Operating Speed	≤ 40 km/h	≤ 40 km/h									
Unsignalized Crossing - Lowest LoS	A	A	-	-	-	-	-	-			
Level of Service	E	E	-	-	-	-	-	-			
Transit	Facility Type	-									
	Friction or Ratio Transit:Posted Speed										
Level of Service	-	-	-	-	-	-	-	-			
Truck	Truck Lane Width	-									
	Travel Lanes per Direction										
Level of Service	-	-	-	-	-	-	-	-			

APPENDIX



SYNCHRO AND SIDRA RESULTS




Lane Group	EBL	EBT	WBT	WBR	SBL	SBR	Ø9
Lane Configurations	↖	↗	↖	↗	↖	↗	
Traffic Volume (vph)	28	314	196	157	161	26	
Future Volume (vph)	28	314	196	157	161	26	
Satd. Flow (prot)	1676	1765	1765	1500	1676	1500	
Flt Permitted	0.950				0.950		
Satd. Flow (perm)	1676	1765	1765	1500	1676	1500	
Satd. Flow (RTOR)				174			29
Peak Hour Factor	0.90	0.90	0.90	0.90	0.90	0.90	
Shared Lane Traffic (%)							
Lane Group Flow (vph)	31	349	218	174	179	29	
Turn Type	Prot	NA	NA	custom	Perm	Perm	
Protected Phases	7	9 7 10	9 10				9
Permitted Phases				10	6	6	
Minimum Initial (s)	5.0			5.0	5.0	5.0	2.0
Minimum Split (s)	11.2			23.2	30.2	30.2	5.0
Total Split (s)	26.2			51.6	36.0	36.0	5.0
Total Split (%)	22.1%			43.4%	30.3%	30.3%	4%
Maximum Green (s)	20.0			45.4	30.0	30.0	3.0
Yellow Time (s)	4.6			4.6	3.3	3.3	2.0
All-Red Time (s)	1.6			1.6	2.7	2.7	0.0
Total Lost Time (s)	6.2			6.2	6.0	6.0	
Lead/Lag				Lag			Lead
Lead-Lag Optimize?				Yes			Yes
Vehicle Extension (s)	3.0			3.0	3.0	3.0	3.0
Recall Mode	None			None	Max	Max	None
Walk Time (s)				7.0	7.0	7.0	
Flash Dont Walk (s)				10.0	17.0	17.0	
Pedestrian Calls (#/hr)				5	5	5	
Act Effct Green (s)	14.9	43.2	22.1	12.8	30.3	30.3	
Actuated g/C Ratio	0.18	0.53	0.27	0.16	0.37	0.37	
v/c Ratio	0.10	0.37	0.46	0.46	0.29	0.05	
Control Delay	29.8	12.1	28.3	9.3	21.8	8.3	
Queue Delay	0.0	0.0	0.0	0.0	0.0	0.0	
Total Delay	29.8	12.1	28.3	9.3	21.8	8.3	
LOS	C	B	C	A	C	A	
Approach Delay		13.6	19.9		19.9		
Approach LOS		B	B		B		


Intersection Summary

Cycle Length: 118.8
 Actuated Cycle Length: 81.6
 Control Type: Actuated-Uncoordinated
 Maximum v/c Ratio: 0.46
 Intersection Signal Delay: 17.4
 Intersection Capacity Utilization 38.0%
 Analysis Period (min) 15

Intersection LOS: B
 ICU Level of Service A

Splits and Phases: 2: Fernbank Rd & Robert Grant Ave







Lane Group	EBL	EBT	WBT	WBR	SBL	SBR	Ø9
Lane Configurations	↖	↗	↖	↗	↖	↗	
Traffic Volume (vph)	17	260	441	176	173	25	
Future Volume (vph)	17	260	441	176	173	25	
Satd. Flow (prot)	1676	1765	1765	1500	1676	1500	
Flt Permitted	0.950				0.950		
Satd. Flow (perm)	1676	1765	1765	1500	1676	1500	
Satd. Flow (RTOR)				196			28
Peak Hour Factor	0.90	0.90	0.90	0.90	0.90	0.90	
Shared Lane Traffic (%)							
Lane Group Flow (vph)	19	289	490	196	192	28	
Turn Type	Prot	NA	NA	custom	Perm	Perm	
Protected Phases	7	9 7 10	9 10				9
Permitted Phases				10	6	6	
Minimum Initial (s)	5.0			5.0	5.0	5.0	2.0
Minimum Split (s)	11.2			23.2	30.2	30.2	5.0
Total Split (s)	26.2			51.6	36.0	36.0	5.0
Total Split (%)	22.1%			43.4%	30.3%	30.3%	4%
Maximum Green (s)	20.0			45.4	30.0	30.0	3.0
Yellow Time (s)	4.6			4.6	3.3	3.3	2.0
All-Red Time (s)	1.6			1.6	2.7	2.7	0.0
Total Lost Time (s)	6.2			6.2	6.0	6.0	
Lead/Lag				Lag			Lead
Lead-Lag Optimize?				Yes			Yes
Vehicle Extension (s)	3.0			3.0	3.0	3.0	3.0
Recall Mode	None			None	Max	Max	None
Walk Time (s)				7.0	7.0	7.0	
Flash Dont Walk (s)				10.0	17.0	17.0	
Pedestrian Calls (#/hr)				5	5	5	
Act Effct Green (s)	12.9	58.1	38.9	29.5	30.5	30.5	
Actuated g/C Ratio	0.13	0.60	0.40	0.31	0.32	0.32	
v/c Ratio	0.08	0.27	0.69	0.33	0.36	0.06	
Control Delay	41.1	9.4	29.4	4.9	31.3	11.4	
Queue Delay	0.0	0.0	0.0	0.0	0.0	0.0	
Total Delay	41.1	9.4	29.4	4.9	31.3	11.4	
LOS	D	A	C	A	C	B	
Approach Delay		11.4	22.4		28.7		
Approach LOS		B	C		C		

Intersection Summary

Cycle Length: 118.8
 Actuated Cycle Length: 96.7
 Control Type: Actuated-Uncoordinated
 Maximum v/c Ratio: 0.69
 Intersection Signal Delay: 20.8
 Intersection Capacity Utilization 43.0%
 Analysis Period (min) 15
 Intersection LOS: C
 ICU Level of Service A

Splits and Phases: 2: Fernbank Rd & Robert Grant Ave






Lane Group	EBL	EBT	WBT	WBR	SBL	SBR	Ø9
Lane Configurations	↖	↗	↖	↗	↖	↗	
Traffic Volume (vph)	38	320	200	173	172	32	
Future Volume (vph)	38	320	200	173	172	32	
Satd. Flow (prot)	1676	1765	1765	1500	1676	1500	
Flt Permitted	0.950				0.950		
Satd. Flow (perm)	1676	1765	1765	1500	1676	1500	
Satd. Flow (RTOR)				173		32	
Peak Hour Factor	1.00	1.00	1.00	1.00	1.00	1.00	
Shared Lane Traffic (%)							
Lane Group Flow (vph)	38	320	200	173	172	32	
Turn Type	Prot	NA	NA	custom	Perm	Perm	
Protected Phases	7	9 7 10	9 10				9
Permitted Phases				10	6	6	
Total Split (s)	26.2			51.6	36.0	36.0	5.0
Total Lost Time (s)	6.2			6.2	6.0	6.0	
Act Effct Green (s)	13.9	41.2	21.1	11.8	30.2	30.2	
Actuated g/C Ratio	0.17	0.52	0.27	0.15	0.38	0.38	
v/c Ratio	0.13	0.35	0.43	0.47	0.27	0.05	
Control Delay	29.9	12.1	27.6	9.7	20.4	7.8	
Queue Delay	0.0	0.0	0.0	0.0	0.0	0.0	
Total Delay	29.9	12.1	27.6	9.7	20.4	7.8	
LOS	C	B	C	A	C	A	
Approach Delay		14.0	19.3		18.4		
Approach LOS		B	B		B		

















Intersection Summary


Cycle Length: 118.8
 Actuated Cycle Length: 79.5
 Control Type: Actuated-Uncoordinated
 Maximum v/c Ratio: 0.47
 Intersection Signal Delay: 17.1
 Intersection Capacity Utilization 38.8%
 Analysis Period (min) 15

Intersection LOS: B
 ICU Level of Service A


Splits and Phases: 2: Fernbank Rd & Robert Grant Ave



												
Lane Group	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations												
Traffic Volume (vph)	0	3	6	21	0	25	5	220	26	19	126	0
Future Volume (vph)	0	3	6	21	0	25	5	220	26	19	126	0
Satd. Flow (prot)	0	1606	0	0	1600	0	0	1738	0	0	1752	0
Flt Permitted					0.978			0.999			0.993	
Satd. Flow (perm)	0	1606	0	0	1600	0	0	1738	0	0	1752	0
Peak Hour Factor	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
Shared Lane Traffic (%)												
Lane Group Flow (vph)	0	9	0	0	46	0	0	251	0	0	145	0
Sign Control		Yield			Yield			Yield			Yield	
Intersection Summary												
Control Type: Roundabout												
Intersection Capacity Utilization 34.3%						ICU Level of Service A						
Analysis Period (min) 15												



Lane Group	EBL	EBT	WBT	WBR	SBL	SBR
Lane Configurations		↕	↕		↕	
Traffic Volume (vph)	0	0	0	0	0	0
Future Volume (vph)	0	0	0	0	0	0
Satd. Flow (prot)	0	1765	1765	0	1765	0
Flt Permitted						
Satd. Flow (perm)	0	1765	1765	0	1765	0
Peak Hour Factor	1.00	1.00	1.00	1.00	1.00	1.00
Shared Lane Traffic (%)						
Lane Group Flow (vph)	0	0	0	0	0	0
Sign Control		Stop	Stop		Stop	
Intersection Summary						
Control Type: Unsignalized						
Intersection Capacity Utilization 0.0%			ICU Level of Service A			
Analysis Period (min) 15						





Lane Group	EBL	EBT	WBT	WBR	SBL	SBR	Ø9
Lane Configurations	↖	↗	↖	↗	↖	↗	
Traffic Volume (vph)	21	265	450	186	185	32	
Future Volume (vph)	21	265	450	186	185	32	
Satd. Flow (prot)	1676	1765	1765	1500	1676	1500	
Flt Permitted	0.950				0.950		
Satd. Flow (perm)	1676	1765	1765	1500	1676	1500	
Satd. Flow (RTOR)				186			32
Peak Hour Factor	1.00	1.00	1.00	1.00	1.00	1.00	
Shared Lane Traffic (%)							
Lane Group Flow (vph)	21	265	450	186	185	32	
Turn Type	Prot	NA	NA	custom	Perm	Perm	
Protected Phases	7	9 7 10	9 10				9
Permitted Phases				10	6	6	
Total Split (s)	26.2			51.6	36.0	36.0	5.0
Total Lost Time (s)	6.2			6.2	6.0	6.0	
Act Effct Green (s)	12.2	54.1	35.6	26.3	30.4	30.4	
Actuated g/C Ratio	0.13	0.58	0.38	0.28	0.33	0.33	
v/c Ratio	0.10	0.26	0.66	0.33	0.34	0.06	
Control Delay	39.6	9.6	28.6	5.3	28.6	10.2	
Queue Delay	0.0	0.0	0.0	0.0	0.0	0.0	
Total Delay	39.6	9.6	28.6	5.3	28.6	10.2	
LOS	D	A	C	A	C	B	
Approach Delay		11.8	21.8		25.9		
Approach LOS		B	C		C		

Intersection Summary

Cycle Length: 118.8
 Actuated Cycle Length: 92.6
 Control Type: Actuated-Uncoordinated
 Maximum v/c Ratio: 0.66
 Intersection Signal Delay: 20.1 Intersection LOS: C
 Intersection Capacity Utilization 44.2% ICU Level of Service A
 Analysis Period (min) 15

Splits and Phases: 2: Fernbank Rd & Robert Grant Ave






Lane Group	EBL	EBT	WBT	WBR	SBL	SBR	Ø9
Lane Configurations	↖	↗	↖	↗	↖	↗	
Traffic Volume (vph)	43	320	200	195	187	36	
Future Volume (vph)	43	320	200	195	187	36	
Satd. Flow (prot)	1676	1765	1765	1500	1676	1500	
Flt Permitted	0.950				0.950		
Satd. Flow (perm)	1676	1765	1765	1500	1676	1500	
Satd. Flow (RTOR)				195			36
Peak Hour Factor	1.00	1.00	1.00	1.00	1.00	1.00	
Shared Lane Traffic (%)							
Lane Group Flow (vph)	43	320	200	195	187	36	
Turn Type	Prot	NA	NA	custom	Perm	Perm	
Protected Phases	7	9 7 10	9 10				9
Permitted Phases				10	6	6	
Total Split (s)	26.2			51.6	36.0	36.0	5.0
Total Lost Time (s)	6.2			6.2	6.0	6.0	
Act Effct Green (s)	13.9	41.2	21.1	11.8	30.2	30.2	
Actuated g/C Ratio	0.17	0.52	0.27	0.15	0.38	0.38	
v/c Ratio	0.15	0.35	0.43	0.50	0.29	0.06	
Control Delay	30.2	12.1	27.6	9.7	20.7	7.4	
Queue Delay	0.0	0.0	0.0	0.0	0.0	0.0	
Total Delay	30.2	12.1	27.6	9.7	20.7	7.4	
LOS	C	B	C	A	C	A	
Approach Delay		14.3	18.8		18.5		
Approach LOS		B	B		B		


Intersection Summary

Cycle Length: 118.8
 Actuated Cycle Length: 79.5
 Control Type: Actuated-Uncoordinated
 Maximum v/c Ratio: 0.50
 Intersection Signal Delay: 17.0
 Intersection Capacity Utilization 39.7%
 Analysis Period (min) 15

Intersection LOS: B
 ICU Level of Service A

Splits and Phases: 2: Fernbank Rd & Robert Grant Ave







Lane Group	EBL	EBT	WBT	WBR	SBL	SBR	Ø9
Lane Configurations	↖	↗	↖	↗	↖	↗	
Traffic Volume (vph)	23	265	450	194	197	35	
Future Volume (vph)	23	265	450	194	197	35	
Satd. Flow (prot)	1676	1765	1765	1500	1676	1500	
Flt Permitted	0.950				0.950		
Satd. Flow (perm)	1676	1765	1765	1500	1676	1500	
Satd. Flow (RTOR)				194		35	
Peak Hour Factor	1.00	1.00	1.00	1.00	1.00	1.00	
Shared Lane Traffic (%)							
Lane Group Flow (vph)	23	265	450	194	197	35	
Turn Type	Prot	NA	NA	custom	Perm	Perm	
Protected Phases	7	9 7 10	9 10				9
Permitted Phases				10	6	6	
Total Split (s)	26.2			51.6	36.0	36.0	5.0
Total Lost Time (s)	6.2			6.2	6.0	6.0	
Act Effct Green (s)	12.2	54.1	35.6	26.3	30.4	30.4	
Actuated g/C Ratio	0.13	0.58	0.38	0.28	0.33	0.33	
v/c Ratio	0.10	0.26	0.66	0.34	0.36	0.07	
Control Delay	39.6	9.6	28.6	5.3	28.9	9.9	
Queue Delay	0.0	0.0	0.0	0.0	0.0	0.0	
Total Delay	39.6	9.6	28.6	5.3	28.9	9.9	
LOS	D	A	C	A	C	A	
Approach Delay		12.0	21.6		26.0		
Approach LOS		B	C		C		

Intersection Summary

Cycle Length: 118.8
 Actuated Cycle Length: 92.6
 Control Type: Actuated-Uncoordinated
 Maximum v/c Ratio: 0.66
 Intersection Signal Delay: 20.1 Intersection LOS: C
 Intersection Capacity Utilization 44.9% ICU Level of Service A
 Analysis Period (min) 15

Splits and Phases: 2: Fernbank Rd & Robert Grant Ave






Lane Group	EBL	EBT	WBT	WBR	SBL	SBR	Ø9
Lane Configurations	↖	↗	↖	↗	↖	↗	
Traffic Volume (vph)	74	479	324	334	404	75	
Future Volume (vph)	74	479	324	334	404	75	
Satd. Flow (prot)	1676	1765	1765	1500	1676	1500	
Flt Permitted	0.950				0.950		
Satd. Flow (perm)	1676	1765	1765	1500	1676	1500	
Satd. Flow (RTOR)				334		75	
Peak Hour Factor	1.00	1.00	1.00	1.00	1.00	1.00	
Shared Lane Traffic (%)							
Lane Group Flow (vph)	74	479	324	334	404	75	
Turn Type	Prot	NA	NA	custom	Perm	Perm	
Protected Phases	7	9 7 10	9 10				9
Permitted Phases				10	6	6	
Total Split (s)	26.2			51.6	36.0	36.0	5.0
Total Lost Time (s)	6.2			6.2	6.0	6.0	
Act Effct Green (s)	18.1	54.7	30.3	21.0	30.3	30.3	
Actuated g/C Ratio	0.19	0.59	0.33	0.23	0.33	0.33	
v/c Ratio	0.23	0.46	0.56	0.56	0.74	0.14	
Control Delay	35.7	12.2	29.9	7.2	39.9	7.5	
Queue Delay	0.0	0.0	0.0	0.0	0.0	0.0	
Total Delay	35.7	12.2	29.9	7.2	39.9	7.5	
LOS	D	B	C	A	D	A	
Approach Delay		15.3	18.4		34.8		
Approach LOS		B	B		C		


Intersection Summary

Cycle Length: 118.8
 Actuated Cycle Length: 93.1
 Control Type: Actuated-Uncoordinated
 Maximum v/c Ratio: 0.74
 Intersection Signal Delay: 22.0
 Intersection Capacity Utilization 59.5%
 Analysis Period (min) 15

Intersection LOS: C
 ICU Level of Service B

Splits and Phases: 2: Fernbank Rd & Robert Grant Ave






Lane Group	EBL	EBT	WBT	WBR	SBL	SBR	Ø9
Lane Configurations	↖	↗	↖	↗	↖	↗	
Traffic Volume (vph)	61	384	628	439	380	66	
Future Volume (vph)	61	384	628	439	380	66	
Satd. Flow (prot)	1676	1765	1765	1500	1676	1500	
Flt Permitted	0.950				0.950		
Satd. Flow (perm)	1676	1765	1765	1500	1676	1500	
Satd. Flow (RTOR)				439		66	
Peak Hour Factor	1.00	1.00	1.00	1.00	1.00	1.00	
Shared Lane Traffic (%)							
Lane Group Flow (vph)	61	384	628	439	380	66	
Turn Type	Prot	NA	NA	custom	Perm	Perm	
Protected Phases	7	9 7 10	9 10				9
Permitted Phases				10	6	6	
Total Split (s)	26.2			51.6	36.0	36.0	5.0
Total Lost Time (s)	6.2			6.2	6.0	6.0	
Act Effct Green (s)	15.8	70.6	48.6	39.3	30.3	30.3	
Actuated g/C Ratio	0.14	0.65	0.45	0.36	0.28	0.28	
v/c Ratio	0.25	0.34	0.80	0.53	0.82	0.14	
Control Delay	45.9	9.2	35.1	4.9	54.3	9.2	
Queue Delay	0.0	0.0	0.0	0.0	0.0	0.0	
Total Delay	45.9	9.2	35.1	4.9	54.3	9.2	
LOS	D	A	D	A	D	A	
Approach Delay		14.3	22.7		47.6		
Approach LOS		B	C		D		


Intersection Summary

Cycle Length: 118.8
 Actuated Cycle Length: 109
 Control Type: Actuated-Uncoordinated
 Maximum v/c Ratio: 0.82
 Intersection Signal Delay: 26.4
 Intersection Capacity Utilization 74.8%
 Analysis Period (min) 15

Intersection LOS: C
 ICU Level of Service D

Splits and Phases: 2: Fernbank Rd & Robert Grant Ave





Lane Group	EBL	EBT	WBT	WBR	SBL	SBR
Lane Configurations	↖	↗	↗	↖	↖	↖
Traffic Volume (vph)	79	479	324	356	419	79
Future Volume (vph)	79	479	324	356	419	79
Satd. Flow (prot)	1676	1765	1765	1500	1676	1500
Flt Permitted	0.950				0.950	
Satd. Flow (perm)	1676	1765	1765	1500	1676	1500
Satd. Flow (RTOR)				356		79
Peak Hour Factor	1.00	1.00	1.00	1.00	1.00	1.00
Shared Lane Traffic (%)						
Lane Group Flow (vph)	79	479	324	356	419	79
Turn Type	Prot	NA	NA	Perm	Perm	Perm
Protected Phases	7	4	8			
Permitted Phases				8	6	6
Total Split (s)	17.0	52.0	35.0	35.0	48.0	48.0
Total Lost Time (s)	6.2	4.5	4.5	4.5	6.0	6.0
Act Effct Green (s)	9.2	38.1	25.1	25.1	51.4	51.4
Actuated g/C Ratio	0.09	0.38	0.25	0.25	0.51	0.51
v/c Ratio	0.51	0.71	0.73	0.55	0.49	0.10
Control Delay	54.7	31.6	44.4	6.6	20.4	4.4
Queue Delay	0.0	0.0	0.0	0.0	0.0	0.0
Total Delay	54.7	31.6	44.4	6.6	20.4	4.4
LOS	D	C	D	A	C	A
Approach Delay		34.9	24.6		17.8	
Approach LOS		C	C		B	


Intersection Summary


Cycle Length: 100
 Actuated Cycle Length: 100
 Offset: 0 (0%), Referenced to phase 2: and 6:SBL, Start of Green
 Control Type: Actuated-Coordinated
 Maximum v/c Ratio: 0.73
 Intersection Signal Delay: 26.0
 Intersection Capacity Utilization 61.0%
 Analysis Period (min) 15

Intersection LOS: C

ICU Level of Service B

Splits and Phases: 2: Fernbank Rd & Robert Grant Ave






Lane Group	EBL	EBT	WBT	WBR	SBL	SBR
Lane Configurations						
Traffic Volume (vph)	63	384	628	447	392	69
Future Volume (vph)	63	384	628	447	392	69
Satd. Flow (prot)	1676	1765	1765	1500	1676	1500
Flt Permitted	0.139				0.950	
Satd. Flow (perm)	245	1765	1765	1500	1676	1500
Satd. Flow (RTOR)				447		69
Peak Hour Factor	1.00	1.00	1.00	1.00	1.00	1.00
Shared Lane Traffic (%)						
Lane Group Flow (vph)	63	384	628	447	392	69
Turn Type	pm+pt	NA	NA	Perm	Perm	Perm
Protected Phases	7	4	8			
Permitted Phases	4			8	6	6
Total Split (s)	10.0	59.0	49.0	49.0	41.0	41.0
Total Lost Time (s)	2.0	6.2	6.2	6.2	6.0	6.0
Act Effct Green (s)	51.8	47.6	39.7	39.7	40.2	40.2
Actuated g/C Ratio	0.52	0.48	0.40	0.40	0.40	0.40
v/c Ratio	0.27	0.46	0.90	0.52	0.58	0.11
Control Delay	13.0	18.6	44.8	4.1	29.6	6.1
Queue Delay	0.0	0.0	0.0	0.0	0.0	0.0
Total Delay	13.0	18.6	44.8	4.1	29.6	6.1
LOS	B	B	D	A	C	A
Approach Delay		17.8	27.9		26.1	
Approach LOS		B	C		C	

Intersection Summary

Cycle Length: 100	
Actuated Cycle Length: 100	
Offset: 0 (0%), Referenced to phase 2: and 6:SBL, Start of Green	
Control Type: Actuated-Coordinated	
Maximum v/c Ratio: 0.90	
Intersection Signal Delay: 25.2	Intersection LOS: C
Intersection Capacity Utilization 75.5%	ICU Level of Service D
Analysis Period (min) 15	

Splits and Phases: 2: Fernbank Rd & Robert Grant Ave



MOVEMENT SUMMARY

 Site: 101 [Abbott Street East / Robert Grant Avenue AM]

Existing Conditions AM
Roundabout

Movement Performance - Vehicles											
Mov ID	OD Mov	Demand Total veh/h	Flows HV %	Deg. Satn v/c	Average Delay sec	Level of Service	95% Back of Queue Vehicles veh	Distance m	Prop. Queued	Effective Stop Rate per veh	Average Speed km/h
South: Robert Grant Avenue											
1	L2	286	2.0	0.376	6.2	LOS A	2.4	17.2	0.14	0.04	47.6
3	R2	213	2.0	0.376	6.2	LOS A	2.4	17.2	0.14	0.04	46.2
Approach		499	2.0	0.376	6.2	LOS A	2.4	17.2	0.14	0.04	47.0
East: Abott Street East											
4	L2	79	2.0	0.131	4.7	LOS A	0.6	4.1	0.43	0.31	48.2
5	T1	54	2.0	0.131	4.7	LOS A	0.6	4.1	0.43	0.31	45.3
Approach		133	2.0	0.131	4.7	LOS A	0.6	4.1	0.43	0.31	46.9
West: Abott Street East											
11	T1	21	2.0	0.140	4.0	LOS A	0.7	4.7	0.22	0.10	47.1
12	R2	154	2.0	0.140	4.0	LOS A	0.7	4.7	0.22	0.10	49.1
Approach		175	2.0	0.140	4.0	LOS A	0.7	4.7	0.22	0.10	48.9
All Vehicles		807	2.0	0.376	5.5	LOS A	2.4	17.2	0.20	0.10	47.4

Site Level of Service (LOS) Method: Delay & v/c (HCM 6). Site LOS Method is specified in the Parameter Settings dialog (Site tab).

Roundabout LOS Method: Same as Sign Control.

Vehicle movement LOS values are based on average delay and v/c ratio (degree of saturation) per movement.

LOS F will result if v/c > 1 irrespective of movement delay value (does not apply for approaches and intersection).

Intersection and Approach LOS values are based on average delay for all movements (v/c not used as specified in HCM 6).

Roundabout Capacity Model: US HCM 6.

HCM Delay Formula option is used. Control Delay does not include Geometric Delay since Exclude Geometric Delay option applies.

Gap-Acceptance Capacity: Traditional M1.

HV (%) values are calculated for All Movement Classes of All Heavy Vehicle Model Designation.

SIDRA INTERSECTION 7.0 | Copyright © 2000-2017 Akcelik and Associates Pty Ltd | sidrasolutions.com

Organisation: WSP CANADA INC. | Processed: May 12, 2022 12:30:29 AM

Project: L:\W.O. # Directories\219-00014-00_CEPEO Kanata-Sud School TIA\04 Technical\01 Analysis\SIDRA\Existing Conditions AM.sip7

MOVEMENT SUMMARY

 Site: 101 [Abbott Street East / Robert Grant Avenue PM]

Existing Conditions PM
Roundabout

Movement Performance - Vehicles											
Mov ID	OD Mov	Demand Total veh/h	Flows HV %	Deg. Satn v/c	Average Delay sec	Level of Service	95% Back of Queue Vehicles veh	Prop. Queued Distance m	Effective Stop Rate per veh	Average Speed km/h	
South: Robert Grant Avenue											
1	L2	200	2.0	0.252	5.0	LOS A	1.3	9.6	0.19	0.07	48.3
3	R2	125	2.0	0.252	5.0	LOS A	1.3	9.6	0.19	0.07	46.8
Approach		325	2.0	0.252	5.0	LOS A	1.3	9.6	0.19	0.07	47.7
East: Abott Street East											
4	L2	191	2.0	0.223	5.3	LOS A	1.1	7.8	0.39	0.26	47.3
5	T1	57	2.0	0.223	5.3	LOS A	1.1	7.8	0.39	0.26	44.5
Approach		248	2.0	0.223	5.3	LOS A	1.1	7.8	0.39	0.26	46.6
West: Abott Street East											
11	T1	48	2.0	0.302	6.1	LOS A	1.6	11.4	0.42	0.28	45.9
12	R2	289	2.0	0.302	6.1	LOS A	1.6	11.4	0.42	0.28	47.8
Approach		337	2.0	0.302	6.1	LOS A	1.6	11.4	0.42	0.28	47.5
All Vehicles		910	2.0	0.302	5.5	LOS A	1.6	11.4	0.33	0.20	47.3

Site Level of Service (LOS) Method: Delay & v/c (HCM 6). Site LOS Method is specified in the Parameter Settings dialog (Site tab).

Roundabout LOS Method: Same as Sign Control.

Vehicle movement LOS values are based on average delay and v/c ratio (degree of saturation) per movement.

LOS F will result if v/c > 1 irrespective of movement delay value (does not apply for approaches and intersection).

Intersection and Approach LOS values are based on average delay for all movements (v/c not used as specified in HCM 6).

Roundabout Capacity Model: US HCM 6.

HCM Delay Formula option is used. Control Delay does not include Geometric Delay since Exclude Geometric Delay option applies.

Gap-Acceptance Capacity: Traditional M1.

HV (%) values are calculated for All Movement Classes of All Heavy Vehicle Model Designation.

SIDRA INTERSECTION 7.0 | Copyright © 2000-2017 Akcelik and Associates Pty Ltd | sidrasolutions.com

Organisation: WSP CANADA INC. | Processed: May 30, 2022 4:33:06 PM

Project: L:\W.O. # Directories\219-00014-00_CEPEO Kanata-Sud School TIA\04 Technical\01 Analysis\SIDRA\Existing Conditions PM.sip7

MOVEMENT SUMMARY

 Site: 102 [Robert Grant Avenue / Bobolink Ridge AM]

Existing Conditions AM
Roundabout

Movement Performance - Vehicles											
Mov ID	OD Mov	Demand Total veh/h	Flows HV %	Deg. Satn v/c	Average Delay sec	Level of Service	95% Back of Queue Vehicles veh	Distance m	Prop. Queued	Effective Stop Rate per veh	Average Speed km/h
South: Robert Grant Avenue											
1	L2	26	2.0	0.197	4.6	LOS A	1.0	7.0	0.25	0.12	49.7
2	T1	206	2.0	0.197	4.6	LOS A	1.0	7.0	0.25	0.12	53.0
3	R2	13	2.0	0.197	4.6	LOS A	1.0	7.0	0.25	0.12	48.3
Approach		245	2.0	0.197	4.6	LOS A	1.0	7.0	0.25	0.12	52.3
East: Bobolink Ridge											
4	L2	13	0.0	0.069	4.1	LOS A	0.3	2.0	0.41	0.27	49.4
5	T1	1	0.0	0.069	4.1	LOS A	0.3	2.0	0.41	0.27	46.3
6	R2	57	0.0	0.069	4.1	LOS A	0.3	2.0	0.41	0.27	48.3
Approach		71	0.0	0.069	4.1	LOS A	0.3	2.0	0.41	0.27	48.5
North: Robert Grand Avenue											
7	L2	31	2.0	0.143	3.9	LOS A	0.7	4.8	0.15	0.05	49.9
8	T1	112	2.0	0.143	3.9	LOS A	0.7	4.8	0.15	0.05	53.2
9	R2	43	2.0	0.143	3.9	LOS A	0.7	4.8	0.15	0.05	48.5
Approach		186	2.0	0.143	3.9	LOS A	0.7	4.8	0.15	0.05	51.5
West: Bobolink Ridge											
10	L2	52	2.0	0.065	3.7	LOS A	0.3	2.0	0.30	0.16	48.1
11	T1	3	2.0	0.065	3.7	LOS A	0.3	2.0	0.30	0.16	45.3
12	R2	20	2.0	0.065	3.7	LOS A	0.3	2.0	0.30	0.16	47.2
Approach		75	2.0	0.065	3.7	LOS A	0.3	2.0	0.30	0.16	47.7
All Vehicles		577	1.8	0.197	4.2	LOS A	1.0	7.0	0.24	0.12	50.9

Site Level of Service (LOS) Method: Delay & v/c (HCM 6). Site LOS Method is specified in the Parameter Settings dialog (Site tab).

Roundabout LOS Method: SIDRA Roundabout LOS.

Vehicle movement LOS values are based on average delay and v/c ratio (degree of saturation) per movement.

LOS F will result if v/c > 1 irrespective of movement delay value (does not apply for approaches and intersection).

Intersection and Approach LOS values are based on average delay for all movements (v/c not used as specified in HCM 6).

Roundabout Capacity Model: US HCM 6.

HCM Delay Formula option is used. Control Delay does not include Geometric Delay since Exclude Geometric Delay option applies.

Gap-Acceptance Capacity: Traditional M1.

HV (%) values are calculated for All Movement Classes of All Heavy Vehicle Model Designation.

SIDRA INTERSECTION 7.0 | Copyright © 2000-2017 Akcelik and Associates Pty Ltd | sidrasolutions.com

Organisation: WSP CANADA INC. | Processed: May 30, 2022 3:56:48 PM

Project: L:\W.O. # Directories\219-00014-00_CEPEO Kanata-Sud School TIA\04 Technical\01 Analysis\SIDRA\Existing Conditions AM.sip87

MOVEMENT SUMMARY

 Site: 102 [Robert Grant Avenue / Bobolink Ridge PM]

Existing Conditions PM
Roundabout

Movement Performance - Vehicles											
Mov ID	OD Mov	Demand Total veh/h	Flows HV %	Deg. Satn v/c	Average Delay sec	Level of Service	95% Back of Queue Vehicles veh	Distance m	Prop. Queued	Effective Stop Rate per veh	Average Speed km/h
South: Robert Grant Avenue											
1	L2	13	2.0	0.141	4.2	LOS A	0.7	4.6	0.27	0.14	50.1
2	T1	139	2.0	0.141	4.2	LOS A	0.7	4.6	0.27	0.14	53.4
3	R2	18	2.0	0.141	4.2	LOS A	0.7	4.6	0.27	0.14	48.7
Approach		170	2.0	0.141	4.2	LOS A	0.7	4.6	0.27	0.14	52.6
East: Bobolink Ridge											
4	L2	12	0.0	0.059	3.7	LOS A	0.3	1.8	0.34	0.20	49.6
5	T1	5	0.0	0.059	3.7	LOS A	0.3	1.8	0.34	0.20	46.5
6	R2	49	0.0	0.059	3.7	LOS A	0.3	1.8	0.34	0.20	48.6
Approach		66	0.0	0.059	3.7	LOS A	0.3	1.8	0.34	0.20	48.6
North: Robert Grand Avenue											
7	L2	60	2.0	0.232	4.7	LOS A	1.2	8.7	0.14	0.05	49.3
8	T1	187	2.0	0.232	4.7	LOS A	1.2	8.7	0.14	0.05	52.5
9	R2	58	2.0	0.232	4.7	LOS A	1.2	8.7	0.14	0.05	48.0
Approach		305	2.0	0.232	4.7	LOS A	1.2	8.7	0.14	0.05	51.0
West: Bobolink Ridge											
10	L2	47	2.0	0.078	4.1	LOS A	0.3	2.3	0.39	0.26	48.2
11	T1	8	2.0	0.078	4.1	LOS A	0.3	2.3	0.39	0.26	45.3
12	R2	26	2.0	0.078	4.1	LOS A	0.3	2.3	0.39	0.26	47.2
Approach		81	2.0	0.078	4.1	LOS A	0.3	2.3	0.39	0.26	47.5
All Vehicles		622	1.8	0.232	4.4	LOS A	1.2	8.7	0.23	0.12	50.6

Site Level of Service (LOS) Method: Delay & v/c (HCM 6). Site LOS Method is specified in the Parameter Settings dialog (Site tab).

Roundabout LOS Method: SIDRA Roundabout LOS.

Vehicle movement LOS values are based on average delay and v/c ratio (degree of saturation) per movement.

LOS F will result if v/c > 1 irrespective of movement delay value (does not apply for approaches and intersection).

Intersection and Approach LOS values are based on average delay for all movements (v/c not used as specified in HCM 6).

Roundabout Capacity Model: US HCM 6.

HCM Delay Formula option is used. Control Delay does not include Geometric Delay since Exclude Geometric Delay option applies.

Gap-Acceptance Capacity: Traditional M1.

HV (%) values are calculated for All Movement Classes of All Heavy Vehicle Model Designation.

SIDRA INTERSECTION 7.0 | Copyright © 2000-2017 Akcelik and Associates Pty Ltd | sidrasolutions.com

Organisation: WSP CANADA INC. | Processed: May 30, 2022 4:36:23 PM

Project: L:\W.O. # Directories\219-00014-00_CEPEO Kanata-Sud School TIA\04 Technical\01 Analysis\SIDRA\Existing Conditions PM.sip7

MOVEMENT SUMMARY

 Site: 103 [Robert Grant Avenue / Cope Drive AM]

Existing Conditions AM
Roundabout

Movement Performance - Vehicles											
Mov ID	OD Mov	Demand Total veh/h	Flows HV %	Deg. Satn v/c	Average Delay sec	Level of Service	95% Back of Queue Vehicles veh	Distance m	Prop. Queued	Effective Stop Rate per veh	Average Speed km/h
South: Robert Grant Avenue											
1	L2	5	2.0	0.189	4.3	LOS A	1.0	6.8	0.11	0.03	50.0
2	T1	220	2.0	0.189	4.3	LOS A	1.0	6.8	0.11	0.03	53.3
3	R2	26	2.0	0.189	4.3	LOS A	1.0	6.8	0.11	0.03	48.6
Approach		251	2.0	0.189	4.3	LOS A	1.0	6.8	0.11	0.03	52.7
East: Cope Drive											
4	L2	21	2.0	0.043	3.7	LOS A	0.2	1.3	0.36	0.21	48.8
5	T1	1	0.0	0.043	3.7	LOS A	0.2	1.3	0.36	0.21	45.9
6	R2	25	2.0	0.043	3.7	LOS A	0.2	1.3	0.36	0.21	47.8
Approach		47	2.0	0.043	3.7	LOS A	0.2	1.3	0.36	0.21	48.2
North: Robert Grant Avenue											
7	L2	19	2.0	0.110	3.6	LOS A	0.5	3.6	0.12	0.03	50.1
8	T1	126	2.0	0.110	3.6	LOS A	0.5	3.6	0.12	0.03	53.5
9	R2	1	0.0	0.110	3.6	LOS A	0.5	3.6	0.12	0.03	48.8
Approach		146	2.0	0.110	3.6	LOS A	0.5	3.6	0.12	0.03	53.0
West: Cope Drive											
10	L2	1	0.0	0.009	3.2	LOS A	0.0	0.2	0.29	0.13	50.2
11	T1	3	0.0	0.009	3.2	LOS A	0.0	0.2	0.29	0.13	47.1
12	R2	6	0.0	0.009	3.2	LOS A	0.0	0.2	0.29	0.13	49.1
Approach		10	0.0	0.009	3.2	LOS A	0.0	0.2	0.29	0.13	48.6
All Vehicles		454	1.9	0.189	4.0	LOS A	1.0	6.8	0.14	0.05	52.2

Site Level of Service (LOS) Method: Delay (SIDRA). Site LOS Method is specified in the Parameter Settings dialog (Site tab).

Roundabout LOS Method: Same as Sign Control.

Vehicle movement LOS values are based on average delay per movement.

Intersection and Approach LOS values are based on average delay for all vehicle movements.

Roundabout Capacity Model: US HCM 6.

HCM Delay Formula option is used. Control Delay does not include Geometric Delay since Exclude Geometric Delay option applies.

Gap-Acceptance Capacity: Traditional M1.

HV (%) values are calculated for All Movement Classes of All Heavy Vehicle Model Designation.

SIDRA INTERSECTION 7.0 | Copyright © 2000-2017 Akcelik and Associates Pty Ltd | sidrasolutions.com

Organisation: WSP CANADA INC. | Processed: May 30, 2022 4:25:11 PM

Project: L:\W.O. # Directories\219-00014-00_CEPEO Kanata-Sud School TIA\04 Technical\01 Analysis\SIDRA\Existing Conditions AM.sip7

MOVEMENT SUMMARY

 Site: 103 [Robert Grant Avenue / Cope Drive PM]

Existing Conditions PM
Roundabout

Movement Performance - Vehicles											
Mov ID	OD Mov	Demand Total veh/h	Flows HV %	Deg. Satn v/c	Average Delay sec	Level of Service	95% Back of Queue Vehicles veh	Distance m	Prop. Queued	Effective Stop Rate per veh	Average Speed km/h
South: Robert Grant Avenue											
1	L2	6	2.0	0.130	3.8	LOS A	0.6	4.3	0.10	0.03	50.3
2	T1	143	2.0	0.130	3.8	LOS A	0.6	4.3	0.10	0.03	53.7
3	R2	23	2.0	0.130	3.8	LOS A	0.6	4.3	0.10	0.03	48.9
Approach		172	2.0	0.130	3.8	LOS A	0.6	4.3	0.10	0.03	52.9
East: Cope Drive											
4	L2	35	2.0	0.064	3.6	LOS A	0.3	2.0	0.30	0.16	48.8
5	T1	10	0.0	0.064	3.6	LOS A	0.3	2.0	0.30	0.16	45.9
6	R2	30	2.0	0.064	3.6	LOS A	0.3	2.0	0.30	0.16	47.8
Approach		75	1.7	0.064	3.6	LOS A	0.3	2.0	0.30	0.16	48.0
North: Robert Grant Avenue											
7	L2	15	2.0	0.174	4.2	LOS A	0.9	6.1	0.18	0.07	49.9
8	T1	210	2.0	0.174	4.2	LOS A	0.9	6.1	0.18	0.07	53.2
9	R2	1	0.0	0.174	4.2	LOS A	0.9	6.1	0.18	0.07	48.6
Approach		226	2.0	0.174	4.2	LOS A	0.9	6.1	0.18	0.07	53.0
West: Cope Drive											
10	L2	4	0.0	0.007	3.5	LOS A	0.0	0.2	0.37	0.19	48.6
11	T1	2	0.0	0.007	3.5	LOS A	0.0	0.2	0.37	0.19	45.7
12	R2	1	0.0	0.007	3.5	LOS A	0.0	0.2	0.37	0.19	47.7
Approach		7	0.0	0.007	3.5	LOS A	0.0	0.2	0.37	0.19	47.6
All Vehicles		480	1.9	0.174	4.0	LOS A	0.9	6.1	0.17	0.07	52.0

Site Level of Service (LOS) Method: Delay (SIDRA). Site LOS Method is specified in the Parameter Settings dialog (Site tab).

Roundabout LOS Method: Same as Sign Control.

Vehicle movement LOS values are based on average delay per movement.

Intersection and Approach LOS values are based on average delay for all vehicle movements.

Roundabout Capacity Model: US HCM 6.

HCM Delay Formula option is used. Control Delay does not include Geometric Delay since Exclude Geometric Delay option applies.

Gap-Acceptance Capacity: Traditional M1.

HV (%) values are calculated for All Movement Classes of All Heavy Vehicle Model Designation.

SIDRA INTERSECTION 7.0 | Copyright © 2000-2017 Akcelik and Associates Pty Ltd | sidrasolutions.com

Organisation: WSP CANADA INC. | Processed: May 30, 2022 4:37:58 PM

Project: L:\W.O. # Directories\219-00014-00_CEPEO Kanata-Sud School TIA\04 Technical\01 Analysis\SIDRA\Existing Conditions PM.sip7

MOVEMENT SUMMARY

 Site: 101 [Abbott Street East / Robert Grant Avenue AM]

2023 Future Background Conditions AM
Roundabout

Movement Performance - Vehicles											
Mov ID	OD Mov	Demand Total veh/h	Flows HV %	Deg. Satn v/c	Average Delay sec	Level of Service	95% Back of Queue Vehicles veh	Distance m	Prop. Queued	Effective Stop Rate per veh	Average Speed km/h
South: Robert Grant Avenue											
1	L2	300	2.0	0.399	6.5	LOS A	2.7	19.0	0.14	0.04	47.5
3	R2	230	2.0	0.399	6.5	LOS A	2.7	19.0	0.14	0.04	46.0
Approach		530	2.0	0.399	6.5	LOS A	2.7	19.0	0.14	0.04	46.8
East: Abott Street East											
4	L2	103	2.0	0.158	5.0	LOS A	0.7	5.0	0.45	0.33	47.8
5	T1	55	2.0	0.158	5.0	LOS A	0.7	5.0	0.45	0.33	44.9
Approach		158	2.0	0.158	5.0	LOS A	0.7	5.0	0.45	0.33	46.8
West: Abott Street East											
11	T1	21	2.0	0.157	4.3	LOS A	0.7	5.3	0.26	0.13	47.0
12	R2	170	2.0	0.157	4.3	LOS A	0.7	5.3	0.26	0.13	49.0
Approach		191	2.0	0.157	4.3	LOS A	0.7	5.3	0.26	0.13	48.7
All Vehicles		879	2.0	0.399	5.8	LOS A	2.7	19.0	0.22	0.11	47.2

Site Level of Service (LOS) Method: Delay & v/c (HCM 6). Site LOS Method is specified in the Parameter Settings dialog (Site tab).

Roundabout LOS Method: Same as Sign Control.

Vehicle movement LOS values are based on average delay and v/c ratio (degree of saturation) per movement.

LOS F will result if v/c > 1 irrespective of movement delay value (does not apply for approaches and intersection).

Intersection and Approach LOS values are based on average delay for all movements (v/c not used as specified in HCM 6).

Roundabout Capacity Model: US HCM 6.

HCM Delay Formula option is used. Control Delay does not include Geometric Delay since Exclude Geometric Delay option applies.

Gap-Acceptance Capacity: Traditional M1.

HV (%) values are calculated for All Movement Classes of All Heavy Vehicle Model Designation.

SIDRA INTERSECTION 7.0 | Copyright © 2000-2017 Akcelik and Associates Pty Ltd | sidrasolutions.com

Organisation: WSP CANADA INC. | Processed: May 30, 2022 4:41:13 PM

Project: L:\W.O. # Directories\219-00014-00_CEPEO Kanata-Sud School TIA\04 Technical\01 Analysis\SIDRA\2023 Future Background Conditions AM.sip7

MOVEMENT SUMMARY

 Site: 101 [Abbott Street East / Robert Grant Avenue PM]

2023 Future Background Conditions PM
Roundabout

Movement Performance - Vehicles											
Mov ID	OD Mov	Demand Total veh/h	Flows HV %	Deg. Satn v/c	Average Delay sec	Level of Service	95% Back of Queue Vehicles veh	Distance m	Prop. Queued	Effective Stop Rate per veh	Average Speed km/h
South: Robert Grant Avenue											
1	L2	213	2.0	0.277	5.2	LOS A	1.5	10.9	0.20	0.08	48.2
3	R2	144	2.0	0.277	5.2	LOS A	1.5	10.9	0.20	0.08	46.7
Approach		357	2.0	0.277	5.2	LOS A	1.5	10.9	0.20	0.08	47.6
East: Abott Street East											
4	L2	205	2.0	0.240	5.5	LOS A	1.2	8.5	0.41	0.28	47.1
5	T1	58	2.0	0.240	5.5	LOS A	1.2	8.5	0.41	0.28	44.4
Approach		263	2.0	0.240	5.5	LOS A	1.2	8.5	0.41	0.28	46.5
West: Abott Street East											
11	T1	49	2.0	0.319	6.4	LOS A	1.7	12.2	0.44	0.31	45.7
12	R2	301	2.0	0.319	6.4	LOS A	1.7	12.2	0.44	0.31	47.6
Approach		350	2.0	0.319	6.4	LOS A	1.7	12.2	0.44	0.31	47.4
All Vehicles		970	2.0	0.319	5.7	LOS A	1.7	12.2	0.34	0.22	47.2

Site Level of Service (LOS) Method: Delay & v/c (HCM 6). Site LOS Method is specified in the Parameter Settings dialog (Site tab).

Roundabout LOS Method: Same as Sign Control.

Vehicle movement LOS values are based on average delay and v/c ratio (degree of saturation) per movement.

LOS F will result if v/c > 1 irrespective of movement delay value (does not apply for approaches and intersection).

Intersection and Approach LOS values are based on average delay for all movements (v/c not used as specified in HCM 6).

Roundabout Capacity Model: US HCM 6.

HCM Delay Formula option is used. Control Delay does not include Geometric Delay since Exclude Geometric Delay option applies.

Gap-Acceptance Capacity: Traditional M1.

HV (%) values are calculated for All Movement Classes of All Heavy Vehicle Model Designation.

SIDRA INTERSECTION 7.0 | Copyright © 2000-2017 Akcelik and Associates Pty Ltd | sidrasolutions.com

Organisation: WSP CANADA INC. | Processed: May 30, 2022 4:50:31 PM

Project: L:\W.O. # Directories\219-00014-00_CEPEO Kanata-Sud School TIA\04 Technical\01 Analysis\SIDRA\2023 Future Background Conditions PM.sip7

MOVEMENT SUMMARY

 Site: 102 [Robert Grant Avenue / Bobolink Ridge AM]

2023 Future Background Conditions AM
Roundabout

Movement Performance - Vehicles											
Mov ID	OD Mov	Demand Total veh/h	Flows HV %	Deg. Satn v/c	Average Delay sec	Level of Service	95% Back of Queue Vehicles veh	Distance m	Prop. Queued	Effective Stop Rate per veh	Average Speed km/h
South: Robert Grant Avenue											
1	L2	27	2.0	0.219	4.8	LOS A	1.1	7.9	0.26	0.12	49.6
2	T1	231	2.0	0.219	4.8	LOS A	1.1	7.9	0.26	0.12	52.8
3	R2	13	2.0	0.219	4.8	LOS A	1.1	7.9	0.26	0.12	48.2
Approach		271	2.0	0.219	4.8	LOS A	1.1	7.9	0.26	0.12	52.2
East: Bobolink Ridge											
4	L2	13	0.0	0.072	4.3	LOS A	0.3	2.1	0.43	0.30	49.3
5	T1	1	0.0	0.072	4.3	LOS A	0.3	2.1	0.43	0.30	46.2
6	R2	58	0.0	0.072	4.3	LOS A	0.3	2.1	0.43	0.30	48.2
Approach		72	0.0	0.072	4.3	LOS A	0.3	2.1	0.43	0.30	48.4
North: Robert Grand Avenue											
7	L2	32	2.0	0.174	4.2	LOS A	0.9	6.1	0.16	0.06	49.8
8	T1	150	2.0	0.174	4.2	LOS A	0.9	6.1	0.16	0.06	53.1
9	R2	44	2.0	0.174	4.2	LOS A	0.9	6.1	0.16	0.06	48.4
Approach		226	2.0	0.174	4.2	LOS A	0.9	6.1	0.16	0.06	51.7
West: Bobolink Ridge											
10	L2	53	2.0	0.068	3.8	LOS A	0.3	2.1	0.34	0.20	48.0
11	T1	3	2.0	0.068	3.8	LOS A	0.3	2.1	0.34	0.20	45.2
12	R2	20	2.0	0.068	3.8	LOS A	0.3	2.1	0.34	0.20	47.0
Approach		76	2.0	0.068	3.8	LOS A	0.3	2.1	0.34	0.20	47.6
All Vehicles		645	1.8	0.219	4.4	LOS A	1.1	7.9	0.25	0.13	51.0

Site Level of Service (LOS) Method: Delay & v/c (HCM 6). Site LOS Method is specified in the Parameter Settings dialog (Site tab).

Roundabout LOS Method: SIDRA Roundabout LOS.

Vehicle movement LOS values are based on average delay and v/c ratio (degree of saturation) per movement.

LOS F will result if v/c > 1 irrespective of movement delay value (does not apply for approaches and intersection).

Intersection and Approach LOS values are based on average delay for all movements (v/c not used as specified in HCM 6).

Roundabout Capacity Model: US HCM 6.

HCM Delay Formula option is used. Control Delay does not include Geometric Delay since Exclude Geometric Delay option applies.

Gap-Acceptance Capacity: Traditional M1.

HV (%) values are calculated for All Movement Classes of All Heavy Vehicle Model Designation.

SIDRA INTERSECTION 7.0 | Copyright © 2000-2017 Akcelik and Associates Pty Ltd | sidrasolutions.com

Organisation: WSP CANADA INC. | Processed: May 30, 2022 4:43:20 PM

Project: L:\W.O. # Directories\219-00014-00_CEPEO Kanata-Sud School TIA\04 Technical\01 Analysis\SIDRA\2023 Future Background Conditions AM.sip7

MOVEMENT SUMMARY

 Site: 102 [Robert Grant Avenue / Bobolink Ridge PM]

2023 Future Background Conditions PM
Roundabout

Movement Performance - Vehicles											
Mov ID	OD Mov	Demand Total veh/h	Flows HV %	Deg. Satn v/c	Average Delay sec	Level of Service	95% Back of Queue Vehicles veh	Distance m	Prop. Queued	Effective Stop Rate per veh	Average Speed km/h
South: Robert Grant Avenue											
1	L2	13	2.0	0.161	4.4	LOS A	0.8	5.4	0.28	0.15	50.0
2	T1	163	2.0	0.161	4.4	LOS A	0.8	5.4	0.28	0.15	53.3
3	R2	18	2.0	0.161	4.4	LOS A	0.8	5.4	0.28	0.15	48.6
Approach		194	2.0	0.161	4.4	LOS A	0.8	5.4	0.28	0.15	52.6
East: Bobolink Ridge											
4	L2	12	0.0	0.062	3.8	LOS A	0.3	1.8	0.36	0.22	49.6
5	T1	5	0.0	0.062	3.8	LOS A	0.3	1.8	0.36	0.22	46.4
6	R2	50	0.0	0.062	3.8	LOS A	0.3	1.8	0.36	0.22	48.5
Approach		67	0.0	0.062	3.8	LOS A	0.3	1.8	0.36	0.22	48.5
North: Robert Grand Avenue											
7	L2	61	2.0	0.248	4.9	LOS A	1.3	9.5	0.14	0.05	49.3
8	T1	207	2.0	0.248	4.9	LOS A	1.3	9.5	0.14	0.05	52.5
9	R2	59	2.0	0.248	4.9	LOS A	1.3	9.5	0.14	0.05	47.9
Approach		327	2.0	0.248	4.9	LOS A	1.3	9.5	0.14	0.05	51.0
West: Bobolink Ridge											
10	L2	48	2.0	0.082	4.3	LOS A	0.3	2.4	0.41	0.28	48.1
11	T1	8	2.0	0.082	4.3	LOS A	0.3	2.4	0.41	0.28	45.2
12	R2	27	2.0	0.082	4.3	LOS A	0.3	2.4	0.41	0.28	47.1
Approach		83	2.0	0.082	4.3	LOS A	0.3	2.4	0.41	0.28	47.5
All Vehicles		671	1.8	0.248	4.6	LOS A	1.3	9.5	0.24	0.12	50.7

Site Level of Service (LOS) Method: Delay & v/c (HCM 6). Site LOS Method is specified in the Parameter Settings dialog (Site tab).

Roundabout LOS Method: SIDRA Roundabout LOS.

Vehicle movement LOS values are based on average delay and v/c ratio (degree of saturation) per movement.

LOS F will result if v/c > 1 irrespective of movement delay value (does not apply for approaches and intersection).

Intersection and Approach LOS values are based on average delay for all movements (v/c not used as specified in HCM 6).

Roundabout Capacity Model: US HCM 6.

HCM Delay Formula option is used. Control Delay does not include Geometric Delay since Exclude Geometric Delay option applies.

Gap-Acceptance Capacity: Traditional M1.

HV (%) values are calculated for All Movement Classes of All Heavy Vehicle Model Designation.

SIDRA INTERSECTION 7.0 | Copyright © 2000-2017 Akcelik and Associates Pty Ltd | sidrasolutions.com

Organisation: WSP CANADA INC. | Processed: May 30, 2022 4:52:42 PM

Project: L:\W.O. # Directories\219-00014-00_CPEPO Kanata-Sud School TIA\04 Technical\01 Analysis\SIDRA\2023 Future Background Conditions PM.sip7

MOVEMENT SUMMARY

 Site: 103 [Robert Grant Avenue / Cope Drive AM]

2023 Future Background Conditions AM
Roundabout

Movement Performance - Vehicles											
Mov ID	OD Mov	Demand Total veh/h	Flows HV %	Deg. Satn v/c	Average Delay sec	Level of Service	95% Back of Queue Vehicles veh	Distance m	Prop. Queued	Effective Stop Rate per veh	Average Speed km/h
South: Robert Grant Avenue											
1	L2	27	2.0	0.216	4.6	LOS A	1.1	7.9	0.19	0.07	49.5
2	T1	224	2.0	0.216	4.6	LOS A	1.1	7.9	0.19	0.07	52.8
3	R2	27	2.0	0.216	4.6	LOS A	1.1	7.9	0.19	0.07	48.2
Approach		278	2.0	0.216	4.6	LOS A	1.1	7.9	0.19	0.07	52.0
East: Cope Drive											
4	L2	21	2.0	0.058	4.0	LOS A	0.2	1.7	0.39	0.26	48.9
5	T1	13	0.0	0.058	4.0	LOS A	0.2	1.7	0.39	0.26	46.0
6	R2	26	2.0	0.058	4.0	LOS A	0.2	1.7	0.39	0.26	47.9
Approach		60	1.6	0.058	4.0	LOS A	0.2	1.7	0.39	0.26	47.8
North: Robert Grant Avenue											
7	L2	19	2.0	0.143	4.0	LOS A	0.7	4.8	0.19	0.08	50.0
8	T1	129	2.0	0.143	4.0	LOS A	0.7	4.8	0.19	0.08	53.3
9	R2	36	0.0	0.143	4.0	LOS A	0.7	4.8	0.19	0.08	48.6
Approach		184	1.6	0.143	4.0	LOS A	0.7	4.8	0.19	0.08	52.0
West: Cope Drive											
10	L2	21	0.0	0.044	3.5	LOS A	0.2	1.3	0.31	0.16	49.1
11	T1	11	0.0	0.044	3.5	LOS A	0.2	1.3	0.31	0.16	46.1
12	R2	19	0.0	0.044	3.5	LOS A	0.2	1.3	0.31	0.16	48.1
Approach		51	0.0	0.044	3.5	LOS A	0.2	1.3	0.31	0.16	48.0
All Vehicles		573	1.7	0.216	4.3	LOS A	1.1	7.9	0.22	0.10	51.1

Site Level of Service (LOS) Method: Delay (SIDRA). Site LOS Method is specified in the Parameter Settings dialog (Site tab).

Roundabout LOS Method: Same as Sign Control.

Vehicle movement LOS values are based on average delay per movement.

Intersection and Approach LOS values are based on average delay for all vehicle movements.

Roundabout Capacity Model: US HCM 6.

HCM Delay Formula option is used. Control Delay does not include Geometric Delay since Exclude Geometric Delay option applies.

Gap-Acceptance Capacity: Traditional M1.

HV (%) values are calculated for All Movement Classes of All Heavy Vehicle Model Designation.

SIDRA INTERSECTION 7.0 | Copyright © 2000-2017 Akcelik and Associates Pty Ltd | sidrasolutions.com

Organisation: WSP CANADA INC. | Processed: May 30, 2022 4:46:21 PM

Project: L:\W.O. # Directories\219-00014-00_CEPEO Kanata-Sud School TIA\04 Technical\01 Analysis\SIDRA\2023 Future Background Conditions AM.sip7

MOVEMENT SUMMARY

 **Site: 103 [Robert Grant Avenue / Cope Drive PM]**

2023 Future Background Conditions PM
Roundabout

Movement Performance - Vehicles											
Mov ID	OD Mov	Demand Total veh/h	Flows HV %	Deg. Satn v/c	Average Delay sec	Level of Service	95% Back of Queue Vehicles veh	Distance m	Prop. Queued	Effective Stop Rate per veh	Average Speed km/h
South: Robert Grant Avenue											
1	L2	16	2.0	0.144	4.0	LOS A	0.7	4.9	0.18	0.07	50.0
2	T1	146	2.0	0.144	4.0	LOS A	0.7	4.9	0.18	0.07	53.3
3	R2	23	2.0	0.144	4.0	LOS A	0.7	4.9	0.18	0.07	48.6
Approach		185	2.0	0.144	4.0	LOS A	0.7	4.9	0.18	0.07	52.4
East: Cope Drive											
4	L2	36	2.0	0.074	3.8	LOS A	0.3	2.3	0.33	0.20	48.7
5	T1	16	0.0	0.074	3.8	LOS A	0.3	2.3	0.33	0.20	45.8
6	R2	31	2.0	0.074	3.8	LOS A	0.3	2.3	0.33	0.20	47.7
Approach		83	1.6	0.074	3.8	LOS A	0.3	2.3	0.33	0.20	47.8
North: Robert Grant Avenue											
7	L2	15	2.0	0.192	4.5	LOS A	1.0	6.8	0.21	0.09	49.8
8	T1	214	2.0	0.192	4.5	LOS A	1.0	6.8	0.21	0.09	53.1
9	R2	16	0.0	0.192	4.4	LOS A	1.0	6.8	0.21	0.09	48.4
Approach		245	1.9	0.192	4.5	LOS A	1.0	6.8	0.21	0.09	52.5
West: Cope Drive											
10	L2	29	0.0	0.054	3.9	LOS A	0.2	1.6	0.39	0.25	48.5
11	T1	11	0.0	0.054	3.9	LOS A	0.2	1.6	0.39	0.25	45.6
12	R2	17	0.0	0.054	3.9	LOS A	0.2	1.6	0.39	0.25	47.6
Approach		57	0.0	0.054	3.9	LOS A	0.2	1.6	0.39	0.25	47.7
All Vehicles		570	1.7	0.192	4.2	LOS A	1.0	6.8	0.24	0.12	51.2

Site Level of Service (LOS) Method: Delay (SIDRA). Site LOS Method is specified in the Parameter Settings dialog (Site tab).

Roundabout LOS Method: Same as Sign Control.

Vehicle movement LOS values are based on average delay per movement.

Intersection and Approach LOS values are based on average delay for all vehicle movements.

Roundabout Capacity Model: US HCM 6.

HCM Delay Formula option is used. Control Delay does not include Geometric Delay since Exclude Geometric Delay option applies.

Gap-Acceptance Capacity: Traditional M1.

HV (%) values are calculated for All Movement Classes of All Heavy Vehicle Model Designation.

SIDRA INTERSECTION 7.0 | Copyright © 2000-2017 Akcelik and Associates Pty Ltd | sidrasolutions.com

Organisation: WSP CANADA INC. | Processed: May 30, 2022 4:54:16 PM

Project: L:\W.O. # Directories\219-00014-00_CEPEO Kanata-Sud School TIA\04 Technical\01 Analysis\SIDRA\2023 Future Background Conditions PM.sip7

MOVEMENT SUMMARY

 Site: 101 [Abbott Street East / Robert Grant Avenue AM]

2028 Future Background Conditions AM
Roundabout

Movement Performance - Vehicles											
Mov ID	OD Mov	Demand Total veh/h	Flows HV %	Deg. Satn v/c	Average Delay sec	Level of Service	95% Back of Queue Vehicles veh	Distance m	Prop. Queued	Effective Stop Rate per veh	Average Speed km/h
South: Robert Grant Avenue											
1	L2	442	2.0	0.693	12.3	LOS B	8.5	60.2	0.30	0.10	44.4
3	R2	473	2.0	0.693	12.3	LOS B	8.5	60.2	0.30	0.10	43.2
Approach		915	2.0	0.693	12.3	LOS B	8.5	60.2	0.30	0.10	43.8
East: Abott Street East											
4	L2	172	2.0	0.269	7.0	LOS A	1.3	8.9	0.57	0.52	46.4
5	T1	61	2.0	0.269	7.0	LOS A	1.3	8.9	0.57	0.52	43.7
Approach		233	2.0	0.269	7.0	LOS A	1.3	8.9	0.57	0.52	45.7
West: Abott Street East											
11	T1	26	2.0	0.234	5.3	LOS A	1.2	8.3	0.37	0.23	46.4
12	R2	240	2.0	0.234	5.3	LOS A	1.2	8.3	0.37	0.23	48.3
Approach		266	2.0	0.234	5.3	LOS A	1.2	8.3	0.37	0.23	48.1
All Vehicles		1414	2.0	0.693	10.1	LOS B	8.5	60.2	0.36	0.19	44.8

Site Level of Service (LOS) Method: Delay & v/c (HCM 6). Site LOS Method is specified in the Parameter Settings dialog (Site tab).

Roundabout LOS Method: Same as Sign Control.

Vehicle movement LOS values are based on average delay and v/c ratio (degree of saturation) per movement.

LOS F will result if v/c > 1 irrespective of movement delay value (does not apply for approaches and intersection).

Intersection and Approach LOS values are based on average delay for all movements (v/c not used as specified in HCM 6).

Roundabout Capacity Model: US HCM 6.

HCM Delay Formula option is used. Control Delay does not include Geometric Delay since Exclude Geometric Delay option applies.

Gap-Acceptance Capacity: Traditional M1.

HV (%) values are calculated for All Movement Classes of All Heavy Vehicle Model Designation.

SIDRA INTERSECTION 7.0 | Copyright © 2000-2017 Akcelik and Associates Pty Ltd | sidrasolutions.com

Organisation: WSP CANADA INC. | Processed: May 30, 2022 4:58:01 PM

Project: L:\W.O. # Directories\219-00014-00_CEPEO Kanata-Sud School TIA\04 Technical\01 Analysis\SIDRA\2028 Future Background Conditions AM.sip7

MOVEMENT SUMMARY

 Site: 101 [Abbott Street East / Robert Grant Avenue PM]

2028 Future Background Conditions PM
Roundabout

Movement Performance - Vehicles											
Mov ID	OD Mov	Demand Total veh/h	Flows HV %	Deg. Satn v/c	Average Delay sec	Level of Service	95% Back of Queue Vehicles veh	Distance m	Prop. Queued	Effective Stop Rate per veh	Average Speed km/h
South: Robert Grant Avenue											
1	L2	307	2.0	0.486	8.2	LOS A	3.5	24.7	0.39	0.22	46.6
3	R2	287	2.0	0.486	8.2	LOS A	3.5	24.7	0.39	0.22	45.2
Approach		594	2.0	0.486	8.2	LOS A	3.5	24.7	0.39	0.22	45.9
East: Abott Street East											
4	L2	420	2.0	0.486	9.5	LOS A	3.2	22.5	0.62	0.54	44.7
5	T1	64	2.0	0.486	9.5	LOS A	3.2	22.5	0.62	0.54	42.2
Approach		484	2.0	0.486	9.5	LOS A	3.2	22.5	0.62	0.54	44.4
West: Abott Street East											
11	T1	102	2.0	0.626	14.0	LOS B	6.7	47.6	0.77	0.97	41.8
12	R2	449	2.0	0.626	14.0	LOS B	6.7	47.6	0.77	0.97	43.4
Approach		551	2.0	0.626	14.0	LOS B	6.7	47.6	0.77	0.97	43.1
All Vehicles		1629	2.0	0.626	10.5	LOS B	6.7	47.6	0.59	0.57	44.5

Site Level of Service (LOS) Method: Delay & v/c (HCM 6). Site LOS Method is specified in the Parameter Settings dialog (Site tab).

Roundabout LOS Method: Same as Sign Control.

Vehicle movement LOS values are based on average delay and v/c ratio (degree of saturation) per movement.

LOS F will result if v/c > 1 irrespective of movement delay value (does not apply for approaches and intersection).

Intersection and Approach LOS values are based on average delay for all movements (v/c not used as specified in HCM 6).

Roundabout Capacity Model: US HCM 6.

HCM Delay Formula option is used. Control Delay does not include Geometric Delay since Exclude Geometric Delay option applies.

Gap-Acceptance Capacity: Traditional M1.

HV (%) values are calculated for All Movement Classes of All Heavy Vehicle Model Designation.

SIDRA INTERSECTION 7.0 | Copyright © 2000-2017 Akcelik and Associates Pty Ltd | sidrasolutions.com

Organisation: WSP CANADA INC. | Processed: May 30, 2022 5:06:31 PM

Project: L:\W.O. # Directories\219-00014-00_CEPEO Kanata-Sud School TIA\04 Technical\01 Analysis\SIDRA\2028 Future Background Conditions PM.sip7

MOVEMENT SUMMARY

 Site: 102 [Robert Grant Avenue / Bobolink Ridge AM]

2028 Future Background Conditions AM
Roundabout

Movement Performance - Vehicles											
Mov ID	OD Mov	Demand Total veh/h	Flows HV %	Deg. Satn v/c	Average Delay sec	Level of Service	95% Back of Queue Vehicles veh	Distance m	Prop. Queued	Effective Stop Rate per veh	Average Speed km/h
South: Robert Grant Avenue											
1	L2	29	2.0	0.578	9.9	LOS A	4.7	33.8	0.48	0.28	46.6
2	T1	652	2.0	0.578	9.9	LOS A	4.7	33.8	0.48	0.28	49.4
3	R2	17	2.0	0.578	9.9	LOS A	4.7	33.8	0.48	0.28	45.4
Approach		698	2.0	0.578	9.9	LOS A	4.7	33.8	0.48	0.28	49.2
East: Bobolink Ridge											
4	L2	28	0.0	0.166	7.6	LOS A	0.7	4.7	0.63	0.63	47.0
5	T1	1	0.0	0.166	7.6	LOS A	0.7	4.7	0.63	0.63	44.1
6	R2	77	0.0	0.166	7.6	LOS A	0.7	4.7	0.63	0.63	46.0
Approach		106	0.0	0.166	7.6	LOS A	0.7	4.7	0.63	0.63	46.2
North: Robert Grand Avenue											
7	L2	51	2.0	0.450	7.4	LOS A	3.2	22.5	0.28	0.12	48.0
8	T1	476	2.0	0.450	7.4	LOS A	3.2	22.5	0.28	0.12	51.0
9	R2	48	2.0	0.450	7.4	LOS A	3.2	22.5	0.28	0.12	46.7
Approach		575	2.0	0.450	7.4	LOS A	3.2	22.5	0.28	0.12	50.3
West: Bobolink Ridge											
10	L2	59	2.0	0.111	5.8	LOS A	0.4	3.2	0.56	0.50	46.8
11	T1	3	2.0	0.111	5.8	LOS A	0.4	3.2	0.56	0.50	44.1
12	R2	23	2.0	0.111	5.8	LOS A	0.4	3.2	0.56	0.50	45.9
Approach		85	2.0	0.111	5.8	LOS A	0.4	3.2	0.56	0.50	46.5
All Vehicles		1464	1.9	0.578	8.5	LOS A	4.7	33.8	0.41	0.26	49.2

Site Level of Service (LOS) Method: Delay & v/c (HCM 6). Site LOS Method is specified in the Parameter Settings dialog (Site tab).

Roundabout LOS Method: SIDRA Roundabout LOS.

Vehicle movement LOS values are based on average delay and v/c ratio (degree of saturation) per movement.

LOS F will result if v/c > 1 irrespective of movement delay value (does not apply for approaches and intersection).

Intersection and Approach LOS values are based on average delay for all movements (v/c not used as specified in HCM 6).

Roundabout Capacity Model: US HCM 6.

HCM Delay Formula option is used. Control Delay does not include Geometric Delay since Exclude Geometric Delay option applies.

Gap-Acceptance Capacity: Traditional M1.

HV (%) values are calculated for All Movement Classes of All Heavy Vehicle Model Designation.

SIDRA INTERSECTION 7.0 | Copyright © 2000-2017 Akcelik and Associates Pty Ltd | sidrasolutions.com

Organisation: WSP CANADA INC. | Processed: May 30, 2022 5:02:33 PM

Project: L:\W.O. # Directories\219-00014-00_CEPEO Kanata-Sud School TIA\04 Technical\01 Analysis\SIDRA\2028 Future Background Conditions AM.sip7

MOVEMENT SUMMARY

 Site: 102 [Robert Grant Avenue / Bobolink Ridge PM]

2028 Future Background Conditions PM
Roundabout

Movement Performance - Vehicles											
Mov ID	OD Mov	Demand Total veh/h	Flows HV %	Deg. Satn v/c	Average Delay sec	Level of Service	95% Back of Queue Vehicles veh	Distance m	Prop. Queued	Effective Stop Rate per veh	Average Speed km/h
South: Robert Grant Avenue											
1	L2	15	2.0	0.455	8.0	LOS A	3.0	21.0	0.46	0.30	47.8
2	T1	485	2.0	0.455	8.0	LOS A	3.0	21.0	0.46	0.30	50.8
3	R2	24	2.0	0.455	8.0	LOS A	3.0	21.0	0.46	0.30	46.5
Approach		524	2.0	0.455	8.0	LOS A	3.0	21.0	0.46	0.30	50.5
East: Bobolink Ridge											
4	L2	22	0.0	0.117	5.8	LOS A	0.5	3.4	0.56	0.50	48.1
5	T1	6	0.0	0.117	5.8	LOS A	0.5	3.4	0.56	0.50	45.1
6	R2	63	0.0	0.117	5.8	LOS A	0.5	3.4	0.56	0.50	47.1
Approach		91	0.0	0.117	5.8	LOS A	0.5	3.4	0.56	0.50	47.2
North: Robert Grand Avenue											
7	L2	97	2.0	0.558	9.1	LOS A	4.8	34.4	0.28	0.11	46.8
8	T1	563	2.0	0.558	9.1	LOS A	4.8	34.4	0.28	0.11	49.7
9	R2	65	2.0	0.558	9.1	LOS A	4.8	34.4	0.28	0.11	45.6
Approach		725	2.0	0.558	9.1	LOS A	4.8	34.4	0.28	0.11	48.9
West: Bobolink Ridge											
10	L2	53	2.0	0.135	6.9	LOS A	0.5	3.8	0.61	0.59	46.5
11	T1	9	2.0	0.135	6.9	LOS A	0.5	3.8	0.61	0.59	43.8
12	R2	29	2.0	0.135	6.9	LOS A	0.5	3.8	0.61	0.59	45.6
Approach		91	2.0	0.135	6.9	LOS A	0.5	3.8	0.61	0.59	45.9
All Vehicles		1431	1.9	0.558	8.3	LOS A	4.8	34.4	0.39	0.24	49.1

Site Level of Service (LOS) Method: Delay & v/c (HCM 6). Site LOS Method is specified in the Parameter Settings dialog (Site tab).

Roundabout LOS Method: SIDRA Roundabout LOS.

Vehicle movement LOS values are based on average delay and v/c ratio (degree of saturation) per movement.

LOS F will result if v/c > 1 irrespective of movement delay value (does not apply for approaches and intersection).

Intersection and Approach LOS values are based on average delay for all movements (v/c not used as specified in HCM 6).

Roundabout Capacity Model: US HCM 6.

HCM Delay Formula option is used. Control Delay does not include Geometric Delay since Exclude Geometric Delay option applies.

Gap-Acceptance Capacity: Traditional M1.

HV (%) values are calculated for All Movement Classes of All Heavy Vehicle Model Designation.

SIDRA INTERSECTION 7.0 | Copyright © 2000-2017 Akcelik and Associates Pty Ltd | sidrasolutions.com

Organisation: WSP CANADA INC. | Processed: May 30, 2022 5:08:40 PM

Project: L:\W.O. # Directories\219-00014-00_CPEPO Kanata-Sud School TIA\04 Technical\01 Analysis\SIDRA\2028 Future Background Conditions PM.sip7

MOVEMENT SUMMARY

 Site: 103 [Robert Grant Avenue / Cope Drive AM]

2028 Future Background Conditions AM
Roundabout

Movement Performance - Vehicles											
Mov ID	OD Mov	Demand Total veh/h	Flows HV %	Deg. Satn v/c	Average Delay sec	Level of Service	95% Back of Queue Vehicles veh	Distance m	Prop. Queued	Effective Stop Rate per veh	Average Speed km/h
South: Robert Grant Avenue											
1	L2	89	2.0	0.511	10.6	LOS B	3.9	27.6	0.67	0.69	45.7
2	T1	349	2.0	0.511	10.6	LOS B	3.9	27.6	0.67	0.69	48.4
3	R2	30	2.0	0.511	10.6	LOS B	3.9	27.6	0.67	0.69	44.6
Approach		468	2.0	0.511	10.6	LOS B	3.9	27.6	0.67	0.69	47.6
East: Cope Drive											
4	L2	29	2.0	0.288	8.8	LOS A	1.3	8.9	0.66	0.66	46.5
5	T1	48	0.0	0.288	8.7	LOS A	1.3	8.9	0.66	0.66	43.8
6	R2	122	2.0	0.288	8.8	LOS A	1.3	8.9	0.66	0.66	45.6
Approach		199	1.5	0.288	8.7	LOS A	1.3	8.9	0.66	0.66	45.3
North: Robert Grant Avenue											
7	L2	113	2.0	0.455	8.0	LOS A	3.0	21.2	0.47	0.31	47.1
8	T1	232	2.0	0.455	8.0	LOS A	3.0	21.2	0.47	0.31	50.1
9	R2	181	0.0	0.455	8.0	LOS A	3.0	21.2	0.47	0.31	45.9
Approach		526	1.3	0.455	8.0	LOS A	3.0	21.2	0.47	0.31	47.9
West: Cope Drive											
10	L2	227	0.0	0.394	8.3	LOS A	2.1	14.9	0.60	0.53	45.7
11	T1	44	0.0	0.394	8.3	LOS A	2.1	14.9	0.60	0.53	43.1
12	R2	99	0.0	0.394	8.3	LOS A	2.1	14.9	0.60	0.53	44.8
Approach		370	0.0	0.394	8.3	LOS A	2.1	14.9	0.60	0.53	45.1
All Vehicles		1563	1.2	0.511	8.9	LOS A	3.9	27.6	0.59	0.52	46.8

Site Level of Service (LOS) Method: Delay (SIDRA). Site LOS Method is specified in the Parameter Settings dialog (Site tab).

Roundabout LOS Method: Same as Sign Control.

Vehicle movement LOS values are based on average delay per movement.

Intersection and Approach LOS values are based on average delay for all vehicle movements.

Roundabout Capacity Model: US HCM 6.

HCM Delay Formula option is used. Control Delay does not include Geometric Delay since Exclude Geometric Delay option applies.

Gap-Acceptance Capacity: Traditional M1.

HV (%) values are calculated for All Movement Classes of All Heavy Vehicle Model Designation.

SIDRA INTERSECTION 7.0 | Copyright © 2000-2017 Akcelik and Associates Pty Ltd | sidrasolutions.com

Organisation: WSP CANADA INC. | Processed: May 30, 2022 5:04:19 PM

Project: L:\W.O. # Directories\219-00014-00_CEPEO Kanata-Sud School TIA\04 Technical\01 Analysis\SIDRA\2028 Future Background Conditions AM.sip7

MOVEMENT SUMMARY

 **Site: 103 [Robert Grant Avenue / Cope Drive PM]**

2028 Future Background Conditions PM
Roundabout

Movement Performance - Vehicles											
Mov ID	OD Mov	Demand Total veh/h	Flows HV %	Deg. Satn v/c	Average Delay sec	Level of Service	95% Back of Queue Vehicles veh	Queue Distance m	Prop. Queued	Effective Stop Rate per veh	Average Speed km/h
South: Robert Grant Avenue											
1	L2	86	2.0	0.398	7.7	LOS A	2.3	16.1	0.52	0.40	47.3
2	T1	299	2.0	0.398	7.7	LOS A	2.3	16.1	0.52	0.40	50.3
3	R2	31	2.0	0.398	7.7	LOS A	2.3	16.1	0.52	0.40	46.1
Approach		416	2.0	0.398	7.7	LOS A	2.3	16.1	0.52	0.40	49.3
East: Cope Drive											
4	L2	40	2.0	0.171	6.4	LOS A	0.7	5.1	0.57	0.53	47.5
5	T1	20	0.0	0.171	6.4	LOS A	0.7	5.1	0.57	0.53	44.7
6	R2	74	2.0	0.171	6.4	LOS A	0.7	5.1	0.57	0.53	46.5
Approach		134	1.7	0.171	6.4	LOS A	0.7	5.1	0.57	0.53	46.5
North: Robert Grant Avenue											
7	L2	71	2.0	0.521	9.0	LOS A	3.8	27.1	0.49	0.32	46.8
8	T1	344	2.0	0.521	9.0	LOS A	3.8	27.1	0.49	0.32	49.7
9	R2	199	0.0	0.521	8.9	LOS A	3.8	27.1	0.49	0.32	45.6
Approach		614	1.4	0.521	9.0	LOS A	3.8	27.1	0.49	0.32	48.0
West: Cope Drive											
10	L2	158	0.0	0.302	7.5	LOS A	1.5	10.2	0.59	0.55	46.1
11	T1	26	0.0	0.302	7.5	LOS A	1.5	10.2	0.59	0.55	43.5
12	R2	77	0.0	0.302	7.5	LOS A	1.5	10.2	0.59	0.55	45.2
Approach		261	0.0	0.302	7.5	LOS A	1.5	10.2	0.59	0.55	45.6
All Vehicles		1425	1.3	0.521	8.1	LOS A	3.8	27.1	0.53	0.40	47.7

Site Level of Service (LOS) Method: Delay (SIDRA). Site LOS Method is specified in the Parameter Settings dialog (Site tab).

Roundabout LOS Method: Same as Sign Control.

Vehicle movement LOS values are based on average delay per movement.

Intersection and Approach LOS values are based on average delay for all vehicle movements.

Roundabout Capacity Model: US HCM 6.

HCM Delay Formula option is used. Control Delay does not include Geometric Delay since Exclude Geometric Delay option applies.

Gap-Acceptance Capacity: Traditional M1.

HV (%) values are calculated for All Movement Classes of All Heavy Vehicle Model Designation.

SIDRA INTERSECTION 7.0 | Copyright © 2000-2017 Akcelik and Associates Pty Ltd | sidrasolutions.com

Organisation: WSP CANADA INC. | Processed: May 30, 2022 5:11:13 PM

Project: L:\W.O. # Directories\219-00014-00_CEPEO Kanata-Sud School TIA\04 Technical\01 Analysis\SIDRA\2028 Future Background Conditions PM.sip7