



Marco Ianni Architect LTD
26 Revol Road, Ottawa, ON
K2G0B9
613-883-9425
marcoianniarchitect@gmail.com

1. ANY ERRORS AND OMISSIONS IN THE DRAWING ARE TO BE CHECKED BY THE GENERAL CONTRACTOR AND RELAYED TO THE ARCHITECT
2. DO NOT SCALE DRAWINGS
3. ALL WORK SHALL COMPLY WITH THE ONTARIO BUILDING CODE AND WITH AUTHORITIES HAVING JURISDICTION
4. LUMBER SECTIONS SHOWN ARE NOMINAL LIGHT FRAMING SIZES (i.e. 2"x4" = 1.5" x 3.5" ACTUAL) U.N.O
5. DIMENSIONS SHOWN ARE FROM FACE OF Poured CONCRETE, OR FACE OF STUD CORE UNLESS OTHERWISE SHOWING WINDOW/DOOR ROUGH OPENING OR WIDTH OF TRAVEL PATH
6. UNLESS OTHERWISE DIMENSIONED OR NOTED ALL DOORS R/O TO BE 4" FROM NEAREST FINISHED FACE OF WALL OR CENTERED ON WALL
7. FOR ELECTRICAL DRAWINGS, REFER TO ELECTRICAL
8. FOR MECHANICAL DRAWINGS, REFER TO MECHANICAL
9. FOR STRUCTURAL DRAWINGS, REFER TO STRUCTURAL
10. FOR CIVIL DRAWINGS, REFER TO SITE PLAN CONTROL DOCUMENTS PREVIOUSLY SUBMITTED


| No. | Description | Date |
|-----|-------------------|----------|
| 1 | STRUCT SUBMISSION | 10/01/24 |
| 2 | PERMIT SUBMISSION | 30/04/24 |
| 3 | PERMIT SUBMISSION | 06/06/24 |

SITE PLAN

Project number 016
Date 30/04/2024
Drawn by Author
Checked by Checker

A100

Scale 1" = 10'-0"



KEY PLAN NOT TO SCALE LOCATION OF SUBJECT PROPERTY

ADDRESS 370 CAMBRIDGE STREET NORTH OTTAWA, ON K1R 7B7

LEGAL DESCRIPTION PART 1 Plan of LOT 15 WEST CAMBRIDGE STREET NORTH, SOUTH OF STONE BOUNDARY WARD 14, SOMERSET CITY OF OTTAWA REGISTERED PLAN 33

ZONING ZONING BY-LAW 2008-250 R4-U - MATURE NEIGHBOURHOODS OVERLAY

| LOW-RISE APARTMENT, 9 OR MORE UNITS | ZONING (REQ.) | PROPOSED |
|-------------------------------------|-------------------|---------------------|
| MIN. LOT WIDTH | 15m | 16.64m |
| MIN. LOT AREA | 450m ² | 628.6m ² |
| MAX. BUILDING HEIGHT | 14.5m | 14.5m |
| MIN. FRONT YARD SETBACK | 1.5m* | 1.57m |
| MIN. CORNER YARD SETBACK | 4.5m | - |
| MIN. REAR YARD SETBACK | 7.5m* | 8.95m |
| MIN. INTERIOR YARD SETBACK | 1.5m | 1.54m |

ZONE PROVISIONS (8) Except for a lot of less than 450 square metres in area in the R4-UB, R4-UB, R4-UB and R4-UD zones, thirty percent of the lot area must be provided as landscaped area for a lot containing an apartment dwelling, low-rise, stacked dwelling, or retirement home, or a planned unit development that contains any one or more of these dwelling types. (By-law 2020-290)

(9) The maximum height of any permitted use may not exceed that which is specified in Column V of Table 162A, and in no case, may be greater than a maximum four stories. (15) In the case of a Three-unit Dwelling, Low-rise Apartment Dwelling or Stacked Dwelling in the R4-UB, R4-UB, R4-UB and R4-UD zones:

(a) Any part of the rear yard not occupied by accessory buildings and structures, permitted projections, bicycle parking and aisles, hardscaped paths of travel for waste and recycling management, pedestrian walkways, patios, and permitted driveways, parking aisles and parking spaces, must be softly landscaped.

(b) The minimum area of soft landscaping per (a) must be:

- (i) in the case of a lot of less than 350 square metres in area, at least 35 square metres
- (ii) in the case of a lot equal to or greater than 350 square metres but less than 450 square metres in area, at least 50 square metres
- (iii) in the case of a lot 450 square metres or greater, at least 50 per cent of the rear yard

(c) In all cases, must comprise at least one aggregated rectangular area of at least 25 square metres and whose longer dimension is not more than twice its shorter dimension, for the purposes of tree planting.

(d) Any part of any yard other than the rear yard not occupied by accessory buildings and structures, permitted projections, bicycle parking and aisles, hardscaped paths of travel for waste and recycling management, pedestrian walkways, permitted driveways and parking exclusion fixtures per (a) must be softly landscaped.

(e) The minimum area of soft landscaping in the front yard is per Table 161:

Table 161: Front Yard Setback 1.5 metres - three metres Minimum Aggregated Soft Landscaped Area (% of the Front Yard Area) | 20%

(a) The front yard and corner side yard must be equipped with solid, permanent fixtures sufficient to prevent motor vehicle parking in contravention of this By-law, and for greater clarity:

- (i) such parking exclusion fixtures may include bicycle racks, benches, bollards, ornamental fences or garden walls, raised planters, trees, wheelchair lifting devices, wheelchair lifting devices or some combination thereof; and
- (ii) raised planters are deemed to be soft landscaping for the purposes of (c) and (d).

(f) At least one principal entrance to a ground-floor unit or to a common interior corridor or stairwell must be located on the facade and provide direct access to the street, and furthermore:

- (i) in the case of a corner lot, the principal entrance may be located on front or corner facade; and
- (ii) in the case of a lot of 24 metres width or greater, one principal entrance is required for every 12 metres of lot width or part thereof.

(g) The front facade must comprise at least 25 per cent windows, and furthermore:

- (i) any corner side facade must comprise at least 15 per cent windows;
- (ii) windows located in doors may count towards the minimum fenestration requirement; and
- (iii) any window counted towards the minimum fenestration requirement, other than windows in doors or at the basement level, must have a lower sill no higher than 100 centimetres above the floor level.

(h) At least 20 per cent of the area of the front facade must be recessed an additional 0.6 metres from the front setback line.

(j) Despite (h), no additional recession of the front facade is required when balconies or porches are provided on the front or corner side facade as follows:

- (i) in the case of a lot of less than 15 metres width, one balcony or porch for each storey at or above the first storey is provided;
- (ii) in the case of a lot of 15 metres width or greater, one balcony or porch for every unit that faces a public street at or above the first storey; and
- (iii) in any case each balcony or porch must have a horizontal area of at least two square metres.

(k) No rooftop amenity space is permitted within the area shown on Schedule 383. (By-law 2020-290)

(16) In the case of a Low-rise Apartment Dwelling or Stacked Dwelling in the R4-UB, R4-UB, R4-UB and R4-UD zones:

- (a) No motor vehicle parking is permitted on a lot less than 450 square metres in area.
- (b) In the case of a lot of 450 square metres or greater
- (i) at least 25 per cent of dwelling units must have at least two bedrooms; and
- (ii) the calculation of (i) may be rounded down to the nearest whole number.

MINOR VARIANCES REQUESTED: A) TO PERMIT A REDUCED TOTAL OF 3 PARKING SPACES, (COMPRISED OF 3 UNIT SPACES AND NO VISITOR SPACES), WHEREAS THE BY-LAW REQUIRES A MINIMUM OF 5 PARKING SPACES AND 4 VISITOR SPACES AND 1 VISITOR SPACE [Sec 101 & 102]

VEHICLE PARKING:

SECTION 101 - MINIMUM PARKING SPACE RATES
(1) Within the areas shown as Areas B, C, D, X, Y and Z on Schedule 1A, off-street motor vehicle parking must be provided for any land use at the rate set out in Table 101 below.
(2) Despite Subsection (1), within the areas shown as Area X on Schedule 1A:
(a) in the case of a building containing residential uses, no off-street motor vehicle parking is required to be provided under this section for the first twelve dwelling units and the parking requirements under Table 101 apply only to dwelling units and rooming units in excess of 12.
(b) in the case of a building containing residential uses, no off-street motor vehicle parking is required to be provided under this section for the first twelve dwelling units and the parking requirements under Table 101 apply only to dwelling units and rooming units in excess of 12.

Table 101 - MINIMUM PARKING SPACE RATES 1 ROW 111
Land Use = Dwelling, Low-rise Apartment
Area X and Y on Schedule 1A = 0.3 per dwelling unit

SECTION 102 - MINIMUM VISITOR PARKING SPACE RATES
(1) Within the areas shown as Areas B, C, D, X, Y and Z on Schedule 1A, in addition to the parking required under Section 101, off-street visitor motor vehicle parking must be provided for dwelling units at the rate set out in Table 102.
(2) Despite (1), within Areas B, X, Y and Z, no visitor parking spaces are required for the first twelve dwelling units on a lot.

Table 102 - MINIMUM VISITOR PARKING SPACE RATES
Land Use = Apartment dwelling, low-rise or mid-high-rise
Area X and Y on Schedule 1A | 0.1 per dwelling unit

SECTION 111 - BICYCLE PARKING SPACE RATES AND PROVISIONS

Table 111A - Bicycle parking space rates
Land use (b) (i) (j) apartment building, low-rise; apartment dwelling, mid-rise; apartment dwelling, high-rise; dwelling unit in the same building as a non-residential use; stacked dwelling without a garage or carport for each dwelling unit
Minimum number of spaces required | 0.50 per dwelling unit

LOT DETAILS:

LOT FRONTAGE (CAMBRIDGE): 16.64m
LOT DEPTH: 37.82m (IRREGULAR)
LOT AREA: 628.6m²

TOTAL LANDSCAPED AREA: 215.2m² (34.3% OF LOT AREA)
[REQ. 30%]

FRONT YARD AREA: 26.1m²
AREA OF SOFT LANDSCAPING: 18.3m² (70.1% OF FRONT YARD AREA)
[REQ. 20%]

REAR YARD AREA: 149.1m²
AREA OF SOFT LANDSCAPING: 85.5m² (57.4% OF REAR YARD AREA)
[REQ. 50%]

REAR YARD AMENITY AREA: 82.5m² (AGGREGATE AREA AT GRADE)

3 SURFACE PARKING SPACES ACCESSED FROM REAR LANE
22 INTERIOR BIKE SPACES

BUILDING DETAILS:

GROSS FLOOR AREA = 1,136.7m²
BUILDING HEIGHT: 14.5m (4-STORIES)
BUILDING FOOTPRINT: 346.9m²

FEATURES:
FLUSH ENTRANCE, SPLIT-LEVEL MAIN FLOOR/BASEMENT
DOUBLE-SIDED ELEVATOR
INTERIOR GARBAGE ROOM
INTERIOR BIKE STORAGE
INDIVIDUAL BALCONIES ALL UNITS EXCEPT BACHELORS

UNIT COUNT:

BACHELOR = 2
1 BEDROOM = 8 (2 B.F.)
1 BEDROOM + DEN = 4
2 BEDROOM = 6 (1 B.F.)
TOTAL = 20 (3 B.F.)

FAÇADE AREA CALCULATIONS:
SEC. 161 (15)

g) The front facade must comprise at least 25 percent windows.

AREA OF FRONT FAÇADE = 185.7m² (1999.39 sq.ft.)
AREA OF WINDOWS = 71.6m² (771sq.ft.)
71.6 / 185.7 = 38.55%

*The front facade comprises at least 38.55% windows.



h) At least 20 percent of the area of the front facade must be recessed an additional 0.6 metres from the front setback line.

AREA OF FRONT FAÇADE = 185.7m² (1999.4 sq.ft.)
1.5M (REQ. MIN 0.6M) RECESSED AREA OF FRONT FAÇADE = 92.89m² (999.9 sq.ft.)
92.9 / 185.7 = 50.02%

*At least 50.02% of the area of the front facade is recessed by at least 1.5 metres from the front setback line.

LEGEND

| | | |
|--------------------|-------------------------|---------------------------|
| PROPOSED BUILDING | REQ. TREE PLANTING AREA | LINE OF REQUIRED SETBACK |
| ASPHALT | OVERHEAD WIRES | FENCE |
| INTERLOCK WALKWAY | SOD / SOFT LANDSCAPING | EXISTING TO BE DEMOLISHED |
| OTHER INTERLOCKING | | |



ANDREW MCCREIGHT
MANAGER, DEVELOPMENT REVIEW CENTRAL
PLANNING, DEVELOPMENT & BUILDING SERVICES
DEVELOPMENT DEPARTMENT, CITY OF OTTAWA

APPROVED
By Andrew McCreight at 7:38 am, Jun 07, 2024