STRATZ3R

TECHNICAL NOTE

GWL Realty Advisor 170 Slater, Ottawa, ON Waste Management Plan

June 08, 2023

1.	Initial Information	2
2.	Waste generation evaluation	7
3.	Indoor Storage Scenarios	8
4.	Collection area requirements (538 units)	12
5.	Recommendation	15
6.	Container handling	16
7.	Eligible containers	18
	SectionS from the City of Ottawa Solid Waste Collection Design Guidelines for Multi-Unit	23




1. INITIAL INFORMATION

1.1 PROJECT SUMMARY

The 170 Slater project, in Ottawa, consists of two new residential buildings and a podium. The North

Tower has 24 floors, while the South Tower has 25 floors. The podium, connecting the two towers, has 7 floors. Furthermore, underground parking levels will be present.

The North Tower will accommodate 173 residential units and a 467.5 m² retail, while the South Tower contains 184 units and a 376.4 m² retail. The podium will have 181 residential units. The waste management for the residential units will be done separately between the two buildings, except for the collection, which will take place for both buildings at the same location, in the loading bay located between the two towers and under the podium. Waste



from retail will be managed separately from the residential waste.

The size of the different units and the estimated number of occupants for each one allows determining the expected number of residents. These data are presented in Table 1 below.

Average number of **Total number of Unit Type Number of Units** residents per unit residents per unit (assumptions) type 364 173 2.1 **North Tower** 92 61 1.5 1 Bedroom 33 22 1.5 1 Bedroom + Den 190 2.5 76 2 Bedroom 49 14 3.5 3 Bedroom 384 184 2.1 **South Tower** 99 1.5 1 Bedroom 66 36 24 1.5 1 Bedroom + Den 200 2.5 80 2 Bedroom 49

3.5

1.6

14

181

23

Table 1. Distribution of the residents of 170 Slater



3 Bedroom

Podium

Studio

296

23

Unit Type	Number of Units	Average number of residents per unit (assumptions)	Total number of residents per unit type
1 Bedroom	28	1.5	42
1 Bedroom + Den	95	1.5	143
2 Bedroom	34	2.5	85
3 Bedroom	1	3.5	4
TOTAL (residential)	538	1.9	1,044
North Tower – commercial	467.5 m²	N/A	N/A
South Tower – commercial	376.4 m²	N/A	N/A
TOTAL (commercial)	843.9 m ²	N/A	N/A

1.2 CHARACTERISTICS OF THE PROJECT'S WASTE MANAGEMENT

- Both the North Tower and the South Tower have access to two chutes, one with a bi-sorter unit for garbage and organics and the other for recyclables (containers). The Podium has access to chutes from both towers:
- The chutes from each tower lead to a waste storage room on the ground floor of each tower;
- Fibres will be transported by the residents to the waste storage room on the ground floor;
- The retail stores located on both towers share a separate waste storage room located in the North Tower, also on the ground floor;
- A loading bay is available for picking up the waste from both towers' residential units and from retail.
- A staging pad for waste pickup is located by the loading bay, under the podium;
- For collection of either residential or retail waste, the containers or carts will be moved to the loading space and staging pad to be hauled;
- Residential waste will be serviced by the City of Ottawa, while retail waste will have to be collected by a private service provider;
- A garbage compactor will be located in each residential waste storage room under the garbage chute. These compactors would be accessible only to building employees;
- A cardboard baler might be located in the waste storage rooms;
- A bulky storage area might be available to be used for collection of other materials eligible for special collection services, such as batteries, mercury lamps or electronics;







Figure 1: Plan Presenting Location of Garbage Rooms







GARBAGE ROOM
RESIDENTIAL

TO THE PROOF OF TH

Figure 3: Garbage Rooms - Retail + Residential - South Tower + loading bay and staging area

1.3 CONSTRAINTS OF THE MUNICIPAL COLLECTION SERVICE1

Table 1 outlines the City of Ottawa's collection design guidelines and requirements for buildings with 6 units and above. All collections are performed during the day. These parameters apply only to residential waste, as commercial waste should be hauled by a private service provider.

All waste streams must be available for the residents – Garbage, Blue Box recycling (glass, metal, and plastic), Black Box recycling (paper and cardboard) and Green Bin (organics). If chutes are planned, they should be available to collect three streams – garbage and two streams of recyclables, either using three chutes or a single chute with tri-sorter. Organics can be transported to the garbage room on the ground floor.

Front-end loading container (FEL) are mandatory in developments with more than 18 units, to be used for all streams but organics. Organics should be collected with 240 Litres green carts, supplied by the City.

The development must have at least 75% occupancy per building or project/phase to be eligible for the municipal collection. The Application Form and Acknowledgement and Release Form (see

Steve Nardelli - Waste Management Inspector (Multi-Res Services) - 613-880-7124.
City of Ottawa's Solid Waste Collection Design Guidelines for Multi-Unit Residential Development, October 2012.



¹ Sources of information:

Section 8, Appendix G and Appendix H) have been received and approved by the City before municipal collection starts.

If the collection vehicle is required to drive onto or over a supported structure (such as an underground parking garage) the City must be provided with a letter certified by a qualified engineer that the structure can safely support a fully loaded collection vehicle weighing 35,000 kilograms.

A compactor might be used for garbage or recyclables, but nor for organics.

The retail waste is not eligible for the municipal collection and must use a private hauler.

In situations where a development is unable to meet the City od Ottawa's guidelines, then a Waste Management Brief will be required with the site plan application, to the satisfaction of Solid Waste Services. The intention of the brief is to ensure that the development has been designed with due diligence for on-site solid waste management. Pre-consultation with Solid Waste Services is recommended if a Waste Management Brief will be submitted with the Site Plan application. The following describes some (but not all) situations in which a site design might be outside the realm of these guidelines and warrant a Waste Management Brief.

More details regarding the City of Ottawa's requirements can be consulted at sections 4 and 8.

Table 2. Municipal Collection Parameters - City of Ottawa

Waste stream	Types of equipment accepted	Frequency of collection
Garbage	Front-end loading container Containers up to 8 yd³ are allowed. For compacted containers, 4 yd³ is the maximum size allowed.	Once a week
Recyclables – black box and blue box*	Front-end containers (with or without compaction). Containers up to 8 yd³ are allowed (provided by the City).	Once a week
Organic materials	240 litres rolling carts (provided by the City).	Once a week

^{*} Blue box is for glass, metal and plastic. Black box is for paper/cardboard.



2.WASTE GENERATION EVALUATION

Table 3 presents the weekly volume estimates considering the parameters described in Section 1.1. The weights are first calculated and then transposed into volume by applying standard densities.

Table 3. Weekly generation of the different collection streams in volume (estimates)

	Number of units	Volume of garbage	Volume of Blue Box	Volume of Black Box	Volume of organics
North Tower – residential	173 units	19.03 vg ³	3.11 vg³	6.57 vg ³	1.09 vg ³
South Tower – residential	184 units	20.24 vg ³	3.31 vg ³	6.99 vg ³	1.16 vg³
Podium (residential)	181 units	19.91 vg ³	3.26 vg ³	6.88 vg ³	1.14 vg ³
North Tower – commercial*	467.5 m ²	0.56 v ³	0.10 v ³	0.57 v ³	0.02 v ³
South Tower – commercial*	376.4 m ²	0.50 v ³	0.09 v ³	0.50 v ³	0.02 v ³

^{*} Considering retail – boutique use.



3.INDOOR STORAGE SCENARIOS

3.1 EVALUATION OF REQUIRED INTERIOR AREAS — GARBAGE ROOMS (RESIDENTIAL UNITS AND RETAIL STORE)

Before developing storage layout and process scenarios, it is important to validate the space required to store these materials according to the use of different types of equipment and the different collection frequencies, which is presented below in **Table 4** (garbage), **Table 5** (Black Box), **Table 6** (Blue Box), and **Table 7** (organics). Those scenarios are compared with the minimal exigences from the City of Ottawa, to be validated.

Regarding the tables:

- This tables present equipment for the garbage rooms of the **two residential towers + the podium and the retail stores**;
- Other types of containers exist and could be considered, but the tables include the most common types and those most appropriate for the project;
- All tables include one extra container per stream to be left in the garbage room while the others are taken out for collection;
- The surfaces include the minimum space for handling the equipment despite the presence of corners, doors, and columns;
- The area needed for the compactor is included. A conservative compaction ratio of 2:1 is used for garbage.

The municipal collection service available is indicated in **bold** in the tables. The recommended equipment, that respects the municipal collection requirements, is indicated in **bold and blue**.



Table 4. Estimated indoor storage areas and number of containers – Garbage

	2 yd³	3 yd³	4 yd³	6 yd³ non-
	compacted	compacted	compacted	compacted
North Tower + ½ Podium – residential	388 ft² (7 + 1 containers)	326 ft² (5 + 1 containers)	334 ft² (4 + 1 containers)	480 ft² (5 + 1 containers)
	2 yd³	3 yd³	4 yd³	6 yd³ non-
	compacted	compacted	compacted	compacted
South Tower + ½ Podium	430 ft ²	326 ft ²	334 ft ²	560 ft ²
- residential	(8 + 1	(5 + 1	(4 + 1	(6 + 1
	containers)	containers)	containers)	containers)
	(8 + 1	(5 + 1	(4 + 1	(6 + 1

Table 5. Estimated indoor storage areas and number of containers – Black Box

	2 yd³ non- compacted	3 yd³ non- compacted	4 yd³ non- compacted	6 yd³ non- compacted
North Tower + ½ Podium – residential	288 ft² (6 + 1 containers)	222 ft ² 4 + 1 containers)	220 ft² (3 + 1 containers)	240 ft² (2 + 1 containers)
	2 yd³ non- compacted	3 yd³ non- compacted	4 yd³ non- compacted	6 yd³ non- compacted
South Tower + ½ Podium – residential	288 ft² (6 + 1 containers)	222 ft² (4 + 1 containers)	220 ft ² (3 + 1 containers)	240 ft ² 2 + 1 containers)
	(6 + 1	(4 + 1	(3 + 1	



Table 6. Estimated indoor storage areas and number of containers – Blue Box

	2 yd³ non- compacted	3 yd³ non- compacted	4 yd³ non- compacted	6 yd³ non- compacted
North Tower + ½ Podium – residential	164 ft² (3 + 1 containers)	134 ft² (2 + 1 containers)	164 ft² (2 + 1 containers)	160 ft² (1 + 1 containers)
	2 yd³ non- compacted	3 yd³ non- compacted	4 yd³ non- compacted	6 yd³ non- compacted
South Tower + ½ Podium – residential	164 ft² (3 + 1 containers)	134 ft² (2 + 1 containers)	164 ft² (2 + 1 containers)	160 ft² (1 + 1 containers)
	(3 + 1	(2 + 1	(2 + 1	(1 + 1

Table 7. Estimated indoor storage areas and number of containers – Organics

	240 litre cart	360 litre cart
North Tower + ½ Podium – residential	70 ft ² (6 + 1 carts)	62 ft² (4 + 1 carts)
	240 litre cart	360 litre cart
South Tower + ½ Podium – residential	70 ft ² (6 + 1 carts)	62 ft² (4 + 1 carts)
	240 litre cart	360 litre cart

Retail waste is not eligible for a municipal collection and therefore needs a private service provider to be collected.

Considering a once-a-week collection for the waste, the estimated size for the garbage rooms is:

For the North Tower (including ½ of the Podium's waste generation) – 752 ft² (69.9 m²) for garbage collected with 3 yd³ compacted containers, fibres (Black Box) collected with 3 yd³ non-compacted containers, containers (Blue Box) collected with 3 yd³ non-compacted containers and organics (Green Bin) collected with 240 litres carts. To be noted that the planned North Tower garbage room measures 83.0 m².



For the South Tower (including ½ of the Podium's waste generation) – 752 ft² (69.9 m²) for garbage collected with 3 yd³ compacted containers, fibres (Black Box) collected with 3 yd³ non-compacted containers (Blue Box) collected with 3 yd³ non-compacted containers and organics (Green Bin) collected with 240 litre carts. The planned South Tower Garbage Room measures 72.0 m².

For the commercial waste (private collection) – a minimum of 134 ft² (12.4 m²) for garbage collected with 360 litre carts, fibres (Black Box) collected with 360 litre carts, containers (Blue Box) collected with 360 litre carts and organics (Green Bin) collected with 240 litre carts. The planned retail garbage room measures 35.0 m².

These areas include sufficient space for manoeuvring the containers and for extra containers if needed. To be noted that compacted containers for garbage bigger than 3 yd³ are not recommended because of their weight.

It is anticipated but not confirmed that a baler and cardboard bales fits in the garbage rooms, as they will replace containers needed for cardboard (Black Box). To note that Black Box containers will still be needed for papers collection and for accumulating cardboard brought in by residents. The possibility to use a cardboard baler should be validated with the City of Ottawa, to check if it allows the installation of such equipment.

3.2 ADDITIONAL INFORMATION FOR INDOOR STORAGE

To the minimum areas calculated, it is recommended to add:

- A space for washing bins and containers;
- Besides the garbage rooms, an area is needed for storing bulky items (e.g., furniture) and other items eligible for special collection services. It is recommended that this area had between 100 ft² and 150 ft² (9.3 m² and 13.9 m²);
- To be noted that the compactors must not be accessible to the residents.

The indoor storage area should have:

- an adequate ventilation system and odor control to prevent the spread of odors;
- a floor drain, as the floor will need to be washed periodically;
- a water source for washing of the bins and containers;
- an epoxy coating on the concrete.

Although it is not required, it may be advisable to air-condition (10°C to 12°C) the storage room, at least for garbage and organic materials.



4. COLLECTION AREA REQUIREMENTS (538 UNITS)

Waste from the **residential units of both towers and the podium** will be collected at the same place in a loading bay and staging area located under the Podium. Therefore, the staging area should be large /long enough to accommodate all containers from residential units during collection time.

The retail will use the same loading bay and staging area as the residential, for waste collection.

The layout should allow containers to be accessible by the truck. Solid waste collection vehicle operator must not have to manually move the containers. However, if needed, arrangements can be made through the City's contracted hauler (at the property owner's expense) to manoeuvre a FEL garbage container for the required distance to facilitate collection.

The access route and loading area must be designed in such a way as to allow a collection vehicle to enter the site, collect the waste, and exit the site in a forward motion without the need to reverse onto a public road.

City of Ottawa's specifications for loading area and access route follows:

- Provide a loading area of 4.0 metres (13.1 ft) wide and 13.0 metres (42.6 ft) long (add 2.5 metres [8.2 ft] for each additional container) this will require a 40.5 m long loading area, considering 11 containers for garbage collection;
- Ensure the loading area is level (+/- 2% grade);
- Ensure the loading area is level with the storage/collection area;
- Ensure the loading area is not higher than 0.6m (2 ft) above the driveway levels;
- Provide a vertical loading clearance of 6.1 metres (20 ft);
- Design internal access routes with a minimum width of 6 metres (19.6 ft);
- Provide "no parking" signage for all internal access routes;
- Design and construct internal access routes with a hard surface material such as asphalt or concrete to support a minimum of 35,000 kilograms (the weight of a fully loaded waste collection vehicle);
- Provide 4.4 m (14.4 ft) vertical clearance throughout the access route;
- Provide the preferred grade of +/- 2% but no more than 8% grade for the access route;
- If drive-through access is not possible, provide a "T" type turnaround (see Section 8) to ensure that the collection vehicle does not have to back up through the site or back up onto a municipal road;
- Provide a hose bib within 60 metres (197 ft) of the storage/collection area and loading area;
- Provide adequate on-site space to ensure that snow and snow storage does not impede the access route(s), the storage/collection area, or loading area.

The space required for different types of equipment are presented below in **Table 8** (garbage), **Table 9** (Black Box), **Table 10** (Blue Box), and **Table 11** (organics).

Regarding the tables:



- Tables include the number of containers to be collected from both towers and the podium, (538 units) excluding the commercial waste;
- Other types of containers exist and could be considered, but the tables include the most common types and those most appropriate for the project;
- Front-end containers are used in the tables;
- The surfaces include the space for handling the equipment despite the presence of corners, doors and columns.

The municipal collection service available is indicated in **bold** in the tables. The recommended equipment, that respects the municipal collection requirements, is indicated in **bold and blue**.

Table 8. Estimated staging area needed and number of containers – Garbage

	2 yd³	3 yd³	4 yd³	6 yd³ non-
	compacted	compacted	compacted	compacted
North Tower + ½ Podium	288 ft²	222 ft ²	220 ft ²	400 ft ²
- residential	(7 containers)	(5 containers)	(4 containers)	(5 containers)
	2 yd³	3 yd³	4 yd³	6 yd³ non-
	compacted	compacted	compacted	compacted
South Tower + ½ Podium – residential	328 ft ²	222 ft ²	220 ft ²	480 ft²
	(8 containers)	(5 containers)	(4 containers)	(6 containers)
	700 P.			
	360 litre	660 litre	2 yd³ non-	3 yd³ non-
	carts	carts	compacted	compacted



Table 9. Estimated staging area needed and number of containers – Black Box

	2 yd³ non-	3 yd³ non-	4 yd³ non-	6 yd³ non-
	compacted	compacted	compacted	compacted
North Tower + ½ Podium – residential	246 ft²	178 ft ²	164 ft²	160 ft²
	(6 containers)	4 containers)	(3 containers)	(2 containers)
	2 yd³ non-	3 yd³ non-	4 yd³ non-	6 yd³ non-
	compacted	compacted	compacted	compacted
South Tower + ½ Podium – residential	246 ft²	178 ft ²	164 ft²	160 ft ²
	(6 containers)	(4 containers)	(3 containers)	2 containers)

Table 10. Estimated staging area needed and number of containers – Blue Box

	2 yd³ non-	3 yd³ non-	4 yd³ non-	6 yd³ non-
	compacted	compacted	compacted	compacted
North Tower + ½ Podium – residential	124 ft²	90 ft ²	110 ft²	80 ft²
	(3 containers)	(2 containers)	(2 containers)	(1 containers)
	2 yd³ non-	3 yd³ non-	4 yd³ non-	6 yd³ non-
	compacted	compacted	compacted	compacted
South Tower + ½ Podium - residential	124 ft²	90 ft ²	110 ft²	80 ft²
	(3 containers)	(2 containers)	(2 container)	(1 container)
		00.10		



Table 11. Estimated staging area needed and number of containers - Organics

3 3		
	240 litre cart	360 litre cart
North Tower + ½ Podium – residential	60 ft² (6 carts)	50 ft² (4 carts)
	240 litre cart	360 litre cart
South Tower + ½ Podium – residential	60 ft² (6 carts)	50 ft² (4 carts)
	240 litre cart	360 litre cart
Commercial	10 ft² (1 cart)	14 ft² (1 cart)

The area required for the residential stage pad is 1,100 ft² (102.2 m²) if both garbage, recyclables (Black Box and Blue Box), and organics are collected at the same time using 3 yd³ containers and 240 litre carts. This area was calculated in a conservative way, with ample space between containers. If only garbage and organics are collected at the same time, the area needed is 564 ft² (52.4 m²). For only recyclables and organics, the area needed is 656 ft² (60.9 m²).

For the retail waste, the area needed is 88 ft² (8.2 m²). Since it will use the same staging area as the residential waste, the surface is more than sufficient, considering that retail waste is collected in a different date/time than the residential waste.

5. RECOMMENDATION

In order to minimize the space required for the waste storage rooms and the staging pad, to facilitate operations, and to respect the requirements for a municipal collection the following equipment is suggested for the **residential** part of the project:

- 3 yd³ containers for the garbage stream (with compaction), collected once a week;
- 3 yd³ containers for the Black Box stream, collected once a week;
- 3 yd³ containers for the Blue Box stream, collected once a week;
- 240 litre carts for the organics stream, collected once a week;

A baler could be used to replace some of the containers for the Black Box stream, but a few containers will still be needed for this stream. The possibility to use a cardboard baler should be validated with the City of Ottawa, to check if it allows the installation of such equipment.

If the waste from the **retail store** is collected by a private hauler using 360 L bins instead of containers, it would allow an economy of space for the commercial garbage room. The 360 L bins could be used for garbage and recycling (both Black Box and Blue Box). Organics could be collected in 240 L bins.



6.CONTAINER HANDLING

Since containers must be moved from the waste storage room to the staging area, the use of a pull vehicle is recommended. Some examples of suitable vehicles are indicated below.

WasteCaddy - DJ Products

https://www.djproducts.com/product/dumpster-tow/

- Base price: around 7,500 US\$ + shipping
- Tow capacity: 2.3 tonnes / 5 000 lb
- 36 volts battery system
- Speed: 0 to 6 km/h (forward and reverse)
- Works on slopes, snow and ice
- Charger works on 120/220 Hz
- A more powerful model is also available:
 WasteCaddy HD model (10,300 US\$); 4.6 tonnes (10,000 lb);
 Able to pull containers over garage ramps.

https://youtu.be/XvLYGAd2CFY



V-Move XL+ 1.7 KW – Verhagen

https://www.xerowaste.ca/electric-tugs/v-move-xl-plus-electric-load-mover/

- Base price: around 14,400 CAN\$
- Tow capacity: 7.5 tonnes / 16 535 lb
- Tow capacity: 1.1 tonne (2,500 lb) on 18% slope
- Tow capacity: 0.6 tonne (1,400 lb) on 30% slope
- Speed: 0 to 6 km/h
- Propulsion: 24 volts
- Motor type: AC
- Battery type: 2 x 12 volts 50Ah AGM no maintenance (lithium in option)
- UL/CSA approved charger included

This is a more powerful model, able to move two containers at a time on a slope. Safer. Otherwise, there is also the V-Move XL 1.5 KW model, capable of pulling 1 container at a time (9,700 CAN\$).





AT800 TOW - MasterMover

https://www.mastermover.com/en-ca/products/at-tow-at800-tow/

Full price: 34,500 CAN\$Tow capacity: 8 tonnes

• Propulsion: 24V, 2 x 2.0 kW

• Motor type: AC

• Battery: 24 Volts, 119 Ah (lithium in option)

Max speed: 5 km/hRange of 4 km





7.ELIGIBLE CONTAINERS

The dimensions and other specifications included in this section are examples only. Final dimensions should be obtained from the selected service provider, as they could change per manufacturer or model chosen.

Container specifications from the City of Ottawa Solid Waste Collection Design Guidelines for Multi-Unit Residential Development.




Appendix A - Waste Collection Container Dimensions

Garbage Container Specifications

2 yard Container: Height 44 inch (excluding castors), Width 84 inch, Length 36 inch



84 inch pocket to pocket



2 Yard "Tall"

Height 56 inch Width 84 inch Length 25.5 inch Photo Unavailable

3 Yard Container Compacted: Height 56 inch (excluding castors), Width 84 inch, Length 42 inch






3 Yard "Tall"

Height 62 inch Width 84 inch Length 36.5 inch Photo Unavailable 4-Yard Container: Height 48 inch (excluding castors), Width 84 inch, Length 54 inch





4 Yard "Tall"

Height 66 inch Width 84 inch Length 40.5 inch Photo Unavailable

6 Yard Container: Height 60 inch, Width 84 inch, Length 66 inch





 Please note: all bins are available with plastic lids and castors. The 6-yrd bin has no castors. The width of all bins includes side-lifting pockets.

Solid Waste Collection Guidelines for Multi-Unit Residential Development

Page 16




Recycling Container Specifications

FEL Fibre Recycling Container Specifications


2 Cubic Yard: Height 38 inch (excluding castors), Width 84 inches, Length 35 inches





2 Cubic Yard "Tall": Height 58 3/8 inch (excluding castors), Width 84 inches, Length 28.25 inches






3 Cubic Yard: Height 48 inch (excluding castors), Width 84 inch, Length 42 inch


Photo Unavailable 4 Cubic Yard: Height 48 inch (excluding castors), Width 84 inch, Length 54 inch






4 Cubic Yard" Tall": Height 58 inch (excluding castors), Width 84 inch, Length 45 ½ inch





6 Cubic Yard: Height 60 inch (excluding castors), Width 84 inch, Length 67 inch





Solid Waste Collection Guidelines for Multi-Unit Residential Development

Page 17




2 Cubic Yard (Slant Style): Height 38 inch/front 44 inch/rear (excluding castors), Width 84 inch, Length 36 inch





2 Cubic Yard (Flat Style) "Tall": Height 48 inches (excluding castors), Width 84 inches, Length 36 inches





3 Cubic Yard: Height 43 inch/front 48 inch/rear (excluding castors), Width 84 inch, Length 43 inch





4 Cubic Yard Slant Style: Height 48 inch/front, 64 inch/rear (excluding castors), Width 84 inches, Length 48 inches





4 Cubic Yard "Tall": Height 58 inches (excluding castors), Width 84 inches, Length 45 $\frac{1}{2}$ inches



6 Cubic Yard: Height 60 inches (excluding castors), Width 84 inches, Length 67 inches



RECYCLING CART SPECIFICATIONS

Recycling Carts: Height 46.50 inch, Width 26.38 inch, Depth 33.62 inch





Page 18



Stationary mini-compactor 0.4 yd^{3 2}

Advantages:

- Designed to be used with garbage or recycling chutes,
- Reduces collection frequency by reducing the volume of material by 2 to 4 times, thus reducing the number of containers required and the space used by the containers,
- Deploys a superior and constant compaction force,
- Can be installed in any type of waste room,
- Safe equipment,
- Autonomous operation human intervention only to change the container,
- Can be adapted to compact without being attached to a chute.



Disadvantages:

- Cost in investment, maintenance, and operation;
- Weight of the bin is increased, therefore less easy to handle;
- Requires metal containers on wheels;
- Requires a bin lift if used without a chute.

Technical Specifications						
Capacity	0.4 cubic yard capacity 28" x 24" (71 x 61 cm) loading opening Cycle time: 35 seconds					
Dimensions	Width: 40½" (103 cm) Length: 71" (180 cm) Height: 38" without hopper (97 cm) Weight: 1,400 lbs (635 kg)					
Design	Motor: 3 HP, 600 volts Cylinder: 3" (7.5 cm)					



² https://industek.com/en/products/mini-stationary-compactor-fk04/

8.SECTIONS FROM THE CITY OF OTTAWA SOLID WASTE COLLECTION DESIGN GUIDELINES FOR MULTI-UNIT RESIDENTIAL DEVELOPMENT

Appendix C – 'T'-Turnaround Specification

Appendix F – Site Plan Checklist for Solid Waste Collection Design


Appendix G – Application Form for Solid Waste Collection

Appendix H - Acknowledgement and Release Form

Appendix I – Example Site Plan Agreement Conditions



Appendix C - "T"-Turnaround Specification



Solid Waste Collection Guidelines for Multi-Unit Residential Development

Page 20



Appendix F - Site Plan Checklist for Solid Waste Collection Design

Ensure that the following have been identified on the site plan drawing:					
Number of dwelling units and number of storeys in the development					
Proposed waste handling system for recyclables, organics and garbage					
Size and number of garbage and recycling receptacles to be used (i.e. for multi-unit buildings receiving front-end and/or semi-automated waste collection services)					
Loading facilities					
All waste storage facilities					
All waste collection areas	٥				
Access routes and dimensions for waste collection vehicles on private property					
Above ground features such as parking areas in relation to the access route	۵				
Pedestrian routes and building access(es) in relation to the access route					
Waste Management Brief if applicable					





Appendix G - Application Form for Solid Waste Collection

	APPLICATION FOR PRIVATE PROPERTY			Building Type	Number of Containers					
		COLLECTION SER		Site Plan Number	Size of ContainersCu. Yd.					
Ottawa				Number of Units	Number of Pick-Up Locations					
	Corporation of the City of Ottawa		Application for Private Property Waste Collection Services	Condominium?	Is Garbage Compacted? Yes No					
	City of Ottawa	City of Ottawa 3rd Floor, 150 Katimavik		Size of Enclosures	Number Enclosures					
		Kanata, ON K2L 2N2	Date: / /	Important Information						
			_	~ Collection area to be signed and kept clea						
Thedensioned as			ided by the City of Ottom	~ Collection area must be fully plowed and	saited during winter months					
The undersigned requests the waste collection service(s) as provided by the City of Ottawa, Public Works and Services.			ided by the City of Ottawa,	~ Do not place scrap in front of bins						
Fublic Works and a	ervices.			~ Regularly clean and sanitize containers ~ All waste must be set out for pick up before	so 7 am on your schoolyled collection day					
Please indicate which se	envice vou require			- All waste mast be set out for pick up before	re r am on your scrieduled collection day					
□ Front-End Contain		□ Curbside D	rive-Through Service	Note: Requests will not be processed unless the	aπached general release form is signed and sealed.					
Apartment Recycling Curbside Recycling				All applicants must provide a reduced site plan.						
Applicant		Property Owr	ner	For Office Use Only						
Address of Owner				Application Inspected by	Date of Inspection:					
City	Postal	CodeP	hone Number	Service Start Date	Zone					
Collection is requested at				Garbage Collection Days	Scrap Collection Day					
Name of Property		Contact			Recycling Collection Days					
Address		PI	hone Number	Comments						
				City of Ottawa Solid Waste Servi	ces Branch, 3rd Floor 150 Katimavik, Kanata, ON K2L 2N2					



Appendix H - Acknowledgement and Release Form

	A(CKNOWLEDGEMENT AND	RELEASE Acknowledgement			Public	Works and Servic	es	e City's Deputy City Manager of ontainers in good and operable	
	fawa of the		and Release			conditio		outpasson equipment of	and the st good and operation	
	City of	Ottawa City of Ottawa 3rd Floor, 150 Katimavi Kanata, ON K2L 2N2	K					ig set up for collection in ap ted date for collection.	proved containers no later than	
				.3)	The Own	er further acknowledges the	e City's waste coll	ection service is limited to:		
1)	in consideration of the C service,	eration of the Corporation of the City of Citawa (hereinafter the "City") providing a waste collection (hereinafter the "Owner") being the			a) Services as outlined in the City of Ottawa's Solid Waste Mar					
	registered Owner of		(here nafter the "lands") shall:							
	a)	Permit the City and its authorized agents of collection; and		4)	white goo	ds and applicances, apartr	ment fires, parking		d from building renovations, es being replaced on a mass basis. ement By-law.	
	b)		om all actions, causes of actions, damages, the City and its agenda utilizing the driveway	DATED			this		day of	
		ramp, loading and parking areas of the lar collection service, save and except any co- negligence of the City or those for whom it	sims or damages attributable to the		-	AND DELIVERED)	(Company Name)		
2) It is	It is herein acknowledge	is herein acknowledged by the Owner that the City's waste collection for the lands is conditional on:)) Per:	10.57		
	a)	The Owner providing free and clear acces satisfactory by the Public Works and Serv proposed route of access for collection pu building and parking lot which is attached	ces for these purposes. The Owner's rposes as set out on a plot plan of the)))) Per:	Name: Title:		
		ownering and parking lot which is attached	en eu.)	Name: Title:		

