

NOTES GÉNÉRALES General Notes	
<ol> <li>Ces documents d'architecture sont la proprié architect(e)s et ne pourront être utilisés, repr préalable. / These architectural documents a</li> </ol>	oduits ou copiés sans autorisation écrite re the exclusive property of NEUF
architect(e)s and cannot be used, copied or authorisation 2. Les dimensions apparaissant aux documents l'entrepreneur avant le début des travaux. / A	s devront être vérifiées par
documents must be verify by the contractor b 3. Veuillez aviser l'architecte de toute dimensio	pefore to start the work. In erreur et/ou divergences entre ces
documents et ceux des autres professionnel errors, omissions and discrepancies between others professionnals.	
<ol> <li>Les dimensions sur ces documents doivent é dimensions on these documents must be real</li> </ol>	
PLANNER FOTENN Planning and U 396, Cooper Street, Ottawa, ON K2P 2H7 T 613 730 5709 www.fotenn.com	rban design
LANDSCAPE ARCHITECT	
500 Bayview Ave, Suite 300 Toronto, ON M4W 3X sprucelab.ca	8
MECHANICAL / ELECTRICAL Smith + Andersen 600 Carling Avenue, Suite 530 Ottawa, ON K1Z 10 7613-230-1186 smithandandersen.com	63
CIVIL	
CIMA+ 600-1400 Blair Towers Place Ottawa, ON K1J 9B8 T 613-860-2462 cima.ca	
GEOTECHNICAL PATERSON GROUP 154 Colonnade Rd S, Nepean, On. K2E 7J5 T 613 226 7381 patersongroup.ca	
STRUCTURAL	
D+M Structural Engineer 333 Preston Street, Suite 110 Ottawa, ON K1S 5N T 613-651-9490 dm-structural.ca	
ENVIRONMENTAL Pinchin Ltd. 1 Hines Road, Suite 200 Kanata, ON K2K 3C7 T 855-746-2446 pinchin.com	
HERITAGE Bray Heritage	
BIAY FILLIAGE 837 Princess Street, Suite 400 Kingston, ON K7L T 613-542-3393 brayheritage.ca GENERAL CONTRACTOR	168
Doran Contractors Ltd. 3187 Albion Rd S Ottawa, ON K1T 1W9 T613-526-2400 doran.ca	
ENERGY MODELING EQ Building Perfomance 20 Floral Parkway Concord, ON L4K 4R1	Inc
T 416-645-1186 eqbuilding.com ARCHITECT	
NEUF architect(e)s 630, boul. René-Lévesque O. 32e étages, Montréa 7 514 847 1117 neuf.ca	al QC H3B 1S6
SCEAU / Seal	
S FROFESSIONAL SIE	
<b>J. M. E. POTVIN</b> 100208490	
0004/40/04	
BOWNCE OF ONTARIO	
	•
CLIENT Client	
150 Elgin St, Suite 1000 Ottawa, ON K2P 1L4 613-820-5600 windmilldevelopments.com	
OUVRAGE Project 384 ARLINGT(	Л
AVENUE	
EMPLACEMENT Location	NO PROJET №.
Adresse / Address	12805
NO RÉVISION	DATE (aa-mm-jj)
0 FOR SPC 1 FOR SPC FORMAL	2024-06-06 2024-10-04
DESSINÉ PAR Drawn by	VÉRIFIÉ PAR Checked by
DESSINE PAR Drawn by D.VAGHELA DATE (aa.mm.jj)	VERIFIE PAR Checked by É. POTVIN ÉCHELLE Scale
2024-10-04 TITRE DU DESSIN Drawing Title	1:150
TOPOGRAPHICAL	•
SEDIMENT, EROS AND DEMOLITION	
RÉVISION Revision	NO. DESSIN Dwg Number
	C001

#### 1. <u>GENERAL</u>

- 1.1. The Contractor must conform to all laws, codes, ordinances, and regulations adopted by federal, provincial or municipal government councils and government agencies, applying to work to be carried out.
- 1.2. Unless otherwise indicated, all materials and construction methods to be in accordance with the requirements of the latest edition of the Ontario Provincial Standard Specifications and Drawings (OPSS and OPSD), the Ontario Ministry of Environment, Conservation and Parks (MECP), applicable Conservation Authorities (CA), the municipal standard specifications and drawings, and all other governing authorities as they apply.
- 1.3. Wherever standards, laws and/or regulations are mentioned they refer to their current versions, modifications included.
- 1.4. The Contractor is responsible for obtaining all permits required to complete all works and bear cost of same, including road cut permit and water permit and their associated costs
- 1.5. The Contractor is responsible for the coordination of his activities with others on
- 1.6. Independent géotechnical laboratory for quality control: 1.6.1. An independent geotechnical laboratory hired by the Owner will perform material testing, inspection and quality control services.
- 1.6.2. Geotechnical laboratory to review asphalt and concrete mix designs as requested.
- 1.6.3. The Contractor must provide equipment required for executing inspection and testing by appointed geotechnical firm.
- 1.6.4. The Contractor must provide labour and facilities to obtain and handle samples and materials on site. Provide sufficient space to store and cure test samples.
- 1.6.5. Employment of geotechnical laboratory does not relax responsibility to perform work in accordance with Contract Documents.
- 1.6.6. If defects are revealed during inspection and/or testing, appointed geotechnical firm will request additional inspection and/or testing to ascertain full degree of defect. Contractor to correct defect and irregularities at no cost to Owner. Contractor to pay costs for retesting and reinspection.
- 1.7. The location of existing underground municipal services and public utilities as shown on the plans are approximate. The Contractor must determine the exact location, size, material and elevation of all existing utilities (on-site and off-site) prior to any excavation work. Damage to any existing services and/or existing utilities during construction, whether or not shown on the drawings must be repaired by the Contractor at his own expense.
- 1.8. Site preparation includes clearing, grubbing, stripping of topsoil, demolition, removal of unsuitable materials, cut, fill and rough grading of all areas to receive finished surfaces
- 1.9. All material must be compacted as per the requirements of the governing authority and be approved by the Consultant prior to delivery to the site.
- 1.10. Compaction must conform to the following requirements: Exposed subgrade: 95% Standard Proctor maximum dry density (SPMDD) <u>Subgrade fill</u> (landscaping areas): 95% Standard Proctor Maximum Dry Density (SPMDD) - <u>Subgrade fill</u> (pavement areas - OPSS Select Subgrade Material): 98% Standard Proctor Maximum Dry Density (SPMDD) - Pavement Granular Subbase foundations: 100% Standard Proctor maximum dry density (SPMDD) Pavement Granular Base foundations 100% Standard Proctor maximum dry density (SPMDD) Asphalt pavement
  - City of Ottawa Special Provisions F-3130
  - <u>Structural fill</u> (building and light standard footprints OPSS Granular 'A' or Granular 'B' Type II Material): 98% Standard Proctor Maximum Dry Density (SPMDD)
- 1.11. It is anticipated that groundwater infiltration into excavations should be low to moderate and controllable using open sumps. The contractor should be prepared to direct water away from all subgrades, regardless of the source to prevent disturbance to the founding medium. Dewatering of excavations to be as per OPSS.MUNI 517. As required under the "Ontario Water Resources Act (OWRA)", the Contractor must register all water taking activities on Ontario's "Environmental Activity and Sector Registry (EASR)" if water taking exceeds 50,000 I/day, and obtain a "Permit to Take Water (PTTW)" if water taking exceeds 400,000 l/day. Furthermore, Contractor must provide all necessary measures required to ensure dewatering operations does not affect in any way the integrity of the existing surrounding buildings and must plan his work accordingly. Water Taking and Discharge Plan to be prepared by a Qualified Person as stipulated under O.Reg. 63/16.
- 1.12. Control disposal or runoff of water containing suspended materials or other harmful substances in accordance with local authority requirements and as
- 1.12.1. Provide flocculation tanks, settling basins, or other treatment facilities to remove suspended solids or other materials to within the required parameters of the receiving body before discharging to storm sewers, watercourses or drainage areas.
- 1.12.2. Before discharging to storm sewers, watercourses or drainage areas, discharge water must be sampled and tested to ensure quality requirements in accordance with City of Ottawa Sewer Use By-Law No. 2003-514 and the MECP are adhered to. The Contractor is to perform all additional sampling and testing as required by City of Ottawa. All associated fees to be paid by the Contractor.
- 1.12.3. Where water is not suitable for discharge into the adjacent storm sewers, watercourses or drainage areas it must be discharged into the on-site sanitary sewer collection system, or disposed off-site at an approved disposal facility.
- 1.12.4. Combined Sewer Discharge: When discharging to the combined sewer, the Contractor must obtain a Sanitary/Combined Sewer Agreement for Dewatering from the City of Ottawa in accordance with City of Ottawa Sewer Use By-Law No. 2003-514 and pay all associated fees.
  - A copy of the signed Combined Sewer Agreement for Dewatering must be provided to the Departmental Representative in advance of dewatering and discharge.
  - The Contractor must ensure all requirements of the Discharge Agreement are adhered to and all prerequisite requirements of the
  - Agreement are in place prior to commencing dewatering. - Provide flow meter and record discharge rate in accordance with City of
  - Ottawa requirements. Dewatering discharge rate to combined sewer not to exceed rate
  - specified by City.
- 1.13. The Contractor must maintain benchmarks and landmark references as is. Otherwise these references will be repositioned by a certified land surveyor at the Contractor's expense.
- Contractor is responsible for providing adequate protection of the workers, other personnel and the general public, protection of materials, as well as maintaining in good condition the completed works and works to be completed. The Contractor must supply, install and maintain an appropriate safety fence along the work perimeter until the work is complete.
- The Contractor must provide at any time:
- A sufficient number barriers, posters, guards and others to ensure safety; Necessary conveniences for the completion of the work such as heating, lighting, ventilation, etc.
- 1.15. Temporary excavations in the overburden must be completed as per the equirements of the Occupational Health and Safety Act (OHSA), O. Reg. 213/91, Part III - Excavations.

The side slopes of excavations in the soil and fill overburden materials should either be cut back at acceptable slopes or should be retained by shoring systems from the star of the excavation until the structure is backfilled. The excavation side slopes above the groundwater level extending to a maximum depth of 3 m should be cut back at 1H:1V or flatter. The flatter slope is required for excavation below groundwater level. The subsurface soil is considered to be mainly a Type 2 and 3 soil according to the Occupational Health and Safety Act and Regulations for Construction Projects. Slopes in excess of 3 m in height should be periodically inspected by the geotechnical consultant in order to detect if the slopes are exhibiting signs of distress.

- 1.16. The Contractor must pace deliveries and removals in order to minimize and control stockpiles
- 1.17. Stockpile material must be stored away from excavations at a distance at least equal to the depth of the excavation. Construction traffic should be limited near open excavation

#### 1 18 Cleanliness on the site

- The Contractor must clean roadways at his own cost as directed by the Owner's representative - All site roads and walkways to and from the construction zone must be
- kept clean at all times, from mud, dirt, granular material, debris, etc.; - The Contractor must leave the work area clean at the end of each day; - Materials and equipment must be laid out in an organized and safe
- manner: - All material, equipment and temporary structures which are no longer necessary for the execution of the Contract must be removed from the
- If required the Contractor must reduce noise, dust, interference, obstruction, etc., in conformity with the requirements of the provincial and municipal authorities having jurisdiction.
- 1.19. During the construction period the Contractor is responsible for installing and maintaining temporary traffic signage, including traffic signs, traffic markings and temporary traffic lights, and flagmen, as required by the Owner, the Consultant, the Municipality and other governing authorities.
- 1.20. The Contractor must control surface runoff from precipitation during construction

#### SEDIMENT AND EROSION CONTROL

- 2.1. Specifically, sediment and erosion control measures to be constructed as per OPSS.MUNI 805
- 2.2. The Contractor must implement best management practices, to provide for protection of the area drainage system and the receiving watercourse as well as air pollution from dust and particle matter, during construction activities. The contractor acknowledges that failure to implement appropriate erosion and sediment control measures may be subject to penalties imposed by any applicable regulatory agency.
- The Contractor must set up the measures shown on the plan, inspect them frequently and clean and repair or replace the deteriorated structures.
- 2.4. The light duty silt fence barrier must be installed as per OPSD 219.110.
- 2.5. Provisions must be made for sediment and erosion control measures prior to stripping the site of vegetation and other deleterious materials. Measures such as silt fences, etc. must be constructed and maintained in order to control sediment, as required by the provincial and municipal governing authorities.
- 2.6. When the sediment and erosion control measures have to be removed in order to complete a portion of the work, these same measures must be reinstated.
- 2.7. When storing soil on site in piles the Contractor must cover each pile with tarps, straw or a geotextile fabric to avoid fine particle transport by wind and/or streaming rainwater
- 2.8. During the construction period, sediment capture silt sacks or filter cloths must be installed and maintained between the frame and cover of all catchbasins and catchbasin/manholes to minimize sediments entering the storm sewer system All landscaping areas must be completed prior to the removal of the silt sacks or filter cloths.
- 2.9. At all times the Contractor is responsible to maintain the municipal access roads clean and free of mud, debris and sediments. When cleaning the access roads the Contractor must take the necessary precautions to clear the surfaces covered with sediment prior to cleaning with water.
- 2.10. At the end of the construction period, the Contractor is responsible for removal of the temporary sediment and erosion control measures and reconditioning the affected areas.
- 2.11. This plan is a "Living Document" which may be revised in the event that the control measures are not sufficient

### DEMOLITION AND REMOVALS

- 3.1. The Contractor must visit the premises in order to be fully aware of existing conditions on site, including all elements to be removed and demolished. No claim will be accepted due to a poor evaluation of the work to be completed.
- 3.2. The Contractor must protect and maintain in service the existing works which must remain in place. If they are damaged, the Contractor must immediately make the replacements and necessary repairs to the satisfaction of the Owner's representative and without additional expense to the Owner.
- 3.3. The Contractor must perform the nessessary clearing and grubbing in accordance with OPSS.MUNI 201.

accordance with OPSS.MUNI 180 and OPSS.MUNI 510.

- 3.4. The Contractor must carry out necessary saw cuts even if they are not shown on the drawings.
- 3.5. The Contractor must entirely remove the demolition wreckage from the construction site in accordance with the requirements of the MECP and in
  - The Contractor must discard recyclable demolition materials in collaboration with a regional recycling company. The Contractor must be able to provide proof, upon request, that the materials were properly recycled and that the chosen recycling company is recognized in the recycling field.
  - All other demolition materials must be disposed off-site at authorized licensed landfills and in conformity with the applicable laws and regulations. The Contractor must be able to provide, upon request, copies of the disposal tickets.
- 3.6. The Contractor is responsible for locating existing public utilities and (if required) submit a request for the interruption of public utility services, such as gas, telephone, power, cable, sewers, watermain, etc.
- 3.7. Sewer and water laterals to be abandoned must be blanked, capped, and fill with unshrinkable concrete conforming to City of Ottawa Special Provisions F-4104, F-4411, and OPSS 510 as well as the City of Ottawa Standard Detail
- 3.8. The Contractor must conduct all removals required to make the work complete. 3.9. Unless otherwise specified, all materials, products and others coming from the
- 1.14. The Contractor is the only person in charge of safety on the building site. The 3.10. Surfaces and works located outside of the construction work limit must be reinstated as they were before beginning of work.

### GENERAL SUBGRADE PREPARATION

demolition belong to the Contractor.

- 4.1. Earth removal must be inspected by an experienced Geotechnical Engineer to ensure that all unsuitable materials are removed prior to the placement of fill. including concrete and/or others, and to confirm the compaction degree and condition of the founding soils. All unsuitable materials must be hauled off site and disposed as per provincial and municipal regulations.
- 4.2. Subgrade must be approved by experienced geotechnical personnel before proceeding with placement of fill.

All soft, wet or disturbed areas revealed under surface compaction must be 43 removed to a minimum depth of 500 mm and replaced with compacted suitable subgrade fill as directed by the Geotechnical Engineer and/or an approved non-woven Class 1 geotextile, as per OPSS 1860.MUNI. Transition around sub-excavation, where backfill and native material are not of similar nature, must be sloped at 3 horizontal to 1 vertical, within 1.2 m of finished surface.

# quickly as possible.

4.6.

4.7.

Excess soils generated must be managed in accordance O.Reg. 406/19 made under the Environmental Protection Act, R.S.O. 1990, c.E19 (EPA) and the adopted by reference "Rules for Soil Management and Excess Soil Quality Standards" (the 'Soil Rules') as well as other regulatory amendments related to the management of excess soil. Excess soil is defined as non-hazardous soil, or soil mixed with rock, that has been excavated as part of a project and removed from the project area for the project. As it relates to this Contract, the Project Leader is "the Client", as per the definition under O.Reg. 406/19.

Where excess soils are anticipated to be generated, a notice is to be filed to the Resource Productivity and Recovery Authority (RPRA or successor organization) Excess Soils Registry (the 'Registry') prior to the removal of excess soil from the project area unless exempt in accordance with the Regulation. The Contractor is to provide "the Client" all information required for filing the notice to the Registry. - A Soil Management Plan is to be developed by the Contractor for submission to "the Client". Where applicable, the Soil Management Plan is to be prepared in accordance with the MECP Management of Excess Soil - A Guide for Best Management Practices and in accordance with O.Reg. 406/19. - The Contractor is responsible for retaining a Qualified Person (QP\_{ESA}, as per the definition under O.Reg. 153/04) to evaluate and provide all the necessary services required in accordance with O.Reg. 406/19. The services may include but not be limited to an Assessment of Past Uses Sampling and Analysis Plan, Soil Characterization Report, and Excess Soil Destination Assessment Report, collectively described as the 'Planning Documents', as specified within the Soil Rules. The Contractor may rely on existing Planning Documents and/or site characterization reports where provided "within the Contract Documents OR by the Engineer" in relation to Excess Soils. The Contractor is responsible to finalize any preliminary Planning Document reports required, identify proposed soil destination site(s) for "the Client" approval, and satisfy all associated requirements specified by the selected destination site. - The Contractor is responsible to notify "the Client" if actual construction activities and/or site conditions encountered are not consistent, or appear not to be consistent, with the information presented within the Planning Documents.

- The Contractor is responsible to implement a tracking system in accordance with O.Reg. 406/19, to track each load of excess soil during its transportation and deposit at the approved destination site (i.e. reuse site, Class 1 soil management site, local waste transfer facility, landfilling site or dump, and any transportation to and from a Class 2 soil management site).

and zinc.

# EXCAVATION AND BACKFILI Subgrade Preparation"

excess soils with O.Reg 406/19.

# settlement sensitive structures 5.4.

more than 25% silt.

# 5.5. fill should be compacted in thin lifts.

5.6. Structural fill used for grading beneath the footings of buildings, signs and light standards must consist of OPSS Granular 'A' or Granular 'B' Type II Material.

5.7. by hoe-ramming.

Explosives, as amended.

# carried out.

residents.

As a general guideline to reduce the risks of damage to the existing structures, peak particle velocity (measured at the structures) during construction must not exceed 20 mm/s for frequencies below 40 Hz, and 50 mm/s for frequencies 40 Hz and higher. The warning level limits are 10 mm/s for frequencies below 40 Hz, and 40 mm/s for frequencies 40 Hz and higher.

elevation

5.8.

5.9.

If construction is required during freezing temperatures, the native soils should be protected immediately from freezing using straw, propane heaters, polystyrene insulation, insulated tarpaulins, or other suitable means that prevent the underlying native soils from freezing, which could cause significant frost

4.5. All granular fill must be placed in maximum 300 mm thick loose lifts and compacted using suitable methods as per the requirements.

All heavy equipment must not operate directly on the subgrade. A minimum of 500 mm of fill must be used to allow traffic over subgrade. Subgrade surfaces will be prone to disturbance by weather and traffic, therefore preparation of the subgrade must be scheduled such that the granular materials are placed as

4.8. If contaminated material is encountered during the work, the Contractor must dispose off-site all materials from the contaminated area in accordance with the equirements of the MECP and OPSS.MUNI 180. Prior to the start of work the Contractor must provide the name and location of landfill(s) where the contaminated materials will be disposed to the Consultant. The Contractor must obtain from the landfill Owner documents confirming that he has the right to accept the contaminated material. During the work, the contractor must provide the Consultant copies of all check-in receipts issued by the landfill Owner.

The Contractor is responsible for providing a confirmation that the imported material used as subgrade fill is free of any contaminants such as Petroleum Hvdrocarbons (C10-C50), PAH (Polycyclic Aromatic Hydrocarbons), MAH (Monocyclic Aromatic Hydrocarbons) and metals like mercury, silver, arsenic cadmium, cobalt, chromium, copper, tin, manganese, molybdenum, nickel, lead

5.1. Subgrade preparation must be completed as per Section "4.0 General

5.2. The management of excess materials to comply with OPSS.MUNI 180 and any

5.3. Topsoil and deleterious fill, such as those containing organic materials, must be stripped from under any buildings, paved areas, pipe bedding, and other

Subgrade fill used for grading beneath asphalt or concrete pavement must consist of OPSS Select Subgrade Material or equivalent, approved by the Geotechnical Engineer prior to delivery to the site. Subgrade fill used below rigid surfaces, such as concrete sidewalks and concrete slabs, must not contain

Non-specified fills and on-site excavated soils may be used in landscaping areas where settlement of the ground surface is of minor concern. This material must be spread in thin lifts and compacted by the tracks of spreading equipment to minimize voids. When used to build up subgrade level in areas to be paved

It is expected that line-drilling in conjunction with hoe-ramming, rock grinding and controlled blasting will be required to remove the bedrock for the underground parking levels. In areas of weathered bedrock and where only a small quantity of bedrock is to be removed, bedrock removal may be possible

Pre-Construction Survey (Piling/Hoe Ramming, Rock Anchors, Shoring and/or close proximity to City Assets) or Pre-Blasting Survey will be required for any buildings/dwellings within proximity of 75m of the site. Circulation of notice of vibration/noise is required to residents within 150 m of site. Conditions for Pre-Construction/ Pre-Blast Survey & Use of Explosives will be applied to agreements. Refer to City's Standard S.P. No. F-1201 entitled Use of

Rock excavation must conform to OPSS 403.MUNI and to all laws, codes, ordinances and regulations adopted by federal, provincial and municipal government councils and government agencies, applying to the work to be

Construction operations could cause vibrations, and possibly, sources of nuisance to the community. Vibrations caused by blasting or construction operations (e.g. piling equipment, hoe ram, compactors, dozers, cranes, etc.) could cause detrimental vibrations on the adjoining buildings and structures as well as being a source of nuisance to the community. Therefore, means to reduce the vibration levels as much as possible must be incorporated in the construction operations to maintain a cooperative environment with the

5.10. Excavation side slopes in sound bedrock may be completed with almost vertical side walls. A minimum of 1 m horizontal ledge must remain between the bottom of the overburden and the top of the bedrock surface to provide an area for potential sloughing. The 1 m horizontal ledge set back can be eliminated with a shoring program which has drilled piles extending below the proposed founding

### PAVEMENT STRUCTURES, CURBS, AND SIDEWALKS

6.1. Construction of granular foundation must conform to City of Ottawa Special

- 6.2. Granular materials used on site must conform to the requirements of OPSS.MUNI 1010.
- 6.3. Road cut reinstatement as per City of Ottawa Detail R10.
- 6.4. Construction of asphalt must conform to City of Ottawa Special Provision F-3130.
- 6.4.1. Paving must not be carried out if the roadbed is frozen or wet.
- The granular grade must be free of standing water at the time of hot mix 6.4.2. asphalt placement. The surface of a pavement upon which hot mix asphalt is to be placed must be dry at the time of hot mix asphalt placement. Following the final compaction of a hot mix asphalt course, a 4 hour minimum time laps must be respected before placing a new new hot mix asphalt course. Additionally, the temperature of the previous course must be 60°C or less.
- 6.4.3. The asphalt base coarse must not be placed unless the air temperature at the surface of the road is a minimum of 2°C and rising.
- The asphalt surface coarse must not be placed unless the air temperature 6.4.4. at the surface of the road is a minimum of 7°C, except for SMA and Superpave 12.5 FC2, where the air temperature at the surface of the road shall be minimum 12°C.
- Asphalt concrete material must conform to City of Ottawa Special Provision 6.5. F-3104 and OPSS.MUNI 1150 for HL hot mix asphalt mixtures, and City of Ottawa Special Provision F-3106 for Superpave hot mix asphalt mixtures. Minimum Performance Graded (PG) 58-34 asphalt cement must be used for this project.
- Asphalt mix design must be reviewed and approved by a Geotechnical 6.6. Engineer before paving
- 6.7. Concrete curbs must conform to OPSS 353.MUNI and City of Ottawa Special Provisions F-3531, F-9040 and F-9045.
- 6.8. Concrete curbs to be constructed as per City of Ottawa Detail SC1.1.
- 6.9. Concrete sidewalks must conform to City of Ottawa Special Provisions F-3510, F-9040 and F-9045
- 6.10. Concrete sidewalks to be constructed as per City of Ottawa Details SC2, SC5, SC6 and SC7.1.
- 6.11. For all concrete placement during cold weather Contractor must place material in accordance to City of Ottawa Special Provision F-9040.

MISCELLANEOUS

- 7.1. Free standing signs to comply with Detail 401.
- Existing pavement markings in municipal right-of-way to be reinstated if erased/partially removed during construction. Pavement markings to be "Organic Solvent Based" as per OPSS.MUNI 710 and OPSS.MUNI 1712.
- 7.3. Tactile Walking Surface Indicators (TWSI) to be constructed as per detail SC7.3. Product shall be from the following list or approved equivalent:

Manufacturer		Specific Model (when applicable)
Manufacturer		Specific Model (when applicable)
ADA Solutions	<b>→</b>	Irondome
Advantage Cast Iron		
Bibby Ste. Croix	$\rightarrow$	Safety Detection System
Cedar Infrastructure		
East Jordan	$\rightarrow$	Duralast
Ironped		
Neenah		
OUC		
Star Pipe Products		

### 8. MUNICIPAL SERVICES - GENERAL

- 8.1. The location of existing underground municipal services and public shown on the plans are approximate, the contractor must determine location, size, material and elevation of all existing utilities (on-site a prior to any excavation work. Damage to any existing services and/ utilities during construction, whether or not shown on the drawings r repaired by the contractor at his own expense. 8.2. Terminate and plug water and sanitary service connections at 1.0 m edge of the building/underground parking. Terminate storm service of at the cistern. 8.3. Combined service lateral trenches must be as per City of Ottawa De 8.4. The Contractor must complete trench and backfill compaction as pe OPSS.MUNI 401 and OPSS.MUNI 501: MATERIALS COMPACTION Pipe bedding 98% SPMDD 98% SPMDD Pipe cover Trench backfill 98% SPMDD 98% SPMDD Structure bedding 8.5. The Contractor is responsible for making or arranging all connection existing sewers as per municipal requirements. Prior to connection. Contractor must provide, to the Engineer and the City for approval, results performed on the internal services. Test results must include inspection of sewers, infiltration/exfiltration tests for sewers and man deformation tests of sewers, watermain hydrostatic leakage test, flus disinfecting operations, and bacteriological water analysis.
- 8.6 Advise the City Public Works at least 72 hours in advance before at connection to the City services. Coordinate with City as required.
- 8.7. The Contractor must determine the exact invert (geodetic elevation) and construction material of the existing conduits at the proposed co He must also carry out, if necessary, exploratory excavations in orde determine the exact location and inverts of existing duck banks. Thi must immediately be provided to the Engineer prior to start undertal municipal services work and a 48 hour period must be allocated to for design review.
- 8.8. The Contractor is responsible for all excavation, backfill and reinstate areas disturbed during construction to existing conditions or better a associated works to the satisfaction of the Engineer and municipal a
  - Asphalt reinstatement must be in accordance with OPSS.MUNI City of Ottawa Standard Detail R10. Landscape areas to be reinstated in accordance to landscaping and specifications.
- 8.9. Within landscaping areas, backfill for service trenches may consist of material replaced and compacted in lifts.
- 8.10. A minimum of 150 mm of OPSS Granular A must be used for pipe to sewer and water pipes and must extend to the spring line of the pipe material from the spring line to at least 300 mm above the pipe obvert must also consist of Granular A material. Bedding and cover material must be placed in maximum 225 mm lifts.
- 8.11. Where hard surface areas are considered above the trench backfill, the trench backfill material within the frost zone (about 1.8 m below finished grade) and above the cover material should match the soils exposed at the trench walls to minimize differential frost heaving. The trench backfill should be placed in maximum 225 mm thick loose lifts. All cobbles larger than 200 mm in their longest direction should be segregated from re-use as trench backfill.
- 8.12. All existing sewer and water services are to be adequately blanked as per City of Ottawa Special Provision F-4104, F-4411, OPSS 510 and Drawing S11.4. Refer to Topographical Survey, Sediment, Erosion Control and Demolition plan.

9. WATERMAIN

- 9.1. Water pipe materials must be Pressure Class 150, DR 18, manufactured to WWA C-900 and CSA B137.3 or Pressure Class 235psi/1620 kPA AWW C-909 and CSA B137.3.1 standards. Pipe shall have the cast iron outside diameter dimensions, be blue in colour and supplied complete with gaskets Furthermore, watermain, water service connections and associated appurtenances must be constructed in accordance with the OPSS.MUNI 441.
- 9.2. All watermain must be installed with a minimum of 2.40 metres cover from finished grade. Where a minimum of 2.40 metres cover is not reached, thermal insulation is required as per City of Ottawa Details W22 and W23. Insulation for use in roads over pipe trenches shall: - be type Extruded Polystyrene Foam Insulation Boards (XPS) in 600 x 2400
  - x 50mm size;
  - meet the requirements of OPSS.MUNI 1605; Grade A (275 kPa compressive strength shall meet ASTM C578 Type VI;
- Grade B (400 kPa compressive strength shall meet ASTM C578 Type VII.
- 9.3. Tracer wire to be as per City of Ottawa Detail W36.
- 9.4. Cathodic protection must be installed as per City of Ottawa Details W40 and
- 9.5. Thrust block and restraints must be as per City of Ottawa Details W25.3, W25.4, W25.5 and W25.6.
- 9.6. Valves to be installed as per City of Ottawa Special Provision F-4413 and conform to the following:
- All valves must open in a clockwise direction; Valves between 100-300mm range to be resilient seat gate valves (AWWA C515) with mechanical joint connections.
- 9.7. Valve box assembly to be as per City of Ottawa Detail W24. In asphalt, install floating valve boxes equivalent to Bibby-Ste-Croix equipped with a ductile iron floating top extension (i.e. adjustable road leveler). In concrete, installed sliding valve boxes equivalent to Bibby-Ste-Croix equipped with stantard sliding flat top (no floating extension).
- 9.8. When a watermain pipe crosses a sewer pipe, installation must be as per City of Ottawa Details W-25 and/or W-25.2.
- 9.9. All watermains must be thoroughly flushed and cleaned to remove all dirt and debris prior to the disinfection process
- 9.10. All watermains must be hydrostatically and bacteriologically tested as per provincial and municipal regulations. It is the Contractor's responsibility to ensure that all requirements are followed.
- 9.11. The Contractor must make arrangements with and give a minimum of 24 hours' notice to the City for the closing off of necessary valves in the water distribution system. The City will operate valves at the time of tie-ins, etc. at no expense to the Contractor under normal conditions; however the Contractor will be responsible for all costs associated with emergency shutdowns if they occur outside of the normal working hours of the City forces (Monday to Friday, 7:00 a.m. to 5:00 p.m.)
- 9.12. Hydrostatic testing to be completed as per OPSS 441.07.24. Testing must be completed under the supervision of the Contract Administrator. The test section will be either a section between valves or the completed watermain. Test pressure to be 1035 kPa.
- 9.13. The Contractor must obtain a permit from the City before using an existing fire hydrant located within the City's territory.
- 9.14. The Contractor must coordinate and pay the cost of connection, inspection and lisinfection by municipal personnel. Service connection to be as per City of Ottawa Special Provision F-4411 and F-4418 as well as Detail W50.
- 9.15. Contractor must coordinate the supply and installation of water meter and remote water meter for the building with the mechanical engineer.

	10. <u>ST</u>	ORM SEWER
utilities as e the exact and off-site) or existing must be	10.1.	Storm pipe materials must be SDR 35 conforming to OPSS 1841, unless noted otherwise on the drawings. Sewer pipe and fittings must be certified to CSA standards B182.2 or CSA B182.7. Furthermore, storm sewer, storm lateral and associated appurtenances must be constructed in accordance with the OPSS.MUNI 410.
neter from connections	10.2.	The allowable deflected pipe diameter when using flexible pipe is as follows: - Pipes 100 to 750 mm: 7.5% of the base inside diameter of the pipe.
etail S7. er	10.3.	Final backfill material for storm sewers must be approved native material or select subgrade material in conformance with OPSS.MUNI 212 and City of Ottawa Special Provision F-2120.
	10.4.	All storm sewers to be C.C.T.V. inspected by the Contractor as per OPSS.MUNI 409 and City of Ottawa Special Provision F-4090. Report must be provided to the Engineer in two (2) copies and the C.C.T.V. inspection in DVD format only.
	10.5.	Adjustment or rebuilding of manholes, manhole/catchbasins, catchbasins, ditch inlets and valve chambers to be completed as per OPSS.MUNI 408 and City of Ottawa Special Provisions F-4080 and F-4081.
ns to the the all test c.C.T.V. nholes, ishing and	10.6.	The Contractor must implement best management practices to provide for protection of receiving storm sewer or drainage during construction activities (i.e. catchbasin inserts (or approved equivalent), straw bale check dams, any other sediment control measures required around all disturbed areas). Dewatering must be sumped into sediment traps.
0	10.7.	For building roof drain sizes and location refer to architectural and mechanical drawings.
ny	10.8.	For the storm cistern specifications, refer to architectural and mechanical.
), diameter onnections. er to	11. <u>SA</u>	NITARY SEWER
is information king any the Engineer	11.1.	Sanitary pipe materials must be SDR 35 conforming to OPSS 1841, unless noted otherwise on the drawings. Sewer pipe and fittings must be certified to CSA standards B182.2 or CSA B182.7. Furthermore, sanitary sewer, sanitary lateral and associated appurtenances must be constructed in accordance with the OPSS.MUNI 410.
tement of all and all authorities.	11.2.	<ul> <li>The allowable deflected pipe diameter when using flexible pipe is as follows:</li> <li>Pipes 100 to 750 mm: 7.5% of the base inside diameter of the pipe.</li> </ul>
II 310 and g drawings	11.3.	Final backfill material for sanitary sewers must be approved native material or select subgrade material in conformance with OPSS.MUNI 212 and City of Ottawa Special Provision F-2120.
of excavated	11.4.	Il sanitary sewers to be C.C.T.V. inspected by the Contractor as per OPSS.MUNI 409 and City of Ottawa Special Provision F-4090. Report must be provided to the Engineer in two (2) copies and the C.C.T.V. inspection in DVD format only.
bedding for e. Cover	44.5	

- 11.5. Sanitary manholes to be installed as per OPSS.MUNI 407 and conform to OPSS 1351 and City of Ottawa Special Provisions F-4070. 11.6. Excavating, backfilling, and compacting for sanitary manholes to be completed as per OPSS.MUNI 402.
- 11.7. Sanitary manholes to be backfilled with OPSS Granular 'B'. Joints between sections must be wrapped in a non-woven geotextile.
- 11.8. Sanitary manholes to be as per OPSD 701.010 (sizes specified on drawings) and must be equipped with safety platform as per OPSD 404.020 when exceeding 5.0 m to the lowest invert.
- 11.9. Sanitary manhole frame and cover to be as per OPSD 401.010 Type "A" closed
- 11.10. Sanitary service connections to main sewer pipe to be as per City of Ottawa Detail S11.1 (for flexible main).
- 11.11. Benching is required inside the concrete bottom of sanitary manholes as per

NOTES GÉNÉRALES General Notes

- 1. Ces documents d'architecture sont la propriété exclusive de NEUF architect(e)s et ne pourront être utilisés, reproduits ou copiés sans autorisation écrite préalable. / These architectural documents are the exclusive property of NEUF architect(e)s and cannot be used, copied or reproduced without written pre-
- 2. Les dimensions apparaissant aux documents devront être vérifiées par l'entrepreneur avant le début des travaux. / All dimensions which appear on the documents must be verify by the contractor before to start the work.
- 3. Veuillez aviser l'architecte de toute dimension erreur et/ou divergences entre ces documents et ceux des autres professionnels. / The architect must be notified of all errors, omissions and discrepancies between these documents and those of the

4. Les dimensions sur ces documents doivent être lues et non mesurées. / The dimensions on these documents must be read and not measured

FOTENN Planning and Urban design 396, Cooper Street, Ottawa, ON K2P 2H7 T 613 730 5709 www.fotenn.com

LANDSCAPE ARCHITECT SPRUCE LAB 500 Bayview Ave, Suite 300 Toronto, ON M4W 3X8 sprucelab.ca

MECHANICAL / ELECTRICAL Smith + Andersen 600 Carling Avenue, Suite 530 Ottawa, ON K1Z 1G3 613-230-1186 smithandandersen.com

CIMA+ 600-1400 Blair Towers Place Ottawa, ON K1J 9B8 T 613-860-2462 cima.ca

GEOTECHNICAL PATERSON GROUP 154 Colonnade Rd S, Nepean, On. K2E 7J5 T 613 226 7381 patersongroup.ca

STRUCTURAL D+M Structural Engineers 333 Preston Street, Suite 110 Ottawa, ON K1S 5N4 T 613-651-9490 dm-structural.ca

ENVIRONMENTAL Pinchin Ltd. 1 Hines Road, Suite 200 Kanata, ON K2K 3C7 T 855-746-2446 pinchin.com

HERITAGE Bray Heritage 837 Princess Street, Suite 400 Kingston, ON K7L 1G8 613-542-3393 brayheritage.ca

GENERAL CONTRACTOR Doran Contractors Ltd. 3187 Albion Rd S Ottawa, ON K1T 1W9 613-526-2400 doran.ca

ENERGY MODELING EQ Building Perfomance Inc 20 Floral Parkway Concord, ON L4K 4R1 T 416-645-1186 eqbuilding.com

ARCHITECT NEUF architect(e)s 630, boul. René-Lévesque O. 32e étages, Montréal QC H3B 1S6 T 514 847 1117 neuf.ca SCEAU / Seal







613-820-5600 windmilldevelopments.com OUVRAGE Project

## **384 ARLINGTON** AVENUE

EMPLACEMENT Location Adresse / Address

NO PROJET No 12805

NO RÉVISION DATE (aa-mm-jj) 0 FOR SPO FOR SPC FORM

DESSINÉ PAR Drawn by D.VAGHELA DATE (aa.mm.ii)


2024-10-04

VÉRIFIÉ PAR Checked by É. POTVIN ÉCHELLE Scal

TITRE DU DESSIN Drawing Title NOTES AND SPECIFICATIONS

NO. DESSIN Dwg Number

**RÉVISION Revision** 



EXISTING	LEGEND	PROPOSED		
XX	FENCE OVERHEAD WIRES		NOTES GÉNÉRALES General Notes 1. Ces documents d'architecture sont la propriété e architect(e)s et ne pourront être utilisés, reprodu	
	LOT LINE LOT LINE FOR THE PROPERTY		préalable. / These architectural documents are t architect(e)s and cannot be used, copied or repr authorisation	he exclusive property of NEUF
	TOP OF SLOPE DITCH CENTER		<ol> <li>Les dimensions apparaissant aux documents de l'entrepreneur avant le début des travaux. / All d documents must be verify by the contractor befor</li> </ol>	mensions which appear on the
	BOTTOM OF SLOPE WOOD AREA CATCHBASIN	• • •	<ol> <li>Veuillez aviser l'architecte de toute dimension et documents et ceux des autres professionnels. / errors, omissions and discrepancies between h</li> </ol>	The architect must be notified of all
	MANHOLE/CATCHBASIN MANHOLE		others professionnals. 4. Les dimensions sur ces documents doivent être	
	FIRE HYDRANT VALVE	Ç © ©	dimensions on these documents must be read a	nd not measured.
× × S	VALVE CHAMBER PRIVATE UTILITIES (WATERMAIN)		FOTENN Planning and Urb 396, Cooper Street, Ottawa, ON K2P 2H7	an design
e N	SLUICEWAY	0	T 613 730 5709 www.fotenn.com	
	NATURAL GAS VALVE SIGN ELECTRICITY POLE		SPRUCE LAB 500 Bayview Ave, Suite 300 Toronto, ON M4W 3X8 sprucelab.ca	
O E O T O PK	ELECTICITY MANHOLE TELEPHONE MANHOLE SURVEY STATION		MECHANICAL / ELECTRICAL	
ن الر × رئ <sup>و</sup> ن	ELEVATION BOTTOM OF PLANTER CURB	+ 99,000 + BC99,000	Smith + Andersen 600 Carling Avenue, Suite 530 Ottawa, ON K1Z 1G3 T 613-230-1186 smithandandersen.com	
	STORM ROOF TYPE DRAINS (SEE MECHANICAL AND STRUCTURAL)	٥	civi∟ CIMA+	
	WORK LIMIT UNDERGROUND PARKING LIMIT		600-1400 Blair Towers Place Ottawa, ON K1J 9B8 T 613-860-2462 cima.ca	
	BUILDING ENTRANCE	$\triangleright$	GEOTECHNICAL	
	MAIN ENTRANCE		154 Colonnade Rd S, Nepean, On. K2E 7J5 T 613 226 7381 patersongroup.ca	
	SIAMESE CONNECTION	*-	STRUCTURAL D+M Structural Engineers	
	HARD LANDSCAPING AREA (SEE LANDSCAPE)		333 Preston Street, Suite 110 Ottawa, ON K1S 5N4 T 613-651-9490 dm-structural.ca	
	SOFT LANDSCAPING AREA		ENVIRONMENTAL Pinchin Ltd.	
	(SEE LANDSCAPE)	· · · · ·	1 Hines Road, Suite 200 Kanata, ON K2K 3C7 T 855-746-2446 pinchin.com	
	CONCRETE SIDEWALK		Bray Heritage 837 Princess Street, Suite 400 Kingston, ON K7L 1G8	
			T 613-542-3393 brayheritage.ca GENERAL CONTRACTOR	
	DEPRESSED CONCRETE SIDEWALK		Doran Contractors Ltd. 3187 Albion Rd S Ottawa, ON K1T 1W9 T 613-526-2400 doran.ca	
	ASPHALT ROADWAY REINSTATMENT AS PER CITY OF OTTAWA DETAIL R10.		ENERGY MODELING	
			EQ Building Perfomance II 20 Floral Parkway Concord, ON L4K 4R1 T 416-645-1186 eqbuilding.com	1C
			ARCHITECT NEUF architect(e)s	
			630, boul. René-Lévesque O. 32e étages, Montréal Q( T 514 847 1117 neuf.ca	C H3B 1S6
			SCEAU / Seal	
			ROFESSIONAL	
			Stie Ports	
			<b>3</b> J. M. E. POTVIN 100208490	
			2024/10/04 3000 05 05 0NTARIO	
			MACE OF ONT	
				\/_+
			CLIENT Client	
			wind	
			150 Elgin St, Suite 1000 Ottawa, ON K2P 1L4 61-3820-5600 windmilldevelopments.com	
			OUVRAGE Project 384 ARLINGTO	N
			AVENUE	
			EMPLACEMENT Location	NO PROJET N
	1:150		Adresse / Address	1280
	0 1.5	3 6 9m		
	Not fo	r construction	NO RÉVISION           0         FOR SPC           1         FOR SPC FORMAL	DATE (aa-mm-) 2024-06-0 2024-10-0
			1 FOR SPC FORMAL	2024-10-0
TH	IE GEODETIC COORDINATES OF EVERY IT IIS DOCUMENT ARE IN <b>NAD83 - ORIGINAL</b> ID HAVE NO LEGAL VALUE. THE SITE LAY	/ MTM - REFERENCE SYSTEM		
US	SING THE OFFICIAL BENCHMARKS OF AN A IRVEYOR IN THE NAD83 - ORIGINAL / MTN	ACCREDITED LAND		
	E UNDERGROUND FEATURES AND INFOR			
CO	E DRAWINGS WERE OBTAINED FROM TH DMPANIES AND/OR FROM THE CITY EACH	RESPECTIVELY.		
10	L INFORMATION UNDER THE LEGEND 'EX ILY. COMPLETE OR EXACT LOCATION AN IDERGROUND SERVICES ARE NOT GUAR	D ELEVATION OF	DESSINÉ PAR Drawn by	VÉRIFIÉ PAR Checked b
CE	RTAIN UNDERGROUND FEATURES ON PF		D.VAGHELA DATE (aa.mm.jj)	É. POTVIN ÉCHELLE Scal
A	YONE WHO PROCEEDS WITH EXCAVATIO		2024-10-04 TITRE DU DESSIN Drawing Title	1:150
E> RE	ACT LOCATION OF ALL UNDERGROUND F PLORATORY EXCAVATIONS, AND SHALL A SPONSIBILITY IF THERE IS ANY DAMAGE	ASSUME FULL	GRADING AND	ROAD
w	ORK.		REINSTATMEN	_
OF	E CONTRACTOR WILL HAVE THE RESPON BLIGATION TO VALIDATE, BY EXPLORATOR THE PUBLIC UTILITIES UNDERGROUND \$	RY EXCAVATION, THE SIZE		

ENGINEER OF ANY CONFLICT WITH THE PROJECTED WORK.


NDSCAPE ARCHITECT SPRUCE LAB 00 Bayview Ave, Suite 300 Toronto, ON M4W 3X8 prucelab.ca	
ECHANICAL / ELECTRICAL Smith + Andersen 00 Carling Avenue, Suite 530 Ottawa, ON K1Z 1G3 613-230-1186 smithandandersen.com	
VIL CIMA+ 00-1400 Blair Towers Place Ottawa, ON K1J 9B8 613-860-2462 cima.ca	
EOTECHNICAL PATERSON GROUP 54 Colonnade Rd S, Nepean, On. K2E 7J5 613 226 7381 patersongroup.ca	
TRUCTURAL <b>)+M Structural Engineers</b> 33 Preston Street, Suite 110 Ottawa, ON K1S 5N4 613-651-9490 dm-structural.ca	
NVIRONMENTAL Pinchin Ltd. Hines Road, Suite 200 Kanata, ON K2K 3C7 855-746-2446 pinchin.com	
ERITAGE <b>Bray Heritage</b> 37 Princess Street, Suite 400 Kingston, ON K7L 1G8 613-542-3393 brayheritage.ca	
ENERAL CONTRACTOR Doran Contractors Ltd. 187 Albion Rd S Ottawa, ON K1T 1W9 613-526-2400 doran.ca	
NERGY MODELING EQ Building Perfomance Inc 0 Floral Parkway Concord, ON L4K 4R1 416-645-1186 eqbuilding.com	
RCHITECT <b>IEUF architect(e)s</b> 30, boul. René-Lévesque O. 32e étages, Montréal QC H3B 1S6 514 847 1117 neuf.ca	
J. M. E. POTVIN 100208490 2024/10/04 BOMNCE OF ONTAGO	
	<b>/ +</b>
	nil
50 Elgin St, Suite 1000 Ottawa, ON K2P 1L4 13-820-5600 windmilldevelopments.com UVRAGE Project B84 ARLINGTON	
AVENUE MPLACEMENT Location Adresse / Address	NO PROJET №. 12805
O RÉVISION FOR SPC FOR SPC FORMAL	DATE (aa-mm-jj) 2024-06-06 2024-10-04
ESSINÉ PAR Drawn by	VÉRIFIÉ PAR Checked by
D.VAGHELA	É. POTVIN

RÉVISION Revision

ÉCHELLE Scale 1:150

NO. DESSIN Dwg Number


C003




EXISTING	LEGEND	PROPOSED
— — WM— — — SAN— — — STM— —	WATERMAIN SANITARY SEWER STORM SEWER	— — WM — — — — SAN — — — — STM — —
D G	DRAIN GAS LINE (APPROX. LOC.)	— — D — —
	UNDERGROUND TELEPHONE (APPROX. UNDERGROUND CABLE (APPROX. LOC.) FENCE	
E	UNDERGROUND ELECTRICITY (APPROX. OVERHEAD WIRES	LOC.)
	LOT LINE LOT LINE OF THE PROPERTY	
	TOP OF SLOPE DITCH CENTER	
	BOTTOM OF SLOPE WOOD AREA	
	CATCHBASIN MANHOLE/CATCHBASIN	
O     O     O	MANHOLE FIRE HYDRANT	O op
$\bigotimes_{\pm}$	VALVE REDUCER	©
——————————————————————————————————————	TEE VALVE CHAMBER	<u> </u>
	PRIVATE UTILITIES (WATERMAIN) NATURAL GAS VALVE SIGN	S
© (Å) E.●	STOP SIGN ELECTRICITY POLE	
T O E	TELEPHONE POLE ELECTICITY MANHOLE	
OT OPK	TELEPHONE MANHOLE SURVEY STATION	
	WORK LIMIT UNDERGROUND PARKING LIMIT	
	STORM ROOF TYPE DRAINS (SEE MECHANICAL AND STRUCTURAL)	
	BUILDING ENTRANCE	
	MAIN ENTRANCE SIAMESE CONNECTION	<b>N</b> «_
	CHECK VALVE	× ×
	HARD LANDSCAPING AREA (SEE LANDSCAPE)	
	SOFT LANDSCAPING AREA (SEE LANDSCAPE)	Ψ Ψ Ψ Ψ
	CONCRETE SIDEWALK	
		4
	DEPRESSED CONCRETE SIDEWALK	
	REINSTATMENT AS PER CITY OF OTTAWA DETAIL R10.	
	<ol> <li>SANITARY BACKWATER VALVE REQUIT LATERAL PER CITY DETAIL S14.1. (REFER TO MECHANICAL).</li> <li>ALL FLOOR DRAINS WITHIN THE UN GARAGE MUST DISCHARGE TO THE LATERAL VIA SUMP PUMP (REFER T 4. WATER METER TO BE LOCATED INSI (REFER TO MECHANICAL).</li> <li>THE CONTRACTOR MUST CONFIRM T (GEODETIC ELEVATION), DIAMETER A MATERIAL OF THE EXISTING WATERM PROPOSED CROSSINGS. HE MUST A NECESSARY, EXPLORATORY EXCAVAT DETERMINE THE EXACT LOCATION AN EXISTING DUCK BANKS. THIS INFOR IMMEDIATELY BE PROVIDED TO THE START UNDERTAKING ANY MUNICIPAL AND A 48 HOUR PERIOD MUST BE ENGINEER FOR DESIGN REVIEW.</li> <li>BUILDING FOUNDATION DRAIN, BUILD DRAINS, AND TRENCH DRAIN FOR U PARKING ENTRANCE FROM RAYMON PUMPED INTO UNDERGROUND CISTE BUILDING. BUILDING ROOF DRAIN TO UNDERGROUND CISTERN VIA GRAVIT MECHANICAL)</li> </ol>	DERGROUND PARKING SANITARY SERVICE O MECHANICAL). DE BUILDING THE EXACT INVERT ND CONSTRUCTION IAIN AT THE LSO CARRY OUT, IF IONS IN ORDER TO ND INVERTS OF MATION MUST ENGINEER PRIOR TO - SERVICES WORK ALLOCATED TO THE DING AIR WELL INDERGROUND ID STREET TO BE RN WEST OF O BE DIRECTED INTO
	1:150	6 9m
		Construction
	INOL TOP (	construction
NOT		
THE G	BEODETIC COORDINATES OF EVERY ITEM	
AND F USING	DOCUMENT ARE IN <b>NAD83 - ORIGINAL / M</b> HAVE NO LEGAL VALUE. THE SITE LAYOUT IS THE OFFICIAL BENCHMARKS OF AN ACC EYOR IN THE <b>NAD83 - ORIGINAL / MTM -</b> R	MUST BE COMPLETED REDITED LAND
-	NDERGROUND FEATURES AND INFORMA RAWINGS WERE OBTAINED FROM THE PL	
COMP	ANIES AND/OR FROM THE CITY EACH RES	SPECTIVELY.
ONLY	IFORMATION UNDER THE LEGEND 'EXISTI COMPLETE OR EXACT LOCATION AND EL RGROUND SERVICES ARE NOT GUARANT	EVATION OF
CERT	AIN UNDERGROUND FEATURES ON PRIVA	
	/N ON THE CURRENT DRAWING. NE WHO PROCEEDS WITH EXCAVATION V	VORK SHALL VERIFY THF
EXAC EXPLC	T LOCATION OF ALL UNDERGROUND FEAT DRATORY EXCAVATIONS, AND SHALL ASS DNSIBILITY IF THERE IS ANY DAMAGE THA	TURES, BY UME FULL
OBLIG OF TH	ONTRACTOR WILL HAVE THE RESPONSIB ATION TO VALIDATE, BY EXPLORATORY E E PUBLIC UTILITIES UNDERGROUND SER IEER OF ANY CONFLICT WITH THE PROJE	EXCAVATION, THE SIZE VICES AND TO WARN THE

DTES GÉNÉRALES General Notes Ces documents d'architecture sont la propriété exclusive d architect(e)s et ne pourront être utilisés, reproduits ou copi préalable. / These architectural documents are the exclusiv architect(e)s and cannot be used, copied or reproduced wir euthorisetties	és sans autorisation écrite ve property of NEUF
authorisation Les dimensions apparaissant aux documents devront être l'entrepreneur avant le début des travaux. / All dimensions documents must be verify by the contractor before to start i	which appear on the the work.
Veuillez aviser l'architecte de toute dimension erreur et/ou documents et ceux des autres professionnels. / The archite errors, omissions and discrepancies between these docum others professionnals.	ect must be notified of all lents and those of the
Les dimensions sur ces documents doivent être lues et nor dimensions on these documents must be read and not mea	asured.
OTENN Planning and Urban de 96. Cooper Street, Ottawa, ON K2P 2H7 613 730 5709 www.fotenn.com	esign
INDSCAPE ARCHITECT SPRUCE LAB 10 Bayview Ave, Suite 300 Toronto, ON M4W 3X8 prucelab.ca	
ECHANICAL / ELECTRICAL Smith + Andersen 10 Carling Avenue, Suite 530 Ottawa, ON K1Z 1G3 613-230-1186 smithandandersen.com	
VIL CIMA+ I0-1400 Blair Towers Place Ottawa, ON K1J 9B8 613-860-2462 cima.ca	
EOTECHNICAL PATERSON GROUP 54 Colonnade Rd S, Nepean, On. K2E 7J5 613 226 7381 patersongroup.ca	
RUCTURAL <b>)+M Structural Engineers</b> 33 Preston Street, Suite 110 Ottawa, ON K1S 5N4 613-651-9490 dm-structural.ca	
IVIRONMENTAL P <b>inchin Ltd.</b> Hines Road, Suite 200 Kanata, ON K2K 3C7 855-746-2446 pinchin.com	
RITAGE <b>Sray Heritage</b> 37 Princess Street, Suite 400 Kingston, ON K7L 1G8 613-542-3393 brayheritage.ca	
ENERAL CONTRACTOR Doran Contractors Ltd. 187 Albion Rd S Ottawa, ON K1T 1W9 613-526-2400 doran.ca	
IERGY MODELING <b>C Building Perfomance Inc</b> ) Floral Parkway Concord, ON L4K 4R1 416-645-1186 edbuilding.com	
RCHITECT <b>IEUF architect(e)s</b> 30, boul. René-Lévesque O. 32e étages, Montréal QC H3B 1S6 514 847 1117 neuf.ca	
CEAU / Seal	
So PROFESSIONAL SI	
<b>J. M. E. POTVIN</b> <b>100208490</b> 2024/10/04	
300 NOCE OF ONTRIO	
	/+
LIENT Client	
windr	nil
50 Elgin St, Suite 1000 Ottawa, ON K2P 1L4 13-820-5600 windmilldevelopments.com UVRAGE Project	
84 ARLINGTON	
MPLACEMENT Location	NO PROJET No 12805
O RÉVISION	DATE (aa-mm-jj 2024-06-0
FOR SPC FORMAL	2024-00-0 2024-10-0
n. <b>C.POGGIOLI</b> ATE (aa.mm.ij)	VÉRIFIÉ PAR Checked by É. POTVIN ÉCHELLE Scale
024-10-04 TRE DU DESSIN Drawing Title	1:150
SERVICING PLAN	
ÉVISION Revision	NO. DESSIN Dwg Numbe

C004





EXISTING	
ויויויויויויויויויו	-
	-
E.T. E.T. E.T. C.E. C.E. C.E. C.E. C.E.	

LEGEND WATERMAIN SANITARY SEWER STORM SEWER DRAIN GAS LINE (APPROX. LOC.) UNDERGROUND TELEPHONE (APPROX. LOC.) UNDERGROUND CABLE (APPROX. LOC.) FENCE UNDERGROUND ELECTRICITY (APPROX. LOC.) OVERHEAD WIRES LOT LINE LOT LINE FOR THE PROPERTY TOP OF SLOPE DITCH CENTER BOTTOM OF SLOPE WOOD AREA GRADE CROSSING FLAGPOLE CATCHBASIN MANHOLE/CATCHBASIN MANHOLE FIRE HYDRANT VALVE REDUCER TEE VALVE CHAMBER PRIVATE UTILITIES (WATERMAIN) EXTERIOR WATER FAUCET SLUICEWAY NATURAL GAS VALVE SIGN STOP SIGN TRAFFIC LIGHT ELECTRICITY POLE TELEPHONE POLE ELECT.-TEL.-STREET LIGHT POLE ELECT.-TEL.-TRANSFORMER POLE PRIVATE STREET LIGHT ELECTICITY MANHOLE TELEPHONE MANHOLE SURVEY STATION ELEVATION WORK LIMIT

PROPOSED

NOTES GÉNÉRALES General Notes

- 1. Ces documents d'architecture sont la propriété exclusive de NEUF architect(e)s et ne pourront être utilisés, reproduits ou copiés sans autorisation écrite préalable. / These architectural documents are the exclusive property of NEUF architect(e)s and cannot be used, copied or reproduced without written pre-
- authorisation 2. Les dimensions apparaissant aux documents devront être vérifiées par l'entrepreneur avant le début des travaux. / All dimensions which appear on the documents must be verify by the contractor before to start the work.
- 3. Veuillez aviser l'architecte de toute dimension erreur et/ou divergences entre ces documents et ceux des autres professionnels. / The architect must be notified of all errors, omissions and discrepancies between these documents and those of the others professionnals.

4. Les dimensions sur ces documents doivent être lues et non mesurées. / The dimensions on these documents must be read and not measured.

PLANNER FOTENN Planning and Urban design 396, Cooper Street, Ottawa, ON K2P 2H7 T 613 730 5709 www.fotenn.com

LANDSCAPE ARCHITECT SPRUCE LAB 500 Bayview Ave, Suite 300 Toronto, ON M4W 3X8

sprucelab.ca

. MECHANICAL / ELECTRICAL Smith + Andersen 600 Carling Avenue, Suite 530 Ottawa, ON K1Z 1G3 T 613-230-1186 smithandandersen.com

CIVIL CIMA+ 600-1400 Blair Towers Place Ottawa, ON K1J 9B8 T 613-860-2462 cima.ca

GEOTECHNICAL PATERSON GROUP 154 Colonnade Rd S, Nepean, On. K2E 7J5 T 613 226 7381 patersongroup.ca

STRUCTURAL **D+M Structural Engineers** 333 Preston Street, Suite 110 Ottawa, ON K1S 5N4 T 613-651-9490 dm-structural.ca

ENVIRONMENTAL Pinchin Ltd. 1 Hines Road, Suite 200 Kanata, ON K2K 3C7 T 855-746-2446 pinchin.com

HERITAGE Bray Heritage 837 Princess Street, Suite 400 Kingston, ON K7L 1G8 T 613-542-3393 brayheritage.ca

GENERAL CONTRACTOR Doran Contractors Ltd. 3187 Albion Rd S Ottawa, ON K1T 1W9

T 613-526-2400 doran.ca ENERGY MODELING EQ Building Perfomance Inc 20 Floral Parkway Concord, ON L4K 4R1 T 416-645-1186 eqbuilding.com

SCEAU / Seal

ARCHITECT NEUF architect(e)s 630, boul. René-Lévesque O. 32e étages, Montréal QC H3B 1S6 T 514 847 1117 neuf.ca







613-820-5600 windmilldevelopments.com OUVRAGE Project

# **384 ARLINGTON** AVENUE

EMPLACEMENT Location Adresse / Address

9m

NO PROJET No 12805

NO RÉVISION DATE (aa-mm-jj) 0 FOR SPC FOR SPC FORM DESSINÉ PAR Drawn by VÉRIFIÉ PAR Checked b S.C.POGGIOLI É. POTVIN DATE (aa.mm.jj) ÉCHELLE Scale 2024-10-04 1:150 TITRE DU DESSIN Drawing Title **STORM WATER** MANAGEMENT PLAN (PRE-DEVELOPMENT) RÉVISION Revision NO. DESSIN Dwg Numl C00

Not for construction

## NOTE OF CAUTION

THE GEODETIC COORDINATES OF EVERY ITEM INCLUDED AS PART OF THIS DOCUMENT ARE IN NAD83 - ORIGINAL / MTM - REFERENCE SYSTEM AND HAVE NO LEGAL VALUE. THE SITE LAYOUT MUST BE COMPLETED USING THE OFFICIAL BENCHMARKS OF AN ACCREDITED LAND SURVEYOR IN THE NAD83 - ORIGINAL / MTM - REFERENCE SYSTEM.


THE UNDERGROUND FEATURES AND INFORMATION THAT APPEAR ON THE DRAWINGS WERE OBTAINED FROM THE PUBLIC UTILITY COMPANIES AND/OR FROM THE CITY EACH RESPECTIVELY. ALL INFORMATION UNDER THE LEGEND 'EXISTING' IS FOR INFORMATION

ONLY. COMPLETE OR EXACT LOCATION AND ELEVATION OF UNDERGROUND SERVICES ARE NOT GUARANTEED.

CERTAIN UNDERGROUND FEATURES ON PRIVATE PROPERTY ARE NOT SHOWN ON THE CURRENT DRAWING.

ANYONE WHO PROCEEDS WITH EXCAVATION WORK SHALL VERIFY THE EXACT LOCATION OF ALL UNDERGROUND FEATURES, BY EXPLORATORY EXCAVATIONS, AND SHALL ASSUME FULL RESPONSIBILITY IF THERE IS ANY DAMAGE THAT OCCURS DURING WORK.

THE CONTRACTOR WILL HAVE THE RESPONSIBILITY AND THE OBLIGATION TO VALIDATE, BY EXPLORATORY EXCAVATION, THE SIZE OF THE PUBLIC UTILITIES UNDERGROUND SERVICES AND TO WARN THE ENGINEER OF ANY CONFLICT WITH THE PROJECTED WORK.



EXISTING	
ויויויויויויויויויו	-
	-
E.T. E.T. E.T. C.E. C.E. C.E. C.E. C.E.	

LEGEND WATERMAIN SANITARY SEWER STORM SEWER DRAIN GAS LINE (APPROX. LOC.) UNDERGROUND TELEPHONE (APPROX. LOC.) UNDERGROUND CABLE (APPROX. LOC.) FENCE UNDERGROUND ELECTRICITY (APPROX. LOC.) OVERHEAD WIRES LOT LINE LOT LINE FOR THE PROPERTY TOP OF SLOPE DITCH CENTER BOTTOM OF SLOPE WOOD AREA GRADE CROSSING FLAGPOLE CATCHBASIN MANHOLE/CATCHBASIN MANHOLE FIRE HYDRANT VALVE REDUCER TEE VALVE CHAMBER PRIVATE UTILITIES (WATERMAIN) EXTERIOR WATER FAUCET SLUICEWAY NATURAL GAS VALVE SIGN STOP SIGN TRAFFIC LIGHT ELECTRICITY POLE TELEPHONE POLE ELECT.-TEL.-STREET LIGHT POLE ELECT.-TEL.-TRANSFORMER POLE PRIVATE STREET LIGHT ELECTICITY MANHOLE TELEPHONE MANHOLE SURVEY STATION ELEVATION WORK LIMIT

PROPOSED

NOTES GÉNÉRALES General Notes

- Ces documents d'architecture sont la propriété exclusive de NEUF architect(e)s et ne pourront être utilisés, reproduits ou copiés sans autorisation écrite préalable. / These architectural documents are the exclusive property of NEUF architect(e)s and cannot be used, copied or reproduced without written pre-
- Les dimensions apparaissant aux documents devront être vérifiées par l'entrepreneur avant le début des travaux. / All dimensions which appear on the documents must be verify by the contractor before to start the work.
- Veuillez aviser l'architecte de toute dimension erreur et/ou divergences entre ces documents et ceux des autres professionnels. / The architect must be notified of all errors, omissions and discrepancies between these documents and those of the others professionnals.

 Les dimensions sur ces documents doivent être lues et non mesurées. / The dimensions on these documents must be read and not measured.

PLANNER FOTENN Planning and Urban design 396, Cooper Street, Ottawa, ON K2P 2H7 T 613 730 5709 www.fotenn.com

LANDSCAPE ARCHITECT SPRUCE LAB 500 Bayview Ave, Suite 300 Toronto, ON M4W 3X8

sprucelab.ca

MECHANICAL / ELECTRICAL
Smith + Andersen
600 Carling Avenue, Suite 530 Ottawa, ON K1Z 1G3
T 613-230-1186 smithandandersen.com

CIVIL CIMA+ 600-1400 Blair Towers Place Ottawa, ON K1J 9B8 T 613-860-2462 cima.ca

GEOTECHNICAL **PATERSON GROUP** 154 Colonnade Rd S, Nepean, On. K2E 7J5 T 613 226 7381 patersongroup.ca

STRUCTURAL **D+M Structural Engineers** 333 Preston Street, Suite 110 Ottawa, ON K1S 5N4 T 613-651-9490 dm-structural.ca

ENVIRONMENTAL **Pinchin Ltd.** 1 Hines Road, Suite 200 Kanata, ON K2K 3C7 T 855-746-2446 pinchin.com

HERITAGE **Bray Heritage** 837 Princess Street, Suite 400 Kingston, ON K7L 1G8 T 613-542-3393 brayheritage.ca

GENERAL CONTRACTOR
Doran Contractors Ltd.
3187 Albion Rd S Ottawa, ON K1T 1W9

T 613-526-2400 doran.ca ENERGY MODELING EQ Building Perfomance Inc

20 Floral Parkway Concord, ON L4K 4R1 T 416-645-1186 eqbuilding.com ARCHITECT **NEUF architect(e)s** 630, boul. René-Lévesque O. 32e étages, Montréal QC H3B 1S6

T 514 847 1117 neuf.ca SCEAU / Seal







150 Eigin St, Suite 1000 Ottawa, ON K2P 1L4 613-820-5600 windmilldevelopments.com

# 384 ARLINGTON AVENUE

EMPLACEMENT Location
Adresse / Address

NO PROJET No 12805

NO RÉVISION DATE (aa-mm-jj) 0 FOR SPC FOR SPC FORM DESSINÉ PAR Drawn by VÉRIFIÉ PAR Checked by S.C.POGGIOLI É. POTVIN ÉCHELLE Scale DATE (aa.mm.jj) 2024-10-04 1:150 TITRE DU DESSIN Drawing Title **STORM WATER** MANAGEMENT PLAN (POST-DEVELOPMENT) RÉVISION Revisio NO. DESSIN Dwg Numbe **C006** 

Not for construction

6

1.5 3

## NOTE OF CAUTION

THE GEODETIC COORDINATES OF EVERY ITEM INCLUDED AS PART OF THIS DOCUMENT ARE IN **NAD83 - ORIGINAL / MTM -** REFERENCE SYSTEM AND HAVE NO LEGAL VALUE. THE SITE LAYOUT MUST BE COMPLETED USING THE OFFICIAL BENCHMARKS OF AN ACCREDITED LAND SURVEYOR IN THE **NAD83 - ORIGINAL / MTM -** REFERENCE SYSTEM.

THE UNDERGROUND FEATURES AND INFORMATION THAT APPEAR ON THE DRAWINGS WERE OBTAINED FROM THE PUBLIC UTILITY COMPANIES AND/OR FROM THE CITY EACH RESPECTIVELY. ALL INFORMATION UNDER THE LEGEND 'EXISTING' IS FOR INFORMATION

ONLY. COMPLETE OR EXACT LOCATION AND ELEVATION OF UNDERGROUND SERVICES ARE NOT GUARANTEED.

CERTAIN UNDERGROUND FEATURES ON PRIVATE PROPERTY ARE NOT SHOWN ON THE CURRENT DRAWING.

ANYONE WHO PROCEEDS WITH EXCAVATION WORK SHALL VERIFY THE EXACT LOCATION OF ALL UNDERGROUND FEATURES, BY EXPLORATORY EXCAVATIONS, AND SHALL ASSUME FULL RESPONSIBILITY IF THERE IS ANY DAMAGE THAT OCCURS DURING WORK.

THE CONTRACTOR WILL HAVE THE RESPONSIBILITY AND THE OBLIGATION TO VALIDATE, BY EXPLORATORY EXCAVATION, THE SIZE OF THE PUBLIC UTILITIES UNDERGROUND SERVICES AND TO WARN THE ENGINEER OF ANY CONFLICT WITH THE PROJECTED WORK.