

re: **Groundwater Monitoring Program**
Proposed Commercial Development
5923 Ottawa Street, Richmond, Ontario

to: Stratford Foxrun – **Jack Gulas** – jack@stratfordfoxrun.com
date: August 5, 2025
file: PH4924-MEMO.01

Further to your request and authorization, Paterson Group (Paterson) conducted a groundwater monitoring program in support of a Low Impact Development (LID) design for the proposed commercial development at the aforementioned site. This report should be read in conjunction with Paterson Report PG7183-1 Revision 1 dated November 20, 2024, and PG7183-2 Revision 1 dated July 9, 2025.

1.0 Background Information

Geotechnical field investigations were carried out between June 17, 2024, and April 17, 2025, where a total of eight (8) boreholes were advanced, respectively. The boreholes were advanced to a maximum depth of 6.71 m below existing grade (bgs). The test holes were distributed in a manner to provide general coverage of the study area, taking into consideration existing site features.

Field Survey

The borehole locations, and ground surface elevations at each borehole location, were surveyed by Paterson using a high precision, handheld GPS and referenced to a geodetic datum. The location and ground surface elevation at each borehole location is presented on Drawing PG7183-2 - Test Hole Location Plan attached to the current memorandum.

Subsurface Profile

The subsurface profile at the borehole locations generally consisted of topsoil underlain by silty clay and/or glacial till deposits. The glacial till layer typically consisted of compact to very dense, brown silty sand with varying amounts of gravel, cobbles, boulders and clay. Practical refusal to augering was encountered between 3.4 and 3.6 m bgs in BH 2-25 and BH 1-24, respectively, while practical DCPT refusal was encountered at a depth of approximately 8.1 m bgs at BH 3-25.

Details of the subsurface profile can be found in the Soil Profile and Test Data Sheets attached to the current report.



Monitoring Well Installation

Typical monitoring well construction details are described below:

- 1.5 m of slotted 51 mm diameter PVC screen at the base of the aforementioned boreholes.
- 51 mm diameter PVC riser pipe from the top of the screen to above ground surface.
- No.3 silica sand backfill within the annular space around the screen.
- Bentonite hole plug placed directly above PVC slotted screen extending to the existing ground surface.
- The 51 mm diameter PVC riser extended above the ground surface was covered with a protective steel monitoring well casing.

Specific details of the installation of each monitoring well are further included in the Soil Profile and Test Data Sheets attached to the current report.

2.0 Groundwater Monitoring Program

The monitoring wells installed at BH 2-24, BH 3-24, and BH 5-24 were equipped with a Van Essen Instrument Mini-Diver Water Level Logger on April 4, 2025, October 22, 2024, and October 22, 2024, respectively, to accurately monitor fluctuations in the groundwater levels. In addition, a Van Essen Instruments Baro-Diver was installed in BH 3-24 to monitor changes in atmospheric pressure. The Mini-Divers were programmed to continuously measure and record groundwater levels throughout the subject site at a rate of 1 reading every 24 hours for BH 2-24 for a period of approximately 4 months, and every 12 hours for a period of 9 months for BH 3-24 and BH 5-24.

The results of the groundwater fluctuations and correlated precipitation events at the monitoring well location between October 2024 and July 2025, have been summarized in Figure 1 through Figure 3 attached to the current report.

3.0 Groundwater Monitoring Results

The data presented in Figure 1 through Figure 3 illustrates the collected groundwater elevations between October 2024 and July 2025. The groundwater readings measured within the monitoring wells varied from an elevation of 91.83 m asl to a maximum elevation of 93.79 m asl for BH 2-24; 91.21 to 93.86 m asl for BH 3-24; and 91.13 to 93.82 m asl for BH 5-24. The low and high groundwater elevation are summarized in Table 1 below.



Based on our analysis of the data logger groundwater readings, seasonal groundwater fluctuations can be observed at the well location with a difference in elevation between low and high readings of 1.96, 2.64, and 2.69 m for BH 2-24, BH 3-24, and BH 5-24, respectively. Note that the highest groundwater elevations were noted to be greater than the ground surface elevation for BH 2-24 and BH 3-24.

Table 1: Groundwater Monitoring Summary

Monitoring Well ID	Ground Surface Elevation (m asl)	Low Groundwater Elevation (m asl)	High Groundwater Elevation (m asl)	Difference in Groundwater Elevation (m asl)
BH 2-24	93.69	91.83	93.79	1.96
BH 3-24	93.85	91.21	93.86	2.64
BH 5-24	93.92	91.13	93.82	2.69

We trust that this information satisfies your requirements.

Best Regards,

Paterson Group Inc.

Nicholas Zulinski, P.Geo., géo.




Alexander Schopf, PhD, EIT.


Attachments

- Figure 1 through Figure 3 – Groundwater Monitoring Levels
- Soil Profile and Test Data Sheets
- Drawing PG7183-2 – Test Hole Location Plan




BH2-24 - Monitoring Well Water Elevations





BH5-24 - Monitoring Well Water Elevations



EASTING: 358362.138 NORTHING:

EASTING: 358362.138 NORTHING: 5005913.959 ELEVATION: 94.20

DATUM: Geodetic


REMARKS:

BORINGS BY: CME 55 Power Auger

DATE: June 17, 2024

FILE NO. PG7183

HOLE NO. **BH 1-24**



EASTING: 358409.319 **NORTHING:**

EASTING: 358409.319 NORTHING: 5005999.639 ELEVATION: 93.69

DATUM: Geodetic


REMARKS:

BORINGS BY: CME 55 Power Auger

DATE: June 17, 2024

FILE NO. PG7183

HOLE NO. **BH 2-24**



EASTING: 358326.994 NORTHING: 5005950.976 ELEVATION: 93.85

FILE NO. **PG7183**

DATUM: Geodetic


REMARKS:

BORINGS BY: CME 55 Power Auger

DATE: June 17, 2024

HOLE NO.

BH 3-24



EASTING: 358331.858 NORTHING: 5005978.835 ELEVATION: 94.11

FILE NO. **PG7183**

DATUM: Geodetic


REMARKS:

BORINGS BY: CME 55 Power Auger

DATE: June 17, 2024

HOLE NO.

BH 4-24



EASTING: 358383.011 NORTHING: 5005949.836 ELEVATION: 93.92

DATUM: Geodetic


REMARKS:

BORINGS BY: CME 55 Power Auger

FILE NO. **PG7183**

HOLE NO. **BH 5-24**

DATE: June 17, 2024





COORD. SYS.: MTM ZONE 9

EASTING: 358355.92

NORTHING: 5006024.43

ELEVATION: 94.07

PROJECT: Proposed Commercial Development


FILE NO.: PG7183

ADVANCED BY: Track Mounted Drill Rig

REMARKS:

DATE: April 17, 2025

HOLE NO.: BH 1-25





COORD. SYS.: MTM ZONE 9

EASTING: 358380.22

NORTHING: 5006016.15

ELEVATION: 94.07

PROJECT: Proposed Commercial Development


FILE NO.: PG7183

ADVANCED BY: Track Mounted Drill Rig

REMARKS:

DATE: April 17, 2025

HOLE NO.: BH 2-25



DISCLAIMER: THE DATA PRESENTED IN THIS SHEET IS THE PROPERTY OF PATERSON GROUP AND THE CLIENT FOR WHOM IT WAS PRODUCED. THIS SHEET SHOULD BE READ IN CONJUNCTION WITH ITS CORRESPONDING REPORT. PATERSON GROUP IS NOT RESPONSIBLE FOR THE UNAUTHORIZED USE OF THIS DATA.



COORD. SYS.: MTM ZONE 9

EASTING: 358388.50

NORTHING: 5005993.41

ELEVATION: 94.07

PROJECT: Proposed Commercial Development

FILE NO.: PG7183

ADVANCED BY: Track Mounted Drill Rig

REMARKS:

DATE: April 17, 2025

HOLE NO.: BH 3-25

