

1. ANY DISTURBED AREA DURING CONSTRUCTION TO BE RESTORED TO ORIGINAL CONDITION OR BETTER TO THE SATISFACTION OF THE AUTHORITIES HAVING JURISDICTION
2. EXISTING MATERIALS TO BE REMOVED TO UNCOVER THE PRECISE LOCATIONS AND INVERT ELEVATIONS OF EX. UNDERGROUND SERVICES AND EX. UTILITIES PRIOR TO STARTING CONSTRUCTION
3. ALL EXISTING TREES, SHRUBS ETC. WITHIN LOTS, BLOCKS AND ALLEYS TO BE REMOVED, UNLESS OTHERWISE NOTED
4. PERMISSION REQUIRED FOR WORK ON ADJACENT LANDS
5. FILL MATERIALS TO BE PROVIDED, 2.4m MIN. COVER TO BE STUBS
6. ANY DISTURBED MATERIAL EXPOSED BELOW THE SUBGRADE LEVEL WITHIN A BUILDING FOOTPRINT TO BE SUB-EXCAVATED AND BACKFILLED WITH COMPACTED FILL MATERIALS TO THE PERMITS OF SUB GEOTECHNICAL ENGINEERS
7. RECOMMENDATION
8. FOR PRELIMINARY DATA, REFER TO DWG. No. 2 FOR DETAILS
9. ALL DWELLINGS TO BE PROVIDED WITH PROTECTIVE REDUCING VALVES UNLESS OTHERWISE NOTED.
10. WATERMAIN INSULATION TO BE PROVIDED PER DWG. STW-2
11. WATERMANS OVER SEWERS TO BE PER CITY STD. W2.5
12. WATERMANS UNDER SEWERS TO BE PER CITY STD. W2.2

