

REPORT NO. 161-06382-00

PHASE TWO ENVIRONMENTAL SITE ASSESSMENT

PART OF LOT 4, CONCESSION 3,
PARTS 1, 2, 3, 4 AND 5,
GLOUCESTER, ONTARIO
(3646, 3636 AND 3604 INNES ROAD,
Ottawa, Ontario)

JULY 27, 2016

PHASE TWO ENVIRONMENTAL SITE ASSESSMENT

PART OF LOT 4, CONCESSION 3,

PARTS 1, 2, 3, 4 AND 5,

GLOUCESTER, ONTARIO

(3646, 3636 AND 3604 INNES ROAD,
OTTAWA, ONTARIO)

The Builders Warehouse Inc.

Project no: 161-06382-00

Date: July 27 2016

WSP Canada Inc.

2611 Queensview Drive, Suite 300
Ottawa, Ontario K2B 8K2 Canada

Phone: +1-613-829-2800

Fax: +1-613-829-8299

www.wspgroup.com





July 27, 2016

The Builder's Warehouse
Attn: Martin Juneau, Vice Président Finances
1501 rue Ampère, bureau 200
Boucherville, Qc, J4B 5Z5

**Subject: Phase Two Environmental Site Assessment
Lot 4, Concession 4, Parts 1, 2, 3, 4, 5 Gloucester, Ontario
(3646, 3636, 3604 Innes Road, Ottawa, Ontario)
161-06382-00**

Dear Mr. Juneau,

We are pleased to forward our report documenting the results of the Phase Two Environmental Site Assessment (ESA) completed at the above-noted property.

The Phase Two ESA was completed in general accordance with *Ontario Regulation (O. Reg.) 153/04* to investigate areas of potential environmental concern (APECs) identified in the Phase One ESA and to document the environmental quality of soil and groundwater at the Site.

Based on the findings of the investigation, elevated concentrations of contaminants of concern were identified in soil and groundwater at the Site. The management of impacted soil and groundwater will be required, either through remediation or risk assessment, before filing a Record of Site Condition.

If you have any questions or require further information, please contact the undersigned.

Yours truly,

WSP Canada Inc.

A handwritten signature in dark ink, appearing to read "Kmaton", written over a light blue horizontal line.

Kathryn Maton, C.E.T.
Environmental Technologist

A handwritten signature in dark ink, appearing to read "Carolyn Adams", written over a light blue horizontal line.

Carolyn Adams, M.A.Sc., P.Eng., QP_{ESA/RA}
Manager, Environmental Management

WSP Canada Inc.
2611 Queensview Drive, Suite 300
Ottawa, Ontario K2B 8K2

Phone: +1 613-829-2800
Fax: +1 613-829-8299
www.wspgroup.com

EXECUTIVE SUMMARY

WSP Canada Inc. (WSP) was retained by The Builders Warehouse Inc. to conduct a Phase Two Environmental Site Assessment (ESA) of the seven (7) parcels of land located at Part of Lot 4, Concession 4, Parts 1, 2, 3, 4, 5 Gloucester, Ontario (with municipal addresses of 3646, 3636, 3604 Innes Road, Ottawa, Ontario, and Part of Lot 4, Concession 3, Part 2, Plan 5R8348, Gloucester, Ontario) (the "Site"). The Site is a rectangular shaped vacant property with a square portion located on the northeast corner along Innes Road.

There are eight (8) structures present on the north side of the Site, which are currently vacant commercial buildings (a former BMR hardware store). Five of the eight structures are on the east side of 3636 Innes Road and include a main retail building closest to Innes Road with four storage sheds (one of which is three-sided) located south of the main building. The remaining structures are located on the west side of the north portion of the Site, and include two shelters not completely closed in used for material storage and seasonal cashiers and one closed building used to house a circular saw. The remaining south portion of the Site is vacant forested land.

The Phase Two ESA was completed to characterize subsurface conditions according to current industry standards, in general accordance with *Ontario Regulation (O. Reg.) 153/04*. We understand that the Site may be sold and the south, vacant portion of the Site may be developed for residential uses; the north portion of the Site would remain commercial use. Full compliance with *O. Reg. 153/04* would require the filing of a Record of Site Condition (RSC) if the north portion of the Site is used for residential purposes. This Phase Two ESA may be used to support the filing of an RSC, if required by municipal planning approvals or the land conveyance of undevelopable land.

Through an evaluation of the information gathered from a records review, interviews, and a site reconnaissance, WSP identified two Areas of Potential Environmental Concern (APECs) at the Site resulting from two on site PCAs, and one APEC that was attributed to one off-site PCA with the potential for contaminant migration through groundwater movement. The potential environmental concerns are related to a confirmed exceedance of petroleum hydrocarbon compound (PHC) F3 and F4 fractions (GENIVAR, September 2013), historical snow storage (GENIVAR, June 2013) and interview (WSP, 2016) and aerial photographs showing disturbed areas on the north side of the properties located at 3637, 3682 and 3698 Innes Road (70 metres east of the Site), with large commercial vehicle storage/maintenance present.

The Phase Two ESA consisted of the completion of 13 boreholes to a maximum depth of 7.01 m below ground surface (mbgs), installation of three groundwater monitoring wells, and the collection of soil and groundwater samples for chemical analysis. As the Phase One ESA identified multiple well records that may be located on the Site and within the Phase One Study Area (WSP, 2016), the applicable generic soil and groundwater standards selected for evaluating subsurface conditions are the Ontario Ministry of the Environment and Climate Change (MOECC) Table 2: Full Depth Generic Site Condition Standards (SCS) in a Potable Ground Water Condition for residential/institutional/parkland property uses.

Based on the results of the Phase Two ESA, elevated concentrations of metals and inorganics (MI), and/or PHCs (including BTEX) in soil exceeding the Table 2 SCS were identified within the fill and native soils, extending to at least 6.10 mbgs across the site. In summary:

- Review of the chemical analysis of metals and inorganics of the soil submitted within the fill and native materials across the Site identified exceedances of barium, cobalt, and vanadium. Due to the presence of these chemicals in the native silty clay or clayey silt (in both 2013 and 2016 drilling programs), they

may be representative of background in this area and not necessarily indicative of any off-Site or on-Site sources of contamination.

- The elevated concentrations of electrical conductivity (EC) and sodium adsorption ratio (SAR) identified in BH16-6 and BH16-8 may be attributed to the historic application of road salt on the Site. The salt impacts were identified in the shallow native soils.
- In 2013, elevated concentrations of PHC- F3 and F4 were identified within the fill material at TE-02 (located on the southeast corner of the 'overstock storage yard', from ground surface to 0.35 mbgs. The fill material was described as 55% brick, wood, burnt wood, plastic and 45% sandy silt with trace organic material. In 2016, BH16-4, BH/MW16-5 and BH16-6 were advanced around TE-02 to delineate the PHC F3 and F4 contamination. All samples collected from these boreholes met the applicable Table 2 SCS, indicating that impacts are limited to surface soil at TE-02.
- Elevated concentrations of ethylbenzene and PHC F2 were present in the groundwater of MW16-5 (located in the southeast corner of the 'overstock storage yard') when compared to the Table 2 SCS.

Based on the findings of the investigation, elevated concentrations of contaminants of concern were identified in soil and groundwater at the Site. Based on delineation efforts of the PHC F3 impacted soil located at FE-02, it has been determined that approximately 105 m² of impacted soil is in this location. Removal of the impacted soil may address groundwater impacts and it is recommended that groundwater be resampled after soil remediation.

The elevated metal concentrations in soil can be managed through a risk assessment process to identify risk management measures that will allow for this soil to remain onsite. This contaminant management (e.g., remediation and risk assessment) will be required prior to filing a Record of Site Condition.

TABLE OF CONTENTS

1	INTRODUCTION.....	1
1.1	BACKGROUND.....	1
1.2	SITE DESCRIPTION AND PROPERTY OWNERSHIP	1
1.3	CURRENT AND PROPOSED FUTURE USES	2
1.4	APPLICABLE SITE CONDITION STANDARD	2
2	BACKGROUND INFORMATION.....	4
2.1	PHYSICAL SETTING	4
2.2	PAST INVESTIGATIONS.....	4
2.2.1	PHASE I ESA - 2013	4
2.2.2	PHASE II ESA - 2013	5
2.2.3	PHASE ONE ESA - 2016	6
2.3	POTENTIAL CONTAMINANTS OF CONCERN.....	7
3	SCOPE OF THE INVESTIGATION.....	8
3.1	OVERVIEW OF THE SITE INVESTIGATION	8
3.2	MEDIA INVESTIGATED.....	8
3.3	PHASE ONE CONCEPTUAL SITE MODEL	9
3.4	DEVIATIONS FROM SAMPLING AND ANALYSIS PLAN	9
3.5	IMPEDIMENTS	9
4	INVESTIGATION METHOD	10
4.1	GENERAL	10
4.2	DRILLING	10
4.3	SOIL.....	10
4.3.1	SOIL SAMPLING	10
4.4	FIELD SCREENING MEASUREMENTS	11

4.5	GROUND WATER: MONITORING WELL INSTALLATION	11
4.6	GROUNDWATER: FIELD MEASUREMENT OF WATER QUALITY PARAMETERS.....	12
4.7	GROUNDWATER SAMPLING.....	12
4.8	SEDIMENT SAMPLING	12
4.9	ANALYTICAL TESTING	12
4.10	RESIDUE MANAGEMENT PROCEDURES.....	13
4.11	ELEVATION SURVEYING	13
4.12	QUALITY ASSURANCE AND QUALITY CONTROL MEASURES.....	13
5	REVIEW AND EVALUATION.....	15
5.1	GEOLOGY.....	15
5.2	GROUNDWATER: ELEVATIONS AND FLOW DIRECTION.....	15
5.3	SOIL: FIELD SCREENING	15
5.4	SOIL QUALITY.....	16
5.4.1	METALS AND INORGANICS	16
5.4.2	PETROLEUM HYDROCARBONS (INCLUDING BTEX).....	17
5.4.3	POLYCYCLIC AROMATIC HYDROCARBONS	17
5.5	GROUNDWATER QUALITY.....	17
5.6	QUALITY ASSURANCE AND QUALITY CONTROL RESULTS.....	18
5.7	PHASE TWO CONCEPTUAL SITE MODEL.....	19
5.7.1	POTENTIALLY CONTAMINATING ACTIVITIES AND AREAS OF POTENTIAL ENVIRONMENTAL CONCERN.....	19
5.7.2	SUBSURFACE UTILITIES	19
5.7.3	PHYSICAL SETTING	19
5.7.4	BUILDINGS AND STRUCTURES	20
5.7.5	ENVIRONMENTALLY SENSITIVE AREAS	20
5.7.6	IMPORTED SOIL.....	20
5.7.7	SOIL AND GROUNDWATER QUALITY	20
6	CONCLUSIONS.....	22
6.1	SUMMARY OF PHASE TWO FINDINGS	22

7	QUALIFICATIONS OF THE ASSESSORS	23
7.1	SIGNATURES	23
8	REFERENCES.....	8-24

TABLES

TABLE 1A	METALS AND INORGANICS SOIL ANALYTICAL RESULTS (2013)
TABLE 1B	METALS AND INORGANICS SOIL ANALYTICAL RESULTS (2013)
TABLE 1C	METALS AND INORGANICS SOIL ANALYTICAL RESULTS (2016)
TABLE 1D	METALS AND INORGANICS SOIL ANALYTICAL RESULTS (2016)
TABLE 1E	METALS AND INORGANICS SOIL ANALYTICAL RESULTS (2016)
TABLE 1F	METALS AND INORGANICS SOIL ANALYTICAL RESULTS (2016)
TABLE 2A	PHC (INCLUDING BTEX) SOIL ANALYTICAL RESULTS (2013)
TABLE 2B	PHC (INCLUDING BTEX) SOIL ANALYTICAL RESULTS (2013)
TABLE 2C	PHC (INCLUDING BTEX) SOIL ANALYTICAL RESULTS (2016)
TABLE 3A	PAH SOIL ANALYTICAL RESULTS (2013)
TABLE 3B	PAH SOIL ANALYTICAL RESULTS (2013)
TABLE 3C	PAH SOIL ANALYTICAL RESULTS (2016)
TABLE 4	METALS AND INORGANICS GROUNDWATER ANALYTICAL RESULTS (2016)
TABLE 5	PAH GROUNDWATER ANALYTICAL RESULTS (2016)
TABLE 6	PHC (INCLUDING BTEX) GROUNDWATER ANALYTICAL RESULTS
TABLE 7	SUMMARY OF GROUNDWATER ELEVATIONS
TABLE 8	SUMMARY OF RELATIVE PERCENT DIFFERENCES (RPDS) IN SOIL
TABLE 9	SUMMARY OF RELATIVE PERCENT DIFFERENCES (RPDS) IN GROUNDWATER

FIGURES

FIGURE 1	SITE LOCATION PLAN
FIGURE 2	SITE PLAN AND STUDY AREA
FIGURE 3	CONTAMINANT DISTRIBUTION OF METALS AND INORGANICS IN SOIL
FIGURE 4	CONTAMINANT DISTRIBUTION OF PHCS IN SOIL
FIGURE 5	CONTAMINANT DISTRIBUTION OF PHCS IN GROUNDWATER

APPENDICES

APPENDIX A	SAMPLE AND ANALYSIS PLANS
APPENDIX B	BOREHOLE LOGS
APPENDIX C	CERTIFICATES OF ANALYSIS

1 INTRODUCTION

1.1 BACKGROUND

WSP Canada Inc. (WSP) was retained by The Builders Warehouse Inc. to conduct a Phase Two Environmental Site Assessment (ESA) of the seven (7) parcels of land located at Part of Lot 4, Concession 4, Parts 1, 2, 3, 4, 5 Gloucester, Ontario (with municipal addresses of 3646, 3636, 3604 Innes Road, Ottawa, Ontario, and Part of Lot 4, Concession 3, Part 2, Plan 5R8348, Gloucester, Ontario) (the "Site"). The Site is a rectangular shaped vacant property with a square portion located on the northeast corner along Innes Road. The Site location is shown in Figure 1.

The Phase Two ESA was completed to characterize subsurface conditions according to current industry standards, in general accordance with *Ontario Regulation (O. Reg.) 153/04*. We understand that the Site may be sold and the south, vacant portion of the Site may be developed for residential uses; the north portion of the Site would remain commercial use. Full compliance with *O. Reg. 153/04* would require the filing of a Record of Site Condition (RSC) if the north portion of the Site is used for residential purposes. This Phase Two ESA may be used to support the filing of an RSC, if required by municipal planning approvals or the land conveyance of undevelopable land.

1.2 SITE DESCRIPTION AND PROPERTY OWNERSHIP

The Site is rectangular in shape with a small square portion extending east along Innes Road (on the northeast corner) with approximately 230 m of frontage along Innes Road, and extending 996 m south, covering approximately 23 hectares (57 acres) in plan area. There are eight (8) structures present on the north side of the Site, which are currently vacant commercial buildings (a former BMR hardware store). Five of the eight structures are on the east side of 3636 Innes Road and include a main retail building closest to Innes Road with four storage sheds (one of which is three-sided) located south of the main building. The remaining structures are located on the west side of the north portion of the Site, and include two shelters not completely closed in used for material storage and seasonal cashiers and one closed building used house a circular saw. The remaining south portion of the Site is vacant forested land. The site boundary is shown in Figure 2.

Mr. Martin Juneau of the Builders Warehouse authorized the Phase Two ESA on May 2, 2016. Mr. Juneau can be reached at mjuneau@bmr.co. Property information for the Site is provided in Table 1.

Table 1 Property Information

CRITERIA	PHASE TWO PROPERTY INFORMATION	
Current Property Owners	Part of Lot 4, Concession 3, Part 1 (3646 Innes Road) P.I.N. 0440400470	The Builder's Warehouse Holdings (2004) Inc.
	Part of Lot 4, Concession 3, Part 2, Plan 5R8348 P.I.N. 044040099	The Builder's Warehouse Inc.
	Part of Lot 4, Concession 3, Part 3, Plan 5R8348 (3636 Innes Road) P.I.N. 044040450	The Builder's Warehouse Inc.

CRITERIA	PHASE TWO PROPERTY INFORMATION	
	Part of Lot 4, Concession 3, Part 4 (3604 Innes Road) P.I.N. 044040444	The Builder's Warehouse Inc.
	Part of Lot 4, Concession 3, Part 5 (3636 Innes Road) P.I.N. 044040452	166441 Canada Inc. (in part) The Builder's Warehouse (in part)
	PIN 044040448	The Builder's Warehouse Inc.

1.3 CURRENT AND PROPOSED FUTURE USES

The Site consists of a vacant commercial development (former BMR hardware store) along Innes Road (3636 and 3604 Innes Road), which contained eight vacant buildings. The buildings were present on the north side of the Site, and were comprised of a main retail building on the northeast corner of 3636 Innes Road (building #5 in Figure 2), three sheds south of the main building along the east property line (buildings #1, #2, and #3) (Photo 3), a three sided shelter southwest of the three sheds (building #4), and a partially open self-serve retail shelter (building # 6), cashier shelter with four individual kiosks (building #7) and a shed which formerly contained a large circular saw (building #8) located on the west side of the Site, west of the main building and sheds. The surface of the north side of the property around building #5 was asphalt, with the remaining area around the buildings covered with gravel. Beyond the commercial operation, the ground surface is covered with natural vegetation ranging from grasses to trees. The topography of the Site has a gentle slope down towards the south.

The Builders Warehouse is considering the sale of the Site and recognizes that a residential development may be considered over the south portion of the site. The Phase Two ESA was completed to investigate areas of potential environmental concern (APECs) identified in the Phase One ESA and to document the environmental quality of soil and groundwater at the Site.

1.4 APPLICABLE SITE CONDITION STANDARD

WSP identified the applicable generic soil and groundwater standards based on the following information available for the Site:

- A surface water management ditch runs south along the west side of the Site and connects with the storm water management pond (SWMP) located on the south adjacent property. The ditch is not a watercourse, as defined in O.Reg. 153/04;
- Four well records located on the Site, and 24 well records for the Phase One Study Area. These were identified as public, domestic and public wells. Although the Study Area was rural, many of these wells are not likely still active and the City of Ottawa obtains its potable water from the Ottawa River;
- Surrounding properties are residential, commercial and vacant;
- The Site is not considered an "environmentally sensitive" site, as defined by O. Reg. 153/04;
- Field observations indicate that the soil at the Site is consistent with the definition of 'coarse textured' in O. Reg 153/04; and,
- Residential land use may be proposed for some or all of the Site.

→ Stratified soil conditions were not used for evaluating laboratory results.

Based on the above site specific details, soil and groundwater quality at the Site was compared to Table 2: Full Depth Generic Site Condition Standards (SCS) in a Potable Ground Water Condition Site Condition Standards for residential/institutional/parkland property uses set out in the Ministry of the Environment and Climate Change (MOECC) publication *Soil, Ground Water and Sediment Standards for Use Under Part XV.1 of the Environmental Protection Act* (April 15, 2011), hereinafter referred to as the “MOECC Table 2 SCS”.

2 BACKGROUND INFORMATION

2.1 PHYSICAL SETTING

The Site is situated within the Ottawa Valley Clay Plains physiographic region which consists of clay plains interrupted by ridges of rock or sand and characterized by deep grey silty clays mildly calcareous suggesting an origin from the more acidic rocks of the Canadian Shield (Chapman, et al., 2007). Bedrock within the Phase Two Study Area consists of the Middle Ordovician Rocks of Bobcaygeon Training Group of Simcoe and consists of limestone (Ontario Geological Survey, 2011).

The surface topography of the Site generally slopes southwest, with a 'lumber yard' identified on the north side of the Site. An unnamed water course is identified on the south adjacent property, just southwest of the Site. McKinnon Creek is identified as being approximately 600 m southeast of the Site. The Site is approximately 87 meters above sea level (masl). The principle direction of local groundwater flow in the overburden is inferred to the south/southwest with deeper aquifer groundwater flow expected to be to the north towards the Ottawa River (approximately 5 km away).

2.2 PAST INVESTIGATIONS

2.2.1 PHASE I ESA - 2013

A Phase I Environmental Site Assessment entitled '*Site 38 Orléans, 3636-3646, chemin Innes, Orléans (Ontario), Évaluation environnementale de site Phase I*' was completed by GENIVAR (now known as WSP) in June, 2013. The report outlined the following information:

- The Phase I was completed to the CSA Z768-01 Standards, and consisted of a records review, Site visit and interview.
- The Site consisted of seven (7) lots owned by the Builder's Warehouse Inc.:
 - 3646 Innes Road (PIN 044040470);
 - 3636 Innes Road (PIN 044040452, 044040451, 044040450 and 044040448)
 - 3604 Innes Road (PIN 044040444)
 - The north portion of Part of Lot 4, Concession 3, Part 2, Plan 5R8348, Gloucester, Ontario (PIN 044040099)
- A records review was conducted of the following:
 - ERIS Custom Report:
 - Ministry of the Environment (Now MOECC) FOI request
 - City of Ottawa FOI request
 - Aerial photographs
- The report identified the following environmental concerns:

- Evidence of impacted gravel fill underneath two diesel tanks of 4550 liters and a diesel tank of 2270 liters located outside the storage building No. 3.
- A barrel filled with potentially contaminated water on the northeast corner of the Site (3646 Innes Road). (Note: although not investigated through sampling, this concern is considered the least likely to have resulted in impacts compared to other areas that were investigated and confirmed to be acceptable.)
- Nine (9) barrels of waste oil observed on the southwest portion of the Site with visible evidence of petroleum hydrocarbon impacts.
- A dump was located on the southwest portion of the Site and southwest adjacent land.
- Snow storage historically occurred on the southern land.
- A Phase II Environmental Site Assessment was recommended to assess soil and groundwater quality for PHC F1-F4 (including BTEX) and PAHs contaminants in the areas of concern.
- It was recommended that observed wood debris, bricks, plastics, used tires located on the southwest corner of the Site be disposed of.
- It was also recommended that the floor of Storage building No. 2 be cleaned as a result of some leaking from barrels of hydraulic oil that were stored in the vicinity.

2.2.2 PHASE II ESA - 2013

A Phase II Environmental Site Assessment entitled '*Site 38 Orléans, 3636-3646, chemin Innes, Orléans (Ontario), Évaluation environnementale de site Phase II*' was completed by GENIVAR (now known as WSP) in September, 2013. The report outlined the following information:

- The Phase II Environmental Site Assessment was completed generally in accordance with O. Reg. 153/04 Records of Site Conditions-XV.1 Part of the Environmental Protection Act, however, the report format is not compliant with the regulation.
- The program consisted of advancing five test pits and 10 boreholes across the Site, one of which was completed into a monitoring well (located east of building number 2).
- Five test pits were completed in the following areas:
 - TE-01 in the southeast sector of the study site, near a container of waste;
 - TE-02 in the southeast section of the Site, where visible staining was observed underneath 9 barrels of waste oil;
 - TE-03 in the southern section of the Site, east of observed railway sleepers;
 - TE-04 southwest of the Site, north of the brick storage area;
 - TE-05 along the south boundary of the Site, north of the brick storage area, on top of the pile of soil.
- A total of 61 soil samples (including five duplicate samples) were collected from the test pits and boreholes advanced on the Site. Twenty-three samples (including two duplicate samples, with one analysed twice) were analyzed for petroleum hydrocarbons (PHC F1-F4 including BTEX) and polycyclic aromatic hydrocarbons (PAHs), and metals (Ag, As, B, Ba, Be, Cd, Cr, Co, Cu, Mo, Ni, Pb, Se, Sn, Ti, U, V and Zn) at EXOVA laboratory located in Ottawa, Ontario.
- A total of four samples (including three quality control samples) for groundwater were collected from the monitoring well and submitted to EXOVA laboratory located in Ottawa, Ontario.

- The results of the soil and groundwater chemical analysis were compared with the *Table 7: Generic Site Condition Standards for Shallow Soils in a Non-Potable Groundwater Condition, Industrial/Commercial/Community (ICC) and RPI property use under the Soil, Ground Water and Sediment Standards for Use Under Part XV.1 of the Environmental Protection Act.*
- The sample collected from 0.00 to 0.35 metres below ground surface (m bgs) in TE-02 had concentrations of PHC F3 and F4 above the Table 7 ICC and RPI criteria.
- A soil sample analysed from F-05 located at depths between 1.32 to 1.83 m bgs and a sample collected from TE-02 between 1.00 to 1.45 m bgs had concentrations of vanadium above the Table 7 SCS ICC and barium above the Table 7 SCS RPI standards. These exceedences were determined to likely be representative of the natural soil conditions of that area.
- All other soil samples submitted for analysis met the Table 7 SCS ICC and RPI criteria.
- The groundwater sample submitted for the monitoring well met the Table 7 SCS ICC and RPI criteria.

The volume of impacted soil located in the area of TE-02 was estimated to be approximately 105 m³, assuming the depth of contamination extends to 0.35 m bgs, and a 300m² surface area.

2.2.3 PHASE ONE ESA - 2016

A Phase One ESA was completed by WSP on June 27, 2016, in accordance with the requirements of O. Reg. 153/04. The Phase One ESA included a thorough review of the Phase I and II ESAs completed by GENIVAR in 2013.

Two APECs at the Site were identified that were resulting from two on site PCAs, and one APEC that was attributed to one off-site PCA with the potential for contaminant migration through groundwater movement.

The APECs identified at the Site include:

APEC-1 (southeast corner of the 'overstock storage yard'): The former Phase I and II ESA confirmed an exceedance of PHC F3 and F4 to the Table 7 SCS. The extent of the soil contamination should be delineated in order to provide an accurate estimate of the quantity of soil to be removed from the Site.

APEC-2 (south of the overstock storage yard/soil pile and fence/gate running east west south of the 'overstock storage yard'): Historical snow storage identified in the former Phase I ESA and interview may impact the soil and groundwater quality at the Site.

APEC-3 (along the east property line): Review of the 1996 and 2014 aerial photographs revealed that 3637, 3682 and 3698 Innes Road (located 70 metres east of the Site) had disturbed areas on the north side of the properties, with large commercial vehicle storage/maintenance present.

A Phase Two ESA was recommended to investigate soil and groundwater quality in the vicinity of the APECs identified at the Site.

It is also recommended that the miscellaneous plastics, wood, drywall and construction debris located across the north section of the Site be removed for off-site disposal.

2.3 POTENTIAL CONTAMINANTS OF CONCERN

Contaminants of potential concern (COPCs) associated with past activities at the adjacent lands include: metals and inorganics (MI), polycyclic aromatic hydrocarbons (PAHs), and petroleum hydrocarbon compounds (PHCs).

3

SCOPE OF THE INVESTIGATION

3.1 OVERVIEW OF THE SITE INVESTIGATION

The scope of work for the Phase Two ESA is in general accordance with the objectives outlined in O. Reg. 153/04. The sampling methods complied with the requirements established by the MOECC in the Guidance on Sampling and Analytical Methods for Use at Contaminated Sites in Ontario, 1997 and technical updates provided to support regulatory amendments. The tasks completed during the Phase Two ESA included:

- Preparing a sample and analysis plan to document the rationale for the investigation, including the number of sampling points, sampling frequency, analytical parameters and media to be sampled.
- Co-ordinating with the drilling contractor Strata Group Ltd. (Strata), and private/public locators to obtain utility locates near the proposed borehole locations.
- Providing site supervision during drilling to obtain samples of soil that are representative of the worst case conditions observed during the investigation.
- Advancing 13 boreholes to a maximum depth of 7.01 m. Soil samples were recovered from each borehole. Three of the boreholes were advanced into bedrock and completed as groundwater monitoring wells constructed with 31 mm diameter polyvinyl chloride (PVC) pipe with 3 m long screens and locked monument casings;
- Collecting, screening, and classifying soil samples at each borehole for possible laboratory analysis. Soil sample headspace vapours were monitored using a combustible gas indicator (CGI) and/or photoionization detector (PID) to assess the presence of VOCs and combustible petroleum contaminants;
- Selecting soil samples for submission to AGAT Laboratories, an accredited laboratory for chemical analysis of MI, PHCs, and PAHs.
- Monitoring subsurface vapour concentrations and water levels in the monitoring wells. Groundwater samples were collected from the monitoring wells and submitted and analysed for MIs, PAHs and PHCs;
- Collecting quality assurance/quality control (QA/QC) duplicate samples at a frequency of 10% throughout the field program, in compliance with regulatory requirements; and
- Comparing the results of soil and groundwater analysis to MOECC Table 2 SCS.

3.2 MEDIA INVESTIGATED

A Sampling and Analysis Plan (SAP) was developed prior to the field sampling events which outlined the proposed sampling locations and related analysis for both the soil and groundwater investigation. The sample locations are shown on Figure 2 and the SAPs are provided in Appendix A.

3.3 PHASE ONE CONCEPTUAL SITE MODEL

The preliminary Phase One Conceptual Site Model (CSM) presented in the Phase One ESA report (WSP, 2016) includes figures and narrative that provided the logical basis for the interpretation of PCAs and APECs on the Site. The Phase One CSM is summarized as follows:

- A surface water management ditch runs south along the west side of the Site and connects with the storm water management pond located on the south adjacent property.;
- Four well records located for the Site, and 24 well records for the Phase One Study Area. These were identified as public, domestic and public wells;
- Surrounding properties are residential, commercial and vacant;
- Road names are shown on Figures 2 and 3;
- Eight (8) vacant buildings are located on the north side of the Site, which are currently vacant commercial buildings. The remaining south portion of the Site is vacant/forested land;
- The Site is at approximately 87 masl and slopes slightly down to the south. The surrounding lands generally slope gently down to the south.
- Surficial geology mapping, the Phase II ESA report completed by GENIVAR in 2013 and well records suggest the Site consists of silt and clay. Bedrock consists of Limestone of the Middle Ordovician Rocks typically starting at ground surface in some areas;
- Based on the findings of the records review, interviews, and the site reconnaissance completed as part of the Phase One ESA, two PCAs were identified that have led to APECs at the Site. These PCAs include:
 - Other (snow disposal); and,
 - 52-Storage, maintenance, fueling, and repair of equipment, vehicles, and materials used to maintain transportation systems.

Information considered for the development of this CSM was gathered from numerous sources (i.e., aerial photographs, city directories, environmental database searches, physical setting sources, historical reports, interviews and a site reconnaissance), which reduces the potential for not identifying a former property use or PCA.

3.4 DEVIATIONS FROM SAMPLING AND ANALYSIS PLAN

The SAPs prepared in advance of the Phase Two ESA sampling events are included in Appendix A. The intent of these plans was followed during the investigations to ensure that the subsurface was adequately assessed at the APECs on the Site.

3.5 IMPEDIMENTS

There were no impediments or denial of access that prevented the completion of the original defined scope of the investigation.

4

INVESTIGATION METHOD

4.1 GENERAL

The soil and groundwater quality at the Site was investigated at the locations shown on Figure 2 through the advancement of boreholes and installation of groundwater monitoring wells to characterize environmental conditions at the APECs identified in the Phase One ESA. Investigation methods followed Standard Operating Procedures prepared by WSP for the conduct of environmental investigations. The investigation methods are described in the following sections.

4.2 DRILLING

WSP retained Strata Drilling Group (Strata), a MOECC-licensed driller to conduct the drilling activities at the Site under the supervision of WSP field staff between June 1 and June 2, 2016. The boreholes were advanced to evaluate subsurface locations, collect soil samples, and install groundwater monitoring wells at the Site. The drilling included:

- Six exterior boreholes to delineate the extent of the contaminants identified at TE-02 and F-05, which were advanced during the 2013 Phase II ESA (GENIVAR, September 2013). Two of these boreholes were completed as groundwater monitoring wells (BH/MW16-3 and BH/MW16-5) with screen lengths of 3.05 m in order to determine if the contaminants of concern were present in the groundwater.
- Four exterior boreholes into the areas identified during the Phase I ESA (GENIVAR, June 2013) and Phase One ESA (WSP, 2016) as snow storage areas. One of these boreholes (BH/MW16-8) was completed as a groundwater monitoring well with a screen length of 3.05 m in order to assess the groundwater conditions.
- Three exterior boreholes along the ATV/snowmobile trail running east-west in the vacant southern portion of the Site in order to assess soil quality.
- Monitoring wells BH/MW16-3, BH/MW16-5 were screened at depths from 1.52-4.57 metres below ground surface (mbgs); and BH/MW16-8 was screened at depths from 1.06 to 4.11 mbgs.

Soil samples were recovered from each of the borehole locations, visually inspected and logged. The borehole logs are presented in Appendix B and locations of the boreholes are presented in **Figure 2**.

4.3 SOIL

4.3.1 SOIL SAMPLING

Soil samples were collected continuously using plastic dual tube liners inserted into an outer rod (also known as an outer extension). Prior to sampling at each depth interval (1.2 m), a new tube was inserted into the outer rod to prevent potential cross-contamination of the recovered samples.

The geological conditions at the Phase Two Property were observed in the soil samples and recorded to a field log by a WSP technologist. Soil samples were collected with dedicated nitrile gloves to prevent cross contamination between sampling locations and were split into two portions: one placed

into labeled polyethylene bags for field screening and another jarred into the appropriate laboratory-supplied sample containers and stored in a cooler with ice for possible laboratory analysis. For samples considered for PHC fraction F1 analysis, a core of soil was placed in a pre-weighed laboratory prepared vial containing a measured amount of methanol. Soil samples considered to be representative of “worst-case” environmental conditions were selected for chemical analysis based on visual and olfactory observations made in the field and vapour readings.

A total of 44 soil samples (including 4 field duplicate samples) were submitted to AGAT Laboratories in Ottawa, Ontario. A summary of the soil samples submitted for chemical analysis are summarized in Table 1a to Table 1f, Table 2c, Table 3c and Tables 4 to Table 8 (appended).

4.4 FIELD SCREENING MEASUREMENTS

Soil samples were screened using an RKI Eagle 2, which operates as both a PID and CGI, to measure total organic vapours and combustible vapours, respectively. Results of field screening and the soil samples submitted to the laboratory for chemical analysis are included on the borehole logs (Appendix B).

The PID was equipped with a 10.6 electron-volt (eV) lamp, which was calibrated with a known concentration of isobutylene. This instrument detects VOCs that emit below an ionization potential of 10.6 eV, which includes a wide range of chemicals such as solvents and fuels. The detection limit of the instrument ranges from 0 to 15,000 ppm and accuracy is +/- 10% for VOCs in the range of 0 and 2,000 ppm and +/- 20% of the reading above 2,000 ppm. The resolution of this instrument is 0.1 ppm for VOCs in the range of 0 and 1,000 ppm and 1 ppm for readings above 1,000 ppm. The PID provides an indication of organic contamination in soil but does not measure concentrations of individual contaminants.

The CGI detects combustible vapours such as those associated with fuels. This instrument measures total combustible gases, calibrated to a known concentration of hexane. The instrument was operated in the methane elimination mode. The detection limit of the instrument ranges from 0 to 11,000 ppm (i.e., 100 % LEL of hexane). The CGI has an accuracy of 25 ppm below 1,000 ppm and 5% of the lower explosive limit (LEL) between 1,000 ppm and 100% LEL. As with the PID, it provides an indication of contamination but not chemical specific concentrations.

The instruments were obtained from Pine Environmental Services Inc. (Pine) for this project. Pine calibrates their instruments on a regular basis, including prior to the use on this project, to ensure consistent results. Site calibration of the field instruments was completed each day according to the manufacturer's instructions.

4.5 GROUND WATER: MONITORING WELL INSTALLATION

Three monitoring wells were installed at the Site to investigate the APECs identified during the Phase One ESA. The monitoring wells were constructed as follows:

- Each monitoring well was constructed using 31 mm diameter well screens and PVC riser pipe;
- The screened interval in the monitoring wells was 3.05 m long with a No. 10 slot size screen.
- Sand pack, consisting of No. 2 silica sand, was placed around the well and piezometer screens and the sand pack was extended to a minimum of 0.3 m above the top of the screen;

- A bentonite seal was then placed around the PVC riser pipe up to within 0.3 m of the ground surface; and
- The monitoring wells were completed with locked monument casings which were cemented into place.

The monitoring wells were installed by a licensed well technician from Strata in accordance with O. Reg. 903, as amended. The monitoring well construction details are shown on the attached borehole logs included as Appendix B.

After the monitoring well installations, well development was carried out to remove particulates and fluids that may have collected in the sand pack during drilling activities. The monitoring wells were equipped with dedicated 5/8-inch LDPE Waterra tubing and an inertial pump (footvalve) to facilitate groundwater sampling. The wells were then developed by purging five well volumes or by purging the wells dry five times prior to sampling.

4.6 GROUNDWATER: FIELD MEASUREMENT OF WATER QUALITY PARAMETERS

Following development, groundwater monitoring wells were sampled. Periodic measurements of the groundwater were recorded for temperature, pH, oxidation/reduction potential (ORP), dissolved oxygen (DO) and electrical conductivity (EC).

Prior to sampling, the depth to groundwater and depth to the bottom of each well was measured with an oil/water interface probe.

4.7 GROUNDWATER SAMPLING

On June 7, 2016 following purging of the wells, groundwater samples were collected using waterra tubing and an inertial lift foot valve.

Groundwater samples were conveyed directly into laboratory-supplied sample containers. Samples submitted for metals analysis were filtered in the field with dedicated 0.45 micron (µm) filters. Groundwater samples were placed in a cooler with ice and a completed chain of custody form for submission to the laboratory.

4.8 SEDIMENT SAMPLING

A water body is not present at the Phase Two Property. Therefore, sediment was not sampled as part of the investigation.

4.9 ANALYTICAL TESTING

Soil and groundwater samples were analyzed by AGAT Laboratories in Mississauga, Ontario which is accredited by the Standards Council of Canada (SCC) and analytical work was conducted in accordance with the requirements of O. Reg. 153/04.

Soil and groundwater samples were submitted for analysis of MI, PAHs and PHCs. Laboratory Certificates of Analysis are included in Appendix C.

4.10 RESIDUE MANAGEMENT PROCEDURES

The management of residues such as soil cuttings, purge and development groundwater, and fluids from equipment cleaning was conducted as indicated in the following table.

Table 2 Summary of Residue Management Procedures

RESIDUE	MANAGEMENT PROCEDURE
i. Soil cuttings from drilling and excavations	Soil cuttings from the drilling were left on-site.
ii. Water from well development and purging	Ground water from the development and purging of the monitoring wells was emptied onto the ground adjacent to the wells consistent with no visual evidence of PHC impacts, and the understanding that the vicinity of MW16-8 is to be excavated during remediation.
iii. Fluids from equipment cleaning.	Equipment cleaning water was emptied onto the ground adjacent to the wells.

4.11 ELEVATION SURVEYING

The elevation of the groundwater monitoring wells (ground elevation and top of PVC pipe) was surveyed by WSP and referenced to the top of the formed concrete pier located on the southwest corner of the most southerly building (building #4) (88.00 masl).

4.12 QUALITY ASSURANCE AND QUALITY CONTROL MEASURES

Quality assurance and quality control of the soil and groundwater water samples was monitored and maintained in a number of ways:

- This field investigation was completed under WSP standard operating procedures (SOPs). Deviations from the SOPs are documented and referenced in this report;
- Samples were given unique identifications as they were collected, identifying the project number, date, and sample location and depth. The sample numbers were recorded in field notes for each location;
- Sample containers provided by the laboratory were used and laboratory requirements for sample size, container type, preservatives and filtering were followed.
- Non-disposable sampling equipment was cleaned using Alconox and distilled water following each use;
- A chain-of-custody form was filled out for the samples prior to submitting the samples to the laboratory. The chain-of-custody documented sample movement from collection to receipt at the laboratory and provided sample identification, requested analysis and conditions of samples upon arrival at the laboratory (e.g., temperature, container status, etc.);

- Soil samples were randomly selected by the WSP field staff for duplicate testing. The number of QC samples submitted is equivalent to a minimum of 10% of the total number of samples submitted.
- Field monitoring equipment was calibrated according to industry requirements prior to the site visit including onsite calibration; and
- Samples were randomly selected by the laboratory for Quality Assurance checks. Generally, one sample for every ten samples submitted is checked. For each parameter, there is an acceptable upper and lower limit for the measured concentration of the parameter. Measured concentrations of analysed samples must fall within the upper and lower acceptable limits in order for the sample to be valid. If a result exceeds the upper or lower acceptable limits, the sample must be re-analysed.

5

REVIEW AND EVALUATION

5.1

GEOLOGY

The soil conditions encountered at the Site during the 2013 and 2016 drilling activities are presented in the borehole logs (Appendix B). The environmental condition of the overburden was investigated.

Fill (sand and gravel) was encountered in the boreholes advanced into the 'overstock storage yard' (BH16-1 to BH16-6). The depth of this layer of granular fill ranged from 0.23 m to 0.43 m. In 2013, granular fill (sandy gravel/gravelly sand or sand and gravel) was encountered to depths as shallow as 0.20 mbgs to a maximum depth of 0.61 mbgs. A sandy silt fill with some organic materials was encountered in TE-01, TE-02 and TE-05 to depths of 0.35 mbgs to 3.60 mbgs. At many locations, the fill material included foreign constituents such as wood, ash, coal and brick fragments.

Top soil was encountered in BH16-7 to BH16-13 from surface to depths of 0.15 to 0.23 mbgs.

The fill and topsoil was underlain by native clayey silt or silty clay. The 2013 investigation that focused on the north part of the Site observed the native soil to extend from 0.5 mbgs to a maximum depth of 2.34 mbgs. At the south part of the site, the native soil was observed as shallow as 2.53 m and extended to the maximum depth of 6.25 mbgs where BH16-2, BH16-3, BH16-4, BH16-6, and BH16-11 to BH16-13 were terminated on assumed bedrock.

A gravel or sandy gravel was encountered in BH16-1, BH16-3 and BH16-7 to BH16-10 to depths between 2.89 to 7.01 m bgs, where the boreholes were terminated on assumed bedrock (with the exception of BH16-3). BH16-3 and BH16-5 were advanced into bedrock to a depth of 4.57 mbgs where they were terminated.

5.2

GROUNDWATER: ELEVATIONS AND FLOW DIRECTION

The rationale for the location of the monitoring wells was to provide an investigation of APECs in the groundwater that were identified in the former ESA reports completed by WSP. The monitoring wells consisted of 3.05 m screen lengths. The screens typically intersected the inferred water table, based on the soil sampling observations.

Groundwater monitoring was completed at the Site on June 7, 2016. No free product or sheen was observed or measured in any of the monitoring wells as part of this investigation; however a PHC odour was observed in BH/MW16-5, located in the area of TE-02. The measured water levels ranged from 1.45 to 2.27 mbgs in all of the monitoring wells. This corresponds to groundwater elevations across the Site ranging from 85.10 to 85.39 masl. Based on the groundwater elevations, the groundwater flow is determined to be southwest.

5.3

SOIL: FIELD SCREENING

CGI and PID readings are shown on the borehole logs in Appendix B and the results are summarized below. The purpose of the screening was to evaluate whether combustible compounds (e.g., PHCs) and VOCs may be present in the recovered samples.

The PID readings for the soil samples were between 0 ppm to 35 ppm, and the CGI readings were from 0 ppm to 15 ppm. The results of the CGI and PID readings were at levels not indicative of gross PHC or VOC contamination.

5.4 SOIL QUALITY

Laboratory analytical results from the 2013 drilling/excavating program were tabulated with the current sampling results and compared to the MOECC Table 2 SCS. The majority of boreholes encountered on June 1 and 2nd, 2016 had more than 2 metres of overburden; therefore, the Table 7 SCS that was formerly used in the 2013 report is considered to no longer apply.

Comparison of the laboratory analytical results for soil samples to the MOECC Table 2 SCS identified elevated concentrations of MI and PHCs at all 13 locations in the June 2016 drilling program, and two of 15 locations in the 2013 drilling/excavating program.

The locations, depths, and type of chemical analysis of soil samples are provided on the borehole/test pit logs in Appendix B as well as identified in the analytical soil results tables provided in Table 1a to Table 1f (MI), Table 2a to Table 2c (PHCs including BTEX), and Table 3c (PAHs). The certificate of analysis is presented in Appendix C.

5.4.1 METALS AND INORGANICS

The soil analytical results for metals and inorganics are summarized in **Table 1a to Table 1f**, and presented in **Figure 3**. A total of 12 soil samples (excluding QA/QC samples) were submitted for analysis of metals in 2013, and 31 (excluding QA/QC samples) were submitted for metals, (inorganics included in 13 of those samples) in June 2016. Initial submission of the samples in June 2016 did not request the full O. Reg. 153 metals and inorganics package for analysis; however, this analysis was requested in subsequent correspondence with AGAT Laboratories.

During the 2013 sampling program, three of the 12 samples, recovered from two locations had one or more metal parameters (barium, cobalt and vanadium) with concentrations exceeding the MOECC Table 2 SCS:

- One sample submitted from FE-05 (located in the 'Overstock Storage Yard') had concentrations of barium and cobalt exceeding the MOECC Table 2 SCS from 1.35 to 1.83 mbgs in the native silty clay soil.
- Two samples from TE-02 (including the duplicate sample) located on the southeast corner of the 'overstock storage yard' had concentrations of vanadium greater than the MOECC Table 2 SCS from 1.00 to 1.45 mbgs in the native clayey silt soil.

During the 2016 sampling program, 25 (including two duplicates) of the 31 samples submitted had one or more metal parameters with elevated concentrations exceeding the Table 2 SCS. These impacts were present at all sampling locations submitted for analysis across the Site. Parameters exceeding the Table 2 SCS included barium, cobalt, vanadium, conductivity and sodium adsorption ratio (SAR).

Details of the frequency and distribution of the soil contaminants exceeding the Table 2 SCS are provided below:

- Three samples submitted from three sampling locations across the Site (BH16-3, BH16-5 and BH16-8) had concentrations of barium exceeding the Table 2 SCS. These exceedances were present at depths ranging from 1.52 to 3.05 mbgs in the native silty clay soils.
- 12 samples submitted from nine sampling locations across the Site (BH16-1, BH16-3, BH16-5, BH16-7, BH16-8, BH16-10, BH16-11, BH16-12, BH16-13) had concentrations of cobalt exceeding the Table 2 SCS. These exceedances were present at depths ranging from 0.20 to 4.57 mbgs in the native clayey silt or silty clay.
- 24 samples submitted from 12 locations across the Site (BH16-1, BH16-2, BH16-3, BH16-4, BH16-5, BH16-7, BH16-8, BH16-9, BH16-10, BH16-11, BH16-12 and BH16-13) had concentrations of vanadium exceeding the Table 2 SCS. These exceedances were present at depths ranging from 0.20 to 6.10 mbgs in the native soils.
- One sample submitted from BH16-6 had a concentration of SAR exceeding the Table 2 SCS. This exceedance was present from 0.23 to 1.52 mbgs in the native clayey silt soil.
- One sample submitted from BH16-8 had a concentration of EC exceeding the Table 2 SCS. This exceedance was present from 0.20 to 1.52 mbgs in the native clayey silt soil.

5.4.2 PETROLEUM HYDROCARBONS (INCLUDING BTEX)

The soil analytical results for petroleum hydrocarbons (PHC) including benzene, toluene, ethylbenzene, and xylenes (BTEX) are summarized in **Table 2a to Table 2c**, and presented in **Figure 4**. In 2013, a total of 16 soil samples were submitted for analysis of PHC including BTEX, and 4 soil samples were submitted for analysis of PHC F2 to F4, only. In 2016, three samples (including a duplicate) were submitted for PHC F2 to F4 analysis, and four samples were submitted for PHC F1 to F4 (including BTEX).

One (TE-02) of the 20 samples from 2013 had elevated PHC F2 and F3 concentrations exceeding the Table 2 SCS. This impact was present on the southeast corner of the 'overstock storage yard' in the fill material (55% brick, wood, burnt wood, plastic and 45% sandy silt with trace organic material) located from ground surface to 0.35 mbgs. Sampling conducted in 2016 did not identify any further PHC impacts.

5.4.3 POLYCYCLIC AROMATIC HYDROCARBONS

A total of 20 soil samples were submitted for analysis of polycyclic aromatic hydrocarbons (PAH) in 2013, and three soil samples were submitted in 2016. The soil analytical results for PAHs are summarized in **Table 3a to Table 3c**. The concentrations of PAHs from soil recovered in the 2013 and 2016 drilling programs were less than the Table 2 SCS.

5.5 GROUNDWATER QUALITY

The analytical groundwater results tables are provided in **Table 4 (MI)**, **Table 5 (PAHs)** and **Table 6 (PHC including BTEX)** and presented in **Figure 5**. The certificate of analysis is presented in Appendix C.

A total of 4 samples (including 1 duplicate) were submitted for MI, PHC including BTEX and PAH analysis during the 2016 sampling event. A trip blank was also analysed for PHC F1 and BTEX for

QA/QC purposes. Results from the 2013 groundwater sampling event were not tabulated with the 2016 results, as groundwater quality changes over time.

A comparison of the laboratory analytical results for the groundwater samples to the Table 2 SCS identified elevated concentrations of ethylbenzene and PHC F2 in MW16-5.

All MI and PAH parameters were less than the Table 2 SCS.

5.6 QUALITY ASSURANCE AND QUALITY CONTROL RESULTS

AGAT completed a variety of QA/QC measures on the soil and groundwater samples submitted as part of the sampling program. These QA/QC measures include: sample replicates, matrix spiked laboratory blanks, and process blanks.

Soil and groundwater samples were randomly selected by the WSP field staff for field duplicate testing. Duplicate samples were selected for every 10 samples submitted for analysis. WSP submitted the following field duplicate soil and groundwater samples:

Soil

- BH16-4-102 was a blind field duplicate of BH16-4-2 (2.28-3.05 m) and analyzed for MI;
- BH16-5-101B was a blind field duplicate of BH16-5-1B (0.23-1.52 m) and analyzed for MI;
- BH16-13-102A was a blind field duplicate of BH16-13-2A (1.52-2.75 m) and analyzed for MI; and,
- BH16-5-101B was a blind field duplicate of BH16-5-1B (0.23-1.52.66 m) and analyzed for PHC F2 to F4.

Groundwater

- MW16-108 was a blind field duplicate of MW16-8 and analyzed for MI, PAHs, and PHCs;

The results from the duplicate samples were used to assess the accuracy and reliability of the laboratory procedures and instruments.

A calculation of the relative percent difference (RPD) between the sample and its duplicate was performed and compared to the acceptance limits outlined in the Protocol for Analytical Methods Used in the Assessment of Properties under Part XV.1 of the Environmental Protection Act, April 2011. The RPD calculation is only applicable when both the sample and the field duplicate concentrations are greater than five times the reported detection limit.

The results are presented in Table 8 and Table 9 for soil and groundwater, respectively. An unacceptable level of agreement between the results of the parent and duplicate samples were identified as follows:

Soil

- Barium at BH16-4-102 exceeded the RPD criteria of 20%; and,

- Barium, Chromium (total), Cobalt, Copper, Nickel, Vanadium and Zinc at BH16-5-101B exceeded the RPD criteria of 20%.

The elevated RPDs may be attributed to the heterogeneity within the soil. These deviations from acceptable RPD criteria are not considered indicative of unacceptable data quality, however, where the concentrations of the contaminants (barium, chromium, cobalt, nickel and vanadium) approach Table 2 SCS, it should be considered that the values may be indicative of an exceedance of the standard.

Groundwater

The RPDs at MW16-106 were all below the 20% RPD criteria.

5.7 PHASE TWO CONCEPTUAL SITE MODEL

5.7.1 POTENTIALLY CONTAMINATING ACTIVITIES AND AREAS OF POTENTIAL ENVIRONMENTAL CONCERN

The Phase One ESA (WSP, 2016) identified two APECs at the Site that were resulting from two on site PCAs, and one APEC that was attributed to one off-site PCA with the potential for contaminant migration through groundwater movement.

The APECs identified at the Site include:

APEC-1 (southeast corner of the 'overstock storage yard'): The former Phase I and II ESA confirmed an exceedance of PHC F3 and F4 to the Table 7 SCS. The extent of the soil contamination should be delineated in order to provide an accurate estimate of the quantity of soil to be removed from the Site.

APEC-2 (south of the overstock storage yard/soil pile and fence/gate running east west south of the 'overstock storage yard'): Historical snow storage identified in the former Phase I ESA and interview may impact the soil and groundwater quality at the Site.

APEC-3 (along the east property line): Review of the 1996 and 2014 aerial photographs revealed that 3637, 3682 and 3698 Innes Road (located 70 metres east of the Site) had disturbed areas on the north side of the properties, with large commercial vehicle storage/maintenance present.

5.7.2 SUBSURFACE UTILITIES

There are no known underground utilities at the Site affecting the local groundwater flow.

5.7.3 PHYSICAL SETTING

Geological conditions encountered on the Site during the 2013 and 2016 drilling programs consisted of granular fill materials on the north side of the Site including foreign constituents in some areas such as wood, charred remains and brick fragments. The fill extended from ground surface to 0.61 mbgs, and was generally underlain by native silty clay and/or clayey silt until the boreholes/test pits were terminated. The boreholes advanced on the south side of the Site had top soil from ground surface to

0.23 mbgs, which was then underlain by native clayey silt or silty clay to a maximum depth of 6.25 mbgs. Bedrock was encountered from 0.5 to 4.57 mbgs.

Bedrock in the area consists of Middle Ordovician Rocks of Bobcaygeon Training Group of Simcoe and consists of limestone (Ontario Geological Survey, 2011).

5.7.4 BUILDINGS AND STRUCTURES

There are eight (8) structures present on the north side of the Site, which are currently vacant commercial buildings (a former BMR hardware store). Five of the eight structures are on the east side of 3636 Innes Road and include a main retail building closest to Innes Road with four storage sheds (one of which is three-sided) located south of the main building. The remaining structures are located on the west side of the north portion of the Site, and include two shelters not completely closed in used for material storage and seasonal cashiers and one closed building used house a circular saw.

5.7.5 ENVIRONMENTALLY SENSITIVE AREAS

No conditions were found on the Site which would apply under Section 41 (Environmentally Sensitive Areas) and Section 43.1 (Shallow Soil Property or lands within 30 m of a water body) of O.Reg. 153/04.

5.7.6 IMPORTED SOIL

During the Phase Two ESA conducted by WSP, no soil was imported onto the Site. Mixed fill conditions were encountered during the drilling and test pitting programs in 2013 and 2016. The origin of the fill material is unknown; however, an interview with the former co-owner of the Site Mr. Richard Laplante during the Phase One EAS indicated that the fill was brought in from local pits/quarries (WSP, 2016).

5.7.7 SOIL AND GROUNDWATER QUALITY

The laboratory analytical results indicate that the maximum measured concentrations of the following soil parameters exceed the applicable Table 2 SCS:

Table 3 Soil Parameters that exceed the Table 2 SCS

Metals and Inorganics	Barium
	Cobalt
	Conductivity
	Sodium Adsorption Ratio
	Vanadium
PHCs	Petroleum Hydrocarbon F3 Fraction
	Petroleum Hydrocarbon F4 Fraction

The laboratory analytical results indicate that the maximum measured concentrations of the following groundwater parameters exceed the applicable Table 2 SCS:

Table 4 Groundwater Parameters that exceed the Table 2 SCS

PHCs	Ethylbenzene
	Petroleum Hydrocarbon F2 Fraction

The distribution of the impacted soil and groundwater identified on the Site is illustrated on Figure 3 to Figure 5.

6

CONCLUSIONS

6.1

SUMMARY OF PHASE TWO FINDINGS

Based on the results of the Phase Two ESA, elevated concentrations of MI, and/or PHCs (including BTEX) in soil exceeding the Table 2 SCS were identified within the fill and native soils, extending to at least 6.10 mbgs across the site. In summary:

- Review of the chemical analysis of metals and inorganics of the soil submitted within the fill and native materials across the Site identified exceedances of barium, cobalt, and vanadium. Due to the presence of these chemicals in the native silty clay or clayey silt (in both 2013 and 2016 drilling programs), they may be representative of background in this area and not necessarily indicative of any off-Site or on-Site sources of contamination.
- The elevated concentrations of electrical conductivity (EC) and sodium adsorption ratio (SAR) identified in BH16-6 and BH16-8 may be attributed to the historic application of road salt on the Site. The salt impacts were identified in the shallow native soils.
- In 2013, elevated concentrations of PHC- F3 and F4 were identified within the fill material at TE-02 (located on the southeast corner of the 'overstock storage yard', from ground surface to 0.35 mbgs. The fill material was described as 55% brick, wood, burnt wood, plastic and 45% sandy silt with trace organic material. In 2016, BH16-4, BH/MW16-5 and BH16-6 were advanced around TE-02 to delineate the PHC F3 and F4 contamination. All samples collected from these boreholes met the applicable Table 2 SCS, indicating that impacts are limited to surface soil at TE-02.
- Elevated concentrations of ethylbenzene and PHC F2 were present in the groundwater of MW16-5 (located in the southeast corner of the 'overstock storage yard') when compared to the Table 2 SCS.

Based on the findings of the investigation, elevated concentrations of contaminants of concern were identified in soil and groundwater at the Site. Based on delineation efforts of the PHC F3 impacted soil located at FE-02, it has been determined that approximately 105 m² of impacted soil is in this location. Removal of the impacted soil may address groundwater impacts and it is recommended that groundwater be resampled after soil remediation.

The elevated metal concentrations in soil can be managed through a risk assessment process to identify risk management measures that will allow for this soil to remain onsite. This contaminant management (e.g., remediation and risk assessment) will be required prior to filing a Record of Site Condition.

7

QUALIFICATIONS OF THE ASSESSORS

The Phase Two ESA was completed by **Ms. Kathryn Maton, C.E.T.**, Environmental Technologist. Kathryn has over 6 years of experience in environmental site assessments. She has conducted Phase One and Two Environmental Site Assessments for industrial, commercial and residential properties. In completing this work she has contributed to identifying, defining and quantifying potential environmental liabilities to satisfy due diligence and regulatory obligations.

The Phase Two ESA was managed and reviewed by **Ms. Carolyn Adams, M.A.Sc., P.Eng.**, Senior Project Manager at WSP. Carolyn is a Chemical Engineer with a Master of Applied Science degree in Environmental Engineering. She has 26 years of experience in completing environmental investigations and has the knowledge and experience to identify potential sources of contamination and the fate and behaviour of contaminants in the environment. Carolyn is a Qualified Person (QP_{ESA}) under the Ministry of the Environment O. Reg. 153/04.

7.1

SIGNATURES

WSP carried out this Phase Two ESA and confirms the findings and conclusions presented in this report.

Report prepared by
WSP Canada Inc.

Reviewed by



Kathryn Maton, C.E.T.
Environmental Technologist




Carolyn Adams, M.A.Sc., P.Eng., QP_{ESA}/RA
Manager, Environmental Management


8

REFERENCES

- Chapman, L.J. and Putnam, D.F. 2007. Physiography of Southern Ontario; Ontario Geological Survey, Miscellaneous Release--Data 228 ISBN 978-1-4249-5158-1
- Gao, C., Shiota, J., Kelly, R. I., Brunton, F.R., van Haaften, S. 2006. Bedrock topography and overburden thickness mapping, southern Ontario; Ontario Geological Survey, Miscellaneous Release--Data 207. ISBN 1-4249-2550-9
- GENIVAR Inc., Juin 2013. Site 38 Orléans, 3636-3646, chemin Innes, Orléans (Ontario), Évaluation environnementale de site Phase I. Prepared for La Coop fédérée.
- GENIVAR Inc., Septembre 2013. Site 38 Orléans, 3636-3646, chemin Innes, Orléans (Ontario), Évaluation environnementale de site Phase II. Prepared for La Coop fédérée.
- Ontario Geological Survey, 2010. Surficial geology of Southern Ontario; Ontario Geological Survey, Miscellaneous Release--Data 128-REV 978-1-4435-2482-7 [zip file]
- Ontario Geological Survey 2011. 1:250 000 scale bedrock geology of Ontario; Ontario Geological Survey, Miscellaneous Release---Data 126-Revision 1. ISBN 978-1-4435-5705-4 [zip file]
- Ontario Ministry of the Environment. 2014b. Ontario Regulation 153/04, Records of Site Condition – Part XV.1 of the Act. January 1, 2014.
- WSP Canada Inc., June 20, 2016. Phase One Environmental Site Assessment, Part of Lot 4, Concession 3, Parts 1, 2 3, 4, and 5, Gloucester, Ontario (3646, 3636 and 3604 Innes Road, Ottawa, Ontario).



FIGURES



500 BOULEVARD GRÉBER 3E ÉTAGE
GATINEAU, QUÉBEC,
CANADA, J8T 7W3
WWW.WSPGROUP.COM

PHASE TWO ENVIRONMENTAL SITE ASSESSMENT
PART OF LOT 4, CONCESSION 3, PARTS 1, 2, 3, 4 AND 5
GLOUCESTER, ONTARIO
(3646, 3636 AND 3604 INNES ROAD, OTTAWA, ONTARIO)
SITE LOCATION PLAN

LEGEND



APPROXIMATE PROPERTY
BOUNDARY

Scale	1:35,000
Date	JUNE 2016
Drawn By	JS
Job No.	161-06382-00

Drawing No.

FIG. 1





500 BOULEVARD GRÉBER 3E ÉTAGE
GATINEAU, QUÉBEC,
CANADA, J8T 7W3
WWW.WSPGROUP.COM

CLIENT:
THE BUILDERS WAREHOUSE LTD

PROJECT:
PHASE TWO ENVIRONMENTAL SITE ASSESSMENT
PART OF LOT 4, CONCESSION 3 PARTS 1,2,3,4 AND 5
GLOUCESTER, ONTARIO
(3646, 3636 AND 3604 INNES ROAD, OTTAWA, ONTARIO)

- LEGEND**
- Borehole (WSP, 2016)
 - Monitoring Well (WSP, 2016)
 - Borehole (WSP, 2013)
 - Monitoring Well (WSP, 2013)
 - Test Pit (WSP, 2013)
 - Property Boundary

PROJECT NUMBER: 161-06382-00	DATE: JUNE 2016
DRAWN BY: JS	
CHECKED BY: KM	
SCALE: 1:4,000	
 NAD1983 ZONE 18	

TITLE

SITE PLAN AND STUDY AREA

FIGURE 2



500 BOULEVARD GRÉBER 3E ÉTAGE
GATINEAU, QUÉBEC,
CANADA, J8T 7W3
WWW.WSPGROUP.COM

CLIENT:
THE BUILDERS WAREHOUSE LTD

PROJECT:
PHASE TWO ENVIRONMENTAL SITE ASSESSMENT
PART OF LOT 4, CONCESSION 3 PARTS 1,2,3,4 AND 5
GLOUCESTER, ONTARIO
(3646, 3636 AND 3604 INNES ROAD, OTTAWA, ONTARIO)

LEGEND

- Borehole (WSP, 2016)
- Monitoring Well (WSP, 2016)
- Borehole (WSP, 2013)
- Monitoring Well (WSP, 2013)
- Test Pit (WSP, 2013)
- Property Boundary


Ba	398	1.52-2.28
Parameter	Concentration (ug/g)	Depth (m)

PROJECT NUMBER: 161-06382-00 DATE: JUNE 2016

DRAWN BY: JS

CHECKED BY: KM

SCALE: 1:4,000



NAD1983 ZONE 18

TITLE
**CONTAMINANT DISTRIBUTION OF
METALS AND INORGANICS IN SOIL**

FIGURE 3

Acronym	Parameter	Standard
Metals and Inorganics		
Ba	Barium	390
Co	Cobalt	22
V	Vanadium	86
EC	Electrical Conductivity (mS/cm)	0.7
SAR	Sodium Absorption Ratio	5
Standard: MOECC Table 2 Full Depth Generic Site Condition Standards in a Potable Groundwater Condition for Residential, Parkland, Institutional (RPI) Property Use with coarse textured soils.		



500 BOULEVARD GRÉBER 3E ÉTAGE
GATINEAU, QUÉBEC,
CANADA, J8T 7W3
WWW.WSPGROUP.COM

CLIENT:
THE BUILDERS WAREHOUSE LTD

PROJECT:
PHASE TWO ENVIRONMENTAL SITE ASSESSMENT
PART OF LOT 4, CONCESSION 3 PARTS 1,2,3,4 AND 5
GLOUCESTER, ONTARIO
(3646, 3636 AND 3604 INNES ROAD, OTTAWA, ONTARIO)

- LEGEND**
- Borehole (WSP, 2016)
 - Monitoring Well (WSP, 2016)
 - Borehole (WSP, 2013)
 - Monitoring Well (WSP, 2013)
 - Test Pit (WSP, 2013)
 - Property Boundary


F3	31100	0-0.35
Parameter	Concentration (ug/g)	Depth (m)

PROJECT NUMBER: 161-06382-00 DATE: JUNE 2016

DRAWN BY: JS

CHECKED BY: KM

SCALE: 1:4,000



NAD1983 ZONE 18

TITLE
**CONTAMINANT DISTRIBUTION OF
PHCS IN SOIL**

FIGURE 4

Acronym	Parameter	Standard
PHCs		
F3	Petroleum Hydrocarbons F3	300
F4	Petroleum Hydrocarbons F4	2800
Standard: MOECC Table 2 Full Depth Generic Site Condition Standards in a Potable Groundwater Condition for Residential, Parkland, Institutional (RPI) Property Use with coarse textured soils.		



500 BOULEVARD GRÉBER 3E ÉTAGE
GATINEAU, QUÉBEC,
CANADA, J8T 7W3
WWW.WSPGROUP.COM

CLIENT:
THE BUILDERS WAREHOUSE LTD

PROJECT:
PHASE TWO ENVIRONMENTAL SITE ASSESSMENT
PART OF LOT 4, CONCESSION 3 PARTS 1,2,3,4 AND 5
GLOUCESTER, ONTARIO
(3646, 3636 AND 3604 INNES ROAD, OTTAWA, ONTARIO)

- LEGEND**
- Monitoring Well (WSP, 2016)
 - Monitoring Well (WSP, 2013)
 - Property Boundary

F2	530
Parameter	Concentration (ug/L)


PROJECT NUMBER: 161-06382-00	DATE: JUNE 2016
DRAWN BY: JS	
CHECKED BY: KM	
SCALE: 1:4,000	

TITLE

CONTAMINANT DISTRIBUTION OF
PHCS IN GROUNDWATER

FIGURE 5

Acronym	Parameter	Standard
PHCs + BTEX		
EB	Ethylbenzene	2.4
F2	F2 Hydrocarbon Fraction	150
Standard: MOECC Table 2 Full Depth Generic Site Condition Standards in a Potable Groundwater Condition for Residential, Parkland, Institutional (RPI) Property Use.		



TABLES

Client: The Builder's Warehouse
Project number: 161-06383-00

Table 1a: Metals and Inorganics Soil Analytical Results (2013)

Parameter	Units	MOECC 2011 ¹ Table 2 ²	F-01	F-02	F-03	F-03	F-03	F-05	PO-01	TE-01
Drilling Date			27-Jun-2013	27-Jun-2013	27-Jun-2013	27-Jun-2013	27-Jun-2013	27-Jun-2013	27-Jun-2013	2-Jul-2013
Depth (m)	m		0.40-0.50	0.45-0.55	0.30-0.50	0.50-0.91	1.01-1.11	1.32-1.83	0.61-0.86	0.30-0.60
pH	N/A	NC	na	na	na	na	na	na	na	na
Antimony	µg/g	7.5	<1	<1	<1	<1	<1	<1	<1	<1
Arsenic	µg/g	18	3	2	3	4	2	1	2	3
Barium	µg/g	390	99	65	177	132	61	421	111	153
Beryllium	µg/g	4	<1	<1	<1	<1	<1	<1	<1	<1
Boron (Hot Water Soluble)	µg/g	1.5	na	na	na	na	na	na	na	na
Boron (Total)	µg/g	120	20	20	20	20	20	40	20	10
Cadmium	µg/g	1.2	<0.5	<0.5	<0.5	<0.5	<0.5	<0.5	<0.5	<0.5
Chromium (total)	µg/g	160	41	36	22	33	18	112	60	59
Chromium (VI)	µg/g	8	na	na	na	na	na	na	na	na
Cobalt	µg/g	22	9	8	4	7	7	27	11	10
Conductivity	mS/cm	0.7	na	na	na	na	na	na	na	na
Copper	µg/g	140	15	11	5	11	15	61	19	21
Cyanide, free	µg/g	0.051	na	na	na	na	na	na	na	na
Lead	µg/g	120	na	na	na	na	na	na	na	na
Mercury	µg/g	0.27	na	na	na	na	na	na	na	na
Molybdenum	µg/g	6.9	<1	<1	1	<1	<1	<1	<1	<1
Nickel	µg/g	100	23	19	16	21	16	70	29	33
Selenium	µg/g	2.4	na	na	na	na	na	na	na	na
Silver	µg/g	20	<0.2	<0.2	<0.2	<0.2	<0.2	<0.2	<0.2	<0.2
Sodium Adsorption Ratio	N/A	5	na	na	na	na	na	na	na	na
Thallium	µg/g	1	<1	<1	<1	<1	<1	<1	<1	<1
Uranium	µg/g	23	<0.5	<0.5	0.6	0.5	<0.5	0.6	0.6	<0.5
Vanadium	µg/g	86	39	36	10	32	27	105	53	45
Zinc	µg/g	340	54	33	10	35	24	140	57	58

NOTES

¹ MOECC 2011: Soil, Ground Water and Sediment Standards for Use Under Part XV.1 of the Environmental Protection Act (April 2011)

²Table 2: Full Depth Generic Site Condition Standards in a Potable Ground Water Condition (Coarse Textured Soil)

na: Not Analyzed

N/A: Not Applicable

NC: No Criteria

Value Yellow shading indicates parameter concentration exceeds MOECC Table 2 Site Condition Standards



Client: Grandmaître Family
Project number: 161-03361-00

Table 1b: Metals and Inorganics Soil Analytical Results (2013)

Parameter	Units	MOECC 2011 ¹ Table 2 ²	TE-02	TE-02	TE-02	Duplicate (TE-02)	TE-04
Drilling Date			2-Jul-2013	2-Jul-2013	2-Jul-2013	3-Jul-2013	2-Jul-2013
Depth (m)	m		0.00-0.35	0.35-1.00	1.00-1.45	1.00-1.45	1.00-2.30
pH	N/A	NC	na	na	na	na	na
Antimony	µg/g	7.5	<1	<1	<1	<1	<1
Arsenic	µg/g	18	5	6	2	2	3
Barium	µg/g	390	98	150	347	383	175
Beryllium	µg/g	4	<1	<1	<1	<1	<1
Boron (Hot Water Soluble)	µg/g	1.5	na	na	na	na	na
Boron (Total)	µg/g	120	20	30	40	40	30
Cadmium	µg/g	1.2	<0.5	<0.5	<0.5	<0.5	<0.5
Chromium (total)	µg/g	160	41	62	111	122	82
Chromium (VI)	µg/g	8	na	na	na	na	na
Cobalt	µg/g	22	7	10	18	20	14
Conductivity	mS/cm	0.7	na	na	na	na	na
Copper	µg/g	140	19	24	50	65	28
Cyanide, free	µg/g	0.051	na	na	na	na	na
Lead	µg/g	120	na	na	na	na	na
Mercury	µg/g	0.27	na	na	na	na	na
Molybdenum	µg/g	6.9	1	<1	<1	<1	<1
Nickel	µg/g	100	25	31	60	65	39
Selenium	µg/g	2.4	na	na	na	na	na
Silver	µg/g	20	<0.2	<0.2	<0.2	<0.2	<0.2
Sodium Adsorption Ratio	N/A	5	na	na	na	na	na
Thallium	µg/g	1	<1	<1	<1	<1	<1
Uranium	µg/g	23	<0.5	0.6	0.9	0.9	1
Vanadium	µg/g	86	38	52	98	109	72
Zinc	µg/g	340	138	80	113	135	110

NOTES

¹ MOECC 2011: Soil, Ground Water and Sediment Standards for Use Under Part XV.1 of the Environmental Protection Act (April 2011)

²Table 2: Full Depth Generic Site Condition Standards in a Potable Ground Water Condition (Coarse Textured Soil)

na: Not Analyzed

N/A: Not Applicable

NC: No Criteria

Value

Yellow shading indicates parameter concentration exceeds MOECC Table 2 Site Condition Standards



Client: The Builder's Warehouse
Project number: 161-06383-00

Table 1c: Metals and Inorganics Soil Analytical Results (2016)

Parameter	Units	MOECC 2011 ¹ Table 2 ²	BH16-1-1B	BH16-1-2A	BH16-1-2B	BH16-2-1B	BH16-2-2A	BH16-2-2B	BH16-3-1B	BH16-3-2A	BH16-3-3
Drilling Date			1-Jun-2016	1-Jun-2016	1-Jun-2016	1-Jun-2016	1-Jun-2016	1-Jun-2016	1-Jun-2016	1-Jun-2016	1-Jun-2016
Depth (m)	m		0.30-1.52	1.52-2.53	2.53-2.89	0.30-1.52	1.52-2.34	2.34-2.44	0.43-1.52	1.52-2.28	3.05-3.12
pH	N/A	NC	7.23	na	na	7.05	na	na	7.15	na	na
Antimony	µg/g	7.5	<0.8	<0.8	<0.8	<0.8	<0.8	<0.8	<0.8	<0.8	<0.8
Arsenic	µg/g	18	1	1	1	1	1	2	2	1	5
Barium	µg/g	390	325	347	198	345	355	271	286	398	346
Beryllium	µg/g	4	0.9	1	0.7	1	0.9	0.8	0.9	0.9	<0.5
Boron (Hot Water Soluble)	µg/g	1.5	0.13	na	na	0.15	na	na	0.24	na	na
Boron (Total)	µg/g	120	<5	<5	6	<5	<5	8	6	5	9
Cadmium	µg/g	1.2	<0.5	<0.5	<0.5	<0.5	<0.5	<0.5	<0.5	<0.5	<0.5
Chromium (total)	µg/g	160	101	108	45	116	99	65	113	111	26
Chromium (VI)	µg/g	8	<0.2	na	na	<0.2	na	na	<0.2	na	na
Cobalt	µg/g	22	19.7	23	10.7	22	20.4	16.7	21.6	22.6	6.8
Conductivity	mS/cm	0.7	0.458	na	na	0.419	na	na	0.465	na	na
Copper	µg/g	140	43	48	28	47	47	33	46	48	15
Cyanide	µg/g	0.051	<0.040	na	na	<0.040	na	na	<0.040	na	na
Lead	µg/g	120	7	7	6	8	7	6	7	7	8
Mercury	µg/g	0.27	<0.10	na	na	<0.10	na	na	<0.10	na	na
Molybdenum	µg/g	6.9	<0.5	<0.5	<0.5	<0.5	<0.5	<0.5	<0.5	<0.5	1
Nickel	µg/g	100	58	60	25	64	55	40	65	62	11
Selenium	µg/g	2.4	<0.4	<0.4	<0.4	<0.4	<0.4	<0.4	<0.4	<0.4	<0.4
Silver	µg/g	20	<0.2	<0.2	<0.2	<0.2	<0.2	<0.2	<0.2	<0.2	<0.2
Sodium Adsorption Ratio	N/A	5	0.486	na	na	0.855	na	na	1.11	na	na
Thallium	µg/g	1	0.4	0.5	<0.4	0.5	0.4	<0.4	<0.4	0.5	<0.4
Uranium	µg/g	23	0.6	0.6	<0.5	0.7	0.6	0.6	0.6	0.7	0.6
Vanadium	µg/g	86	91	101	57	99	98	76	88	102	25
Zinc	µg/g	340	123	137	71	132	129	101	120	146	56

NOTES

¹ MOECC 2011: Soil, Ground Water and Sediment Standards for Use Under Part XV.1 of the Environmental Protection Act (April 2011)

²Table 2: Full Depth Generic Site Condition Standards in a Potable Ground Water Condition (Coarse Textured Soil)

na: Not Analyzed

N/A: Not Applicable

NC: No Criteria

Value Yellow shading indicates parameter concentration exceeds MOECC Table 2 Site Condition Standards:

Client: The Builder's Warehouse
Project number: 161-06383-00

Table 1d: Metals and Inorganics Soil Analytical Results (2016)

Parameter	Units	MOECC 2011 ¹ Table 2 ²	BH16-4-1B	BH16-4-2B	BH16-4-102B (Duplicate of BH16-4-2B)	BH16-5-1B	BH16-5-101B (Duplicate of BH16-5-1B)	BH16-5-2B	BH16-6-1B	BH16-6-2B	BH16-7-1	BH16-7-2B
Drilling Date			1-Jun-2016	1-Jun-2016	1-Jun-2016	1-Jun-2016	1-Jun-2016	1-Jun-2016	1-Jun-2016	1-Jun-2016	1-Jun-2016	1-Jun-2016
Depth (m)	m		0.43-1.52	2.28-3.05	2.28-3.05	0.23-1.52	0.23-1.52	2.90-3.05	0.23-1.52	2.90-3.05	0.20-1.52	2.44-3.05
pH	N/A	NC	7.07	na	na	7.24	na	na	7.42	na	7.13	na
Antimony	µg/g	7.5	<0.8	<0.8	<0.8	<0.8	<0.8	<0.8	<0.8	<0.8	<0.8	<0.8
Arsenic	µg/g	18	1	2	4	1	2	2	3	3	2	1
Barium	µg/g	390	254	347	250	129	266	412	180	285	302	338
Beryllium	µg/g	4	0.8	1	0.8	0.6	0.9	1	0.6	0.9	1	0.7
Boron (Hot Water Soluble)	µg/g	1.5	0.12	na	na	0.29	na	na	0.55	na	0.11	na
Boron (Total)	µg/g	120	<5	8	9	<5	6	8	<5	9	<5	6
Cadmium	µg/g	1.2	<0.5	<0.5	<0.5	<0.5	<0.5	<0.5	<0.5	<0.5	<0.5	<0.5
Chromium (total)	µg/g	160	87	70	57	59	125	72	63	61	118	50
Chromium (VI)	µg/g	8	<0.2	na	na	<0.2	na	na	<0.2	na	<0.2	na
Cobalt	µg/g	22	16.3	20.2	18.2	11.2	22.2	19.1	12.4	18.4	22.4	15.1
Conductivity	mS/cm	0.7	0.363	na	na	0.325	na	na	0.569	na	0.579	na
Copper	µg/g	140	35	35	35	16	44	39	27	35	50	30
Cyanide	µg/g	0.051	<0.040	na	na	<0.040	na	na	<0.040	na	<0.040	na
Lead	µg/g	120	6	7	8	8	8	8	9	8	8	6
Mercury	µg/g	0.27	<0.10	na	na	<0.10	na	na	<0.10	na	<0.10	na
Molybdenum	µg/g	6.9	0.5	<0.5	<0.5	0.5	<0.5	<0.5	0.6	<0.5	<0.5	<0.5
Nickel	µg/g	100	47	43	37	27	66	43	34	37	67	32
Selenium	µg/g	2.4	<0.4	<0.4	<0.4	<0.4	<0.4	<0.4	<0.4	<0.4	<0.4	<0.4
Silver	µg/g	20	<0.2	<0.2	<0.2	<0.2	<0.2	<0.2	<0.2	<0.2	<0.2	<0.2
Sodium Adsorption Ratio	N/A	5	0.565	na	na	0.657	na	na	5.41	na	1.02	na
Thallium	µg/g	1	<0.4	0.4	<0.4	<0.4	<0.4	0.5	<0.4	<0.4	0.5	<0.4
Uranium	µg/g	23	1	0.6	0.6	0.9	1	0.6	0.6	0.6	0.8	0.6
Vanadium	µg/g	86	89	88	80	53	94	93	60	83	103	68
Zinc	µg/g	340	96	127	112	80	109	134	85	118	128	94

NOTES

¹ MOECC 2011: Soil, Ground Water and Sediment Standards for Use Under Part XV.1 of the Environmental Protection Act (April 2011)

² Table 2: Full Depth Generic Site Condition Standards in a Potable Ground Water Condition (Coarse Textured Soil)

na: Not Analyzed

N/A: Not Applicable

NC: No Criteria

Value Yellow shading indicates parameter concentration exceeds MOECC Table 2 Site Condition Standards:

Client: The Builder's Warehouse
Project number: 161-06383-00

Table 1e: Metals and Inorganics Soil Analytical Results (2016)

Parameter	Units	MOECC 2011 ¹ Table 2 ²	BH16-8-1	BH16-8-2B	BH16-9-1	BH16-9-2B	BH16-9-4	BH16-10-1	BH16-10-2B	BH16-10-4A	BH16-11-2A	BH16-11-3B
Drilling Date			1-Jun-2016	1-Jun-2016	2-Jun-2016	2-Jun-2016	2-Jun-2016	2-Jun-2016	2-Jun-2016	2-Jun-2016	2-Jun-2016	2-Jun-2016
Depth (m)	m		0.20-1.52	2.44-3.05	0.17-1.52	2.67-3.05	4.57-6.10	0.23-1.52	2.61-3.05	4.57-6.10	1.52-2.62	4.22-4.57
pH	N/A	NC	7.25	na	7.15	na	na	6.77	na	na	7.05	na
Antimony	µg/g	7.5	<0.8	<0.8	<0.8	<0.8	<0.8	<0.8	<0.8	<0.8	<0.8	<0.8
Arsenic	µg/g	18	2	2	2	1	1	2	1	2	2	1
Barium	µg/g	390	296	524	263	304	84	268	303	294	290	297
Beryllium	µg/g	4	0.9	1	0.9	0.7	<0.5	0.8	0.8	0.7	0.8	0.7
Boron (Hot Water Soluble)	µg/g	1.5	<0.10	na	0.22	na	na	<0.10	na	na	0.25	na
Boron (Total)	µg/g	120	<5	8	<5	<5	<5	<5	<5	8	<5	5
Cadmium	µg/g	1.2	<0.5	<0.5	<0.5	<0.5	<0.5	<0.5	<0.5	<0.5	<0.5	<0.5
Chromium (total)	µg/g	160	121	77	112	99	14	103	102	80	107	99
Chromium (VI)	µg/g	8	na	na	<0.2	na	na	<0.2	na	na	<0.2	na
Cobalt	µg/g	22	25.9	22.7	19.3	20	5.4	18.7	22.6	19.6	23.7	21.1
Conductivity	mS/cm	0.7	1.86	na	0.394	na	na	0.215	na	na	0.176	na
Copper	µg/g	140	44	47	47	46	11	44	45	40	48	47
Cyanide	µg/g	0.051	<0.040	na	<0.040	na	na	<0.040	na	na	<0.040	na
Lead	µg/g	120	9	9	8	6	4	7	6	7	7	6
Mercury	µg/g	0.27	<0.10	na	<0.10	na	na	<0.10	na	na	<0.10	na
Molybdenum	µg/g	6.9	0.5	0.5	0.6	<0.5	0.6	<0.5	<0.5	1	<0.5	0.7
Nickel	µg/g	100	67	49	60	56	10	58	59	47	62	56
Selenium	µg/g	2.4	<0.4	<0.4	<0.4	<0.4	<0.4	<0.4	<0.4	<0.4	<0.4	<0.4
Silver	µg/g	20	<0.2	<0.2	<0.2	<0.2	<0.2	<0.2	<0.2	<0.2	<0.2	<0.2
Sodium Adsorption Ratio	N/A	5	4.79	na	1.1	na	na	1.04	na	na	0.622	na
Thallium	µg/g	1	0.4	0.6	<0.4	0.4	<0.4	<0.4	0.4	<0.4	0.4	<0.4
Uranium	µg/g	23	0.9	0.7	1	0.9	<0.5	0.8	0.8	1.8	1	1
Vanadium	µg/g	86	98	101	99	102	21	89	96	87	100	94
Zinc	µg/g	340	126	149	114	126	21	106	123	117	124	123

NOTES

¹ MOECC 2011: Soil, Ground Water and Sediment Standards for Use Under Part XV.1 of the Environmental Protection Act (April 2011)

² Table 2: Full Depth Generic Site Condition Standards in a Potable Ground Water Condition (Coarse Textured Soil)

na: Not Analyzed

N/A: Not Applicable

NC: No Criteria

Value Yellow shading indicates parameter concentration exceeds MOECC Table 2 Site Condition Standards:

Client: The Builder's Warehouse
Project number: 161-06383-00

Table 1f: Metals and Inorganics Soil Analytical Results (2016)

Parameter	Units	MOECC 2011 ¹ Table 2 ²	BH16-12-2A	BH16-12-3B	BH16-13-2A	BH16-13-102A (Duplicate of BH16-13-2A)	BH16-13-3B
Drilling Date			2-Jun-2016	2-Jun-2016	2-Jun-2016	2-Jun-2016	2-Jun-2016
Depth (m)	m		1.52-2.11	3.81-4.57	1.52-2.75	1.52-2.75	3.53-4.57
pH	N/A	NC	7.13	na	7.13	na	na
Antimony	µg/g	7.5	<0.8	<0.8	<0.8	<0.8	<0.8
Arsenic	µg/g	18	2	1	2	2	2
Barium	µg/g	390	288	369	273	272	246
Beryllium	µg/g	4	0.7	0.7	0.8	0.7	0.7
Boron (Hot Water Soluble)	µg/g	1.5	0.37	na	0.34	na	na
Boron (Total)	µg/g	120	<5	5	5	<5	7
Cadmium	µg/g	1.2	<0.5	<0.5	<0.5	<0.5	<0.5
Chromium (total)	µg/g	160	116	99	112	109	84
Chromium (VI)	µg/g	8	<0.2	na	<0.2	na	na
Cobalt	µg/g	22	24.2	23.2	22.2	22.4	18.2
Conductivity	mS/cm	0.7	0.091	na	0.075	na	na
Copper	µg/g	140	51	50	47	46	38
Cyanide	µg/g	0.051	<0.040	na	<0.040	na	na
Lead	µg/g	120	8	7	7	7	6
Mercury	µg/g	0.27	<0.10	na	<0.10	na	na
Molybdenum	µg/g	6.9	<0.5	1	<0.5	<0.5	0.9
Nickel	µg/g	100	66	58	64	63	48
Selenium	µg/g	2.4	<0.4	<0.4	<0.4	<0.4	<0.4
Silver	µg/g	20	<0.2	<0.2	<0.2	<0.2	<0.2
Sodium Adsorption Ratio	N/A	5	0.436	na	0.416	na	na
Thallium	µg/g	1	0.4	0.5	<0.4	<0.4	<0.4
Uranium	µg/g	23	1.2	0.9	0.9	0.9	1.9
Vanadium	µg/g	86	105	114	94	93	82
Zinc	µg/g	340	129	141	123	120	108

NOTES

¹ MOECC 2011: Soil, Ground Water and Sediment Standards for Use Under Part XV.1 of the Environmental Protection Act (April 2011)

²Table 2: Full Depth Generic Site Condition Standards in a Potable Ground Water Condition (Coarse Textured Soil)

na: Not Analyzed

N/A: Not Applicable

NC: No Criteria

Value Yellow shading indicates parameter concentration exceeds MOECC Table 2 Site Condition Standards

Client: The Builder's Warehouse
Project number: 161-06383-00

Table 2a: PHC (including BTEX) Soil Analytical Results (2013)

Parameter	Units	MOECC 2011 ¹ Table 2 ²	F-01	F-02	F-02	F-03	F-03	F-03	F-04	F-05	F-06	F-07
Date Drilled			27-Jun-2013	27-Jun-2013	27-Jun-2013	27-Jun-2013	27-Jun-2013	27-Jun-2013	27-Jun-2013	27-Jun-2013	27-Jun-2013	27-Jun-2013
Depth (m)	m		0.40-0.50	0.45-0.55	0.55-0.75	0.30-0.50	0.50-0.91	1.01-1.11	0.61-1.22	1.32-1.83	0.00-0.61	0.61-1.22
Benzene	µg/g	0.21	<0.02	na	<0.02	<0.02	<0.02	<0.02	<0.02	<0.02	<0.02	<0.02
Toluene	µg/g	2.3	<0.02	na	<0.2	<0.2	<0.2	<0.2	<0.2	<0.2	<0.2	<0.2
Ethylbenzene	µg/g	1.1	<0.05	na	<0.05	<0.05	<0.05	<0.05	<0.05	<0.05	<0.05	<0.05
m/p xylenes	µg/g	NC	<0.05	na	<0.05	<0.05	<0.05	<0.05	<0.05	<0.05	<0.05	<0.05
o xylene	µg/g	NC	<0.05	na	<0.05	<0.05	<0.05	<0.05	<0.05	<0.05	<0.05	<0.05
Total Xylenes	µg/g	3.1	<0.05	na	<0.05	<0.05	<0.05	<0.05	<0.05	<0.05	<0.05	<0.05
Petroleum Hydrocarbons F1	µg/g	55	<10	20	<10	<10	<10	<10	<10	<10	<10	<10
Petroleum Hydrocarbons F1 - BTEX	µg/g	55	<10	na	<10	<10	<10	<10	<10	<10	<10	<10
Petroleum Hydrocarbons F2	µg/g	98	<10	<10	<10	<10	<10	<10	<10	<10	<10	<10
Petroleum Hydrocarbons F3	µg/g	300	<20	<20	<20	<20	<20	<20	<20	<20	30	<20
Petroleum Hydrocarbons F4	µg/g	2800	40	100	60	20	<20	<20	20	<20	60	<20

NOTES

¹ MOECC 2011: Soil, Ground Water and Sediment Standards for Use Under Part XV.1 of the Environmental Protection Act (April 2011)

²Table 2: Full Depth Generic Site Condition Standards in a Potable Ground Water Condition (Coarse Textured Soil)

na: Not Analyzed

N/A: Not Applicable

NC: No Criteria

Value Yellow shading indicates parameter concentration exceeds MOECC Table 2 Site Condition Standards

Client: The Builder's Warehouse
Project number: 161-06383-00

Table 2b: PHC (including BTEX) Soil Analytical Results (2013)

Parameter	Units	MOECC 2011 ¹ Table 2 ²	F-08	F-09	PO-01	TE-01	TE-02	TE-02	TE-02	TE-03	TE-04	TE-05
Date Drilled			27-Jun-2013	27-Jun-2013	27-Jun-2013	2-Jul-2013	2-Jul-2013	2-Jul-2013	2-Jul-2013	2-Jul-2013	2-Jul-2013	2-Jul-2013
Depth (m)	m		0.61-1.22	0.00-0.61	0.61-0.86	0.30-0.60	0.00-0.35	0.35-1.00	1.00-1.45	0.30-1.00	1.00-2.30	0.15-2.30
Benzene	µg/g	0.21	<0.02	<0.02	<0.02	<0.02	<0.02	<0.02	<0.02	na	na	na
Toluene	µg/g	2.3	<0.2	<0.2	<0.2	<0.2	<0.2	<0.2	<0.2	na	na	na
Ethylbenzene	µg/g	2	<0.05	<0.05	<0.05	<0.05	<0.05	<0.05	<0.05	na	na	na
m/p xylenes	µg/g	NC	<0.05	<0.05	<0.05	<0.05	<0.05	<0.05	<0.05	na	na	na
o xylene	µg/g	NC	<0.05	<0.05	<0.05	<0.05	<0.05	<0.05	<0.05	na	na	na
Total Xylenes	µg/g	3.1	<0.05	<0.05	<0.05	<1	<1	<0.05	<0.05	na	na	na
Petroleum Hydrocarbons F1	µg/g	55	30	<10	<10	<10	<10	<10	<10	<10	<10	<10
Petroleum Hydrocarbons F1 - BTEX	µg/g	55	30	<10	<10	<10	<10	<10	<10	na	na	na
Petroleum Hydrocarbons F2	µg/g	98	<10	<10	<10	<10	20	<10	<10	<10	<10	<10
Petroleum Hydrocarbons F3	µg/g	300	80	60	<20	<20	31100	100	110	<20	30	<20
Petroleum Hydrocarbons F4	µg/g	2800	30	240	140	70	10400	160	60	<20	40	<20

NOTES

¹ MOECC 2011: Soil, Ground Water and Sediment Standards for Use Under Part XV.1 of the Environmental Protection Act (April 2011)

² Table 2: Full Depth Generic Site Condition Standards in a Potable Ground Water Condition (Coarse Textured Soil)

na: Not Analyzed

N/A: Not Applicable

NC: No Criteria

Value Yellow shading indicates parameter concentration exceeds MOECC Table 2 Site Condition Standard:

Client: The Builder's Warehouse
Project number: 161-06383-00

Table 2c: PHC (including BTEX) Soil Analytical Results (2016)

Parameter	Units	MOECC 2011 ¹ Table 2 ²	BH16-4-1B	BH16-5-1B	BH16-5-101B (Duplicate of BH16-5-1B)	BH16-5-2B	BH16-6-1B	BH16-7-1	BH16-8-1
Date Drilled			1-Jun-2016	1-Jun-2016	1-Jun-2016	1-Jun-2016	1-Jun-2016	1-Jun-2016	1-Jun-2016
Depth (m)	m		0.43-1.52	0.23-1.52	0.23-1.52	2.9-3.05	0.23-1.52	0.20-1.52	0.20-1.53
Benzene	µg/g	0.21	na	na	na	<0.02	<0.02	<0.02	<0.02
Toluene	µg/g	2.3	na	na	na	<0.08	<0.08	<0.08	<0.08
Ethylbenzene	µg/g	1.1	na	na	na	0.16	<0.05	<0.05	<0.05
Total Xylenes	µg/g	3.1	na	na	na	0.06	<0.05	<0.05	<0.05
Petroleum Hydrocarbons F1	µg/g	55	na	na	na	11	<5	<5	<5
Petroleum Hydrocarbons F1 - BTEX	µg/g	55	na	na	na	11	<5	<5	<5
Petroleum Hydrocarbons F2	µg/g	98	<10	<10	<10	34	<10	<10	<10
Petroleum Hydrocarbons F3	µg/g	300	<50	<50	<50	<50	<50	<50	<50
Petroleum Hydrocarbons F4	µg/g	2800	<50	<50	<50	<50	<50	<50	<50

NOTES

¹ MOECC 2011: Soil, Ground Water and Sediment Standards for Use Under Part XV.1 of the Environmental Protection Act (April 2011)

²Table 2: Full Depth Generic Site Condition Standards in a Potable Ground Water Condition (Coarse Textured Soil)

na: Not Analyzed

N/A: Not Applicable

NC: No Criteria

Value Yellow shading indicates parameter concentration exceeds MOECC Table 2 Site Condition Standards

Client: The Builder's Warehouse
Project number: 161-06383-00

Table 3a: PAH Soil Analytical Results

Parameter	MOECC 2011 ¹ Table 2 ²	Units	F-01	F-02	F-02	F-03	F-03	F-03	F-04	F-05	F-06	F-07
Date Drilled			27-Jun-2013	27-Jun-2013	27-Jun-2013	27-Jun-2013	27-Jun-2013	27-Jun-2013	27-Jun-2013	27-Jun-2013	27-Jun-2013	27-Jun-2013
Depth (m)		m	0.40-0.50	0.45-0.55	0.55-0.75	0.30-0.50	0.50-0.91	1.01-1.11	0.61-1.22	1.32-1.83	0.00-0.61	0.61-1.22
Acenaphthene	7.9	µg/g	<0.05	<0.05	<0.05	<0.05	<0.05	<0.05	<0.05	<0.05	<0.05	<0.05
Acenaphthylene	0.15	µg/g	<0.05	<0.05	<0.05	<0.05	<0.05	<0.05	<0.05	<0.05	<0.05	<0.05
Anthracene	0.67	µg/g	<0.05	<0.05	<0.05	<0.05	<0.05	<0.05	<0.05	<0.05	<0.05	<0.05
Benzo(a)anthracene	0.5	µg/g	<0.05	<0.05	<0.05	<0.05	<0.05	<0.05	<0.05	<0.05	<0.05	<0.05
Benzo(a)pyrene	0.3	µg/g	<0.05	<0.05	<0.05	<0.05	<0.05	<0.05	<0.05	<0.05	<0.05	<0.05
Benzo(b)fluoranthene	0.78	µg/g	<0.05	<0.05	<0.05	<0.05	<0.05	<0.05	<0.05	<0.05	<0.05	<0.05
Benzo(ghi)perylene	6.6	µg/g	<0.05	<0.05	<0.05	<0.05	<0.05	<0.05	<0.05	<0.05	<0.05	<0.05
Benzo(k)fluoranthene	0.78	µg/g	<0.05	<0.05	<0.05	<0.05	<0.05	<0.05	<0.05	<0.05	<0.05	<0.05
Chrysene	7	µg/g	<0.05	<0.05	<0.05	<0.05	<0.05	<0.05	<0.05	<0.05	<0.05	<0.05
Dibenzo(a,h)anthracene	0.1	µg/g	<0.05	<0.05	<0.05	<0.05	<0.05	<0.05	<0.05	<0.05	<0.05	<0.05
Fluoranthene	0.69	µg/g	<0.05	<0.05	<0.05	<0.05	<0.05	<0.05	<0.05	<0.05	<0.05	<0.05
Fluorene	62	µg/g	<0.05	<0.05	<0.05	<0.05	<0.05	<0.05	<0.05	<0.05	<0.05	<0.05
Indeno(1,2,3-cd)pyrene	0.38	µg/g	<0.05	<0.05	<0.05	<0.05	<0.05	<0.05	<0.05	<0.05	<0.05	<0.05
1-Methylnaphthalene	NC	µg/g	<0.05	<0.05	<0.05	<0.05	<0.05	<0.05	<0.05	<0.05	<0.05	<0.05
2-Methylnaphthalene	NC	µg/g	<0.05	<0.05	<0.05	<0.05	<0.05	<0.05	<0.05	<0.05	<0.05	<0.05
Methylnaphthalene, 2-(1-)	0.99	µg/g	<0.10	<0.10	<0.10	<0.10	<0.10	<0.10	<0.10	<0.10	<0.10	<0.10
Naphthalene	0.6	µg/g	<0.05	<0.05	<0.05	<0.05	<0.05	<0.05	<0.05	<0.05	<0.05	<0.05
Phenanthrene	6.2	µg/g	<0.05	<0.05	<0.05	<0.05	<0.05	<0.05	<0.05	<0.05	<0.05	<0.05
Pyrene	78	µg/g	<0.05	<0.05	0.12	<0.05	<0.05	<0.05	<0.05	0.16	<0.05	<0.05

NOTES

¹ MOECC 2011: Soil, Ground Water and Sediment Standards for Use Under Part XV.1 of the Environmental Protection Act (April 2011)

² Table 2: Full Depth Generic Site Condition Standards in a Potable Ground Water Condition (Coarse Textured Soi

Value Yellow Shading indicates parameter concentration exceeds MOECC Table 2 Standards

Client: The Builder's Warehouse
Project number: 161-06383-00

Table 3b: PAH Soil Analytical Results (2013)

Parameter	MOECC 2011 ¹ Table 2 ²	Units	F-08	F-09	PO-01	TE-01	TE-02	TE-02	TE-02	TE-03	TE-04	TE-05
Date Drilled			27-Jun-2013	27-Jun-2013	27-Jun-2013	2-Jul-2013	2-Jul-2013	2-Jul-2013	2-Jul-2013	2-Jul-2013	2-Jul-2013	2-Jul-2013
Depth (m)		m	0.61-1.22	0.00-0.61	0.61-0.86	0.30-0.60	0.00-0.35	0.35-1.00	1.00-1.45	0.30-1.00	1.00-2.30	0.15-2.30
Acenaphthene	7.9	µg/g	<0.05	<0.05	<0.05	<0.05	<0.05	<0.05	<0.05	<0.05	<0.05	<0.05
Acenaphthylene	0.15	µg/g	<0.05	<0.05	<0.05	<0.05	<0.05	<0.05	<0.05	<0.05	<0.05	<0.05
Anthracene	0.67	µg/g	<0.05	<0.05	<0.05	<0.05	0.15	<0.05	<0.05	<0.05	<0.05	<0.05
Benzo(a)anthracene	0.5	µg/g	<0.05	<0.05	<0.05	<0.05	<0.05	<0.05	<0.05	<0.05	<0.05	<0.05
Benzo(a)pyrene	0.3	µg/g	<0.05	<0.05	<0.05	<0.05	<0.05	<0.05	<0.05	<0.05	<0.05	<0.05
Benzo(b)fluoranthene	0.78	µg/g	<0.05	<0.05	<0.05	<0.05	<0.05	<0.05	<0.05	<0.05	<0.05	<0.05
Benzo(ghi)perylene	6.6	µg/g	<0.05	<0.05	<0.05	<0.05	<0.05	<0.05	<0.05	<0.05	<0.05	<0.05
Benzo(k)fluoranthene	0.78	µg/g	<0.05	<0.05	<0.05	<0.05	<0.05	<0.05	<0.05	<0.05	<0.05	<0.05
Chrysene	7	µg/g	<0.05	<0.05	<0.05	<0.05	<0.05	<0.05	<0.05	<0.05	<0.05	<0.05
Dibenzo(a,h)anthracene	0.1	µg/g	<0.05	<0.05	<0.05	<0.05	<0.05	<0.05	<0.05	<0.05	<0.05	<0.05
Fluoranthene	0.69	µg/g	<0.05	<0.05	<0.05	<0.05	0.17	<0.05	<0.05	<0.05	<0.05	0.05
Fluorene	62	µg/g	<0.05	<0.05	<0.05	<0.05	<0.05	<0.05	<0.05	<0.05	<0.05	<0.05
Indeno(1,2,3-cd)pyrene	0.38	µg/g	<0.05	<0.05	<0.05	<0.05	<0.05	<0.05	<0.05	<0.05	<0.05	<0.05
1-Methylnaphthalene	NC	µg/g	<0.05	<0.05	<0.05	<0.05	<0.05	<0.05	<0.05	<0.05	<0.05	<0.05
2-Methylnaphthalene	NC	µg/g	<0.05	<0.05	<0.05	<0.05	<0.05	<0.05	<0.05	<0.05	<0.05	<0.05
Methylnaphthalene, 2-(1-)	0.99	µg/g	<0.10	<0.10	<0.10	<0.10	<0.10	<0.10	<0.10	<0.10	<0.10	<0.10
Naphthalene	0.6	µg/g	<0.05	<0.05	<0.05	<0.05	<0.05	<0.05	<0.05	<0.05	<0.05	<0.05
Phenanthrene	6.2	µg/g	<0.05	<0.05	<0.05	<0.05	0.07	<0.05	<0.05	<0.05	<0.05	<0.05
Pyrene	78	µg/g	<0.05	<0.05	<0.05	<0.05	0.17	<0.05	<0.05	<0.05	<0.05	<0.05

NOTES

¹ MOECC 2011: Soil, Ground Water and Sediment Standards for Use Under Part XV.1 of the Environmental Protection Act (April 2011)

² Table 2: Full Depth Generic Site Condition Standards in a Potable Ground Water Condition (Coarse Textured Soil)

Value Yellow Shading indicates parameter concentration exceeds MOECC Table 2 Standard:

Phase Two Environmental Site Assessment
Part of Lot 4, Concession 3, Parts 1 to 5, Gloucester, Ontario
(3646, 3636 and 3604 Innes Road, Ottawa, Ontario)

Client: The Builder's Warehouse
Project number: 161-06383-00

Table 3c: PAH Soil Analytical Results (2016)

Parameter	MOECC 2011 ¹ Table 2 ²	Units	BH16-5-2B	BH16-7-1	BH16-8-1
Date Drilled			1-Jun-2016	1-Jun-2016	1-Jun-2016
Depth (m)		m	2.90-3.05	0.2-1.52	0.2-1.52
Acenaphthene	7.9	µg/g	<0.05	<0.05	<0.05
Acenaphthylene	0.15	µg/g	<0.05	<0.05	<0.05
Anthracene	0.67	µg/g	<0.05	<0.05	<0.05
Benzo(a)anthracene	0.5	µg/g	<0.05	<0.05	<0.05
Benzo(a)pyrene	0.3	µg/g	<0.05	<0.05	<0.05
Benzo(b/j)fluoranthene	0.78	µg/g	<0.05	<0.05	<0.05
Benzo(ghi)perylene	6.6	µg/g	<0.05	<0.05	<0.05
Benzo(k)fluoranthene	0.78	µg/g	<0.05	<0.05	<0.05
Chrysene	7	µg/g	<0.05	<0.05	<0.05
Dibenzo(a,h)anthracene	0.1	µg/g	<0.05	<0.05	<0.05
Fluoranthene	0.69	µg/g	<0.05	<0.05	<0.05
Fluorene	62	µg/g	0.11	<0.05	<0.05
Indeno(1,2,3-cd)pyrene	0.38	µg/g	<0.05	<0.05	<0.05
Methylnaphthalene, 2-(1-)	0.99	µg/g	0.50	<0.05	<0.05
Naphthalene	0.6	µg/g	0.06	<0.05	<0.05
Phenanthrene	6.2	µg/g	0.17	<0.05	<0.05
Pyrene	78	µg/g	<0.05	<0.05	<0.05

NOTES

¹ MOECC 2011: Soil, Ground Water and Sediment Standards for Use Under Part XV.1 of the Environmental Protection Act (April 2011)

² Table 2: Full Depth Generic Site Condition Standards in a Potable Ground Water Condition (Coarse Textured Soil)

Value

Yellow Shading indicates parameter concentration exceeds MOECC Table 2 Standards



Client: The Builder's Warehouse
Project number: 161-06383-00

Table 4: Metals and Inorganics Groundwater Analytical Results

Parameter	Units	MOECC 2011 ¹ Table 2 ²	MW16-3	MW16-5	MW16-8	MW16-108 (Duplicate of MW16-8)
Sample Date			7-Jun-16	7-Jun-16	7-Jun-16	7-Jun-16
Antimony	µg/L	6	<1.0	<1.0	<1.0	<1.0
Arsenic	µg/L	25	<1.0	1.9	<1.0	<1.0
Barium	µg/L	1000	89.7	166	224	187
Beryllium	µg/L	4	<0.5	<0.5	<0.5	<0.5
Boron	µg/L	5000	48.5	41.9	21.5	16.3
Cadmium	µg/L	2.7	<0.2	<0.2	<0.2	<0.2
Chloride	µg/L	790000	133000	286000	341000	358000
Chromium	µg/L	50	2.4	4.9	2.6	5
Chromium VI	µg/L	25	<5	<5	<5	<5
Cobalt	µg/L	3.8	<0.5	3.3	0.9	0.8
Copper	µg/L	87	2	<1.0	1.1	<1.0
Cyanide, Free	µg/L	66	<2	<2	<2	<2
Lead	µg/L	10	<0.5	<0.5	<0.5	<0.5
Mercury	µg/L	0.29	<0.02	<0.02	<0.02	<0.02
Molybdenum	µg/L	70	0.6	1.2	<0.5	<0.5
Nickel	µg/L	100	1.3	<1.0	1.4	<1.0
Sodium	µg/L	2300000	63200	65600	66900	65200
Selenium	µg/L	10	1.6	<1.0	<1.0	<1.0
Silver	µg/L	1.5	<0.2	<0.2	<0.2	<0.2
Thallium	µg/L	2	<0.3	<0.3	<0.3	<0.3
Vanadium	µg/L	6.2	2.4	1.5	4.8	4.8
Uranium	µg/L	20	1.3	5	4.4	3.7
Zinc	µg/L	1100	<5.0	<5.0	<5.0	<5.0

NOTES

¹ MOECC 2011: Soil, Ground Water and Sediment Standards for Use Under Part XV.1 of the Environmental Protection Act (April 2011)

² Table 2: Full Depth Generic Site Condition Standards in a Potable Ground Water Condition for Residential Property Use

na: Not Analyzed

Client: The Builder's Warehouse
Project number: 161-06383-00

Table 5: PAH Groundwater Analytical Results (2016)

Parameter	Units	MOECC 2011 ¹ Table 2 ²	MW16-3	MW16-5	MW16-8	MW16-108 (Duplicate of MW16-8)
Sample Date			7-Jun-16	7-Jun-16	7-Jun-16	7-Jun-16
Acenaphthene	µg/L	4.1	<0.20	<0.20	<0.20	<0.20
Acenaphthylene	µg/L	1	<0.20	<0.20	<0.20	<0.20
Anthracene	µg/L	2.4	<0.10	<0.10	<0.10	<0.10
Benzo(a)anthracene	µg/L	1	<0.20	<0.20	<0.20	<0.20
Benzo(a)pyrene	µg/L	0.01	<0.01	<0.01	<0.01	<0.01
Benzo(b,j)fluoranthene	µg/L	0.1	<0.10	<0.10	<0.10	<0.10
Benzo(ghi)perylene	µg/L	0.2	<0.20	<0.20	<0.20	<0.20
Benzo(k)fluoranthene	µg/L	0.1	<0.10	<0.10	<0.10	<0.10
Chrysene	µg/L	0.1	<0.10	<0.10	<0.10	<0.10
Dibenzo(a,h)anthracene	µg/L	0.2	<0.20	<0.20	<0.20	<0.20
Fluoranthene	µg/L	0.41	<0.20	<0.20	<0.20	<0.20
Fluorene	µg/L	120	<0.20	<0.20	<0.20	<0.20
Indeno(1,2,3-cd)pyrene	µg/L	0.2	<0.20	<0.20	<0.20	<0.20
Methylnaphthalene, 2-(1-)	µg/L	3.2	<0.20	<0.20	<0.20	<0.20
Naphthalene	µg/L	11	<0.20	<0.20	<0.20	<0.20
Phenanthrene	µg/L	1	<0.10	<0.10	<0.10	<0.10
Pyrene	µg/L	4.1	<0.20	<0.20	<0.20	<0.20

NOTES

¹ MOECC 2011: Soil, Ground Water and Sediment Standards for Use Under Part XV.1 of the Environmental Protection Act (April 2011)

² Table 2: Full Depth Generic Site Condition Standards in a Potable Ground Water Condition for Residential Property Us

NC: No Criteria

Value Yellow shading indicates parameter concentration exceeds MOECC Table 2 Site Condition

Client: The Builder's Warehouse
Project number: 161-06383-00

Table 6: PHC (including BTEX) Groundwater Analytical Results (2016)

Parameter	Units	MOECC 2011 ¹ Table 2 ²	MW16-3	MW16-5	MW16-8	MW16-108 (Duplicate of MW16-8)	Trip Blank
Sample Date			7-Jun-16	7-Jun-16	7-Jun-16	7-Jun-16	25-May-16
Benzene	µg/L	5	<0.20	1.1	<0.20	<0.20	<0.20
Toluene	µg/L	24	<0.20	0.39	<0.20	<0.20	<0.20
Ethylbenzene	µg/L	2.4	<0.10	15	<0.10	<0.10	<0.10
m/p xylenes	µg/L	NC	-	-	-	-	-
o xylene	µg/L	NC	-	-	-	-	-
Total Xylenes	µg/L	300	<0.20	4.2	<0.20	<0.20	<0.20
Petroleum Hydrocarbons F1	µg/L	750	<25	360	<25	<25	<25
Petroleum Hydrocarbons F1-BTEX	µg/L	750	<25	360	<25	<25	<25
Petroleum Hydrocarbons F2	µg/L	150	<100	530	<100	<100	na
Petroleum Hydrocarbons F3	µg/L	500	<100	390	<100	<100	na
Petroleum Hydrocarbons F4	µg/L	500	<100	<100	<100	<100	na

NOTES

¹ MOECC 2011: Soil, Ground Water and Sediment Standards for Use Under Part XV.1 of the Environmental Protection Act (April 2011)

² Table 2: Full Depth Generic Site Condition Standards in a Potable Ground Water Condition for Residential Property Use

NC: No Criteria

Value Yellow shading indicates parameter concentration exceeds MOECC Table 2 Site Condition Standard

Phase Two Environmental Site Assessment
Part of Lot 4, Concession 3, Parts 1 to 5, Gloucester, Ontario
(3646, 3636 and 3604 Innes Road, Ottawa, Ontario)

Client: The Builder's Warehouse
Project number: 161-06383-00

Table 7: Summary of Groundwater Elevations

Location	Depth (m)	Total Depth of Well (mbgs)	Ground Surface Elevation (m) ¹	7-Jun-16					
				Groundwater Level (mbgs)	Liquid Hydrocarbon Thickness (mm)	Groundwater Elevation (masl) ¹	Groundwater Level Above Well Screen? (yes/no)	Well Headspace PID Vapour Readings (ppm)	
								Hexane	Isobutylene
MW16-3	1.52-4.57	4.57	87.23	2.13	0	85.10	no	0	0
MW16-5	1.52-4.57	4.57	87.47	2.27	0	85.20	no	0	0
MW16-8	1.06-4.11	4.11	86.84	1.45	0	85.39	no	0	0

NOTES

¹ Approximate to an assumed elevation (88.00 masl) for the top of the formed concrete pier located on the southwest corner of the most southerly building (building #4).

Table 8: Summary of Relative Percent Differences (RPDs) in Soil

Parameter	RDL	Sample ⁽¹⁾	Duplicate	% Difference	Sample ⁽¹⁾	Duplicate	% Difference	Sample ⁽¹⁾	Duplicate	% Difference	MOECC Criteria
		BH16-4-2B	BH16-4-102B		BH16-5-1B	BH16-5-101B		BH16-13-2A	BH16-13-102A		
Metals and Inorganics											
As	-	-	-	-	7.24	-	-	7.13	-	-	-
Arsenic	0.8	<0.8	<0.8	-	<0.8	<0.8	-	<0.8	<0.8	-	20.0%
Barium	1	2	4	66.7%	1	2	66.7%	2	2	0.0%	20.0%
Boron	2	247	250	30.5%	129	266	69.4%	273	272	0.4%	20.0%
Beryllium	0.5	1	0.6	-	0.6	0.9	40.0%	0.6	0.7	-	20.0%
Boron (Hot Water Soluble)	0.10	-	-	-	0.29	-	-	0.34	-	-	20.0%
Boron (Total)	5	6	9	-11.8%	<5	6	-	5	<5	-	20.0%
Cadmium	0.5	<0.5	<0.5	-	<0.5	<0.5	-	<0.5	<0.5	-	20.0%
Chromium (total)	2	70	57	20.9%	59	125	71.7%	112	109	2.7%	20.0%
Chromium (VI)	0.2	-	-	-	<0.2	-	-	<0.2	-	-	20.0%
Cobalt	0.5	20.2	18.2	10.4%	11.2	22.2	65.9%	22.2	22.4	0.9%	20.0%
Conductivity	0.005	-	-	-	0.325	-	-	0.075	-	-	20.0%
Copper	1	35	35	0.0%	16	44	93.3%	47	46	2.2%	20.0%
Cyanide	0.040	-	-	-	<0.040	-	-	<0.040	-	-	20.0%
Lead	1	7	8	13.3%	8	-	0.0%	7	-	0.0%	20.0%
Mercury	0.10	-	-	-	<0.10	-	-	<0.10	-	-	20.0%
Molybdenum	0.5	<0.5	<0.5	-	0.5	<0.5	-	<0.5	<0.5	-	20.0%
Nickel	1	43	37	16.0%	21	56	83.8%	64	63	1.6%	20.0%
Selenium	0.4	<0.4	<0.4	-	<0.4	<0.4	-	<0.4	<0.4	-	20.0%
Silver	0.2	<0.2	<0.2	-	<0.2	<0.2	-	<0.2	<0.2	-	20.0%
Sodium Adsorption Ratio	-	-	-	-	0.657	-	-	0.435	-	-	20.0%
Thallium	0.4	0.4	<0.4	-	<0.4	<0.4	-	<0.4	<0.4	-	20.0%
Uranium	0.5	0.5	0.6	0.0%	0.9	1	-	0.9	0.9	0.0%	20.0%
Vanadium	1	85	85	0.0%	33	84	55.8%	34	35	3.1%	20.0%
Zinc	5	127	112	12.6%	80	109	30.7%	123	120	2.5%	20.0%

Parameter	RDL	Sample ⁽¹⁾	Duplicate	% Difference	MOECC Criteria
		BH16-5-1B	BH16-5-101B		
BTEX and PHCs					
Benzene	0.02	na	na	-	20.0%
Ethene	0.09	na	na	-	20.0%
Ethylbenzene	0.05	na	na	-	20.0%
Petroleum Hydrocarbons P1	5	na	na	-	20.0%
Petroleum Hydrocarbons P1 - BTEX	5	na	na	-	20.0%
Petroleum Hydrocarbons P2	10	<10	<10	-	20.0%
Petroleum Hydrocarbons P3	50	<50	<50	-	20.0%
Petroleum Hydrocarbons P4	90	<90	<90	-	20.0%

Notes:

(1)
<
% Difference
-

All results reported in micrograms per gram (µg/g) unless otherwise noted.
Parameter not detected above value specified.
Relative Percent Difference = [(X-Y)/Average(X,Y)] x 100% where X is the sample and Y
RPD could not be calculated.

Client: The Builder's Warehouse
Project number: 161-06383-00

Table 9: Summary of Relative Percent Differences (RPDs) in Groundwater

Parameter	RDL	Sample ⁽¹⁾	Duplicate	% Difference	MOECC Criteria
		MW16-8	MW16-108		
Metals and Inorganics					
Antimony	1.0	<1.0	<1.0	-	20.0%
Arsenic	1.0	<1.0	<1.0	-	20.0%
Barium	2.0	224	187	18.0%	20.0%
Beryllium	0.5	<0.5	<0.5	-	20.0%
Boron	10.0	21.5	16.3	27.5%	20.0%
Cadmium	0.2	<0.2	<0.2	-	20.0%
Chloride	1000	341000	358000	-4.9%	20.0%
Chromium	2.0	2.6	5	-63.2%	20.0%
Chromium VI	5.0	<5	<5	-	20.0%
Cobalt	0.5	0.9	0.8	11.8%	20.0%
Copper	1.0	1.1	<1.0	-	20.0%
Cyanide	2.0	<2	<2	-	20.0%
Lead	0.5	<0.5	<0.5	-	20.0%
Mercury	0.02	<0.02	<0.02	-	20.0%
Molybdenum	0.5	<0.5	<0.5	-	20.0%
Nickel	1.0	1.4	<1.0	-	20.0%
Sodium	2500	66900	65200	-2.6%	20.0%
Selenium	1.0	<1.0	<1.0	-	20.0%
Silver	0.2	<0.2	<0.2	-	20.0%
Thallium	0.3	<0.3	<0.3	-	20.0%
Vanadium	0.4	4.8	4.8	0.0%	20.0%
Uranium	0.5	4.4	3.7	17.3%	20.0%
Zinc	5.0	<5.0	<5.0	-	20.0%

Parameter	RDL	Sample ⁽¹⁾	Duplicate	% Difference	MOECC Criteria
		MW16-8	MW16-108		
BTEX and PHCs					
Benzene	0.20	<0.20	<0.20	-	20.0%
Toluene	0.20	<0.20	<0.20	-	20.0%
Ethylbenzene	0.10	<0.10	<0.10	-	20.0%
m/p xylenes	-	-	-	-	20.0%
o xylene	-	-	-	-	20.0%
Total Xylenes	0.2	<0.20	<0.20	-	20.0%
Petroleum Hydrocarbons F1	25	<25	<25	-	20.0%
Petroleum Hydrocarbons F1-BTEX	25	<25	<25	-	20.0%
Petroleum Hydrocarbons F2	100	<100	<100	-	20.0%
Petroleum Hydrocarbons F3	100	<100	<100	-	20.0%
Petroleum Hydrocarbons F4	100	<100	<100	-	20.0%

Parameter	RDL	Sample ⁽¹⁾	Duplicate	% Difference	MOECCCC Criteria
		MW16-8	MW16-108		
PAHs					
Acenaphthene	0.20	<0.20	<0.20	-	20.0%
Acenaphthylene	0.20	<0.20	<0.20	-	20.0%
Anthracene	0.10	<0.10	<0.10	-	20.0%
Benzo(a)anthracene	0.20	<0.20	<0.20	-	20.0%
Benzo(a)pyrene	0.01	<0.01	<0.01	-	20.0%
Benzo(b,j)fluoranthene	0.10	<0.10	<0.10	-	20.0%
Benzo(ghi)perylene	0.20	<0.20	<0.20	-	20.0%
Benzo(k)fluoranthene	0.10	<0.10	<0.10	-	20.0%
Chrysene	0.10	<0.10	<0.10	-	20.0%
Dibenzo(a,h)anthracene	0.20	<0.20	<0.20	-	20.0%
Fluoranthene	0.20	<0.20	<0.20	-	20.0%
Fluorene	0.20	<0.20	<0.20	-	20.0%
Indeno(1,2,3-cd)pyrene	0.20	<0.20	<0.20	-	20.0%
Methylnaphthalene, 2-(1-)	0.20	<0.20	<0.20	-	20.0%
Naphthalene	0.20	<0.20	<0.20	-	20.0%
Phenanthrene	0.10	<0.10	<0.10	-	20.0%
Pyrene	0.20	<0.20	<0.20	-	20.0%

Notes:

(1)
<
% Difference
-

All results reported in micrograms per gram (µg/L) unless otherwise noted.
Parameter not detected above value specified
Relative Percent Difference = |(X-Y)/Average(X,Y)| x 100% where X is the sample and Y is
RPD could not be calculated.

Appendix A

SAMPLE AND ANALYSIS PLAN

Sampling and Analysis Plan
Phase Two Environmental Site Assessment
Lot 4, Concession 4, Parts 1, 2, 3, 4, 5 Gloucester, Ontario
(3646, 3636, 3604 Innes Road, Ottawa, Ontario)

Soil				
Sample Location	Proposed Borehole/Test Pit Depth (mbgs)	Reg 153 Metals & Inorganics	PHC F1-F4	PAHs
BH16-1	6	3	0	0
BH16-2	6	3	0	0
BH/MW16-3	6	3	0	0
BH16-4	6	2	1	0
BH/MW16-5	6	2	2	1
BH16-6	10-15	2	1	0
BH16-7	6	2	1	1
BH/MW16-8	6	2	1	1
BH16-9	6	3	0	0
BH16-10	6	3	0	0
BH16-11	6	2	0	0
BH16-12	6	2	0	0
BH16-13	6	2	0	0
Blind Field Duplicates		2	1	0
TOTALS		17	10	7

*PHC F1-BTEX samples to be placed directly into vials with preservative or using hermetic core.

Sampling and Analysis Plan
Phase Two Environmental Site Assessment
Lot 4, Concession 4, Parts 1, 2, 3, 4, 5 Gloucester, Ontario
(3646, 3636, 3604 Innes Road, Ottawa, Ontario)

Groundwater					Environmental Investigation Notes
Sample Location	Proposed Monitoring Well Depth	Reg 153 Metals & Inorganics	PHC F1-F4	PAHs	
MW-3	4.5 m (Screen: 1.5-4.5 m)	1	1	1	Take headspace vapour readings before purging and collecting samples
MW-5	4.5 m (Screen: 1.5-4.5 m)	1	1	1	
MW-8	4.5 m (Screen: 1.5-4.5 m)	1	1	1	
Blind Field Duplicates		1	1	1	
TOTALS		4	4	4	

Appendix B

BOREHOLE LOGS

BOREHOLE DRILLING RECORD : **BH16-1**

Prepared by: **Kathryn Maton**
Reviewed by: **Carolyn Adams**

Date (Start): 1/6/2016
Date (End): 1/6/2016

Project Name: **Phase Two Environmental Site Assessment**
 Site: **Part of Lot 4, Concession 3, Parts 1-5, Gloucester, Ontario**
 Sector:
 Client: **The Builders Warehouse Inc.**

Project Number: **161-06382-00**
 Geographic Coordinates: X = 5032601 mE
 Y = 459357 mN
 Surface Elevation: m ()
 Top of PVC Elevation:

Drilling Company:	Strata Drilling Group
Drilling Equipment:	Geomachine GS100
Drilling Method:	Probe rod
Borehole Diameter:	50 mm
Drilling Fluid:	None
Sampling Method:	

ODOUR
F - Light
M - Medium
P - Persistent

VISUAL
D - Disseminated Product
S - Saturated with Product

SAMPLE TYPE
DC - Diamond Core
SS - Split Spoon
MA - Manual Auger
TR - Trowel
ST - Shelby Tube
TU - DT32 Liner
MC - Macro Core Liner

CHEMICAL ANALYSIS			
PCB	Poly-Chlorinated Biphenyls	MAH	Monocyclic Aromatic Hydrocarbons
BTEX	Benzene, Toluene, Ethylbenzene, Xylene	PAH	Polycyclic Aromatic Hydrocarbons
Inorg. C.	Inorganic Compounds	PH C ₁₀ -C ₂₀	Petroleum Hydrocarbons C ₁₀ -C ₂₀
Phenol. C.	Phenolic Compounds	PH F1-F4	Aromatic Hydrocarbons F1-F4 (C ₁₀ -C ₂₀)
VOC	Volatile Organic Compounds (MAH & CAH)	Metals	Potassium, Barium, Cadmium, Chromium, Cobalt, Copper, Lead, Manganese, Molybdenum, Nickel, Silver, Tin, Zinc.
Diox. & Fur.	Dioxins & Furans	HWR	Leachate Tests (Haz. Waste Reg.)
CAH	Chlorinated Aliphatic Hydrocarbons		

▽ Water Level ▼ Free Phase

[illegible]

BOREHOLE DRILLING RECORD : **BH16-2**

Prepared by: **Kathryn Maton**
Reviewed by: **Carolyn Adams**

Date (Start): 1/6/2016
Date (End): 1/6/2016

Project Name: **Phase Two Environmental Site Assessment**
Site: **Part of Lot 4, Concession 3, Parts 1-5, Gloucester, Ontario**
Sector:
Client: **The Builders Warehouse Inc.**

Project Number: **161-06382-00**
Geographic Coordinates: X = 5032622 mE
Y = 459337 mN
Surface Elevation: m ()
Top of PVC Elevation:

Drilling Company:	Strata Drilling Group
Drilling Equipment:	Geomachine GS100
Drilling Method:	Probe rod
Borehole Diameter:	50 mm
Drilling Fluid:	None
Sampling Method:	

ODOUR
F - Light
M - Medium
P - Persistent

VISUAL
D - Disseminated Product
S - Saturated with Product

SAMPLE TYPE
DC - Diamond Core
SS - Split Spoon
MA - Manual Auger
TR - Trowel
ST - Shelby Tube
TU - DT32 Liner
MC - Macro Core Liner

CHEMICAL ANALYSIS			
PCB	Poly-Chlorinated Biphenyls	MAH	Monocyclic Aromatic Hydrocarbons
BTEX	Benzene, Toluene, Ethylbenzene, Xylene	PAH	Polycyclic Aromatic Hydrocarbons
Inorg. C.	Inorganic Compounds	PH C ₁₂ -C ₅₀	Petroleum Hydrocarbons C ₁₂ -C ₅₀
Phenol. C.	Phenolic Compounds	PH F1-F4	Aromatic Hydrocarbons F1-F4 (C ₁₂ -C ₅₀)
VOC	Volatile Organic Compounds (MAH & CAH)	Metals	Anteism, Barium, Cadmium, Chromium, Cobalt, Copper, Lead, Manganese, Molybdenum, Nickel, Silver, Tin, Zinc.
Diox. & Fur.	Dioxins & Furans	HWR	Leachate Tests (Haz. Waste Reg.)
CAH	Chlorinated Aliphatic Hydrocarbons		

 Water Level Free Phase

[illegible]

BOREHOLE DRILLING RECORD : **BH/MW16-3**

Prepared by: **Kathryn Maton**
Reviewed by: **Carolyn Adams**

Date (Start): **1/6/2016**
Date (End): **2/6/2016**

Project Name: **Phase Two Environmental Site Assessment**
Site: **Part of Lot 4, Concession 3, Parts 1-5, Gloucester, Ontario**
Sector:
Client: **The Builders Warehouse Inc.**

Project Number: **161-06382-00**
 Geographic Coordinates: X = 5011286 mE
 Y = 472354 mN
 Surface Elevation: 87.23 m (*Relative*)
 Top of PVC Elevation:

Drilling Company:	Strata Drilling Group
Drilling Equipment:	Geomachine GS100
Drilling Method:	Probe rod
Borehole Diameter:	50 mm
Drilling Fluid:	Air
Sampling Method:	

ODOUR
F - Light
M - Medium
P - Persistent

VISUAL
D - Disseminated Product
S - Saturated with Product

SAMPLE TYPE
DC - Diamond Corer
SS - Split Spoon
MA - Manual Auger
TR - Trowel
ST - Shelby Tube
TU - DT32 Liner
MC - Macro Core Line

CHEMICAL ANALYSIS	
PCB	Poly-Chlorinated Biphenyls
BTEX	Benzene, Toluene, Ethylbenzene, Xylene
Inorg. C.	Inorganic Compounds
Phenol. C.	Phenolic Compounds
VOC	Volatile Organic Compounds (MAH & CAH)
Diox. & Fur.	Dioxins & Furans
CAH	Chlorinated Aliphatic Hydrocarbons

MAH	Monocyclic Aromatic Hydrocarbons
PAH	Polycyclic Aromatic Hydrocarbons
PH C ₁₀ -C ₅₀	Petroleum Hydrocarbons C ₁₀ -C ₅₀
PH F1-F4	Petroleum Hydrocarbons F1-F4 (C ₁₀ -C ₅₀)
Metals	Arsenic, Barium, Cadmium, Chromium, Cobalt, Copper, Lead, Manganese, Molybdenum, Nickel, Silver, Tin, Zinc.
HWR	Leachate Tests (Haz. Waste Req.)

▽ Water Level ▼ Free Phase

[illegible]

BOREHOLE DRILLING RECORD : **BH16-4**

Prepared by: **Kathryn Maton**
Reviewed by: **Carolyn Adams**

Date (Start): 1/6/2016
Date (End): 1/6/2016

Project Name: **Phase Two Environmental Site Assessment**
Site: **Part of Lot 4, Concession 3, Parts 1-5, Gloucester, Ontario**
Sector:
Client: **The Builders Warehouse Inc.**

Project Number: **161-06382-00**
 Geographic Coordinates: X = 5032619 mE
 Y = 459397 mN
 Surface Elevation: m ()
 Top of PVC Elevation:

Drilling Company:	Strata Drilling Group
Drilling Equipment:	Geomachine GS100
Drilling Method:	Probe rod
Borehole Diameter:	50 mm
Drilling Fluid:	None
Sampling Method:	

ODOUR
F - Light
M - Medium
P - Persistent

VISUAL
D - Disseminated Product
S - Saturated with Product

SAMPLE TYPE
DC - Diamond Core
SS - Split Spoon
MA - Manual Auger
TR - Trowel
ST - Shelby Tube
TU - DT32 Liner
MC - Macro Core Liner

CHEMICAL ANALYSIS			
PCB	Poly-Chlorinated Biphenyls	MAH	Monocyclic Aromatic Hydrocarbons
BTEX	Benzene, Toluene, Ethylbenzene, Xylene	PAH	Polycyclic Aromatic Hydrocarbons
		$\text{PH}_{\text{C}_{10}-\text{C}_{20}}$	Petroleum Hydrocarbons $\text{C}_{10}-\text{C}_{20}$
Inorg. C.	Inorganic Compounds	PH F1-F4	Petroleum Hydrocarbons F1-F4 ($\text{C}_{10}-\text{C}_{20}$)
Phenol. C.	Phenolic Compounds	Metals	Arsenic, Barium, Cadmium, Chromium, Cobalt, Copper, Lead, Manganese, Molybdenum, Nickel, Silver, Tin, Zinc.
VOC	Volatile Organic Compounds (MAH & CAH)		Leachate Tests (Haz. Waste Reg.)
Diox. & Fur.	Dioxins & Furans	HWR	
CAH	Chlorinated Aliphatic Hydrocarbons		

[illegible]

BOREHOLE DRILLING RECORD : **BH/MW16-5**

Page 1 of 1


Prepared by: **Kathryn Maton**
Reviewed by: **Carolyn Adams**Date (Start): **1/6/2016**
Date (End): **2/6/2016**Project Name: **Phase Two Environmental Site Assessment**
Site: **Part of Lot 4, Concession 3, Parts 1-5, Gloucester, Ontario**
Sector:
Client: **The Builders Warehouse Inc.**Project Number: **161-06382-00**
Geographic Coordinates: X = 5032607 mE
Y = 459421 mN
Surface Elevation: **87.47 m (Relative)**
Top of PVC Elevation:Drilling Company: **Strata Drilling Group**
Drilling Equipment: **Geomachine GS100**
Drilling Method: **Probe rod**
Borehole Diameter: **50 mm**
Drilling Fluid: **Air**
Sampling Method:ODOUR
F - Light
M - Medium
P - Persistent

VISUAL
D - Disseminated Product
S - Saturated with ProductSAMPLE TYPE
DC - Diamond Corer
SS - Split Spoon
MA - Manual Auger
TR - Trowel
ST - Shelby Tube
TU - DT32 Liner
MC - Macro Core LinerCHEMICAL ANALYSIS
PCB Poly-Chlorinated Biphenyls
BTEX Benzene, Toluene, Ethylbenzene, Xylene
Inorg. C. Inorganic Compounds
Phenol. C. Phenolic Compounds
VOC Volatile Organic Compounds (MAH & CAH)
Diox. & Fur. Dioxins & Furans
CAH Chlorinated Aliphatic HydrocarbonsMAH Monocyclic Aromatic Hydrocarbons
PAH Polycyclic Aromatic Hydrocarbons
PH C₁₀-C₅₀ Petroleum Hydrocarbons C₁₀-C₅₀
PH F1-F4 Petroleum Hydrocarbons F1-F4 (C₁₀-C₅₀)
Metals Arsenic, Barium, Cadmium, Chromium, Cobalt, Copper, Lead, Manganese, Molybdenum, Nickel, Silver, Tin, Zinc.
HWR Leachate Tests (Haz. Waste Reg.)

Water Level

Free Phase

Project : 161-08368-00 PHASE TWO ESA - 3636 INNES ROAD.GPJ Type rapport : WSP_EN_WELL-ENVIRONMENTAL Data Template : WSP_TEMPLATE_GEOTECH.GDT 6/10/2016

DEPTH ELEVATION (m)	GEOLOGY / LITHOLOGY		OBSERVATIONS					SAMPLES					MONITORING WELL		REMARKS		
	LITHOLOGY	DESCRIPTION	VAPOR CONC. I - Isobutylene (ppm) H - Hexane (ppm)	ODOUR					SAMPLE TYPE	% RECOVERY	N (Blow/6")	NUMBER	ANALYSIS	DUPLICATE		DIAGRAM	DESCRIPTION
				F	M	P	D	S									
		Ground surface.															
87.47		FILL sand and gravel, brown, dry	H - 0, I - 0						MC	76		BH/MW16-5 1A					
0.23																	
87.24		CLAYEY SILT brown, moist, stiff	H - 0, I - 0									BH/MW16-5 1B	Metals and Inorganics PHCs F2-F4	BH16- 5- 101B			
0.5																	0.5
1.0																	1.0
1.52		SILTY CLAY grey-brown, moist, stiff	H - 0, I - 30						MC	83		BH/MW16-5 2A					1.5
85.95																	2.0
2.0																	2.5
2.5																	3.0
3.0		← becoming wet and soft															3.0
3.05		BEDROCK	H - 0, I - 35									BH/MW16-5 2B	Metals and Inorganics PH _F -F ₄ BTEX PAH				3.5
84.42																	4.0
3.5																	4.5
4.0																	5.0
4.5																	5.0
4.57		End of borehole at 4.57 m.															5.0
82.90																	5.0

← Bentonite

← Sand

← Slotted PVC pipe

SCREEN
Diam.: 51 mm
Open.: 0.25 mm
Length: 3.05 m

WATER
Depth: 2.27 m
Elev.: m
Date: 6/7/2016

Bentonite

Sand

Slotted PVC pipe

SCREEN

Diam.: 51 mm
Open.: 0.25 mm
Length: 3.05 mWATER
Depth: 2.27 m
Elev.: m
Date: 6/7/2016

BOREHOLE DRILLING RECORD : **BH16-6**

Prepared by: **Kathryn Maton**
Reviewed by: **Carolyn Adams**

Date (Start): 1/6/2016
Date (End): 1/6/2016

Project Name: **Phase Two Environmental Site Assessment**
Site: **Part of Lot 4, Concession 3, Parts 1-5, Gloucester, Ontario**
Sector:
Client: **The Builders Warehouse Inc.**

Project Number: **161-06382-00**
 Geographic Coordinates: X = 5032622 mE
 Y = 459430 mN
 Surface Elevation: m ()
 Top of PVC Elevation:

Drilling Company:	Strata Drilling Group
Drilling Equipment:	Geomachine GS100
Drilling Method:	Probe rod
Borehole Diameter:	50 mm
Drilling Fluid:	None
Sampling Method:	

ODOUR
F - Light
M - Medium
P - Persistent

VISUAL
D - Disseminated Product
S - Saturated with Product

SAMPLE TYPE
DC - Diamond Core
SS - Split Spoon
MA - Manual Auger
TR - Trowel
ST - Shelby Tube
TU - DT32 Liner
MC - Macro Core Liner

CHEMICAL ANALYSIS			
PCB	Poly-Chlorinated Biphenyls	MAH	Monocyclic Aromatic Hydrocarbons
BTEX	Benzene, Toluene, Ethylbenzene, Xylene	PAH	Polycyclic Aromatic Hydrocarbons
Inorg. C.	Inorganic Compounds	PH C ₁₂ -C ₅₀	Petroleum Hydrocarbons C ₁₂ -C ₅₀
Phenol. C.	Phenolic Compounds	PH F1-F4	Aromatic Hydrocarbons F1-F4 (C ₁₂ -C ₅₀)
VOC	Volatile Organic Compounds (MAH & CAH)	Metals	Antimony, Barium, Cadmium, Chromium, Cobalt, Copper, Lead, Manganese, Molybdenum, Nickel, Silver, Tin, Zinc.
Diox. & Fur.	Dioxins & Furans	HWR	Leachate Tests (Haz. Waste Reg.)
CAH	Chlorinated Aliphatic Hydrocarbons		

[illegible]

BOREHOLE DRILLING RECORD : **BH16-7**

Prepared by: **Kathryn Maton**
Reviewed by: **Carolyn Adams**

Date (Start): 1/6/2016
Date (End): 1/6/2016

Project Name: **Phase Two Environmental Site Assessment**
Site: **Part of Lot 4, Concession 3, Parts 1-5, Gloucester, Ontario**
Sector:
Client: **The Builders Warehouse Inc.**

Project Number: **161-06382-00**
 Geographic Coordinates: X = 5032572 mE
 Y = 459424 mN
 Surface Elevation: m ()
 Top of PVC Elevation:

Drilling Company:	Strata Drilling Group
Drilling Equipment:	Geomachine GS100
Drilling Method:	Probe rod
Borehole Diameter:	50 mm
Drilling Fluid:	None
Sampling Method:	

ODOUR
F - Light
M - Medium
P - Persistent

VISUAL
D - Disseminated Product
S - Saturated with Product

SAMPLE TYPE
DC - Diamond Core
SS - Split Spoon
MA - Manual Auger
TR - Trowel
ST - Shelby Tube
TU - DT32 Liner
MC - Macro Core Liner

CHEMICAL ANALYSIS			
PCB	Poly-Chlorinated Biphenyls	MAH	Monocyclic Aromatic Hydrocarbons
BTEX	Benzene, Toluene, Ethylbenzene, Xylene	PAH	Polycyclic Aromatic Hydrocarbons
Inorg. C.	Inorganic Compounds	PH C ₁₀ -C ₅₀	Petroleum Hydrocarbons C ₁₀ -C ₅₀
Phenol. C.	Phenolic Compounds	PH F1-F4	Aromatic Hydrocarbons F1-F4 (C ₁₀ -C ₅₀)
VOC	Volatile Organic Compounds (MAH & CAH)	Metals	Antimony, Barium, Cadmium, Chromium, Cobalt, Copper, Lead, Manganese, Molybdenum, Nickel, Silver, Tin, Zinc.
Diox. & Fur.	Dioxins & Furans	HWR	Leachate Tests (Haz. Waste Reg.)
CAH	Chlorinated Aliphatic Hydrocarbons		

 Water Level Free Phase

[illegible]

BOREHOLE DRILLING RECORD : **BH/MW16-8**

Prepared by: **Kathryn Maton**
Reviewed by: **Carolyn Adams**

Date (Start): **1/6/2016**
Date (End): **2/6/2016**

Project Name: **Phase Two Environmental Site Assessment**
Site: **Part of Lot 4, Concession 3, Parts 1-5, Gloucester, Ontario**
Sector:
Client: **The Builders Warehouse Inc.**

Project Number: **161-06382-00**
 Geographic Coordinates: X = 5032569 mE
 Y = 4594449 mN
 Surface Elevation: 86.84 m (*Relative*)
 Top of PVC Elevation:

Drilling Company:	Strata Drilling Group
Drilling Equipment:	Geomachine GS100
Drilling Method:	Probe rod
Borehole Diameter:	50 mm
Drilling Fluid:	Air
Sampling Method:	

ODOUR
F - Light
M - Medium
P - Persistent




VISUAL
D - Disseminated Product
S - Saturated with Product

SAMPLE TYPE
DC - Diamond Corer
SS - Split Spoon
MA - Manual Auger
TR - Trowel
ST - Shelby Tube
TU - DT32 Liner
MC - Macro Core Line

CHEMICAL ANALYSIS	
PCB	Poly-Chlorinated Biphenyls
BTEX	Benzene, Toluene, Ethylbenzene, Xylene
Inorg. C.	Inorganic Compounds
Phenol. C.	Phenolic Compounds
VOC	Volatile Organic Compounds (MAH & CAH)
Diox. & Fur.	Dioxins & Furans
CAH	Chlorinated Aliphatic Hydrocarbons

MAH	Monocyclic Aromatic Hydrocarbons
PAH	Polycyclic Aromatic Hydrocarbons
PH C ₁₀ -C ₅₀	Petroleum Hydrocarbons C ₁₀ -C ₅₀
PH F1-F4	Petroleum Hydrocarbons F1-F4 (C ₁₀ -C ₅₀)
Metals	Arsenic, Barium, Cadmium, Chromium, Cobalt, Copper, Lead, Manganese, Molybdenum, Nickel, Silver, Tin, Zinc.
HWR	Leachate Tests (Haz. Waste Req.)

▽ Water Level ▼ Free Phase

DEPTH ELEVATION (m)	GEOLOGY / LITHOLOGY		OBSERVATIONS					SAMPLES					MONITORING WELL		REMARKS	
	LITHOLOGY	DESCRIPTION	VAPOR CONC. I - Isobutylene (ppm) H - Hexane (ppm)	ODOUR			VISUAL	SAMPLE TYPE	% RECOVERY	N (Blow/ft)	NUMBER	ANALYSIS	DUPLICATE	DIAGRAM		DESCRIPTION
				F	M	P										
		Ground surface.														
86.84 0.20 86.64		TOP SOIL						MC	100							
0.5 1.0 1.5 2.0 2.5 2.44 84.40		CLAYEY SILT brown or grey-brown, moist, stiff	H - 10, I - 0							BH/MW16-8 1	Metals and Inorganics PAH PHF-F ₄ BTEX				← Bentonite	0.5 1.0 1.5 2.0 2.5
3.0 3.05 83.79		SILTY CLAY grey-brown, moist, stiff	H - 5, I - 0					MC	100	BH/MW16-8 2A					← Sand	1.5 2.0 2.5
3.5 4.0 4.11 82.73		SANDY GRAVEL with trace to some silty clay grey-brown, wet, soft	H - 0, I - 0							BH/MW16-8 3A	Metals and Inorganics				← Slotted PVC pipe	2.5 3.0 3.5 4.0
4.5 5.0		End of borehole at 4.11 m.	H - 15, I - 0							BH/MW16-8 3B						4.5 5.0

SCREEN
Diam.: 51 mm
Open.: 0.25 mm
Length: 3.05 m

WATER
Depth: 1.45 m
Elev.: m
Date: 6/7/2016

BOREHOLE DRILLING RECORD : **BH16-9**

Prepared by: **Kathryn Maton**
Reviewed by: **Carolyn Adams**

Date (Start): **2/6/2016**
Date (End): **2/6/2016**

Project Name: **Phase Two Environmental Site Assessment**
Site: **Part of Lot 4, Concession 3, Parts 1-5, Gloucester, Ontario**
Sector:
Client: **The Builders Warehouse Inc.**

Project Number: **161-06382-00**
 Geographic Coordinates: X = 5032512 mE
 Y = 459382 mN
 Surface Elevation: m ()
 Top of PVC Elevation:

Drilling Company:	Strata Drilling Group
Drilling Equipment:	Geomachine GS100
Drilling Method:	Probe rod
Borehole Diameter:	50 mm
Drilling Fluid:	None
Sampling Method:	

ODOUR
F - Light
M - Medium
P - Persistent

VISUAL
D - Disseminated Product
S - Saturated with Product

SAMPLE TYPE
DC - Diamond Core
SS - Split Spoon
MA - Manual Auger
TR - Trowel
ST - Shelby Tube
TU - DT32 Liner
MC - Macro Core Liner

CHEMICAL ANALYSIS	
PCB	Poly-Chlorinated Biphenyls
BTEX	Benzene, Toluene, Ethylbenzene, Xylene
Inorg. C.	Inorganic Compounds
Phenol. C.	Phenolic Compounds
VOC	Volatile Organic Compounds (MAH & CAH)
Diox. & Fur.	Dioxins & Furans
CAH	Chlorinated Aliphatic Hydrocarbons

MAH	Monocyclic Aromatic Hydrocarbons
PAH	Polycyclic Aromatic Hydrocarbons
PH C ₁₀ -C ₅₀	Petroleum Hydrocarbons C ₁₀ -C ₅₀
PH F1-F4	Petroleum Hydrocarbons F1-F4 (C ₁₀ -C ₅₀)
Metals	Arsenic, Barium, Cadmium, Chromium, Cobalt, Copper, Lead, Manganese, Molybdenum, Nickel, Silver, Tin, Zinc.
HWR	Leachate Tests (Haz. Waste Reg.)

[illegible]

BOREHOLE DRILLING RECORD : **BH16-10**

Prepared by: **Kathryn Maton**
Reviewed by: **Carolyn Adams**

Date (Start): **2/6/2016**
Date (End): **2/6/2016**

Project Name: **Phase Two Environmental Site Assessment**
Site: **Part of Lot 4, Concession 3, Parts 1-5, Gloucester, Ontario**
Sector:
Client: **The Builders Warehouse Inc.**

Project Number: **161-06382-00**
Geographic Coordinates: X = 5032473 mE
Y = 4594402 mN
Surface Elevation: m ()
Top of PVC Elevation:

Drilling Company:	Strata Drilling Group
Drilling Equipment:	Geomachine GS100
Drilling Method:	Probe rod
Borehole Diameter:	50 mm
Drilling Fluid:	None
Sampling Method:	

ODOUR
F - Light
M - Medium
P - Persistent

VISUAL
D - Disseminated Product
S - Saturated with Product

SAMPLE TYPE
DC - Diamond Core
SS - Split Spoon
MA - Manual Auger
TR - Trowel
ST - Shelby Tube
TU - DT32 Liner
MC - Macro Core Liner

▼ Free Phase

CHEMICAL ANALYSIS	
PCB	Poly-Chlorinated Biphenyls
BTEX	Benzene, Toluene, Ethylbenzene, Xylene
Inorg. C.	Inorganic Compounds
Phenol. C.	Phenolic Compounds
VOC	Volatile Organic Compounds (MAH & CAH)
Diox. & Fur.	Dioxins & Furans
CAH	Chlorinated Aliphatic Hydrocarbons

MAH	Monocyclic Aromatic Hydrocarbons
PAH	Polycyclic Aromatic Hydrocarbons
PH C ₁₀ -C ₅₀	Petroleum Hydrocarbons C ₁₀ -C ₅₀
PH F1-F4	Petroleum Hydrocarbons F1-F4 (C ₁₀ -C ₅₀)
Metals	Arsenic, Barium, Cadmium, Chromium, Cobalt, Copper, Lead, Manganese, Molybdenum, Nickel, Silver, Tin, Zinc.
HWR	Leachate Tests (Haz. Waste Rec.)

[illegible]

BOREHOLE DRILLING RECORD : BH16-12

Prepared by: **Kathryn Maton**
Reviewed by: **Carolyn Adams**

Date (Start): 2/6/2016
Date (End): 2/6/2016

Project Name: **Phase Two Environmental Site Assessment**
Site: **Part of Lot 4, Concession 3, Parts 1-5, Gloucester, Ontario**
Sector:
Client: **The Builders Warehouse Inc.**

Project Number: **161-06382-00**
Geographic Coordinates: X = 5032334 mE
Y = 459386 mN
Surface Elevation: m ()
Top of PVC Elevation:

Drilling Company:	Strata Drilling Group
Drilling Equipment:	Geomachine GS100
Drilling Method:	Probe rod
Borehole Diameter:	50 mm
Drilling Fluid:	None
Sampling Method:	

ODOUR
F - Light
M - Medium
P - Persistent

VISUAL
D - Disseminated Product
S - Saturated with Product

SAMPLE TYPE
DC - Diamond Core
SS - Split Spoon
MA - Manual Auger
TR - Trowel
ST - Shelby Tube
TU - DT32 Liner
MC - Macro Core Liner

▽ Water Level ▼ Free Phase

CHEMICAL ANALYSIS

PCB	Polychlorinated Biphenyls
BTEX	Benzene, Toluene, Ethylbenzene, Xylene
Inorg. C.	Inorganic Compounds
Phenol. C.	Phenolic Compounds
VOC	Volatile Organic Compounds (MAH & CAH)
Diox. & Fur.	Dioxins & Furans
CAH	Chlorinated Aliphatic Hydrocarbons

MAH	Monocyclic Aromatic Hydrocarbons
PAH	Polycyclic Aromatic Hydrocarbons
PH C ₁₀ -C ₅₀	Petroleum Hydrocarbons C ₁₀ -C ₅₀
PH F1-F4	Petroleum Hydrocarbons F1-F4 (C ₁₀ -C ₅₀)
Metals	Arsenic, Barium, Cadmium, Chromium, Cobalt, Copper, Lead, Manganese, Molybdenum, Nickel, Silver, Tin, Zinc.
HWR	Leachate Tests (Haz. Waste Reg.)

[illegible]

BOREHOLE DRILLING RECORD : **BH16-13**

Prepared by: **Kathryn Maton**
Reviewed by: **Carolyn Adams**

Date (Start): 2/6/2016
Date (End): 2/6/2016

Project Name: **Phase Two Environmental Site Assessment**
Site: **Part of Lot 4, Concession 3, Parts 1-5, Gloucester, Ontario**
Sector:
Client: **The Builders Warehouse Inc.**

Project Number: **161-06382-00**
Geographic Coordinates: X = 5032385 mE
Y = 459515 mN
Surface Elevation: m ()
Top of PVC Elevation:

Drilling Company:	Strata Drilling Group
Drilling Equipment:	Geomachine GS100
Drilling Method:	Probe rod
Borehole Diameter:	50 mm
Drilling Fluid:	None
Sampling Method:	

ODOUR
F - Light
M - Medium
P - Persistent

VISUAL
D - Disseminated Product
S - Saturated with Product

SAMPLE TYPE
DC - Diamond Core
SS - Split Spoon
MA - Manual Auger
TR - Trowel
ST - Shelby Tube
TU - DT32 Liner
MC - Macro Core Liner

CHEMICAL ANALYSIS

PCB	Polychlorinated Biphenyls
BTEX	Benzene, Toluene, Ethylbenzene, Xylene
Inorg. C.	Inorganic Compounds
Phenol. C.	Phenolic Compounds
VOC	Volatile Organic Compounds (MAH & CAH)
Diox. & Fur.	Dioxins & Furans
CAH	Chlorinated Aliphatic Hydrocarbons

MAH	Monocyclic Aromatic Hydrocarbons
PAH	Polycyclic Aromatic Hydrocarbons
PH C ₁₀ -C ₅₀	Petroleum Hydrocarbons C ₁₀ -C ₅₀
PH F1-F4	Petroleum Hydrocarbons F1-F4 (C ₁₀ -C ₅₀)
Metals	Arsenic, Barium, Cadmium, Chromium, Cobalt, Copper, Lead, Manganese, Molybdenum, Nickel, Silver, Tin, Zinc.
HWR	Leachate Tests (Haz. Waste Req.)

▽ Water Level ▼ Free Phase

[illegible]

Préparé par : Catherine Tardy Laporte
Vérifié par : Annie GauthierDate début : 2013-06-27
Date fin : 2013-06-27

Nom du projet : Évaluation Environnementale de site (ÉES) Phase II

Site : Site # 38 Orléans

Secteur : 3636-3646, chemin Innes, Orléans (Ontario)

Client : La Coop fédérée

Numéro de projet : 131-13558-00

Coordonnées géographiques : X = 75.5191369842 °O

Y = 45.4458564224 °N

Élévation surface : 90.69 m ()

Élévation marginale :

Entrepreneur forage : Marathon Drilling Co. Ltd.

Type de foreuse : CME 75

Équipement de forage : Tarière tige pleine /

Diamètre du forage : 200 mm

Fluide forage : Aucun

Équip. d'échantillonnage : Carottier fendu

ODEUR

F - Faible odeur

M - Odeur moyenne

P - Odeur persistante

VISUEL

D - Produit disséminé

S - Sol saturé de produit

TYPE D'ÉCHANTILLON

CD - Carottier à diamants

CF - Cuillère fendue

PS - Échantillonneur à piston

TC - Tube creux

TM - Tarière manuelle

TR - Truelle

TS - Tube Shelby

TT - Tube transparent

Niveau d'eau

Phase libre

ANALYSES CHIMIQUES

BPC Biphényles polychlorés

BTEX Benzène, toluène, éthylbenzène, xylène

COT Carbone organique total

C. Inorg. Autres composés inorganiques (cyanure, fluorure, bromure, soufre total)

C. Phénol. Composés phénoliques

COV Hydrocarbures HAM et HAC

Diox. & Fur. Dioxines et furanes

HAC

HAM

HAP

HP C₁₀-C₂₀

HP F1-F4

Mercure

Métaux

RMD

Hydrocarb. aliphatiques chlorés

Hydrocarbures aromatiques monocycliques

Hydrocarbures aromatiques polycycliques

Hydrocarbures pétroliers C₁₀-C₂₀Hydrocarb. pétrol. F1-F4 (C₁₀-C₂₀)

Mercure

Argent, arsenic, baryum, cadmium, cobalt, chrome, cuivre, étain, manganèse, molybdène, nickel, plomb, sélénium, zinc,

Lixiviation (mat. dangereuses)

PROFONDEUR ÉLÉVATION (m)		STRATIGRAPHIE	GÉOLOGIE / STRATIGRAPHIE DESCRIPTION	OBSERVATIONS CONC. VAPEUR (ppm OU % LIE)	ODEUR				VISUEL	TYPE ÉCHANTILLON	% RÉCUPÉRATION	N (Coups/6")	NUMÉRO	ANALYSES	DUPLICATA	DIAGRAMME	DESCRIPTION	REMARQUES	
					F	M	P	D											S
			Surface du terrain.																
0.10 90.59			Asphalte.																
			Remblai : Gravier sableux sec.																
0.50 90.19			Sol naturel : Gravier sableux.																
1.06 89.63			Fin du forage à 1.06 m de profondeur.																
1.5																			
2.0																			
2.5																			
3.0																			
3.5																			
4.0																			



Préparé par : Catherine Tardy Laporte
Vérifié par : Annie Gauthier

Date début : 2013-06-27
Date fin : 2013-06-27

Nom du projet : Évaluation Environnementale de site (ÉES) Phase II

Site : Site # 38 Orléans

Secteur : 3636-3646, chemin Innes, Orléans (Ontario)

Client : La Coop fédérée

Numéro de projet :

131-13558-00

Coordonnées géographiques : X = 75.5189257577 °O

Y = 45.445930007 °N

Élévation surface :

90.64 m ()

Élévation margelle :

Entrepreneur forage : Marathon Drilling Co. Ltd.

Type de foreuse : CME 75

Équipement de forage : Tarière tige pleine /

Diamètre du forage : 200 mm

Fluide forage : Aucun

Équip. d'échantillonnage : Carottier fendu

ODEUR

F - Faible odeur

M - Odeur moyenne

P - Odeur persistante

VISUEL

D - Produit disséminé

S - Sol saturé de produit

TYPE D'ÉCHANTILLON

CD - Carottier à diamants

CF - Cuillère fendue

PS - Échantillonneur à piston

TC - Tube creux

TM - Tarière manuelle

TR - Truelle

TS - Tube Shelby

TT - Tube transparent

ANALYSES CHIMIQUES

BPC Biphényles polychlorés

BTEX Benzène, toluène, éthylbenzène, xylène

COT Carbone organique total

C. Inorg. Autres composés inorganiques (cyanure, fluorure, bromure, soufre total)

C. Phénol. Composés phénoliques

COV Hydrocarbures HAM et HAC

Diox. & Fur. Dioxines et furanes

HAC

HAM

HAP

HP C₁₀-C₂₀

HP F1-F4

Mercure

Métaux

RMD

Hydrocarb. aliphatiques chlorés

Hydrocarbures aromatiques monocycliques

Hydrocarbures aromatiques polycycliques

Hydrocarbures pétroliers C₁₀-C₂₀

Hydrocarb. pétrol. F1-F4 (C₁₀-C₂₀)

Mercure

Argent, arsenic, baryum, cadmium, cobalt, chrome, cuivre, étain, manganèse, molybdène, nickel, plomb, sélénium, zinc.



Lixiviation (mat. dangereuses)

▽ Niveau d'eau

▽ Phase libre

PROFONDEUR ÉLÉVATION (m)		STRATIGRAPHIE	GÉOLOGIE / STRATIGRAPHIE DESCRIPTION	OBSERVATIONS CONC. VAPEUR (ppm OU % LIE)	ODEUR					VISUEL	ÉCHANTILLONS					PUITS D'OBSERVATION			REMARQUES
					F	M	P	D	S		TYPE ÉCHANTILLON	% RÉCUPÉRATION	N (Coupes/6")	NUMÉRO	ANALYSES	DUPLICATA	DIAGRAMME	DESCRIPTION	
			Surface du terrain.																
0.10			Asphalte.																
90.54			Remblai : Gravier sableux brun gris sec.																
0.45																			
0.55			Sol naturel : Sable silteux noir.																
90.09																			
			Sol naturel : Sable silteux brun sec.																
0.75																			
89.89			Sol naturel : Sable graveleux.																
1.21			Fin du forage à 1.21 m de profondeur.																
89.43																			

Préparé par : Catherine Tardy Laporte
Vérifié par : Annie GauthierDate début : 2013-06-27
Date fin : 2013-06-27Nom du projet : Évaluation Environnementale de site (ÉES) Phase II
Site : Site # 38 Orléans
Secteur : 3636-3646, chemin Innes, Orléans (Ontario)
Client : La Coop fédéréeNuméro de projet : 131-13558-00
Coordonnées géographiques : X = 75.5196137735 °O
Y = 45.4456012321 °N
Élévation surface : 90.39 m ()
Élévation margelle :Entrepreneur forage : Marathon Drilling Co. Ltd.
Type de foreuse : CME 75
Équipement de forage : Tarière tige pleine /
Diamètre du forage : 200 mm
Fluide forage : Aucun
Équip. d'échantillonnage : Carottier fenduODEUR
F - Faible odeur
M - Odeur moyenne
P - Odeur persistante
VISUEL
D - Produit disséminé
S - Sol saturé de produit
TYPE D'ÉCHANTILLON
CD - Carottier à diamants
CF - Cuillère fendue
PS - Échantillonneur à piston
TC - Tube creux
TM - Tarière manuelle
TR - Truelle
TS - Tube Shelby
TT - Tube transparent
Niveau d'eau
Phase libreANALYSES CHIMIQUES
BPC Biphényles polychlorés
BTEX Benzène, toluène, éthylbenzène, xylène
COT Carbone organique total
C. Inorg. Autres composés inorganiques (cyanure, fluorure, bromure, soufre total)
C. Phénol. Composés phénoliques
COV Hydrocarbures HAM et HAC
Diox. & Fur. Dioxines et furanes
HAC Hydrocarb. aliphatiques chlorés
HAM Hydrocarbures aromatiques monocycliques
HAP Hydrocarbures aromatiques polycycliques
HP C₁₀-C₂₀ Hydrocarbures pétroliers C₁₀-C₂₀
HP F1-F4 Hydrocarb. pétrol. F1-F4 (C₁₀-C₂₀)
Mercure Mercure
Métaux Argent, arsenic, baryum, cadmium, cobalt, chrome, cuivre, étain, manganèse, molybdène, nickel, plomb, sélénium, zinc.
RMD Lixiviation (mat. dangereuses)

PROFONDEUR ÉLÉVATION (m)	STRATIGRAPHIE	GÉOLOGIE / STRATIGRAPHIE DESCRIPTION	CONC. VAPEUR (ppm OU % LIE)	OBSERVATIONS					ÉCHANTILLONS					PUITS D'OBSERVATION		REMARQUES
				ODEUR	VISUEL	TYPE ÉCHANTILLON	% RÉCUPÉRATION	N (Coups/6")	NUMÉRO	ANALYSES	DUPLICATA	DIAGRAMME	DESCRIPTION			
														F	M	
		Surface du terrain.														
0.10 90.29		Asphalte.														
0.30 90.09		Remblai : Gravier sableux sec.														
0.50 89.89		Sol naturel : Sable graveleux gris.					CF	49	12	F-03 (0.30-0.50)	HP F1-F4 HAP BTEX Métaux (R153)					0.5
		Sol naturel : Sable silteux avec trace de gravier.								F-03 (0.50-0.91)	HP F1-F4 HAP BTEX Métaux (R153)					
0.91 89.48		Sol naturel : Sable silteux.					CF	33		F-03 (0.91-1.01) F-03 (1.01-1.11)	HP F1-F4 HAP BTEX Métaux (R153)					1.0
1.52 88.87		Fin du forage à 1.52 m de profondeur.														1.5
2.0																2.0
2.5																2.5
3.0																3.0
3.5																3.5
4.0																4.0



Page 1 de 1

Date début : 2013-06-27
Date fin : 2013-06-27

Numéro de projet : **131-13558-00**
 Coordonnées géographiques : X = 75.5201167458 °O
 Y = 45.4451939281 °N
 Élévation surface : 89.29 m (l)
 Élévation marquée :

ODEUR F - Faible odeur M - Odeur moyenne P - Odeur persistante VISUEL D - Produit disséminé S - Sol saturé de produit	TYPE D'ÉCHANTILLON CD - Carotier à diamants CF - Cuillère fendue PS - Échantillonneur à piston TC - Tube creux TM - Tarière manuelle TR - Truelle TS - Tube Shelby TT - Tube transparent
--	---

ANALYSES CHIMIQUES	HAC	Hydrocarb. aliphatiques chlorés
BPC	HAM	Hydrocarbures aromatiques
BTEX	HAP	monocycliques
		Hydrocarbures aromatiques
		polycycliques
COT	Carbone organique total	
C. Inorg.	HC $C_{10}-C_{50}$	Hydrocarbures pétroliers $C_{10}-C_{50}$
	HC F1-F4	Hydrocarb. pétrol. F1-F4 ($C_{10}-C_{50}$)
	(cyanure, fluorure, bromure, soufre total)	
	Mercurie	Mercurie
C. Phénol.	Métaux	Argent, arsenic, baryum, cadmium
COV	Hydrocarbures HAM et HAC	cobalt, chrome, cuivre, étain,
Diox. & Fur.	Dioxines et furanes	manganèse, molybdène, nickel,
		plomb, sélénium, zinc.
	RMD	Lixiviation (mat. dangereuses)

		GÉOLOGIE / STRATIGRAPHIE		OBSERVATIONS					ÉCHANTILLONS					PUITS D'OBSERVATION			
PROFONDEUR ÉLÉVATION (m)	STRATIGRAPHIE	DESCRIPTION	CONC. VAPEUR (ppm OU % LIE)	ODEUR				VISUEL	TYPE ÉCHANTILLON	% RECUPÉRATION	N (Coups/6")	NUMÉRO	ANALYSES	DUPLICATA	DIAGRAMME	DESCRIPTION	REMARQUES
				F	M	P	D										
		Surface du terrain.															
89.29 0.20 89.09		Remblai : Sable graveleux gris et blanc.							CF	74	85 55 30 18	F-04 (0.00-0.20)					0.5
89.09		Remblai : Gravier sableux saturé											F-04 (0.20-0.61)				
0.5 0.61 88.68		Sol naturel : Argile silteuse brune grise.							CF	90	1 1 2 6	F-04 (0.61-1.22)	HP F1-F4 HAP BTEX			1.0	
1.22 88.07			Fin du forage à 1.22 m de profondeur.														Refus à 1.22 m sur bloc ou roc.
1.5																	1.5
2.0																	2.0
2.5																	2.5
3.0																	3.0
3.5																	3.5
4.0																	4.0



Préparé par : Catherine Tardy Laporte
Vérifié par : Annie Gauthier

Date début : 2013-06-27
Date fin : 2013-06-27

Nom du projet : Évaluation Environnementale de site (ÉES) Phase II

Site : Site # 38 Orléans

Secteur : 3636-3646, chemin Innes, Orléans (Ontario)

Client : La Coop fédérée

Numéro de projet :

131-13558-00

Coordonnées géographiques : X = 75.5198284892 °O

Y = 45.4453512328 °N

Élévation surface :

89.21 m ()

Élévation margelle :

Entrepreneur forage : Marathon Drilling Co. Ltd.

Type de foreuse : CME 75

Équipement de forage : Tarière tige pleine /

Diamètre du forage : 200 mm

Fluide forage : Aucun

Équip. d'échantillonnage : Carottier fendu

ODEUR

F - Faible odeur

M - Odeur moyenne

P - Odeur persistante

VISUEL

D - Produit disséminé

S - Sol saturé de produit

TYPE D'ÉCHANTILLON

CD - Carottier à diamants

CF - Cuillère fendue

PS - Échantillonneur à piston

TC - Tube creux

TM - Tarière manuelle

TR - Truelle

TS - Tube Shelby

TT - Tube transparent

ANALYSES CHIMIQUES

BPC Biphényles polychlorés

BTEX Benzène, toluène, éthylbenzène, xylène

COT Carbone organique total

C. Inorg. Autres composés inorganiques (cyanure, fluorure, bromure, soufre total)

C. Phénol. Composés phénoliques

COV Hydrocarbures HAM et HAC

Diox. & Fur. Dioxines et furanes

HAC

HAM

HAP

HP C₁₀-C₂₀

HP F1-F4

Mercur

Métaux

RMD

Hydrocarb. aliphatiques chlorés

Hydrocarbures aromatiques monocycliques

Hydrocarbures aromatiques polycycliques

Hydrocarbures pétroliers C₁₀-C₂₀


Hydrocarb. pétrol. F1-F4 (C₁₀-C₂₀)

Argent, arsenic, baryum, cadmium, cobalt, chrome, cuivre, étain, manganèse, molybdène, nickel, plomb, sélénium, zinc,

Lixiviation (mat. dangereuses)

▽ Niveau d'eau

▽ Phase libre

PROFONDEUR ÉLÉVATION (m)		STRATIGRAPHIE	GÉOLOGIE / STRATIGRAPHIE DESCRIPTION	OBSERVATIONS CONC. VAPEUR (ppm OU % LIE)	OBSERVATIONS					ÉCHANTILLONS					PUITS D'OBSERVATION			REMARQUES
					ODEUR					VISUEL TYPE ÉCHANTILLON	% RÉCUPÉRATION	N (Coups/6")	NUMÉRO	ANALYSES	DUPLICATA	DIAGRAMME	DESCRIPTION	
					F	M	P	D	S									
			Surface du terrain.															
89.21			Remblai : Sable et gravier sec							CF	66	58 21 18	F-05 (0.00-0.20)					
0.20																		
89.01			Sol naturel : Gravier noir et saturé avec un peu de sable.										F-05 (0.20-0.61)					
0.5																		0.5
0.61																		
88.60			Sol naturel : Argile silteuse brune-beige et humide.							CF	100	1 1 6	F-05 (0.61-1.22)					
1.0																		1.0
										CF	100		F-05 (1.22-1.32) F-05 (1.32-1.83)	HP F1-F4 HAP BTEX Métaux (R153)				1.5
1.83																		
87.38			Sol naturel : Argile silteuse grise humide.							CF	82	3 22 8	F-05 (1.83-2.10)					2.0
2.10																		
87.11			Sol naturel : Gravier sableux gris.										F-05 (2.10-2.34)					
2.34																		
86.87			Fin du forage à 2.34 m de profondeur.															
2.5			Roc atteint															2.5
																		3.0
																		3.5
																		4.0



Préparé par : Catherine Tardy Laporte
Vérifié par : Annie Gauthier

Date début : 2013-06-27
Date fin : 2013-06-27

Nom du projet : Évaluation Environnementale de site (ÉES) Phase II

Site : Site # 38 Orléans

Secteur : 3636-3646, chemin Innes, Orléans (Ontario)

Client : La Coop fédérée

Numéro de projet :

131-13558-00

Coordonnées géographiques : X = 75.5200570318 °O

Y = 45.4478309683 °N

Élévation surface :

89.22 m ()

Élévation margelle :

Entrepreneur forage : Marathon Drilling Co. Ltd.

Type de foreuse : CME 75

Équipement de forage : Tarière tige pleine /

Diamètre du forage : 200 mm

Fluide forage : Aucun

Équip. d'échantillonnage : Carottier fendu

ODEUR

F - Faible odeur

M - Odeur moyenne

P - Odeur persistante

VISUEL

D - Produit disséminé

S - Sol saturé de produit

TYPE D'ÉCHANTILLON

CD - Carottier à diamants

CF - Cuillère fendue

PS - Échantillonneur à piston

TC - Tube creux

TM - Tarière manuelle

TR - Truelle

TS - Tube Shelby

TT - Tube transparent

ANALYSES CHIMIQUES

BPC Biphényles polychlorés

BTEX Benzène, toluène, éthylbenzène, xylène

COT Carbone organique total

C. Inorg. Autres composés inorganiques (cyanure, fluorure, bromure, soufre total)

C. Phénol. Composés phénoliques

COV Hydrocarbures HAM et HAC

Diox. & Fur. Dioxines et furanes

HAC

HAM

HAP

HP C₁₀-C₅₀

HP F1-F4

Mercure

Métaux

RMD

Hydrocarb. aliphatiques chlorés

Hydrocarbures aromatiques monocycliques

Hydrocarbures aromatiques polycycliques

Hydrocarbures pétroliers C₁₀-C₅₀

Hydrocarb. pétrol. F1-F4 (C₁₀-C₅₀)

Mercure

Argent, arsenic, baryum, cadmium, cobalt, chrome, cuivre, étain, manganèse, molybdène, nickel, plomb, sélénium, zinc,

Lixiviation (mat. dangereuses)

▽ Niveau d'eau

▽ Phase libre

RMD

Lixiviation (mat. dangereuses)

PROFONDEUR ÉLÉVATION (m)		STRATIGRAPHIE		GÉOLOGIE / STRATIGRAPHIE		CONC. VAPEUR (ppm OU % LIE)	OBSERVATIONS					ÉCHANTILLONS					PUITS D'OBSERVATION			REMARQUES
							ODEUR	VISUEL	TYPE ÉCHANTILLON	% RÉCUPÉRATION	N (Coups/6")	NUMÉRO	ANALYSES	DUPLICATA	DIAGRAMME	DESCRIPTION				
																	F	M	P	
				Surface du terrain.																
89.22				Remblai : Sable graveleux gris-brun et sec.						CF	100	1 3 4 7	F-06 (0.00-0.61)	HP F1-F4 HAP BTEX						
0.61																				0.5
88.61											CF	100	1 4 4 6	F-06 (0.61-1.22)						1.0
																				1.5
1.0																				
										CF	49	56 36 19 10	F-06 (1.22-1.83)							1.5
87.70																				
1.83																				
				Fin du forage à 1.52 m de profondeur.																2.0
2.0																				2.0
2.5																				2.5
3.0																				3.0
3.5																				3.5
4.0																				4.0



Préparé par : **Catherine Tardy Laporte**
Vérifié par : **Annie Gauthier**

Date début : **2013-06-27**
Date fin : **2013-06-27**

Nom du projet : **Évaluation Environnementale de site (ÉES) Phase II**
Site : **Site # 38 Orléans**
Secteur : **3636-3646, chemin Innes, Orléans (Ontario)**
Client : **La Coop fédérée**

Numéro de projet : **131-13558-00**
Coordonnées géographiques : **X = 75.5199577902 °O**
Y = 45.4476971365 °N
Élévation surface : **89.47 m ()**
Élévation margelle :

Entrepreneur forage : **Marathon Drilling Co. Ltd.**
Type de foreuse : **CME 75**
Équipement de forage : **Tarière tige pleine /**
Diamètre du forage : **200 mm**
Fluide forage : **Aucun**
Équip. d'échantillonnage : **Carottier fendu**

ODEUR
F - Faible odeur
M - Odeur moyenne
P - Odeur persistante
VISUEL
D - Produit disséminé
S - Sol saturé de produit

TYPE D'ÉCHANTILLON
CD - Carottier à diamants
CF - Cuillère fendue
PS - Échantillonneur à piston
TC - Tube creux
TM - Tarière manuelle
TR - Truelle
TS - Tube Shelby
TT - Tube transparent

▽ Niveau d'eau ▼ Phase libre

ANALYSES CHIMIQUES
BPC Biphényles polychlorés
BTEX Benzène, toluène, éthylbenzène, xylène
COT Carbone organique total
C. Inorg. Autres composés inorganiques (cyanure, fluorure, bromure, soufre total)
C. Phénol. Composés phénoliques
COV Hydrocarbures HAM et HAC
Diox. & Fur. Dioxines et furanes

HAC Hydrocarb. aliphatiques chlorés
HAM Hydrocarbures aromatiques monocycliques
HAP Hydrocarbures aromatiques polycycliques
HP C₁₀-C₂₀ Hydrocarbures pétroliers C₁₀-C₂₀
HP F1-F4 Hydrocarb. pétrol. F1-F4 (C₁₀-C₂₀)
Mercure Mercure
Métaux Argent, arsenic, baryum, cadmium, cobalt, chrome, cuivre, étain, manganèse, molybdène, nickel, plomb, sélénium, zinc
RMD Lixiviation (mat. dangereuses)

PROFONDEUR ÉLEVATION (m)		STRATIGRAPHIE	GÉOLOGIE / STRATIGRAPHIE DESCRIPTION	OBSERVATIONS					ÉCHANTILLONS				PUITS D'OBSERVATION			REMARQUES		
				CONC. VAPEUR (ppm ou % LIE)	ODEUR				VISUEL	TYPE ÉCHANTILLON	% RÉCUPÉRATION	N (Coups/6")	NUMÉRO	ANALYSES	DUPLICATA		DIAGRAMME	DESCRIPTION
					F	M	P	D										
			Surface du terrain.															
89.47			Remblai : Sable graveleux gris-blanc et sec.						CF	57	110 54 13 11	F-07 (0.00-0.50)						
0.50																		
0.60			Remblai : Sable graveleux gris-blanc et humide.						CF	90	1 3 4 6	F-07 (0.50-0.61) F-07 (0.61-1.22)	HP F1-F4 HAP BTEX					
88.87																		
			Sol naturel : Argile silteuse.															
1.0																		
									CF			F-07 (1.22-1.83)						
1.5																		
87.95																		
1.83																		
			Fin du forage à 1.52 m de profondeur.															
2.0																		
2.5																		
3.0																		
3.5																		
4.0																		

Préparé par : Catherine Tardy Laporte
Vérifié par : Annie GauthierDate début : 2013-06-27
Date fin : 2013-06-27

Nom du projet : Évaluation Environnementale de site (ÉES) Phase II

Site : Site # 38 Orléans

Secteur : 3636-3646, chemin Innes, Orléans (Ontario)

Client : La Coop fédérée

Numéro de projet : 131-13558-00

Coordonnées géographiques : X = 75.5196453839 °O

Y = 45.4472729549 °N

Élévation surface : 89.2 m ()

Élévation margelle :

Entrepreneur forage : Marathon Drilling Co. Ltd.

Type de foreuse : CME 75

Équipement de forage : Tarière tige pleine /

Diamètre du forage : 200 mm

Fluide forage : Aucun

Équip. d'échantillonnage :

ODEUR

F - Faible odeur

M - Odeur moyenne

P - Odeur persistante

VISUEL

D - Produit disséminé

S - Sol saturé de produit

TYPE D'ÉCHANTILLON

CD - Carottier à diamants

CF - Cuillère fendue

PS - Échantillonneur à piston

TC - Tube creux

TM - Tarière manuelle

TR - Truelle

TS - Tube Shelby

TT - Tube transparent

Niveau d'eau

Phase libre

ANALYSES CHIMIQUES

BPC Biphényles polychlorés

BTX Benzène, toluène, éthylbenzène, xylène

COT Carbone organique total

C. Inorg. Autres composés inorganiques (cyanure, fluorure, bromure, soufre total)

C. Phénol. Composés phénoliques

COV Hydrocarbures HAM et HAC

Diox. & Fur. Dioxines et furanes

HAC

HAM

HAP

HP C₁₀-C₂₀

HP F1-F4

Mercure

Métaux

RMD

Hydrocarb. aliphatiques chlorés

Hydrocarbures aromatiques monocycliques


Hydrocarbures aromatiques polycycliques

Hydrocarbures pétroliers C₁₀-C₂₀Hydrocarb. pétrol. F1-F4 (C₁₀-C₂₀)

Mercure

Argent, arsenic, baryum, cadmium, cobalt, chrome, cuivre, étain, manganèse, molybdène, nickel, plomb, sélénium, zinc.

Lixiviation (mat. dangereuses)

PROFONDEUR ÉLÉVATION (m)		STRATIGRAPHIE		GÉOLOGIE / STRATIGRAPHIE	DESCRIPTION	CONC. VAPEUR (ppm OU % LIE)	OBSERVATIONS					ÉCHANTILLONS					PUITS D'OBSERVATION					REMARQUES
							ODEUR		VISUEL			TYPE ÉCHANTILLON	% RÉCUPÉRATION	N (Coups/6")	NUMÉRO	ANALYSES	DUPLICATA	DIAGRAMME	DESCRIPTION			
							F	M	P	D	S											
					Surface du terrain.																	
0.10 89.10				Remblai : Argile graveleuse.						CF	41	2 11 8 22			HP F1-F4 HAP BTX							
					Remblai : Sable graveleux gris.																	
0.5 0.61 88.59				Fin du forage à 0.61 m de profondeur.																	Refus à 0.61 m sur bloc ou roc.	
1.0																						
1.5																						
2.0																						
2.5																						
3.0																						
3.5																						
4.0																						



GENIVAR

RAPPORT DE FORAGE : F-09

Page 1 de 1

Préparé par : **Catherine Tardy Laporte**
Vérifié par : **Annie Gauthier**

Date début : **2013-06-27**
Date fin : **2013-06-27**

Nom du projet : **Évaluation Environnementale de site (ÉES) Phase II**
Site : **Site # 38 Orléans**
Secteur : **3636-3646, chemin Innes, Orléans (Ontario)**
Client : **La Coop fédérée**

Numéro de projet : **131-13558-00**
Coordonnées géographiques : **X = 75.5190143537 °O**
Y = 45.4460829513 °N
Élévation surface : **89.71 m ()**
Élévation margelle :

Entrepreneur forage : **Marathon Drilling Co. Ltd.**
Type de foreuse : **CME 75**
Équipement de forage : **Tarière tige pleine /**
Diamètre du forage : **200 mm**
Fluide forage : **Aucun**
Équip. d'échantillonnage :

ODEUR
F - Faible odeur
M - Odeur moyenne
P - Odeur persistante
VISUEL
D - Produit disséminé
S - Sol saturé de produit

TYPE D'ÉCHANTILLON
CD - Carottier à diamants
CF - Cuillère fendue
PS - Échantillonneur à piston
TC - Tube creux
TM - Tarière manuelle
TR - Truelle
TS - Tube Shelby
TT - Tube transparent

ANALYSES CHIMIQUES
BPC Biphényles polychlorés
BTEX Benzène, toluène, éthylbenzène, xylène
COT Carbone organique total
C. Inorg. Autres composés inorganiques (cyanure, fluorure, bromure, soufre total)
C. Phénol. Composés phénoliques
COV Hydrocarbures HAM et HAC
Diox. & Fur. Dioxines et furanes

HAC Hydrocarb. aliphatiques chlorés
HAM Hydrocarbures aromatiques monocycliques
HAP Hydrocarbures aromatiques polycycliques
HP C₁₀-C₅₀ Hydrocarbures pétroliers C₁₀-C₅₀
HP F1-F4 Hydrocarb. pétrol. F1-F4 (C₁₀-C₅₀)
Mercure Mercure
Métaux Argent, arsenic, baryum, cadmium, cobalt, chrome, cuivre, étain, manganèse, molybdène, nickel, plomb, sélénium, zinc
RMD Lixiviation (mat. dangereuses)

▽ Niveau d'eau

▽ Phase libre

PROFONDEUR ÉLÉVATION (m)		GÉOLOGIE / STRATIGRAPHIE		OBSERVATIONS					ÉCHANTILLONS					PUITS D'OBSERVATION			REMARQUES	
		STRATIGRAPHIE	DESCRIPTION	CONC. VAPEUR (ppm OU % LIE)	ODEUR				VISUEL	TYPE ÉCHANTILLON	% RÉCUPÉRATION	N (Coups/6")	NUMÉRO	ANALYSES	DUPLICATA	DIAGRAMME		DESCRIPTION
					F	M	P	D										
			Surface du terrain.															
89.71			Remblai : Sable et gravier. Gris blanc sec devenant humide.							CF	74	64 66 24 16		HP F1-F4 HAP BTEX	DUP7			
0.61																		
89.10																		
			Sol naturel : Argile silteuse avec un peu de sable humide.							CF	25	1 2 3 4						
1.0																		
1.5																		
88.19																		
1.83																		
			Fin du forage à 1.52 m de profondeur.															
2.0																		
2.5																		
3.0																		
3.5																		
4.0																		

Préparé par : Catherine Tardy Laporte
Vérifié par : Annie GauthierDate début : 2013-06-27
Date fin : 2013-06-27

Nom du projet : Évaluation Environnementale de site (ÉES) Phase II

Site : Site # 38 Orléans

Secteur : 3636-3646, chemin Innes, Orléans (Ontario)

Client : La Coop fédérée

Numéro de projet : 131-13558-00

Coordonnées géographiques : X = 75.5189110706 °O

Y = 45.446095328 °N

Élévation surface : 89.99 m ()

Élévation margelle : 89.99 m ()

Entrepreneur forage : Marathon Drilling Co. Ltd.

Type de foreuse : CME 75

Équipement de forage : Tarière tige pleine /

Diamètre du forage : 200 mm

Fluide forage : Aucun

Équip. d'échantillonnage : Carottier fendu

ODEUR

F - Faible odeur

M - Odeur moyenne

P - Odeur persistante

VISUEL

D - Produit disséminé

S - Sol saturé de produit

TYPE D'ÉCHANTILLON

CD - Carottier à diamants

CF - Cuillère fendue

PS - Échantillonneur à piston

TC - Tube creux

TM - Tarière manuelle

TR - Truelle

TS - Tube Shelby

TT - Tube transparent

ANALYSES CHIMIQUES

BPC

Biphényles polychlorés

BTX

Benzène, toluène, éthylbenzène, xylène

COT

Carbone organique total

C. Inorg.

Autres composés inorganiques (cyanure, fluorure, bromure, soufre total)

C. Phénol.

Composés phénoliques

COV

Hydrocarbures HAM et HAC

Diox. & Fur.

Dioxines et furanes

HAC

HAM

HAP

HP C₁₀-C₂₀

HP F1-F4

Mercure

Métaux

RMD

Lixiviation (mat. dangereuses)

Hydrocarb. aliphatiques chlorés

Hydrocarbures aromatiques monocycliques

Hydrocarbures aromatiques polycycliques

Hydrocarbures pétroliers C₁₀-C₂₀Hydrocarb. pétrol. F1-F4 (C₁₀-C₂₀)

Mercure

Argent, arsenic, baryum, cadmium, cobalt, chrome, cuivre, étain, manganèse, molybdène, nickel, plomb, sélénium, zinc.

Niveau d'eau

Phase libre

PROFONDEUR ÉLÉVATION (m)		STRATIGRAPHIE		GÉOLOGIE / STRATIGRAPHIE	DESCRIPTION	CONC. VAPEUR (ppm OU % LIE)	OBSERVATIONS					ÉCHANTILLONS					PUITS D'OBSERVATION					REMARQUES
												TYPE ÉCHANTILLON	% RÉCUPÉRATION	N (Coups/6")	NUMÉRO	ANALYSES	DUPLICATA	DIAGRAMME	DESCRIPTION			
																				ODEUR	VISUEL	
								F	M	P	D	S										
				Surface du terrain.																		
89.99				Remblai : Sable graveleux gris avec trace d'oxydation.									CF	57	60 22 55 50	PO-01 (0.00-0.61)						
0.61				Sol naturel : Argile silteuse brune.									CF	90	2 0 0 0 0	PO-01 (0.61-0.86)	HP F1-F4 HAP BTEX Métaux (R153)					
0.86				Sol naturel : Sable silteux humide.												PO-01 (0.86-1.22)						
89.13				Sol naturel : Sable silteux humide.																		
1.22				Sol naturel : Argile silteuse grise et humide.									CF	100	2 2 4 6	PO-01 (1.22-1.83)						
88.77				Sol naturel : Argile silteuse grise et humide.																		
1.83				Fin du forage à 2.08 m de profondeur.																		
87.91				Fin du forage à 2.08 m de profondeur.																		
				</																		



Préparé par : Catherine Tardy Laporte
Vérifié par : Annie Gauthier

Date début : 2013-07-02
Date fin : 2013-07-02

Nom du projet : Évaluation Environnementale de site (ÉES) Phase II
Site : Site # 38 Orléans
Secteur : 3636-3646, chemin Innes, Orléans (Ontario)
Client : La Coop fédérée

Numéro de projet : 131-13558-00
Coordonnées géographiques : X = 75.5199533185 °O
Y = 45.4457572743 °N
Élévation surface : 89.57 m ()
Élévation margelle :

Entrepreneur forage : Denis Ladouceur Excavation Ltée
Type de foreuse : Rétrocaveuse
Équipement de forage : Manuelle /
Diamètre du forage :
Fluide forage :
Équip. d'échantillonnage : Carottier fendu

ODEUR
F - Faible odeur
M - Odeur moyenne
P - Odeur persistante
VISUEL
D - Produit disséminé
S - Sol saturé de produit
TYPE D'ÉCHANTILLON
CD - Carottier à diamants
CF - Cuillère fendue
PS - Échantillonneur à piston
TC - Tube creux
TM - Tarière manuelle
TR - Truelle
TS - Tube Shelby
TT - Tube transparent
Niveau d'eau
Phase libre

ANALYSES CHIMIQUES
BPC Biphényles polychlorés
BTEX Benzène, toluène, éthylbenzène, xylène
COT Carbone organique total
C. Inorg. Autres composés inorganiques (cyanure, fluorure, bromure, soufre total)
C. Phénol. Composés phénoliques
COV Hydrocarbures HAM et HAC
Diox. & Fur. Dioxines et furanes
HAC Hydrocarb. aliphatiques chlorés
HAM Hydrocarbures aromatiques monocycliques
HAP Hydrocarbures aromatiques polycycliques
HP C₁₀-C₅₀ Hydrocarbures pétroliers C₁₀-C₅₀
HP F1-F4 Hydrocarb. pétrol. F1-F4 (C₁₀-C₅₀)
Mercure Mercure
Métaux Argent, arsenic, baryum, cadmium, cobalt, chrome, cuivre, étain, manganèse, molybdène, nickel, plomb, sélénium, zinc
RMD Lixiviation (mat. dangereuses)

PROFONDEUR ÉLÉVATION (m)		STRATIGRAPHIE	GÉOLOGIE / STRATIGRAPHIE	DESCRIPTION	OBSERVATIONS					ÉCHANTILLONS				PUITS D'OBSERVATION			REMARQUES	
					CONC. VAPEUR (ppm OU % LIE)	ODEUR			VISUEL	TYPE ÉCHANTILLON	% RÉCUPÉRATION	N (Couples/6")	NUMÉRO	ANALYSES	DUPLICATA	DIAGRAMME		DESCRIPTION
						F	M	P										
				Surface du terrain.														
89.57				Remblai : Gravier sableux avec trace de silt. Gris et humide.						TR		TE-01 (0.00-0.30)						
0.30				Remblai : Silt sableux brun avec trace de matière résiduelle (bois brûlé).								TE-01 (0.30-0.60)	HP F1-F4 HAP BTEX Métaux (R153)					0.5
89.27																		
0.60				Infiltration d'eau à 0.6 m.														
88.97				Sol naturel : Silt argileux gris humide.								TE-01 (0.60-1.00)						
1.00				Sol naturel : Silt sableux graveleux avec trace d'argile. Gris humide.								TE-01 (1.00-3.50)						1.0
88.57																		
1.5																		1.5
2.0																		2.0
2.5																		2.5
3.0																		3.0
3.5				Infiltration d'eau.														3.5
86.07				Fin de la tranchée														
				Roc atteint														
4.0																		4.0



Préparé par : Catherine Tardy Laporte
Vérifié par : Annie Gauthier

Date début : 2013-07-02
Date fin : 2013-07-02

Nom du projet : Évaluation Environnementale de site (ÉES) Phase II
Site : Site # 38 Orléans
Secteur : 3636-3646, chemin Innes, Orléans (Ontario)
Client : La Coop fédérée

Numéro de projet : 131-13558-00
Coordonnées géographiques : X = 75.5205637155 °O
Y = 45.4458202359 °N
Élévation surface : 89.59 m ()
Élévation margelle :

Entrepreneur forage : Denis Ladouceur Excavation Ltée
Type de foreuse : Rétrocaveuse
Équipement de forage : Manuelle /
Diamètre du forage :
Fluide forage :
Équip. d'échantillonnage : Carottier fendu

ODEUR
F - Faible odeur
M - Odeur moyenne
P - Odeur persistante
VISUEL
D - Produit disséminé
S - Sol saturé de produit

TYPE D'ÉCHANTILLON
CD - Carottier à diamants
CF - Cuillère fendue
PS - Échantillonneur à piston
TC - Tube creux
TM - Tarière manuelle
TR - Truelle
TS - Tube Shelby
TT - Tube transparent

ANALYSES CHIMIQUES
BPC Biphényles polychlorés
BTEX Benzène, toluène, éthylbenzène, xylène
COT Carbone organique total
C. Inorg. Autres composés inorganiques (cyanure, fluorure, bromure, soufre total)
C. Phénol. Composés phénoliques
COV Hydrocarbures HAM et HAC
Diox. & Fur. Dioxines et furanes

HAC Hydrocarb. aliphatiques chlorés
HAM Hydrocarbures aromatiques monocycliques
HAP Hydrocarbures aromatiques polycycliques
HP C₁₀-C₂₀ Hydrocarbures pétroliers C₁₀-C₂₀
HP F1-F4 Hydrocarb. pétrol. F1-F4 (C₁₀-C₂₀)
Mercure Mercure
Métaux Argent, arsenic, baryum, cadmium, cobalt, chrome, cuivre, étain, manganèse, molybdène, nickel, plomb, sélénium, zinc
RMD Lixiviation (mat. dangereuses)

▽ Niveau d'eau

▽ Phase libre

RMD

PROFONDEUR ÉLÉVATION (m)		STRATIGRAPHIE	GÉOLOGIE / STRATIGRAPHIE	DESCRIPTION	OBSERVATIONS					ÉCHANTILLONS				PUITS D'OBSERVATION			REMARQUES		
					CONC. VAPEUR (ppm ou % LIE)	ODEUR				VISUEL	TYPE ÉCHANTILLON	% RÉCUPÉRATION	N (Coups/6")	NUMÉRO	ANALYSES	DUPLICATA		DIAGRAMME	DESCRIPTION
						F	M	P	D										
				Surface du terrain.															
89.59				Remblai : Matière résiduelle (55%) (brique, bois, bois brûlé et plastique) et silt sableux avec trace de matière organique. Brun humide.									TR		TE-02 (0.00-0.35)	HP F1-F4 HAP BTEX Métaux (R153)			
0.35																			
89.24				Sol naturel : Silt avec un peu de sable et trace de matière organique.											TE-02 (0.35-1.00)	HP F1-F4 HAP BTEX Métaux (R153)		0.5	
0.5																			
1.00				Sol naturel : Silt argileux avec traces de gravier brun-beige.											TE-02 (1.00-1.45)	HP F1-F4 HAP BTEX Métaux (R153)		1.0	
88.59																			
1.45				Sol naturel : Silt argileux gris avec traces de gravier.											TE-02 (1.45-3.30)			1.5	
88.14																			
1.5																			
2.0																		2.0	
2.5																		2.5	
3.0																		3.0	
3.30				Infiltration d'eau.															
86.29				Fin de la tranchée															
3.5																		3.5	
				Roc atteint															
4.0																		4.0	



Préparé par : Catherine Tardy Laporte
Vérifié par : Annie Gauthier

Date début : 2013-07-02
Date fin : 2013-07-02


Nom du projet : Évaluation Environnementale de site (ÉES) Phase II
Site : Site # 38 Orléans
Secteur : 3636-3646, chemin Innes, Orléans (Ontario)
Client : La Coop fédérée

Numéro de projet : 131-13558-00
Coordonnées géographiques : X = 75.5206801071 °O
Y = 45.4461519033 °N
Élévation surface : 88.98 m ()
Élévation margelle :

Entrepreneur forage : Denis Ladouceur Excavation Ltée
Type de foreuse : Rétrocaveuse
Équipement de forage : Manuelle /
Diamètre du forage :
Fluide forage :
Équip. d'échantillonnage : Carottier fendu

ODEUR
F - Faible odeur
M - Odeur moyenne
P - Odeur persistante
VISUEL
D - Produit disséminé
S - Sol saturé de produit
TYPE D'ÉCHANTILLON
CD - Carottier à diamants
CF - Cuillère fendue
PS - Échantillonneur à piston
TC - Tube creux
TM - Tarière manuelle
TR - Truelle
TS - Tube Shelby
TT - Tube transparent
Niveau d'eau
Phase libre

ANALYSES CHIMIQUES
BPC Biphényles polychlorés
BTX Benzène, toluène, éthylbenzène, xylène
COT Carbone organique total
C. Inorg. Autres composés inorganiques (cyanure, fluorure, bromure, soufre total)
C. Phénol. Composés phénoliques
COV Hydrocarbures HAM et HAC
Diox. & Fur. Dioxines et furanes
HAC Hydrocarb. aliphatiques chlorés
HAM Hydrocarbures aromatiques monocycliques
HAP Hydrocarbures aromatiques polycycliques
HP C₁₀-C₅₀ Hydrocarbures pétroliers C₁₀-C₅₀
HP F1-F4 Hydrocarb. pétrol. F1-F4 (C₁₀-C₅₀)
Mercure Mercure
Métaux Argent, arsenic, baryum, cadmium, cobalt, chrome, cuivre, étain, manganèse, molybdène, nickel, plomb, sélénium, zinc.
RMD Lixiviation (mat. dangereuses)

PROFONDEUR ÉLÉVATION (m)		STRATIGRAPHIE	GÉOLOGIE / STRATIGRAPHIE DESCRIPTION	OBSERVATIONS					ÉCHANTILLONS				PUITS D'OBSERVATION			REMARQUES	
				CONC. VAPEUR (ppm ou % LIE)	ODEUR			VISUEL	TYPE ÉCHANTILLON	% RÉCUPÉRATION	N (Coups/6")	NUMÉRO	ANALYSES	DUPLICATA	DIAGRAMME		DESCRIPTION
					F	M	P										
			Surface du terrain.														
88.98			Remblai : Gravier sableux gris saturé. <i>Eau à la surface.</i>						TR			TE-03 (0.00-0.30)					
0.30			Sol naturel : Silt argileux gris humide.									TE-03 (0.30-1.00)	HP F1-F4 HAP	DUP8			0.5
88.68																	
0.5																	
1.00			Sol naturel : Silt avec un peu d'argile gris humide.									TE-03 (1.00-2.60)					1.0
87.98																	
1.0																	
1.5																	1.5
2.0																	2.0
2.5																	2.5
2.60																	
86.38		 Roc atteint	Fin de la tranchée														
3.0																	3.0
3.5																	3.5
4.0																	4.0


Préparé par : **Catherine Tardy Laporte**
Vérifié par : **Annie Gauthier**

Date début : **2013-07-02**
Date fin : **2013-07-02**

Nom du projet : **Évaluation Environnementale de site (ÉES) Phase II**

Numéro de projet : **131-13558-00**

Site : **Site # 38 Orléans**

Coordonnées géographiques : **X = 75.5202005926 °O**

Secteur : **3636-3646, chemin Innes, Orléans (Ontario)**
Y = 45.4465543177 °N

Client : **La Coop fédérée**

Élévation surface : **90.77 m ()**

Élévation margelle :

Entrepreneur forage : **Denis Ladouceur Excavation Ltée**

Type de foreuse : **Rétrocaveuse**

Équipement de forage : **Manuelle /**

Diamètre du forage :

Fluide forage :

Équip. d'échantillonnage : **Carottier fendu**

ODEUR

F - Faible odeur

M - Odeur moyenne

P - Odeur persistante

VISUEL

D - Produit disséminé

S - Sol saturé de produit

TYPE D'ÉCHANTILLON

CD - Carottier à diamants

CF - Cuillère fendue

PS - Échantillonneur à piston

TC - Tube creux

TM - Tarière manuelle

TR - Truelle

TS - Tube Shelby

TT - Tube transparent

ANALYSES CHIMIQUES

BPC Biphényles polychlorés

BTX Benzène, toluène, éthylbenzène, xylène

COT Carbone organique total

C. Inorg. Autres composés inorganiques (cyanure, fluorure, bromure, soufre total)

C. Phénol. Composés phénoliques

COV Hydrocarbures HAM et HAC

Diox. & Fur. Dioxines et furanes

HAC

HAM

HAP

HP C₁₀-C₅₀

HP F1-F4

Mercure

Métaux

RMD

Hydrocarb. aliphatiques chlorés

Hydrocarbures aromatiques monocycliques

Hydrocarbures aromatiques polycycliques

Hydrocarbures pétroliers C₁₀-C₅₀

Hydrocarb. pétrol. F1-F4 (C₁₀-C₅₀)

Mercure

Argent, arsenic, baryum, cadmium, cobalt, chrome, cuivre, étain, manganèse, molybdène, nickel, plomb, sélénium, zinc,

Lixiviation (mat. dangereuses)

Niveau d'eau

Phase libre

PROFONDEUR ÉLÉVATION (m)		GÉOLOGIE / STRATIGRAPHIE		OBSERVATIONS					ÉCHANTILLONS				PUITS D'OBSERVATION		REMARQUES		
				CONC. VAPEUR (ppm OU % LIÉ)	ODEUR			VISUEL	TYPE ÉCHANTILLON	% RÉCUPÉRATION	N (Coups/6")	NUMÉRO	ANALYSES	DUPLICATA		DIAGRAMME	DESCRIPTION
					F	M	P										
				Surface du terrain.													
90.77																	
0.5																	0.5
1.00																	1.0
89.77																	
1.5																	1.5
2.0																	2.0
2.30																	
88.47																	
2.5																	2.5
3.0																	3.0
3.20																	
87.57																	
3.5																	3.5
4.0																	4.0

Préparé par : Catherine Tardy Laporte
Vérifié par : Annie GauthierDate début : 2013-07-02
Date fin : 2013-07-02

Nom du projet : Évaluation Environnementale de site (ÉES) Phase II

Site : Site # 38 Orléans

Secteur : 3636-3646, chemin Innes, Orléans (Ontario)

Client : La Coop fédérée

Numéro de projet : 131-13558-00

Coordonnées géographiques : X = 75.5204743629 °O

Y = 45.4472004843 °N

Élévation surface : 92.43 m ()

Élévation margelle :

Entrepreneur forage : Denis Ladouceur Excavation Ltée

Type de foreuse : Rétrocaveuse

Équipement de forage : Manuelle /

Diamètre du forage :

Fluide forage :

Équip. d'échantillonnage : Carottier fendu

ODEUR

F - Faible odeur
M - Odeur moyenne
P - Odeur persistante

VISUEL

D - Produit disséminé
S - Sol saturé de produit

TYPE D'ÉCHANTILLON

CD - Carottier à diamants
CF - Cuillère fendue
PS - Échantillonneur à piston
TC - Tube creux
TM - Tarière manuelle
TR - Truelle
TS - Tube Shelby
TT - Tube transparent

▽ Niveau d'eau


▽ Phase libre

ANALYSES CHIMIQUES

BPC Biphényles polychlorés
BTEX Benzène, toluène, éthylbenzène, xylène
COT Carbone organique total
C. Inorg. Autres composés inorganiques (cyanure, fluorure, bromure, soufre total)
C. Phénol. Composés phénoliques
COV Hydrocarbures HAM et HAC
Diox. & Fur. Dioxines et furanes

HAC

HAM Hydrocarb. aliphatiques chlorés
HAP Hydrocarbures aromatiques monocycliques
HP C₁₀-C₅₀ Hydrocarbures aromatiques polycycliques
HP F1-F4 Hydrocarb. pétrol. F1-F4 (C₁₀-C₅₀)
Mercure Mercure
Métaux Argent, arsenic, baryum, cadmium, cobalt, chrome, cuivre, étain, manganèse, molybdène, nickel, plomb, sélénium, zinc.
RMD Lixiviation (mat. dangereuses)

PROFONDEUR ÉLÉVATION (m)		STRATIGRAPHIE	GÉOLOGIE / STRATIGRAPHIE DESCRIPTION	OBSERVATIONS CONC. VAPEUR (ppm OU % LIE)	OBSERVATIONS				ÉCHANTILLONS					PUITS D'OBSERVATION		REMARQUES	
					ODEUR	VISUEL	TYPE ÉCHANTILLON	% Récupération	N (Coups/6")	NUMÉRO	ANALYSES	DUPLICATA	DIAGRAMME	DESCRIPTION			
															F		M
			Surface du terrain.														
92.43			Terre végétale et un peu de matière résiduelle (20%) (brique).					TR									
0.15																	
92.28				Remblai : Silt sableux graveleux avec trace de matière résiduelle (bois) brun.							TE-05 (0.15-2.30)	HP F1-F4 HAP					0.5
0.5																	
1.0																1.0	
1.5																1.5	
2.0																2.0	
2.30																	
90.13			Remblai : Silt argileux avec trace de matière organique brun noir.							TE-05 (2.30-3.00)						2.5	
2.5																	
3.0										TE-05 (3.00-3.60)						3.0	
3.5																3.5	
3.60																	
88.83			Fin de la tranchée														
4.0																4.0	

Appendix C

CERTIFICATES OF ANALYSIS

**CLIENT NAME: WSP CANADA INC.
500, BOUL GREBER 3E ETAGE
GATINEAU, QC J8T7W3
(819) 243-2827**

ATTENTION TO: Matthieu Rochon

PROJECT: 161-06382-00-101-980

AGAT WORK ORDER: 16Z101291

SOIL ANALYSIS REVIEWED BY: Amanjot Bhela, Inorganic Coordinator

TRACE ORGANICS REVIEWED BY: Neli Popnikolova, Senior Chemist

DATE REPORTED: Jun 15, 2016

PAGES (INCLUDING COVER): 21

VERSION*: 2

Should you require any information regarding this analysis please contact your client services representative at (905) 712-5100

***NOTES**

VERSION 2: Revised report sent on June 15, 2016. Data for Inorganics has been added this report.

All samples will be disposed of within 30 days following analysis. Please contact the lab if you require additional sample storage time.



AGAT Laboratories

Certificate of Analysis

AGAT WORK ORDER: 16Z101291

PROJECT: 161-06382-00-101-980

5835 COOPERS AVENUE
MISSISSAUGA, ONTARIO
CANADA L4Z 1Y2
TEL (905)712-5100
FAX (905)712-5122
<http://www.agatlabs.com>

CLIENT NAME: WSP CANADA INC.

ATTENTION TO: Matthieu Rochon

SAMPLING SITE: Phase Two ESA. Orleans GW Monitoring.

SAMPLED BY: Kathryn Maton

O. Reg. 153(511) - Metals & Inorganics (Soil)

DATE RECEIVED: 2016-06-03

DATE REPORTED: 2016-06-15

		SAMPLE DESCRIPTION:		BH16-1-1B	BH16-2-1B	BH16-3-1B	BH16-4-1B	BH16-5-1B	BH16-6-1B	BH16-7-1	BH16-8-1
		SAMPLE TYPE:		Soil	Soil	Soil	Soil	Soil	Soil	Soil	Soil
		DATE SAMPLED:		6/1/2016	6/1/2016	6/1/2016	6/1/2016	6/1/2016	6/1/2016	6/1/2016	6/1/2016
Parameter	Unit	G / S	RDL	7608015	7608030	7608034	7608053	7608075	7608096	7608105	7608133
Antimony	µg/g	0.8	<0.8	<0.8	<0.8	<0.8	<0.8	<0.8	<0.8	<0.8	<0.8
Arsenic	µg/g	1	1	1	1	2	1	1	3	2	2
Barium	µg/g	2	325	345	286	254	129	180	302	296	
Beryllium	µg/g	0.5	0.9	1.0	0.9	0.8	0.6	0.6	1.0	0.9	
Boron	µg/g	5	<5	<5	6	<5	<5	5	<5	<5	
Boron (Hot Water Soluble)	µg/g	0.10	0.13	0.15	0.24	0.12	0.29	0.55	0.11	<0.10	
Cadmium	µg/g	0.5	<0.5	<0.5	<0.5	<0.5	<0.5	<0.5	<0.5	<0.5	
Chromium	µg/g	2	101	116	113	87	59	63	118	121	
Cobalt	µg/g	0.5	19.7	22.0	21.6	16.3	11.2	12.4	22.4	25.9	
Copper	µg/g	1	43	47	46	35	16	27	50	44	
Lead	µg/g	1	7	8	7	6	8	9	8	9	
Molybdenum	µg/g	0.5	<0.5	<0.5	<0.5	0.5	0.5	0.6	<0.5	0.5	
Nickel	µg/g	1	58	64	65	47	27	34	67	67	
Selenium	µg/g	0.4	<0.4	<0.4	<0.4	<0.4	<0.4	<0.4	<0.4	<0.4	
Silver	µg/g	0.2	<0.2	<0.2	<0.2	<0.2	<0.2	<0.2	<0.2	<0.2	
Thallium	µg/g	0.4	0.4	0.5	<0.4	<0.4	<0.4	<0.4	0.5	0.4	
Uranium	µg/g	0.5	0.6	0.7	0.6	1.0	0.9	0.6	0.8	0.9	
Vanadium	µg/g	1	91	99	88	89	53	60	103	98	
Zinc	µg/g	5	123	132	120	96	80	85	128	126	
Chromium VI	µg/g	0.2	<0.2	<0.2	<0.2	<0.2	<0.2	<0.2	<0.2	<0.2	
Cyanide	µg/g	0.040	<0.040	<0.040	<0.040	<0.040	<0.040	<0.040	<0.040	<0.040	
Mercury	µg/g	0.10	<0.10	<0.10	<0.10	<0.10	<0.10	<0.10	<0.10	<0.10	
Electrical Conductivity	mS/cm	0.005	0.458	0.419	0.465	0.363	0.325	0.569	0.579	1.86	
Sodium Adsorption Ratio	NA	NA	0.486	0.855	1.11	0.565	0.657	5.41	1.02	4.79	
pH, 2:1 CaCl2 Extraction	pH Units	NA	7.23	7.05	7.15	7.07	7.24	7.42	7.13	7.25	

Certified By:

Amanjot Bhela



Certificate of Analysis

AGAT WORK ORDER: 16Z101291

PROJECT: 161-06382-00-101-980

5835 COOPERS AVENUE
MISSISSAUGA, ONTARIO
CANADA L4Z 1Y2
TEL (905)712-5100
FAX (905)712-5122
<http://www.agatlabs.com>

CLIENT NAME: WSP CANADA INC.

SAMPLING SITE: Phase Two ESA. Orleans GW Monitoring.

ATTENTION TO: Matthieu Rochon

SAMPLED BY: Kathryn Maton

O. Reg. 153(511) - Metals & Inorganics (Soil)

DATE RECEIVED: 2016-06-03

DATE REPORTED: 2016-06-15

		SAMPLE DESCRIPTION:		BH16-9-1	BH16-10-1	BH16-11-2A	BH16-12-2A	BH16-13-2A
		SAMPLE TYPE:		Soil	Soil	Soil	Soil	Soil
		DATE SAMPLED:		6/2/2016	6/2/2016	6/2/2016	6/2/2016	6/2/2016
Parameter	Unit	G / S	RDL	7608148	7608156	7608164	7608171	7608178
Antimony	µg/g	0.8	<0.8	<0.8	<0.8	<0.8	<0.8	<0.8
Arsenic	µg/g	1	2	2	2	2	2	2
Barium	µg/g	2	263	268	290	288	273	
Beryllium	µg/g	0.5	0.9	0.8	0.8	0.7	0.8	
Boron	µg/g	5	<5	<5	<5	<5	5	
Boron (Hot Water Soluble)	µg/g	0.10	0.22	<0.10	0.25	0.37	0.34	
Cadmium	µg/g	0.5	<0.5	<0.5	<0.5	<0.5	<0.5	
Chromium	µg/g	2	112	103	107	116	112	
Cobalt	µg/g	0.5	19.3	18.7	23.7	24.2	22.2	
Copper	µg/g	1	47	44	48	51	47	
Lead	µg/g	1	8	7	7	8	7	
Molybdenum	µg/g	0.5	0.6	<0.5	<0.5	<0.5	<0.5	
Nickel	µg/g	1	60	58	62	66	64	
Selenium	µg/g	0.4	<0.4	<0.4	<0.4	<0.4	<0.4	
Silver	µg/g	0.2	<0.2	<0.2	<0.2	<0.2	<0.2	
Thallium	µg/g	0.4	<0.4	<0.4	0.4	0.4	<0.4	
Uranium	µg/g	0.5	1.0	0.8	1.0	1.2	0.9	
Vanadium	µg/g	1	99	89	100	105	94	
Zinc	µg/g	5	114	106	124	129	123	
Chromium VI	µg/g	0.2	<0.2	<0.2	<0.2	<0.2	<0.2	
Cyanide	µg/g	0.040	<0.040	<0.040	<0.040	<0.040	<0.040	
Mercury	µg/g	0.10	<0.10	<0.10	<0.10	<0.10	<0.10	
Electrical Conductivity	mS/cm	0.005	0.394	0.215	0.176	0.091	0.075	
Sodium Adsorption Ratio	NA	NA	1.10	1.04	0.622	0.436	0.416	
pH, 2:1 CaCl2 Extraction	pH Units	NA	7.15	6.77	7.05	7.13	7.13	

Comments: RDL - Reported Detection Limit; G / S - Guideline / Standard: Refers to T1(All)

7608015-7608178 EC & SAR were determined on the DI water extract obtained from the 2:1 leaching procedure (2 parts DI water:1 part soil). pH was determined on the 0.01M CaCl2 extract prepared at 2:1 ratio.

Certified By:

Amanjot Bhela



AGAT Laboratories

Certificate of Analysis

AGAT WORK ORDER: 16Z101291

PROJECT: 161-06382-00-101-980

5835 COOPERS AVENUE
MISSISSAUGA, ONTARIO
CANADA L4Z 1Y2
TEL (905)712-5100
FAX (905)712-5122
<http://www.agatlabs.com>

CLIENT NAME: WSP CANADA INC.

ATTENTION TO: Matthieu Rochon

SAMPLING SITE: Phase Two ESA. Orleans GW Monitoring.

SAMPLED BY: Kathryn Maton

O. Reg. 153(511) - Metals (Comprehensive) (Soil)

DATE RECEIVED: 2016-06-03

DATE REPORTED: 2016-06-15

		SAMPLE DESCRIPTION:		BH16-1-2A	BH16-1-2B	BH16-2-2A	BH16-2-2B	BH16-3-2A	BH16-3-3	BH16-4-2B	BH16-4-102B
		SAMPLE TYPE:		Soil	Soil	Soil	Soil	Soil	Soil	Soil	Soil
		DATE SAMPLED:		6/1/2016	6/1/2016	6/1/2016	6/1/2016	6/1/2016	6/1/2016	6/1/2016	6/1/2016
Parameter	Unit	G / S	RDL	7608016	7608020	7608023	7608027	7608038	7608050	7608062	7608065
Antimony	µg/g		0.8	<0.8	<0.8	<0.8	<0.8	<0.8	<0.8	<0.8	<0.8
Arsenic	µg/g		1	1	1	1	2	1	5	2	4
Boron	µg/g		5	<5	6	<5	8	5	9	8	9
Barium	µg/g		2	347	198	355	271	398	346	347	250
Beryllium	µg/g		0.5	1.0	0.7	0.9	0.8	0.9	<0.5	1.0	0.8
Cadmium	µg/g		0.5	<0.5	<0.5	<0.5	<0.5	<0.5	<0.5	<0.5	<0.5
Chromium	µg/g		2	108	45	99	65	111	26	70	57
Cobalt	µg/g		0.5	23.0	10.7	20.4	16.7	22.6	6.8	20.2	18.2
Copper	µg/g		1	48	28	47	33	48	15	35	35
Lead	µg/g		1	7	6	7	6	7	8	7	8
Molybdenum	µg/g		0.5	<0.5	<0.5	<0.5	<0.5	<0.5	1.0	<0.5	<0.5
Nickel	µg/g		1	60	25	55	40	62	11	43	37
Selenium	µg/g		0.4	<0.4	<0.4	<0.4	<0.4	<0.4	<0.4	<0.4	<0.4
Silver	µg/g		0.2	<0.2	<0.2	<0.2	<0.2	<0.2	<0.2	<0.2	<0.2
Thallium	µg/g		0.4	0.5	<0.4	0.4	<0.4	0.5	<0.4	0.4	<0.4
Uranium	µg/g		0.5	0.6	<0.5	0.6	0.6	0.7	0.6	0.6	0.6
Vanadium	µg/g		1	101	57	98	76	102	25	88	80
Zinc	µg/g		5	137	71	129	101	146	56	127	112

Certified By:

Amanjot Bhela



AGAT Laboratories

Certificate of Analysis

AGAT WORK ORDER: 16Z101291

PROJECT: 161-06382-00-101-980

5835 COOPERS AVENUE
MISSISSAUGA, ONTARIO
CANADA L4Z 1Y2
TEL (905)712-5100
FAX (905)712-5122
<http://www.agatlabs.com>

CLIENT NAME: WSP CANADA INC.

ATTENTION TO: Matthieu Rochon

SAMPLING SITE: Phase Two ESA. Orleans GW Monitoring.

SAMPLED BY: Kathryn Maton

O. Reg. 153(511) - Metals (Comprehensive) (Soil)

DATE RECEIVED: 2016-06-03

DATE REPORTED: 2016-06-15

		SAMPLE DESCRIPTION:		BH16-5-101B	BH16-5-2B	BH16-6-2B	BH16-7-2B	BH16-8-2B	BH16-9-2B	BH16-9-4	BH16-10-2B
		SAMPLE TYPE:		Soil	Soil	Soil	Soil	Soil	Soil	Soil	Soil
		DATE SAMPLED:		6/1/2016	6/1/2016	6/1/2016	6/1/2016	6/1/2016	6/2/2016	6/2/2016	6/2/2016
Parameter	Unit	G / S	RDL	7608077	7608081	7608100	7608122	7608139	7608151	7608154	7608158
Antimony	µg/g		0.8	<0.8	<0.8	<0.8	<0.8	<0.8	<0.8	<0.8	<0.8
Arsenic	µg/g		1	2	2	3	1	2	1	1	1
Boron	µg/g		5	6	8	9	6	8	<5	<5	<5
Barium	µg/g		2	266	412	285	338	524	304	84	303
Beryllium	µg/g		0.5	0.9	1.0	0.9	0.7	1.0	0.7	<0.5	0.8
Cadmium	µg/g		0.5	<0.5	<0.5	<0.5	<0.5	<0.5	<0.5	<0.5	<0.5
Chromium	µg/g		2	125	72	61	50	77	99	14	102
Cobalt	µg/g		0.5	22.2	19.1	18.4	15.1	22.7	20.0	5.4	22.6
Copper	µg/g		1	44	39	35	30	47	46	11	45
Lead	µg/g		1	8	8	8	6	9	6	4	6
Molybdenum	µg/g		0.5	<0.5	<0.5	<0.5	<0.5	0.5	<0.5	0.6	<0.5
Nickel	µg/g		1	66	43	37	32	49	56	10	59
Selenium	µg/g		0.4	<0.4	<0.4	<0.4	<0.4	<0.4	<0.4	<0.4	<0.4
Silver	µg/g		0.2	<0.2	<0.2	<0.2	<0.2	<0.2	<0.2	<0.2	<0.2
Thallium	µg/g		0.4	<0.4	0.5	<0.4	<0.4	0.6	0.4	<0.4	0.4
Uranium	µg/g		0.5	1.0	0.6	0.6	0.6	0.7	0.9	<0.5	0.8
Vanadium	µg/g		1	94	93	83	68	101	102	21	96
Zinc	µg/g		5	109	134	118	94	149	126	21	123

Certified By:

Amanjot Bhela



AGAT Laboratories

Certificate of Analysis

AGAT WORK ORDER: 16Z101291

PROJECT: 161-06382-00-101-980

5835 COOPERS AVENUE
MISSISSAUGA, ONTARIO
CANADA L4Z 1Y2
TEL (905)712-5100
FAX (905)712-5122
<http://www.agatlabs.com>

CLIENT NAME: WSP CANADA INC.

ATTENTION TO: Matthieu Rochon

SAMPLING SITE: Phase Two ESA. Orleans GW Monitoring.

SAMPLED BY: Kathryn Maton

O. Reg. 153(511) - Metals (Comprehensive) (Soil)

DATE RECEIVED: 2016-06-03

DATE REPORTED: 2016-06-15

		SAMPLE DESCRIPTION:		BH16-10-4A	BH16-11-3B	BH16-12-3B	BH16-13-3B	BH16-13-102A
		SAMPLE TYPE:		Soil	Soil	Soil	Soil	Soil
		DATE SAMPLED:		6/2/2016	6/2/2016	6/2/2016	6/2/2016	6/2/2016
Parameter	Unit	G / S	RDL	7608161	7608167	7608174	7608185	7608670
Antimony	µg/g		0.8	<0.8	<0.8	<0.8	<0.8	<0.8
Arsenic	µg/g		1	2	1	1	2	2
Boron	µg/g		5	8	5	5	7	<5
Barium	µg/g		2	294	297	369	246	272
Beryllium	µg/g		0.5	0.7	0.7	0.7	0.7	0.7
Cadmium	µg/g		0.5	<0.5	<0.5	<0.5	<0.5	<0.5
Chromium	µg/g		2	80	99	99	84	109
Cobalt	µg/g		0.5	19.6	21.1	23.2	18.2	22.4
Copper	µg/g		1	40	47	50	38	46
Lead	µg/g		1	7	6	7	6	7
Molybdenum	µg/g		0.5	1.0	0.7	1.0	0.9	<0.5
Nickel	µg/g		1	47	56	58	48	63
Selenium	µg/g		0.4	<0.4	<0.4	<0.4	<0.4	<0.4
Silver	µg/g		0.2	<0.2	<0.2	<0.2	<0.2	<0.2
Thallium	µg/g		0.4	<0.4	<0.4	0.5	<0.4	<0.4
Uranium	µg/g		0.5	1.8	1.0	0.9	1.9	0.9
Vanadium	µg/g		1	87	94	114	82	93
Zinc	µg/g		5	117	123	141	108	120

Comments: RDL - Reported Detection Limit; G / S - Guideline / Standard

Certified By:

Amanjot Bhela



Certificate of Analysis

AGAT WORK ORDER: 16Z101291

PROJECT: 161-06382-00-101-980

5835 COOPERS AVENUE
MISSISSAUGA, ONTARIO
CANADA L4Z 1Y2
TEL (905)712-5100
FAX (905)712-5122
<http://www.agatlabs.com>

CLIENT NAME: WSP CANADA INC.

SAMPLING SITE: Phase Two ESA. Orleans GW Monitoring.

ATTENTION TO: Matthieu Rochon

SAMPLED BY: Kathryn Maton

O. Reg. 153(511) - PAHs (Soil)

DATE RECEIVED: 2016-06-03

DATE REPORTED: 2016-06-15

		SAMPLE DESCRIPTION:		BH16-5-2B	BH16-7-1	BH16-8-1
		SAMPLE TYPE:		Soil	Soil	Soil
		DATE SAMPLED:		6/1/2016	6/1/2016	6/1/2016
Parameter	Unit	G / S	RDL	7608081	7608105	7608133
Naphthalene	µg/g		0.05	0.06	<0.05	<0.05
Acenaphthylene	µg/g		0.05	<0.05	<0.05	<0.05
Acenaphthene	µg/g		0.05	<0.05	<0.05	<0.05
Fluorene	µg/g		0.05	0.11	<0.05	<0.05
Phenanthrene	µg/g		0.05	0.17	<0.05	<0.05
Anthracene	µg/g		0.05	<0.05	<0.05	<0.05
Fluoranthene	µg/g		0.05	<0.05	<0.05	<0.05
Pyrene	µg/g		0.05	<0.05	<0.05	<0.05
Benz(a)anthracene	µg/g		0.05	<0.05	<0.05	<0.05
Chrysene	µg/g		0.05	<0.05	<0.05	<0.05
Benzo(b)fluoranthene	µg/g		0.05	<0.05	<0.05	<0.05
Benzo(k)fluoranthene	µg/g		0.05	<0.05	<0.05	<0.05
Benzo(a)pyrene	µg/g		0.05	<0.05	<0.05	<0.05
Indeno(1,2,3-cd)pyrene	µg/g		0.05	<0.05	<0.05	<0.05
Dibenz(a,h)anthracene	µg/g		0.05	<0.05	<0.05	<0.05
Benzo(g,h,i)perylene	µg/g		0.05	<0.05	<0.05	<0.05
2-and 1-methyl Naphthalene	µg/g		0.05	0.50	<0.05	<0.05
Moisture Content	%		0.1	17.1	26.3	27.7
Surrogate	Unit	Acceptable Limits				
Chrysene-d12	%	50-140		96	119	104

Comments: RDL - Reported Detection Limit; G / S - Guideline / Standard

7608081-7608133 Results are based on the dry weight of the soil.

Note: The result for Benzo(b)Fluoranthene is the total of the Benzo(b)&(j)Fluoranthene isomers because the isomers co-elute on the GC column.

Certified By:

N Popmukolof



Certificate of Analysis

AGAT WORK ORDER: 16Z101291

PROJECT: 161-06382-00-101-980

5835 COOPERS AVENUE
MISSISSAUGA, ONTARIO
CANADA L4Z 1Y2
TEL (905)712-5100
FAX (905)712-5122
<http://www.agatlabs.com>

CLIENT NAME: WSP CANADA INC.

SAMPLING SITE: Phase Two ESA. Orleans GW Monitoring.

ATTENTION TO: Matthieu Rochon

SAMPLED BY: Kathryn Maton

O. Reg. 153(511) - PHCs F1 - F4 (Soil)

DATE RECEIVED: 2016-06-03

DATE REPORTED: 2016-06-15

		SAMPLE DESCRIPTION: BH16-6-1B	
		SAMPLE TYPE: Soil	
		DATE SAMPLED: 6/1/2016	
Parameter	Unit	G / S	RDL
			7608096
Benzene	µg/g	0.02	<0.02
Toluene	µg/g	0.08	<0.08
Ethylbenzene	µg/g	0.05	<0.05
Xylene Mixture	µg/g	0.05	<0.05
F1 (C6 to C10)	µg/g	5	<5
F1 (C6 to C10) minus BTEX	µg/g	5	<5
F2 (C10 to C16)	µg/g	10	<10
F3 (C16 to C34)	µg/g	50	<50
F4 (C34 to C50)	µg/g	50	<50
Gravimetric Heavy Hydrocarbons	µg/g	50	NA
Moisture Content	%	0.1	29.7
Surrogate	Unit	Acceptable Limits	
Terphenyl	%	60-140	103

Comments: RDL - Reported Detection Limit; G / S - Guideline / Standard

7608096

Results are based on sample dry weight.

The C6-C10 fraction is calculated using Toluene response factor.

The C10 - C16, C16 - C34, and C34 - C50 fractions are calculated using the average response factor for n-C10, n-C16, and n-C34.

Gravimetric Heavy Hydrocarbons are not included in the Total C16-C50 and are only determined if the chromatogram of the C34 - C50 hydrocarbons indicates that hydrocarbons >C50 are present.

The chromatogram has returned to baseline by the retention time of nC50.

Total C6 - C50 results are corrected for BTEX contributions.

This method complies with the Reference Method for the CWS PHC and is validated for use in the laboratory.

nC6 and nC10 response factors are within 30% of Toluene response factor.

nC10, nC16 and nC34 response factors are within 10% of their average.

C50 response factor is within 70% of nC10 + nC16 + nC34 average.

Linearity is within 15%.

Extraction and holding times were met for this sample.

Fractions 1-4 are quantified with the contribution of PAHs. Under Ontario Regulation 153, results are considered valid without determining the PAH contribution if not requested by the client.

Quality Control Data is available upon request.

Certified By:



AGAT Laboratories

Certificate of Analysis

AGAT WORK ORDER: 16Z101291

PROJECT: 161-06382-00-101-980

5835 COOPERS AVENUE
MISSISSAUGA, ONTARIO
CANADA L4Z 1Y2
TEL (905)712-5100
FAX (905)712-5122
<http://www.agatlabs.com>

CLIENT NAME: WSP CANADA INC.

SAMPLING SITE: Phase Two ESA. Orleans GW Monitoring.

ATTENTION TO: Matthieu Rochon

SAMPLED BY: Kathryn Maton

O. Reg. 153(511) - PHCs F1 - F4 (Soil) - F2-F4

DATE RECEIVED: 2016-06-03

DATE REPORTED: 2016-06-15

		SAMPLE DESCRIPTION:		BH16-4-1B	BH16-5-1B	BH16-5-101B
		SAMPLE TYPE:		Soil	Soil	Soil
		DATE SAMPLED:		6/1/2016	6/1/2016	6/1/2016
Parameter	Unit	G / S	RDL	7608053	7608075	7608077
F2 (C10 to C16)	µg/g		10	<10	<10	<10
F3 (C16 to C34)	µg/g		50	<50	<50	<50
F4 (C34 to C50)	µg/g		50	<50	<50	<50
Gravimetric Heavy Hydrocarbons	µg/g		50	NA	NA	NA
Moisture Content	%		0.1	19.0	19.8	21.8
Surrogate	Unit	Acceptable Limits				
Terphenyl	%	60-140	92	116	99	

Comments: RDL - Reported Detection Limit; G / S - Guideline / Standard

7608053-7608077 Results are based on sample dry weight.

The C10 - C16, C16 - C34, and C34 - C50 fractions are calculated using the average response factor for n-C10, n-C16, and n-C34.

Gravimetric Heavy Hydrocarbons are not included in the Total C16-C50 and are only determined if the chromatogram of the C34 - C50 hydrocarbons indicates that hydrocarbons >C50 are present.

The chromatogram has returned to baseline by the retention time of nC50.

This method complies with the Reference Method for the CWS PHC and is validated for use in the laboratory.

nC10, nC16 and nC34 response factors are within 10% of their average.

C50 response factor is within 70% of nC10 + nC16 + nC34 average.

Linearity is within 15%.

Extraction and holding times were met for this sample.

Fractions 2-4 are quantified with the contribution of PAHs. Under Ontario Regulation 153, results are considered valid without determining the PAH contribution if not requested by the client.

Quality Control Data is available upon request.

Certified By:



Certificate of Analysis

AGAT WORK ORDER: 16Z101291

PROJECT: 161-06382-00-101-980

5835 COOPERS AVENUE
MISSISSAUGA, ONTARIO
CANADA L4Z 1Y2
TEL (905)712-5100
FAX (905)712-5122
<http://www.agatlabs.com>

CLIENT NAME: WSP CANADA INC.

ATTENTION TO: Matthieu Rochon

SAMPLING SITE: Phase Two ESA. Orleans GW Monitoring.

SAMPLED BY: Kathryn Maton

O. Reg. 153(511) - PHCs F1 - F4 (with PAHs) (Soil)

DATE RECEIVED: 2016-06-03

DATE REPORTED: 2016-06-15

		SAMPLE DESCRIPTION:		BH16-5-2B	BH16-7-1	BH16-8-1
		SAMPLE TYPE:		Soil	Soil	Soil
		DATE SAMPLED:		6/1/2016	6/1/2016	6/1/2016
Parameter	Unit	G / S	RDL	7608081	7608105	7608133
Benzene	µg/g		0.02	<0.02	<0.02	<0.02
Toluene	µg/g		0.08	<0.08	<0.08	<0.08
Ethylbenzene	µg/g		0.05	0.16	<0.05	<0.05
Xylene Mixture	µg/g		0.05	0.06	<0.05	<0.05
F1 (C6 to C10)	µg/g		5	11	<5	<5
F1 (C6 to C10) minus BTEX	µg/g		5	11	<5	<5
F2 (C10 to C16)	µg/g		10	34	<10	<10
F2 (C10 to C16) minus Naphthalene	µg/g		10	34	<10	<10
F3 (C16 to C34)	µg/g		50	<50	<50	<50
F3 (C16 to C34) minus PAHs	µg/g		50	<50	<50	<50
F4 (C34 to C50)	µg/g		50	<50	<50	<50
Gravimetric Heavy Hydrocarbons	µg/g		50	NA	NA	NA
Moisture Content	%		0.1	17.1	26.3	27.7
Surrogate	Unit	Acceptable Limits				
Terphenyl	%	60-140	100	85	136	

Comments: RDL - Reported Detection Limit; G / S - Guideline / Standard

7608081-7608133 Results are based on sample dry weight.
The C6-C10 fraction is calculated using toluene response factor.
The C10 - C16, C16 - C34, and C34 - C50 fractions are calculated using the average response factor for n-C10, n-C16, and n-C34.
Gravimetric Heavy Hydrocarbons are not included in the Total C16-C50 and are only determined if the chromatogram of the C34 - C50 hydrocarbons indicates that hydrocarbons >C50 are present.
The chromatogram has returned to baseline by the retention time of nC50.
Total C6 - C50 results are corrected for BTEX and PAH contributions.
This method complies with the Reference Method for the CWS PHC and is validated for use in the laboratory.
nC6 and nC10 response factors are within 30% of Toluene response factor.
nC10, nC16 and nC34 response factors are within 10% of their average.
C50 response factor is within 70% of nC10 + nC16 + nC34 average.
Linearity is within 15%.
Extraction and holding times were met for this sample.

Certified By:

N Popmukolof

Quality Assurance

CLIENT NAME: WSP CANADA INC.

PROJECT: 161-06382-00-101-980

SAMPLING SITE: Phase Two ESA. Orleans GW Monitoring.

AGAT WORK ORDER: 16Z101291

ATTENTION TO: Matthieu Rochon

SAMPLED BY: Kathryn Maton

Soil Analysis

RPT Date: Jun 15, 2016			DUPLICATE			Method Blank	REFERENCE MATERIAL			METHOD BLANK SPIKE			MATRIX SPIKE		
PARAMETER	Batch	Sample Id	Dup #1	Dup #2	RPD		Measured Value	Acceptable Limits		Recovery	Acceptable Limits		Recovery	Acceptable Limits	
								Lower	Upper		Lower	Upper		Lower	Upper
O. Reg. 153(511) - Metals (Comprehensive) (Soil)															
Antimony	7608105	7608105	<0.8	<0.8	NA	< 0.8	108%	70%	130%	100%	80%	120%	102%	70%	130%
Arsenic	7608105	7608105	2	2	NA	< 1	105%	70%	130%	93%	80%	120%	95%	70%	130%
Boron	7608105	7608105	<5	5	NA	< 5	76%	70%	130%	91%	80%	120%	79%	70%	130%
Barium	7608105	7608105	302	309	2.3%	< 2	92%	70%	130%	85%	80%	120%	93%	70%	130%
Beryllium	7608105	7608105	1.0	0.9	NA	< 0.5	91%	70%	130%	97%	80%	120%	91%	70%	130%
Cadmium	7608105	7608105	<0.5	<0.5	NA	< 0.5	95%	70%	130%	105%	80%	120%	102%	70%	130%
Chromium	7608105	7608105	118	120	1.7%	< 2	80%	70%	130%	100%	80%	120%	108%	70%	130%
Cobalt	7608105	7608105	22.4	21.7	3.2%	< 0.5	91%	70%	130%	92%	80%	120%	90%	70%	130%
Copper	7608105	7608105	50	51	2.0%	< 1	87%	70%	130%	92%	80%	120%	90%	70%	130%
Lead	7608105	7608105	8	8	0.0%	< 1	101%	70%	130%	87%	80%	120%	85%	70%	130%
Molybdenum	7608105	7608105	<0.5	<0.5	NA	< 0.5	103%	70%	130%	100%	80%	120%	100%	70%	130%
Nickel	7608105	7608105	67	67	0.0%	< 1	90%	70%	130%	91%	80%	120%	92%	70%	130%
Selenium	7608105	7608105	<0.4	<0.4	NA	< 0.4	117%	70%	130%	95%	80%	120%	98%	70%	130%
Silver	7608105	7608105	<0.2	<0.2	NA	< 0.2	100%	70%	130%	102%	80%	120%	99%	70%	130%
Thallium	7608105	7608105	0.5	0.5	NA	< 0.4	93%	70%	130%	101%	80%	120%	99%	70%	130%
Uranium	7608105	7608105	0.8	0.8	NA	< 0.5	91%	70%	130%	84%	80%	120%	84%	70%	130%
Vanadium	7608105	7608105	103	106	2.9%	< 1	85%	70%	130%	89%	80%	120%	99%	70%	130%
Zinc	7608105	7608105	128	130	1.6%	< 5	99%	70%	130%	100%	80%	120%	103%	70%	130%

Comments: NA signifies Not Applicable.

Duplicate Qualifier: As the measured result approaches the RL, the uncertainty associated with the value increases dramatically, thus duplicate acceptance limits apply only where the average of the two duplicates is greater than five times the RL.

O. Reg. 153(511) - Metals & Inorganics (Soil)

Antimony	7608015	7608015	<0.8	<0.8	NA	< 0.8	109%	70%	130%	104%	80%	120%	105%	70%	130%
Arsenic	7608015	7608015	1	1	NA	< 1	104%	70%	130%	94%	80%	120%	97%	70%	130%
Barium	7608015	7608015	325	342	5.1%	< 2	87%	70%	130%	86%	80%	120%	97%	70%	130%
Beryllium	7608015	7608015	0.9	1.0	NA	< 0.5	99%	70%	130%	108%	80%	120%	103%	70%	130%
Boron	7608015	7608015	<5	<5	NA	< 5	71%	70%	130%	99%	80%	120%	92%	70%	130%
Boron (Hot Water Soluble)	7617440		<0.10	<0.10	NA	< 0.10	85%	60%	140%	101%	70%	130%	104%	60%	140%
Cadmium	7608015	7608015	<0.5	<0.5	NA	< 0.5	91%	70%	130%	110%	80%	120%	103%	70%	130%
Chromium	7608015	7608015	101	105	3.9%	< 2	86%	70%	130%	95%	80%	120%	109%	70%	130%
Cobalt	7608015	7608015	19.7	20.1	2.0%	< 0.5	91%	70%	130%	94%	80%	120%	93%	70%	130%
Copper	7608015	7608015	43	45	4.5%	< 1	84%	70%	130%	93%	80%	120%	90%	70%	130%
Lead	7608015	7608015	7	7	0.0%	< 1	100%	70%	130%	90%	80%	120%	88%	70%	130%
Molybdenum	7608015	7608015	<0.5	<0.5	NA	< 0.5	101%	70%	130%	100%	80%	120%	102%	70%	130%
Nickel	7608015	7608015	58	60	3.4%	< 1	86%	70%	130%	92%	80%	120%	94%	70%	130%
Selenium	7608015	7608015	<0.4	<0.4	NA	< 0.4	91%	70%	130%	99%	80%	120%	101%	70%	130%
Silver	7608015	7608015	<0.2	<0.2	NA	< 0.2	99%	70%	130%	103%	80%	120%	99%	70%	130%
Thallium	7608015	7608015	0.4	0.4	NA	< 0.4	97%	70%	130%	103%	80%	120%	102%	70%	130%

AGAT QUALITY ASSURANCE REPORT (V2)

Page 11 of 21

AGAT Laboratories is accredited to ISO/IEC 17025 by the Canadian Association for Laboratory Accreditation Inc. (CALA) and/or Standards Council of Canada (SCC) for specific tests listed on the scope of accreditation. AGAT Laboratories (Mississauga) is also accredited by the Canadian Association for Laboratory Accreditation Inc. (CALA) for specific drinking water tests. Accreditations are location and parameter specific. A complete listing of parameters for each location is available from www.cala.ca and/or www.scc.ca. The tests in this report may not necessarily be included in the scope of accreditation.

Results relate only to the items tested and to all the items tested



Quality Assurance

CLIENT NAME: WSP CANADA INC.

PROJECT: 161-06382-00-101-980

SAMPLING SITE: Phase Two ESA. Orleans GW Monitoring.

AGAT WORK ORDER: 16Z101291

ATTENTION TO: Matthieu Rochon

SAMPLED BY: Kathryn Maton

Soil Analysis (Continued)

RPT Date: Jun 15, 2016			DUPLICATE				REFERENCE MATERIAL			METHOD BLANK SPIKE			MATRIX SPIKE		
PARAMETER	Batch	Sample Id	Dup #1	Dup #2	RPD	Method Blank	Measured Value	Acceptable Limits		Recovery	Acceptable Limits		Recovery	Acceptable Limits	
								Lower	Upper		Lower	Upper		Lower	Upper
Uranium	7608015	7608015	0.6	0.6	NA	< 0.5	92%	70%	130%	86%	80%	120%	87%	70%	130%
Vanadium	7608015	7608015	91	93	2.2%	< 1	88%	70%	130%	90%	80%	120%	99%	70%	130%
Zinc	7608015	7608015	123	126	2.4%	< 5	100%	70%	130%	104%	80%	120%	103%	70%	130%
Chromium VI	7614373		<0.2	<0.2	NA	< 0.2	97%	70%	130%	92%	80%	120%	93%	70%	130%
Cyanide	7608015	7608015	<0.040	<0.040	NA	< 0.040	91%	70%	130%	103%	80%	120%	104%	70%	130%
Mercury	7608015	7608015	<0.10	<0.10	NA	< 0.10	97%	70%	130%	96%	80%	120%	89%	70%	130%
Electrical Conductivity	7608015	7608015	0.458	0.458	0.0%	< 0.005	99%	90%	110%	NA			NA		
Sodium Adsorption Ratio	7608015	7608015	0.486	0.470	3.3%	NA	NA			NA			NA		
pH, 2:1 CaCl ₂ Extraction	7608156	7608156	6.77	6.86	1.3%	NA	101%	80%	120%	NA			NA		

Comments: NA signifies Not Applicable.

Duplicate Qualifier: As the measured result approaches the RL, the uncertainty associated with the value increases dramatically, thus duplicate acceptance limits apply only where the average of the two duplicates is greater than five times the RL.

Certified By:

Amanjot Bhela

Quality Assurance

CLIENT NAME: WSP CANADA INC.

PROJECT: 161-06382-00-101-980

SAMPLING SITE: Phase Two ESA. Orleans GW Monitoring.

AGAT WORK ORDER: 16Z101291

ATTENTION TO: Matthieu Rochon

SAMPLED BY: Kathryn Maton

Trace Organics Analysis

RPT Date: Jun 15, 2016			DUPLICATE			Method Blank	REFERENCE MATERIAL		METHOD BLANK SPIKE		MATRIX SPIKE	
PARAMETER	Batch	Sample Id	Dup #1	Dup #2	RPD		Measured Value	Acceptable Limits		Recovery	Acceptable Limits	
								Lower	Upper		Lower	Upper

O. Reg. 153(511) - PHCs F1 - F4 (Soil) - F2-F4

F2 (C10 to C16)	7608075	7608075	< 10	< 10	NA	< 10	102%	60%	130%	101%	80%	120%	70%	70%	130%
F3 (C16 to C34)	7608075	7608075	< 50	< 50	NA	< 50	105%	60%	130%	84%	80%	120%	100%	70%	130%
F4 (C34 to C50)	7608075	7608075	< 50	< 50	NA	< 50	100%	60%	130%	96%	80%	120%	100%	70%	130%

O. Reg. 153(511) - PHCs F1 - F4 (with PAHs) (Soil)

Benzene	7607223		< 0.02	< 0.02	NA	< 0.02	105%	60%	130%	109%	60%	130%	115%	60%	130%
Toluene	7607223		< 0.08	< 0.08	NA	< 0.08	110%	60%	130%	106%	60%	130%	112%	60%	130%
Ethylbenzene	7607223		< 0.05	< 0.05	NA	< 0.05	119%	60%	130%	106%	60%	130%	112%	60%	130%
Xylene Mixture	7607223		< 0.05	< 0.05	NA	< 0.05	117%	60%	130%	108%	60%	130%	112%	60%	130%
F1 (C6 to C10)	7607223		< 5	< 5	NA	< 5	81%	60%	130%	95%	85%	115%	97%	70%	130%

O. Reg. 153(511) - PAHs (Soil)

Naphthalene	7599332		< 0.05	< 0.05	NA	< 0.05	103%	50%	140%	112%	50%	140%	94%	50%	140%
Acenaphthylene	7599332		< 0.05	< 0.05	NA	< 0.05	105%	50%	140%	114%	50%	140%	94%	50%	140%
Acenaphthene	7599332		< 0.05	< 0.05	NA	< 0.05	103%	50%	140%	111%	50%	140%	96%	50%	140%
Fluorene	7599332		< 0.05	< 0.05	NA	< 0.05	106%	50%	140%	113%	50%	140%	98%	50%	140%
Phenanthrene	7599332		< 0.05	< 0.05	NA	< 0.05	102%	50%	140%	107%	50%	140%	92%	50%	140%
Anthracene	7599332		< 0.05	< 0.05	NA	< 0.05	101%	50%	140%	112%	50%	140%	96%	50%	140%
Fluoranthene	7599332		< 0.05	< 0.05	NA	< 0.05	102%	50%	140%	110%	50%	140%	104%	50%	140%
Pyrene	7599332		< 0.05	< 0.05	NA	< 0.05	101%	50%	140%	110%	50%	140%	104%	50%	140%
Benz(a)anthracene	7599332		< 0.05	< 0.05	NA	< 0.05	87%	50%	140%	98%	50%	140%	93%	50%	140%
Chrysene	7599332		< 0.05	< 0.05	NA	< 0.05	93%	50%	140%	104%	50%	140%	95%	50%	140%
Benzo(b)fluoranthene	7599332		< 0.05	< 0.05	NA	< 0.05	100%	50%	140%	125%	50%	140%	108%	50%	140%
Benzo(k)fluoranthene	7599332		< 0.05	< 0.05	NA	< 0.05	122%	50%	140%	140%	50%	140%	125%	50%	140%
Benzo(a)pyrene	7599332		< 0.05	< 0.05	NA	< 0.05	119%	50%	140%	129%	50%	140%	105%	50%	140%
Indeno(1,2,3-cd)pyrene	7599332		< 0.05	< 0.05	NA	< 0.05	108%	50%	140%	89%	50%	140%	83%	50%	140%
Dibenz(a,h)anthracene	7599332		< 0.05	< 0.05	NA	< 0.05	106%	50%	140%	91%	50%	140%	86%	50%	140%
Benzo(g,h,i)perylene	7599332		< 0.05	< 0.05	NA	< 0.05	101%	50%	140%	84%	50%	140%	81%	50%	140%
2-and 1-methyl Naphthalene	7599332		< 0.05	< 0.05	NA	< 0.05	119%	50%	140%	100%	50%	140%	88%	50%	140%

Comments: When the average of the sample and duplicate results is less than 5x the RDL, the Relative Percent Difference (RPD) will be indicated as Not Applicable (NA).

Certified By:



Method Summary

CLIENT NAME: WSP CANADA INC.

PROJECT: 161-06382-00-101-980

SAMPLING SITE: Phase Two ESA. Orleans GW Monitoring.

AGAT WORK ORDER: 16Z101291

ATTENTION TO: Matthieu Rochon

SAMPLED BY: Kathryn Maton

PARAMETER	AGAT S.O.P	LITERATURE REFERENCE	ANALYTICAL TECHNIQUE
Soil Analysis			
Antimony	MET-93-6103	EPA SW-846 3050B & 6020A	ICP-MS
Arsenic	MET-93-6103	EPA SW-846 3050B & 6020A	ICP-MS
Barium	MET-93-6103	EPA SW-846 3050B & 6020A	ICP-MS
Beryllium	MET-93-6103	EPA SW-846 3050B & 6020A	ICP-MS
Boron	MET-93-6103	EPA SW-846 3050B & 6020A	ICP-MS
Boron (Hot Water Soluble)	MET-93-6104	EPA SW 846 6010C; MSA, Part 3, Ch.21	ICP/OES
Cadmium	MET-93-6103	EPA SW-846 3050B & 6020A	ICP-MS
Chromium	MET-93-6103	EPA SW-846 3050B & 6020A	ICP-MS
Cobalt	MET-93-6103	EPA SW-846 3050B & 6020A	ICP-MS
Copper	MET-93-6103	EPA SW-846 3050B & 6020A	ICP-MS
Lead	MET-93-6103	EPA SW-846 3050B & 6020A	ICP-MS
Molybdenum	MET-93-6103	EPA SW-846 3050B & 6020A	ICP-MS
Nickel	MET-93-6103	EPA SW-846 3050B & 6020A	ICP-MS
Selenium	MET-93-6103	EPA SW-846 3050B & 6020A	ICP-MS
Silver	MET-93-6103	EPA SW-846 3050B & 6020A	ICP-MS
Thallium	MET-93-6103	EPA SW-846 3050B & 6020A	ICP-MS
Uranium	MET-93-6103	EPA SW-846 3050B & 6020A	ICP-MS
Vanadium	MET-93-6103	EPA SW-846 3050B & 6020A	ICP-MS
Zinc	MET-93-6103	EPA SW-846 3050B & 6020A	ICP-MS
Chromium VI	INOR-93-6029	SM 3500 B; MSA Part 3, Ch. 25	SPECTROPHOTOMETER
Cyanide	INOR-93-6052	MOE CN-3015 & E 3009 A; SM 4500 CN	TECHNICON AUTO ANALYZER
Mercury	MET-93-6103	EPA SW-846 3050B & 6020A	ICP-MS
Electrical Conductivity	INOR-93-6036	McKeague 4.12, SM 2510 B	EC METER
Sodium Adsorption Ratio	INOR-93-6007	McKeague 4.12 & 3.26 & EPA SW-846 6010B	ICP/OES
pH, 2:1 CaCl ₂ Extraction	INOR-93-6031	MSA part 3 & SM 4500-H+ B	PH METER

Method Summary

CLIENT NAME: WSP CANADA INC.

PROJECT: 161-06382-00-101-980

SAMPLING SITE:Phase Two ESA. Orleans GW Monitoring.

AGAT WORK ORDER: 16Z101291

ATTENTION TO: Matthieu Rochon

SAMPLED BY:Kathryn Maton

PARAMETER	AGAT S.O.P	LITERATURE REFERENCE	ANALYTICAL TECHNIQUE
Trace Organics Analysis			
Naphthalene	ORG-91-5106	EPA SW846 3541 & 8270	GC/MS
Acenaphthylene	ORG-91-5106	EPA SW846 3541 & 8270	GC/MS
Acenaphthene	ORG-91-5106	EPA SW846 3541 & 8270	GC/MS
Fluorene	ORG-91-5106	EPA SW846 3541 & 8270	GC/MS
Phenanthrene	ORG-91-5106	EPA SW846 3541 & 8270	GC/MS
Anthracene	ORG-91-5106	EPA SW846 3541 & 8270	GC/MS
Fluoranthene	ORG-91-5106	EPA SW846 3541 & 8270	GC/MS
Pyrene	ORG-91-5106	EPA SW846 3541 & 8270	GC/MS
Benz(a)anthracene	ORG-91-5106	EPA SW846 3541 & 8270	GC/MS
Chrysene	ORG-91-5106	EPA SW846 3541 & 8270	GC/MS
Benzo(b)fluoranthene	ORG-91-5106	EPA SW846 3541 & 8270	GC/MS
Benzo(k)fluoranthene	ORG-91-5106	EPA SW846 3541 & 8270	GC/MS
Benzo(a)pyrene	ORG-91-5106	EPA SW846 3541 & 8270	GC/MS
Indeno(1,2,3-cd)pyrene	ORG-91-5106	EPA SW846 3541 & 8270	GC/MS
Dibenz(a,h)anthracene	ORG-91-5106	EPA SW846 3541 & 8270	GC/MS
Benzo(g,h,i)perylene	ORG-91-5106	EPA SW846 3541 & 8270	GC/MS
2-and 1-methyl Naphthalene	ORG-91-5106	EPA SW846 3541 & 8270	GC/MS
Moisture Content	ORG-91-5106	EPA SW-846 3541 & 8270	BALANCE
Chrysene-d12	ORG-91-5106	EPA SW846 3541 & 8270	GC/MS
Benzene	VOL-91-5009	EPA SW-846 5035 & 8260	P & T GC/MS
Toluene	VOL-91-5009	EPA SW-846 5035 & 8260	P & T GC/MS
Ethylbenzene	VOL-91-5009	EPA SW-846 5035 & 8260	P & T GC/MS
Xylene Mixture	VOL-91-5009	EPA SW-846 5035 & 8260	P & T GC/MS
F1 (C6 to C10)	VOL-91-5009	CCME Tier 1 Method	P & T GC/FID
F1 (C6 to C10) minus BTEX	VOL-91-5009	CCME Tier 1 Method	P & T GC/FID
F2 (C10 to C16)	VOL-91-5009	CCME Tier 1 Method, EPA SW846 8015	GC / FID
F3 (C16 to C34)	VOL-91-5009	CCME Tier 1 Method, EPA SW846 8015	GC / FID
F4 (C34 to C50)	VOL-91-5009	CCME Tier 1 Method, EPA SW846 8015	GC / FID
Gravimetric Heavy Hydrocarbons	VOL-91-5009	CCME Tier 1 Method	BALANCE
Moisture Content	VOL-91-5009	CCME Tier 1 Method	BALANCE
Terphenyl	VOL-91-5009		GC/FID
F1 (C6 to C10)	VOL-91-5009	CCME Tier 1 Method	GC / FID
F1 (C6 to C10) minus BTEX	VOL-91-5009	CCME Tier 1 Method	GC / FID
F2 (C10 to C16)	VOL-91-5009	CCME Tier 1 Method	GC / FID
F2 (C10 to C16) minus Naphthalene	VOL-91-5009	CCME Tier 1 Method	GC / FID
F3 (C16 to C34)	VOL-91-5009	CCME Tier 1 Method	GC / FID
F3 (C16 to C34) minus PAHs	VOL-91-5009	CCME Tier 1 Method	GC / FID
F4 (C34 to C50)	VOL-91-5009	CCME Tier 1 Method	GC / FID
Gravimetric Heavy Hydrocarbons	VOL-91-5009	CCME Tier 1 Method	GRAVIMETRIC ANALYSIS



AGAT

Laboratories

464442/464947
434952
300

5635 Coopers Avenue
Mississauga, Ontario L4Z 1Y2
Ph: 905.712.5100 Fax: 905.712.5122
web@at.agatlabs.com

Chain of Custody Record

If this is a Drinking Water sample, please use Drinking Water Chain of Custody Form (portable water intended for human consumption)

Report Information:

Company: WSP Canada Inc.
Contact: Kathryn Walker / Matthew Rakon
Address: 500 Greber & Stage
Bathurst St
613-243-2237 Fax: 613-243-2249
Reports to be sent to: Kathryn.walker@wspgroup.com
1. Email: Matthew.Rakon@wspgroup.com
2. Email:

Regulatory Requirements:

(Please check all appropriate boxes)

☒ Regulation 153/04
Table 1 (acute One)

☐ Sewer Use
☐ Sanitary

☐ Regulation 558
☐ CCME

☒ Agriculture
☐ Pesticide/Park

☐ Storm

☐ Prov. Water Quality
Objectives (PMOQ)

Soil Texture (check One)
☒ Coarse
☐ Fine

Region: Indicate One

☐ Other

Is this submission for a
Record of Site Condition?

☒ Yes ☐ No

Report Guideline on
Certificate of Analysis

☒ Yes ☐ No

AGAT Quote #:

PO:

Please note: a sample number is not provided. Client will be billed full price for analysis.

Invoice Information:

Bill To Same: Yes ☒ No ☐

Company:
Contact:
Address:
Email:

161-06382-00-101-980

Sample Matrix

Legend

B Biota
GW Ground Water
O Oil
P Paint
S Soil
SD Sediment
SW Surface Water

(Check Applicable)

Metals and Inorganics

Metal Scan

Hydride Forming Metals

Client Custom Metals

ORPs: ☐ B-HWS ☐ Cl ☐ CN
☐ Cr⁶⁺ ☐ EC ☐ FOC ☐ NO₂/NO₃
☐ Total N ☐ Hg ☐ pH ☐ SAR

Nutrients: ☐ TP ☐ NH₃ ☐ TKN
☐ NO₂ ☐ NO₃ ☐ NO₂/NO₃

Volatiles: ☐ VOC ☐ BTEX ☐ THM

CCME Fractions 1 to 4

ABNs

PAHs

Chlorophenols

PCBs

Organochlorine Pesticides

TCLP Metals/Inorganics

Sewer Use

153 METALS 93-101
F2-F4 91-107

Sample Identification	Date Sampled	Time Sampled	# of Containers	Sample Matrix	Comments / Special Instructions
BH16-1-1B	3/6/16	9:03am	4	Soil	1x 150, 1x 120, 1x 2x415.
BH16-1-2A			4		2x 2x415, 1x 250.
BH16-1-2B			4		2x 2x415, 1x 250, 1x 120.
BH16-2-2A			3		1x 250, 2x 2x415
BH16-2-2B			4		1x 250, 2x 2x415, 1x 120
BH16-3-1B			4		1x 250, 2x 2x415, 1x 120
BH16-3-2A			4		
BH16-3-2B			4		
BH16-4-1B			4		

Sampled / Analyzed By (Print Name and Sign)	Date	Time	Sampled / Analyzed By (Print Name and Sign)	Date	Time
Kathryn Walker	6/6/16	7:30pm	Matthew Rakon	6/6/16	8:00
Matthew Rakon	6/6/16	7:30pm	Matthew Rakon	6/6/16	11:05

Laboratory Use Only

Work Order #: 16T101291

Cooler Quantity: 3

Arrival Temperature: 4.1/4.9/5.5/3.5/4.5/4.3
on ice 5.5/5.2/5.0

Custody Seal Intact: ☐ Yes ☐ No ☐ N/A

Notes:

Turn Rush
RUSH-3 DAY
AS per client email

3 Business Days ☐ 2 Business Days ☐ 1 Business Day ☐

OR Date Required (Rush Surcharges May Apply):

Please provide prior notification for rush TAT
*TAT is exclusive of weekends and statutory holidays



AGAT

Laboratories

5835 Coopers Avenue
Mississauga, Ontario L4Z 1Y2
Ph: 905.712.5100 Fax 905.712.5122
web@atn.agatlabs.com

Chain of Custody Record

If this is a Drinking Water sample, please use Drinking Water Chain of Custody Form (goodie water intended for human consumption)

Report Information:

Company: WSP
Contact: Kathryn Mahon / Matthew Rochon
Address: 500 Gower Ave
613-617-9237 Fax: 613-617-9237
Phone: Kathryn.Mahon@wspgroup.com
Reports to be sent to: matthew.rochon@wspgroup.com
1. Email: matthew.rochon@wspgroup.com
2. Email:

Regulatory Requirements:

(Please check all applicable boxes)

☒ Regulation 153/04
☐ Sewer Use
☐ Sanitary
☐ COME
☐ Prov. Water Quality Objectives (PM10)
☐ Other

Soil Texture (check one):
☒ Coarse
☐ Fine
Region: Indicate One

Project Information:

Project: Phase Two ESA
Site Location: 3636 Innes Rd, Ottawa
Sampled By: K.M.
AGAT Quote #:
PO: Phase Two

Invoice Information:

Company: Bill To Same: Yes ☒ No ☐
Contact: Yes ☒ No ☐
Address: Yes ☒ No ☐
Email: Yes ☒ No ☐

Sample Matrix

☐ B Biot
☐ GW Ground Water
☐ Oil
☐ Paint
☐ S Soil
☐ SD Sediment
☐ SW Surface Water

Is this submission for a Record of Site Condition?
☒ Yes ☐ No

Report Guidelines on Certificate of Analysis
☒ Yes ☐ No

Laboratory Use Only

Work Order #: 102101291

Cooler Quantity: 1

Arrival Temperatures: 1

Custody Seal Intact: ☐ Yes ☐ No ☐ N/A

Notes: 1

Turnaround Time (TAT) Required:
☐ Regular TAT ☐ 5 to 7 Business Days
☐ Rush TAT (Rush Surcharges Apply)

☐ 3 Business Days ☐ 2 Business Days ☐ 1 Business Day

OR Date Required (Rush Surcharges May Apply):

Please provide prior notification for rush TAT
*TAT is exclusive of weekends and statutory holidays

Sample Identification	Date Sampled	Time Sampled	# of Containers	Sample Matrix	Comments/ Special Instructions	Metals	Metal Scan	Hydride Forming Metals	Client Custom Metals	ORPs: ☐ Cr ⁶⁺ ☐ Total	Nutrients ☐ NO ₃	Volatiles	CCME Fractions	ABNs	PAHs	Chlorophenols	PCBs	Organochlorine Pesticides	TCLP Metals/Inorganics	Sewer Use
BH16-4-2A	31/05/16	10am	4	Soil	2xvals, 1x250, 1x120.															
BH16-4-2B			2		Initial, 1x20															
BH16-4-102K			4		2xvals, 1x250, 1x120															
BH16-5-1B			2		Initial, 1x250															
BH16-5-101B			2		Initial, 1x120.															
BH16-5-2B			4		2xvals, 1x120, 1x250															
BH16-5-2A			4		Initial, 1x20															
BH16-6-2A																				
BH16-6-1B																				
BH16-6-2B																				

Signature: Kathryn Mahon Date: 31/05/16 Time: 7:30pm Signature: Matthew Rochon Date: 31/05/16 Time: 8:00
Sample Received By: Simon Signature: Simon Date: 14/6/14 Time: 11:05 N°: T 018590
Page: 2 of 6

AGAT Laboratories

5835 Coopers Avenue
Mississauga, Ontario L4Z 1Y2
Ph: 905.712.5100 Fax: 905.712.5122
web@agatlabs.com

Chain of Custody Record

If this is a Drinking Water sample, please use Drinking Water Chain of Custody Form (public water intended for human consumption)

Report Information:

Company: WSP
Contact: Kathryn Weber / Nathalie Kordon
Address: 5800 Besset
613-613-9237 Fax: 613-613-9237

Phone: Kathryn Weber
Reports to be sent to: Kathryn Weber
1. Email: Kathryn.Weber@wspgroup.com
2. Email: Nathalie.Kordon@wspgroup.com

Project Information:

Project: Phase Two ESH
Site Location: 3636 Lakeshore Blvd E
Sampled By: AKHAKON
AGAT Quote #: PO:

Invoice Information:

Company: AKHAKON
Contact: AKHAKON
Address: AKHAKON
Email: AKHAKON

Regulatory Requirements:

☒ Regulation 153/04
☐ Sewer Use
☐ Regulation 558
☐ Sanitary
☐ Storm
☐ CCME
☐ Prox. Water Quality Objectives (PWQO)
☐ Other

Is this submission for a Record of Site Condition?
☒ Yes ☐ No

Report Guideline on Certificate of Analysis

☒ Yes ☐ No

Legend

B Biota
GW Ground Water
O Oil
P Paint
S Soil
SD Sediment
SW Surface Water

Metals and Inorganics
Metal Scan
Hydride Forming Metals
Client Custom Metals

ORPs: ☐ B-HWS ☐ Cl ☐ CN
☐ C₆H₆ ☐ EC ☐ FOC ☐ NO₃/NO₂
☐ Total N ☐ Hg ☐ pH ☐ SAR
Nutrients: ☐ TP ☐ NH₃ ☐ TKN
☐ NO₃ ☐ NO₂ ☐ NO₂/NO₃
Volatiles: ☐ VOC ☐ BTEX ☐ THM
CCME Fractions 1 to 4
ABNs
PAHs
Chlorophenols
PCBs
Organochlorine Pesticides
TCLP Metals/Inorganics
Sewer Use

153 Metals 93-101

Sample Identification	Date Sampled	Time Sampled	# of Containers	Sample Matrix	Comments/Special Instructions
BH16-9-2A	Bilbelle	8am.	1		250.
BH16-9-2B					
BH16-9-3A					
BH16-9-3B					
BH16-9-4					
BH16-9-5					
BH16-10-4					
BH16-10-2A					
BH16-10-2B					
BH16-10-3A					
BH16-10-3B					

Laboratory Use Only

Work Order #: 162101291

Cooler Quantity: 1

Arrival Temperature: 1

Custody Seal Intact: ☒ Yes ☐ No ☐ N/A

Notes:

Turnaround Time (TAT) Required:

Regular TAT ☒ 3 to 7 Business Days
Rush TAT (rush surcharges apply) ☐ 3 Business Days ☐ 2 Business Days ☐ 1 Business Day

OR Date Required (Rush Surcharges May Apply):

Please provide prior notification for rush TAT
*TAT is exclusive of weekends and statutory holidays

Signature: Kathryn Weber Date: 01/06/16 Time: 7:30pm Page: 4 of 6

Signature: AKHAKON Date: 01/06/16 Time: 11:05 No: T 018532



GGAT Laboratories

5835 Coopers Avenue
Mississauga, Ontario L4Z 1Y2
Ph: 905.712.5100 Fax: 905.712.5122
web@earth.agatlabs.com

Chain of Custody Record

If this is a Drinking Water sample, please use Drinking Water Chain of Custody Form (potable water intended for human consumption)

Report Information:

Company: USP
Contact: Kathryn Watson/Matthew Rochon
Address: 3636 Jones Rd. #102
500 Guelph, ON G1G 4W2
613-613-9232 Fax: _____

Phone: _____

Report to be sent to:

1. Email: Kathryn.Watson@usppg.com

2. Email: matthew.rochon@usppg.com

Project: Phase Two ESR

Site Location: 3636 Jones Rd. #102

Sampled By: _____

AGAT Quote #: _____ PO: _____

Invoice Information:

Company: _____
Contact: _____
Address: _____
Email: _____

Bill To Same: Yes ☒ No ☐

Regulatory Requirements:

(Please check all applicable boxes)

Regulation 153/04 ☒ Sewer Use ☐
Table Indicate One ☐ Sanitary ☐
☐ Lind/Cont ☐ CCME ☐
☐ Beer/Park ☐ Storm ☐
☐ Agriculture ☐ Prov. Water Quality Objectives (PWQO) ☐
Soil Temperature (core One) ☒ Region Indicate One ☐ Other Indicate One ☐

Is this submission for a Record of Site Condition? ☒ Yes ☐ No

Report Guideline on Certificate of Analysis ☒ Yes ☐ No

Sample Matrix Legend

B Biota
GW Ground Water
O Oil
P Paint
S Soil
SD Sediment
SW Surface Water

Comments/Special Instructions

Metals and Inorganics
Metal Scan
Hydride Forming Metals
Client Custom Metals

ORPs: ☐ B-HWS ☐ Cl ☐ CN
☐ Cr⁶⁺ ☐ EC ☐ FOC ☐ NO₃/NO₂
☐ Total N ☐ Hg ☐ pH ☐ SAR
Nutrients: ☐ TP ☐ NH₃ ☐ TKN
☐ NO₃ ☐ NO₂ ☐ NO₃/NO₂
Volatiles: ☐ VOC ☐ BTEX ☐ THM

CCME Fractions 1 to 4
ABNs
PAHs
Chlorophenols
PCBs
Organochlorine Pesticides
TCLP Metals/Inorganics
Sewer Use

(Check Applicable)
153 Metals 93-101

Laboratory Use Only

Work Order #: 162101291

Order Quantity: _____

Arrival Temperatures: _____

Custody Seal Intact ☐ Yes ☐ No ☐ N/A

Notes: _____

Turnaround Time (TAT) Required:

Regular TAT ☒ 5 to 7 Business Days

Rush TAT (must be arranged in advance)

☐ 3 Business Days ☐ 2 Business Days ☐ 1 Business Day

OR Date Required (Rush Surcharges May Apply): _____

Please provide prior notification for rush TAT
*TAT is exclusive of weekends and statutory holidays

Sample Identification	Date Sampled	Time Sampled	# of Containers	Sample Matrix	Comments/Special Instructions
BH16-10-11A	01/06/16	1 PM	1	Soil	
BH16-10-11B					
BH16-11-1					
BH16-11-2A					
BH16-11-2B					
BH16-11-3A					
BH16-11-3B					
BH16-11-4A					
BH16-11-4B					
BH16-12-1					
BH16-12-2A					

Signature: Kathryn Watson Date: 01/06/16 Time: 7:30 PM Sampled by: (Signature)
Signature: Matth Date: 01/06/16 Time: 8:10 PM Sampled by: (Signature)
Print Copy - Client | Yellow Copy - AGAT | White Copy - AGAT
Page 5 of 6
018578



AGAT

Laboratories

5835 Coopers Avenue
Mississauga, Ontario L4Z 1Y2
Ph: 905.712.5100 Fax: 905.712.5122
web@atn.agatlabs.com

Chain of Custody Record

If this is a Drinking Water sample, please use Drinking Water Chain of Custody Form (portable water intended for human consumption)

Report Information:

Company: WSP
Contact: Kathryn Baker/Matthew Baker
Address: 500 Guelph St.
Guelph, ON, N1H 6A1
613-617-9237 Fax: _____

Phone:

1. Email: Kathryn.Baker@wspgroup.com
2. Email: matthew.baker@wspgroup.com

Project Information:

Project: Phase 11
Site Location: 3636 Wines Rd, Ottawa
Sampled By: KW
ACU Quote #: _____ PO: _____

Invoice Information:

Company: _____ Bill To Same: ☒ Yes ☐ No
Contact: _____
Address: _____
Email: _____

Regulatory Requirements:

Regulation 153/04 ☐ Indicate One
☐ Sewer Use ☐ Regulation 558
☐ Sanitary ☐ COME
☐ Odour/Am ☐ Storm
☐ Disinfectant ☐ Pow. Water Quality Objectives (PWQO)
☐ Agriculture ☐ Other
Soil Texture (check one) ☐ Region: _____
☐ Fine ☐ Coarse ☐ Indicate One

Is this submission for a Record of Site Condition?

☒ Yes ☐ No

Report Guideline on Certificate of Analysis

☒ Yes ☐ No

Sample Matrix Legend

B Bids
GW Ground Water
O Oil
P Paint
S Soil
SD Sediment
SW Surface Water

Metals and Inorganics
Metal Scan
Hydride Forming Metals
Client Custom Metals
ORPs: ☐ B-HWS ☐ Cl ☐ CN
☐ Cr⁶⁺ ☐ EC ☐ FOC ☐ NO₂/NO₃
☐ Total N ☐ Hg ☐ pH ☐ SAR
Nutrients: ☐ TP ☐ NH₃ ☐ TKN
☐ NO₂ ☐ NO₃ ☐ NO₂/NO₃
Volatiles: ☐ VOC ☐ BTEX ☐ THM
CCME Fractions 1 to 4
ABNs
PAHs
Chlorophenols
PCBs
Organochlorine Pesticides
TCLP Metals/Inorganics
Sewer Use

(Check Applicable)

153 Metals 93-101

Laboratory Use Only

Work Order #: 162101291

Cooler Quantity: _____

Arrival Temperature: _____

Custody Seal Intact: ☐ Yes ☐ No ☐ N/A

Notes: _____

Turnaround Time (TAT) Required:

Regular TAT ☒ 5 to 7 Business Days
Rush TAT (rush Surcharge Applies) ☐ 3 Business Days ☐ 2 Business Days ☐ 1 Business Day

OR Date Required (Rush Surcharges May Apply): _____

Please provide prior notification for rush TAT
*TAT is exclusive of weekends and statutory holidays

Sample Identification	Date Sampled	Time Sampled	# of Containers	Sample Matrix	Comments/Special Instructions
BH16-12-28	01/16/16	11PM	1	Soil	
BH16-12-3A					
BH16-12-3B					
BH16-12-4A					
BH16-13-1					
BH16-13-2A					
BH16-13-2B					
BH16-13-3A					
BH16-13-3B					
BH16-13-4					

Signature of Analyst: Kathryn Baker Date: 01/16/16 Time: 7:30pm Samples Received By: Client Date: 01/16/16 Time: 11:00 Page: 6 of 6
Signature of Client: [Signature] Date: 01/16/16 Time: 11:05 No: T018579

CLIENT NAME: WSP CANADA INC.
500, BOUL GREBER 3E ETAGE
GATINEAU, QC J8T7W3
(819) 243-2827

ATTENTION TO: Matthieu Rochon

PROJECT: 161-06382-00 Phase Two ESA

AGAT WORK ORDER: 16Z102773

TRACE ORGANICS REVIEWED BY: Gylhan Yalamova, Report Reviewer

WATER ANALYSIS REVIEWED BY: Mike Muneswar, BSc (Chem), Senior Inorganic Analyst

DATE REPORTED: Jun 13, 2016

PAGES (INCLUDING COVER): 10

VERSION*: 1

Should you require any information regarding this analysis please contact your client services representative at (905) 712-5100

*NOTES

All samples will be disposed of within 30 days following analysis. Please contact the lab if you require additional sample storage time.



AGAT Laboratories

Certificate of Analysis

AGAT WORK ORDER: 16Z102773

PROJECT: 161-06382-00 Phase Two ESA

5835 COOPERS AVENUE
MISSISSAUGA, ONTARIO
CANADA L4Z 1Y2
TEL (905)712-5100
FAX (905)712-5122
<http://www.agatlabs.com>

CLIENT NAME: WSP CANADA INC.

SAMPLING SITE: 3636 Innes Road, Ottawa

ATTENTION TO: Matthieu Rochon

SAMPLED BY: Kathryn Maton

O. Reg. 153(511) - PAHs (Water)

DATE RECEIVED: 2016-06-07

DATE REPORTED: 2016-06-13

		SAMPLE DESCRIPTION:		MW16-3	MW16-5	MW16-8	MW16-108
		SAMPLE TYPE:		Water	Water	Water	Water
		DATE SAMPLED:		6/7/2016	6/7/2016	6/7/2016	6/7/2016
Parameter	Unit	G / S	RDL	7615636	7615659	7615681	7615693
Naphthalene	µg/L	0.20	<0.20	<0.20	<0.20	<0.20	<0.20
Acenaphthylene	µg/L	0.20	<0.20	<0.20	<0.20	<0.20	<0.20
Acenaphthene	µg/L	0.20	<0.20	<0.20	<0.20	<0.20	<0.20
Fluorene	µg/L	0.20	<0.20	<0.20	<0.20	<0.20	<0.20
Phenanthrene	µg/L	0.10	<0.10	<0.10	<0.10	<0.10	<0.10
Anthracene	µg/L	0.10	<0.10	<0.10	<0.10	<0.10	<0.10
Fluoranthene	µg/L	0.20	<0.20	<0.20	<0.20	<0.20	<0.20
Pyrene	µg/L	0.20	<0.20	<0.20	<0.20	<0.20	<0.20
Benz(a)anthracene	µg/L	0.20	<0.20	<0.20	<0.20	<0.20	<0.20
Chrysene	µg/L	0.10	<0.10	<0.10	<0.10	<0.10	<0.10
Benzo(b)fluoranthene	µg/L	0.10	<0.10	<0.10	<0.10	<0.10	<0.10
Benzo(k)fluoranthene	µg/L	0.10	<0.10	<0.10	<0.10	<0.10	<0.10
Benzo(a)pyrene	µg/L	0.01	<0.01	<0.01	<0.01	<0.01	<0.01
Indeno(1,2,3-cd)pyrene	µg/L	0.20	<0.20	<0.20	<0.20	<0.20	<0.20
Dibenz(a,h)anthracene	µg/L	0.20	<0.20	<0.20	<0.20	<0.20	<0.20
Benzo(g,h,i)perylene	µg/L	0.20	<0.20	<0.20	<0.20	<0.20	<0.20
2-and 1-methyl Naphthalene	µg/L	0.20	<0.20	<0.20	<0.20	<0.20	<0.20
Surrogate	Unit	Acceptable Limits					
Chrysene-d12	%	50-140	118	92	103	116	

Comments: RDL - Reported Detection Limit; G / S - Guideline / Standard

7615636-7615693 Note: The result for Benzo(b)Flouranthene is the total of the Benzo(b)&(j)Flouranthene isomers because the isomers co-elute on the GC column.

Certified By:



AGAT Laboratories

Certificate of Analysis

AGAT WORK ORDER: 16Z102773

PROJECT: 161-06382-00 Phase Two ESA

5835 COOPERS AVENUE
MISSISSAUGA, ONTARIO
CANADA L4Z 1Y2
TEL (905)712-5100
FAX (905)712-5122
<http://www.agatlabs.com>

CLIENT NAME: WSP CANADA INC.

SAMPLING SITE: 3636 Innes Road, Ottawa

ATTENTION TO: Matthieu Rochon

SAMPLED BY: Kathryn Maton

O. Reg. 153(511) - PHCs F1 - F4 (Water) - BTEX/F1

DATE RECEIVED: 2016-06-07

DATE REPORTED: 2016-06-13

		SAMPLE DESCRIPTION:		Trip Blank
		SAMPLE TYPE:		Water
		DATE SAMPLED:		5/25/2016
Parameter	Unit	G / S	RDL	7615703
Benzene	µg/L		0.20	<0.20
Toluene	µg/L		0.20	<0.20
Ethylbenzene	µg/L		0.10	<0.10
Xylene Mixture	µg/L		0.20	<0.20
F1 (C6 to C10)	µg/L		25	<25
F1 (C6 to C10) minus BTEX	µg/L		25	<25

Comments: RDL - Reported Detection Limit; G / S - Guideline / Standard
7615703 The C6-C10 fraction is calculated using Toluene response factor.
Total C6-C10 results are corrected for BTEX contributions.
This method complies with the Reference Method for the CWS PHC and is validated for use in the laboratory.
nC6 and nC10 response factors are within 30% of Toluene response factor.
Extraction and holding times were met for this sample.
Fractions 1-4 are quantified with the contribution of PAHs. Under Ontario Regulation 153/04, results are considered valid without determining the PAH contribution if not requested by the client.
NA = Not Applicable

Certified By:



Certificate of Analysis

AGAT WORK ORDER: 16Z102773

PROJECT: 161-06382-00 Phase Two ESA

5835 COOPERS AVENUE
MISSISSAUGA, ONTARIO
CANADA L4Z 1Y2
TEL (905)712-5100
FAX (905)712-5122
<http://www.agatlabs.com>

CLIENT NAME: WSP CANADA INC.

SAMPLING SITE: 3636 Innes Road, Ottawa

ATTENTION TO: Matthieu Rochon

SAMPLED BY: Kathryn Maton

O. Reg. 153(511) - PHCs F1 - F4 (with PAHs) (Water)

DATE RECEIVED: 2016-06-07

DATE REPORTED: 2016-06-13

		SAMPLE DESCRIPTION:		MW16-3	MW16-5	MW16-8	MW16-108
		SAMPLE TYPE:		Water	Water	Water	Water
		DATE SAMPLED:		6/7/2016	6/7/2016	6/7/2016	6/7/2016
Parameter	Unit	G / S	RDL	7615636	7615659	7615681	7615693
Benzene	µg/L	0.20	<0.20	1.1	<0.20	<0.20	<0.20
Toluene	µg/L	0.20	<0.20	0.39	<0.20	<0.20	<0.20
Ethylbenzene	µg/L	0.10	<0.10	15	<0.10	<0.10	<0.10
Xylene Mixture	µg/L	0.20	<0.20	4.2	<0.20	<0.20	<0.20
F1 (C6 to C10)	µg/L	25	<25	380	<25	<25	<25
F1 (C6 to C10) minus BTEX	µg/L	25	<25	360	<25	<25	<25
F2 (C10 to C16)	µg/L	100	<100	530	<100	<100	<100
F2 (C10 to C16) minus Naphthalene	µg/L	100	<100	530	<100	<100	<100
F3 (C16 to C34)	µg/L	100	<100	390	<100	<100	<100
F3 (C16 to C34) minus PAHs	µg/L	100	<100	390	<100	<100	<100
F4 (C34 to C50)	µg/L	100	<100	<100	<100	<100	<100
Gravimetric Heavy Hydrocarbons	µg/L	500	NA	NA	NA	NA	NA
Surrogate	Unit	Acceptable Limits					
Terphenyl	%	60-140	80	89	89	89	68

Comments: RDL - Reported Detection Limit; G / S - Guideline / Standard

7615636-7615693 The C6-C10 fraction is calculated using Toluene response factor.

The C10 - C16, C16 - C34, and C34 - C50 fractions are calculated using the average response factor for n-C10, n-C16, and n-C34.

Gravimetric Heavy Hydrocarbons are not included in the Total C16 - C50 and are only determined if the chromatogram of the C34 - C50 Hydrocarbons indicated that hydrocarbons >C50 are present.

The chromatogram has returned to baseline by the retention time of nC50.

Total C6-C50 results are corrected for BTEX and PAH contributions.

This method complies with the Reference Method for the CWS PHC and is validated for use in the laboratory.

nC6 and nC10 response factors are within 30% of Toluene response factor.

nC10, nC16 and nC34 response factors are within 10% of their average.

C50 response factor is within 70% of nC10 + nC16 nC34 average.

Linearity is within 15%.

Extraction and holding times were met for this sample.

Certified By:



Certificate of Analysis

AGAT WORK ORDER: 16Z102773

PROJECT: 161-06382-00 Phase Two ESA

5835 COOPERS AVENUE
MISSISSAUGA, ONTARIO
CANADA L4Z 1Y2
TEL (905)712-5100
FAX (905)712-5122
<http://www.agatlabs.com>

CLIENT NAME: WSP CANADA INC.

SAMPLING SITE: 3636 Innes Road, Ottawa

ATTENTION TO: Matthieu Rochon

SAMPLED BY: Kathryn Maton

O. Reg. 153(511) - Metals & Inorganics (Water)

DATE RECEIVED: 2016-06-07

DATE REPORTED: 2016-06-13

		SAMPLE DESCRIPTION:		MW16-3	MW16-5	MW16-8	MW16-108
		SAMPLE TYPE:		Water	Water	Water	Water
		DATE SAMPLED:		6/7/2016	6/7/2016	6/7/2016	6/7/2016
Parameter	Unit	G / S	RDL	7615636	7615659	7615681	7615693
Antimony	µg/L	1.0	<1.0	<1.0	<1.0	<1.0	<1.0
Arsenic	µg/L	1.0	<1.0	1.9	<1.0	<1.0	<1.0
Barium	µg/L	2.0	89.7	166	224	187	
Beryllium	µg/L	0.5	<0.5	<0.5	<0.5	<0.5	<0.5
Boron	µg/L	10.0	48.5	41.9	21.5	16.3	
Cadmium	µg/L	0.2	<0.2	<0.2	<0.2	<0.2	<0.2
Chromium	µg/L	2.0	2.4	4.9	2.6	5.0	
Cobalt	µg/L	0.5	<0.5	3.3	0.9	0.8	
Copper	µg/L	1.0	2.0	<1.0	1.1	<1.0	
Lead	µg/L	0.5	<0.5	<0.5	<0.5	<0.5	<0.5
Molybdenum	µg/L	0.5	0.6	1.2	<0.5	<0.5	
Nickel	µg/L	1.0	1.3	<1.0	1.4	<1.0	<1.0
Selenium	µg/L	1.0	1.6	<1.0	<1.0	<1.0	<1.0
Silver	µg/L	0.2	<0.2	<0.2	<0.2	<0.2	<0.2
Thallium	µg/L	0.3	<0.3	<0.3	<0.3	<0.3	<0.3
Uranium	µg/L	0.5	1.3	5.0	4.4	3.7	
Vanadium	µg/L	0.4	2.4	1.5	4.8	4.8	
Zinc	µg/L	5.0	<5.0	<5.0	<5.0	<5.0	<5.0
Mercury	µg/L	0.02	<0.02	<0.02	<0.02	<0.02	<0.02
Chromium VI	µg/L	5	<5	<5	<5	<5	<5
Cyanide	µg/L	2	<2	<2	<2	<2	<2
Sodium	µg/L	2500	63200	65600	66900	65200	
Chloride	µg/L	1000	133000	286000	341000	358000	
Electrical Conductivity	µS/cm	2	1340	1940	1900	1970	
pH	pH Units	NA	7.96	7.89	8.04	8.05	

Comments: RDL - Reported Detection Limit; G / S - Guideline / Standard

7615636-7615693 Elevated RDLs for Anions & Cations indicate the degree of dilution prior to analysis in order to keep analytes within the calibration range of the instruments and to reduce matrix interferences.

Certified By:

Quality Assurance

CLIENT NAME: WSP CANADA INC.

PROJECT: 161-06382-00 Phase Two ESA

SAMPLING SITE: 3636 Innes Road, Ottawa

AGAT WORK ORDER: 16Z102773

ATTENTION TO: Matthieu Rochon

SAMPLED BY: Kathryn Maton

Trace Organics Analysis

RPT Date: Jun 13, 2016			DUPLICATE			Method Blank	REFERENCE MATERIAL		METHOD BLANK SPIKE		MATRIX SPIKE	
PARAMETER	Batch	Sample Id	Dup #1	Dup #2	RPD		Measured Value	Acceptable Limits		Recovery	Acceptable Limits	
								Lower	Upper		Lower	Upper

O. Reg. 153(511) - PHCs F1 - F4 (with PAHs) (Water)

Benzene	7615636	7515636	< 0.20	< 0.20	NA	< 0.20	109%	50%	140%	111%	60%	130%	113%	50%	140%
Toluene	7615636	7515636	< 0.20	< 0.20	NA	< 0.20	110%	50%	140%	104%	60%	130%	115%	50%	140%
Ethylbenzene	7615636	7515636	< 0.10	< 0.10	NA	< 0.10	116%	50%	140%	113%	60%	130%	115%	50%	140%
Xylene Mixture	7615636	7515636	< 0.20	< 0.20	NA	< 0.20	108%	50%	140%	109%	60%	130%	99%	50%	140%
F1 (C6 to C10)	7615636	7515636	< 25	< 25	NA	< 25	104%	60%	140%	118%	60%	140%	94%	60%	140%

F2 (C10 to C16)		TW	< 100	< 100	NA	< 100	98%	60%	140%	65%	60%	140%	72%	60%	140%
F3 (C16 to C34)		TW	< 100	< 100	NA	< 100	102%	60%	140%	92%	60%	140%	93%	60%	140%
F4 (C34 to C50)		TW	< 100	< 100	NA	< 100	86%	60%	140%	71%	60%	140%	101%	60%	140%

O. Reg. 153(511) - PAHs (Water)

Naphthalene		TW	< 0.20	< 0.20	NA	< 0.20	88%	50%	140%	115%	50%	140%	109%	50%	140%
Acenaphthylene		TW	< 0.20	< 0.20	NA	< 0.20	96%	50%	140%	115%	50%	140%	112%	50%	140%
Acenaphthene		TW	< 0.20	< 0.20	NA	< 0.20	100%	50%	140%	118%	50%	140%	113%	50%	140%
Fluorene		TW	< 0.20	< 0.20	NA	< 0.20	96%	50%	140%	114%	50%	140%	111%	50%	140%
Phenanthrene		TW	< 0.10	< 0.10	NA	< 0.10	95%	50%	140%	111%	50%	140%	106%	50%	140%

Anthracene		TW	< 0.10	< 0.10	NA	< 0.10	96%	50%	140%	114%	50%	140%	111%	50%	140%
Fluoranthene		TW	< 0.20	< 0.20	NA	< 0.20	100%	50%	140%	122%	50%	140%	116%	50%	140%
Pyrene		TW	< 0.20	< 0.20	NA	< 0.20	102%	50%	140%	125%	50%	140%	117%	50%	140%
Benz(a)anthracene		TW	< 0.20	< 0.20	NA	< 0.20	111%	50%	140%	121%	50%	140%	125%	50%	140%
Chrysene		TW	< 0.10	< 0.10	NA	< 0.10	124%	50%	140%	130%	50%	140%	127%	50%	140%

Benzo(b)fluoranthene		TW	< 0.10	< 0.10	NA	< 0.10	105%	50%	140%	113%	50%	140%	110%	50%	140%
Benzo(k)fluoranthene		TW	< 0.10	< 0.10	NA	< 0.10	123%	50%	140%	136%	50%	140%	129%	50%	140%
Benzo(a)pyrene		TW	< 0.01	< 0.01	NA	< 0.01	113%	50%	140%	129%	50%	140%	129%	50%	140%
Indeno(1,2,3-cd)pyrene		TW	< 0.20	< 0.20	NA	< 0.20	103%	50%	140%	105%	50%	140%	111%	50%	140%
Dibenz(a,h)anthracene		TW	< 0.20	< 0.20	NA	< 0.20	104%	50%	140%	109%	50%	140%	118%	50%	140%

Benzo(g,h,i)perylene		TW	< 0.20	< 0.20	NA	< 0.20	105%	50%	140%	110%	50%	140%	119%	50%	140%
2-and 1-methyl Naphthalene		TW	< 0.20	< 0.20	NA	< 0.20	110%	50%	140%	57%	50%	140%	60%	50%	140%

Comments: Tap water analysis has been performed as QC sample testing for duplicate and matrix spike due to insufficient sample volume.
When the average of the sample and duplicate results is less than 5x the RDL, the Relative Percent Difference (RPD) will be indicated as Not Applicable (NA).

Certified By:



Quality Assurance

CLIENT NAME: WSP CANADA INC.

PROJECT: 161-06382-00 Phase Two ESA

SAMPLING SITE: 3636 Innes Road, Ottawa

AGAT WORK ORDER: 16Z102773

ATTENTION TO: Matthieu Rochon

SAMPLED BY: Kathryn Maton

Water Analysis															
RPT Date: Jun 13, 2016			DUPLICATE			Method Blank	REFERENCE MATERIAL			METHOD BLANK SPIKE			MATRIX SPIKE		
PARAMETER	Batch	Sample Id	Dup #1	Dup #2	RPD		Measured Value	Acceptable Limits		Recovery	Acceptable Limits		Recovery	Acceptable Limits	
								Lower	Upper		Lower	Upper		Lower	Upper
O. Reg. 153(511) - Metals & Inorganics (Water)															
Antimony	7615636	7615636	< 1.0	<1.0	NA	< 1.0	102%	70%	130%	91%	80%	120%	93%	70%	130%
Arsenic	7615636	7615636	< 1.0	<1.0	NA	< 1.0	105%	70%	130%	98%	80%	120%	101%	70%	130%
Barium	7615636	7615636	89.7	92.3	2.9%	< 2.0	104%	70%	130%	96%	80%	120%	97%	70%	130%
Beryllium	7615636	7615636	< 0.5	<0.5	NA	< 0.5	96%	70%	130%	100%	80%	120%	92%	70%	130%
Boron	7615636	7615636	48.5	46.1	NA	< 10.0	101%	70%	130%	100%	80%	120%	93%	70%	130%
Cadmium	7615636	7615636	< 0.2	<0.2	NA	< 0.2	102%	70%	130%	98%	80%	120%	97%	70%	130%
Chromium	7615636	7615636	2.4	2.7	NA	< 2.0	109%	70%	130%	100%	80%	120%	99%	70%	130%
Cobalt	7615636	7615636	< 0.5	<0.5	NA	< 0.5	107%	70%	130%	98%	80%	120%	99%	70%	130%
Copper	7615636	7615636	2.0	2.1	NA	< 1.0	107%	70%	130%	99%	80%	120%	98%	70%	130%
Lead	7615636	7615636	< 0.5	<0.5	NA	< 0.5	101%	70%	130%	92%	80%	120%	92%	70%	130%
Molybdenum	7615636	7615636	0.6	0.7	NA	< 0.5	103%	70%	130%	95%	80%	120%	96%	70%	130%
Nickel	7615636	7615636	1.3	1.2	NA	< 1.0	109%	70%	130%	104%	80%	120%	98%	70%	130%
Selenium	7615636	7615636	1.6	<1.0	NA	< 1.0	108%	70%	130%	99%	80%	120%	102%	70%	130%
Silver	7615636	7615636	< 0.2	<0.2	NA	< 0.2	104%	70%	130%	107%	80%	120%	104%	70%	130%
Thallium	7615636	7615636	< 0.3	<0.3	NA	< 0.3	108%	70%	130%	103%	80%	120%	102%	70%	130%
Uranium	7615636	7615636	1.3	1.4	NA	< 0.5	104%	70%	130%	95%	80%	120%	92%	70%	130%
Vanadium	7615636	7615636	2.4	2.5	4.1%	< 0.4	105%	70%	130%	98%	80%	120%	98%	70%	130%
Zinc	7615636	7615636	< 5.0	<5.0	NA	< 5.0	105%	70%	130%	98%	80%	120%	99%	70%	130%
Mercury	7615636	7615636	< 0.02	<0.02	NA	< 0.02	101%	70%	130%	100%	80%	120%	102%	70%	130%
Chromium VI	7615173		<5	<5	NA	< 5	102%	70%	130%	107%	80%	120%	106%	70%	130%
Cyanide	7615636		< 2	< 2	NA	< 2	105%	70%	130%	102%	80%	120%	102%	70%	130%
Sodium	7600828		95400	93000	2.5%	< 500	91%	70%	130%	90%	80%	120%	103%	70%	130%
Chloride	7615565		447000	442000	1.1%	< 100	106%	70%	130%	107%	70%	130%	95%	70%	130%
Electrical Conductivity	7615636	7615636	1340	1350	0.7%	< 2	106%	90%	110%	NA			NA		
pH	7615636	7615636	7.96	8.01	0.6%	NA	101%	90%	110%	NA			NA		

Comments: NA signifies Not Applicable.

Duplicate Qualifier: As the measured result approaches the RL, the uncertainty associated with the value increases dramatically, thus duplicate acceptance limits apply only where the average of the two duplicates is greater than five times the RL.

Certified By:



Method Summary

CLIENT NAME: WSP CANADA INC.

AGAT WORK ORDER: 16Z102773

PROJECT: 161-06382-00 Phase Two ESA

ATTENTION TO: Matthieu Rochon

SAMPLING SITE: 3636 Innes Road, Ottawa

SAMPLED BY: Kathryn Maton

PARAMETER	AGAT S.O.P	LITERATURE REFERENCE	ANALYTICAL TECHNIQUE
Trace Organics Analysis			
Naphthalene	ORG-91-5105	EPA SW-846 3510 & 8270	GC/MS
Acenaphthylene	ORG-91-5105	EPA SW-846 3510 & 8270	GC/MS
Acenaphthene	ORG-91-5105	EPA SW-846 3510 & 8270	GC/MS
Fluorene	ORG-91-5105	EPA SW-846 3510 & 8270	GC/MS
Phenanthrene	ORG-91-5105	EPA SW-846 3510 & 8270	GC/MS
Anthracene	ORG-91-5105	EPA SW-846 3510 & 8270	GC/MS
Fluoranthene	ORG-91-5105	EPA SW-846 3510 & 8270	GC/MS
Pyrene	ORG-91-5105	EPA SW-846 3510 & 8270	GC/MS
Benz(a)anthracene	ORG-91-5105	EPA SW-846 3510 & 8270	GC/MS
Chrysene	ORG-91-5105	EPA SW-846 3510 & 8270	GC/MS
Benzo(b)fluoranthene	ORG-91-5105	EPA SW-846 3510 & 8270	GC/MS
Benzo(k)fluoranthene	ORG-91-5105	EPA SW-846 3510 & 8270	GC/MS
Benzo(a)pyrene	ORG-91-5105	EPA SW-846 3510 & 8270	GC/MS
Indeno(1,2,3-cd)pyrene	ORG-91-5105	EPA SW-846 3510 & 8270	GC/MS
Dibenz(a,h)anthracene	ORG-91-5105	EPA SW-846 3510 & 8270	GC/MS
Benzo(g,h,i)perylene	ORG-91-5105	EPA SW-846 3510 & 8270	GC/MS
2-and 1-methyl Naphthalene	ORG-91-5105	EPA SW-846 3510 & 8270	GC/MS
Chrysene-d12	ORG-91-5105	EPA SW-846 3510 & 8270	GC/MS
Benzene	VOL-91-5010	MOE PHC-E3421	(P&T)GC/FID
Toluene	VOL-91-5010	MOE PHC-E3421	(P&T)GC/FID
Ethylbenzene	VOL-91-5010	MOE PHC-E3421	(P&T)GC/FID
Xylene Mixture	VOL-91-5010	MOE PHC-E3421	(P&T)GC/FID
F1 (C6 to C10)	VOL-91-5010	MOE PHC-E3421	(P&T)GC/FID
F1 (C6 to C10) minus BTEX	VOL-91-5010	MOE PHC-E3421	(P&T)GC/FID
Benzene	VOL-91-5010	MOE PHC E3421	(P&T)GC/MS
Toluene	VOL-91-5010	MOE PHC E3421	(P&T)GC/MS
Ethylbenzene	VOL-91-5010	MOE PHC E3421	(P&T)GC/MS
Xylene Mixture	VOL-91-5010	MOE PHC E3421	(P&T)GC/MS
F1 (C6 to C10)	VOL-91-5010	MOE PHC E3421	(P&T)GC/FID
F1 (C6 to C10) minus BTEX	VOL-91-5010	MOE PHC E3421	(P&T)GC/FID
F2 (C10 to C16)	VOL-91-5010	MOE PHC E3421	GC/FID
F2 (C10 to C16) minus Naphthalene	VOL-91-5010	MOE PHC E3421	GC/FID
F3 (C16 to C34)	VOL-91-5010	MOE PHC E3421	GC/FID
F3 (C16 to C34) minus PAHs	VOL-91-5010	MOE PHC E3421	GC/FID
F4 (C34 to C50)	VOL -91- 5010	MOE PHC- E3421	GC/FID
Gravimetric Heavy Hydrocarbons	VOL-91-5010	MOE PHC E3421	BALANCE
Terphenyl	VOL-91-5010		GC/FID



Method Summary

CLIENT NAME: WSP CANADA INC.

AGAT WORK ORDER: 16Z102773

PROJECT: 161-06382-00 Phase Two ESA

ATTENTION TO: Matthieu Rochon

SAMPLING SITE: 3636 Innes Road, Ottawa

SAMPLED BY: Kathryn Maton

PARAMETER	AGAT S.O.P	LITERATURE REFERENCE	ANALYTICAL TECHNIQUE
Water Analysis			
Antimony	MET-93-6103	EPA SW-846 6020A & 200.8	ICP-MS
Arsenic	MET-93-6103	EPA SW-846 6020A & 200.8	ICP-MS
Barium	MET-93-6103	EPA SW-846 6020A & 200.8	ICP-MS
Beryllium	MET-93-6103	EPA SW-846 6020A & 200.8	ICP-MS
Boron	MET-93-6103	EPA SW-846 6020A & 200.8	ICP-MS
Cadmium	MET-93-6103	EPA SW-846 6020A & 200.8	ICP-MS
Chromium	MET-93-6103	EPA SW-846 6020A & 200.8	ICP-MS
Cobalt	MET-93-6103	EPA SW-846 6020A & 200.8	ICP-MS
Copper	MET-93-6103	EPA SW-846 6020A & 200.8	ICP-MS
Lead	MET-93-6103	EPA SW-846 6020A & 200.8	ICP-MS
Molybdenum	MET-93-6103	EPA SW-846 6020A & 200.8	ICP-MS
Nickel	MET-93-6103	EPA SW-846 6020A & 200.8	ICP-MS
Selenium	MET-93-6103	EPA SW-846 6020A & 200.8	ICP-MS
Silver	MET-93-6103	EPA SW-846 6020A & 200.8	ICP-MS
Thallium	MET-93-6103	EPA SW-846 6020A & 200.8	ICP-MS
Uranium	MET-93-6103	EPA SW-846 6020A & 200.8	ICP-MS
Vanadium	MET-93-6103	EPA SW-846 6020A & 200.8	ICP-MS
Zinc	MET-93-6103	EPA SW-846 6020A & 200.8	ICP-MS
Mercury	MET-93-6100	EPA SW-846 7470 & 245.1	CVAAS
Chromium VI	INOR-93-6034	SM 3500-Cr B	SPECTROPHOTOMETER
Cyanide	INOR-93-6052	MOE METHOD CN- 3015 & SM 4500 CN- I	TECHNICON AUTO ANALYZER
Sodium	MET-93-6105	EPA SW-846 6010C & 200.7	ICP/OES
Chloride	INOR-93-6004	SM 4110 B	ION CHROMATOGRAPH
Electrical Conductivity	INOR-93-6000	SM 2510 B	PC TITRATE
pH	INOR-93-6000	SM 4500-H+ B	PC TITRATE



Laboratories

5635 Coopers Avenue
Mississauga, Ontario L4Z 1Y2
Ph: 905.712.5100 Fax: 905.712.5122
web@earth.agatlabs.com

Chain of Custody Record

If this is a Drinking Water sample, please use Drinking Water Chain of Custody Form (potable water intended for human consumption)

Report Information:

Company: WSP Canada Inc.
Contact: Walter Rodon / Kathryn Makin
Address: 500 G. Greer Blvd. 3rd floor
Gahmeu de, 181 Ave 3
Phone: 603-617-9233 Fax: 819-243-2019
Reports to be sent to: Walter Rodon / Kathryn Makin
1. Email: makin.kathryn@wspgroup.com
2. Email: Kathryn.makin@wspgroup.com

Project Information:

Project: Phase Two ESA
Site Location: 3636 Innes Rd, Ottawa
Sampled By: KLH
AGAT Quote #: PO: 161-06382-00

Invoice Information:

Bill To Same: Yes ☐ No ☒
Company: _____
Contact: _____
Address: _____
Email: _____

Regulatory Requirements:

(Please check all applicable boxes)
☒ Regulation 153/C4
Table: _____
☐ Sewer Use
☐ Sanitary
☐ Storm
☐ CCME
☐ Prov. Water Quality Objectives (PWQO)
☐ Other
☐ Agriculture
☐ Soil Texture (check one)
☒ Fine
☐ Coarse
Region: _____

Is this submission for a Record of Site Condition?

Yes ☒ No ☐

Report Guideline on Certificate of Analysis

Yes ☒ No ☐

Sample Matrix Legend

B Biotin
GW Ground Water
O Oil
P Paint
S Soil
SD Sediment
SW Surface Water

Comments/Special Instructions

Metals and Inorganics

Metal Scan

Hydride Forming Metals

Client Custom Metals

ORPs: ☐ B-HWS ☐ Cl ☐ CN ☐ Cr⁶⁺ ☐ EC ☐ FOC ☐ NO₃/NO₂ ☐ Total N ☐ Hg ☐ pH ☐ SAR
Nutrients: ☐ TP ☐ NH₃ ☐ TKN ☐ NO₃ ☐ NO₂ ☐ NO₃/NO₂
Volatiles: ☐ VOC ☐ BTEX ☐ THM

CCME Fractions 1 to 4

ABNs

PAHs

Chlorophenols

PCBs

Organochlorine Pesticides

TCLP Metals/Inorganics

Sewer Use

CCME FI-F4+BTEX
Reg 153 PAHs
Reg 153 Metals
CCME FI+BTEX

Sample Identification	Date Sampled	Time Sampled	# of Containers	Sample Matrix	Comments/Special Instructions	Metals and Inorganics	ABNs	PAHs	Chlorophenols	PCBs	Organochlorine Pesticides	TCLP Metals/Inorganics	Sewer Use
RAWA/BARBAR	02/06/16	13:31	10	GW									
MW16-3		13:50											
MW16-5		13:24											
MW16-8		13:24											
MW16-108		13:24											
Trip Blank	25/05/16												

Laboratory Use Only

Work Order #: 162102373

Cooler Quantity: 8.3 6.4 6.9

Arrival Temperatures: 8.3 6.4 6.9

Custody Seal Intact: ☐ Yes ☐ No ☒ N/A

Notes: _____

Turnaround Time (TAT) Required:

Regular TAT ☐ 5 to 7 Business Days

Rush TAT (Rush Surcharges Apply)

3 Business Days ☐ 2 Business Days ☐ 1 Business Day ☒

OR Date Required (Rush Surcharges May Apply): _____

Please provide prior notification for rush TAT

*TAT is exclusive of weekends and statutory holidays

Samples Requisitioned By: (Print Name and Sign) Kathryn Makin Date 02/06/16 Time 4:30pm

Samples Received By: (Print Name and Sign) Shawni Date 02/06/16 Time 9:00

Samples Requisitioned By: (Print Name and Sign) Makin Date 02/06/16 Time 4:30pm

Samples Received By: (Print Name and Sign) Shawni Date 02/06/16 Time 9:00

Page 1 of 1

No. T 018580

Document ID: DW-76-13.1.010

Pink Copy - Client | Yellow Copy - AGAT | White Copy - AGAT

Date Issued: November 2, 2015

Client: Genivar INC.
500 Boul. Greber, 3rd Floor
Gatineau, QC
J8T 7W3
Attention: Ms. David Feghali
PO#:
Invoice to: Genivar Inc.

Report Number: 1313177
Date Submitted: 2013-06-28
Date Reported: 2013-07-10
Project: 131-13558-00-700
COC #: 157780

Page 1 of 13

Dear David Feghali:

Please find attached the analytical results for your samples. If you have any questions regarding this report, please do not hesitate to call (613-727-5692).

Report Comments:

APPROVAL: _____

Lorna Wilson
Laboratory Supervisor, Inorganics

APPROVAL: _____

Charlie (Long) Qu
Laboratory Supervisor, Organics

Exova (Ottawa) is certified and accredited for specific parameters by:

CALA, Canadian Association for Laboratory Accreditation (to ISO 17025), OMAFRA, Ontario Ministry of Agriculture, Food and Rural Affairs (for farm soils), Licensed by Ontario MOE for specific tests in drinking water.

Exova (Mississauga) is certified and accredited for specific parameters by:

SCC, Standards Council of Canada (to ISO 17025)

Please note: Field data, where presented on the report, has been provided by the client and is presented for informational purposes only.

Client: Genivar INC.
500 Boul. Greber, 3rd Floor
Gatineau, QC
J8T 7W3
Attention: Ms. David Feghali
PO#:
Invoice to: Genivar Inc.

Report Number: 1313177
Date Submitted: 2013-06-28
Date Reported: 2013-07-10
Project: 131-13558-00-700
COC #: 157780

Group	Analyte	MRL	Units	Guideline	Lab I.D.	1037902	1037903	1037904	1037905
					Sample Matrix Sample Type Sampling Date Sample I.D.	Soil 2013-06-27 P0-1 (0.61-0.86)	Soil 2013-06-27 F-09 (0-0.61)	Soil 2013-06-27 DUP-7	Soil 2013-06-27 F-02 (0.45-0.55)
Inorganics	Antimony	1	ug/g	STD-7.5		<1			<1
	Arsenic	1	ug/g	STD-18		2			2
	Barium	1	ug/g	STD-390		111			65
	Beryllium	1	ug/g	STD-4		<1			<1
	Boron (total)	10	ug/g	STD-120		20			20
	Cadmium	0.5	ug/g	STD-1.2		<0.5			<0.5
	Chromium Total	1	ug/g	STD-160		60			36
	Cobalt	1	ug/g	STD-22		11			8
	Copper	1	ug/g	STD-140		19			11
	Lead	1	ug/g	STD-120		7			4
	Molybdenum	1	ug/g	STD-6.9		<1			<1
	Nickel	1	ug/g	STD-100		29			19
	Selenium	1	ug/g	STD-2.4		<1			<1
	Silver	0.2	ug/g	STD-20		<0.2			<0.2
	Thallium	1	ug/g	STD-1		<1			<1
	Uranium	0.5	ug/g	STD-23		0.6			<0.5
	Vanadium	2	ug/g	STD-86		53			36
	Zinc	2	ug/g	STD-340		57			33
Moisture	Moisture	0.1	%			15.6	1.2	2.6	312.0
Petroleum Hydrocarbons	Petroleum Hydrocarbons F1	10	ug/g	STD-55		<10	<10	<10	20
	Petroleum Hydrocarbons F1-BTEX	10	ug/g			<10	<10	<10	
	Petroleum Hydrocarbons F2	10	ug/g	STD-98		<10	<10	<10	<10
	Petroleum Hydrocarbons F3	20	ug/g	STD-300		<20	60	120	<20
	Petroleum Hydrocarbons F4	20	ug/g	STD-2800		140	240	440	100
	Petroleum Hydrocarbons F4g	500	ug/g					1400	
Semi-Volatiles	Acenaphthene	0.05	ug/g	STD-7.9		<0.05	<0.05	<0.05	<0.05

Guideline = O.Reg 153-T7-Res/Park-Coarse

* = Guideline Exceedence

** - Analysis completed in Mississauga

Results relate only to the parameters tested on the samples submitted.

Methods references and/or additional QA/QC information available on request.

MRL = Method Reporting Limit, AO = Aesthetic Objective, OG = Operational Guideline, MAC = Maximum Acceptable Concentration, IMAC = Interim Maximum Acceptable Concentration, STD = Standard, PWQO = Provincial Water Quality Guideline, IPWQO = Interim Provincial Water Quality Objective, TDR = Typical Desired Range

Client: Genivar INC.
500 Boul. Greber, 3rd Floor
Gatineau, QC
J8T 7W3
Attention: Ms. David Feghali
PO#:
Invoice to: Genivar Inc.

Report Number: 1313177
Date Submitted: 2013-06-28
Date Reported: 2013-07-10
Project: 131-13558-00-700
COC #: 157780

					Lab I.D.	1037902	1037903	1037904	1037905
					Sample Matrix	Soil	Soil	Soil	Soil
					Sample Type				
					Sampling Date	2013-06-27	2013-06-27	2013-06-27	2013-06-27
					Sample I.D.	P0-1 (0.61-0.86)	F-09 (0-0.61)	DUP-7	F-02 (0.45-0.55)
Group	Analyte	MRL	Units	Guideline					
Semi-Volatiles	Acenaphthylene	0.05	ug/g	STD-0.15		<0.05	<0.05	<0.05	<0.05
	Anthracene	0.05	ug/g	STD-0.67		<0.05	<0.05	<0.05	<0.05
	Benz[a]anthracene	0.05	ug/g	STD-0.5		<0.05	<0.05	<0.05	<0.05
	Benzo[a]pyrene	0.05	ug/g	STD-0.3		<0.05	<0.05	<0.05	<0.05
	Benzo[b]fluoranthene	0.05	ug/g	STD-0.78		<0.05	<0.05	<0.05	<0.05
	Benzo[ghi]perylene	0.05	ug/g	STD-6.6		<0.05	<0.05	<0.05	<0.05
	Benzo[k]fluoranthene	0.05	ug/g	STD-0.78		<0.05	<0.05	<0.05	<0.05
	Chrysene	0.05	ug/g	STD-7		<0.05	<0.05	<0.05	<0.05
	Dibenz[a h]anthracene	0.05	ug/g	STD-0.1		<0.05	<0.05	<0.05	<0.05
	Fluoranthene	0.05	ug/g	STD-0.69		<0.05	<0.05	<0.05	<0.05
	Fluorene	0.05	ug/g	STD-62		<0.05	<0.05	<0.05	<0.05
	Indeno[1 2 3-cd]pyrene	0.05	ug/g	STD-0.38		<0.05	<0.05	<0.05	<0.05
	Methlynaphthalene, 1-	0.05	ug/g	STD-0.99		<0.05	<0.05	<0.05	<0.05
	Methlynaphthalene, 2-	0.05	ug/g	STD-0.99		<0.05	<0.05	<0.05	<0.05
	Naphthalene	0.05	ug/g	STD-0.6		<0.05	<0.05	<0.05	<0.05
	Phenanthrene	0.05	ug/g	STD-6.2		<0.05	<0.05	<0.05	<0.05
	Pyrene	0.05	ug/g	STD-78		<0.05	<0.05	<0.05	<0.05
VOCs	Benzene	0.02	ug/g	STD-0.21		<0.02	<0.02	<0.02	
	Ethylbenzene	0.05	ug/g	STD-2		<0.05	<0.05	<0.05	
	m/p-xylene	0.05	ug/g			<0.05	<0.05	<0.05	
	o-xylene	0.05	ug/g			<0.05	<0.05	<0.05	
	Toluene	0.20	ug/g	STD-2.3		<0.20	<0.20	<0.20	
	Xylene Mixture	0.05	ug/g	STD-3.1		<0.05	<0.05	<0.05	
VOCs Surrogates (%)	Toluene-d8	0	%			98	99	97	

Guideline = O.Reg 153-T7-Res/Park-Coarse

* = Guideline Exceedence

** - Analysis completed in Mississauga

Results relate only to the parameters tested on the samples submitted.

Methods references and/or additional QA/QC information available on request.

MRL = Method Reporting Limit, AO = Aesthetic Objective, OG = Operational Guideline,
MAC = Maximum Acceptable Concentration, IMAC = Interim Maximum Acceptable
Concentration, STD = Standard, PWQO = Provincial Water Quality Guideline, IPWQO =
Interim Provincial Water Quality Objective, TDR = Typical Desired Range

Client: Genivar INC.
500 Boul. Greber, 3rd Floor
Gatineau, QC
J8T 7W3
Attention: Ms. David Feghali
PO#:
Invoice to: Genivar Inc.

Report Number: 1313177
Date Submitted: 2013-06-28
Date Reported: 2013-07-10
Project: 131-13558-00-700
COC #: 157780

Group	Analyte	MRL	Units	Guideline	Lab I.D. Sample Matrix Sample Type Sampling Date Sample I.D.	1037906	1037907	1037908	1037909
						Soil 2013-06-27 F-02 (0.55-0.75)	Soil 2013-06-27 F-01 (0.4-0.5)	Soil 2013-06-27 F-04 (0.61-1.22)	Soil 2013-06-27 F-03 (0.3-0.5)
Inorganics	Antimony	1	ug/g	STD-7.5			<1		<1
	Arsenic	1	ug/g	STD-18			3		3
	Barium	1	ug/g	STD-390			99		177
	Beryllium	1	ug/g	STD-4			<1		<1
	Boron (total)	10	ug/g	STD-120			20		20
	Cadmium	0.5	ug/g	STD-1.2			<0.5		<0.5
	Chromium Total	1	ug/g	STD-160			41		22
	Cobalt	1	ug/g	STD-22			9		4
	Copper	1	ug/g	STD-140			15		5
	Lead	1	ug/g	STD-120			13		7
	Molybdenum	1	ug/g	STD-6.9			<1		1
	Nickel	1	ug/g	STD-100			23		16
	Selenium	1	ug/g	STD-2.4			<1		<1
	Silver	0.2	ug/g	STD-20			<0.2		<0.2
	Thallium	1	ug/g	STD-1			<1		<1
	Uranium	0.5	ug/g	STD-23			<0.5		0.6
	Vanadium	2	ug/g	STD-86			39		10
	Zinc	2	ug/g	STD-340			54		10
Moisture	Moisture	0.1	%			14.8	15.5	15.7	3.6
Petroleum Hydrocarbons	Petroleum Hydrocarbons F1	10	ug/g	STD-55		<10	<10	<10	<10
	Petroleum Hydrocarbons F1-BTEX	10	ug/g			<10	<10	<10	<10
	Petroleum Hydrocarbons F2	10	ug/g	STD-98		<10	<10	<10	<10
	Petroleum Hydrocarbons F3	20	ug/g	STD-300		<20	<20	<20	<20
	Petroleum Hydrocarbons F4	20	ug/g	STD-2800		60	40	20	20
Semi-Volatiles	Acenaphthene	0.05	ug/g	STD-7.9		<0.05	<0.05	<0.05	<0.05
	Acenaphthylene	0.05	ug/g	STD-0.15		<0.05	<0.05	<0.05	<0.05

Guideline = O.Reg 153-T7-Res/Park-Coarse

* = Guideline Exceedence

** - Analysis completed in Mississauga

Results relate only to the parameters tested on the samples submitted.

Methods references and/or additional QA/QC information available on request.

MRL = Method Reporting Limit, AO = Aesthetic Objective, OG = Operational Guideline, MAC = Maximum Acceptable Concentration, IMAC = Interim Maximum Acceptable Concentration, STD = Standard, PWQO = Provincial Water Quality Guideline, IPWQO = Interim Provincial Water Quality Objective, TDR = Typical Desired Range

Client: Genivar INC.
500 Boul. Greber, 3rd Floor
Gatineau, QC
J8T 7W3
Attention: Ms. David Feghali
PO#:
Invoice to: Genivar Inc.

Report Number: 1313177
Date Submitted: 2013-06-28
Date Reported: 2013-07-10
Project: 131-13558-00-700
COC #: 157780

					Lab I.D.	1037906	1037907	1037908	1037909
					Sample Matrix	Soil	Soil	Soil	Soil
					Sample Type				
					Sampling Date	2013-06-27	2013-06-27	2013-06-27	2013-06-27
					Sample I.D.	F-02 (0.55-0.75)	F-01 (0.4-0.5)	F-04 (0.61-1.22)	F-03 (0.3-0.5)
Group	Analyte	MRL	Units	Guideline					
Semi-Volatiles	Anthracene	0.05	ug/g	STD-0.67		<0.05	<0.05	<0.05	<0.05
	Benz[a]anthracene	0.05	ug/g	STD-0.5		<0.05	<0.05	<0.05	<0.05
	Benzo[a]pyrene	0.05	ug/g	STD-0.3		<0.05	<0.05	<0.05	<0.05
	Benzo[b]fluoranthene	0.05	ug/g	STD-0.78		<0.05	<0.05	<0.05	<0.05
	Benzo[ghi]perylene	0.05	ug/g	STD-6.6		<0.05	<0.05	<0.05	<0.05
	Benzo[k]fluoranthene	0.05	ug/g	STD-0.78		<0.05	<0.05	<0.05	<0.05
	Chrysene	0.05	ug/g	STD-7		<0.05	<0.05	<0.05	<0.05
	Dibenz[a h]anthracene	0.05	ug/g	STD-0.1		<0.05	<0.05	<0.05	<0.05
	Fluoranthene	0.05	ug/g	STD-0.69		<0.05	<0.05	<0.05	<0.05
	Fluorene	0.05	ug/g	STD-62		<0.05	<0.05	<0.05	<0.05
	Indeno[1 2 3-cd]pyrene	0.05	ug/g	STD-0.38		<0.05	<0.05	<0.05	<0.05
	Methlynaphthalene, 1-	0.05	ug/g	STD-0.99		<0.05	<0.05	<0.05	<0.05
	Methlynaphthalene, 2-	0.05	ug/g	STD-0.99		<0.05	<0.05	<0.05	<0.05
	Naphthalene	0.05	ug/g	STD-0.6		<0.05	<0.05	<0.05	<0.05
	Phenanthrene	0.05	ug/g	STD-6.2		<0.05	<0.05	<0.05	<0.05
VOCs	Pyrene	0.05	ug/g	STD-78		0.12	<0.05	0.16	<0.05
	Benzene	0.02	ug/g	STD-0.21		<0.02	<0.02	<0.02	<0.02
	Ethylbenzene	0.05	ug/g	STD-2		<0.05	<0.05	<0.05	<0.05
	m/p-xylene	0.05	ug/g			<0.05	<0.05	<0.05	<0.05
	o-xylene	0.05	ug/g			<0.05	<0.05	<0.05	<0.05
	Toluene	0.20	ug/g	STD-2.3		<0.20	<0.20	<0.20	<0.20
	Xylene Mixture	0.05	ug/g	STD-3.1		<0.05	<0.05	<0.05	<0.05
VOCs Surrogates (%)	Toluene-d8	0	%			98	97	97	100

Guideline = O.Reg 153-T7-Res/Park-Coarse

* = Guideline Exceedence

** - Analysis completed in Mississauga

Results relate only to the parameters tested on the samples submitted.

Methods references and/or additional QA/QC information available on request.

MRL = Method Reporting Limit, AO = Aesthetic Objective, OG = Operational Guideline,
MAC = Maximum Acceptable Concentration, IMAC = Interim Maximum Acceptable
Concentration, STD = Standard, PWQO = Provincial Water Quality Guideline, IPWQO =
Interim Provincial Water Quality Objective, TDR = Typical Desired Range

Client: Genivar INC.
500 Boul. Greber, 3rd Floor
Gatineau, QC
J8T 7W3
Attention: Ms. David Feghali
PO#:
Invoice to: Genivar Inc.

Report Number: 1313177
Date Submitted: 2013-06-28
Date Reported: 2013-07-10
Project: 131-13558-00-700
COC #: 157780

Group	Analyte	MRL	Units	Guideline	Lab I.D.	Sample Matrix	Sample Type	Sampling Date	Sample I.D.
					1037910	1037911	1037912	1037913	
					Soil	Soil	Soil	Soil	
					2013-06-27	2013-06-27	2013-06-27	2013-06-27	
					F-03 (0.5-0.91)	F-08 (0.10-0.61)	F-07 (0.61-1.22)	F-06 (0-0.61)	
Inorganics	Antimony	1	ug/g	STD-7.5	<1				
	Arsenic	1	ug/g	STD-18	4				
	Barium	1	ug/g	STD-390	132				
	Beryllium	1	ug/g	STD-4	<1				
	Boron (total)	10	ug/g	STD-120	20				
	Cadmium	0.5	ug/g	STD-1.2	<0.5				
	Chromium Total	1	ug/g	STD-160	33				
	Cobalt	1	ug/g	STD-22	7				
	Copper	1	ug/g	STD-140	11				
	Lead	1	ug/g	STD-120	7				
	Molybdenum	1	ug/g	STD-6.9	<1				
	Nickel	1	ug/g	STD-100	21				
	Selenium	1	ug/g	STD-2.4	<1				
	Silver	0.2	ug/g	STD-20	<0.2				
	Thallium	1	ug/g	STD-1	<1				
	Uranium	0.5	ug/g	STD-23	0.5				
	Vanadium	2	ug/g	STD-86	32				
	Zinc	2	ug/g	STD-340	35				
Moisture	Moisture	0.1	%		14.1	3.8	26.8	3.2	
Petroleum Hydrocarbons	Petroleum Hydrocarbons F1	10	ug/g	STD-55	<10	30	<10	<10	
	Petroleum Hydrocarbons F1-BTEX	10	ug/g		<10	30	<10	<10	
	Petroleum Hydrocarbons F2	10	ug/g	STD-98	<10	<10	<10	<10	
	Petroleum Hydrocarbons F3	20	ug/g	STD-300	<20	80	<20	30	
	Petroleum Hydrocarbons F4	20	ug/g	STD-2800	<20	30	<20	60	
Semi-Volatiles	Acenaphthene	0.05	ug/g	STD-7.9	<0.05	<0.05	<0.05	<0.05	
	Acenaphthylene	0.05	ug/g	STD-0.15	<0.05	<0.05	<0.05	<0.05	

Guideline = O.Reg 153-T7-Res/Park-Coarse

* = Guideline Exceedence

** - Analysis completed in Mississauga

Results relate only to the parameters tested on the samples submitted.

Methods references and/or additional QA/QC information available on request.

MRL = Method Reporting Limit, AO = Aesthetic Objective, OG = Operational Guideline, MAC = Maximum Acceptable Concentration, IMAC = Interim Maximum Acceptable Concentration, STD = Standard, PWQO = Provincial Water Quality Guideline, IPWQO = Interim Provincial Water Quality Objective, TDR = Typical Desired Range

Client: Genivar INC.
500 Boul. Greber, 3rd Floor
Gatineau, QC
J8T 7W3
Attention: Ms. David Feghali
PO#:
Invoice to: Genivar Inc.

Report Number: 1313177
Date Submitted: 2013-06-28
Date Reported: 2013-07-10
Project: 131-13558-00-700
COC #: 157780

					1037910 Soil 2013-06-27 F-03 (0.5-0.91)	1037911 Soil 2013-06-27 F-08 (0.10-0.61)	1037912 Soil 2013-06-27 F-07 (0.61-1.22)	1037913 Soil 2013-06-27 F-06 (0-0.61)
Group	Analyte	MRL	Units	Guideline				
Semi-Volatiles	Anthracene	0.05	ug/g	STD-0.67	<0.05	<0.05	<0.05	<0.05
	Benz[a]anthracene	0.05	ug/g	STD-0.5	<0.05	<0.05	<0.05	<0.05
	Benzo[a]pyrene	0.05	ug/g	STD-0.3	<0.05	<0.05	<0.05	<0.05
	Benzo[b]fluoranthene	0.05	ug/g	STD-0.78	<0.05	<0.05	<0.05	<0.05
	Benzo[ghi]perylene	0.05	ug/g	STD-6.6	<0.05	<0.05	<0.05	<0.05
	Benzo[k]fluoranthene	0.05	ug/g	STD-0.78	<0.05	<0.05	<0.05	<0.05
	Chrysene	0.05	ug/g	STD-7	<0.05	<0.05	<0.05	<0.05
	Dibenz[a h]anthracene	0.05	ug/g	STD-0.1	<0.05	<0.05	<0.05	<0.05
	Fluoranthene	0.05	ug/g	STD-0.69	<0.05	<0.05	<0.05	<0.05
	Fluorene	0.05	ug/g	STD-62	<0.05	<0.05	<0.05	<0.05
	Indeno[1 2 3-cd]pyrene	0.05	ug/g	STD-0.38	<0.05	<0.05	<0.05	<0.05
	Methlynaphthalene, 1-	0.05	ug/g	STD-0.99	<0.05	<0.05	<0.05	<0.05
	Methlynaphthalene, 2-	0.05	ug/g	STD-0.99	<0.05	<0.05	<0.05	<0.05
	Naphthalene	0.05	ug/g	STD-0.6	<0.05	<0.05	<0.05	<0.05
	Phenanthrene	0.05	ug/g	STD-6.2	<0.05	<0.05	<0.05	<0.05
	Pyrene	0.05	ug/g	STD-78	<0.05	<0.05	<0.05	<0.05
VOCs	Benzene	0.02	ug/g	STD-0.21	<0.02	<0.02	<0.02	<0.02
	Ethylbenzene	0.05	ug/g	STD-2	<0.05	<0.05	<0.05	<0.05
	m/p-xylene	0.05	ug/g		<0.05	<0.05	<0.05	<0.05
	o-xylene	0.05	ug/g		<0.05	<0.05	<0.05	<0.05
	Toluene	0.20	ug/g	STD-2.3	<0.20	<0.20	<0.20	<0.20
	Xylene Mixture	0.05	ug/g	STD-3.1	<0.05	<0.05	<0.05	<0.05
VOCs Surrogates (%)	Toluene-d8	0	%		97	96	100	99

Guideline = O.Reg 153-T7-Res/Park-Coarse

* = Guideline Exceedence

** - Analysis completed in Mississauga

Results relate only to the parameters tested on the samples submitted.

Methods references and/or additional QA/QC information available on request.

MRL = Method Reporting Limit, AO = Aesthetic Objective, OG = Operational Guideline,
MAC = Maximum Acceptable Concentration, IMAC = Interim Maximum Acceptable
Concentration, STD = Standard, PWQO = Provincial Water Quality Guideline, IPWQO =
Interim Provincial Water Quality Objective, TDR = Typical Desired Range

Client: Genivar INC.
500 Boul. Greber, 3rd Floor
Gatineau, QC
J8T 7W3
Attention: Ms. David Feghali
PO#:
Invoice to: Genivar Inc.

Report Number: 1313177
Date Submitted: 2013-06-28
Date Reported: 2013-07-10
Project: 131-13558-00-700
COC #: 157780

QC Summary

Analyte	Blank	QC % Rec	QC Limits
Run No 0 Analysis Date 2013-07-08 Method CCME			
Petroleum Hydrocarbons F1-BTEX			
Xylene Mixture			
Run No 253766 Analysis Date 2013-07-08 Method C SM2540B			
Moisture	<0.1 %	102	80-120
Run No 253770 Analysis Date 2013-07-08 Method CCME			
Petroleum Hydrocarbons F2	<10 ug/g	83	50-120
Petroleum Hydrocarbons F3	<20 ug/g	83	50-120
Petroleum Hydrocarbons F4	<20 ug/g	83	50-120
Run No 253806 Analysis Date 2013-07-08 Method CCME			
Petroleum Hydrocarbons F4g	<500 ug/g		
Run No 253828 Analysis Date 2013-07-08 Method EPA 200.8			
Silver	<0.2 ug/g	87	70-130
Arsenic	<1 ug/g	103	70-130
Barium	<1 ug/g	103	70-130

Guideline = O.Reg 153-T7-Res/Park-Coarse

*** = Guideline Exceedence**

** - Analysis completed in Mississauga

Results relate only to the parameters tested on the samples submitted.

Methods references and/or additional QA/QC information available on request.

MRL = Method Reporting Limit, AO = Aesthetic Objective, OG = Operational Guideline,
MAC = Maximum Acceptable Concentration, IMAC = Interim Maximum Acceptable
Concentration, STD = Standard, PWQO = Provincial Water Quality Guideline, IPWQO =
Interim Provincial Water Quality Objective, TDR = Typical Desired Range

Client: Genivar INC.
500 Boul. Greber, 3rd Floor
Gatineau, QC
J8T 7W3
Attention: Ms. David Feghali
PO#:
Invoice to: Genivar Inc.

Report Number: 1313177
Date Submitted: 2013-06-28
Date Reported: 2013-07-10
Project: 131-13558-00-700
COC #: 157780

QC Summary

Analyte	Blank	QC % Rec	QC Limits
Beryllium	<1 ug/g	102	70-130
Cadmium	<0.5 ug/g	98	70-130
Cobalt	<1 ug/g	105	70-130
Chromium Total	<1 ug/g	103	70-130
Copper	<1 ug/g	108	70-130
Molybdenum	<1 ug/g	106	70-130
Nickel	<1 ug/g	106	70-130
Lead	<1 ug/g	92	70-130
Antimony	<1 ug/g	90	70-130
Selenium	<1 ug/g	103	70-130
Thallium	<1 ug/g	92	70-130
Uranium	<0.5 ug/g	87	70-130
Vanadium	<2 ug/g	114	70-130
Zinc	<2 ug/g	113	70-130
Run No 253831 Analysis Date 2013-07-05 Method V 8260B			
Benzene	<0.02 ug/g	96	80-120
Ethylbenzene	<0.05 ug/g	94	80-120

Guideline = O.Reg 153-T7-Res/Park-Coarse

*** = Guideline Exceedence**

** - Analysis completed in Mississauga

Results relate only to the parameters tested on the samples submitted.

Methods references and/or additional QA/QC information available on request.

MRL = Method Reporting Limit, AO = Aesthetic Objective, OG = Operational Guideline,
MAC = Maximum Acceptable Concentration, IMAC = Interim Maximum Acceptable
Concentration, STD = Standard, PWQO = Provincial Water Quality Guideline, IPWQO =
Interim Provincial Water Quality Objective, TDR = Typical Desired Range

Client: Genivar INC.
500 Boul. Greber, 3rd Floor
Gatineau, QC
J8T 7W3
Attention: Ms. David Feghali
PO#:
Invoice to: Genivar Inc.

Report Number: 1313177
Date Submitted: 2013-06-28
Date Reported: 2013-07-10
Project: 131-13558-00-700
COC #: 157780

QC Summary

Analyte	Blank	QC % Rec	QC Limits
m/p-xylene	<0.05 ug/g	97	80-120
o-xylene	<0.05 ug/g	97	80-120
Toluene	<0.20 ug/g	99	80-120
Toluene-d8	92 %	101	
Run No 253832 Analysis Date 2013-07-05 Method CCME			
Petroleum Hydrocarbons F1	<10 ug/g		80-120
Run No 253841 Analysis Date 2013-07-05 Method CCME			
Petroleum Hydrocarbons F1	<10 ug/g	95	80-120
Run No 253842 Analysis Date 2013-07-05 Method CCME			
Petroleum Hydrocarbons F1-BTEX			
Run No 253843 Analysis Date 2013-07-05 Method CCME			
Petroleum Hydrocarbons F1	<10 ug/g	95	80-120
Run No 253857 Analysis Date 2013-07-08 Method M SM3120B-3050B			
Boron (total)	<10 ug/g	83	
Run No 254009 Analysis Date 2013-07-10 Method P 8270			
Methlynaphthalene, 1-	<0.05 ug/g	62	20-150
Methlynaphthalene, 2-	<0.05 ug/g	61	20-150

Guideline = O.Reg 153-T7-Res/Park-Coarse

*** = Guideline Exceedence**

** - Analysis completed in Mississauga

Results relate only to the parameters tested on the samples submitted.

Methods references and/or additional QA/QC information available on request.

MRL = Method Reporting Limit, AO = Aesthetic Objective, OG = Operational Guideline, MAC = Maximum Acceptable Concentration, IMAC = Interim Maximum Acceptable Concentration, STD = Standard, PWQO = Provincial Water Quality Guideline, IPWQO = Interim Provincial Water Quality Objective, TDR = Typical Desired Range

Client: Genivar INC.
500 Boul. Greber, 3rd Floor
Gatineau, QC
J8T 7W3
Attention: Ms. David Feghali
PO#:
Invoice to: Genivar Inc.

Report Number: 1313177
Date Submitted: 2013-06-28
Date Reported: 2013-07-10
Project: 131-13558-00-700
COC #: 157780

QC Summary

Analyte	Blank	QC % Rec	QC Limits
Acenaphthene	<0.05 µg/g	63	20-150
Acenaphthylene	<0.05 µg/g	62	20-150
Anthracene	<0.05 µg/g	70	20-150
Benz[a]anthracene	<0.05 µg/g	77	20-150
Benzo[a]pyrene	<0.05 µg/g	76	20-150
Benzo[b]fluoranthene	<0.05 µg/g	77	20-150
Benzo[ghi]perylene	<0.05 µg/g	85	20-150
Benzo[k]fluoranthene	<0.05 µg/g	75	20-150
Chrysene	<0.05 µg/g	72	20-150
Dibenz[a h]anthracene	<0.05 µg/g	86	20-150
Fluoranthene	<0.05 µg/g	73	20-150
Fluorene	<0.05 µg/g	64	20-150
Indeno[1 2 3-cd]pyrene	<0.05 µg/g	86	20-150
Naphthalene	<0.05 µg/g	59	20-150
Phenanthrene	<0.05 µg/g	68	20-150
Pyrene	<0.05 µg/g	73	20-150

Guideline = O.Reg 153-T7-Res/Park-Coarse

*** = Guideline Exceedence**

** - Analysis completed in Mississauga

Results relate only to the parameters tested on the samples submitted.

Methods references and/or additional QA/QC information available on request.

MRL = Method Reporting Limit, AO = Aesthetic Objective, OG = Operational Guideline,
MAC = Maximum Acceptable Concentration, IMAC = Interim Maximum Acceptable
Concentration, STD = Standard, PWQO = Provincial Water Quality Guideline, IPWQO =
Interim Provincial Water Quality Objective, TDR = Typical Desired Range

Client: Genivar INC.
500 Boul. Greber, 3rd Floor
Gatineau, QC
J8T 7W3
Attention: Ms. David Feghali
PO#:
Invoice to: Genivar Inc.

Report Number: 1313177
Date Submitted: 2013-06-28
Date Reported: 2013-07-10
Project: 131-13558-00-700
COC #: 157780

Guideline = O.Reg 153-T7-Res/Park-Coarse

*** = Guideline Exceedence**

**-.Analysis completed in Mississauga

Results relate only to the parameters tested on the samples submitted.

Methods references and/or additional QA/QC information available on request.

MRL = Method Reporting Limit, AO = Aesthetic Objective, OG = Operational Guideline,
MAC = Maximum Acceptable Concentration, IMAC = Interim Maximum Acceptable
Concentration, STD = Standard, PWQO = Provincial Water Quality Guideline, IPWQO =
Interim Provincial Water Quality Objective, TDR = Typical Desired Range

Client: Genivar INC.
500 Boul. Greber, 3rd Floor
Gatineau, QC
J8T 7W3
Attention: Ms. David Feghali
PO#:
Invoice to: Genivar Inc.

Report Number: 1313177
Date Submitted: 2013-06-28
Date Reported: 2013-07-10
Project: 131-13558-00-700
COC #: 157780

Sample Comment Summary

Sample ID: 1037904 DUP-7 The result for F4 (C34-C50) gravimetric must be substituted if it is greater than the result for F4 (C34-C50).

Guideline = O.Reg 153-T7-Res/Park-Coarse

*** = Guideline Exceedence**

**-.Analysis completed in Mississauga

Results relate only to the parameters tested on the samples submitted.

Methods references and/or additional QA/QC information available on request.

MRL = Method Reporting Limit, AO = Aesthetic Objective, OG = Operational Guideline,
MAC = Maximum Acceptable Concentration, IMAC = Interim Maximum Acceptable
Concentration, STD = Standard, PWQO = Provincial Water Quality Guideline, IPWQO =
Interim Provincial Water Quality Objective, TDR = Typical Desired Range

Client: Genivar INC.
500 Boul. Greber, 3rd Floor
Gatineau, QC
J8T 7W3
Attention: Ms. David Feghali
PO#:
Invoice to: Genivar Inc.

Report Number: 1314739
Date Submitted: 2013-06-28
Date Reported: 2013-07-15
Project: 131-13558-00-700
COC #: 157780

Page 1 of 7

Dear David Feghali:

Please find attached the analytical results for your samples. If you have any questions regarding this report, please do not hesitate to call (613-727-5692).

Report Comments:

APPROVAL: _____

Lorna Wilson
Laboratory Supervisor, Inorganics

APPROVAL: _____

Charlie (Long) Qu
Laboratory Supervisor, Organics

Exova (Ottawa) is certified and accredited for specific parameters by:

CALA, Canadian Association for Laboratory Accreditation (to ISO 17025), OMAFRA, Ontario Ministry of Agriculture, Food and Rural Affairs (for farm soils), Licensed by Ontario MOE for specific tests in drinking water.

Exova (Mississauga) is accredited for specific parameters by:

SCC, Standards Council of Canada (to ISO 17025)

Please note: Field data, where presented on the report, has been provided by the client and is presented for informational purposes only.

Client: Genivar INC.
500 Boul. Greber, 3rd Floor
Gatineau, QC
J8T 7W3
Attention: Ms. David Feghali
PO#:
Invoice to: Genivar Inc.

Report Number: 1314739
Date Submitted: 2013-06-28
Date Reported: 2013-07-15
Project: 131-13558-00-700
COC #: 157780

					1037930 Soil 2013-06-27 F-03 (1.01-1.11)	1037935 Soil 2013-06-27 F-05 (1.32-1.83)
Group	Analyte	MRL	Units	Guideline		
General Chemistry	Moisture	0.1	%		12.2	30.0
Hydrocarbons	F1 (C6-C10)	10	ug/g		<10	<10
	F1-BTEX (C6-C10)	10	ug/g		<10	<10
	F2 (C10-C16)	10	ug/g		<10	<10
	F3 (C16-C34)	20	ug/g		<20	<20
	F4 (C34-C50)	20	ug/g		<20	<20
Metals	Ag	0.2	ug/g		<0.2	<0.2
	As	1	ug/g		2	1
	B	10	ug/g		20	40
	Ba	1	ug/g		61	421
	Be	1	ug/g		<1	<1
	Cd	0.5	ug/g		<0.5	<0.5
	Co	1	ug/g		7	27
	Cr	1	ug/g		18	112
	Cu	1	ug/g		15	61
	Mo	1	ug/g		<1	<1
	Ni	1	ug/g		16	70
	Pb	1	ug/g		6	8
	Sb	1	ug/g		<1	<1
	Se	1	ug/g		<1	<1
	Tl	1	ug/g		<1	<1
	U	0.5	ug/g		<0.5	0.6
	V	2	ug/g		27	105
	Zn	2	ug/g		24	140
Semi-Volatiles	1-methylnaphthalene	0.05	ug/g		<0.05	<0.05
	2-methylnaphthalene	0.05	ug/g		<0.05	<0.05

Guideline = * = **Guideline Exceedence**

** = Analysis completed at Mississauga, Ontario.

Results relate only to the parameters tested on the samples submitted.

Methods references and/or additional QA/QC information available on request.

MRL = Method Reporting Limit, AO = Aesthetic Objective, OG = Operational Guideline, MAC = Maximum Acceptable Concentration, IMAC = Interim Maximum Acceptable Concentration, STD = Standard, PWQO = Provincial Water Quality Guideline, IPWQO = Interim Provincial Water Quality Objective, TDR = Typical Desired Range

Client: Genivar INC.
500 Boul. Greber, 3rd Floor
Gatineau, QC
J8T 7W3
Attention: Ms. David Feghali
PO#:
Invoice to: Genivar Inc.

Report Number: 1314739
Date Submitted: 2013-06-28
Date Reported: 2013-07-15
Project: 131-13558-00-700
COC #: 157780

					Lab I.D. Sample Matrix Sample Type Sampling Date Sample I.D.	1037930 Soil 2013-06-27 F-03 (1.01-1.11)	1037935 Soil 2013-06-27 F-05 (1.32-1.83)
Group	Analyte	MRL	Units	Guideline			
Semi-Volatiles	Acenaphthene	0.05	ug/g			<0.05	<0.05
	Acenaphthylene	0.05	ug/g			<0.05	<0.05
	Anthracene	0.05	ug/g			<0.05	<0.05
	Benzo(a)anthracene	0.05	ug/g			<0.05	<0.05
	Benzo(a)pyrene	0.05	ug/g			<0.05	<0.05
	Benzo(b)fluoranthene	0.05	ug/g			<0.05	<0.05
	Benzo(g,h,i)perylene	0.05	ug/g			<0.05	<0.05
	Benzo(k)fluoranthene	0.05	ug/g			<0.05	<0.05
	Chrysene	0.05	ug/g			<0.05	<0.05
	Dibenzo(a,h)anthracene	0.05	ug/g			<0.05	<0.05
	Fluoranthene	0.05	ug/g			<0.05	<0.05
	Fluorene	0.05	ug/g			<0.05	<0.05
	Indeno(1,2,3-c,d)pyrene	0.05	ug/g			<0.05	<0.05
	Naphthalene	0.05	ug/g			<0.05	<0.05
	Phenanthrene	0.05	ug/g			<0.05	<0.05
	Pyrene	0.05	ug/g			<0.05	<0.05
VOCs	Benzene	0.02	ug/g			<0.02	<0.02
	Ethylbenzene	0.05	ug/g			<0.05	<0.05
	m/p-xylene	0.05	ug/g			<0.05	<0.05
	o-xylene	0.05	ug/g			<0.05	<0.05
	Toluene	0.20	ug/g			<0.20	<0.20
	Toluene-d8	0	%			101	104
	Xylene; total	0.05	ug/g			<0.05	<0.05

Guideline = * = **Guideline Exceedence**

** = Analysis completed at Mississauga, Ontario.

Results relate only to the parameters tested on the samples submitted.

Methods references and/or additional QA/QC information available on request.

MRL = Method Reporting Limit, AO = Aesthetic Objective, OG = Operational Guideline, MAC = Maximum Acceptable Concentration, IMAC = Interim Maximum Acceptable Concentration, STD = Standard, PWQO = Provincial Water Quality Guideline, IPWQO = Interim Provincial Water Quality Objective, TDR = Typical Desired Range

Client: Genivar INC.
500 Boul. Greber, 3rd Floor
Gatineau, QC
J8T 7W3
Attention: Ms. David Feghali
PO#:
Invoice to: Genivar Inc.

Report Number: 1314739
Date Submitted: 2013-06-28
Date Reported: 2013-07-15
Project: 131-13558-00-700
COC #: 157780

QC Summary

Analyte	Blank	QC % Rec	QC Limits
Run No 0 Analysis Date 2013-07-15 Method V 8260B			
Xylene; total			
Run No 254258 Analysis Date 2013-07-12 Method V 8260B			
Benzene	<0.02 ug/g	83	80-120
Ethylbenzene	<0.05 ug/g	100	80-120
m/p-xylene	<0.05 ug/g	106	80-120
o-xylene	<0.05 ug/g	110	80-120
Toluene	<0.20 ug/g	107	80-120
Toluene-d8	100 %	107	
Run No 254259 Analysis Date 2013-07-15 Method CCME			
F1 (C6-C10)	<10 ug/g	80	80-120
F1-BTEX (C6-C10)			
Run No 254297 Analysis Date 2013-07-12 Method P 8270			
1-methylnaphthalene	<0.05 ug/g	52	20-150
2-methylnaphthalene	<0.05 ug/g	51	20-150

Guideline = *** = Guideline Exceedence**
 ** = Analysis completed at Mississauga, Ontario.
 Results relate only to the parameters tested on the samples submitted.
 Methods references and/or additional QA/QC information available on request.

MRL = Method Reporting Limit, AO = Aesthetic Objective, OG = Operational Guideline,
 MAC = Maximum Acceptable Concentration, IMAC = Interim Maximum Acceptable
 Concentration, STD = Standard, PWQO = Provincial Water Quality Guideline, IPWQO
 = Interim Provincial Water Quality Objective, TDR = Typical Desired Range

Client: Genivar INC.
500 Boul. Greber, 3rd Floor
Gatineau, QC
J8T 7W3
Attention: Ms. David Feghali
PO#:
Invoice to: Genivar Inc.

Report Number: 1314739
Date Submitted: 2013-06-28
Date Reported: 2013-07-15
Project: 131-13558-00-700
COC #: 157780

QC Summary

Analyte	Blank	QC % Rec	QC Limits
Acenaphthene	<0.05 ug/g	58	20-150
Acenaphthylene	<0.05 ug/g	54	20-150
Anthracene	<0.05 ug/g	72	20-150
Benzo(a)anthracene	<0.05 ug/g	84	20-150
Benzo(a)pyrene	<0.05 ug/g	81	20-150
Benzo(b)fluoranthene	<0.05 ug/g	81	20-150
Benzo(g,h,i)perylene	<0.05 ug/g	92	20-150
Benzo(k)fluoranthene	<0.05 ug/g	83	20-150
Chrysene	<0.05 ug/g	81	20-150
Dibenzo(a,h)anthracene	<0.05 ug/g	90	20-150
Fluoranthene	<0.05 ug/g	83	20-150
Fluorene	<0.05 ug/g	63	20-150
Indeno(1,2,3-c,d)pyrene	<0.05 ug/g	96	20-150
Naphthalene	<0.05 ug/g	47	20-150
Phenanthrene	<0.05 ug/g	73	20-150
Pyrene	<0.05 ug/g	84	20-150
Run No 254314 Analysis Date 2013-07-15 Method C SM2540B			

Guideline = *** = Guideline Exceedence**

** = Analysis completed at Mississauga, Ontario.

Results relate only to the parameters tested on the samples submitted.

Methods references and/or additional QA/QC information available on request.

MRL = Method Reporting Limit, AO = Aesthetic Objective, OG = Operational Guideline,
MAC = Maximum Acceptable Concentration, IMAC = Interim Maximum Acceptable
Concentration, STD = Standard, PWQO = Provincial Water Quality Guideline, IPWQO
= Interim Provincial Water Quality Objective, TDR = Typical Desired Range

Client: Genivar INC.
500 Boul. Greber, 3rd Floor
Gatineau, QC
J8T 7W3
Attention: Ms. David Feghali
PO#:
Invoice to: Genivar Inc.

Report Number: 1314739
Date Submitted: 2013-06-28
Date Reported: 2013-07-15
Project: 131-13558-00-700
COC #: 157780

QC Summary

Analyte	Blank	QC % Rec	QC Limits
Moisture	<0.1 %	102	80-120
Run No 254316 Analysis Date 2013-07-15 Method CCME			
F2 (C10-C16)	<10 ug/g	81	50-120
F3 (C16-C34)	<20 ug/g	81	50-120
F4 (C34-C50)	<20 ug/g	81	50-120
Run No 254336 Analysis Date 2013-07-15 Method EPA 200.8			
Ag	<0.2 ug/g	95	70-130
As	<1 ug/g	103	70-130
Ba	<1 ug/g	97	70-130
Be	<1 ug/g	102	70-130
Cd	<0.5 ug/g	101	70-130
Co	<1 ug/g	116	70-130
Cr	<1 ug/g	111	70-130
Cu	<1 ug/g	108	70-130
Mo	<1 ug/g	113	70-130
Ni	<1 ug/g	109	70-130
Pb	<1 ug/g	99	70-130

Guideline = *** = Guideline Exceedence**

** = Analysis completed at Mississauga, Ontario.

Results relate only to the parameters tested on the samples submitted.

Methods references and/or additional QA/QC information available on request.

MRL = Method Reporting Limit, AO = Aesthetic Objective, OG = Operational Guideline,
MAC = Maximum Acceptable Concentration, IMAC = Interim Maximum Acceptable
Concentration, STD = Standard, PWQO = Provincial Water Quality Guideline, IPWQO
= Interim Provincial Water Quality Objective, TDR = Typical Desired Range

Client: Genivar INC.
500 Boul. Greber, 3rd Floor
Gatineau, QC
J8T 7W3
Attention: Ms. David Feghali
PO#:
Invoice to: Genivar Inc.

Report Number: 1314739
Date Submitted: 2013-06-28
Date Reported: 2013-07-15
Project: 131-13558-00-700
COC #: 157780

QC Summary

Analyte	Blank	QC % Rec	QC Limits
Sb	<1 ug/g	99	70-130
Se	<1 ug/g	106	70-130
Tl	<1 ug/g	101	70-130
U	<0.5 ug/g	97	70-130
V	<2 ug/g	111	70-130
Zn	<2 ug/g	108	70-130
Run No 254339 Analysis Date 2013-07-15 Method M SM3120B-3050B			
B	<10 ug/g	83	

Guideline = *** = Guideline Exceedence**

** = Analysis completed at Mississauga, Ontario.

Results relate only to the parameters tested on the samples submitted.

Methods references and/or additional QA/QC information available on request.

MRL = Method Reporting Limit, AO = Aesthetic Objective, OG = Operational Guideline,
MAC = Maximum Acceptable Concentration, IMAC = Interim Maximum Acceptable
Concentration, STD = Standard, PWQO = Provincial Water Quality Guideline, IPWQO
= Interim Provincial Water Quality Objective, TDR = Typical Desired Range

Client: Genivar INC.
500 Boul. Greber, 3rd Floor
Gatineau, QC
J8T 7W3
Attention: Ms. David Feghali
PO#:
Invoice to: Genivar Inc.

Report Number: 1313315
Date Submitted: 2013-07-02
Date Reported: 2013-07-11
Project: 131-13558-00
COC #: 144561

Page 1 of 9

Dear David Feghali:

Please find attached the analytical results for your samples. If you have any questions regarding this report, please do not hesitate to call (613-727-5692).

Report Comments:

APPROVAL: _____

Lorna Wilson
Laboratory Supervisor, Inorganics

APPROVAL: _____

Charlie (Long) Qu
Laboratory Supervisor, Organics

Exova (Ottawa) is certified and accredited for specific parameters by:

CALA, Canadian Association for Laboratory Accreditation (to ISO 17025), OMAFRA, Ontario Ministry of Agriculture, Food and Rural Affairs (for farm soils), Licensed by Ontario MOE for specific tests in drinking water.

Exova (Mississauga) is accredited for specific parameters by:

SCC, Standards Council of Canada (to ISO 17025)

Please note: Field data, where presented on the report, has been provided by the client and is presented for informational purposes only.

Client: Genivar INC.
500 Boul. Greber, 3rd Floor
Gatineau, QC
J8T 7W3
Attention: Ms. David Feghali
PO#:
Invoice to: Genivar Inc.

Report Number: 1313315
Date Submitted: 2013-07-02
Date Reported: 2013-07-11
Project: 131-13558-00
COC #: 144561

Group	Analyte	MRL	Units	Lab I.D. Sample Matrix Sample Type Sampling Date Sample I.D. Guideline	1038273	1038274	1038275	1038276
					Soil 2013-07-02 TE-01 (0.30-0.60)	Soil 2013-07-02 TE-02 (0 - 0.35)	Soil 2013-07-02 TE-02 (0.35 - 1.00)	Soil 2013-07-02 TE-02 (1.00-1.45)
General Chemistry	Moisture	0.1	%		23.2	11.7	15.3	26.1
Hydrocarbons	F1 (C6-C10)	10	ug/g		<10	<10	<10	<10
	F1-BTEX (C6-C10)	10	ug/g		<10	<10	<10	<10
	F2 (C10-C16)	10	ug/g		<10	20	<10	<10
	F3 (C16-C34)	20	ug/g		<20	31100	100	110
	F4 (C34-C50)	20	ug/g		70	10400	160	60
	F4 (C34-C50) gravimetric	500	ug/g			40400		
Metals	Ag	0.2	ug/g		<0.2	<0.2	<0.2	<0.2
	As	1	ug/g		3	5	6	2
	B	10	ug/g		10	20	30	40
	Ba	1	ug/g		153	98	150	347
	Be	1	ug/g		<1	<1	<1	<1
	Cd	0.5	ug/g		<0.5	<0.5	<0.5	<0.5
	Co	1	ug/g		10	7	10	18
	Cr	1	ug/g		59	41	62	111
	Cu	1	ug/g		21	19	24	50
	Mo	1	ug/g		<1	1	<1	<1
	Ni	1	ug/g		33	25	31	60
	Pb	1	ug/g		8	11	10	7
	Sb	1	ug/g		<1	<1	<1	<1
	Se	1	ug/g		<1	<1	<1	<1
	Tl	1	ug/g		<1	<1	<1	<1
	U	0.5	ug/g		<0.5	<0.5	0.6	0.9
	V	2	ug/g		45	38	52	98
	Zn	2	ug/g		58	138	80	113
Semi-Volatiles	1-methylnaphthalene	0.05	ug/g		<0.05	<0.05	<0.05	<0.05

Guideline = * = Guideline Exceedence

** = Analysis completed at Mississauga, Ontario.

Results relate only to the parameters tested on the samples submitted.

Methods references and/or additional QA/QC information available on request.

MRL = Method Reporting Limit, AO = Aesthetic Objective, OG = Operational Guideline,
MAC = Maximum Acceptable Concentration, IMAC = Interim Maximum Acceptable
Concentration, STD = Standard, PWQO = Provincial Water Quality Guideline, IPWQO =
Interim Provincial Water Quality Objective, TDR = Typical Desired Range

Client: Genivar INC.
500 Boul. Greber, 3rd Floor
Gatineau, QC
J8T 7W3
Attention: Ms. David Feghali
PO#:
Invoice to: Genivar Inc.

Report Number: 1313315
Date Submitted: 2013-07-02
Date Reported: 2013-07-11
Project: 131-13558-00
COC #: 144561

Group	Analyte	MRL	Units	Lab I.D. Sample Matrix Sample Type Sampling Date Sample I.D. Guideline	1038273	1038274	1038275	1038276
					Soil 2013-07-02 TE-01 (0.30-0.60)	Soil 2013-07-02 TE-02 (0 - 0.35)	Soil 2013-07-02 TE-02 (0.35 - 1.00)	Soil 2013-07-02 TE-02 (1.00-1.45)
Semi-Volatiles	2-methylnaphthalene	0.05	ug/g		<0.05	<0.05	<0.05	<0.05
	Acenaphthene	0.05	ug/g		<0.05	<0.05	<0.05	<0.05
	Acenaphthylene	0.05	ug/g		<0.05	<0.05	<0.05	<0.05
	Anthracene	0.05	ug/g		<0.05	0.15	<0.05	<0.05
	Benzo(a)anthracene	0.05	ug/g		<0.05	<0.05	<0.05	<0.05
	Benzo(a)pyrene	0.05	ug/g		<0.05	<0.05	<0.05	<0.05
	Benzo(b)fluoranthene	0.05	ug/g		<0.05	<0.05	<0.05	<0.05
	Benzo(g,h,i)perylene	0.05	ug/g		<0.05	<0.05	<0.05	<0.05
	Benzo(k)fluoranthene	0.05	ug/g		<0.05	<0.05	<0.05	<0.05
	Chrysene	0.05	ug/g		<0.05	<0.05	<0.05	<0.05
	Dibenzo(a,h)anthracene	0.05	ug/g		<0.05	<0.05	<0.05	<0.05
	Fluoranthene	0.05	ug/g		<0.05	0.17	<0.05	<0.05
	Fluorene	0.05	ug/g		<0.05	<0.05	<0.05	<0.05
	Indeno(1,2,3-c,d)pyrene	0.05	ug/g		<0.05	<0.05	<0.05	<0.05
	Naphthalene	0.05	ug/g		<0.05	<0.05	<0.05	<0.05
	Phenanthrene	0.05	ug/g		<0.05	0.07	<0.05	<0.05
	Pyrene	0.05	ug/g		<0.05	0.17	<0.05	<0.05
VOCs	Benzene	0.02	ug/g		<0.02	<0.02	<0.02	<0.02
	Ethylbenzene	0.05	ug/g		<0.05	<0.05	<0.05	<0.05
	m/p-xylene	0.05	ug/g		<0.05	<0.05	<0.05	<0.05
	o-xylene	0.05	ug/g		<0.05	<0.05	<0.05	<0.05
	Toluene	0.20	ug/g		<0.20	<0.20	<0.20	<0.20
	Toluene-d8	0	%		96	95	96	94
	Xylene; total	1.0	ug/L		<1.0	<1.0	<1.0	<1.0

Guideline = * = Guideline Exceedence

** = Analysis completed at Mississauga, Ontario.

Results relate only to the parameters tested on the samples submitted.

Methods references and/or additional QA/QC information available on request.

MRL = Method Reporting Limit, AO = Aesthetic Objective, OG = Operational Guideline,
MAC = Maximum Acceptable Concentration, IMAC = Interim Maximum Acceptable
Concentration, STD = Standard, PWQO = Provincial Water Quality Guideline, IPWQO =
Interim Provincial Water Quality Objective, TDR = Typical Desired Range

Client: Genivar INC.
500 Boul. Greber, 3rd Floor
Gatineau, QC
J8T 7W3
Attention: Ms. David Feghali
PO#:
Invoice to: Genivar Inc.

Report Number: 1313315
Date Submitted: 2013-07-02
Date Reported: 2013-07-11
Project: 131-13558-00
COC #: 144561

QC Summary

Analyte	Blank	QC % Rec	QC Limits
Run No 253766 Analysis Date 2013-07-08 Method C SM2540B			
Moisture	<0.1 %	102	80-120
Run No 253770 Analysis Date 2013-07-08 Method CCME			
F2 (C10-C16)	<10 ug/g	83	50-120
F3 (C16-C34)	<20 ug/g	83	50-120
F4 (C34-C50)	<20 ug/g	83	50-120
Run No 253806 Analysis Date 2013-07-08 Method CCME			
F4 (C34-C50) gravimetric	<500 ug/g		
Run No 253828 Analysis Date 2013-07-08 Method EPA 200.8			
Ag	<0.2 ug/g	87	70-130
As	<1 ug/g	103	70-130
Ba	<1 ug/g	103	70-130
Be	<1 ug/g	102	70-130
Cd	<0.5 ug/g	101	70-130
Co	<1 ug/g	105	70-130

Guideline = *** = Guideline Exceedence**

** = Analysis completed at Mississauga, Ontario.

Results relate only to the parameters tested on the samples submitted.

Methods references and/or additional QA/QC information available on request.

MRL = Method Reporting Limit, AO = Aesthetic Objective, OG = Operational Guideline,
MAC = Maximum Acceptable Concentration, IMAC = Interim Maximum Acceptable
Concentration, STD = Standard, PWQO = Provincial Water Quality Guideline, IPWQO =
Interim Provincial Water Quality Objective, TDR = Typical Desired Range

Client: Genivar INC.
500 Boul. Greber, 3rd Floor
Gatineau, QC
J8T 7W3
Attention: Ms. David Feghali
PO#:
Invoice to: Genivar Inc.

Report Number: 1313315
Date Submitted: 2013-07-02
Date Reported: 2013-07-11
Project: 131-13558-00
COC #: 144561

QC Summary

Analyte	Blank	QC % Rec	QC Limits
Cr	<1 ug/g	103	70-130
Cu	<1 ug/g	108	70-130
Mo	<1 ug/g	106	70-130
Ni	<1 ug/g	106	70-130
Pb	<1 ug/g	92	70-130
Sb	<1 ug/g	90	70-130
Se	<1 ug/g	103	70-130
Tl	<1 ug/g	92	70-130
U	<0.5 ug/g	87	70-130
V	<2 ug/g	114	70-130
Zn	<2 ug/g	109	70-130
Run No 253852 Analysis Date 2013-07-06 Method V 8260B			
Benzene	<0.02 ug/g	96	80-120
Ethylbenzene	<0.05 ug/g	94	80-120
m/p-xylene	<0.05 ug/g	97	80-120
o-xylene	<0.05 ug/g	97	80-120
Toluene	<0.20 ug/g	99	80-120

Guideline =
*** = Guideline Exceedence**

** = Analysis completed at Mississauga, Ontario.

Results relate only to the parameters tested on the samples submitted.

Methods references and/or additional QA/QC information available on request.

MRL = Method Reporting Limit, AO = Aesthetic Objective, OG = Operational Guideline,
MAC = Maximum Acceptable Concentration, IMAC = Interim Maximum Acceptable
Concentration, STD = Standard, PWQO = Provincial Water Quality Guideline, IPWQO =
Interim Provincial Water Quality Objective, TDR = Typical Desired Range

Client: Genivar INC.
500 Boul. Greber, 3rd Floor
Gatineau, QC
J8T 7W3
Attention: Ms. David Feghali
PO#:
Invoice to: Genivar Inc.

Report Number: 1313315
Date Submitted: 2013-07-02
Date Reported: 2013-07-11
Project: 131-13558-00
COC #: 144561

QC Summary

Analyte	Blank	QC % Rec	QC Limits
Toluene-d8	92 %	101	
Xylene; total			
Run No 253856 Analysis Date 2013-07-05 Method CCME			
F1 (C6-C10)	<10 ug/g	104	80-120
Run No 253857 Analysis Date 2013-07-08 Method M SM3120B-3050B			
B	<10 ug/g	83	
Run No 253859 Analysis Date 2013-07-05 Method CCME			
F1-BTEX (C6-C10)			
Run No 254078 Analysis Date 2013-07-11 Method P 8270			
1-methylnaphthalene	<0.05 ug/g	62	20-150
2-methylnaphthalene	<0.05 ug/g	61	20-150
Acenaphthene	<0.05 ug/g	63	20-150
Acenaphthylene	<0.05 ug/g	62	20-150
Anthracene	<0.05 ug/g	70	20-150
Benzo(a)anthracene	<0.05 ug/g	77	20-150
Benzo(a)pyrene	<0.05 ug/g	76	20-150
Benzo(b)fluoranthene	<0.05 ug/g	77	20-150

Guideline =
*** = Guideline Exceedence**

** = Analysis completed at Mississauga, Ontario.

Results relate only to the parameters tested on the samples submitted.

Methods references and/or additional QA/QC information available on request.

MRL = Method Reporting Limit, AO = Aesthetic Objective, OG = Operational Guideline,
MAC = Maximum Acceptable Concentration, IMAC = Interim Maximum Acceptable
Concentration, STD = Standard, PWQO = Provincial Water Quality Guideline, IPWQO =
Interim Provincial Water Quality Objective, TDR = Typical Desired Range

Client: Genivar INC.
500 Boul. Greber, 3rd Floor
Gatineau, QC
J8T 7W3
Attention: Ms. David Feghali
PO#:
Invoice to: Genivar Inc.

Report Number: 1313315
Date Submitted: 2013-07-02
Date Reported: 2013-07-11
Project: 131-13558-00
COC #: 144561

QC Summary

Analyte	Blank	QC % Rec	QC Limits
Benzo(g,h,i)perylene	<0.05 ug/g	85	20-150
Benzo(k)fluoranthene	<0.05 ug/g	75	20-150
Chrysene	<0.05 ug/g	72	20-150
Dibenzo(a,h)anthracene	<0.05 ug/g	86	20-150
Fluoranthene	<0.05 ug/g	73	20-150
Fluorene	<0.05 ug/g	64	20-150
Indeno(1,2,3-c,d)pyrene	<0.05 ug/g	86	20-150
Naphthalene	<0.05 ug/g	59	20-150
Phenanthrene	<0.05 ug/g	68	20-150
Pyrene	<0.05 ug/g	73	20-150
Run No 254082 Analysis Date 2013-07-11 Method P 8270			
1-methylnaphthalene	<0.05 ug/g	62	20-150
2-methylnaphthalene	<0.05 ug/g	61	20-150
Acenaphthene	<0.05 ug/g	63	20-150
Acenaphthylene	<0.05 ug/g	62	20-150
Anthracene	<0.05 ug/g	70	20-150
Benzo(a)anthracene	<0.05 ug/g	77	20-150

Guideline = *** = Guideline Exceedence**

** = Analysis completed at Mississauga, Ontario.

Results relate only to the parameters tested on the samples submitted.

Methods references and/or additional QA/QC information available on request.

MRL = Method Reporting Limit, AO = Aesthetic Objective, OG = Operational Guideline,
MAC = Maximum Acceptable Concentration, IMAC = Interim Maximum Acceptable
Concentration, STD = Standard, PWQO = Provincial Water Quality Guideline, IPWQO =
Interim Provincial Water Quality Objective, TDR = Typical Desired Range

Client: Genivar INC.
500 Boul. Greber, 3rd Floor
Gatineau, QC
J8T 7W3
Attention: Ms. David Feghali
PO#:
Invoice to: Genivar Inc.

Report Number: 1313315
Date Submitted: 2013-07-02
Date Reported: 2013-07-11
Project: 131-13558-00
COC #: 144561

QC Summary

Analyte	Blank	QC % Rec	QC Limits
Benzo(a)pyrene	<0.05 µg/g	76	20-150
Benzo(b)fluoranthene	<0.05 µg/g	77	20-150
Benzo(g,h,i)perylene	<0.05 µg/g	85	20-150
Benzo(k)fluoranthene	<0.05 µg/g	75	20-150
Chrysene	<0.05 µg/g	72	20-150
Dibenzo(a,h)anthracene	<0.05 µg/g	86	20-150
Fluoranthene	<0.05 µg/g	73	20-150
Fluorene	<0.05 µg/g	64	20-150
Indeno(1,2,3-c,d)pyrene	<0.05 µg/g	86	20-150
Naphthalene	<0.05 µg/g	59	20-150
Phenanthrene	<0.05 µg/g	68	20-150
Pyrene	<0.05 µg/g	73	20-150

Guideline = *** = Guideline Exceedence**

** = Analysis completed at Mississauga, Ontario.

Results relate only to the parameters tested on the samples submitted.

Methods references and/or additional QA/QC information available on request.

MRL = Method Reporting Limit, AO = Aesthetic Objective, OG = Operational Guideline,
MAC = Maximum Acceptable Concentration, IMAC = Interim Maximum Acceptable
Concentration, STD = Standard, PWQO = Provincial Water Quality Guideline, IPWQO =
Interim Provincial Water Quality Objective, TDR = Typical Desired Range

Client: Genivar INC.
500 Boul. Greber, 3rd Floor
Gatineau, QC
J8T 7W3
Attention: Ms. David Feghali
PO#:
Invoice to: Genivar Inc.

Report Number: 1313315
Date Submitted: 2013-07-02
Date Reported: 2013-07-11
Project: 131-13558-00
COC #: 144561

Sample Comment Summary

Sample ID: 1038274 TE-02 (0 - 0.35) The result for F4 (C34-C50) gravimetric must be substituted if it is greater than the result for F4 (C34-C50).
--

Guideline = * = Guideline Exceedence

** = Analysis completed at Mississauga, Ontario.

Results relate only to the parameters tested on the samples submitted.

Methods references and/or additional QA/QC information available on request.

MRL = Method Reporting Limit, AO = Aesthetic Objective, OG = Operational Guideline,
MAC = Maximum Acceptable Concentration, IMAC = Interim Maximum Acceptable
Concentration, STD = Standard, PWQO = Provincial Water Quality Guideline, IPWQO =
Interim Provincial Water Quality Objective, TDR = Typical Desired Range

Client: Genivar INC.
500 Boul. Greber, 3rd Floor
Gatineau, QC
J8T 7W3
Attention: Ms. Catherine Tardy Laporte
PO#:
Invoice to: Genivar INC.

Report Number: 1314497
Date Submitted: 2013-07-11
Date Reported: 2013-07-15
Project: 131-13558-00
COC #: 144561

Page 1 of 4

Dear Catherine Tardy Laporte:

Please find attached the analytical results for your samples. If you have any questions regarding this report, please do not hesitate to call (613-727-5692).

Report Comments:

APPROVAL: _____

Lorna Wilson
Laboratory Supervisor, Inorganics

Exova (Ottawa) is certified and accredited for specific parameters by:

CALA, Canadian Association for Laboratory Accreditation (to ISO 17025), OMAFRA, Ontario Ministry of Agriculture, Food and Rural Affairs (for farm soils), Licensed by Ontario MOE for specific tests in drinking water.

Exova (Mississauga) is accredited for specific parameters by:

SCC, Standards Council of Canada (to ISO 17025)

Please note: Field data, where presented on the report, has been provided by the client and is presented for informational purposes only.

Client: Genivar INC.
500 Boul. Greber, 3rd Floor
Gatineau, QC
J8T 7W3
Attention: Ms. Catherine Tardy Laporte
PO#:
Invoice to: Genivar INC.

Report Number: 1314497
Date Submitted: 2013-07-11
Date Reported: 2013-07-15
Project: 131-13558-00
COC #: 144561

					Lab I.D. Sample Matrix Sample Type Sampling Date Sample I.D.
					1041600 Soil 2013-07-02 TE-02 (1.00-1.45)
Group	Analyte	MRL	Units	Guideline	
Metals	Ag	0.2	ug/g		<0.2
	As	1	ug/g		2
	B	10	ug/g		40
	Ba	1	ug/g		383
	Be	1	ug/g		<1
	Cd	0.5	ug/g		<0.5
	Co	1	ug/g		20
	Cr	1	ug/g		122
	Cu	1	ug/g		65
	Mo	1	ug/g		<1
	Ni	1	ug/g		65
	Pb	1	ug/g		19
	Sb	1	ug/g		<1
	Se	1	ug/g		<1
	Tl	1	ug/g		<1
	U	0.5	ug/g		0.9
	V	2	ug/g		109
	Zn	2	ug/g		135

Guideline = *** = Guideline Exceedence**

** = Analysis completed at Mississauga, Ontario.

Results relate only to the parameters tested on the samples submitted.

Methods references and/or additional QA/QC information available on request.

MRL = Method Reporting Limit, AO = Aesthetic Objective, OG = Operational Guideline, MAC = Maximum Acceptable Concentration, IMAC = Interim Maximum Acceptable Concentration, STD = Standard, PWQO = Provincial Water Quality Guideline, IPWQO = Interim Provincial Water Quality Objective, TDR = Typical Desired Range

Client: Genivar INC.
500 Boul. Greber, 3rd Floor
Gatineau, QC
J8T 7W3
Attention: Ms. Catherine Tardy Laporte
PO#:
Invoice to: Genivar INC.

Report Number: 1314497
Date Submitted: 2013-07-11
Date Reported: 2013-07-15
Project: 131-13558-00
COC #: 144561

QC Summary

Analyte	Blank	QC % Rec	QC Limits
Run No 254229	Analysis Date 2013-07-12	Method EPA 200.8	
Ag	<0.2 ug/g	90	70-130
As	<1 ug/g	96	70-130
Ba	<1 ug/g	101	70-130
Be	<1 ug/g	98	70-130
Cd	<0.5 ug/g	102	70-130
Co	<1 ug/g	97	70-130
Cr	<1 ug/g	98	70-130
Cu	<1 ug/g	102	70-130
Mo	<1 ug/g	100	70-130
Ni	<1 ug/g	99	70-130
Pb	<1 ug/g	90	70-130
Sb	<1 ug/g	87	70-130
Se	<1 ug/g	95	70-130
Tl	<1 ug/g	86	70-130

Guideline = * = **Guideline Exceedence**

** = Analysis completed at Mississauga, Ontario.

Results relate only to the parameters tested on the samples submitted.

Methods references and/or additional QA/QC information available on request.

MRL = Method Reporting Limit, AO = Aesthetic Objective, OG = Operational Guideline, MAC = Maximum Acceptable Concentration, IMAC = Interim Maximum Acceptable Concentration, STD = Standard, PWQO = Provincial Water Quality Guideline, IPWQO = Interim Provincial Water Quality Objective, TDR = Typical Desired Range

Client: Genivar INC.
500 Boul. Greber, 3rd Floor
Gatineau, QC
J8T 7W3
Attention: Ms. Catherine Tardy Laporte
PO#:
Invoice to: Genivar INC.

Report Number: 1314497
Date Submitted: 2013-07-11
Date Reported: 2013-07-15
Project: 131-13558-00
COC #: 144561

QC Summary

Analyte	Blank	QC % Rec	QC Limits
U	<0.5 ug/g	86	70-130
V	<2 ug/g	104	70-130
Zn	<2 ug/g	101	70-130
Run No 254302 Analysis Date 2013-07-15 Method M SM3120B-3050B			
B	<10 ug/g	93	

Guideline = *** = Guideline Exceedence**

** = Analysis completed at Mississauga, Ontario.

Results relate only to the parameters tested on the samples submitted.

Methods references and/or additional QA/QC information available on request.

MRL = Method Reporting Limit, AO = Aesthetic Objective, OG = Operational Guideline,
MAC = Maximum Acceptable Concentration, IMAC = Interim Maximum Acceptable
Concentration, STD = Standard, PWQO = Provincial Water Quality Guideline, IPWQO
= Interim Provincial Water Quality Objective, TDR = Typical Desired Range

Client: Genivar INC.
500 Boul. Greber, 3rd Floor
Gatineau, QC
J8T 7W3
Attention: Ms. David Feghali
PO#:
Invoice to: Genivar Inc.

Report Number: 1313316
Date Submitted: 2013-07-02
Date Reported: 2013-07-11
Project: 131-13558-00
COC #: 157046

Page 1 of 7

Dear David Feghali:

Please find attached the analytical results for your samples. If you have any questions regarding this report, please do not hesitate to call (613-727-5692).

Report Comments:

APPROVAL: _____

Lorna Wilson
Laboratory Supervisor, Inorganics

APPROVAL: _____

Charlie (Long) Qu
Laboratory Supervisor, Organics

Exova (Ottawa) is certified and accredited for specific parameters by:

CALA, Canadian Association for Laboratory Accreditation (to ISO 17025), OMAFRA, Ontario Ministry of Agriculture, Food and Rural Affairs (for farm soils), Licensed by Ontario MOE for specific tests in drinking water.

Exova (Mississauga) is accredited for specific parameters by:

SCC, Standards Council of Canada (to ISO 17025)

Please note: Field data, where presented on the report, has been provided by the client and is presented for informational purposes only.

Client: Genivar INC.
500 Boul. Greber, 3rd Floor
Gatineau, QC
J8T 7W3
Attention: Ms. David Feghali
PO#:
Invoice to: Genivar Inc.

Report Number: 1313316
Date Submitted: 2013-07-02
Date Reported: 2013-07-11
Project: 131-13558-00
COC #: 157046

Group	Analyte	MRL	Units	Lab I.D. Sample Matrix Sample Type Sampling Date Sample I.D. Guideline	1038279	1038280	1038281	1038282
					Soil 2013-07-02 TE-03 (0.30 - 1.00)	Soil 2013-07-02 TE-04 (1.00 - 2.30)	Soil 2013-07-02 TE-05 (0.15 - 2.30)	Soil 2013-07-02 DUP - 8
General Chemistry	Moisture	0.1	%		30.2	21.4	21.3	29.4
Hydrocarbons	F1 (C6-C10)	10	ug/g		<10	<10	<10	<10
	F2 (C10-C16)	10	ug/g		<10	<10	<10	<10
	F3 (C16-C34)	20	ug/g		<20	30	<20	<20
	F4 (C34-C50)	20	ug/g		<20	40	<20	<20
Metals	Ag	0.2	ug/g			<0.2		
	As	1	ug/g			3		
	B	10	ug/g			30		
	Ba	1	ug/g			175		
	Be	1	ug/g			<1		
	Cd	0.5	ug/g			<0.5		
	Co	1	ug/g			14		
	Cr	1	ug/g			82		
	Cu	1	ug/g			28		
	Mo	1	ug/g			<1		
	Ni	1	ug/g			39		
	Pb	1	ug/g			9		
	Sb	1	ug/g			<1		
	Se	1	ug/g			<1		
	Tl	1	ug/g			<1		
	U	0.5	ug/g			1.0		
	V	2	ug/g			72		
	Zn	2	ug/g			110		
Semi-Volatiles	1-methylnaphthalene	0.05	ug/g		<0.05	<0.05	<0.05	<0.05
	2-methylnaphthalene	0.05	ug/g		<0.05	<0.05	<0.05	<0.05
	Acenaphthene	0.05	ug/g		<0.05	<0.05	<0.05	<0.05

Guideline = * = Guideline Exceedence

** = Analysis completed at Mississauga, Ontario.

Results relate only to the parameters tested on the samples submitted.

Methods references and/or additional QA/QC information available on request.

MRL = Method Reporting Limit, AO = Aesthetic Objective, OG = Operational Guideline, MAC = Maximum Acceptable Concentration, IMAC = Interim Maximum Acceptable Concentration, STD = Standard, PWQO = Provincial Water Quality Guideline, IPWQO = Interim Provincial Water Quality Objective, TDR = Typical Desired Range

Client: Genivar INC.
500 Boul. Greber, 3rd Floor
Gatineau, QC
J8T 7W3
Attention: Ms. David Feghali
PO#:
Invoice to: Genivar Inc.

Report Number: 1313316
Date Submitted: 2013-07-02
Date Reported: 2013-07-11
Project: 131-13558-00
COC #: 157046

				Lab I.D. Sample Matrix Sample Type Sampling Date Sample I.D.	1038279 Soil 2013-07-02 TE-03 (0.30 - 1.00)	1038280 Soil 2013-07-02 TE-04 (1.00 - 2.30)	1038281 Soil 2013-07-02 TE-05 (0.15 - 2.30)	1038282 Soil 2013-07-02 DUP - 8
Group	Analyte	MRL	Units	Guideline				
Semi-Volatiles	Acenaphthylene	0.05	ug/g		<0.05	<0.05	<0.05	<0.05
	Anthracene	0.05	ug/g		<0.05	<0.05	<0.05	<0.05
	Benzo(a)anthracene	0.05	ug/g		<0.05	<0.05	<0.05	<0.05
	Benzo(a)pyrene	0.05	ug/g		<0.05	<0.05	<0.05	<0.05
	Benzo(b)fluoranthene	0.05	ug/g		<0.05	<0.05	<0.05	<0.05
	Benzo(g,h,i)perylene	0.05	ug/g		<0.05	<0.05	<0.05	<0.05
	Benzo(k)fluoranthene	0.05	ug/g		<0.05	<0.05	<0.05	<0.05
	Chrysene	0.05	ug/g		<0.05	<0.05	<0.05	<0.05
	Dibenzo(a,h)anthracene	0.05	ug/g		<0.05	<0.05	<0.05	<0.05
	Fluoranthene	0.05	ug/g		<0.05	<0.05	0.05	<0.05
	Fluorene	0.05	ug/g		<0.05	<0.05	<0.05	<0.05
	Indeno(1,2,3-c,d)pyrene	0.05	ug/g		<0.05	<0.05	<0.05	<0.05
	Naphthalene	0.05	ug/g		<0.05	<0.05	<0.05	<0.05
	Phenanthrene	0.05	ug/g		<0.05	<0.05	<0.05	<0.05
	Pyrene	0.05	ug/g		<0.05	<0.05	<0.05	<0.05

Guideline = * = **Guideline Exceedence**

** = Analysis completed at Mississauga, Ontario.

Results relate only to the parameters tested on the samples submitted.

Methods references and/or additional QA/QC information available on request.

MRL = Method Reporting Limit, AO = Aesthetic Objective, OG = Operational Guideline,
MAC = Maximum Acceptable Concentration, IMAC = Interim Maximum Acceptable
Concentration, STD = Standard, PWQO = Provincial Water Quality Guideline, IPWQO =
Interim Provincial Water Quality Objective, TDR = Typical Desired Range

Client: Genivar INC.
500 Boul. Greber, 3rd Floor
Gatineau, QC
J8T 7W3
Attention: Ms. David Feghali
PO#:
Invoice to: Genivar Inc.

Report Number: 1313316
Date Submitted: 2013-07-02
Date Reported: 2013-07-11
Project: 131-13558-00
COC #: 157046

QC Summary

Analyte	Blank	QC % Rec	QC Limits
Run No 253766 Analysis Date 2013-07-08 Method C SM2540B			
Moisture	<0.1 %	102	80-120
Run No 253770 Analysis Date 2013-07-08 Method CCME			
F2 (C10-C16)	<10 ug/g	83	50-120
F3 (C16-C34)	<20 ug/g	83	50-120
F4 (C34-C50)	<20 ug/g	83	50-120
Run No 253828 Analysis Date 2013-07-08 Method EPA 200.8			
Ag	<0.2 ug/g	87	70-130
As	<1 ug/g	103	70-130
Ba	<1 ug/g	103	70-130
Be	<1 ug/g	102	70-130
Cd	<0.5 ug/g	101	70-130
Co	<1 ug/g	105	70-130
Cr	<1 ug/g	103	70-130
Cu	<1 ug/g	108	70-130

Guideline = *** = Guideline Exceedence**

** = Analysis completed at Mississauga, Ontario.

Results relate only to the parameters tested on the samples submitted.

Methods references and/or additional QA/QC information available on request.

MRL = Method Reporting Limit, AO = Aesthetic Objective, OG = Operational Guideline,
MAC = Maximum Acceptable Concentration, IMAC = Interim Maximum Acceptable
Concentration, STD = Standard, PWQO = Provincial Water Quality Guideline, IPWQO =
Interim Provincial Water Quality Objective, TDR = Typical Desired Range

Client: Genivar INC.
500 Boul. Greber, 3rd Floor
Gatineau, QC
J8T 7W3
Attention: Ms. David Feghali
PO#:
Invoice to: Genivar Inc.

Report Number: 1313316
Date Submitted: 2013-07-02
Date Reported: 2013-07-11
Project: 131-13558-00
COC #: 157046

QC Summary

Analyte	Blank	QC % Rec	QC Limits
Mo	<1 ug/g	106	70-130
Ni	<1 ug/g	106	70-130
Pb	<1 ug/g	92	70-130
Sb	<1 ug/g	90	70-130
Se	<1 ug/g	103	70-130
Tl	<1 ug/g	92	70-130
U	<0.5 ug/g	87	70-130
V	<2 ug/g	114	70-130
Zn	<2 ug/g	109	70-130
Run No 253856 Analysis Date 2013-07-05 Method CCME			
F1 (C6-C10)	<10 ug/g	104	80-120
Run No 253857 Analysis Date 2013-07-08 Method M SM3120B-3050B			
B	<10 ug/g	83	
Run No 253864 Analysis Date 2013-07-05 Method CCME			
F1 (C6-C10)	<10 ug/g	104	80-120
Run No 253953 Analysis Date 2013-07-09 Method CCME			
F1 (C6-C10)	<10 ug/g	90	80-120

Guideline =
*** = Guideline Exceedence**

** = Analysis completed at Mississauga, Ontario.

Results relate only to the parameters tested on the samples submitted.

Methods references and/or additional QA/QC information available on request.

MRL = Method Reporting Limit, AO = Aesthetic Objective, OG = Operational Guideline,
MAC = Maximum Acceptable Concentration, IMAC = Interim Maximum Acceptable
Concentration, STD = Standard, PWQO = Provincial Water Quality Guideline, IPWQO =
Interim Provincial Water Quality Objective, TDR = Typical Desired Range

Client: Genivar INC.
500 Boul. Greber, 3rd Floor
Gatineau, QC
J8T 7W3
Attention: Ms. David Feghali
PO#:
Invoice to: Genivar Inc.

Report Number: 1313316
Date Submitted: 2013-07-02
Date Reported: 2013-07-11
Project: 131-13558-00
COC #: 157046

QC Summary

Analyte	Blank	QC % Rec	QC Limits
Run No 254078 Analysis Date 2013-07-11 Method P 8270			
1-methylnaphthalene	<0.05 µg/g	62	20-150
2-methylnaphthalene	<0.05 µg/g	61	20-150
Acenaphthene	<0.05 µg/g	63	20-150
Acenaphthylene	<0.05 µg/g	62	20-150
Anthracene	<0.05 µg/g	70	20-150
Benzo(a)anthracene	<0.05 µg/g	77	20-150
Benzo(a)pyrene	<0.05 µg/g	76	20-150
Benzo(b)fluoranthene	<0.05 µg/g	77	20-150
Benzo(g,h,i)perylene	<0.05 µg/g	85	20-150
Benzo(k)fluoranthene	<0.05 µg/g	75	20-150
Chrysene	<0.05 µg/g	72	20-150
Dibenzo(a,h)anthracene	<0.05 µg/g	86	20-150
Fluoranthene	<0.05 µg/g	73	20-150
Fluorene	<0.05 µg/g	64	20-150
Indeno(1,2,3-c,d)pyrene	<0.05 µg/g	86	20-150
Naphthalene	<0.05 µg/g	59	20-150

Guideline = *** = Guideline Exceedence**

** = Analysis completed at Mississauga, Ontario.

Results relate only to the parameters tested on the samples submitted.

Methods references and/or additional QA/QC information available on request.

MRL = Method Reporting Limit, AO = Aesthetic Objective, OG = Operational Guideline,
MAC = Maximum Acceptable Concentration, IMAC = Interim Maximum Acceptable
Concentration, STD = Standard, PWQO = Provincial Water Quality Guideline, IPWQO =
Interim Provincial Water Quality Objective, TDR = Typical Desired Range

Client: Genivar INC.
500 Boul. Greber, 3rd Floor
Gatineau, QC
J8T 7W3
Attention: Ms. David Feghali
PO#:
Invoice to: Genivar Inc.

Report Number: 1313316
Date Submitted: 2013-07-02
Date Reported: 2013-07-11
Project: 131-13558-00
COC #: 157046

QC Summary

Analyte	Blank	QC % Rec	QC Limits
Phenanthrene	<0.05 µg/g	68	20-150
Pyrene	<0.05 µg/g	73	20-150

Guideline = *** = Guideline Exceedence**

** = Analysis completed at Mississauga, Ontario.

Results relate only to the parameters tested on the samples submitted.

Methods references and/or additional QA/QC information available on request.

MRL = Method Reporting Limit, AO = Aesthetic Objective, OG = Operational Guideline,
MAC = Maximum Acceptable Concentration, IMAC = Interim Maximum Acceptable
Concentration, STD = Standard, PWQO = Provincial Water Quality Guideline, IPWQO =
Interim Provincial Water Quality Objective, TDR = Typical Desired Range

Client: Genivar INC.
500 Boul. Greber, 3rd Floor
Gatineau, QC
J8T 7W3
Attention: Ms. Catherine Tardy Laporte
PO#:
Invoice to: Genivar INC.

Report Number: 1314097
Date Submitted: 2013-07-08
Date Reported: 2013-07-11
Project: 131-13558-00-700-001
COC #: 500429

Page 1 of 8

Dear Catherine Tardy Laporte:

Please find attached the analytical results for your samples. If you have any questions regarding this report, please do not hesitate to call (613-727-5692).

Report Comments:

APPROVAL: _____

Lorna Wilson
Laboratory Supervisor, Inorganics

APPROVAL: _____

Charlie (Long) Qu
Laboratory Supervisor, Organics

Exova (Ottawa) is certified and accredited for specific parameters by:

CALA, Canadian Association for Laboratory Accreditation (to ISO 17025), OMAFRA, Ontario Ministry of Agriculture, Food and Rural Affairs (for farm soils), Licensed by Ontario MOE for specific tests in drinking water.

Exova (Mississauga) is certified and accredited for specific parameters by:

SCC, Standards Council of Canada (to ISO 17025)

Please note: Field data, where presented on the report, has been provided by the client and is presented for informational purposes only.

